



Symbols

(* , G) state, 435

Numerics

6bone, 647
 6REN (IPv6 Research and Education Networks,
 646–648

A

A (Address) records, 350
 ABRs (area border routers), 456–457
 access lists
 alternation, 817
 BGP
 filtering by AS_PATH, 219–224
 filtering by NLRI, 211–218
 filtering with route maps, 224–226
 bracketing, 817
 community lists, 276
 delineation, 816
 regular expressions, negation, 817
 wildcards, 817
 accounting, 756
 IP accounting, 756–757
 NetFlow switching, 757–765
 accuracy of summarization, 63
 active gateways, EGP, 10
 Active state (BGP), 97
 adding multicast addresses to CAM table, 421
 address family ipv4 command, 617
 Address Length field (CBT messages), 469
 address translation table
 clearing entries, 387
 NAT, 335
 addresses
 IPv6, 649
 address type allocation, 652–653
 compacting, 650
 embedded IPv4 addresses, 659
 IPv4 compatible, 659
 link-local addresses, 659
 loopback, 658
 site-local addresses, 660
 structure, 654–666
 text representation, 650
 unspecified, 658
 leaking to Internet, 73, 339
 overloading, 342
 preferred, 678
 prefixes, 57
 reachability, maintaining during ISP
 migration, 339
 resolution, ND protocol, 680–681
 space depletion, 71
 address-family ipv4 command, 615
 Adj-RIBs-In, 113
 Adj-RIBs-Out, 113
 administrative distance, BGP, 234–241
 administrative scoping, 440, 594–595, 664
 administrative weight, 110
 filtering multiple routes to the same destination,
 226–234
 advertisements
 LSAs, OSPFv2, 701–704
 NA, 679
 ND protocol, 677–678
 RA, 677–678
 advertising BGP aggregate routes, 188–195.
 See also route maps
 Advertising Router fields (Group Membership
 LSAs), 460
 AFI (Address Family Identifier), 606
 agent (SNMP), 731–732
 aggregatable global address structure, 654
 FP, 656
 interface identifier, 657
 reserved field, 656
 SLAID, 657
 TLAID, 656
 unicast format, 655
 aggregate-address command, 185–188, 203, 290

aggregation, BGP

- AS_SET attribute, 111–113
- based on more-specific routes, 202–204
- case study, 185–204
- loss of path information, 199–200
- modifying route attributes, 196–197
- static routes, 186
- suppressing more-specific routes, 187–188
- See* route aggregation
- AGGREGATOR attribute (BGP), 107, 109
- AH (Authentication Header), IPv6, 671
- "all systems on this subnet" group, 412
- alternation in regular expressions, 817
- analyzing multicast traffic behavior, 580–582
- anycast addresses, IPv6, 660
- Anycast RP, 627–632
- anycasting, 627, 708
- APNIC (Asia Pacific Network Information Center), 69
- applications
 - CiscoWorks, router management, 733–739
 - many-to-one, NAT, 337
- application-specific integrated circuits (ASICs), 422
- applying
 - access lists (BGP)
 - filtering by AS_PATH attribute, 219, 224
 - filtering by NLRI, 212, 214–217
 - filtering with route maps, 224–226
 - route maps (BGP)
 - AS_PATH prepending, 252–256
 - filtering multiple routes to same destination, 226–234
 - filtering multiple routes to same destination learned from different routing protocols, 234–241
 - filtering with LOCAL_PREF, 241–245
 - filtering with MULTI_EXIT_DISC attribute, 246–252
 - route tagging, 256–260
 - route attributes to MBGP, 616
- ARIN (American Registry for Internet Numbers), 69
- ARPANET, scalability, 5
- AS numbers, 6
- AS_PATH attribute, 100–101
 - AS_SET, 111–113
 - prepending, 101, 252, 255–256
 - route filtering, 219–222
- ASBR (Autonomous System Boundary Router), 459
- AS-External LSAs, flooding outside OSPF domains, 459
- ASICs (application-specific integrated circuits), 422
- Ask Neighbor messages (DVMRP), format, 451
- ASs (autonomous systems)
 - BGP routing policies, 209
 - inter-AS MOSPF, 459–460
 - extension formats, 460–462
 - inter-AS multicasting, 602
 - multi-homing
 - NAT, 340–342
 - to multiple ASs, 84–87
 - to single AS, 80–84
 - physical links, 79
 - private numbers, 284–286
 - single-homed, 78–79
 - transit traffic, configuring IBGP without an IGP, 168–174
- Assert messages (PIMv2), 515–516
- assessing need for BGP-4, 75–77
- assigning
 - groups to RPs, 549–550
 - policies to BGP communities, 274–277
 - unique router IDs to BGP routers, 154
- asterisk (*), in regular expressions, 818
- asymmetric traffic, 64
- ATOMIC_AGGREGATE attribute (BGP), 107–109
- attacks (DoS), preventing, 771–772
- attributes (BGP), 606
 - applying to MBGP routes, 616
 - AS_PATH
 - AS_SET, 111–113
 - prepending, 252–256
 - communities, 270–283
 - LOCAL_AS, 274
 - LOCAL_PREF
 - manipulating route preference within local AS, 241–245
 - modifying, 241
 - MULTI_EXIT_DISC
 - applying external metric, 246–252
 - filtering between confederations, 294–300
 - NLRI, 606
 - Type codes, 135

- authentication
 - MD5, 206
 - OSPFv2, 701
 - TACACS+, 773–779
 - autoconfiguration, IPv6
 - renumbering, 689–690
 - stateful, 688
 - stateless, 685–688
 - automatic summarization, disabling
 - BGP, 157
 - EIGRP, 158
 - automatic tags, 260
 - automatic tunnels, 659
 - Auto-RP, configuring, 551–558
- ## B
-
- backdoor routes, filtering multiple routes to the same destination, 234–241
 - bandwidth, multicast load sharing, 568–575
 - bar (|) in regular expressions, 817
 - best routes (BGP), selection process, 114
 - BGP, 55. *See also* large-scale BGP; MBGP
 - administrative weight, 110
 - aggregation
 - based on more-specific routes, 202–204
 - case study, 185–202
 - loss of path information, 199–200
 - suppressing more-specific routes, 187–188
 - AS_PATH prepending, 252–256
 - ASs, physical links, 79
 - assessing need for, 75–77
 - assigning unique router IDs, 154
 - Attribute Type codes, 135
 - automatic summarization, disabling, 157
 - confederations, 287–300
 - configuring, 149–152
 - default distances, modifying, 235
 - EBGP multihop, configuring, 182, 184–185
 - equal-cost paths, 92
 - FSM (Finite State Machine), 95
 - Active state, 97
 - Connect state, 97
 - Established state, 98
 - Idle state, 96
 - OpenConfirm state, 98
 - OpenSent state, 97
 - hold time interval, configuring, 208
 - IBGP over an IGP, configuring, 174–182
 - IBGP/IGP synchronization, 117–123
 - injecting routes into IGP, case study, 155–167
 - inter-AS topologies
 - multi-homing to multiple ASs, 84–87
 - multi-homing to single AS, 80–84
 - single-homing, 78–79
 - keepalive timer, configuring, 208
 - Keepalive message, 94
 - format, 136
 - large-scale peering, managing
 - with communities, 123
 - with confederations, 130–131
 - with peer groups, 123
 - with route reflectors, 124–125, 129
 - load balancing, 88
 - local routes, 235
 - LOCAL_AS attribute, 274
 - loopback interfaces, configuring, 154
 - misconfiguration, ramifications of, 209
 - multiprotocol extensions, 704–708
 - mutual redistribution, 215–218
 - neighbors, displaying information, 805–812
 - Notification message, 95
 - fields, 136
 - Open message, 93
 - fields, 132
 - path attributes, 90, 98, 606
 - AGGREGATOR, 107–109
 - applying to MBGP routes, 616
 - AS_PATH, 100–101
 - ATOMIC_AGGREGATE, 107–109
 - CLUSTER_LIST, 110
 - COMMUNITY, 109, 270–283
 - LOCAL_AS, 274
 - LOCAL_PREF, 105, 241–245
 - MULTI_EXIT_DISC, 106, 246–252, 294–300
 - NEXT-HOP, 102–104
 - NLRI, 606
 - ORIGIN, 99
 - ORIGINATOR_ID, 110
 - Type codes, 135
 - peer groups, 265–267

- peering, 88–89, 93
 - connections, managing, 204–208
 - during neighbor authentication, 205
 - large-scale, 123
- private AS numbers, 284–286
- redistribution, configuring, 159
- resetting connections, 209–211
- reuse limit, 261
- RIB (Routing Information Base), 113–115
- route dampening, 115–116
 - configuring, 261–264
- route filtering
 - by AS_PATH, 219–222
 - by NLRI, 211–214
- route maps
 - case study, 224–226
 - filtering by NLRI, 216–219
 - filtering routes with LOCAL_PREF attribute, 241–245
 - filtering with MULTI_EXIT_DISC attribute, 246–252
 - multiple routes to same destination, 226–234
 - multiple routes to same destination learned from different routing protocols, 234–241
- route reflectors, clusters, 125
- route tagging, 256–260
- routes
 - selection process, 114
 - tie-breaking process, 114–115
- routing loops, detecting, 91
- routing policies, 208–209
- routing table
 - directly connected links, 119
 - invalid routes, 217
- sessions, clearing, 154
- soft reconfiguration, 210
- suppress limit, 261
- Update message, 94
 - fields, 133–135
- bgp always-compare med command, 299
- bgp bestpath as-path ignore command, 206
- bgp bestpath med confed command, 300
- bgp cluster-id command, 303
- bgp confederation identifier command, 289
- bgp confederation peers command, 289

- bgp dampening command, 261
- bgp deterministic-med command, 299
- bgp router-id command, 155
- big-endian, 403
- bilateral peering agreements, 67
- black holes (EGP), troubleshooting, 43
- Bootstrap messages, 513–515
- bootstrap protocol, 489–491
 - configuring, 562–567
- boundaries in regular expressions, 818
- brackets in regular expressions, 816
- broadcast domains, 420
- broadcast-and-prune protocols, 432–434
- broadcasting, 395
- BSR Priority field
 - hash-mask, 567
 - PIMv2 Bootstrap messages, 515

C

- caching, enabling for MSDP, 609
- CAM (content addressable memory) table, 421–423
- candidate core routers, 465
- Candidate-RP-Advertisement messages, 516–517
- Capabilities field (DVMRP Probe messages), 447
- capturing
 - IP multicast packets, 547
 - packets, 741
- carets (^) in regular expressions, 817
- case studies
 - aggregate routes, 185–202
 - applying route maps, 224–226
 - BGP
 - configuring, 149–152
 - routes, injecting, 161–167
 - dynamic NAT, configuring, 364–368
 - EBGP multihop, 182, 184–185
 - IBGP over an IGP, 174, 176, 179–182
 - injecting IGP routes, 155–161
 - ISP multihoming with NAT, 374–379
 - load balancing, 381
 - multicast load sharing, 568–573
 - multicasting across non-multicast domains, 595–598
 - network mergers, 369–374

- route filtering
 - by AS_PATH, 219–222
 - by NLRI, 211–214
- service distribution, 383–385
- static NAT, configuring, 356–364
- Catalyst switches, CAM (content addressable memory) table, 421–423
- CBT (core-based trees), 462–463
 - Candidate Core messages, 465
 - child interfaces, 464
 - DRs, 465–466
 - ECHO_REQUEST messages, 472
 - FLUSH_TREE messages, 464, 473
 - JOIN_ACK messages, 471
 - JOIN_REQUEST messages, 463–464
 - fields, 470
 - member sources, 466–467
 - message fields, 468–473
 - nonmember sources, 467
 - parent interface, 464
 - QUIT_NOTIFICATION messages, 464, 471–472
 - transient join state, 464
- CCBs (change control boards), 729
- CC-sets (candidate core), 465
- CGMP (Cisco Group Membership Protocol), 419–421
 - CAM table, 423
 - MAC addresses, 422–426
 - operation of, 422–426
 - packets, 422
 - format, 426–427
- change management, 729–730
- character classes, 219
- characteristics of confederation EBGp, 290
- Checksum field
 - CBT messages, 469
 - DVMRP messages, 446
 - IGMP messages, 418
- checksums, 346
- child interfaces, 464
- CIDR (Classless Interdomain Routing), 55, 69–70
 - blocks, 70
 - depletion of address space, 71
 - troubleshooting, 72–73
- Cisco IOS, DVMRP implementation, 598–600
- Cisco Policy Routes, 208
- Cisco routers, enabling IPv6 capability, 673–674
- CiscoView, 733
- CiscoWorks, 733
 - configuration management, 765
 - router management, 733–739
- Class D IP addresses, 399
- classless routing, 57, 59–60
- classless routing protocols, BGP-4, 55
- clear cam command, 421
- clear config command, 421
- clear ip bgp command, 154, 210
- clear ip bgp dampening command, 264
- clear ip bgp flap-statistics command, 264
- clear ip cgmp command, 426
- clear ip nat translations command, 387
- clearing
 - BGP connections, 209–211
 - BGP sessions, 154
 - entries from address translation table, 387
- CLUSTER_LIST attribute (BGP), 110
 - applying to route reflectors, 129
- clusters, 125
- CNAME (Canonical Name) records, 350
- Code field (DVMRP messages), 446
- colons (:) in IP addresses, 650
- Command field (RIPng messages), 692
- command summary, NAT, 388
- commands
 - address family ipv4, 617
 - address-family ipv4, 615
 - aggregate-address, 185, 188, 203, 290
 - bgp always-compare med, 299
 - bgp bestpath as-path ignore, 206
 - bgp bestpath med confed, 300
 - bgp cluster-id, 303
 - bgp confederation identifier, 289
 - bgp confederation peers, 289
 - bgp dampening, 261
 - bgp deterministic-med, 299
 - bgp router-id, 155
 - clear cam, 421
 - clear config, 421
 - clear ip bgp, 154, 210
 - clear ip bgp dampening, 264
 - clear ip bgp flap-statistics, 264
 - clear ip cgmp, 426
 - clear ip nat translations, 387

- debug ip bgp events, 153
- debug ip packet detail, 476
- debug ip pim auto-rp, 553
- debug ipv6, 682–683
- default-metric, 156
- distribute list, 212
- ebgp-multihop, 184
- ip bgp-community new-format, 278, 281
- ip cgmp, 533
- ip classless, 60
- ip default-gateway, 361
- ip dense-mode, 533
- ip igmp query-interval, 413
- ip igmp query-max-response-time, 413
- ip igmp query-timeout, 414
- ip igmp version, 411, 532
- ip mdsp, 622–623, 626–633
- ip mdsp cache-sa-state, 609
- ip mroute, 573
- ip multicast boundary, 594–595
- ip multicast routing, 531–532
- ip multicast use-functional, 404, 533
- ip nat inside, 358
- ip nat inside source, 381
- ip nat outside source static, 359
- ip nat pool, 365
- ip nat translation, 386
- ip nat translation timeout, 337, 367
- ip pim bsr-candidate, 515, 563, 567
- ip pim query-interval, 509
- ip pim rp-candidate, 563
- ip pim send-rp-announce, 551, 555
- ip pim sparse-dense-mode, 560
- ip pim sparse-mode, 542
- ip pim spt-threshold, 548
- ip pim version, 508
- match interface, 377
- match ip address, 224
- match ip next-hop, 377
- maximum-paths, 92
- maximum-paths, 305
- mrinfo, 577–579
- mstat, 580–584
- mtrace, 580–584
- neighbor activate, 617
- neighbor default-originate, 166
- neighbor description, 204–205
- neighbor distribute-list, 167, 198, 224
- neighbor ebgp-multihop, 184
- neighbor next-hop-self, 290–292
- neighbor remove-private-AS, 286
- neighbor shutdown, 208
- neighbor version, 206
- neighborhood maximum-prefix, 206
- no ip mroute-cache, 533
- redistribute, 156
- set as-path prepend, 254
- set as-path tag, 259
- set automatic-tag, 260
- set comm-list delete, 283
- set gmrp enable, 422
- set igmp enable, 422
- set local-preference, 241
- show ip bgp, 91, 274
- show ip bgp community no-export, 190, 203
- show ip bgp community-list, 280
- show ip bgp dampened-paths, 263
- show ip bgp flap-statistics, 263
- show ip bgp neighbors, 151, 185, 805–812
- show ip bgp peer-groups, 269
- show ip bgp4, 616
- show ip egp, 34–35, 39
- show ip igmp group, 479
- show ip igmp groups, 413
- show ip igmp interface, 540
- show ip mdsp peer, 620
- show ip nat statistics, 387
- show ip pim bsr-router, 564
- show ip pim interface, 546
- show ip pim neighbor, 477
- show ip pim rp, 554–556
- show ip pim rp-hash, 558
- show ip pim sp-hash, 567
- show ip route, 92
- show ipv6 interface, 674
- snmp-server, 733
- snmp-server community, 734
- table-map, 260
- timer egp, 15
- timers bgp, 93, 208
- timers egp, 11, 14
- trace, 354

- communities (BGP), 270–283
 - large-scale BGP peering management, 123
- COMMUNITY attribute (BGP), 109
- community lists, 276, 279–281
- community strings (SNMP), 731
- compacting IP addresses, 650
- comparing
 - host configuration, IPv4 and IPv6, 645
 - IGMPv1 and IGMPv2, 415–416
 - scalability, IPv4 and IPv6, 644
 - security, IPv4 and IPv6, 645
 - sparse and dense topologies, 431
- compatibility, IPv4/IPv6, 659
 - DNS, 716
 - dual stacks, 715
- confederations, 287–300
 - EBGP, 287–293
 - large-scale BGP peering management, 130–131
 - MEDs, filtering, 295–300
 - See also* route reflectors
- configuration management, 765
- configuring. *See also* manual configuration
 - Anycast RP, 627–632
 - Auto-RP, 551
 - BGP, 149–152
 - AS_PATH prepending, 252–256
 - automatic tags, 260
 - communities, 270–281
 - hold time interval, 208
 - IBGP over an IGP, 174–182
 - IBGP without an IGP, 167–174
 - importance of, 209
 - keepalive, 208
 - loopback interfaces, 154
 - peer connections, 204–208
 - peer groups, 265–266, 269
 - private AS numbers, 284–286
 - redistribution, 159
 - route dampening, 261–264
 - route reflectors, 300–307
 - route tagging, 256–260
 - unique router IDs, 154–155
 - bootstrap protocol, 562–567
 - EBGP multihop, 182–185
 - EGP, 26
 - core gateway, 31, 34–35
 - default routes, 38–39
 - indirect neighbors, 35, 38
 - stub gateway, 27–31
 - HSRP, 785–789
 - IP multicast, 531–533
 - fast switching, disabling, 533
 - over Token Ring, 403
 - PIM-DM, 533–541
 - PIM-SM, 542–556
 - sparse-dense mode, 559–562
 - MBGP, 614–619
 - MDSP, 619–624
 - default peers, 633–634
 - mesh groups, 624–627
 - MHSRP, 789–790
 - NAT
 - dynamic NAT, 364–368
 - exercises, 389–391
 - for network mergers, 369, 372–374
 - for TCP load balancing, 381–385
 - ISP multihoming, 374–379
 - PAT, 379–381
 - static NAT, 356–364
 - NTP, 751–755
 - PIM-SM
 - bootstrap protocol, 562–567
 - RPs, 542–548
 - RIPng, 695–697
 - RMON, 741–743
 - SNMP on routers, 733–740
 - syslog, 749–750
 - TTL scoping, 438–440
- congestion, multicast load sharing, 568–575
- Connect state (BGP), 97
- connections, resetting (BGP), 209–211
- conserving
 - AS numbers, 284, 286
 - IP addresses, 336–338
- content addressable memory (CAM), 421
- controlling
 - interactive access, 770–771
 - switched multicast traffic, 421–422
- convergence (EGP), troubleshooting, 41, 43

core gateway (EGP), configuring, 31–35
 Count field (CGMP packets), 427
 creating BGP peer groups, 265–266
 C-RPs (candidate rendezvous points), 489–490, 551
 cryptographic checksum, 206

D

databases

RADB (Routing Arbiter Database), 66
 RIB (Routing Information Base), 113–115

dead neighbors, EGP, 13

debug ip bgp events command, 153

debug ip packet detail command, 476

debug ip pim auto-rp command, 553

debug ipv6 command, 682–683

debugging captured multicast packets, 547

decision-making process, BGP, 113–115

default distances of BGP, modifying, 235

default peers (MDSP), configuring, 633–634

default router selection, ND protocol, 684

default routes (EGP), configuring, 38–39

default-free zone, 654

default-metric command, 156

delineation in regular expressions, 816

dense mode (PIM), 475, 477–481. *See also* sparse-

dense mode

(*, G) entry, 535–536

configuring, 533–541

DRs, 484

PIM forwarder election, 484–487

prune overrides, 481–483

RPF checks, 536

unicast routing changes, 484

depletion

of address space, 71, 649

of AS numbers, assigning private AS numbers,
 284–286

deprecated addresses, 678

IPv6, 689

design goals of IPv6, 643–644

ease of configuration, 645

improve scalability, 644

security, 645

Destination Address field, IPv6 header, 668

Destination Options header, IPv6 packets, 669–671

Destination Unreachable messages (ICMPv6), 675

detecting BGP routing loops, 91

devices

exchanges, 654

routers, POPs, 64

wildcard multiaccess receivers, 459

wildcard multicast receivers, 458

directly connected links in BGP routing table, 119

directly connected networks (BGP), 235

external metric, applying, 246–252

disabling

automatic summarization

BGP, 157

EIGRP, 158

fast switching of IP multicast packets, 533

synchronization, 121–122

discovery process

DVMRP neighbors, 442

multicast sources, MSDP, 607

displaying

BGP neighbor information, 805–812

BGP peer groups, statistics, 269

group-to-RP mappings, 556–557

MSDP session status, 620

NAT statistics, 387

Distance Vector Multicast Routing Protocol.

See DVMRP

distribute list command, 212

DNS

IPv4/IPv6 compatibility, 716

name servers, 350

NAT translation, 349–352

reverse lookups, 351

RRs, 350

zone transfers, 350

documenting network changes, 729–730

DoS (denial-of-service) attacks, preventing,

771–772

dot (.) in regular expressions, 817

dotted decimal notation, IPv6 addresses, 651

downstream interfaces, 428

DRs (designated routers)

CBT, 465–466

PIM-DM, 484

relationship to IGMP querier, 537–541

- dual-stack nodes, 659
 - IPv4/IPv6 compatibility, 715
- duplicate router selection, ND protocol, 685
- DVMRP (Distance Vector Multicast Routing Protocol), 441, 462
 - Cisco IOS implementation, 598–600
 - Graft Retransmission timer, 445
 - hop count, 443
 - message formats, 445–452
 - Ask Neighbor messages, 451
 - Graft Acknowledgment messages, 450
 - Graft messages, 450
 - Neighbor 2 messages, 451
 - Probe messages, 446–447
 - Prune messages, 449
 - Route Report messages, 448
 - mgated, 441
 - mrouted, 441
 - neighbor discovery, 442
 - packet forwarding, 444–445
 - Probes, 442
 - prune lifetime, 444–445
 - routing table, 443
 - RPF check, 444
- dynamic address translation table entries (NAT), 336
- dynamic NAT configuration, case study, 364–368

E

- EBGP (External Border Gateway Protocol)
 - confederation EBGP, 287–293
 - multihop, configuring, 182–185
- ECHO_REPLY messages (CBT), 464, 472
- ECHO_REQUEST messages (CBT), 464, 472
- EGPs
 - configuring, 26
 - convergence, troubleshooting, 41–43
 - core gateway, configuring, 31, 34–35
 - dead neighbors, 13
 - default routes, configuring, 38–39
 - indirect neighbors, 15
 - configuring, 35–38
 - limitations of, 26
- messages
 - Error, 24–25
 - header fields, 18
 - Hello interval, 9
 - Neighbor Acquisition, 19–20
 - Neighbor Reachability, 21
 - Poll, 21
 - sequence number, 10
 - Update, 22–24
 - Neighbor Acquisition Protocol, 9–11
 - Neighbor Reachability Protocol, 11–13
 - Network Reachability Protocol, 13–18
 - operation, 7
 - origins of, 5–6
 - stub gateway, configuring, 27–31
 - topology, 7–8
 - troubleshooting, 39
 - interpreting neighbor table, 39–41
- EIGRP, disabling automatic summarization, 158
- election process, PIM-DM forwarders, 484–487
- embedded IPv4 addresses in IPv6, 659
- enabling
 - IPv6 capability on Cisco routers, 673–674
 - RIPng routing process, 693
- encapsulation between PIM routers, GRE, 597
- Encoded Group Address field
 - Candidate-RP-Advertisement messages, 517
 - PIMv2 Assert messages, 516
- Encoded Multicast Group Address field (PIMv2 Bootstrap messages), 515
- Encoded Unicast Group Address field (PIMv2 Bootstrap messages), 515
- Encoded Unicast RP Address field
 - Candidate-RP-Advertisement messages, 517
 - PIMv2 Bootstrap messages, 515
- Encoded Unicast Source Address field (PIMv2 Assert messages), 516
- encryption, 770
- enforcing routing policies, 77
- enterprise networks
 - ISP migration, 338–340
 - scalability, role of NAT in, 338
- error codes/subcodes, MDSP, 613
- error messages
 - EGP, 24–25
 - ICMPv6, 674–675

escalation procedures, 730
 ESP (Encapsulation Security Payload), 672
 Established state (BGP), 98
 exchanges, 654. *See also* NAPs
 explicit joins, 432–434
 Membership LSA-based, 455
 scalability, 435
 extended community lists, 279–281
 extension formats, MOSPF, 460–462
 extension headers, IPv6, 669, 671–672
 exterior routing protocols, 77
 external metric, applying, 246–252

F

fast switching multicast packets, disabling, 533
 fault management, 766–768
 fault tolerance
 HSRP, configuring, 785–789
 MHSRP, configuring, 789–790
 robustness, 782
 feasible routes (BGP)
 Adj-RIBs-In, 113
 preference level, 114
 fields
 Candidate-RP-Advertisement messages, 517
 CBT messages, 468–473
 CGMP packets, 427
 command format, 535
 DMVRP messages, 445–452
 EGP message headers, 18
 IGMPv2 messages, 417–419
 IPv6 packets, 649
 Notification messages (BGP), 136
 Open messages (BGP), 132
 PIMv2
 Assert messages, 516
 Bootstrap messages, 513–515
 Update messages
 BGP, 133–135
 EGP, 24
 filtering. *See also* route filtering
 MEDs between confederations, 295–298
 SA messages, 623
 finding routes with specified community attributes,
 280–282
 flapping routes, 115
 penalties, 116
 route dampening, 261–264
 flood-and-prune protocols, 432–434
 flooding
 LSAs, 455
 AS-External LSAs outside OSPF
 domains, 459
 Network Summary LSAs outside
 areas, 456
 peer RPF flooding, 607
 FLUSH_TREE messages (CBT), 464, 473
 format
 CGMP packets, 426–427
 command fields, 535
 DVMRP messages
 Ask Neighbor, 451
 Graft, 450
 Graft Acknowledgment, 450
 Neighbor 2, 451
 Probe messages, 446–447
 Prune, 449
 Route Report, 448
 IGMP messages, comparing versions 1 and 2,
 417–418
 IPv6 headers, 667
 Keepalive message (BGP), 136
 MP_REACH_NLRI, 606
 MSDP messages, 609
 of aggregatable addresses, 655
 forwarders (PIM-DM)
 election process, 484–487
 rules, 536–537
 FP (format prefix), 652–653, 656
 Fragment header (IPv6), 671
 Fragment RP Count field (PIMv2 Bootstrap
 messages), 515
 Fragment Tag field (PIMv2 Bootstrap
 messages), 515
 fragmentation, 346
 Freedman, Avi, 79
 FSM (Finite State Machine), BGP, 95
 Active state, 97
 Connect state, 97
 Established state, 98
 Idle state, 96

- OpenConfirm state, 98
- OpenSent state, 97
- FTP (File Transfer Protocol), NAT translation, 352–353
- full DVMRP implementation, comparing to Cisco IOS implementation, 599–600
- full-mesh topologies, MSDP, 624–626
- functional MAC addresses, 403
- functional multicast addresses, 403
- functionality of IPv6, 672–715
 - ND, 675–685
 - ICMP, 675
- functions of multicast routing protocols, 429–430

G

- GARP Multicast Registration Protocol (GMRP), 422
- gateways, EGP, 7
- GDA (Group Destination Address), 422–426
- GDA field, CGMP packets, 427
- General Queries, differences in versions, 416
- General Query messages, Max Response Time, 413
- Generation ID field (DVMRP Probe messages), 447
- get requests (SNMP), 731
- GGP (Gateway-to-Gateway Protocol), 5
- global addresses, 334
- global commands, RIPng, 694
- GMRP (GARP Multicast Registration Protocol), 422
- graft messages, 434
 - DVMRP, format, 450
 - PIM-SM, 481
 - PIMv2, 516
- Graft Retransmission timer (DVMRP), 445
- Graft-Ack messages, PIMv2, 516
- GRE (generic route encapsulation)
 - between PIM routers, 597
 - on tunnel interfaces, 572–576
- Group Address field
 - CBT JOIN_REQUEST messages, 470
 - IGMP messages, 418

- group membership (IP multicast), 404
 - (*, G) state, 435
 - “all systems on this subnet” group, 412
 - broadcast domains, 420
 - CBT, member sources, 466–467
 - CGMP, 419
 - MAC addresses, 422–426
 - operation of, 422–426
 - comparing IGMPv2 and IGMPv1, 415–416
 - IGMPv2
 - message format, 417–418
 - router functions, 413–414
 - IGMPv3, 417
 - join latency, 408
 - leaving, 405–408
 - Old Host Present Timer, 416
- Group Membership Interval, 416
- Group Membership LSAs, 460
 - fields, 461
 - flooding, 455
- groups
 - assigning to RPs, 549–550
 - rp mappings, viewing, 556–557
- Group-Specific queries, 414

H

- half-life
 - flapping routes, 116
 - route penalties, 261
- hash function, 491
- Hash Mask Length field (PIMv2 Bootstrap messages), 515
- hash-mask, 567
- headers
 - checksums, 346
 - EGP messages, fields, 18
 - format
 - DVMRP messages, 445–446
 - PIMv2 messages, 508–509
 - IPv6, 667
 - extension headers, 669–672
 - format, 667
 - IPv6 packets, 649
- Hello interval, EGP messages, 9

Hello messages

- CBT, format, 469–470
- PIMv2, 509

hierarchical routing, 64

hierarchical structure of aggregatable addresses, 654

hold time interval, BGP configuration, 208

holdtime, mapping agents, 555

Holdtime field (Candidate-RP-Advertisement messages), 517

hop count, DVMRP, 443

Hop Limit field (IPv6 header), 668

Hop-by-Hop options header (IPv6), 670

host configuration, comparing IPv4 and IPv6, 645

host renumbering, IPv6, 689–690

HSRP (Hot Standby Routing Protocol), 783–784
configuring, 785–789

I

IANA (Internet Assigned Numbers Authority), 69

IBGP (internal BGP), 93

over IGP

case study, 174–182

configuring, 167–174

synchronization, 117–123

troubleshooting, 183

ICMPv6 (Internet Control Message Protocol), 674–675

Destination Unreachable messages, 675

MTU Path Discovery, 690

Packet Too Big messages, 675

Parameter Problem messages, 675

Time Exceeded messages, 675

Idle state (BGP), 96

IG (inside global) addresses, 334

IGMP (Internet Group Management Protocol), 405

General Query messages, Max Response Time, 413

Group-Specific queries, 414

Membership Reports, Group Membership Interval, 416

queries, rules for, 536–540

snooping, 422

version 1, 416

version 2, 415–416

version 3, 417

IGMPv2 (Internet Group Management Protocol)

version 2, 415–416

comparing to version 1, 415–416

General Queries, 416

host functions, 411–412

message fields, 417–419

router functions, 413–414

IGPs (interior gateway protocols), 6

injecting BGP routes, case study, 161–167

injecting routes into BGP, case study, 155–161

synchronization with IBGP, 117–123

IL (inside local) addresses, 334

implementing

DVMRP with Cisco IOS software, 598–600

IP multicast, 399

IPv6

6bone, 647

6REN, 646–648

vender support, 647

outbound routing policies, 216–217

TTL scoping, 439

implicit joins, 432–434

inbound soft reconfiguration, 210–211

indirect neighbors, EGP, 15

configuring, 35–38

initiating new BGP sessions, 210

injecting

BGP routes, case study, 161–167

IGP routes into BGP, case study, 155–167

INTER_AS METRIC, 106

interactive multicast applications, group members, 436

inter-area MOSPF, 456–459

inter-area multicast forwarders, 457

Inter-Area-Prefix-LSAs, 702

inter-AS MOSPF, 459–460

extension formats, 460–462

inter-AS multicasting, 602

inter-AS topologies (BGP)

multi-homing to multiple ASs, 84–87

multi-homing to single AS, 80–84

single-homing, 78–79

interface identifier, aggregatable global addresses, 657

- interface subcommands, RIPng, 694–695
- interface topology, aggregatable addresses, 654
- interfaces, route dampening, 261–264
- internal peers (BGP), 93
- Internet
 - address leakage, 339
 - scalability, 55–56
- interoperability of internetworks, 77
- interpreting EGP neighbor table, 39–41
- Intra-Area-Prefix-LSAs, 704
- invalid routes in BGP routing table, 217
- IOS. *See* Cisco IOS
- IP accounting, 756–757
- IP addresses, conserving, 336–338
- ip bgp-community new-format command, 278, 281
- ip cgmp command, 533
- ip classless command, 60
- ip default-gateway command, 361
- ip dense-mode command, 533
- ip igmp query-interval command, 413
- ip igmp query-max-response-time commands, 413
- ip igmp query-timeout command, 414
- ip igmp version command, 411, 532
- IP masquerading, 342
- ip mdsdp cache-sa-state command, 609
- ip mdsdp command, 622–623, 626–633
- ip mroute command, 573
- IP multicast. *See also* multicast addresses; multicast groups; multicast routing protocols
 - across non-multicast domains, 595–598
 - addresses, 399
 - administrative scoping, 594–595
 - Anycast RP, 627–632
 - broadcast domains, 420
 - CBT (core-based trees), 462–463
 - Candidate Core messages, 465
 - child interface, 464
 - FLUSH_TREE messages, 464
 - JOIN_REQUEST messages, 463–464
 - member sources, 466–467
 - message fields, 468–473
 - nonmember sources, 467
 - parent interface, 464
 - CGMP, 419
 - CAM table, 423
 - operation of, 422–426
 - packets, 422
 - configuring, 531–533
 - DVMRP, 441–442, 598–600
 - fast switching, disabling, 533
 - functional addresses, 403
 - group membership, 404
 - “all systems on this subnet” group, 412
 - IGMPv2 router functions, 413–414
 - leaving, 405–408
 - IGMPv3, 417
 - implementing, 399
 - inter-AS, 602
 - IPv6, 708
 - PIM routing, 712–714
 - IPv6 multicast addresses, 662
 - join latency, 408
 - leave latency, 408
 - load sharing, 568–575
 - many-to-many applications, 398
 - MBGP (Multicast extensions for BGP), 606–607
 - configuring, 614–619
 - MDSP, 605–606
 - caching, 609
 - configuring, 619–624
 - default peers, 633–634
 - mesh groups, 624–627
 - message format, 609
 - mgated, 441
 - mrouted, 441
 - Multicast Backbone, 399
 - multicast forwarding, 428–429
 - multicast groups, Old Host Present Timer, 416
 - multicast load sharing, 568–575
 - multicast scoping, 593
 - one-to-many applications, 398
 - over Ethernet, 402
 - over FDDI, 402
 - over Token Ring, 403–404
 - packets, capturing, 547
 - permanent multicast groups, 400
 - PIM
 - IPv6, 712–714
 - PMBR, 602
 - sparse-dense mode, 559–562
 - tunneling between routers, 595–598
 - PIM-DM
 - (*, G) entry, 535–536

- configuring, 533–541
 - DRs, 484
 - PIM forwarder election, 484–487
 - prune overrides, 481–483
 - RPF checks, 536
 - unicast routing changes, 484
- PIM-SM
 - Auto-RP, 491
 - bootstrap protocol, 489–491, 562–567
 - configuring, 542–558
 - routing between domains, 603–604
 - RPs, 489–491
 - shared trees, 492–495
 - source registration, 498–499
 - SPTs, 502–506
 - static RP configuration, 542–550
- reports, 409–410
- requirements, 398–399
- static mroutes, 573–575
- switched traffic, controlling, 421–422
- transient multicast groups, 401
- troubleshooting, 576
 - command summary, 576
 - mrinfo command, 577–579
 - mstat command, 580–584
 - mtrace command, 580–583
- TTL scoping, 593
- well-known reserved addresses, 401
- ip multicast boundary command, 594–595
- ip multicast routing command, 531–532
- ip multicast use-functional command, 404, 533
- ip nat inside command, 358
- ip nat inside source command, 381
- ip nat outside source static command, 359
- ip nat pool command, 365
- ip nat translation command, 386
- ip nat translation timeout command, 337, 367
- ip pim bsr-candidate command, 515, 563, 567
- ip pim query-interval command, 509
- ip pim rp-candidate command, 563
- ip pim send-rp-announce command, 551, 555
- ip pim sparse-dense-mode command, 560
- ip pim sparse-mode command, 542
- ip pim spt-threshold command, 548
- ip pim version command, 508
- IPng (IP Next Generation), 56
- IPv4 (Internet Protocol version 4)
 - IPv6 compatible addresses, 659
 - transition to IPv6, 715
 - DNS, 716
 - dual stacks, 715
 - NAT-PT, 720
 - tunneling, 717–719
- IPv6 (Internet Protocol version 6)
 - 6bone, 647
 - 6REN, 646–648
 - address type allocation, 652–653
 - addresses
 - colons, 650
 - compacting, 650
 - embedded IPv4 addresses, 659
 - link-local addresses, 659
 - loopback, 658
 - prefixes, 651
 - site-local addresses, 660
 - size, 649
 - structure, 654–666
 - text representation, 650
 - unspecified, 658
 - anycasting, 708
 - autoconfiguration
 - renumbering, 689–690
 - stateful, 688
 - stateless, 685–688
 - broadcasting, 662
 - compatibility with IPv4, 659
 - design goals, 643–644
 - ease of configuration, 645
 - improve scalability, 644
 - security, 645
 - enabling on Cisco routers, 673–674
 - functionality, 672–715
 - ICMPv6, 674–675
 - multicasting
 - MLD, 709–711
 - PIM routing, 712–714
 - scoped addresses, 708
 - ND (Neighbor Discovery), 675–676, 681, 684–685
 - address resolution, 680–681
 - default router selection, 684
 - duplicate router selection, 685
 - NA, 679

- neighbor unreachable detection, 681–683
- next-hop discovery, 680
- RA, 677–679
- Redirect messages, 680
- router solicitation, 677
- packets, 649
 - headers, 667–672
- QoS, 714
- routing
 - BGP-4 multiprotocol extensions, 704–708
 - MTU path discovery, 690–691
 - OSPFv2, 697–704
 - RIPng, 691–697
- security, ESP, 672
- source nodes, MTU path discovery, 671
- specifications, 646
- vendor support, 647
- IPv6 Research & Education Networks (6REN), 647
- ISPs (Internet Service Providers)
 - address leakage, 339
 - local, 64
 - migration, 338–340

J-K

- join latency, 408
- Join messages (PIMv2), 511, 513
- Join packets (CGMP), 422
- JOIN_ACK messages (CBT), 471
- JOIN_REQUEST messages, 463–464
 - fields, 470
- keepalive
 - BGP configuration, 208
 - TLV format, 612
- Keepalive messages (BGP), 94, 136

L

- lab testing, 791–792
- LANs, 64
- large-scale BGP, 265
 - assigning private AS numbers, 284–286
 - communities, 270–283
 - confederations, 287–291, 294–300
 - peer groups, 265–266, 269
 - peer management
 - with communities, 123
 - with confederations, 130–131
 - with peer groups, 123
 - with route reflectors, 124–125, 129
 - route reflectors, 300–305
- large-scale IP multicast routing, 593
 - Anycast RP, 627–632
 - DVMRP, 598–600
 - MBGP, configuring, 614–619
 - MDSP
 - configuring, 619–625
 - default peers, 633–634
 - message formats, 609–613
- Layer 2 switches, exchanges, 654
- leading zeros, compacting in IP addresses, 650
- leaf networks, 430
- leaking addresses to Internet, 339
- Leave Group messages, 412
- leave latency, 408
- Leave packets (CGMP), 422
- leaving multicast groups, 405, 408
- limitations of EGP, 26
- Link State ID field (Group Membership LSAs), 460
- link-local addresses, 659
 - in OSPFv2, 701
- links
 - backdoor routes, 236–241
 - multiple OPSFv2 process handling, 699–701
 - OSPFv2, 698
- link-state routing protocols
 - OSPFv2, 697–704
 - RIPng, RTEs, 692
- listener discovery, IPv6 multicast addresses, 709–711
- literals, 219
 - in regular expressions, 815
- little-endian, 403

- load balancing, 381
 - BGP, 88
 - per-packet, 569
- local addresses, 334
- local BGP routes, 235
- local group database, MOSPF, 454
- local ISPs, 64
- LOCAL_AS attribute, 274
- LOCAL_PREF attribute, 105
 - manipulating route preference within local AS, 241–245
 - modifying, 241
- local-use addresses (IPv6)
 - link-local addresses, 659
 - site-local addresses, 660
- Loc-RIB, 113
- logging, 744–747
 - syslog, 748
- loopback addresses, IPv6, 658
- loopback interfaces
 - BGP, configuring, 154
 - tunneling, 569–572
- loss of path information, BGP aggregates, 199–200
- loss of routing precision, troubleshooting, 63–64
- LSAs (link state advertisements)
 - As-External LSAs, flooding outside OSPF domains, 459
 - flooding, 455
 - Group Membership LSAs, 460–461
 - Network Summary LSAs, flooding outside MOSPF areas, 456
 - OSPF, flooding scope, 699
 - OSPFv2, 701–704
 - Router LSAs, 461

M

- MAC (media access control) addresses
 - functional, 403
 - GDA (Group Destination Address), 422–426
 - Token Ring, 403
 - USA (Unicast Source Address), 422–426
- MAEs (Metropolitan Area Ethernets), 65
- maintaining
 - DVMRP neighbors, 442
 - loop-free multicast topologies, 437

- Major Version field (DVMRP messages), 446
- management processes, server design, 782
- manager (SNMP), 731–732
- managing
 - BGP peer connections, 204–208
 - large-scale BGP, 265
 - communities, 270–283
 - confederations, 287–300
 - peer groups, 265–266, 269
 - peering with communities, 123
 - peering with confederations, 130–131
 - peering with peer groups, 123
 - peering with route reflectors, 124–125, 129
 - private AS numbers, 284–286
 - route reflectors, 300–305
- manual configuration of switched multicast trees, 421
- many-to-many applications, IP multicasting, 398
- many-to-one applications, NAT, 337
- mapping single multicast groups to multiple RPs, 627–632
- mapping agents, holdtime, 555
- match interface command, 377
- match ip address command, 224
- match ip next-hop command, 377
- Max Response Time field (IGMP messages), 418
- Max Response Time value (General Query messages), 412–413
- maximum suppress limit, 116, 261
- maximum-paths command, 92, 305
- MBGP (Multiprotocol Extensions for BGP), 604–607
 - configuring, 614–619
 - route attributes, applying, 616
- MBone, 399
- MD5 (message digest 5) authentication, 206
- MDSP
 - configuring, 619–624
 - default peers, 633–634
 - error codes and subcodes, 613
 - mesh groups, 627
 - configuring, 624–626
 - messages
 - Keepalive TLV format, 612
 - Notification TLV format, 612–613
 - Source Active Request TLV format, 610

- Source Active Response TLV format, 611
- Source Active TLV format, 609
- session status, displaying, 620
- member sources (CBT), 466–467
- membership
 - (* , G) state, 435
 - “all systems on this subnet” group, 412
 - broadcast domains, 420
 - CGMP, 419
 - MAC addresses, 422–426
 - operation of, 422–426
 - comparing IGMPv1 and IGMPv2, 415–416
 - Group Membership Interval reports, 416
 - IGMPv2
 - message format, 417–418
 - router functions, 413–414
 - IGMPv3, 417
 - leaving, 405–408
 - multicast groups, 404
 - Old Host Present Timer, 416
- memory, CAM (content addressable memory), 421
- mergers (network), case study, 369–374
- mesh groups (MDSP), 627
 - applying to anycast RPs, 627–632
 - configuring, 624–626
- messages
 - BGP
 - Keepalive, 94
 - Keepalive message, 136
 - Notification, 95
 - Notification message, 136
 - Open, 93
 - Open message, 132
 - Update, 94
 - Update message, 133–135
 - Candidate Core, 465
 - CBT
 - Candidate Core, 465
 - ECHO_REQUEST, 472
 - fields, 468–469, 471–473
 - FLUSH_TREE, 464, 473
 - JOIN_ACK, 471
 - JOIN_REQUEST, 463–464, 470
 - QUIT_NOTIFICATION, 464, 471–472
 - DVMRP, formats, 445–452
 - EGP
 - Error, 24–25
 - Hello interval, 9
 - Neighbor Acquisition, 19–20
 - Neighbor Reachability, 21
 - Poll, 21
 - sequence number, 10
 - TTL, 7
 - Update, 22–24
 - General Query, Max Response Time, 413
 - graft, 434
 - Group-Specific Queries, 414
 - ICMPv6
 - Destination Unreachable, 675
 - Packet Too Big, 675
 - Parameter Problem, 675
 - Time Exceeded, 675
 - IGMPv2, fields, 417, 419
 - IPv6 PIM routing, 712
 - Leave Group, 412
 - MDSP, 609
 - Keepalive TLV format, 612
 - Notification TLV format, 612–613
 - Source Active Request TLV format, 610
 - Source Active Response TLV format, 611
 - Source Active TLV format, 609
 - PIM-SM, RP-Discovery, 492
 - PIMv2, 507–510, 513, 515, 517
 - Assert, 515–516
 - Bootstrap, 513, 515
 - Candidate-RP-Advertisement, 516–517
 - Graft, 516
 - Graft-Ack, 516
 - header format, 508–509
 - Hello, 509
 - Join, 511–513
 - Prune, 511–513
 - Register, 510
 - Register Stop, 510
 - Poll, 15
 - prunes, 432
 - Cisco IOS DVMRP implementation, 600
 - Redirect, 680
 - reports, 409–410
 - SA requests/responses, 609

- SNMP, 731
 - traps, 732–733
- Update, 15
- metacharacters, 219
 - in regular expressions, 815
- Metric field (PIMv2 Assert messages), 516
- Metric Preference field (PIMv2 Assert messages), 516
- metrics
 - DVMRP, 443
 - external, applying, 246–252
 - mgated, 441
 - MHSRP (Multigroup HSRP), 784
 - configuring, 789–790
 - MIBs (management information bases), 731
 - threshold-related, 768
 - migration, IPv4 to IPv6, 715
 - DNS, 716
 - dual stacks, 715
 - NAT-PT, 720
 - tunneling, 717–719
 - Minor Version field (DVMRP messages), 446
 - misconfiguration of BGP, ramifications of, 209
 - MLD (Multicast Listener Discovery), 709–711
 - MLPA (multilateral peering agreement), 67
 - modifying BGP, 235
 - aggregate attributes, 196–197
 - local preference, 241
 - MOSPF (Multicast OSPF), 453–456
 - explicit joins, Group Membership LSA-based, 455
 - inter-area, ABRs, 456–459
 - inter-AS, 459–460
 - extension formats, 460–462
 - local group database, 454
 - Network Summary LSAs, flooding outside areas, 456
 - wildcard multicast receivers, 458–459
 - MP_REACH_NLRI attribute, 606, 705–708
 - applying to MBGP, 616
 - format, 606
 - MP_UNREACH_NLRI attribute, 606, 705–708
 - mrinfo command, 577–579
 - mrouted, 441
 - MSDP (Multicast Source Discovery Protocol)
 - caching, enabling, 609
 - mesh groups, applying to anycast RPs, 627–632
 - messages, 609
 - SA messages, filtering, 623
 - mstat command, 580–584
 - mtrace command, 580–584
 - MTU path discovery, 671
 - IPv6, 690–691
 - MULTI_EXIT_DISC attribute (BGP), 106
 - filtering between confederations, 295–300
 - multicast addresses, 402
 - adding to CAM table, 421
 - CGMP, MAC addresses, 422, 424, 426
 - functional, 403
 - IPv6, 662, 664–665
 - Multicast over Token Ring, 403–404
 - permanent multicast groups, 400
 - reserved, 401, 821–829
 - scoping, 437
 - solicited-node, 665
 - TTL scoping, 664
 - well-known, 401, 663–664
 - Multicast Backbone, 399
 - multicast forwarding, 428–429
 - multicast groups, 404
 - “all systems on this subnet” group, 412
 - CGMP, 419
 - packets, 422
 - comparing IGMPv1 and IGMPv2, 415–416
 - IGMP Group-Specific queries, 414
 - IGMPv2
 - Old Host Present Timer, 416
 - router functions, 413–414
 - IGMPv3, 417
 - leaving, 405–408
 - mapping to RPs, 627–632
 - multicast load sharing, 568–573
 - multicast NAPs, 604
 - Multicast OSPF. *See* MOSPF
 - multicast routing protocols, 430
 - (* , G) state, 435
 - broadcast-and-prune protocols, 434
 - CBT, DRs, 465–466

- DVMRP, 441
 - Graft Retransmission timer, 445
 - message format, 445–452
 - metric, 443
 - neighbor discovery, 442
 - packet forwarding, 444
 - prune lifetime, 444–445
 - routing table, 443
 - RPF check, 444
- explicit joins, 432, 434
- flood-and-prune protocols, 434
- graft messages, 434
- implicit joins, 432–434
- leaf networks, 430
- MOSPF, 453–456
 - explicit joins, Group Membership LSA-based, 455
 - inter-area, 456–459
 - inter-AS, 459–462
 - local group database, 454
 - Network Summary LSAs, flooding outside areas, 456
 - wildcard multicast receivers, 458–459
- prune messages, 432
- RPM (reverse path multicast), 430
- shared trees, 435–437
- source-based trees, 435–437
- topologies, 431
- TRPB (truncated reverse path broadcast), 430
- multicast scoping, 437
 - administrative, 440
 - TTL, 438–439
- multicast storms, 428
- multicasting. *See* IP multicast
- multihomed AS
 - NAT, 340, 342
- multihoming, 72
 - NAT, case study, 374–379
- mutual redistribution, between IGP and BGP, 215–218
- MX (Mail Exchange) records, 350

N

- NA (neighbor advertisement)
 - ND, 679
 - packets, 676
 - name servers, 350
- NAPs (network access points), 64
 - MAEs, 65
 - multicast, 604
- NAPT (network address and port translation), 342
- NAT (Network Address Translation). *See also* PAT
 - address translation table, 335
 - clearing entries, 387
 - address types, 334
 - command summary, 388
 - configuration exercises, 389–391
 - IP address conservation, 336–338
 - ISPs
 - migration, 338–340
 - multihoming, case study, 374–379
 - many-to-one applications, 337
 - network mergers, case study, 369–374
 - PAT, 342–343, 379–381
 - protocol-specific issues, 347–348
 - DNS, 349–352
 - FTP, 352–353
 - ICMP, 348
 - routing protocols, 354
 - SMTP, 354
 - SNMP, 354
 - traceroute, 354–355
 - role in scaling enterprise networks, 338
 - security weaknesses, 347
 - TCP load distribution, 343
 - translated timeout, 337
 - troubleshooting, 386–387
- native packet capture, 741
- NAT-PT (Network Address Translation-Protocol Translation), 720

- ND (Neighbor Discovery), 675–676, 681–685
 - address resolution, 680–681
 - default router selection, 684
 - duplicate router selection, 685
 - NA (neighbor advertisement), 679
 - neighbor unreachability detection, 681–683
 - next-hop discovery, 680
 - NS (neighbor solicitation), 679
 - RA (router advertisement), 677–678
 - Redirect messages, 680
 - RS (router solicitation), 677
- necessity of BGP-4, 75, 77
- negation, regular expressions, 817
- Neighbor 2 messages (DVMRP), format, 451
- Neighbor Acquisition messages (EGP), 19–20
- Neighbor Acquisition Protocol (EGP), 9–11
- neighbor activate command, 617
- Neighbor Address field (DVMRP Probe messages), 448
- neighbor default-originate command, 166
- neighbor description command, 204–205
- neighbor discovery, 442
- neighbor distribute-list command, 167, 198, 224
- neighbor ebgp-multihop command, 184
- neighbor maximum-prefix command, 206
- neighbor next-hop-self command, 290–292
- Neighbor Reachability messages (EGP), 21
- Neighbor Reachability Protocol (EGP), 11–13
- neighbor remove-private-AS command, 286
- neighbor shutdown command, 208
- neighbor state (DVMRP)
 - in Cisco IOS DVMRP implementation, 600
 - RPF peers, 607
- neighbor table (EGP), interpreting, 39, 41
- neighbor unreachability detection, ND protocol, 681–683
- neighbor version command, 206
- neighbors (BGP)
 - connections, resetting, 209–211
 - displaying information, 805–812
 - peer groups, 265–266, 269
- NetFlow switching, 757–765
- network labs, 791–792
- network management
 - CiscoWorks, 733
 - SNMP, 731
 - agents, 731–732
 - community strings, 731
 - get requests, 731
 - manager, 731–732
 - traps, 732–733
- Network Reachability Protocol (EGP), 13–18
- network service providers, 64
- Network Summary LSAs, flooding outside MOSPF areas, 456
- networks
 - directly connected, 235
 - applying external metric, 246–252
 - robustness, 782
 - HSRP, 783–790
- Next Header field (IPv6 header), 668
- NEXT_HOP attribute (BGP), 102, 104, 705
- next-hop discovery, 680
- next-hop-self, 104
- next-level providers, 6bone, 648
- NICs (network interface cards)
 - multicast group members, 401
 - Token Ring, identifying functional addresses, 404
- NLA registries, 657
- NLAIDs (next-level aggregation identifiers), 657
- NLRI (Network Layer Reachability Information)
 - AFI, 606
 - BGP-4, 705–707
 - Sub-AFI, 606
- no ip mroute-cache command, 533
- NO_ADVERTISE community attribute, 273–274
- NO_EXPORT community attribute, 270–273
- node addresses, 675–676
 - IPv6, 666
- nonmember sources (CBT), 467
- Notification messages (BGP), 95
 - fields, 136
 - TLV format, 612–613
- NS (neighbor solicitation)
 - ND, 679
 - packets, 676
- NSF, RA (Routing Arbiter) project, 66
- NTP (Network Time Protocol), 750–751
 - configuring, 751–755

O

- octets, compacting, 650
- OG (outside global) addresses, 334
- OL (outside local) addresses, 334
- Old Host Present Timer, 416
- one-to-many applications, 398
- Open messages (BGP), 93
 - fields, 132
- OpenSConfirm state (BGP), 98
- OpenSent state (BGP), 97
- Option Length field (CBT Hello messages), 470
- Option Type field (CBT Hello messages), 470
- Option Value field (CBT Hello messages), 470
- optional characters in regular expressions, 818
- optional nontransitive attributes (BGP), 98, 606
 - CLUSTER_LIST, 110
 - ORIGINATOR_ID, 110
- optional transitive attributes (BGP), 98
 - AGGREGATOR, 107–109
 - COMMUNITY, 109
 - MULTI_EXIT_DISC, 106
- Options header (IPv6), 670
- ORIGIN attribute (BGP), 99
- Originating Router field (CBT JOIN_REQUEST messages), 470
- ORIGINATOR_ID attribute (BGP), 110
 - applying to route reflectors, 129
- origins of EGP, 5–6
- oscillations, 115
- OSPF (Open Shortest Path First), multicast
 - extensions, 460
 - Extended Options field format, 462
 - Extended Router LSA format, 461
 - Group Membership LSA format, 460
- OSPFv2, 697–704
 - addressing semantics, 698
 - authentication, 701
 - IPv6, 697–704
 - link-local addresses, 701
 - links, 698
 - multiple process handling, 699–701
 - LSAs, 701–704
 - flooding scope, 699
- Other Querier Present Interval, 414
- outbound policies, implementing, 216–217
- overloading, 379

P

- packet forwarding, DVMRP, 444–445
- Packet Too Big messages (ICMPv6), 675, 690
- packets
 - capturing, 741
 - CGMP, 422
 - fields, 427
 - format, 426–427
 - fragmentation, 346
 - headers, checksums, 346
 - ICMPv6, 674–675
 - IP multicast
 - capturing, 547
 - disabling fast switching, 533
 - IPv6, 649
 - headers, 667–672
 - multicast storms, 428
- Parameter Problem messages (ICMPv6), 675
- parameters of BGP routes, administrative
 - weight, 110
- parent interface, 464
- passive gateways, EGP, 10
- passive opens, 352
- PAT (Port Address Translation), 342, 379–381
- path attributes (BGP), 90, 98
 - AGGREGATOR, 107, 109
 - AS_PATH, 100–101
 - AS_SET, 111–113
 - ATOMIC_AGGREGATE, 107–109
 - CLUSTER_LIST, 110
 - COMMUNITY, 109
 - LOCAL_PREF, 105
 - MULTI_EXIT_DISC, 106
 - NEXT_HOP, 102–104
 - ORIGIN, 99
 - ORIGINATOR_ID, 110
- path discovery, 690–691
- path vector routing protocols, 90
- Payload Length field (IPv6 header), 667
- peering, 123, 265–266, 269
 - BGP, 88–89, 93
 - connections, managing, 204–208
 - connections, resetting, 209–211
 - displaying group statistics, 269
 - during neighbor authentication, 205
 - large-scale, 123–125, 129–131

- route reflectors, 300–307
 - soft reconfiguration, 210
- MDSP, configuring, 633–634
- RPF flooding, 607
- peering agreements, 67
- penalties for unstable routes, 116, 261–264
- per-destination balancing, 569
- performance
 - change management, 729–730
 - fault management, 766–768
 - thresholds, 767
 - logging, 744–747
 - syslog, 748–750
 - SLAs (Service Level Agreements), 728
- performance management, 769
- per-hop behavior (PHB), 715
- Perl, 766
- permanent multicast groups, 400
 - well-known addresses, 401
- per-packet load balancing, 569
- PHB (per-hop behavior), 715
- physical links between ASs, 79
- PIM (Protocol Independent Multicast), 473–475
 - IPv6 multicast routing, 712–714
 - PMBR (PIM Multicast Border Router), 602
 - shortest-path trees, 478
 - sparse-dense mode, configuring, 559–562
 - tunneling between routers, 595–598
- PIM-DM (Protocol Independent Multicast-Dense Mode), 475–481
 - (*, G) entry, 535–536
 - configuring, 533–541
 - DRs, 484
 - flood-and-prune mechanism, 481
 - PIM forwarder election, 484–487
 - prune overrides, 481–483
 - RPF checks, 536
 - unicast route changes, 484
- PIM-SM (Protocol Independent Multicast-Sparse Mode), 487–488
 - Auto-RP, 491
 - configuring, 551–558
 - bootstrap protocol, 489–491
 - configuring, 562–567
 - configuring, 542–558
 - mapping agents, holdtime, 555
 - routing between domains, 603–604
 - RPs (rendezvous points), 489–491
 - static configuration, 542–548
 - shared trees, 492–495
 - source registration, 498–501
 - SPTs, 502–506
- PIMv2 bootstrap, hash-mask, 567
- plus sign (+) in regular expressions, 818
- PMBR (PIM Multicast Border Router), 602
- point-to-point interfaces, Cisco IOS DVMRP
 - implementation, 600
- policies
 - change management, 729–730
 - escalation procedures, 730
 - routing, enforcing, 77
 - updating, 730
- Policy Routes, 208
- Poll messages (EGP), 15, 21
- POP (Point of Presence), 64
- portability, CIDR, 72–73
- portable address space, 75
- Preference field (CBT Hello messages), 469
- preferred addresses, 678
 - feasible routes, 114
 - IPv6, 689
- Preferred Lifetime, 678
- Prefix Count field (Candidate-RP-Advertisement messages), 517
- prefixes (IP addresses), text representation, 651
- prepending the AS_PATH, 252–256
- preventing DoS attacks, 771–772
- primary DNS servers, 350
- Priority field (Candidate-RP-Advertisement messages), 517
- private AS numbers, 284–286. *See also*
 - confederations
- private links, backdoor routes, 236–241
- private peering, 67
- Probes (DVMRP), 442
 - in Cisco IOS DMVRP implementation, 599
 - message format, 446–447
- production networks, lab testing, 791–792
- programming languages, Perl, 766
- promiscuous packet capture, 741
- Prune messages, 432
 - DVMRP
 - format, 449
 - Cisco IOS implementation, 600

- lifetime, 444–445
- PIMv2, 511, 513
- pseudo transit providers, 6bone, 648
- PTR (Pointer) records, 350
- public topology, aggregatable addresses, 654

Q

- QoS (quality of service)
 - IPv6, 714
 - SLAs (Service Level Agreements), 728
- queries
 - IGMP, rules for, 536–540
 - Max Response Time, 412
- question mark (?) in regular expressions, 818
- QUIT_NOTIFICATION messages (CBT), 464, 471–472

R

- RA (Router Advertisement) packets, 676–678
- RA (Routing Arbiter) project, 66
- RADIUS (Remote Dial-In User Service), 780
- reachability
 - BGP attributes, 705–708
 - maintaining during ISP migration, 339
 - NLRI, 606
- Redirect messages, 680
- Redirect packets, 676
- redistribute command, 156
- redistribution (BGP), 159
- redundant systems, 79, 766–768
- regional IP registries, 69
- regional service providers, 64
- Register messages (PIMv2), 510
- Register Stop messages (PIMv2), 510
- regular expressions, 219
 - alternation, 817
 - boundaries, 818
 - bracketing, 816
 - carets (^), 817
 - delineation, 816
 - literals and metacharacters, 815
 - negation, 817
 - optional characters, 818

- repetition, 818
- wildcards, 817
- remote access, SSH, 780–782
- repetition in regular expressions, 818
- replicated unicast, 396
- report messages, 409–410
 - Route Report Interval, 443
- requirements
 - for IP multicast, 398–399
 - IPv6 node addresses, 666
- Reserved field (CGMP packets), 427
- reserved field (aggregatable global addresses), 656
- reserved multicast addresses, 401, 821–829
- resetting
 - BGP connections, 209–211
 - BGP sessions, 154
- reuse limit, 261
 - flapping routes, 116
- reverse lookups, 351
- reverse path broadcasting (RPB), 430
- reverse path forwarding (RPF), 430
- reverse path multicast (RPM), 430
- RFC 827, scalability of ARPANET, 5
- RFCs relating to IPv6, 646
- RIB (Routing Information Base), 113–115
- RIPE (Resèaux IP Européens), 69
- RIPng (RIP next generation), 691–697
 - global commands, 694
 - interface subcommands, 694–695
 - IPv6, 691–695
 - routing process, enabling, 693
- RMON, 740
 - router configuration, 741–743
- robustness, 782
 - HSRP, 783–790
 - configuring, 785–789
 - MHSRP, configuring, 789–790
- Rosen, Eric, 5
- route aggregation, 56, 61
 - asymmetric traffic patterns, 64
 - CIDR, 56
 - precision of, 61
- route dampening, 115–116, 261–264
- route dependencies, 443
- route expiration time, 443

- route filters (BGP), 216–219
 - community lists, 276
 - filtering by AS_PATH, 219–222
 - filtering by NLRI, 211, 214
 - filtering with route maps, 224–226
 - outbound, implementing, 216–217
- route maps, 194
 - applying, 224–226
 - AS_PATH prepending, 252–256
 - filtering routes
 - AS_PATH as criteria, 219–222
 - LOCAL_PREF as criteria, 241–245
 - MULTI_EXIT_DISC as criteria, 246–252
 - NLRI as criteria, 211, 214
 - route tagging, 256–260
 - multiple routes to same destination, 226–234
 - multiple routes to same destination learned from different routing protocols, 234–241
 - route tagging, 256–260
- route oscillation, 115
- route reflectors
 - clusters, 125
 - configuring, 300–307
 - large-scale BGP peering management, 124–125, 129
- Route Report Interval, 443
- Route Report Messages, format, 448
- route servers, 66
- route tagging, 256–260
- router IDs, assigning to BGP routers, 154
- Router LSAs, 461
- routers
 - ABRs, 456–457
 - ASBRs (Autonomous System Boundary Routers), 459
 - configuring as C-RP, 551
 - default router selection (ND), 684
 - default-free zone, 654
 - DRs
 - CBT, 465–466
 - PIM-DM, relationship to IGMP querier, 537–541
 - duplicate router selection (ND), 685
 - DVMRP, 598–600
 - enabling IPv6 capability, 673–674
 - inter-area multicast forwarders, 457
 - logging, 744–747
 - management
 - change management, 729–730
 - CiscoWorks, 733–739
 - escalation procedures, 730
 - policies, updating, 730
 - SLAs (Service Level Agreements), 728
 - NTP, configuring, 751–755
 - PIM
 - rules for, 536–537
 - tunneling, 595–598
 - PMBR (PIM Multicast Border Router), 602
 - POPs, 64
 - querying, 579
 - RMON, configuring, 741–743
 - syslog, configuring, 749–750
- routes
 - administrative weight, 110
 - aggregate, AS_SET attribute, 111–113
 - BGP
 - selection process, 114
 - tie-breaking, 114–115
- routing
 - BGP-4 multiprotocol extensions, 704–708
 - IPv6, 690–697
 - OSPFv2, 697–704
- Routing header (IPv6), 671
- routing loops, detecting, 91
- routing policies, 77, 208–209
 - enforcing, 77
 - filtering routes
 - by AS_PATH, 219–222
 - by NLRI, 211–219
 - misconfiguration, ramifications of, 209
 - mutual redistribution, 215–218
 - outbound, implementing, 216–217
 - route maps, 224–226
 - soft reconfiguration, 210–211
- routing protocols
 - BGP
 - assessing need for, 75–77
 - decision-making process, 113–115
 - equal cost paths to destination, 92
 - FSM, 95–98
 - Keepalive message, 94
 - load balancing, 88
 - Notification message, 95
 - Open message, 93

- path attributes, 90, 98
 - peering, 88–89, 93
 - tie-breaking process, 114–115
 - Update message, 94
- classless, 57–60
- EGP
 - operation, 7
 - topology, 7–8
- NAT translation, 354
- path vector, 90
- summarization, 61
- routing tables
 - BGP
 - directly-connected links, 119
 - invalid routes, 217
 - DVMRP, 443
 - unicast, 536
- RP Count field (PIMv2 Bootstrap messages), 515
- RP Holdtime field (PIMv2 Bootstrap messages), 515
- RP Priority field (PIMv2 Bootstrap messages), 515
- RPB (reverse path broadcasting), 430
- RPF (reverse path forwarding)
 - DVMRP, 444
 - failover, example, 553
 - peer RPF flooding, 607
 - PIM-DM, 536
- RPM (reverse path multicast), 430
- RPng, RTEs (route table entries), 692
- RPs (rendezvous points), 489–491
 - groups, assigning, 549–550
 - hash function, 491
 - mapping agents, 491
 - mapping to multicast group, 627–632
 - PIM-SM, Auto-RP, 551–558
 - static configuration, 542–550
 - troubleshooting, 551
- RPTs (rendezvous point trees), 478
- RRs (resource records), 350
- RS (Router Solicitation) packets, 676–677
- RSA Data Security, Inc., 206
- RTEs (route table entries), RIPng, 692
- rules
 - for IGMP queries, 540
 - for PIM-DM, 536–537
 - for synchronization, 120–123

S

- SA requests/responses, 609
 - filtering, 623
- scalability
 - ARPANET, 5
 - IPv6, 644
 - of enterprise networks, role of NAT, 338
 - of explicit joins, 435
 - of Internet, 55–56
 - shared trees, 437
- scoping, 395, 437
 - administrative, 594–595
 - multicast addresses
 - administrative scoping, 440
 - IPv6, 664, 708
 - relative addresses, 829
 - TTL, 438–439, 593
- scripts, Perl, 765
- SDR (Session Description Protocol), 405
- secondary DNS servers, 350
- secure hash, 206
- security
 - authentication, OSFPv2, 701
 - encryption, 770
 - ESP (Encapsulating Security Payload)
 - IPv6, 672
 - management, 769
 - controlling interactive access, 770–771
 - DoS attacks, preventing, 771–772
 - passwords, 770
 - RADIUS, 780
 - SSH, 780–782
 - TACACS+, 773–779
 - NAT, weaknesses in, 347
- selection process
 - BGP best routes, 114
 - PIM-DM forwarders, 484–485
 - routes with specified community attributes, 280–282
- semantics, OSPFv2 addressing, 698
- sequence number, EGP messages, 10
- server management processes, designing for, 782
- service distribution, case study, 383–385
- Service Level Agreements, 728

sessions, BGP

- clearing, 154
- configuring, 149–152
- set as-path prepend command, 254
- set as-path tag command, 259
- set automatic-tag command, 260
- set comm-list delete command, 283
- set gmrp enable command, 422
- set igmp enable command, 422
- set local-preference command, 241
- sets (SNMP), 731
- shared trees, 435–437
 - PIM-SM, 492–495
 - scalability, 437
- shortage of IP addresses, 71, 649
- shortcomings of EGP, 26
- shortest-path trees, 478
- show ip bgp command, 91, 274
- show ip bgp community no-export command, 190, 203
- show ip bgp community-list command, 280
- show ip bgp dampened-paths command, 263
- show ip bgp flap-statistics command, 263
- show ip bgp ipv4 command, 616
- show ip bgp neighbors command, 151, 185, 805–812
- show ip bgp peer-groups command, 269
- show ip egp command, 34–35, 39
- show ip igmp group command, 479
- show ip igmp groups command, 413
- show ip igmp interface command, 540
- show ip mdsp peer command, 620
- show ip nat statistics command, 387
- show ip pim bsr-router command, 564
- show ip pim interface command, 546
- show ip pim neighbor command, 477
- show ip pim rp command, 554, 556
- show ip pim rp-hash command, 558
- show ip pim sp-hash command, 567
- show ip route command, 92
- show ipv6 interface command, 674
- single-homed autonomous systems, 78–79
- site renumbering, IPv6, 689–690
- site topology, aggregatable addresses, 654
- site-level aggregation identifier (SLAID), 657
- site-level providers, 6bone, 648
- site-local addresses, 660
- SLAID (site-level aggregation identifier), 657
- SLAs (Service Level Agreements), 728
- SMTP, NAT translation, 354
- SNMP (Simple Network Management Protocol), 731
 - agent, 731–732
 - community strings, 731
 - get requests, 731
 - management station, specifying address, 734
 - manager, 731–732
 - messages, 731
 - NAT translation, 354
 - RMON, 740
 - router management, 733–737
 - traffic, effect on network performance, 732
 - trap messages, 732–733
- snmp-server command, 733
- snmp-server community command, 734
- SOA (Start-of-Authority) records, 350
- sockets, 342
- soft reconfiguration, 210–211
- solicited-node addresses, 665
- Source Active Request TLV format, 610
- Source Active Response TLV format, 611
- Source Active TLV format, 609
- Source Address field (IPv6 header), 668
- source nodes (IPv6), MTU path discovery, 671
- source registration, PIM-SM, 498–501
- source-based trees, 435–437
- sparse mode (PIM), 487
 - Auto-RP, 491
 - bootstrap protocol, 489–491, 562–567
 - configuring, 542
 - mapping agent, holdtime, 555
 - RPs, 489–491
 - static configuration, 542–548
 - shared trees, 492–495
 - source registration, 498–501
 - SPTs, 502–506
- sparse-dense mode, configuring, 559–562
- speakers (BGP), configuring router ID, 155
- special format addresses, IPv6, 658
 - embedded IPv4 addresses, 659
 - loopback, 658
 - unspecified, 658
- specifications of IPv6, 646

specifying management station address (SNMP), 734

SPTs (shortest-path trees), PIM-SIM, 502–503, 505–506

SSH (Secure Shell), 780–782

standard community lists, 279–281

standards, IPv6, 646

stateful autoconfiguration (IPv6), 688

stateless autoconfiguration (IPv6), 676, 685–688

static address translation table entries (NAT), 336

static configuration

- NAT, case study, 356–364
- RPs, 542–551

static mroutes, 573–575

static routes

- BGP, aggregation, 186
- Cisco Policy Routes, 208
- EBGP multihop configuration, 183–184

statistics, displaying

- BGP neighbors, 805–812
- NAT, 387

structure of IPv6 addresses, 654

- aggregatable global address format, 654–657
- anycast addresses, 660
- local-use addresses, 659–660
- multicast addresses, 662–665
- required node addresses, 666
- site-local addresses, 660
- special-format addresses, 658

stub gateways (EGP), configuring, 27–31

Sub-AFI, 606

Subnet-Router anycast addresses, 661

subnets, leaf networks, 430

subscribers, 73

summarization, 56, 61

- asymmetric traffic patterns, 64
- case study, 185–204
- CIDR, 56
- precision of, 61

suppressing

- BGP routes, 261–264
- flapping routes, 116
- suppress limit, 261

switched multicast traffic, controlling, 421–422

switches (Catalyst), CAM table, 421–423

synchronization, 120

- disabling, 121–122
- IBGP/IGP, 117–123
- NTP, 750–755

syntax, timers egp command, 15

syslog, 748–750

T

table-map command, 260

TACACS+, 773–779

tagging routes, 256–260

Target Router field (CBT JOIN_REQUEST messages), 470

TCP load distribution, 343

testing before implementation, labs, 791–792

text representation, IP address prefixes, 651

thresholds (MIBs), 768

tie-breaking process, BGP routes, 114–115

Time Exceeded messages (ICMPv6), 675

time synchronization, NTP (Network Time Protocol), 750–755

timers

- DVMRP, Graft Retransmission timer, 445
- Old Host Present Timer, 416

timers bgp command, 93, 208

timers egp command, 11, 14–15

TLAID (top-level aggregation identifiers), 656

TLV (Type/Length/Value) formats (MSDP)

- Keepalive TLV, 612
- Notification TLVs, 612
- Source Active Request TLV, 610
- Source Active Response TLV, 611
- Source Active TLV, 609

Token Ring

- functional addresses, 403
- MAC addresses, 403
- multicast addresses, 403–404

top-level aggregation identifiers (TLAID), 656

top-level providers, 6bone, 648

topologies

- BGP
 - multi-homing to multiple AS, 84–87
 - multi-homing to single AS, 80–84
 - single-homed autonomous system, 78–79

- EGP, 7–8
 - convergence, 41–43
 - full-mesh, MSDP, 624–626
 - multicast routing, 431
 - trace command, 354
 - traceroute, NAT translation, 354–355
 - traffic
 - asymmetric, 64
 - BGP
 - inbound soft reconfiguration, 210–211
 - load balancing, 88
 - IP accounting, 756–757
 - NetFlow switching, 757–765
 - load balancing, 381
 - per-packet, 569
 - load distribution, NAT-based, 343
 - multicast
 - behavior, analyzing, 580, 582
 - load sharing, 568–575
 - over backdoor routes, 236–241
 - SNMP, effect on network performance, 732
 - switched multicast, controlling, 421–422
 - transient addresses, 662–663
 - transient join state, 464
 - transient multicast groups, 401
 - transit AS traffic, configuring IBGP without an IGP, 168–174
 - transitioning IPv4 to IPv6, 715
 - DNS, 716
 - dual stacks, 715
 - NAT-PT, 720
 - tunneling, 717–719
 - translation timeout, 337
 - trap messages, 732–733
 - troubleshooting
 - CIDR, 72–73
 - EGP, 39
 - convergence, 41–43
 - interpreting neighbor table, 39–41
 - escalation procedures, 730
 - IBGP, 183
 - IP multicast, 576
 - command summary, 576
 - mrinfo command, 577–579
 - mstat command, 580–584
 - mtrace command, 580–583
 - loss of routing precision, 63–64
 - NAT, 386–387
 - static RP configuration, 551
 - TRPB (truncated reverse path broadcast), 430
 - truncated reverse path broadcast (TRPB), 430
 - TTL (time-to-live)
 - EGP messages, 7
 - scoping, 438–439, 593
 - implementing, 439
 - IPv6 multicast addresses, 664
 - tunneling
 - between DVMRP routers, 600
 - between loopback interfaces, 569–572
 - between PIM routers, 595–598
 - IPv6 in IPv4, 717–719
 - tuples, 342
 - turning off automatic summarization
 - BGP, 157
 - EIGRP, 158
 - tutorial, regular expressions, 818–819
 - Type codes, BGP attributes, 135
 - Type field
 - CBT messages, 468
 - CGMP packets, 427
 - DVRMP messages, 445
 - GMP messages, 417
- ## U
-
- underscore (`_`) in regular expressions, 818
 - unicast routing, 395
 - aggregatable global addresses
 - format, 654–655
 - FP, 656
 - interface identifier, 657
 - reserved field, 656
 - SLAID, 657
 - TLAID, 656
 - replicated unicast, 396
 - routing table, example, 536
 - UNIX syslog, 748–750
 - unreachable addresses from ISP migration, 339
 - unspecified addresses, IPv6, 658

- Update messages
 - BGP, 15, 94
 - fields, 133–135
 - EGP, 22–24
 - RIPng, 692
- updating policies, 730
- upstream interfaces, 428
- USA (Unicast Source Address), 422–426
- USA field, CGMP packets, 427
- UUCast, 399

V

- Valid Lifetime, 678
- vendor support, IPv6, 647
- Version field
 - CBT messages, 468
 - CGMP packets, 427
 - IPv6 header, 667
 - RIPng messages, 692
- Vertex Type field (Group Membership LSAs), 461
- viewing
 - BGP neighbor information, 805–812
 - BGP peer group statistics, 269
 - group-to-rp mappings, 556–557
 - MDSP session status, 620
 - NAT statistics, 387
- VLANs (virtual LANs), 419
- VPNs (Virtual Private Networks), IPSec
 - encryption, 347
- vulnerabilities of NAT security, 347

W-X-Y-Z

- weight. *See* administrative weight
- well-known attributes (BGP)
 - discretionary, 98
 - ATOMIC_AGGREGATE, 107–109
 - LOCAL_PREF, 105
 - mandatory (BGP), 98
 - AS_PATH, 100–101
 - NEXT_HOP, 102–104
 - ORIGIN, 99
- well-known multicast addresses, 663–664
 - reserved addresses, 401
- well-known path attributes, 98
- wildcard multicast receiver, 458–459
- wildcards, regular expressions, 817

- zeros in IP addresses, compacting, 650
- zone transfers, 350