

## Cisco Internetwork Troubleshooting

ISBN: 1-57870-092-2

Cisco Press

### Errata

Pg 64 – Add the following paragraph after the third paragraph:

Also, HDLC has a 2-byte control field, allowing for a 7-bit window size (128 values) rather than the 3-bit (8 values) that SDLC allows.

Pg 117 – The fourth paragraph should read: “The term *domain* is sometimes used to describe a portion of the network in which all routers have identical topological databases.”

Pg 237 – Figure caption for figure 5-21 should read:

The **trace** command displays all routers used along the path to a device.

Pg 303 – Figure 7-21, change the Host C address to:

10.1.2.8 255.255.0.0

Pg 306 – Caption for figure 7-23 should read:

Output of the ipconfig /all command

The second sentence of the fifth paragraph should read: “Enter a DOS window on the Windows NT/98 host and enter the **ipconfig/all** command. Those using Windows 95 can use the command **winipcfg** from a DOS window or the Run dialogue.”

Pg 317 – Second paragraph, add the following afterwards:

Make sure that there is a carriage return after the last entry. If not, it will be ignored.

Pg 351 – The first sentence of the sixth paragraph should read: “Use the **display servers** command on the server, the **show ipx servers** command on the router, or the **slist** command on the client to verify that the server is advertising services.”

Pg 494 – The first sentence of the last paragraph should read: “BRI offers 144 kbps for use at small data connection points.”