

Symbols

- /16, 38
- /24, 38
- ? (question mark), invoking Cisco IOS help menu, 550

Numerics

- 2-way communication exchange process
 - troubleshooting neighbor stuck in 2-way state, 156–157
 - troubleshooting neighbor stuck in exstart/exchange state, 151–156
- 2-way state (neighbors), 119, 134

A

- ABRs, 78
 - configuring, 273–274
 - inter-area route summarization, 411
 - inter-area traffic, controlling, 269–270
 - routing table, displaying, 555–556
- access lists
 - applying to interfaces, 504
 - configuring, 501–502
 - creating, 503
 - SNMP, 462
- activating OSPF, 271–272
 - ABR considerations, 273–274
 - ASBR considerations, 274–275
 - backbone router considerations, 275
 - network command, 272
- adaptability as network design goal, 166
- adding routers to OSPF networks, 85–88
- addressing, 180
 - bit splitting, 184
 - discontiguous subnets, 185–186
 - naming schemes, 186
 - public versus private, 180–181
 - summarization, 181–182
 - VLSM, 185
- adjacencies, 82
 - DRs, 83–84
 - selection process, 84–85
 - event logging, 591–593
 - troubleshooting, 136–138
 - versus neighbor relationships, 82–83
- administrative distances, 341–342
 - altering, 313–314
- agents (SNMP), 452
- aggregates, 39
- aggregation, 33
- algorithms, distance vector, 55
- allocating IP addresses, 184
- altering
 - administrative distance, 313–314
 - LSA default behavior
 - blocking LSA flooding, 131
 - group pacing, 128–129
 - configuring, 130
 - ignoring MOSPF LSAs, 132
 - LSA retransmissions, 132
 - LSA transmission delay, 133
 - packet pacing, 131
 - routes to control redistribution, 397
- analyzing network design requirements, 168–169
 - convergence, 170–171
 - deployment, 169
 - load balancing, 170
- ANSI (American National Standards Institute) X3S3.3 committee, 54
- APNIC (Asia Pacific Network Information Centre), 21
- application layer (OSI), 9

- applications
 - Cisco ConfigMaker, 446
 - CiscoView, 444–445
 - CiscoWorks, 445
- applying
 - access lists to interfaces, 504
 - distribute lists, 361–363
- architectures
 - point-to-point, 6–55
 - selecting, 618, 631–674, 688–699
- area 0, 75
 - connecting to, 215–217
 - example configuration, 217–230
- area default-cost command, 306–309
- Area ID field (Hello packets), 126
- area range command, 309–313
 - configuring area route summarization, 413
- area routes, summarizing, 411–413
- areas, 74
 - ABRs, 78
 - area 0, 75
 - backbone design, 206–207
 - characteristics of, 74
 - configuring, 285–288
 - design rules, 74
 - designing, 200
 - naming conventions, 204
 - tunable parameters, 202–204
 - external routing, 73
 - hierarchical network design, 174–175
 - inter-area routing, 72–73
 - intra-area routing, 72
 - NSSAs, 76
 - design, 212–214
 - RFC 1587, 716–717
 - Type 7 LSAs, 110
 - standard design, 205
 - stub area design, 207–211
 - stub areas, 75
 - characteristics, 75
 - restrictions, 75
 - totally stubby areas, 76
 - TSA design, 212
- ARIN (American Registry for Internet Numbers), 21, 71
- ARPANet, development of link-state routing protocols, 64
- AS (autonomous system), 71
 - areas, 74
 - area 0, 75
 - characteristics of, 74
 - design rules, 74
 - NSSAs, 76
 - stub areas, 75
 - numbers, prepending, 664
- AS_path attribute (BGP), 663
- ASBRs, 78
 - configuring, 274–275
 - routing table, displaying, 555–556
 - summary LSAs, 108
- assessing need for security, 467
- assigning
 - metrics to redistributed protocols, 354–358
 - network addresses, 22
 - subnet masks, 29
- ATM (asynchronous transfer mode), 18
- ATM switching versus MPLS, 687
- attempt state (neighbors), 118, 133
- attributes (BGP), 663
- authentication, 479, 504–505
 - benefits of, 480
 - deploying, 481
 - MD5, 483
 - configuring, 483–488
 - configuring on virtual link, 489–491
 - null authentication, configuring, 492
 - on virtual links, troubleshooting, 492
 - plaintext, 482
- auto-cost reference-bandwidth command, 259

autonomous system external LSAs, 109
autonomous systems, 657
avoiding redistribution loops, 364

B

backbone area design, 75, 206–207
 hierarchical, 173
backbone routers, 79
 configuring, 275
backup configuration files, 476
Backup Designated Router field (Hello packets), 126
bandwidth in hierarchical networks, 199
banners, unauthorized use notifications, 477
BDRs, selecting, 84–85
Bellman, R.E., 55
Bellman-Ford protocols. *See* distance vector routing protocols
benefits
 of MPLS, 686
 of summarization, 408
Best Effort routing, 687–688
BGP (Border Gateway Protocol), 660
 AS_path attribute, 663
 attributes, 663
 characteristics, 661
 dual-homed networks, 662
 dynamic route injection, 665
 EBGP, 664
 IBGP, 664
 interaction with OSPF, 665–667
 keepalive messages, 663
 messages, 663
 path vector, 663
 peer routers, 662
 recursive routing, 671–673
 redistribution, 673–679
 routing dependencies, 667
 routing loops, preventing, 663

 static route injection, 665
 synchronization, 668–669
 negative impact of, 669–671
 troubleshooting case study, 680–683
bidirectional communication, exchange process, 126–127
bit splitting, 184
bit V, 711
broadcast networks, 80
 configuring, 277
broadcast storms, 29
broadcast traffic, 28
building shortest-path tree, 93–95

C

cable modems, 18
calculating
 cost metric, 257–260
 number of required adjacencies, 83–84
 shortest paths, SPF algorithm example, 66
candidate database, 93
case studies
 BGP, 680–683
 router and firewall deployment, 518–529
 Secure IOS template, 506–517
caveats for implementing summarization, 409
 effects on routing table, 418–419
 with VLSM, 426–428
CEF (Cisco Express Forwarding), verifying operation, 701–703
characteristics
 of areas, 74
 of BGP, 661
 of link-state database, 115
 of OSPF, 53, 69
 of RIPv1, 56
 of stub areas, 75
Checksum field (Hello packets), 126

- CIDR (classless interdomain routing)
 - as routing protocol selection criteria, 61
 - design guidelines, 37
 - manual IP prefix computation, 40–41
 - need for, 31–32
 - network validation, 37–38
 - translation table, 39–40
- Cisco ConfigMaker, 446
- Cisco IOS Software
 - features, 188
 - help menu, invoking, 550
 - password encryption, 474
- Cisco MIBs, 459–461
- CiscoView, 444–445
- CiscoWorks, 445
- clarifying PVCs in point-to-multipoint networks, 136–138
- Class A addresses, 22
- Class B addresses, 22
- Class C addresses, 23
- Class D addresses, 23
- Class E addresses, 23
- classful protocols, summarizing, 410
- classful routing, 34
- classless routing, 34
- clear ip ospf command, 585
- clear ip ospf counters command, 585–586
- clear ip ospf process command, 586
- clear ip ospf redistribution command, 587
- clearing OSPF processes, 586
- commands
 - area default-cost, 306–309
 - area range, 309–313
 - area range summarization, 413
 - auto-cost reference-bandwidth, 259
 - clear ip ospf, 585
 - clear ip ospf counters, 585–586
 - clear ip ospf process, 586
 - clear ip ospf redistribution, 587
 - debug ip ospf events, 136
 - debug ip ospf adjacency, 591–593
 - debug ip ospf events, 134, 593–595
 - debug ip ospf flood, 595–597
 - debug ip ospf hello, 597
 - debug ip ospf lsa-generation, 598–599
 - debug ip ospf monitor, 599–600
 - debug ip ospf packet, 600–601
 - debug ip ospf retransmission, 602
 - debug ip ospf spf, 602
 - external keyword, 603–604
 - inter keyword, 604–608
 - intra keyword, 608–614
 - debug ip routing, 614–615
 - default-metric, 354
 - get request (SNMP), 450
 - how ip ospf database database-summary, 563–564
 - ip classless, 39
 - ip ospf cost, 259
 - ip ospf hello-interval, 124
 - ip ospf name-lookup, 541
 - ip ospf priority, 82, 88
 - ip ospf transmit-delay, 133
 - log-adjacency-changes, 549
 - neighbor, 230–231
 - network, 272
 - next-hop-self, 673
 - redistribute, 343–344, 354
 - redistribution, 78, 345–346
 - reference-bandwidth, 259
 - SETREQUEST, 451
 - show frame-relay map, 137
 - show ip ospf, 97, 550–553
 - show ip ospf border-routers, 555–556
 - show ip ospf database, 100, 556–560
 - show ip ospf database asbr-summary, 560–562
 - show ip ospf database external, 564–566
 - show ip ospf database network, 566–568
 - show ip ospf database router, 568–570
 - show ip ospf database summary, 570–572
 - show ip ospf delete, 572–575
 - show ip ospf events, 575–578

- show ip ospf flood-list, 579
- show ip ospf interface, 553–555
- show ip ospf maxage-list, 579
- show ip ospf neighbor, 98, 138, 580–581
- show ip ospf neighbor detail, 582
- show ip ospf stat, 583–584
- show ip ospf summary-address, 585
- show ip ospf virtual-links, 583
- show ip route, 416
- show logging, 544–545
- show memory, 547
- show mpls forwarding-table, 702
- summary-address, configuring external route summarization, 416–417
- communication, exchange process, 126–127
 - troubleshooting neighbor stuck in 2-way state, 156–157
 - troubleshooting neighbor stuck in exstart/exchange state, 151–156
- community strings
 - configuring, 477–478
 - SNMP, 462
- components of SNMP, 447–449
- configuring
 - access lists, 501–502
 - area 0, example, 217–230
 - areas, 285, 287–288
 - NSSAs, 297–309
 - route summarization, 412–413
 - stub, 289–293
 - summarization, 309–313
 - TSAs, 294–295
 - backbone routers, 275
 - broadcast networks, 277
 - DNS lookups, 541
 - DRs, 266
 - external route summarization, 414–418
 - group pacing, 130
 - loopback interfaces, 81, 96, 264–266
 - MD5 authentication, 483–488
 - MD5 authentication on virtual link, 489–492
 - MPLS in OSPF networks, 696–697, 700–701
 - network command, 272
 - network type, 276–277
 - nonbroadcast networks, 278
 - nonbroadcast point-to-multipoint interfaces, 231–232
 - on-demand circuits, 324–328
 - point-to-multipoint networks, 279–282
 - point-to-point networks, 283–284
 - redistribution, 343–344
 - between RIP and OSPF, 366–374, 390–391
 - default routes, 348–353
 - distribute lists, 363, 398–403
 - EIGRP into OSPF, 380–385
 - mutual redistribution, 392
 - on connected routes, 376–380
 - route maps, 344, 365
 - route tagging, 393–395
 - RID, 264
 - SNMP community strings, 477–478
 - stub area, 208–211
 - summarization, 411
 - SYSLOG, 543–546
 - date and time stamping, 546
 - logging neighbor state changes, 548–549
 - logging to internal buffer, 546–547
 - logging to SYSLOG server, 547
 - user authentication, 504–505
- connected routes, redistribution, 376–380
- connecting to area 0, 216–217
- connectivity, troubleshooting, 136–138
 - neighbor relationships, 149–157
- control information exchange, 13
- controlling
 - access to network equipment, 493–500
 - inter-area traffic, 269–270
 - redistribution, 396–397
 - with route filtering, 398

- conventional Best Effort routing, 687–688
- convergence, 51, 67, 261
 - altering with dead timer, 262
 - altering with Hello timer, 261
 - altering with SPF timer, 262–263
 - as routing protocol selection criteria, 60
 - requirements, 170–171
- cost effectiveness as network design goal, 166
- cost metric, 256–260
 - altering to control redistribution, 396
 - for external routes, 267
- creating access lists, 503
- criteria for routing protocol selection, 57
 - business considerations, 62
 - multivendor environments, 63
 - proven technologies, 63
 - standards, 63
 - operational considerations, 57
 - IP address management, 59
 - IP encapsulation support, 59
 - routing hierarchies, 58
 - supported protocols, 57
 - technical considerations, 60
 - CIDR support, 61
 - convergence, 60
 - extensibility, 62
 - load sharing, 61
 - metrics, 61–62
 - physical media support, 62
 - routing updates, 61
 - scalability, 62
 - VLSM support, 61

D

- data elements, 453
- data encryption, 478–479
- data link layer, 11
- database information, displaying, 560–562
- database synchronization (link-state database), 116, 119–120

- datagrams, fragmentation, 15
- date and time stamping SYSLOG entries, 546
- DD (database descriptor) packets, 120–122
- dead interval, 124
- dead timer, effect on convergence, 262
- debug commands
 - minimizing debug command processing
 - overload, 588
 - output, timestamping, 589
 - when to use, 587
- debug ip ospf adjacency command, 591–593
- debug ip ospf events command, 134–136, 593–595
- debug ip ospf flood command, 595–597
- debug ip ospf hello command, 597
- debug ip ospf lsa-generation command, 598–599
- debug ip ospf monitor command, 599–600
- debug ip ospf packet command, 600–601
- debug ip ospf retransmission command, 602
- debug ip ospf spf command, 602
 - external keyword, 603–604
 - inter keyword, 604–608
 - intra keyword, 608–614
- debug ip routing command, 614–615
- default routes, 50, 318–321, 347
 - configuring, 348–353
- default-metric command, 354
- demand circuits, RFC 1793, 718–719
- deploying
 - firewalls, case study, 518–529
 - neighbor router authentication, 481
 - OSPF, 187–188
- Designated Router field (Hello packets), 126
- designing OSPF networks, 164
 - addressing, 180
 - bit splitting, 184
 - discontiguous subnets, 185–186
 - naming schemes, 186
 - public versus private, 180–181
 - summarization, 181–182
 - VLSM, 185

- areas, 74, 200
 - backbone area design, 206–207
 - configuring, 285–288
 - naming, 204
 - NSSAs design, 212–214
 - route summarization, 411–413
 - standard area design, 205
 - stub area design, 207–211
 - TSA design, 212
 - tunable parameters, 202–204
- broadcast network configuration, 277
- goals of
 - adaptability, 166
 - cost effectiveness, 166
 - functionality, 165
 - manageability, 166
 - scalability, 165–166
- hardware provisioning, 186
- hierarchical networks, 71
- neighbor command, 230–231
- network management, 189
- nonbroadcast network configuration, 278
- nonbroadcast point-to-multipoint
 - configuration, 231–232
- NSSAs, configuring, 297–309
- point-to-multipoint network, 280–282
- point-to-multipoint network configuration, 279
- point-to-point network, 283–284
- protocol deployment, 187–188
- requirements, analyzing, 168–171
- scalability, 189–190
- security golden rules, 467
 - conduct cost-benefit analysis, 469
 - controlling your secrets, 470
 - documenting security plan, 468–469
 - identifying your assumptions, 470
 - know your enemy, 469
 - know your weaknesses, 472
 - limiting scope of access, 472
 - limiting your trust, 472
 - physical security, 473
 - remembering human factors, 471
- selecting network type, 276–277
- stub areas, configuring, 289–293
- summarization, private addressing
 - schemes, 424
- topologies
 - fully meshed, 171
 - hierarchical, 171–179, 191–199
- topologies, 171
 - hierarchical, 190
- TSAs, configuring, 294–295
- virtual links, 215
 - connecting to area 0, 216–217
 - example configuration, 217–230
 - partitioned area 0, 215
- development
 - of MPLS, 684–686
 - of SNMP, 447
 - of TCP/IP protocol suite, 14
- devices, 77
 - ABRs, 78
 - ASBRs, 78
 - backbone routers, 79
 - internal routers, 78
 - restricting access, 493–500
- Dijkstra's SPF algorithm, 255–256. *See also* SPF
 - convergence, 261
 - altering with dead timer, 262
 - altering with Hello timer, 261
 - altering with SPF timer, 262–263
 - cost metric, 256–260
 - DR, configuring, 266
 - loopback interfaces, configuring, 264–266
 - RID, configuring, 264
- Dijkstra, Edsger W., 64
- discontiguous subnets, 185–186
- displaying
 - buffer-logged messages, 546
 - detailed packet information, 600–601
 - external LSA information, 564–566

- flooding protocol-related events, 598–599
- free processor memory on router, 547
- Hello information, 597
- link-state database, 89–93
- log events, show logging command, 544–545
- LSA summary information, 563–564
- neighbor information, 99, 101
 - on per-interface basis, 580
- network LSA information, 566–568
- router LSA information, 568–570
- routing process information, 550
- SPF-related events, 602–614
- summary address information, 585
- topology database information, 556–560
- virtual link parameters, 583
- distance vector routing protocols, 55
 - RIPv1 characteristics, 56
- distribute lists, 398–403
 - applying, 361–363
- distributed maps, 52
- distributing default routes, 318–321
- DLC (data link control) address, 11
- DLCIs (data-link connection identifiers), 11
- DMZ (demilitarized zone), creating for private
 - address summarization, 424–425
- documentation
 - creating security plan, 468–469
 - OSPF-related RFCs, 707–722
- dotted decimal notation, 21
- Down state, 133
- down state (neighbors), 118
- DRs (designated routers), 83–84
 - configuring, 266
 - link-state ID, 106
 - network LSAs, 105
 - selection process, 84–85, 195
- DSL (digital subscriber line), 18
- DSN lookups, performing, 541
- dual-homed networks, 662
- DWDM (dense wave division multiplexing), 19
- dynamic route injection, 665

- dynamic routing protocols, 49, 656
 - IS-IS, 54
 - routing tables, 51

E

- E1 routes, 73, 267–269
- E2 routes, 73, 267–269
- EBGP (External Border Gateway Protocol), 664
- ECMP (equal cost multiple path), 315–318
- EGP (Exterior Gateway Protocol), 656
 - role in networks, 656–659
 - versus IGP, 658
- egress LSRs, 697
- EIGRP (Enhanced Interior Gateway Protocol),
 - redistribution into OSPF, 380–385
- enable secret passwords, 475
- encapsulation, 13
- establishing
 - adjacencies, 82–83
 - neighbor relationships, 81–82
- Ethernet, 16
- events, displaying information, 593–595
- example LSA operation, 113–116
- examples
 - of area 0 configuration, 217, 229–230
 - of hierarchical network design, 177–179
 - of SPF, 65–66
- exchange process, 126–127
- exchange state (neighbors), 119, 134
- exstart state (neighbors), 119, 134
- extensibility as routing protocol selection criteria, 62
- external keyword, debug ip ospf spf command,
 - 603–604
- external LSAs, displaying information, 564–566
- external routes, 71–73, 267, 347
 - E1, 269
 - E2, 269
 - redistribution into BGP, 677–679
 - summarizing, 411, 414–418

F

- Fast Ethernet, 17
- FDDI (Fiber distributed data internetworking), 17
- features of Cisco IOS Software, 188
- FEC (Forwarding Equivalency Class), 690
- fields of Hello packets, 126
- filtering
 - routes to control redistribution, 398
 - Type 7 LSAs, 306
- firewall deployment, case study, 518–529
- first octet rule, 24, 27
- flooding, 127–128
 - prevention of, 131
- flooding scope, 107
- forwarding packets, 49
- fragmentation, 15
- Frame Relay, 17
 - PVCs, clarifying in point-to-multipoint networks, 136–138
- frames, 15
- full SPF algorithm, 70
- full state (neighbors), 120, 134
- fully meshed topologies, 171
- functionality
 - as network design goal, 165
 - of SPF, 68
 - of TCP, 15

G

- gateway of last resort, 50
- generating default routes, 318–321
- get request commands, 450
- GETRESPONSE command (SNMP), 452
- Gigabit Ethernet, 17
- golden rules of redistribution, 342–343
- group pacing, 128–129
 - configuring, 130
- group-membership-LSAs, 714

H

- hardware provisioning, 186
- Hello interval, manipulating, 124
- hello packets, 122
 - displaying information, 597
 - HelloInterval field (Hello packets), 126
- Hello protocol, 123–124
 - initialization, 139, 143–148
 - operational variations, 124
 - packet format, 125–126
- Hello timer, effect on convergence, 261–262
- help menu (IOS), invoking, 550
- hidden commands
 - debug ip ospf monitor, 599–600
 - show ip ospf delete, 572–575
 - show ip ospf events, 575–578
 - show ip ospf maxage-list, 579
 - show ip ospf stat, 583–584
- hierarchical IP address structure, 27
 - classful routing, 34
 - classless routing, 34
 - effect on summarization, 420–424
 - route summarization, 33–34
 - subnet masks, 29–31
 - subnetting, 28
 - CIDR, 32, 37–41
 - restrictions, 31
 - VLSM, 31–32, 35–37, 41–42
 - supporting summarization, 406
- hierarchical routing, 58
 - adjacencies, 82
 - versus neighbors, 82–83
 - area design, 174–175
 - areas per ABR, calculating, 192
 - sizing, 191–192
 - backbone design, 173
 - bandwidth usage, 199
 - calculating neighbors per router, 194–195
 - design techniques, 71
 - example, 177–179

- LSDDB, 197–199
 - neighbor relationships, 81–82
 - displaying information, 99–101
 - network types
 - broadcast, 80
 - NBMA, 80
 - point-to-multipoint, 80
 - point-to-point, 80
 - router types, 77
 - ABRs, 78
 - ASBRs, 78
 - backbone routers, 79
 - DRs, 83–85
 - internal routers, 78
 - RIDs, 80
 - security, 199
 - selecting DR, 195
 - stub areas, 175, 177
 - host addresses, 21
-
- IBGP, 664
 - identifying state of neighbor relationships, 138
 - IETF (Internet Engineering Task Force)
 - development of SNMP, 447
 - OSPF-related RFCs, 707–722
 - ignoring MOSPF LSAs, 132
 - IGPs (interior gateway protocols), 51, 656
 - IBGP, 664
 - role in networks, 656–659
 - synchronization with BGP, 668–669
 - negative impact of, 669–671
 - versus EGPs, 658
 - implementing
 - MPLS in OSPF networks, 696–697, 700–701
 - on-demand circuits, 324
 - summarization
 - caveats, 409
 - reasons for, 408
 - rules, 409–410
 - with DMZ, 424–425
 - VLSM with summarization, 428
 - init state (neighbors), 119, 133
 - initialization, 139, 143–148
 - Integrated IS-IS (Intermediate System-to-Intermediate System), 54
 - inter keyword, debug ip ospf spf command, 604–608
 - interaction of OSPF and BGP, 665–667
 - inter-area routing, 71–73, 105, 411
 - summarization, 411
 - traffic, controlling, 269–270
 - inter-domain routing, BGP, 661
 - interior gateway protocols. *See* IGPs
 - internal routers, 78
 - internal routes, redistribution into BGP, 676–679
 - interoperability of VLSM with routing protocols, 429–430
 - intra keyword, debug ip ospf spf command, 608–614
 - intra-area routing, 71–72, 105, 411
 - ip access-list command, log keyword, 544
 - IP addressing, 21
 - allocation, 184
 - assignment and redistribution, 406
 - Class A addresses, 22
 - Class B addresses, 22
 - Class C addresses, 23
 - Class D addresses, 23
 - Class E addresses, 23
 - classful routing, 34
 - classless routing, 34
 - dotted decimal notation, 21
 - reserved addresses, 24
 - role of, 27
 - route summarization, CIDR, 33–34
 - subnet masks, 29–31
 - subnet quantities for classes, 24–26
 - subnetting, 21, 28
 - CIDR, 32, 37–41
 - restrictions, 31
 - VLSM, 31–32, 35–37, 41–42

- ip classless command, 39
- ip ospf cost command, 259
- ip ospf hello-interval command, 124
- ip ospf name-lookup command, 541
- ip ospf priority command, 82, 88
- ip ospf transmit-delay command, 133
- IP packets, data encryption, 478–479
- IP prefixes, 38
- IP routing versus MPLS, 686
- ISDN (Integrated Systems Digital Network), 18
- isolating problems with debug commands, 587
- “It Depends Rule,” 54

K-L

- keepalive messages (BGP), 663

- labels (MPLS)

- forwarding, 689
- lookup procedure, 695
- placement of, 692
- structure of MPLS, 691–692

- LANs, 16–17

- layers of OSI reference model, 7–9

- control information, 13
- lower layers, 10–12
- upper layers, 9

- LDPs (label distribution protocols), 696

- leased lines, 18

- LER (Label Edge Router), 690–691

- LIB (Label Information Base), 690

- link state acknowledgment packets, 122

- link state request packets, 122

- link state update packets, 122

- links, 103

- link-state database, 52, 67

- characteristics, 115
- DD packets, 120
- flooding, 127–128
- initialization, 143–148
- LSAs, 88–90

- synchronization, 116, 119–120

- verifying operation, 570–572

- viewing, 89–93

- link-state routing protocols, 52

- distributed maps, 52

- IS-IS, 54

- link-state database, 67

- LSAs, 88, 90

- records, 52

- viewing, 89–93

- SPF, 63

- example, 65–66

- full versus partial SPF algorithm, 70

- functionality, 68

- verifying operation of, 70

- link-state updates, flooding, 127–128

- load balancing, 315

- requirements for, 170

- load sharing as routing protocol selection criteria, 61

- loading state (neighbors), 119, 134

- log keyword (ip access-list command), 544

- log-adjacency-changes command, 549

- logging, SYSLOG, 543–546

- neighbor state changes, 548–549

- severity levels, 544

- timestamping entries, 546

- to internal buffer, 546–547

- to SYSLOG server, 547

- logical hierarchies, 58

- longest match rule, 27

- longest prefix match rule, 407

- loopback addresses, 81

- loopback interfaces

- configuring, 96, 264–266

- redistributing, 376, 378–380

- lower layers of OSI reference model, 10–12

- LSAs, 88–90, 103

- ASBR summary LSAs, 108

- autonomous system external LSAs, 109

- example, 113–116

- external, displaying information, 564–566
- flood prevention, 131
- group pacing, 128–129
 - configuring, 130
- group-membership, 714
- links, 103
- MOSPF, ignoring, 132
- network, displaying information, 566–568
- network LSAs, 105
- NSSA LSAs, 110
- Opaque, 721–722
- Opaque LSAs, 112
- packet pacing, 131
- retransmissions, altering, 132
- router, displaying information, 568–570
- router LSAs, 104–105
- summary information, displaying, 563–564
- summary LSAs, 107
- transmission delay, altering, 133
- Type 7, filtering, 306
- viewing, 89–93

LSDB

- characteristics, 197
- router CPU requirements, 199
- router memory requirements, 197–198
- shortest path algorithm, 255–256
 - convergence, 261–263
 - cost metric, 256–260
 - DR configuration, 266
 - loopback interface configuration, 264–266
 - RID configuration, 264

LSInfinity metric, 711

LSPs (label switch paths), 690

LSRs (label switch routers), 689–690, 696

M

MAC addresses, 11

manageability as network design goal, 166

managed devices (SNMP), 452

managing OSPF networks, 189

manipulating Hello interval, 124

MD5 neighbor router authentication, 483

- configuring, 483–488

- configuring on virtual link, 489–491

messages, BGP, 663

methodology of troubleshooting, 533–535

- analyzing results, 539

- creating an action plan, 539

- defining the problem, 537

- eliminating possible problems, 538

- gathering facts, 537–538

- implementing action plan, 539

- preparing for network failure, 534–535

- reiterate the process, 540

metrics, 49

- administrative distance, 341–342

- altering, 313–314

- as routing protocol selection criteria, 61–62

- assigning to redistributed protocols, 354–358

- cost, 256–260

- altering to control redistribution, 396

- for external routes, 267

- LSInfinity, 711

MIBs, 453

- Cisco MIBs, 459–461

- data elements, 453

- OIDs, 453

- OSPF-related, 462

- proprietary, 450

- RFC 1252, 711

- RFC 1850, 719

monitoring OSPF operation, 541

- logging neighbor changes, 548–549

- system logging, 543–547

Moore's law, 5

Moore, Gordon, 5

MOSPF

- LSAs, ignoring, 132

- RFC 1584, 713

- RFC 1585, 714

MPLS (MultiProtocol Label Switching)

- benefits of, 686
 - configuring in OSPF networks, 696–697, 700–701
 - development of, 684–686
 - label forwarding, 689
 - label lookup procedure, 695
 - label placement, 692
 - label structure, 691–692
 - LSRs, 696
 - overview, 689
 - router functions, 690
 - terminology, 690–691
 - traffic engineering, 693–694
 - verifying operation, 701–703
 - versus ATM switching, 687
 - versus IP routing, 686
 - multivendor environments as routing protocol
 - selection criteria, 63
 - mutual redistribution, 360. *See also* route tagging
 - between EIGRP and OSPF, 384–385
 - between RIP and OSPF, 375–376, 392
- ## N
-
- naming areas, 204
 - naming schemes, 186
 - NBMA networks, 80
 - OSPF over Frame Relay, 715
 - necessity of OSI reference model, 6
 - Neighbor field (Hello packets), 126
 - neighbor relationships, 81–82. *See also* adjacencies
 - 2-way state, 119
 - troubleshooting, 156–157
 - attempt state, 118
 - displaying information, 99–101
 - down state, 118
 - exchange state, 119
 - exstart state, 119
 - flooding process, 127–128
 - full state, 120
 - Hello process, 123–124
 - Hello protocol
 - operational variations, 124
 - packet format, 125–126
 - init state, 119
 - troubleshooting, 150–156
 - loading state, 119
 - states of, 133–134
 - identifying, 138
 - troubleshooting, 149–150
 - neighbor router authentication, 480
 - benefits of, 480
 - configuring, 483–488
 - configuring on virtual links, 489–491
 - deploying, 481
 - MD5, 483
 - plaintext, 482
 - neighbors
 - BGP, 662
 - state changes, logging, 548–549
 - network addresses, 21
 - network command, 272
 - network design, 164
 - addressing, 180
 - bit splitting, 184
 - discontiguous subnets, 185–186
 - naming schemes, 186
 - public versus private, 180–181
 - summarization, 181–182
 - VLSM, 185
 - areas, 200
 - backbone design, 206–207
 - configuring, 285–288
 - naming, 204
 - NSSAs design, 212–214
 - standard design, 205
 - stub area design, 207–211
 - TSA design, 212
 - tunable parameters, 202–204
 - broadcast network configuration, 277

- goals of
 - adaptability, 166
 - cost effectiveness, 166
 - functionality, 165
 - manageability, 166
 - scalability, 165–166
- hardware provisioning, 186
- neighbor command, 230–231
- network management, 189
- nonbroadcast network configuration, 278
- nonbroadcast point-to-multipoint
 - configuration, 231–232
- NSSAs, configuring, 297–309
- point-to-multipoint network configuration, 279–282
- point-to-point network configuration, 283–284
- protocol deployment, 187–188
- requirements, analyzing, 168–171
- scalability, 189–190
- selecting network type, 276–277
- stub areas, configuring, 289–293
- topologies
 - fully meshed, 171
 - hierarchical, 171–179, 190–199
- TSAAs, configuring, 294–295
- virtual links, 215
 - connecting to area 0, 216–217
 - example configuration, 217–222, 229–230
 - partitioned area 0, 215
- network elements, 452
- network layer protocols, 11
 - IP, 16
- network LSAs, 105
 - displaying information, 566–568
- network management, 442
 - SNMP
 - access lists, 462
 - agents, 452
 - Cisco MIBs, 459, 461
 - community strings, 462, 477–478
 - components of, 447–449
 - development of, 447
 - get request command, 450
 - managed devices, 452
 - MIBs, 453
 - NMSs, 451
 - system request events, 456, 459
 - versions of, 450
 - tools
 - Cisco ConfigMaker, 446
 - CiscoView, 444–445
 - CiscoWorks, 445
- Network Mask field (Hello packets), 126
- network security, 466
 - assessing need for, 467
 - Cisco IOS password encryption, 474
 - data encryption, 478–479
 - golden rules
 - controlling your secrets, 470
 - know your weaknesses, 472
 - limiting scope of access, 472
 - limiting your trust, 472
 - physical security, 473
 - remembering human factors, 471
 - user passwords, 475
 - backup configuration files, 476
 - enable secret passwords, 475
- networking
 - IP addressing, 21
 - CIDR, 32, 37–41
 - Class A addresses, 22
 - Class B addresses, 22
 - Class C addresses, 23
 - Class D addresses, 23
 - Class E addresses, 23
 - classful routing, 34
 - classless routing, 34
 - dotted decimal notation, 21
 - reserved addresses, 24
 - role of, 27

- route summarization, 33–34
 - subnet masks, 29–31
 - subnet quantities for classes, 24–26
 - subnets, 21
 - subnetting, 28, 31
 - VLSM, 31–32, 35–37, 41–42
- LANs, 16–17
- OSI reference model, 6
 - control information, 13
 - layers of, 7–9
 - lower layers, 10–12
 - need for, 6
 - upper layers, 9
- WANs, 17–20
- network security golden rules, 467
 - conducting cost-benefit analysis, 469
 - documenting security plan, 468–469
 - identifying your assumptions, 470
 - know your enemy, 469
- next-hop addresses
 - longest prefix match rule, 407
 - reachability, 671–673
- next-hop-self command, 673
- NMF (Network Management Framework), SNMP, 447
- NMSs (network management systems), 451
- nonbroadcast networks, configuring, 278–279
- nonbroadcast point-to-multipoint interface
 - configuration, 231–232
- normal OSPF areas
 - configuring, 285–288
 - NSSAs, configuring, 297–309
 - stub areas, configuring, 289–293
 - summarization, configuring, 309–313
 - TSAs, configuring, 294–295
- NSSA LSAs, 110
- NSSA-external routes, redistribution into BGP, 679
- NSSAs
 - configuring, 297–309
 - designing, 212–214

- RFC 1587, 716–717
 - Type 7 LSA filtering, 306
- null authentication on virtual links, 492

O

- obtaining external routing information, 73
- OIDs (object identifiers), 453
- on-demand circuits, 322–324
 - configuring, 324–328
 - implementing, 324
- Opaque LSAs, 721–722
- Opaque LSAs, 112
- operation of OSPF
 - monitoring, 541
 - system logging, 543–546
 - logging neighbor changes, 548–549
 - logging to internal buffer, 546–547
 - logging to SYSLOG server, 547
 - severity levels, 544
 - timestamping entries, 546
- operational characteristics of OSPF, 69
- OSI (open system interconnection) reference model, 6
 - layers of, 7–9
 - control information, 13
 - lower layers, 10–12
 - need for, 6
 - relationship to TCP/IP protocol suite, 14
 - upper layers, 9

P

- Packet length field (Hello packets), 125
- packet pacing, 131
 - displaying queued LSAs, 579
- packets, 15
 - DD, 120, 122
 - displaying detailed information, 600–601
 - encapsulation, 13

- forwarding, 49
 - hello, 122
 - format, 125–126
 - initialization process, 139, 143–148
 - link state acknowledgment, 122
 - link-state requests, 122
 - link-state updates, 122
 - flooding, 127–128
 - LSAs, 103
 - ASBR summary LSAs, 108
 - autonomous system external LSAs, 109
 - example, 113–116
 - group pacing, 128–130
 - group-membership, 714
 - network LSAs, 105
 - NSSA LSAs, 110
 - Opaque, 721–722
 - Opaque LSAs, 112
 - packet pacing, 131
 - router LSAs, 104–105
 - summary LSAs, 107
 - partial SPF algorithm, 70
 - passive interfaces, 321–322
 - path vector, 663
 - payload, 13
 - peer routers, 662
 - penultimate hops, 697
 - physical media support as routing protocol selection
 - criteria, 62
 - pinging networks reachable via summary
 - entries, 418
 - placement
 - of static routes, 50
 - of MPLS labels, 692
 - plaintext neighbor router authentication, 482
 - point-to-multipoint networks, 80
 - clarifying PVCs, 136–138
 - point-to-point networks, 80
 - policy-based routing, 663
 - preparing for network failure, 534–535
 - prepending, 664
 - presentation layer, 10
 - preventing
 - LSA flooding, 131
 - routing loops, 364
 - with route maps, 385–388
 - with route tagging, 388–390
 - routing loops with BGP, 663
 - private addressing, 180–181
 - private addressing schemes, summarizing, 424
 - with DMZ, 424–425
 - proactive network management, 443
 - problem-solving process
 - analyzing results, 539
 - creating an action plan, 539
 - defining the problem, 537
 - eliminating possible problems, 538
 - gathering facts, 537–538
 - implementing action plan, 539
 - reiterate the process, 540
 - processors, Moore’s Law, 5
 - proprietary MIBs, 450
 - protocols, 14
 - proven technologies as routing protocol selection
 - criteria, 63
 - provisioning hardware, 186
 - proxy agents, 452
 - Proxy-PAR, RFC 2844, 722
 - public addressing, 180–181
 - PVCs (permanent virtual circuits)
 - clarifying in a point-to-multipoint network, 136–138
-

R

- reachability, BGP recursive lookup, 671–673
- reactive network management, 443
- reasons for implementing summarization, 408

- recursive routing, 671–673
- redistribute command, 343–344, 354
- redistribution, 360, 405
 - administrative distances, 341–342
 - between EIGRP and OSPF, 380–383
 - between RIP and OSPF, 366–374
 - route tagging, 390–391
 - configuring, 343–344
 - on connected routes, 376–380
 - controlling, 396–397
 - with route filtering, 398
 - default routes, 347
 - configuring, 348–353
 - distribute lists, 398–403
 - applying, 361–363
 - external routes, 347
 - into BGP, 673–676
 - external routes, 677–679
 - internal routes, 676–677
 - NSSA-external routes, 679
 - loops, avoiding, 364
 - metrics, assigning, 354–358
 - mutual redistribution, 360
 - between EIGRP and OSPF, 384–385
 - between RIP and OSPF, 392
 - redistribution between RIP and OSPF, 375–376
 - reasons for, 340
 - route maps, 344, 365
 - preventing routing loops, 385–388
 - route tagging, 393–395
 - preventing routing loops, 388–390
 - rules, 342–343
 - summary addresses, displaying information, 585
 - versus summarization, 339
- redistribution command, 78, 345–346
- reference-bandwidth command, 259
- requirements of network design, defining, 169–171
- reserved IP addresses, 24
- resetting OSPF processes, 586
- restricting access to network equipment, 493–500
- restrictions
 - for subnetting, 31
 - of stub area use, 75
- RFCs
 - OSPF-related, 707–722
 - RFC 1131, 709
 - RFC 1245, 709
 - RFC 1246, 710–711
 - RFC 1247, 711
 - RFC 1248, 711
 - RFC 1252, 711
 - RFC 1253, 712
 - RFC 1364, 712
 - RFC 1370, 712
 - RFC 1371, 713
 - RFC 1403, 713
 - RFC 1583, 713
 - RFC 1584, 713
 - RFC 1585, 714
 - RFC 1586, 715
 - RFC 1587, 716–717
 - RFC 1745, 718
 - RFC 1765, 718
 - RFC 1793, 718–719
 - RFC 1850, 719
 - RFC 2178, 719
 - RFC 2328, 719–721
 - RFC 2370, 721–722
 - RFC 2676, 722
 - RFC 2740, 722
 - RFC 2844, 722
 - website, 48
- RIDs (router IDs), 80
 - configuring, 264
 - establishing neighbor relationships, 81–82
- RIP (Routing Information Protocol)
 - converting clouds to OSPF areas, 372
 - redistribution into OSPF, 366–374
 - mutual redistribution, 392
 - route tagging, 390–391

- RIPE (Réseaux IP Européens), 21, 71
 - RIPv1, characteristics, 56
 - role of IP addresses, 27
 - route aggregation, 42
 - route maps, 365
 - configuring, 344
 - preventing routing loops, 385–388
 - route oscillation, 363
 - route summarization, 33–34
 - route tagging, 393–395
 - preventing routing loops, 388–390
 - redistribution between RIP and OSPF, 390–391
 - route types, external, 267–269
 - routed protocols, 49
 - Router ID field (Hello packets), 126
 - router LSAs, 104–105
 - displaying information, 568–570
 - router priority, 88
 - RouterDeadInterval field (Hello packets), 126
 - routers
 - adding to networks, 85–88
 - deploying, case study, 518–529
 - DRs 83–84
 - configuring, 266
 - selection process, 84–85
 - gateway of last resort, 50
 - MPLS, 690
 - neighbor relationships, Hello process, 123–126
 - routing loops, preventing, 364
 - on summarized routes, 419
 - with BGP, 663
 - with route maps, 385–388
 - with route tagging, 388–390
 - routing protocols, 48
 - distance vector, 55
 - RIPv1, 56
 - dynamic, 49
 - EGPs, 656
 - role in networks, 656–659
 - IGPs, 656
 - role in networks, 656–659
 - interoperability with VLSM, 429–430
 - link-state, 52
 - distributed maps, 52
 - Integrated IS-IS, 54
 - link-state database, 67
 - SPF, 63–70
 - metrics, 49
 - selecting, 57
 - business considerations, 62–63
 - operational considerations, 57–59
 - technical considerations, 60–62
 - routing tables
 - convergence, 51
 - recursive lookup, 671–673
 - summarization, 408
 - caveats, 409
 - configurations, 411
 - rules, 409–410
 - troubleshooting, 410
 - routing types
 - external, 73
 - inter-area, 72–73
 - intra-area, 72
 - routing updates as routing protocol selection criteria, 61
 - Rtr Pri field (Hello packets), 126
 - rules
 - of redistribution, 342–343
 - of summarization, 409–410
-
- ## S
- scalability, 189–190
 - as network design goal, 165–166
 - as routing protocol selection criteria, 62
 - Secure IOS template case study, 506–517

- security, 466
 - access lists
 - applying to interfaces, 504
 - configuring, 501–502
 - creating, 503
 - assessing need for, 467
 - authentication, 479
 - on virtual links, troubleshooting, 492
 - user authentication, 504–505
 - Cisco IOS password encryption, 474
 - data encryption, 478–479
 - golden rules, 467
 - controlling your secrets, 470
 - cost-benefit analysis, 469
 - documenting security plan, 468–469
 - identifying your assumptions, 470
 - know your enemy, 469
 - know your weaknesses, 472
 - limiting scope of access, 472
 - limiting your trust, 472
 - physical security, 473
 - remembering human factors, 471
 - neighbor router authentication
 - benefits of, 480
 - configuring, 483–491
 - deploying, 481
 - MD5, 483
 - plaintext, 482
 - null authentication, configuring, 492
 - restricting access to network devices, 493–500
 - SNMP community strings, configuring, 477–478
 - user passwords, 475
 - backup configuration files, 476
 - enable secret passwords, 475
- segments, 15
- selecting
 - DRs, 84–85, 195
 - OSPF network type, 276–277
 - broadcast, 277
 - nonbroadcast, 278
 - point-to-multipoint, 279–282
 - point-to-point, 283–284
 - routing protocols, 57
 - business considerations, 62–63
 - operational considerations, 57–59
 - technical considerations, 60–62
- session layer, 10
- SETREQUEST command, 451
- severity levels of logging messages, 544
- SGMP (Simple Gateway Monitoring Protocol), 447
- shortest-path tree, building, 93–95
- show frame-relay map command, 137
- show ip ospf border-routers command, 555–556
- show ip ospf command, 97, 550–553
- show ip ospf database asbr-summary command, 560–562
- show ip ospf database command, 100, 556–560
- show ip ospf database database-summary command, 563–564
- show ip ospf database external command, 564–566
- show ip ospf database network command, 566–568
- show ip ospf database router command, 568–570
- show ip ospf database summary command, 570–572
- show ip ospf delete command, 572–575
- show ip ospf events command, 575–578
- show ip ospf flood-list command, 579
- show ip ospf interface command, 553–555
- show ip ospf maxage-list command, 579
- show ip ospf neighbor command, 98, 138, 580–581
- show ip ospf neighbor detail, 99
- show ip ospf neighbor detail command, 99, 582
- show ip ospf stat command, 583–584
- show ip ospf summary-address command, 585
- show ip ospf virtual-links command, 583
- show ip route command, 416
- show logging command, 544–545
- show memory command, 547
- show mpls forwarding-table command, 702

SNMP (Simple Network Management Protocol)

- access lists, 462
- agents, 452
- community strings, 462
 - configuring, 477–478
- components of, 447–449
- development of, 447
- get request command, 450
- managed devices, 452
- MIBs, 453
 - Cisco MIBs, 459, 461
 - OIDs, 453
 - OSPF-related, 462
 - RFC 1252, 711
 - RFC 1850, 719
- NMSs, 451
- system request events, 456, 459
- versions of, 450

software, NMSs, 451

SONET, 18

SPF (shortest path first) algorithms, 52, 255–256

- candidate database, 93
- convergence, 261
 - altering with dead timer, 262
 - altering with Hello timer, 261
 - altering with SPF timer, 262–263
- cost metric, 256–260
- Dijkstra, Edsger W., 65
- DR, configuring, 266
- example, 65–66
- full versus partial SPF algorithm, 70
- functionality, 68
- loopback interfaces, configuring, 264–266
- RID, configuring, 264
- shortest-path tree, building, 93–95
- verifying operation, 70

SPF timer, effect on convergence, 262–263

standard area design, 205

standards as routing protocol selection criteria, 63

states of link-state database synchronization, 118

states of neighbor relationships, 133–134

static route injection, 665

static routing, 50, 655

Stevens, Richard, 15

structure of MPLS labels, 691–692

stub area

stub areas, 75

- characteristics, 75

- configuring, 208–211, 289–293

- designing, 207–211

- hierarchical network design, 175–177

- restrictions, 75

- totally stubby areas, 76

stub networks, 50

subnet masks, 29–31

subnetting, 11, 21, 28

CIDR

- design guidelines, 37

- manual IP prefix computation, 40–41

- network validation, 37–38

- translation table, 39–40

quantities for network classes, 24–26

restrictions, 31

VLSM, 31–32, 35–36, 41–42

- design guidelines, 36–37

- interoperability with routing protocols, 429–430

- summarized routes, 420–424

- summarizing routes, 426–428

suboptimal routing and summarization, 409

summarization, 73, 181–182. *See also* redistribution

- and IP address assignment, 406

- area configuration, 309–313

- route design considerations, 411–413

- benefits of, 408

- caveats, 409

- configuring, 411

- effects on routing tables, 418–419

- external routes, configuring, 414–418

- hierarchical addressing schemes, 406

- implementing, rules, 409–410
 - inter-area routes, 411
 - longest prefix match rule, 407
 - routing loops, preventing, 419
 - subnetting, 420–424
 - troubleshooting, 410
 - with private addressing schemes, 424
 - with VLSM, 426
 - caveats, 426–428
 - implementing, 428
 - summary LSAs, 107
 - summary-address command, configuring external route summarization, 416–417
 - supernetting, 33 38
 - suppressing syslog message transmission, 132
 - symptoms of internetwork failure, 535
 - synchronization
 - BGP, 668–671
 - flooding process, 127–128
 - of link-state database, 116, 119–120
 - syntax
 - redistribute command, 344
 - redistribution command, 345–346
 - system logging
 - configuring, 543–546
 - data and time stamping, 546
 - logging neighbor changes, 548–549
 - logging to internal buffer, 546–547
 - logging to SYSLOG server, 547
 - performing, 543–546
 - severity levels, 544
 - timestamping entries, 546
 - system request events (SNMP), 456, 459
- T**
-
- tag swapping, verifying operation, 701–703
 - tagging routes, 393–395
 - TCP/IP protocol suite, 14
 - development of, 14
 - IP, 16
 - OSI compliance, 14
 - segments, 15
 - TCP, 15
 - upper layers, 15
 - timers, effect on convergence
 - dead timer, 262
 - Hello, 261
 - SPF timers, 262–263
 - timestamping
 - debug command output, 589
 - SYSLOG entries, 546
 - Token Ring, 17
 - topological database, 90
 - topologies, 171
 - convergence, 51, 67, 261
 - altering with dead timer, 262
 - altering with Hello timer, 261
 - altering with SPF timer, 262–263
 - as routing protocol selection criteria, 60
 - fully meshed, 171
 - hierarchical, 171–173, 190
 - area design, 174–175
 - area sizing, 191–192
 - backbone design, 173
 - bandwidth usage, 199
 - calculating areas per ABR, 192
 - calculating neighbors per router, 194–195
 - example, 177–179
 - LSDB, 197–199
 - security, 199
 - selecting DR, 195
 - stub area design, 175–177
 - LANs, 16–17
 - link-state database, 67
 - WANs, 17–20
 - topology database information, displaying, 556–560
 - totally stubby areas, 76

- traffic, load balancing, 315
- traffic engineering, 684
 - MPLS, 689, 693–694
 - label forwarding, 689
 - label lookup procedure, 695
 - router functions, 690
 - terminology, 690–691
- traffic-filtering, 501
- transparent network communication, 21
- transport layer protocols 10
 - TCP, 15
- TRAP command (SNMP), 452
- troubleshooting. *See also* troubleshooting
 - commands
 - adjacencies, 136–138
 - BGP, case study, 680–683
 - methodology, 533–535
 - analyzing results, 539
 - creating an action plan, 539
 - defining the problem, 537
 - eliminating possible problems, 538
 - gathering facts, 537–538
 - implementing action plan, 539
 - preparing for network failure, 534–535
 - reiterate the process, 540
 - neighbor relationships, 149–150
 - neighbor stuck in 2-way state, 156–157
 - neighbor stuck in exchange state, 151–156
 - neighbor stuck in exstart state, 151–156
 - neighbor stuck in init state, 150–151
 - summarization, 410
 - virtual links, authentication, 492
 - troubleshooting commands
 - clear ip ospf, 585
 - clear ip ospf counters, 585–586
 - clear ip ospf process, 586
 - clear ip ospf redistribution, 587
 - show ip ospf, 550–553
 - show ip ospf border-routers, 555–556
 - show ip ospf database, 556–560
 - show ip ospf database asbr-summary, 560–562
 - show ip ospf database external, 564–566
 - show ip ospf database network, 566–568
 - show ip ospf database router, 568–570
 - show ip ospf database summary, 570–572
 - show ip ospf delete, 572–575
 - show ip ospf events, 575–578
 - show ip ospf flood-list, 579
 - show ip ospf interface, 553–555
 - show ip ospf maxage-list, 579
 - show ip ospf neighbor, 580–581
 - show ip ospf neighbor detail, 582
 - show ip ospf stat, 583–584
 - show ip ospf summary-address, 585
 - show ip ospf virtual-links, 583
- TSAAs
 - configuring, 294–295
 - designing, 212
- tuning OSPF
 - administrative distance, 313–314
 - default routes, 318–321
 - ECMP, 315–318
 - load balancing, 315
 - passive interfaces, 321–322
- two-way communication, exchange process, 126–127
- Type 1 LSAs, 104
- Type 1 routes, 267
- Type 2 LSAs, 105
- Type 2 routes, 267
- Type 3 LSAs, 107
- Type 4 LSAs, 108
- Type 5 LSAs, 109
- Type 6 LSAs, 110
- Type 7 LSAs, filtering, 306
- Type 9 LSAs, 112
- Type 10 LSAs, 113
- Type 11 LSAs, 113
- Type E1 routes, 347
- Type E2 routes, 347
- types of LSAs, 103

- ASBR summary LSAs, 108
- autonomous system external LSAs, 109
- network LSAs, 105
- NSSA LSAs, 110
- opaque LSAs, 112
- router LSAs, 104–105
- summary LSAs, 107
- types of OSPF routers, 77
 - ABRs, 78
 - ASBRs, 78
 - backbone routers, 79
 - internal routers, 78

U

- unauthorized use notifications, setting up, 477
- upper layers
 - of TCP/IP protocol suite, 15
 - of OSI reference model, 9
- user authentication, 504–505
 - configuring, 504–505
- user passwords
 - backup configuration files, 476
 - enable secret passwords, 475
 - security, 475

V-Z

- verifying
 - link-state database operation, 570–572
 - MPLS operation, 701–703
 - OSPF operation, 97–99
 - summarization, 410
- verifying SPF operation, 70
- Version # field (Hello packets), 125
- versions of SNMP, 450
- viewing link-state database, 89–93
- virtual links, 215
 - authentication, troubleshooting, 492
 - connecting to area 0, 216–217

- MD5 authentication, configuring, 489–491
- null authentication, 492
- parameters, displaying information, 583
- partitioned area 0, 215
- VLSM (variable-length subnet masking), 41–42, 185
 - as routing protocol selection criteria, 61
 - design guidelines, 36–37
 - effect on summarization, 420–424
 - interoperability with routing protocols, 429–430
 - need for, 31–36
 - restrictions, 31
 - route aggregation, 42
 - summarizing routes, 426–428

- WANs, 17–20

- WDM (wave division multiplexing), 19
- websites, RFCs, 48