



## Numerics

---

- 802.1q VLAN specification, running MPLS/VPN, 357

## A

---

- address families
  - routing context configuration, 209–211
  - VPN-IPv4, configuring, 208
- address space, overlapping, 164
- address families, 207
- advanced MPLS, troubleshooting, 115–118
- advertisements
  - AS-override, 196
  - extended community attribute, 209
  - PE routers, requirements for, 183
- aggregates, 29
  - penultimate hop popping, 41
- allocating labels
  - across ATM LSR domains, 56–61
  - distribution methods, 34–36
  - independent control, 57
  - VC merge, 58–61
- AllowAS-in feature, deploying, 264–266
- any-to-any connectivity
  - Intranet topology, 184–185
  - extranet topology, 153
- applications
  - hosting, 258
  - MPLS, control protocols, 19–20
- architecture
  - cell-mode MPLS, control-plane connectivity, 51–53
  - Edge-LSRs, 18
  - MPLS/VPN, 13, 161–162
    - Extended Communities ORF-type capability, 219
    - FECs, 16
    - inter-PE router routing, 172–173
    - Intranet topology, 184–185
    - overlapping addresses, 190
    - route distinguishers, 173
      - scalability, 173
      - SOO, 193, 196
  - VPNs
    - route targets, 171–172
    - sites, 169
- area 0 (OSPF), PE-to-CE connectivity, 231, 238, 240–242
- arguments, tag-switching advertise-tags command, 75
- AS Override, 250–252
- assigning
  - interfaces to VRFs, 204
  - labels. *See* bindings
  - loopback addresses to PE routers, 348
  - route distinguishers to VRFs, 411–412
  - unique numbers to route distinguishers, 191–192
- associating VRF with global routing table, 330–331, 334
- ATM (Asynchronous Transfer Mode)
  - backbone networks
    - migration to cell-mode MPLS, 108–110
    - migration to Frame-mode MPLS, 106–108
    - service provider, convergence, 274
  - cell-mode MPLS, 49, 69
    - control-plane connectivity, 52–53
    - limitations, 50
  - frame-mode MPLS, 67–69
  - heterogeneous MPLS-mode operation, 69
  - Layer 3 lookup, 50
  - LSRs, 50
    - convergence, 61–62
    - domains, 50
    - edge LSRs, 13–15, 50
    - IP connectivity, 51
    - labeled packet forwarding, 55–56
    - loopback interfaces, 53
  - switches
    - control-plane implementation, 54
    - ordered control, 57
  - VCs, 49
- attributes (BGP), 187
  - community, removing, 371
  - extended community, 193
    - advertising, 209

- format, 198
- OSPF route propagation, 238
- route target, 194–195
- MP\_REACH\_NLRI, 205–206
- MP\_UNREACH\_NLRI, 205–206
- automatic route filtering, 263
  - PE routers, 213–214
- Autonomous System Number, assigning to route distinguishers, 191
- autonomous systems, sub AS label
  - exchange, 309avoiding
  - routing loops in VPNs, 266
  - summarization on PE routers, 352

## B

---

- backbone
  - migration to Frame-mode MPLS, 97–99
  - MPLS/VPN
    - customer access, 225–226
    - deploying BGP, 344–355
    - OSPF route propagation, 235–238
    - route advertisements, 280–285
    - traceroute, 371–374
  - reachability, 342
  - service provider, convergence, 273–274
- best path selection, reflected routes, 291
- BGP (Border Gateway Protocol), 277
  - attributes, 187
  - community attribute, removing, 371
  - confederations
    - deploying, 300–305
    - multiple IGP environment, 306–309
    - single IGP environment, 305–306
  - deploying in MPLS/VPN backbone, 344–355
  - export policies, configuring, 195–196
  - extended community attribute, 193
    - format, 198
    - OSPF route propagation, 238
    - route target, 194–195
  - import policies, configuring, 195–196
  - internal sessions, 204
  - label bindings, 34
  - next hops, summarizing, 352–353
  - next-hop forwarding, 345–348
  - OPEN messages, Capabilities parameter, 205
  - PE-to-CE connectivity, 227–229
  - peering

- group leader selection, 345
- structure, 101–103
- route reflectors, hierarchical structure, 288–289
- Route Refresh, 215–217
- scanner process, 278–279
- selection process, 263
- standard community extension, filtering on PE routers, 294–297
- unnecessary sessions, removing, 105
- bindings, 12, 34
  - liberal retention mode, 273
- Bottom of Stack bit, 27
- BPX switches, LSC (Label Switch Controller), 54
- business problem-based VPN classification, 132–134

## C

---

- calculating VCs per full-mesh networks, 148
- Capabilities parameter (OPEN messages), 205
- carrier's carrier MPLS/VPNs, 378–380
  - external routes, 379
  - internal routes, 379
  - topologies, 381–392
- case studies
  - migration
    - ATM backbone to cell-mode MPLS, 108–110
    - ATM backbone to Frame-mode MPLS, 106–107
    - backbone network to Frame-mode MPLS, 97–99
    - CEF requirements, 100
    - internal links to MPLS, 103–105
    - premigration infrastructure checks, 99–100
    - MPLS/VPN Intranet service, 184–185
    - SuperCom network VPNs, 162–164
    - VRF configuration, 186
- CE (Customer Edge) devices, 131
  - PE-to-CE connectivity, provisioning, 311–312
  - tunneling to PE routers, 355
- CEF (Cisco Express Forwarding) switching
  - assigning interfaces to VRFs, 204
  - interface-level, troubleshooting, 122–124
  - verifying, 429–430

- cell-mode MPLS, 49
  - ATM LSRs, 50
    - loopback interfaces, 53
  - control-plane connectivity, 52–53
    - implementing in ATM switches, 54
  - IP connectivity, 51
  - loop prevention, 82–87
  - migration from ATM backbone networks, 108–110
    - over ATM, 69
- central services topology, 152
  - VPNs, 258–261
- central sites
  - extranet VPN connectivity, 256
  - IP tunneling, migration to VPN/MPLS, 415–418
- CE-to-PE links
  - troubleshooting, 346
  - verifying routing exchange, 432–434
- Cisco MPLS, 79
- Cisco Secure Integrated Software, 315
- Cisco VPN Solutions Centre, 358
- classification of VPNs
  - business problem-based, 132–134
  - implementation models, 135–143
  - topologies, 144–157
- class-of-service information, 26
- clear ip bgp command, 217
- clusters, route reflection between PE routers, 292
- commands
  - clear ip bgp, 217
  - debug tag tdp transport, 31
  - ip ospf network point-to-point, 348
  - ip route, 201
  - ip vrf, 186
  - ip vrf forwarding, 204
  - maximum routes, 311
  - mpls ip, 31
  - mpls label-distribution, 31
  - neighbor, 208, 347
  - neighbor advertisement-interval, 277
  - neighbor maximum-prefix, 311
  - network, 202
  - next-hop-self, 309, 344–346
  - ping, 426–428
  - propagate-ttl, 373
  - redistribute, 201, 235
  - redistribute bgp metric transparent, 203
  - route-maps, 201
  - router ospf, 233
  - route-target, 195
  - route-target export, 371
  - rr-group, 219
  - set extcommunity, 435
  - set extcommunity rt, 371
  - show atm vc, 54
  - show cef interface, 429
  - show ip bgp neighbor, 217, 283–284, 345
  - show ip ospf, 234
  - show ip route vrf, 434
  - show ip vrf detail, 435
  - show mpls forwarding-table, 116–117
  - show tag tdp neighbor, 33
  - show tag-switching forwarding-table, 220
  - show tag-switching tdp bindings, 36
  - show tag-switching tdp discovery, 121
  - show tag-switching tdp neighbor, 67, 75
  - tag tdp router-id, 33
  - tag-switching, MPLS equivalents, 461–462
  - tag-switching advertise-tags, 75–76
  - tag-switching ip, 31
  - tag-switching mtu, 80
- common services VPNs, route distinguishers, 191
- community attribute (BGP)
  - comparing standard and extended, 364–366
  - removing, 371
- comparing
  - extended and standard BGP communities, 364–366
  - IP routing and IP forwarding tables, 166
  - VPN peer-to-peer models, 143
- complexity of modern VPNs, 132
- confederations
  - configuring, 302–305
  - deploying, 300–305
    - multiple IGP environment, 306–309
    - single IGP environment, 305–306
  - designing IGP, 302

- configuring
  - AS Override, 251–252
  - ATM LSRs, loopback interfaces, 53
  - BGP, import/export policies, 195–196
  - confederations, 302–305
  - Internet access, 312–313
    - dynamic default routing, 328–334
    - performing additional global routing table lookup, 334
    - PE-to-CE connectivity, 320–328
    - separate service provider, 335
    - static default routing, 315–320
  - MP-iBGP, 207–209
  - MPLS/VPN, route reflectors, 219
  - PE routers
    - loopback addresses, 348
    - MP-iBGP, 420
    - summarization on loopback addresses, 349–354
  - PE-CE links, 200
  - route distinguishers, 191–192
  - route reflectors, ORF capability, 299–300
  - SOO extended community, 197–198
  - VRFs, 186
    - import/export policies, 195–196
- connectivity, 414
  - cell-mode MPLS control plane, 51
  - central services topology (VPNs), requirements, 258
  - CE-to-PE links, troubleshooting, 346
  - control-plane
    - in Cisco IOS software, 52–53
  - end-to-end LSPs, 123
  - Internet access
    - configuring, 312–313
    - dynamic default routing, 328–334
    - firewalls, 313–315
    - performing additional global routing table lookup, 334
    - static default routing, 315–320
    - through separate service provider, 335
  - leased lines, 130
  - PE-to-CE, 200–203, 225
    - BGP-4, 227–229
    - convergence, 276–277
    - OSPF, 230–231, 238–242
    - OSPF without site area 0, 242–243
    - provisioning, 311–312
    - redistribution, 226
    - running separate BGP sessions, 320–321
    - tunneling, 355
    - VPN customer network topologies, 244–248
    - VRFs, separating, 232–235
  - PE-to-CE routing exchange
    - verifying, 432–434
  - pinging between CE routers, 426–428
  - route redistribution, verifying, 434–435
  - solutions
    - hierarchical VPNs, 392–394
    - inter-provider VPNs, 394–403
  - SuperCom network example, requirements, 167–169
  - VPNs, verifying, 428–429
- conservative retention mode, 35
- control modes, 73
- control plane, 12
  - cell-mode MPLS, IP connectivity, 51
  - Cisco IOS software, 52–53
  - implementing in ATM switches, 54
  - troubleshooting, 118–121
- control protocols
  - MPLS applications, 19–20
  - MPLSC, 27convergence, 271
  - ATM LSR domains, 61–62
- convergence, 271
  - ATM LSR domains, 61–62
  - between VPN sites, 275–280
  - frame-mode MPLS, 37–39
  - within service provider backbone, 273–274
- Core LSRs, 25
- core redundancy, WANs, 7
- CPE (Customer Premises Equipment) devices, 131
  - VCS, frame-mode MPLS operation over Frame Relay, 65–67
- customer links, network management, 358–367
  - export maps, 368–371
  - importing selected customer routes, 359–363
  - route filtering, 363–367
- customer routes
  - advertising, requirements, 183
  - IGP, migrating to BGP, 339–344
  - next-hop forwarding, 345–348

## D

---

- data plane, 12
  - cell-mode, loop prevention, 86–88
  - MPLS/VPN
    - packet forwarding, 220–221
    - troubleshooting, 122–124
- datagrams, Maximum Intially Labeled IP Datagram Size, 79
- debug tag tdp transport command, 31
- dedicated router approach, peer-to-peer VPN model, 141–142
- default behavior, ATM service provider
  - backbone, 274
- defining VPNs, IP tunneling migration case study, 410
- delays, convergence over ATM LSR domains, 61–62
- deploying
  - AllowAS-in, 264–266
  - BGP
    - confederations, 300–305
    - in MPLS/VPN backbone, 344–355
  - confederations
    - multiple IGP environment, 306–309
    - single IGP environment, 305–306
  - MPLS/VPN on LAN interfaces, 355–357
  - PBR, 10
- designing frame-mode MPLS domains,
  - convergence, 37–39
- detecting routing loops
  - cell-mode MPLS, 82–88
  - frame-mode MPLS, 81–82
- devices
  - CE, 131
  - P devices, 131
  - PE (Provider Edge), 131
  - routers, LSRs, 13
- dial-up lines, 129–130
- differentiated services, IP packet forwarding, 9
- distribution (labels)
  - across ATM LSR domains, 56–61
  - downstream on demand, 57
  - on-demand, 35
  - unsolicited, 34

- domains
  - ATM LSRs
    - convergence, 61–62
    - label allocation and distribution, 56–61
    - labeled packet forwarding, 55–56
  - MPLS (frame-mode) convergence, 37–39
- down-bit (summary LSAs), 241
- downstream label distribution
  - unsolicited, 34
  - on demand, 57, 121
- draft-ietf-mpls-framework document, 11
- dynamic default routing, configuring Internet access, 328–334

## E

---

- Edge-LSRs, 13–14
  - actions, 15
  - architecture, 18
  - Ingress, 25
  - push action, 15–16
- egress LSRs, 17
- EIGRP (Enhanced Interior Gateway Routing Protocol), equal-cost load sharing, 6
- encapsulation, 27–28
  - across Ethernet links, 77
- end-to-end convergence delay between VPN sites, 275
- end-to-end LSP, verifying, 428–429
- end-to-end MPLS path, monitoring, 123–124
- equal-cost load sharing, EIGRP, 6
- establishing
  - LDP sessions, 31–34
  - TDP sessions, 31–34
- Ethernet
  - MPLS encapsulation, 77
  - PE routers, tunneling to CE routers, 355
- evolution of VPNs, 129–131
- examples
  - migration
    - ATM backbone to cell-mode MPLS, 108
    - ATM backbone to Frame-mode MPLS, 106–108
    - backbone network to Frame-mode MPLS, 97–99
    - CEF requirements, 100

- internal links to MPLS, 103–104
- premigration infrastructure checks, 99–100
- PE-to-CE connectivity, 226
- SuperCom network
  - connectivity requirements, 167–169
  - loopback addresses, 24
- experimental bits, 27
- export maps, 368–371
- export policies
  - configuring, 195–196
  - IP tunneling migration case study, 413
  - route target, 194–195
- exporting routes to specific targets, 367–371
- Extended Communities ORF-type, 219
- extended community attribute (BGP)
  - advertising, 209
  - comparing to standard community attribute, 364–366
  - configuring, 197–198
  - route target, 194–195
  - SOO, 196–197
- extended community attribute (BGP), 193
  - format, 198
  - OPSF route propagation, 238
- extended ping command, 427–428
- external controllers, LSC (Label Switch Controller), 54
- external routes, 379
  - propagation, 10
- extranet topology, 150–152
  - central services, 152–155
- extranet VPNs
  - central services, 152
  - route distinguishers, 191
- extranet/intranet integration, VPN architecture, 255–256

## F

---

- Fast Ethernet, mapping VLANs to VPNs, 356–357
- FECs (Forwarding Equivalence Classes), 16
  - label binding, 74
  - unicast routing, 34
- filtering
  - customer links, 363–367
  - label mappings, 74–77
  - ORF, 218
  - VPN-IPv4 routes, 213–214
- firewalls
  - Cisco Secure Integrated software, 315
  - Internet access, 313–315
- flexibility of IP forwarding, 5
- format of extended community attribute (BGP), 198
- forwarding packets, 10
  - label imposition, 16
  - label swapping, 12
  - VRF, 166
- fragmenting packets, Path MTU discovery, 78
- Frame Relay, frame-mode MPLS, 65–67
- Frame-based LSRs, 50
- Frame-mode MPLS
  - control plane, loop detection, 82
  - convergence, 37–39
  - data plane, loop detection, 81
  - label lookup, 28–29
  - loop prevention, 81–82
  - LSR capabilities, 29
  - migrating
    - from ATM backbone networks, 106–108
    - from backbone network, 97–99
- frames, giant, 124
- full mesh topology
  - route reflectors, 290
  - VPNs, provisioning, 149
- full mesh VPNs, 148–149

## G

---

- giant frames
  - fragmentation, 78–80
  - troubleshooting, 124
- Gigabit Ethernet, restrictions on MPLS
  - encapsulation, 77
- global routing table
  - associating with VRF, 330–331, 334
  - performing additional lookup, 334
- goal of MPLS, 11
- GRE tunneling, migration to MPLS/VPN solution, 407–409, 413, 420
  - configuring route reflectors, 418–420
  - defining VPNs, 410
  - routing policies, 410–414
  - staging and execution, 414–418
  - VPN site migration, 421
  - VRF definitions, 411–412

## H

---

- heterogeneous MPLS-modes over ATM, 69
- hierarchical structure
  - route reflectors, 288–290
    - PE routes, 290–291
  - VPNs, 392–394
- hop-by-hop destination-based unicast routing, 5
- hub-and-spoke topology
  - AllowAS-in feature, 264–266
  - route distinguishers, 191
  - SOO (Site of Origin) attribute, 265
  - VPNs, 144–146, 261–263
    - redundancy, 146
- hybrid topology, overlay model, 150

## I

---

- iBGP, migrating to MPLS/VPN, 248–249
- IETF (Internet Engineering Task Force)
  - draft-eitf-mpls-framework, 11
  - web site, 11, 193

- IGPs
  - confederations
    - multiple process configuration, 306–309
    - single process configuration, 305–306
  - customer routes, migrating to BGP, 339–344
- implementation models (VPNs)
  - overlay model, 135–137
  - peer-to-peer model, 138–139
    - dedicated router approach, 141–142
    - shared router approach, 139–141
- implementing
  - BGP confederations, 300–305
  - confederations
    - multiple IGP environment, 306–309
    - single IGP environment, 305–306
  - control-plane in ATM switches, 54
  - multiprotocol BGP in SuperCom network
    - example, 174–177
- implicit-null value, 41–42
- import policies (BGP)
  - configuring, 195–196
  - IP tunneling migration case study, 413
  - route target, 194–195
- importing selected customer routes, 359, 362–363
- in-band management virtual circuit, cell-mode
  - MPLS, 51
- independent control mode, 57, 73, 274
  - frame-mode MPLS over Frame Relay, 65–67
    - label assignment, 34
- infrastructure of VPDNs, 156
- Ingress Edge-LSRs, 25
- ingress PE-to-CE routing exchange, verifying, 439–440
- interface-level CEF, monitoring, 122–123
- interfaces
  - assigning to VRFs, 204
  - LC-ATM
    - control-plane connectivity, 51
    - downstream on demand, 57
    - status, verifying, 53
  - loopback, route summarization, 353
  - partitioning, 355
- internal BGP sessions, 204
- internal links, migration to MPLS, 103–104
- internal routes, 379



## Internet access

- configuring, 312–313
  - dynamic default routing, 328–334
  - global routing table, additional lookup, 334
  - PE-to-CE connectivity, 320–328
- firewalls, 313–315
- global routing table, associating with VRF, 330–334
- separate service provider, configuring, 335
- static default routing, 315–320
- inter-PE router routing, 172–173
- inter-provider VPN solutions, 394–403
- initiating packet labeling, 31
- Intranet topology, MPLS/VPN, 184–185
  - route distinguishers, 191
- intranet/extranet integration, VPN architecture, 255–256
- IOS (Internetwork Operating System), control-plane connectivity, 52–53
- IP
  - connectivity between ATM LSRs, 51
  - forwarding, 5
    - differentiated services, 9
    - external routing information propagation, 10
  - tunneling, migration to MPLS/VPN solution, 407–409, 413, 420
    - configuring route reflectors, 418–420
    - defining VPNs, 410
    - routing policies, 412–414
    - staging and execution, 414–418
    - VPN site migration, 421
    - VRF definitions, 411–412
  - overlapping address space, 164
  - Path MTU
    - discovery, 78–80
    - MSS, 78
  - prefixes, propagation across MPLS VPN network, 430–431
  - routing
    - VRP, 166
    - summarization, 92–93
  - VPDN infrastructure, 156
- ip ospf network point-to-point command, 348
- ip route command, 201

- ip vrf command, 186
- ip vrf forwarding command, 204
- ISPs, Managed Network service, 138

---

**L**

---

- label imposition, Edge-LSRs, 15–16
- label stack , 26, 30
  - Bottom of Stack bit, 27
  - penultimate hop popping, 40
    - implicit-null value, 41–42
  - two-level, 352–354
- labels
  - allocation, VC merge, 58–61
  - allocation/distribution across ATM LSR domains, 56–61
  - binding, 34
  - conservative retention mode, 35
  - independent control, 57
  - liberal retention mode, 35
  - lookup, frame-mode MPLS, 28–29
  - mappings, filtering, 74–77
  - on-demand distribution, 35
  - packet forwarding, 10
    - across ATM LSR domains, 55–56
    - frame-based, 56
  - stack header, 26
  - swapping, 11
  - TTL propagation, 373–374
  - untagging, 29
- label-to-prefix bindings, 34
- LANs
  - encapsulation, 27–28
  - interfaces, MPLS/VPN deployment, 355–357
  - Layer 2 paths, selecting, 6–7
- large-scale networks, route reflection, 289
- Layer 2 paths, WANs selection, 6–7
- Layer 3 lookup, ATM, 50
- LC-ATM (Label Switching Controlled ATM)
  - interface, 50
    - control-plane connectivity, 51
    - downstream on demand, 57
    - status, verifying, 53
    - VCs, minimizing, 56

- LDP (Label Distribution Protocol), 31
  - sessions, establishing, 31–34
  - troubleshooting, 118–121
  - verifying operation, 118–120
- leased lines, 129–130
- LFIB (Label Forwarding Information Base) entries
  - label lookup, frame-mode MPLS, 28–29
- LIB (Label Information Base), 17
- liberal retention mode, 35, 273
  - Frame-mode convergence, 37–39
- limitations of cell-mode MPLS, 50
- limiting label mapping distribution, 73–77
- links
  - customer, managing, 358–371
  - PE-CE
    - configuring, 200
    - convergence, 276–277
    - RIP v2, 202–203
    - running separate BGP sessions, 320–321
    - static routing, 200–201
- link-state routing protocols, OSPF, PE-to-CE
  - connectivity, 230–231
- load sharing, EIGRP equal-cost, 6
- lookup, VPI/VCI, 49
- loopback addresses
  - configuring on PE routers, 348
  - route summarization, 353
  - SuperNet example, 24
  - TDP/LDP identifiers, 75
- loopback interfaces, ATM LSRs, 53
- loops, preventing
  - cell-mode MPLS, 82–87
  - frame-mode MPLS, 81–82
  - SOO, 196
- LSAs (link-state advertisements), down-bits, 241
- LSC (Label Switch Controller), 54
- LSPs (Label Switched Paths), 17
  - end-to-end connectivity, 123
- LSRs (label switch routers), 13
  - actions, 15
  - ATM, 14–15, 50–51
  - ATM-Edge-LSRs, actions, 15
  - conservative retention mode, 35
  - Core LSRs, 25
  - Edge, 14
    - actions, 15
    - architecture, 18
    - Ingress, 25
    - push action, 15–16
  - frame-based, 50
  - Frame-mode, capabilities, 29
  - label stack, 30
  - liberal retention mode, 35
  - loopback interfaces, 53
  - pop action, 13
  - push action, 13

---

## M

- Managed Network service, 138
- managed network VPN topology, 157
- managing customer links, 358–367
  - export maps, 368–371
  - importing selected customer routes, 359–363
  - route filtering, 363–367
- mapping VPNs to VLANs, 356–357
- mappings (label), filtering, 74–77
- Maximum Initially Labeled IP Datagram Size, 79
- maximum routes command, 311
- maximum session handling, route reflectors, 288
- messages, Route Refresh, ORF entries, 218
- migration strategies
  - ATM backbone to cell-mode MPLS, 108
  - ATM backbone to Frame-mode MPLS, 106–107
  - backbone to Frame-mode MPLS, 97–99
  - iBGP customers to MPLS/VPN, 248–249
  - IGP customer routes to BGP, 339–344
  - internal links to MPLS, 103–105
  - IP tunneling to MPLS/VPN solution, 407–409, 413, 420
    - configuring route reflectors, 418–420
    - defining VPNs, 410
    - routing policies, 410–414
    - staging and execution, 414–418
    - VPN site migration, 421
    - VRF definitions, 411–412

- partial migration, 104
- premigration infrastructure checks, 99–100
- minimizing VCs over LC-ATM interfaces, 56
- monitoring
  - end-to-end MPLS path, 123–124
  - interface-level CEF, 122–123
- MP\_REACH\_NLRI attribute, 205–206
- MP\_UNREACH\_NLRI attribute, 205–206
- MP-iBGP (Multiprotocol BGP), 187
  - configuring, 207–209
    - on PE routers, 420
  - PE routers, Route Refresh, 215–217
  - route distinguishers, 188
  - routing context, configuring, 209–211
  - static routes, redistribution, 201
  - SuperCom example configuration, 174–177
- mpls ip command, 31
- mpls label-distribution both command, 31
- MPLS/VPN, 161. *See also* VPNs
  - architecture, 13
  - AS Override, 250–252
  - backbone
    - convergence between VPN sites, 275–280
    - customer access, 225–226
    - deploying BGP, 344–355
    - OSPF route propagation, 235–238
    - route advertisements, 280–285
    - traceroute, 371–374
  - carrier's carrier, 378–392
  - control protocols, 19–20
  - customer routes, next-hop forwarding, 345–348
  - data plane, packet forwarding, 220–221
  - deploying on LAN interfaces, 355–357
  - Extended Communities ORF-type capability, 219
  - FECs, 16
  - inter-PE router routing, 172–173
  - Intranet topology, 184–185
  - goal of, 11
  - migration strategies
    - configuring route reflectors, 418–420
    - defining VPNs, 410
    - from iBGP, 248–249
    - from IP tunneling, 407–409, 413, 420
    - routing policies, 412–414
    - staging and execution, 414–418
  - VPN site migration, 421
  - VRF definitions, 411–412

- MP-iBGP, 187
- overlapping addresses, 190
- PE routers
  - Automatic Route Filtering, 213–214
  - requirements for advertisements, 183
- PE-to-CE link configuration
  - RIP v2, 202–203
  - static routing, 200–201
- PE-to-CE connectivity
  - BGP-4, 227–229
  - OSPF, 230–231
- route distinguishers, 173, 188
  - configuring, 191–192
- route reflectors, configuring, 219
- routes, importing, 195
- SOO extended community, 193, 196
  - configuring, 197–198
- VPN-IPv4 addresses, 207–208
- VRFs
  - assigning interfaces, 204
  - configuring, 186

MPLSCP (MPLS Control Protocol), 27

MSS (maximum segment size), 78

MTU, Path MTU discovery, 78–80

multiprotocol extensions (BGP), 205

## N

---

- NBMA (non-broadcast multi-access), OSPF, PE-to-CE connectivity, 231
- neighbor advertisement-interval command, 277
- neighbor command, 208, 347
- neighbor maximum-prefix command, 311
- network command, 202
- network layer packet forwarding, 5–6
- network management, customer links, 358–367
  - export maps, 368–371
  - importing selected customer routes, 359, 362–363
  - route filtering, 363–367
- networks (large-scale), route reflection, 289

- next hops
  - BGP, summarizing, 352–353
  - penultimate hop popping, 40
    - aggregates, 41
    - implicit-null value, 41–42
  - resetting at subconfederation boundary, 309
- next-hop forwarding, 345–348
- next-hop-self command, 309, 344–346
- NLRI (Network Layer Reachability Information), 205
- numbering route distinguishers, 191–192

## O

- on-demand distribution, 35
- one-site-one-VRF model, 170
- OPEN messages (BGP), Capabilities parameter, 205
- optimization techniques (labels), VC merge, 58–61
- optional, non-transitive attributes (BGP), 205–206
- ordered control mode, 57, 73
- ORF capability, 218
  - configuring on route reflectors, 299–300
  - type definitions, 219
- OSPF (Open Shortest Path First)
  - PE-to-CE connectivity, 230–231
    - VRFs, separating, 232–235
    - without site area 0, 242–243
  - route propagation over MPLS/VPN backbone, 235–238
  - site area 0 support, PE-to-CE connectivity, 238–242
- overlapping addresses, 164
  - MPLS/VPN, 190
- overlapping VPNs, 167–170
- overlay VPN model, 135–137
  - convergence, 275–280
  - full-mesh, 148–149
    - VCs, calculating, 148
  - hub-and-spoke topology, 148
  - hybrid topology, 150
  - partial-mesh, 148
    - PE-to-CE connectivity, OSPF, 230–231
- oversized packets, 124

## P

- packets
  - Ethernet encapsulation, 77
  - forwarding
    - encapsulation, 27–28
    - external routing information
      - propagation, 10
      - label imposition, 16
      - label swapping, 12
      - MPLS/VPN data plane, 220–221
    - giant frames, troubleshooting, 124
    - Path MTU discovery, 78
  - partial mesh VPNs, 148
  - partial migration strategy, 104
  - partitioning, 292
    - interfaces, 355
  - Path MTU discovery, 78–80
  - PBR (policy-based routing)
    - deploying, 10
    - scalability, 10
  - PDBs (protocol descriptor blocks), 312
  - P devices, 131
  - PE (Provider Edge) devices, 131
    - advertisements, requirements for, 183
    - Automatic Route Filtering, 213–214
    - BGP
      - route selection, memory
        - requirements, 211
      - sessions, activating, 207–208
    - loopback addresses
      - configuring, 348
      - summarization, 349–354
    - MP-iBGP, configuring, 420
    - ORF, 218
    - PDBs, 312
    - provisioning, 311–312
    - route filtering based on community value, 294
    - route reflection, 290–291
    - Route Refresh, 215, 217
    - routing policies, IP tunneling migration case study, 410
    - scaling PDBs, 312
    - standard community filtering, 296–297
    - tunneling to CE router, 355
    - VRFs, route distinguishers, numbering, 191–192

- PE-ASBR routers, 396
- PE-CE links, configuring, 200
  - RIP v2, 202–203
  - static routes, 200–201
- peer group leaders, selecting, 345
- peer-to-peer VPN model, 138–139
  - comparing, 143
  - dedicated router approach, 141–142
  - shared router approach, 139–141
- penultimate hop popping, 40–42
  - aggregates, 41
  - implicit-null value, 41–42
- per-VPN routing protocols, 174
- redistribution, 176–177
- PE-to-CE connectivity, 225
  - BGP-4, 227–229
  - convergence, 276–277
  - iBGP customers, migrating to MPLS/VPN, 248–249
  - ingress routing, verifying, 439–440
  - MPLS/VPN backbone, customer access, 225–226
  - OSPF, 230–231
    - route propagation over MPLS/VPN backbone, 235–238
    - site area 0 support, 238–242
    - without site area 0, 242–243
  - redistribution, 226
  - running separate BGP sessions, 320–321
  - VPN customer network topologies, 244–248
  - VRFs, separating, 232–235
- PHP (penultimate hop popping), 16, 179
- physical interfaces, partitioning, 355
- pinging between CE routers, 426–428
- P network, 131
- policies (BGP), import/export, VRF configuration, 195–196
- pop actions, 13
- pop tag, 29
- popping the label stack, penultimate hop popping, 40
- POPs, migrating route reflection to MPLS-based infrastructure, 98–99
- populating VRFs with customer routes, 225–226

- prefixes
  - propagation across MPLS VPN network, 430–431
  - route summarization, 92–93
  - unlabeled, 37
- prefix-to-label mappings, liberal retention mode, 35
- premigration infrastructure checks, 99–100
- preparatory steps, VPN packet forwarding, 177
- preventing
  - labeled packet fragmentation, 79
  - routing loops
    - cell-mode MPLS, 82–87
    - frame-mode MPLS, 81–82
    - SOO, 196
- propagate-ttl command, 373
- propagation of MPLS VPN routes, verifying, 436–437
- protocols, ships-in-the-night, 54
- provisioning
  - full-mesh VPNs, 149
  - PE-to-CE connectivity, PE router configuration, 311–312
  - virtual circuits, 8
- push action, 13
  - Edge-LSRs, 15–16
- push tag, 29
- PVCs (permanent virtual circuits)
  - ATM, frame-mode MPLS operation, 67–69
  - shadow PVCs, 146

---

## R

- RD (route distinguisher), 177
- reachability
  - backbone networks, 342
  - BGP, NLRI (Network Layer Reachability Information), 205
- recursive VPNs, 392–394
- redistribute bgp metric transparent command, 203
- redistribute command, 201, 235
- redistribution, 226
  - into OSPF, 230
  - per-VPN routing, 176–177
  - verifying, 434–435
  - VRF OSPF routes into MP-iBGP, 235–236

- redundancy
  - hub-and-spoke VPN topology, 146
  - route reflectors, 289–290
- reflected routes, 288
  - best path selection, 291
  - improving convergence time, 277
  - partitioning, 292
  - route filtering based on route target attribute, 297
- removing
  - BGP community attribute, 371
  - unneded BGP peering sessions, 105
- requirements
  - BGP configuration in MPLS/VPN environment, 227
  - connectivity, SuperCom network example, 167–169
  - PE router advertisements, 183
  - VPNs
    - central services topology, 258
    - unique addresses, 165
- restricting label mapping distribution, 73–77
- restrictions
  - cell-mode MPLS, 50
  - Ethernet encapsulation, 77
- retention modes (labels), 35
- reusing AS numbers, 250–252
- RIP v2, PE-to-CE link configuration, 202–203
- route distinguishers, 173, 187–188
  - assigning to VRFs, 411–412
  - configuring, 191–192
  - VPN-Ipv4, 188
- route filtering
  - automatic, 263
  - customer links, 363–367
  - route reflectors based on route target attribute, 297
- route propagation across MPLS VPN network, 430–431
- route redistribution, verifying, 434–435
- route reflectors, 288, 292
  - hierarchical structure, 290
    - PE routes, 290–291
  - improving convergence time, 277
  - IP-iBGP, configuring for IP tunneling migration, 418–420
  - maximum session handling, 288
  - migration to MPLS-based infrastructure, 98–99
  - MPLS/VPN architecture, configuring, 219
  - ORF capability, 299–300
  - partitioning, 292
  - redundancy, 289–290
  - route target attribute-base filtering, 297
- Route Refresh, 215–217. *See also* ORF
  - ORF entries, 218
- route summarization, 92–93
  - loopback addresses, 353
- route target attribute, 171–172, 194–195
  - extended community format, 199
  - route filtering on reflected routes, 297
- route-maps command, 201
- router ospf command, 233
- router-on-a-stick, 288
- routers
  - independent control, 57
  - LSRs, 13
    - actions, 15
    - ATM-Edge-LSRs, 15
    - ATM-LSRs, 14–15, 50, 55–56
    - Edge-LSRs, 14–15
    - Frame-based, 50
    - loopback interfaces, 53
    - pop action, 13
    - push action, 13
  - PE
    - MP-iBGP, configuring, 420
    - standard community filtering, 294–297
  - virtual routers, 165
- routes
  - exporting to specific targets, 367–371
  - reflected, 288
  - VPN-IPv4, selecting, 211–213
- route-target command, 195
- route-target export commands, 371
- routing, per-VPN redistribution, 176–177
- routing context, 175, 200
  - MP-iBGP configuration, 209–211

- routing loops, 290
  - preventing
    - cell-mode MPLS, 82–87
    - frame-mode MPLS, 81–82
    - SOO, 196
  - VPNs, avoiding, 266
- routing policies
  - IP tunneling migration case study, 412–414
  - PE routers, IP tunneling migration case study, 410
- routing protocols
  - per-VPN, 174
  - VPN-aware, 200
- routing tables
  - BGP, scanner process, 278–279
  - VRF, verifying route import function, 437–439
- rr-group command, 219

## S

- scalability
  - IP forwarding, 5
  - MPLS/VPN architecture, 173
  - PBR, 10
  - PE routers, PDBs, 312
  - WANs, 7
- scanner process, 278–279
- security
  - central services, 153
  - firewalls
    - Cisco Secure Integrated software, 315
    - Internet connectivity, 313–315
- selection process
  - best path, reflected routes, 291
  - BGP, 263
    - peer group leaders, 345
  - customer routes to import, 359, 362–363
  - VPN-IPv4 routes, 211–213
- service providers
  - application hosting, 258
  - backbone convergence, 273–274
- services, central services topology, 258

- sessions
  - BGP
    - activating between PE routers, 207–208
    - internal, 204
    - PE-to-CE connectivity, 320–321
  - LDP, establishing, 31–34
  - maximum handling capability of route reflectors, 288
  - MP-iBGP, scaling, 288
  - TDP, establishing, 31–34
- set extcommunity command, 435
- set extcommunity rt command, 371
- shadow PVC, 146
- shared router approach, peer-to-peer VPN model, 139–141
- shim header, 27
- ships-in-the-night, 54
- show atm vc command, 54
- show cef interface command, 429
- show ip bgp neighbor command, 217, 283–284, 345
- show ip ospf command, 234
- show ip route vrf command, 434
- show ip vrf detail command, 435
- show mpls forwarding-table command, 116–117
- show tag tdp neighbor command, 33
- show tag-switching forwarding-table command, 220
- show tag-switching tdp bindings command, 36
- show tag-switching tdp discovery command, 121
- show tag-switching tdp neighbor command, 67, 75
- site area 0 (OSPF), 238–242
- sites (web), IETF, 11, 193
- software
  - Cisco IOS, control-plane connectivity, 52–53
  - Cisco Secure Integrated software, 315
- SOO (Site of Origin) attribute, 193, 196, 265
  - configuring, 197–198
  - extended community format, 199
- specifying route targets for export, 367–371
- stack header, 26
  - Bottom of Stack bit, 27
- staging IP tunneling migration, 414–418
- standard communities (BGP)
  - comparing to extended community attribute, 364–366
  - filtering on PE routers, 296–297
  - route filtering on PE routers, 294
- starting MPLS packet labeling, 31

- static default routing, 315–320
- static routing, PE-to-CE link configuration, 200–201
- stripping BGP community attribute, 371
- stub sites, 200
- sub-AS, label exchange, 309
- subnet-to-label bindings, 34
- summarization, 92–93
  - loopback addresses, 353
  - on PE loopback addresses, 349–354
- SuperCom network example
  - loopback addresses, 24
  - multiprotocol BGP, implementing, 174–177
  - VPNs, case study, 162–164
- swap tag, 29
- switched WANs
  - ATM
    - cell-mode MPLS operation, 69
    - frame-mode MPLS operation, 67–69
  - Frame Relay, frame-mode MPLS operation, 65–67
- switches
  - ATM
    - control-plane implementation, 54
    - Layer 3 lookup, 50
    - ordered control, 57
  - Ethernet, MPLS MTU, 80
  - VSI (Virtual Switch Interface), 54
- syntax
  - route target command, 195
  - tag-switching advertise-tags command, 75

## T

- tables, comparing IP forwarding and IP routing, 166
- tag tdp router-id command, 33
- tag-switching advertise-tags command, 75–76
- tag-switching commands, MPLS equivalents, 461–462
- tag-switching ip command, 31
- tag-switching mtu command, 80
- TCP (Transmission Control Protocol), MSS, 78
- TDP (Tag Distribution Protocol), 31
  - label exchange, verifying, 121
  - sessions, establishing, 31–34
  - troubleshooting, 118–121
  - verifying operation, 118–120

- TFIB (Tag Forwarding Information Base), 18
- TIB (Tag Information Base), 17
  - liberal retention mode, 35
- topologies
  - BGP
    - confederations, deploying, 300–305
    - peering structure, 101–103
  - carrier's carrier MPLS/VPN, 381–392
  - convergence
    - across ATM LSR domains, 61–62
    - between VPN sites, 275–280
    - within service provider backbone, 273–274
  - MPLS/VPN, Intranet, 184–185
  - PE-to-CE connectivity options, 226
  - route reflection
    - between PE routers, 290–291
    - hierarchical, 289–290
    - large-scale networks, 289
  - VPNs
    - central services, 258–261
    - central-services extranet, 152–155
    - customer networks, 244–248
    - extranet, 150–152
    - hub-and-spoke, 144–146, 261–263
    - managed network, 157
    - VPDN, 155
- traceroute, 88–92
  - between VPN sites, 371–374
- traffic, forwarding, 10
- TransitNet migration examples, 97
- troubleshooting
  - CE-to-PE links, 346
  - control plane, 118–121
  - LDP, verifying operation, 118–120
  - MPLS, 115
    - checks, 116–118
    - data plane, 122–124
  - TDP, verifying operation, 118–120
  - traceroute utility, 88–92
- TTL (Time-To-Live) field, 26
  - propagation, 373–374
- tuning BGP scanner process, 279
- tunneling PE-to-CE routers, 355
- two-level label stacks, 352–354



## U

- unicast routing, FECs, 34
- unique addresses, VPNs, 165
- unique numbers, assigning to route distinguishers, 191–192
- unlabeled prefixes, 37
- unsolicited downstream label distribution, 34
  - frame-mode MPLS over Frame Relay, 65–67
- untag, 29
- upate-source parameter (neighbor command), 347
- utilities, traceroute, 88–92
  - between VPN sites, 371–374

## V

- VC lookup operation, 49
- VC merge, 58–61
- VCI (virtual circuit identifier), 49
- VCs (Virtual Circuits), 131
  - frame-mode MPLS over Frame Relay, 65–67
  - in-band management, 51
  - minimizing on LC-ATM interfaces, 56
  - provisioning, 8
  - PVCs, shadow PVCs, 146
- verifying
  - CE-to-PE routing exchange, 432–434
  - imported customer routes, 366–367
  - ingress PE-to-CE routing exchange, 439–440
  - LC-ATM interface status, 53
  - LDP label exchange, 121
  - LDP operation, 118–120
  - MPLS VPN operation, 426
    - CEF switching, 429–430
    - connectivity, 426–429
  - propagation of MPLS VPN routes, 436–437
  - proper MPLS setup, 116–118
  - route import functionality, 437–439
  - route redistribution, 434–435
  - TDP operation, 118–120
    - label exchange, 121
- virtual routers, 165
- VLANs
  - 802.1q, running MPLS/VPN, 357
  - mapping to VPNs, 356–357

- VPDN (Virtual Private Dialup Network) topology, 155
- VPI (virtual path identifier), 49
- VPN-aware routing protocols, 200
- VPN-IPv4, 188
  - addresses, MP-iBGP configuration, 207–208
  - Automatic Route Filtering, 213–214
  - route exchange, configuring, 208
  - route selection, 211–213
- VPNs
  - business problem-based classification, 132–134
  - central-services extranet topology, 152–155
  - Cisco VPN Solutions Center, 358
  - complexity of, 132
  - customer network topologies, 244–248
  - defining, IP tunneling migration case study, 410
  - evolution of, 129–131
  - extranet topology, 150–152
  - extranet/intranet integration, 255–256
  - full-mesh topology provisioning, 149
  - hierarchical, 392–394
  - hub-and-spoke topology, 144–146, 261–263
    - AllowAS-in feature, 264–266
    - redundancy, 146
  - inter-provider, 394–403
  - label allocation, 178
  - managed network topology, 157
  - mapping to VLANs, 356–357
  - overlapping, 167–170
  - overlay model, 135–137
    - full-mesh, 148–149
    - hybrid topology, 150
    - OSPF, PE-to-CE connectivity, 230–231
    - partial-mesh, 148
  - packet forwarding, 177–179
  - peer-to-peer models, 138–139
    - comparing, 143
    - dedicated router approach, 141–142
    - shared router approach, 139–141
  - per-VPN routing, redistribution, 176–177
  - PE-to-CE subnets, 426–428
  - requirements for unique addresses, 165
  - route distinguishers, 173
  - route targets, 171–172
  - routes, importing, 195

- routing loops, avoiding, 266
- sites, 169
- SuperCom network example, 162–164
- topologies, central services, 258–261
- VPDN topology, 155
- VRF (VPN routing and forwarding) table, 165–166, 175
  - associating with global routing table, 330–331, 334
  - configuring, 186
    - import/export policies, 195–196
  - customer routes, importing, 359–363
  - defining for IP tunneling migration, 411–412
  - interfaces, assigning, 204
  - one-site-one-VRF model, 170
  - populating with customer routes, 225–226
  - route distinguishers
    - configuring, 191–192
    - numbering, 191–192
  - route distinguishers, assigning, 411–412
  - route filtering, 363–367
  - separating on PE-to-CE links, 232–235
- VSI (Virtual Switch Interface), 54

## W

---

- WANs
  - ATM
    - cell-mode MPLS operation, 69
    - heterogeneous MPLS-mode operation, 69
    - MPLS operation, 67–69
  - core redundancy, 7
  - Frame Relay, MPLS operation, 65–67
  - Layer 2 paths, selecting, 6–7
  - virtual circuits, provisioning, 8
- web sites, IETF, 11, 193