



Symbols

- % VPDN-3-NORESOURCE error message, 128
- % VPDN-4-MIDERROR error message, 128
- % VPDN-4-REFUSED error message, 128
- % VPDN-5-NOIDB error message, 128
- % VPDN-5-UNREACH error message, 129
- % VPDN-6-CLOSED error message, 127
- % VPDN-6-DOWN error message, 129
- % VPDN-6-MAX_SESS_EXCD error message, 128
- % VPDN-6-RESIZE error message, 129
- % VPDN-6-SOFTSHUT error message, 129
- % VPDN-6-TIMEOUT error message, 129
- % VPDN-6-AUTHENERR error message, 127
- % VPDN-6-AUTHENFAIL error message, 127
- % VPDN-6-AUTHORERR error message, 127
- % VPDN-6-AUTHORFAIL error message, 127

Numerics

- 3DES (Triple DES), 658

A

- AAA (authentication, authorization, and accounting)
 - configuration, 683
 - IKE, 686
 - L2F tunnel establishment, 19
 - L2TP misconfiguration, 312–322
 - remote
 - authentication failure, 322–326
 - authorization failure, 326, 331
 - case studies, 98–114
 - configuration, 39, 44
 - L2TP, 241
 - LNS, 249
 - servers, 331–342
- aaa new-model command, 241, 683
- AAL5 over MPLS configuration, 594
- access. *See also* connections
 - Internet
 - interfaces, 440

- VPNs, 439
 - remote clients, 293
- access lists
 - AH, 733
 - AToM, 615
 - crypto
 - asymmetric, 726
 - configuration, 673
 - misconfiguration, 699
 - reconfiguration, 700
 - deleting, 706, 735
 - ESP, 733
 - external interfaces, 705
 - L2TPv3, 395
 - LDP, 622
 - modifying, 729
 - split tunneling, 684
- ACCM (Asynchronous Control Character Map), 59, 227
- ACFC (Address & Control Field Compression), 59, 268
- activation of MP-BGP, 452
- active lines, verifying, 266
- adding
 - default routes, 697
 - preshared keys, 702
- additive keyword, 529
- Address & Control Field Compression (ACFC), 59, 268
- addresses
 - configuration, 46
 - DNS, 248
 - IP
 - misconfigurations, 704
 - mismatches, 644
 - overlapping, 430
 - PPTP, 158
 - virtual templates, 97
 - MDT, 442
 - peer misconfigurations, 700
 - WINS
 - configuration, 46
 - L2TP, 248
- adjacencies, PIM, 442
- Administrator subfields, 431
- Advanced Encryption Standard (AES), 658

- advertisements
 - conditional label, 506, 631
 - IS-IS, 496
 - labels
 - bindings, 502, 628
 - verifying tunnels, 626
 - PE to CE route, 534
 - VPNs, 511–536
- AES (Advanced Encryption Standard), 658
- aggressive mode negotiation, 665–666
- AH (Authentication Header), 657, 733
- alarms, remote, 54
- algorithms
 - CSPF, 429
 - encryption, 671
 - hash, 671
 - modification of MD5, 712
 - reconfiguration of, 724
- any keyword, 730
- Any Transport over MPLS. *See* AToM
- applying crypto maps to external interfaces, 674, 686
- architecture
 - IPSec, 656. *See also* IPSec
 - Layer 3 MPLS VPNs, 421
- AS (autonomous system) numbers, 431
- Assigned Number subfields, 431
- Assigned Tunnel ID AVP, 218
- assignments, 508
- asymmetric crypto access lists, 726
- asymmetric payload types, L2TPv3, 405
- Asynchronous Control Character Map (ACCM), 59, 227
- asynchronous interfaces, L2TP, 240
- asynchronous lines
 - L2TP, 239
 - parameters, 37
- ATM (asynchronous transfer mode)
 - cell relay, 594–596
 - control words, 582
 - VP cell relay, 380
- ATM AAL5 CPCS-SDU control words, 581
- AToM (Any Transport over MPLS), 577
 - CEF, 588
 - commands, 645–652
 - configuration, 588
 - Layer 2 PDU transport, 578
 - LDP
 - Router ID, 589
 - specifying, 589
 - loopback interfaces, 588
 - MPLS
 - backbone IGPs, 590–591
 - core interfaces, 589
 - MTU issues, 602
 - pseudowires, 591–597
 - sample configurations, 597–605
 - technical overview of, 577
 - troubleshooting, 605
 - VC label exchanges, 582–586, 636–645
- attachment circuits
 - AToM
 - Layer 2 PDU transports, 578, 582
 - pseudowires, 591–597
 - configuration, 378, 381
- attributes, RT, 434
- attribute-value-pairs. *See* AVPs
- authentication, 713
 - aggressive mode, 665–666
 - AVPs, 226
 - CAs, 680, 736
 - certificates, 714
 - CHAP, 18. *See also* CHAP
 - IKE, 713
 - L2TPv3, 397
 - LDP
 - mismatches, 499
 - peers, 499
 - troubleshooting, 624
 - LNS, 249
 - local
 - configuration, 44
 - LNS, 249
 - PAC, 158
 - partial, 228
 - partial PPP failures, 64, 273
 - PPP, 176–180, 301
 - preshared key, 663
 - remote AAA
 - failure, 322–326
 - troubleshooting, 105–109
 - RSA signature, 664
 - SHA-1, 253
 - troubleshooting, 713
 - tunneling, 74, 285

Authentication Header (AH), 657, 733
 authentication protocol (AuthProtocol), 63
 authentication, authorization, and accounting. *See*
 AAA
 authorization (remote AAA)
 failure, 326, 331
 troubleshooting, 109–114
 autodetection, PPP, 239
 autonomous system (AS) numbers, 431
 AVPs (attribute-value-pairs), 214
 authentication, 226
 calls
 management, 225
 status, 227
 control connection management, 224
 hiding, 215
 L2TP encoding formats, 221
 L2TPv3, 362–363
 circuit status, 368
 control connection management, 366
 control messages, 364
 Layer 2 Specific Sublayer, 371
 session management, 367
 Result Code, 222

B

backbones
 IGP, 449, 479–481
 L2F, 11. *See also* L2F
 MDT, 444
 MPLS, 590–591. *See also* AToM; MPLS
 MVPNs, 465
 VPNs, 437. *See also* VPNs
 baselining networks, 3
 basic discovery, LDP, 582
 BGP (Border Gateway Protocol), 451
 MP-BGP
 activating, 452
 redistributing routes, 458
 route redistribution, 518
 PIM, 467
 tables, 520
 updating, 447
 bindings
 labels
 advertisements, 502

 blocking, 631
 peer LSR, 628
 verifying, 626
 VC label exchanges, 586
 bits
 DF, 689
 Flags field, 581
 bits per second (bps), 236
 blocking
 IPSec traffic, 735
 ISAKMP firewalls, 705
 label bindings, 631
 LDP, 622
 troubleshooting access lists, 395
 Border Gateway Protocol. *See* BGP
 bottom-up troubleshooting, 5
 bps (bits per second), 236

C

C (Command / Response) bit, 582
 cabling, 767
 calculations
 keys, 16
 MD5, 19
 call management AVPs, 225
 call reception, 228, 260–265
 NAS, 52
 verifying, 56
 call sessions, 163. *See also* sessions
 call setup, verifying, 55
 call status AVPs, 227
 Call-Disconnect-Notify (CDN) message, 233, 364
 carrier's carrier topologies, 419
 CAs (certificate authorities)
 authentication, 680
 declaring, 679
 enrollment, 680, 736
 case studies
 IPSec, 736–746
 L2F tunnel failures from offload servers, 114
 L2TP, 311
 AAA server unreachable, 331–342
 authentication, 322–326
 authorization, 326, 331
 misconfiguration, 312–322

- MPLS VPNs, 536–560
- PPTP
 - MPPE attributes not returned, 197–203
 - split tunnels, 203–204
 - remote AAA, 98–114, 322–331
- CBC (cipher block chaining), 722
- CCP (Compression Control Protocol), 93, 184
- CDN (Call-Disconnect-Notify), 233
 - LNS, 293
 - messages, 223
- CDP (CRL distribution point), 718
- CE (customer edge) devices, 358
 - advertisements, 512, 534
 - configuration, 446
 - MVPNs, 464
- CEF (Cisco Express Forwarding)
 - AToM
 - enabling, 588
 - troubleshooting, 608
 - disabling, 483, 633
 - enabling, 376, 447
 - tables, 424
 - verifying, 509
- cell relay, ATM, 594, 596
- cell-mode, MPLS, 423
- cells, VP relay, 380
- certificate revocation list (CRL), 680
- certificates
 - authentication, 714
 - CAs. *See* CAs
 - digital, 664, 666
 - responders, 707
 - server maps, 678
- Challenge Handshake Authentication Protocol. *See* CHAP
- CHAP (Challenge Handshake Authentication Protocol)
 - configuration, 240
 - L2F tunnel establishment, 18
- cipher block chaining (CBC), 722
- circuit status AVPs, 368
- circuits, configuration, 378, 381
- Cisco Express Forwarding. *See* CEF
- classes
 - L2TPv3, 377
 - pseudowire, 377, 380
- clear crypto isakmp command, 723
- clear crypto sa command, 723
- clear vpdn tunnel command, 34, 120, 348
- clear vpdn tunnel pptp remote access client/PNS_name PAC_name command, 210
- CLID (Client ID), L2F, 15
- clients
 - PPP negotiation failures, 84–98
 - remote access
 - CONFACK, 269
 - disconnections, 293
 - LCP negotiation, 266
 - PPTP, 137
 - remote VPN, 740
 - VPN group policy profiles, 684
- clock set command, 678, 717
- clock timezone command, 678
- clocks
 - configuration, 678
 - troubleshooting, 716–717
- cloning
 - virtual access interfaces, 297
 - virtual interfaces, 168–169
 - virtual templates, 85
- commands, 122–126, 413, 651, 679
 - 12tp hidden, 229
 - aaa new-model, 241, 683
 - AToM, 645–652
 - clear crypto isakmp, 723
 - clear crypto sa, 723
 - clear vpdn tunnel, 34, 120, 348
 - clear vpdn tunnel pptp remote access client/ONS_namePac_name, 210
 - clock set, 678, 717
 - clock timezone, 678
 - crl optional, 680, 718
 - (crl) query, 718
 - crypto ca authenticate name, 680
 - crypto ca enroll name, 680
 - crypto ca identity, 679
 - crypto ipsec transform-set, 667
 - crypto isakmp key key address peer_address, 670
 - crypto isakmp policy, 663

- crypto isakmp sa, 714
- crypto map, 674–675
- crypto transform-set, 671
- debug, 6–8
 - IPSec, 750–751
 - L2F, 129–130
 - L2TP, 351
 - MPLS VPNs, 569–571
 - PPTP, 210
- debug aaa authentication, 105
- debug aaa authorization, 99
- debug acircuit [error | event], 651
- debug crypto ipsec, 749
- debug crypto isakmp, 692, 702, 723
- debug frame-relay events, 650
- debug isdn q931, 55, 263
- debug modem, 264
- debug mpls 12transport packet {data | error}, 650
- debug mpls 12transport signaling, 649
- debug mpls 12transport vc event, 640
- debug mpls atm-ldp api, 501
- debug mpls ldp advertisements, 567
- debug mpls ldp bindings, 568
- debug mpls ldp messages, 567
- debug mpls ldp transport events, 566
- debug mppe packet, 207
- debug ppp authentication, 65, 91, 300
- debug ppp mppe detailed, 208
- debug ppp mppe event, 207
- debug ppp negotiation, 62, 65, 87, 181, 267
- debug radius, 106, 315
- debug vpdn 12-data, 345
- debug vpdn 12-errors, 294
- debug vpdn 12-packets, 346
- debug vpdn 12tp-sequencing, 414
- debug vpdn 12x-errors, 81
- debug vpdn 12x-events, 69, 279, 281
- debug vpdn 12x-packets, 124, 416
- debug vpdn error, 123, 209, 344
- debug vpdn event, 123, 209, 275
- debug vpdn packet, 126, 347, 415
- debug vpdn 12x-data, 124
- debug vtemplate, 85, 168, 298
- debug xconnect event, 414
- enrollment mode ra, 679
- ip dfbit set, 388
- ip domain-name, 678
- ip local pool, 683
- ip ospf network point-to-point, 447
- ip pim sparse-dense-mode, 465
- ip pmtu, 388
- ip unnumbered, 310
- IPSec, 747–751
- L2F, 122–126
- L2TP, 342–348
- L2TPv3, 410–417
- lcp renegotiation, 297
- mpls id, 589
- mpls ip, 449, 611
- mpls label protocol ldp, 589
- mpls ldp advertise-labels, 630
- MPLS VPNs, 560–571
- mtu, 248
- no auto-summary, 453
- no mpls ldp advertise-labels, 504
- no vpdn softshut, 296
- ping, 6–8, 117, 704
 - MPLS VPNs, 476–479
 - tunnel LSP location, 607
- PPTP, 204–210
- protocol none, 381
- redistribute, 533
- redistribute ip, 458
- router isis, 450
- router ospf 100, 451
- service password-encryption, 79
- show, 6–8
 - IPSec, 750–751
 - L2F, 129–130
 - L2TP, 351
 - MPLS VPNs, 569–571
 - PPTP, 210
- show 12tun session all, 411
- show adjacency detail, 561
- show atm vc, 565
- show caller user, 64, 90, 97, 267, 311
- show clock, 716
- show controller e1, 262
- show crypto ca certificates, 716
- show crypto engine connections active, 747
- show crypto ipsec dynamic-map, 748
- show crypto ipsec sa, 726
- show crypto ipsec security-association lifetime, 749

- show crypto ipsec transform-set, 724
- show crypto isakmp key, 701
- show crypto isakmp sa, 695
- show crypto key mypubkey rsa, 747
- show crypto key pubkey-chain rsa, 748
- show crypto map tag, 698–699
- show ip access-lists, 490, 530, 615, 706, 734
- show ip bgp neighbors, 522
- show ip bgp vpn4 vrf vrf-name, 524
- show ip bgp vpnv4 vrf vrf_name, 518
- show ip bgp vpnv4 vrf vrf_name labels, 565
- show ip cef, 481, 609
- show ip cef summary, 509
- show ip interface, 705
- show ip rip database vrf, 532
- show ip route, 535, 697
- show ip route vrf vrf_name static, 515
- show ip vrf detail vrf-name, 526
- show ip vrf interfaces, 513
- show isdn status, 53–54, 261
- show mpls 12transport binding, 648
- show mpls 12transport hw-capability interface_name, 647
- show mpls 12transport summary, 647
- show mpls 12transport vc, 642
- show mpls 12transport vc vcid detail, 636, 646
- show mpls atm-ldp capability, 564
- show mpls forwarding-table, 504, 627
- show mpls idp bindings, 628
- show mpls idp discovery, 489
- show mpls interfaces, 609
- show mpls ldp bindings, 503, 630–631
- show mpls ldp discovery, 613
- show mpls ldp neighbor, 494, 618, 639
- show mpls ldp parameters, 563
- show ppp mpe virtual-access number, 206
- show ppp multilink, 116, 121
- show route-map, 528
- show running-config, 67, 283
- show user, 63
- show vpdn, 204
- show vpdn history failure, 122, 342
- show vpdn session, 81, 205, 292
- show vpdn session all, 179, 343
- show vpdn tunnel, 120, 205
- show vpdn tunnel all, 68, 70, 79, 167, 277
- show 12tun tunnel all, 410
- tools, 6–8
- traceroute, 6–8, 476–479
- tunnel path-mtu-discovery, 689
- tunnel protection, 675
- vpdn domain-delimiter, 19
- vpdn multihop, 120
- vpdn search-order domain, 243
- vpdn session-limit sessions, 297
- vpdn softshut, 84, 296
- xconnect, 393
- Common Part Convergence Sublayer-Service Data Units (CPCS-SDUs), 581
- compression
 - ACFC, 268
 - MS-PPC, 93
 - PFC, 268
- Compression Control Protocol (CCP), 93
- compulsory tunnel modes, 135
 - IPSec, 252–254
 - L2TP, 237, 245
- conditional label advertisements, 506, 631–632
- CONFACK (Configure-Ack), 59, 269
- configuration
 - AAA, 44, 683
 - asynchronous group interfaces, 38
 - asynchronous interfaces, 240
 - asynchronous lines
 - L2TP, 239
 - parameters, 37
 - AToM, 588
 - CEF, 588
 - LDP Router ID, 589
 - loopback interfaces, 588
 - MPLS backbone IGP, 590–591
 - MPLS core interfaces, 589–590
 - pseudowires, 591–597
 - sample configurations, 597–605
 - specifying LDP, 589
 - troubleshooting, 605, 635
 - VC label exchanges, 636–645
 - attachment circuits, 378, 381
 - backbones, 449
 - CE routes, 446
 - CHAP, 240
 - classes, 377
 - clocks, 678
 - control channels, 138–142

- core interfaces, 467
- crypto access list, 673
- crypto maps, 674
- D channels, 238
- DNS addresses, 46
- dynamic crypto maps, 685
- dynamic sessions, 376–380
- E1/T1 controllers, 36, 238
- EBGP, 457
- EIGRP, 455
- Frame Relay trunks, 379
- gateways, 687
- global BGP parameters, 451
- global ISDN parameters, 37
- HDL, 596
- IKE policies, 670, 681, 683
- IP pools, 46
- IPSec VPNs, 668
 - MTU issues, 689–690
 - remote access, 682–688
 - site-to-site, 669–681
 - transform sets, 685
 - troubleshooting, 690–692
- ISDN D channels, 37
- IS-IS, 590
- L2F
 - Home Gateways, 43–48
 - maintenance, 32
 - management messages, 17–18
 - NAS, 35–43
 - PPP negotiation, 84–98
 - PPP on NAS, 58–69
 - sessions, 25–31, 80–84
 - teardown, 34–35
 - technical overview of, 12–17
 - troubleshooting, 48–58
 - tunneling, 18–25, 69–80
- L2TP
 - call reception, 260–265
 - case studies, 311
 - compulsory tunnel mode, 237, 245
 - IPSec, 252–255
 - LNS, 246, 252
 - negotiation, 297–311
 - PPP on LAC, 266–278
 - sessions, 290–297
 - troubleshooting, 255, 260
 - tunnels, 278–290
 - voluntary tunnel mode, 252
- L2TPv3, 375–388
 - MTU issues, 387–388
 - sample configurations, 382–387
 - troubleshooting, 389–410
- LAC, 237, 243
- LDP, 448
- LNS, 245
- loading, 767–771
- local authentication, 44, 249
- local username databases, 682
- MDTs, 466
- Microsoft CA servers, 679
- MPLS, 451
- MPLS Layer 3 VPNs, 445–459
 - P routers, 462–464
 - PE routers, 459–462
- MVPNs, 464–468
- OSPF, 456
- P routers, 465
- PAC, 158
- PE routers, 446, 450
- PE-CE routing protocols, 454
- PFS, 667
- PIM, 467
- PPTP, 155–159
 - PPP negotiation, 146–148
 - sessions, 142–146
- preshared keys, 670
- pseudowires
 - classes, 377, 380
 - troubleshooting AtoM, 636
- remote AAA, 39
 - case studies, 98–114
 - L2TP, 241
 - LNS, 249
- routers, 767–771
- SKYDANCE_POOL, 249
- split tunneling access lists, 684
- static routes, 454, 458
- static sessions, 380–382
- TDP/LDP router IDs, 448
- TE tunnels
 - between P routers, 472
 - MPLS VPNs, 468–473
- transform sets, 253, 671

- tunneling, 40, 44
- VFRs, 454
- virtual templates, 45, 247
- VPDNs
 - groups, 40, 44
 - L2TP, 242
 - LNS, 246
 - WIN addresses, 46
- Configure-Ack (CONFACK), 59, 269
- Configure-Reject (CONFREJ), 60, 270
- Configure-Request (CONFREQ), 59, 170
- connections
 - cabling, 767
 - control, 371–373, 390
 - DLCI-to-DLCI, 593
 - Frame Relay, 379
 - IP, 117, 419. *See also* VPNs
 - IPSec peers, 704
 - L2TPv3, 390
 - LDP neighbor discovery failures, 611
 - port-to-port, 593
 - PPP teardown, 89. *See also* PPP
 - PVP, 380
 - SAs, 660
 - IKE, 660–668
 - transports, 583
- conservative label retention, 427
- constrained shortest path (CSPF) algorithms, 429
- Constraint-based Routed Label Distribution Protocol (CR-LDP), 424
- control channels
 - configuration, 138–142
 - messages, 216
 - PPTP
 - maintenance, 148–150
 - messages, 154
 - termination, 150–153
 - troubleshooting, 163–168
- Control Connection IDs, L2TPv3, 361
- control connections, 371–372
 - maintenance, 373
 - management AVPs, 224, 366
 - teardown, 374
 - troubleshooting, 390
- control messages
 - L2TP, 215, 220–227
 - L2TPv3, 359, 362, 364
- control planes, MPLS, 425
- control VC mismatches, 616
- control words, 579–580
 - ATM AAL5 CPCS-SDU, 581
 - Frame Relay, 580
- controllers, E1/T1, 36, 238
- cookies, values, 370
- copying configuration files, 771
- core interfaces. *See also* interfaces
 - MPLS, 448, 589–590, 610
 - PIM, 467
- CPCS-SDUs (Common Part Convergence Sublayer-Service Data Units), 581
- Create New VPN Connection Entry Wizard, 685
- CRL (certificate revocation list), 680
- CRL distribution point (CDP), 718
- crl optional command, 680, 718
- (crl) query command, 718
- CR-LDP (Constraint-based Routed Label Distribution Protocol), 424
- crypto access lists. *See also* access lists
 - asymmetric, 726
 - configuration, 673
 - misconfiguration, 699
 - reconfiguration of, 700
- crypto ca authenticate name command, 680
- crypto ca enroll name command, 680
- crypto ca identity command, 679
- crypto ipsec transform-set command, 667
- crypto isakmp key key address peer_address command, 670
- crypto isakmp policy command, 663
- crypto isakmp sa command, 714
- crypto map command, 674–675
- crypto maps
 - configuration, 674
 - deleting, 698
 - DN, 730
 - identity lists, 731
 - interfaces, 674, 686
 - troubleshooting, 698
- crypto transform-set command, 671
- CSPF (constrained shortest path) algorithms, 429
- customer edge (CE) devices, 358

D

D channels

- configuration, 37
- L2TP, 238

Data Encryption Standard (DES), 658

data MDTs, configuration, 466. *See also* MDT

data messages

- L2TP, 215
- L2TPv3, 369

data planes, MPLS, 425

data tunnels, 137

databases

- local username, 682
- SAD, 660
- SPD, 660

dCEF (distributed CEF)

- AToM, 588
- enabling, 376

debug aaa authentication command, 105

debug aaa authorization command, 99

debug commands, 6–8

- IPSec, 750–751
- L2F, 129–130
- L2TP, 351
- MPLS VPNs, 569–571

debug crypto ipsec command, 749

debug crypto isakmp command, 692, 702, 723

debug frame-relay events command, 650

debug isdn q931 command, 55, 263

debug modem command, 264

debug mpls atm-ldp api command, 501

debug mpls l2transport packet {data | error} command, 650

debug mpls l2transport signaling command, 649

debug mpls l2transport vc event command, 640

debug mpls ldp advertisements command, 567

debug mpls ldp bindings command, 568

debug mpls ldp messages command, 567

debug mpls ldp transport events command, 566

debug mppe packet command, 207

debug ppp authentication command, 65, 91, 300

debug ppp mppe detailed command, 208

debug ppp mppe event command, 207

debug ppp negotiation command, 62, 65, 87, 181, 267, 273–274, 300

debug radius command, 106, 315

debug vpdn error command, 123, 209, 344

debug vpdn event command, 123, 209, 275

debug vpdn l2tp-sequencing command, 414

debug vpdn l2x-data command, 124, 345

debug vpdn l2x-errors command, 81, 294

debug vpdn l2x-events command, 69, 279, 281

debug vpdn l2x-packets command, 124, 346, 416

debug vpdn packet command, 126, 347, 415

debug vtemplate command, 85, 168, 298

debug xconnect event command, 414

declarations, CAs, 679

default Multicast Distribution Tree (default MDT), 443, 466

default routes, adding, 697

deleting

- access lists, 706, 735
- conditional label advertisements, 632
- crypto maps, 698
- import maps, 531
- VPDN session limitations, 83

demultiplexer fields, VC labels, 578

deny any statement, 490

Department of Defense (DoD) models, 4

DES (Data Encryption Standard), 658

devices

- CE, 358
- NAT, 359, 735

DF (Don't Fragment), 388, 689

diagrams, baselining networks, 3

Dialed Number Identification Service (DNIS), 228

Dialed Number Information Service (DNIS), 19

Diffie-Hellman public values, 667, 693

digital certificates, 664, 666, 677

digital subscriber line access multiplexer (DSLAM), 213

disabling

- CEF, 483, 633
- IPSec, 337
- ISAKMP, 702–703
- label assignments, 508
- MPLS, 609, 610
- VPDN softshut, 296

disconnections, 293. *See also* connections; troubleshooting

discovery (LDP)

- neighbors, 611
- PE peer routers, 637
- VC label exchanges, 582–586

- Distinguished Name (DN), 730
- distributed CEF (dCEF)
 - AToM, 588
 - enabling, 376
- distribution
 - CDP, 718
 - default MDT, 443
 - downstream LSRs, 426
 - label protocols, 428
 - MDT, 442
 - VPN routes, 436
- DLCI-to-DLCI connections, Frame Relay, 593
- DN (Distinguished Name), 730
- DNIS (Dial Number Identification Service), 228
- DNIS (Dial Number Information Service), 19
- DNS (Domain Name Service)
 - addresses
 - configuration, 46
 - L2TP, 248
 - PPTP, 158
- DoD (Department of Defense) models, 4
- domains
 - MD, 441
 - names, 67
- Don't Fragment (DF), 388, 689
- downstream LSRs, 426
- downstream-on-demand label distribution, 426
- DSLAM (digital subscriber line access multiplexer), 213
- dynamic crypto maps, configuration, 685. *See also* crypto maps
- dynamic sessions (L2TPv3)
 - configuration, 376–380
 - sample configurations, 382–387
 - troubleshooting, 400

E

- E1 controllers
 - configuration, 36, 238
 - remote alarms, 54
- EBGP (Enhanced BGP), configuration, 457
- Echo-Reply messages, PPTP, 149
- Echo-Request messages, PPTP, 148
- ED (Multilink-Endpoint-Discriminator), 270
- egress LSRs, penultimate hop popping, 421
- egress PE routers, troubleshooting, 520
- EIGRP (Enhanced IGRP), configuration, 455
 - elements, FEC, 584
 - enabling, 242
 - AAA, 683
 - AToM, 588
 - CEF, 376, 447
 - dCEF, 376
 - loopback interfaces, 621
 - MPLS TE, 469
 - multicasting, 466
 - MVRFs, 466
 - VPDNs, 40, 44
 - L2TP, 242
 - LNS, 246
- Encapsulating Security Payload (ESP), 658–659
 - encapsulation
 - AAL5, 594
 - AH, 657
 - AToM pseudowires, 591–597
 - Ethernets, 378, 592
 - Frame Relay, 378, 592
 - HDLC, 380, 596
 - Layer 3 MPLS VPNs, 420
 - PPP, 240, 380
 - MPLS, 594
 - VLAN (802.1Q) interfaces, 378
 - encoding
 - AVPs, 221
 - RD, 431–432
 - encryption. *See also* security algorithms, 671
 - ESP, 658
 - ESP DES, 253
 - end-to-end troubleshooting, 5
- Enhanced BGP (EBGP), configuration, 457
- Enhanced GRE headers, 147
- Enhanced IGRP (EIGRP), configuration, 455
- enrollment, CAs, 680, 736
- enrollment mode ra command, 679
- error codes. *See also* troubleshooting
 - CDN, 294
 - L2TPv3, 365–366
 - PPTP, 142
 - values, 224
- error messages
 - L2TP, 348–351
 - VPDNs, 126

ESP (Encapsulating Security Payload), 658–659
 access lists, 733
 DES encryption, 253
 establishment of IPSec tunnels, 732
 Ethernets. *See also* connections; servers
 control words, 582
 encapsulation, 378, 592
 port mode attachment circuits, 592
 VLAN (802.1q) mode, 592
 exchanges
 Diffie-Hellman public values, 693
 ISAKMP, 694
 quick mode, 721. *See also* quick mode
 routes, 452
 VC labels, 582–586, 636–645
 Experimental (EXP) field, 422
 export map misconfigurations, 526
 export route target mismatches, 525
 extended authentication (XAuth), 682
 extended discovery, LDP, 582
 external access lists, deleting, 735
 external interfaces. *See also* interfaces
 access lists, 705
 crypto maps
 applying to, 674, 686
 deleting, 698
 troubleshooting, 698

F

failure codes, session/tunnel setup, 35
 FCS (Frame Check Sequence), 231
 FEC (Forwarding Equivalence Class), 421, 584
 fields
 Flags, 581
 Interface Parameters, 585
 Label, 422
 Magic Cookie, 139
 StopCCRQ packet, 152
 TTL, 422
 values, 14
 files, configuration, 767–771
 firewalls, 359. *See also* security
 AH/ESP, 733
 ISAKMP, 705
 Flags field, 581

flowcharts
 IPSec VPN troubleshooting, 690
 L2F, 48–58
 PPTP, 160
 FORCED CONFACK, 88
 FORCED CONFREQ, 300
 FORCED LCP CONFREQ, 88
 formats
 control channels, 138–142
 Echo-Reply messages, 149
 Echo-Request messages, 149
 OCRQ messages, 142–146
 packets (L2F), 12
 RD, 431
 SLI packets, 154
 forwarding
 frames (PPTP), 146–148
 L2F, 11. *See also* L2F
 MDT, 444
 MPLS, 421
 PPP frames, 29
 traffic, 437
 VPNs, 433. *See also* VPNs
 VRF, 433
 Forwarding Equivalence Class (FEC), 421, 584
 Frame Check Sequence (FCS), 231
 Frame Relay
 AToM, 592
 control words, 580
 DLCI-to-DLCI connections, 593
 encapsulation, 378
 port-to-port connections, 593
 transports, 579
 trunks, 379
 frame-mode, MPLS, 422
 frames
 forwarding (PPTP), 146–148
 L2TPv3, 357. *See also* L2TPv3
 PPP, 29
 functions, 662. *See also* commands

G

gateways
 IPSec remote access, 687
 SAs, 660–668

- generation of RSA key pairs, 679
- global BGP parameters, configuration, 451
- global ISDN parameters
 - configuration, 37
 - L2TP, 238
- groups
 - asynchronous interfaces, configuration, 38
 - VPDNs
 - configuration, 40, 44
 - creating virtual templates, 45
 - L2TP, 242
 - LNS, 246
 - misconfiguration of domain names, 67
 - PPTP, 156
 - reconfiguration, 284
 - VPN client policy profiles, 684

H

- hash algorithms, 671, 712, 724
- HDLC (High-level Data-Link Control)
 - control words, 582
 - encapsulation, 380, 596
- head-end (PE) routers, configuration, 469
- headers
 - AH, 657
 - Enhanced GRE, 147
 - ESP, 658–659
 - IP over L2TPv3, 360
 - packets, 12
 - session data messages, 369
 - shim, 422
- hello messages, L2TP, 233
- Hidden (H) bits, 221
- hiding AVPs, 215
- Home Gateways
 - CLID, 15
 - MIDs, 14
 - L2F
 - configuration, 43–48
 - PPP negotiation, 84–98
 - tunnel failures, 114, 122
 - L2F_CONF messages, 21
 - L2F_OPEN messages, 27
 - passwords, 90
 - PPP frames, 29
- hops, penultimate hop popping, 421
- hostnames, 678

- ICCN (Incoming-Call-Connected), 226, 373
- ICMP (Internet Control Message Protocol), 388
- ICRP (Incoming-Call-Reply) messages, 230, 373
- ICRQ (Incoming-Call-Request) messages, 230, 372
- identity lists crypto maps, 731
- identification
 - CLIDs, 16
 - LDP neighbors, 494
 - routers, 448
- IETF (Internet Engineering Task Force), 214
- IGP (Interior Gateway Protocol)
 - backbones
 - configuration, 449
 - troubleshooting, 479–481
 - MPLS, 590–591
- IKE (Internet Key Exchange), 660–668, 713
 - AAA, 686
 - phase 1, 662, 692–718
 - phase 2, 667, 719–733
 - policies, 712
 - configuration, 670, 681–683
 - mismatches, 709
 - remote VPN clients, 740
 - SAs, 712
- import maps
 - deleting, 531
 - ingress PE routers, 529
- import route target mismatches, 525
- inbound traffic, 439
- incoming FORCED CONFREQ, 300
- Incoming-Call-Connected (ICCN), 226, 373
- Incoming-Call-Reply (ICRP) messages, 230, 373
- Incoming-Call-Request (ICRQ) messages, 230, 372
- independent LSP control, 425
- ingress PE routers
 - import maps, 529
 - redistribution, 531
- initialization of L2F tunnels, 69
- initialization vector (IV), 722
- initiation
 - IKE negotiation, 696
 - quick mode negotiation, 729
- initiators, 663
 - IP addressees, 704
 - responders, 707
 - routing, 697

- installation of PE routers, 520
- instances
 - forwarding, 433
 - VFR, 453
 - VRF, 433
- Interface Parameters field, 585
- interfaces
 - access lists, 705, 735
 - asynchronous, 38, 240
 - asynchronous group
 - BGP, 467
 - core
 - configuration MPLS, 448
 - disabling MPLS, 610
 - MPLS, 589–590
 - PIM, 467
 - crypto maps
 - applying to, 674, 686
 - deleting, 698
 - troubleshooting, 698
 - Ethernet encapsulation, 378
 - LC-ATM, 449, 491, 625
 - loopback
 - configuration, 376
 - IS-IS, 621
 - PE routers, 447
 - misconfigurations, 513
 - MPLS, 610
 - MPLS TE, 469, 472
 - MTI, 442
 - PRIs, 36, 263
 - VFRs, 454
 - virtual access, 297
 - virtual templates, 247
 - VPNs, 440
 - VRF, 467
- Intermediate System-to-Intermediate System.
 - See* IS- IS
- Internet access
 - interfaces, 440
 - VPNs, 439
- Internet Control Message Protocol (ICMP), 388
- Internet Engineering Task Force (IETF), 214
- Internet Key Exchange. *See* IKE
- interprovider VPNs, 419. *See also* VPNs
- IP (Internet Protocol)
 - addresses
 - local pools, 683
 - misconfigurations, 700, 704
 - mismatches, 644
 - overlapping, 430
 - peer LCCE misconfiguration, 393
 - PPTP, 158
 - virtual templates, 97
 - backbones, 11
 - connectivity, 117
 - crypto access lists, 673
 - L2TPv3 control message header over, 360
 - pools
 - creating, 46
 - L2TP, 248
 - VPNs, 419. *See also* VPNs
 - ip dfbit set command, 388
 - ip domain-name command, 678
 - ip local pool command, 683
 - ip ospf network point-to-point command, 447
 - ip pim sparse-dense-mode command, 465
 - ip pmtu command, 388
 - IP Security (IPSec), L2TP, 236
 - ip unnumbered command, 310
 - IPCP (Internet Protocol Control Protocol)
 - CONFREQ, 93
 - negotiation, 187
 - IPSec (IP Security), 655
 - case studies, 736–746
 - commands, 747–751
 - configuration, 668
 - IKE, 660–668
 - L2TP, 236, 252–255
 - disabling, 337
 - over with preshared keys, 339
 - lab solutions, 774–775
 - MTU issues, 689–690
 - NAT devices, 735
 - remote access, 682–688
 - SAs, 660, 721
 - security protocols, 656–659
 - site-to-site, 669–681
 - technical overview of, 656–668
 - transform sets, 671, 723
 - troubleshooting, 690–692
 - tunnels, 732

- ISAKMP (Internet Security Association and Key Management Protocol), 660–661
 - disabling, 702–703
 - exchanges, 694
 - firewalls, 705
 - messages, 703
 - presared keys, 670
 - re-enabling, 703
- ISDN (Integrated Services Digital Network), 37
- IS-IS (Intermediate System-to-Intermediate System)
 - advertisements, 496
 - loopback interfaces, 621
 - MPLS backbone IGP, 590
 - PE routers, 450
- IV (initialization vector), 722

K

- keepalives
 - L2F, 32
 - L2TP, 233
 - PPTP, 150
- keys, 679
 - IKE, 660. *See also* IKE
 - L2F calculations, 16
 - presared key authentication, 663
- keywords
 - additive, 529
 - any, 730

L

- L (Cell Loss Priority, CLP) bit, 582
- L2F (Layer 2 Forwarding) Protocol, 11
 - commands, 122–126
 - debug, 129–130
 - show, 129–130
 - Home Gateways, 43–48
 - maintenance, 32
 - management messages, 17–18
 - messages
 - L2F_CLOSE messages, 34
 - L2F_CONF messages, 19, 21
 - L2F_ECHO messages, 32
 - L2F_OPEN message, 22, 25

- NAS, 35–43
- PPP, 58–69, 84–98
- sessions, 25–31, 80–84
- teardown, 34–35
- technical overview of, 12–17
- troubleshooting, 48–58
- tunneling, 18–25, 114, 122
 - misconfiguration on AAA servers, 99–105
 - troubleshooting, 69–80
- VPDNs, 126
- L2TP (Layer Two Tunneling Protocol), 213. *See also* L2TPv2; L2TPv3
 - AVPs, 213. *See also* AVPs
 - case studies, 311
 - AAA server unreachable, 331–342
 - misconfiguration (AAA RADIUS servers), 312–322
 - remote AAA authentication failure, 322–326
 - remote AAA authorization failure, 326
 - commands, 342–348
 - compulsory tunnel mode, 237
 - control messages, 220–227
 - debug commands, 351
 - error messages, 348–351
 - establishment, 227
 - hello messages, 233
 - IPSec, 252–255
 - disabling, 337
 - over with presared keys, 339
 - keepalives, 233
 - LAC
 - call reception, 260–265
 - PPP, 266–278
 - LNS, 246
 - maintenance, 232
 - messages, 234–235
 - negotiation, 297–311
 - outgoing calls, 235–236
 - security, 236
 - sessions, 230–232, 290–297
 - show commands, 351
 - teardown, 233
 - technical overview of, 215–220
 - troubleshooting, 255
 - tunnels, 278–290
 - voluntary tunnel mode, 252
- L2TP Access Concentrator. *See* LAC

- l2tp hidden command, 229
- L2TP Network Server. *See* LNS
- L2TPv2 (Layer Two Tunneling Protocol Version 2), 773
- L2TPv3 (Layer Two Tunneling Protocol Version 3), 357
 - asymmetric payload types, 405
 - class configuration, 377
 - commands, 410–417
 - configuration, 375–388
 - control connections, 371–372
 - maintenance, 373
 - messages, 359–371
 - MTU issues, 387–388
 - sample configurations, 382–387
 - sessions, 372
 - SLI, 375
 - teardown, 374
 - technical overview of, 358
 - troubleshooting, 389–409
- L2TPv3 control connection endpoints (LCCEs), 359
- lab routers
 - configuration files, 768–770
 - troubleshooting, 771–775
- lab routers, 768. *See also* routers
- lab solutions, troubleshooting, 771–775
- Label Controlled ATM (LC-ATM) interfaces, 449
- Label Distribution Protocol (LDP), 424, 428, 578
- Label field, 422
- Label Forwarding Information Base (LFIB), 424, 627
- Label Information Base (LIB), 424
- label switched path (LSP), 420
- labels
 - assignments, 508
 - AToM, 577. *See also* AToM
 - bindings
 - advertisements, 502
 - peer LSR, 628
 - verifying, 626
 - conditional advertisements, 506, 631
 - distribution protocols, 428
 - messages
 - mapping, 584
 - withdraw, 586
 - MPLS, 422
 - retention, 427
 - stacks, 423
 - VC exchanges, 578, 582–586, 636–645
- LAC (L2TP Access Concentrator), 213
 - call reception, 260–265
 - configuration, 237, 243
 - L2TPv3
 - configuration, 375–388
 - control connections, 371–373
 - messages, 359–371
 - sessions, 372
 - SLI, 375
 - teardown, 374
 - technical overview of, 358
 - troubleshooting, 389–410
 - partial PPP authentication failures, 273
 - PPP on, 266–278
- Layer 2
 - AToM, 577. *See also* AToM
 - sublayers, 371
- Layer 3, 419. *See also* VPNs
- Layer Two Forwarding Protocol. *See* L2F
- Layer Two Tunneling Protocol Version 2. *See* L2TPv2
- Layer Two Tunneling Protocol Version 3. *See* L2TPv3
- Layer Two Tunneling Protocol. *See* L2TP
- LC-ATM (Label Controlled ATM) interfaces, 449
- LC-ATM interfaces
 - troubleshooting, 491
 - VPI ranges, 625
- LCCEs (L2TPv3 control connection endpoints), 359
 - IP address misconfigurations, 393
 - L2TPv3 sample configurations, 382–387
 - routers
 - dynamic sessions (L2TPv3), 376–380
 - static sessions (L2TPv3), 380–382
 - VCID mismatches, 403
- LCP (Link Control Protocol)
 - negotiation, 18, 228, 266
 - proxy AVPs, 226
 - troubleshooting, 58, 86, 169–176
- lcp renegotiation command, 297
- LDP (Label Distribution Protocol), 424, 428, 578
 - access lists, 622
 - AToM
 - loopback interfaces, 588
 - Router ID, 589
 - specifying, 589
 - authentication
 - mismatches, 499
 - troubleshooting, 624

- configuration, 448
- control VC mismatches, 616
- mismatches, 488
- neighbor discovery
 - peer PE routers, 637
 - troubleshooting, 611
- password mismatches, 500
- PE routers, 637
- sessions
 - PE routers, 639
 - troubleshooting, 493, 618
- tunnel LSP establishment, 611
- updating, 447
- VC label exchanges, 582–586
- leaking packets, 439
- LFIB (Label Forwarding Information Base), 424, 504, 627
- LIB (Label Information Base), 424
- liberal label retention, 427
- limitations, sessions, 83
- Link Control Protocol. *See* LCP
- LNS
 - AAA severs unreachable from, 331–342
 - CDN, 293
 - configuration, 246, 252
 - L2TP, 246, 252
 - L2TPv3
 - control connections, 371–373
 - messages, 359–371
 - sessions, 372
 - SLI, 375
 - teardown, 374
 - technical overview of, 358
 - RADIUS
 - authentication failures, 322
 - authorization failures, 326
 - VPDNs, 246
- LNS (L2TP Network Server), 5, 213
- loading configuration files, 767–771
- local authentication
 - configuration, 44
 - LNS, 249
 - PAC, 158
- local IP address pool configuration, 683
- local username database configuration, 682
- locating LSP tunnels, 607

- loopback interfaces. *See also* interfaces
 - AToM, 588
 - configuration, 376
 - IS-IS, 621
 - PE routers, 447
- loss of alarm signals, 262
- loss of signals, 54
- LSPs (label switched paths), 420
 - AToM, 607
 - independent control, 425
 - MPLS VPNs, 481–511
 - ordered control, 425
 - tunnels, 611, 626
- LSRs (Labeled Switched Routers)
 - downstream, 426
 - label retention, 427
- LDP
 - neighbor discovery failures, 611
 - session failures, 618
 - penultimate hop popping, 421

M

- Magic Cookie field, 139
- Magic Numbers, 59
- main mode negotiation, 663
 - failure of, 692–718
 - RSA signature authentication, 664
- maintenance. *See also* troubleshooting
 - L2F, 32
 - L2TP, 232
 - L2TPv3, 373
 - PPTP, 148–150
 - tunneling, 32
- management
 - IKE, 660–668
 - L2F messages, 17–18
- mandatory (M) bits, 221
- maps, 678
 - ACCM, 227
 - crypto
 - applying to interfaces, 674, 686
 - configuration, 674
 - deleting, 698
 - DN, 730
 - troubleshooting, 698

- dynamic crypto, 685
- export map misconfiguration, 526
- import
 - deleting, 531
 - ingress PE routers, 529
- label messages, 584
- Maximum Segment Size (MSS), 690
- Maximum Transmission Unit (MTU), 387–388
- MD (Multicast Domains), 441
- MD5 (Message Digest 5)
 - hash algorithms, 712
 - calculating, 19
- Message Digest 5. *See* MD5
- Message Type AVP, 222
- messages
 - CDN, 233, 364
 - control channels (ZLB Ack), 216
 - Echo-Reply (PPTP), 149
 - Echo-Request (PPTP), 148
 - error. *See* error messages
 - hello (L2TP), 233
 - ICMP, 388
 - ICRP, 230
 - ICRQ, 230
 - ISAKMP, 661, 703
 - L2F, 17–18
 - L2F_CLOSE, 34
 - L2F_CONF, 19, 21
 - L2F_ECHO, 32
 - L2F_OPEN, 22, 25
 - L2TP, 220–227, 234–235
 - L2TPv3, 359–371
 - labels, 584–586
 - OCCN, 235
 - OCRP, 144, 235
 - OCRQ, 142–146, 235
 - PPTP, 154
 - PPTP Control, 138
 - SCCCN, 229, 372
 - SCCRP, 229, 371
 - SCCRQ, 139, 229, 371
 - SLI, 234, 375
 - StopCCN, 234, 364
 - TERMACK, 90
 - TERMREQ, 90
 - WEN, 234
- Microsoft CA servers, configuration, 679
- Microsoft Point-to-Point Compression (MS-PPC), 93
- Microsoft Point-to-Point Encryption (MPPE)
 - attributes not returned, 197–203
 - negotiation, 180
- MID (multiplex ID), 14
- midpoint router configuration, 472
- misconfigurations
 - crypto access lists, 699
 - export maps, 526
 - interfaces, 513
 - IP addresses, 704
 - L2TP, 312–322
 - peer addresses, 700
 - peer IP addresses, 644
 - peer LCCE IP addresses, 393
 - preshared keys, 714
 - static routes, 514
- mismatches
 - authentication password, 624
 - IKE policies, 709
 - IP addresses, 644
 - IPSec transform sets, 723
 - LDP, 488
 - authentication, 499
 - passwords, 500
 - MTU, 643
 - Peer LCCE VCIDs, 403
 - proposals, 711
 - targets, 525
 - VC ID, 642
 - VC types, 640
 - VPDN, 72, 281
- MMP (Multichassis Multilink PPP), 213
- models
 - DoD, 4
 - L2TPv3. *See* L2TPv3
 - OSI, 4
 - VPNs. *See* VPNs
- modems, verifying call reception, 56. *See also* connections
- modes
 - aggressive negotiation, 665
 - AH, 657
 - ESP, 658
 - main, 663, 692–718
 - MPLS, 422–423
 - PIM-DM, 442
 - PIM-SM, 442
 - quick, 668, 719–733

modification

- AAA, 44, 683
- access lists, 729
- asynchronous group interfaces, 38
- asynchronous interfaces, 240
- asynchronous lines
 - L2TP, 239
 - parameters, 37
- AToM, 588
 - CEF, 588
 - LDP Router ID, 589
 - loopback interfaces, 588
 - MPLS backbone IGP, 590–591
 - MPLS core interfaces, 589–590
 - pseudowires, 591–597
 - sample configurations, 597–605
 - specifying LDP, 589
 - troubleshooting, 605, 635
 - VC label exchanges, 636–645
- attachment circuits, 378, 381
- backbones, 449
- CE routes, 446
- CHAP, 240
- classes, 377
- clocks, 678
- control channels, 138–142
- core interfaces, 467
- crypto access list, 673
- crypto maps, 674
- D channels, 238
- DNS addresses, 46
- dynamic crypto maps, 685
- dynamic sessions, 376–380
- E1/T1 controllers, 36, 238
- EBGP, 457
- EIGRP, 455
- Frame Relay trunks, 379
- gateways, 687
- global BGP parameters, 451
- global ISDN parameters, 37
- HDL, 596
- IKE policies, 670, 681, 683
- IP pools, 46
- IPSec VPNs, 668
 - MTU issues, 689–690
 - remote access, 682–688
 - site-to-site, 669–681

- transform sets, 685
- troubleshooting, 690–692

- ISDN D channels, 37

- IS-IS, 590

- L2F

- Home Gateways, 43–48
- maintenance, 32
- management messages, 17–18
- NAS, 35–43
- PPP negotiation, 84–98
- PPP on NAS, 58–69
- sessions, 25–31, 80–84
- teardown, 34–35
- technical overview of, 12–17
- troubleshooting, 48–58
- tunneling, 18–25, 69–80

- L2TP

- call reception, 260–265
- case studies, 311
- compulsory tunnel mode, 237, 245
- IPSec, 252–255
- LNS, 246, 252
- negotiation, 297–311
- PPP on LAC, 266–278
- sessions, 290–297
- troubleshooting, 255, 260
- tunnels, 278–290
- voluntary tunnel mode, 252

- L2TPv3, 375–388
 - MTU issues, 387–388
 - sample configurations, 382–387
 - troubleshooting, 389–410

- LAC, 237, 243

- LDP, 448

- LNS, 245

- local authentication, 44, 249

- local username databases, 682

- MDTs, 466

- Microsoft CA servers, 679

- MPLS, 451

- MPLS Layer 3 VPNs, 445–459

- P routers, 462–464

- PE routers, 459–462

- MVPNs, 464–468

- OSPF, 456

- P routers, 465

- PAC, 158

- PE routers, 446, 450
- PE-CE routing protocols, 454
- PFS, 667
- PIM, 467
- PPTP, 155–159
 - PPP negotiation, 146–148
 - sessions, 142–146
- preshared keys, 670
- pseudowires
 - classes, 377, 380
 - troubleshooting AtoM, 636
- remote AAA, 39
 - case studies, 98–114
 - L2TP, 241
 - LNS, 249
- routers, 767–771
- SKYDANCE_POOL, 249
- split tunneling access lists, 684
- static routes, 454, 458
- static sessions, 380–382
- TDP/LDP router IDs, 448
- TE tunnels
 - between P routers, 472
 - MPLS VPNs, 468–473
- transform sets, 253, 671
- tunneling, 40, 44
- VFRs, 454
- virtual templates, 45, 247
- VPDNs
 - groups, 40, 44
 - L2TP, 242
 - LNS, 246
 - WIN addresses, 46
- moving configuration files, 771
- MP (Multilink PPP), 135
- MP-BGP (Multiprotocol Extensions for BGP-4), 428
- MP-BGP, 429
 - activating, 452
 - redistribution, 531
 - route redistribution, 458, 531
- MPLS (multiprotocol label switching)
 - AAL5 over configuration, 594
 - AtoM, 507, 609
 - backbone IGP, 590–591
 - control planes, 425
 - core interfaces, 589–590
 - data planes, 425
 - disabling, 609
 - forwarding, 421
 - HDLC over encapsulation, 596
 - interfaces, 610
 - lab solutions, 773–774
 - labels, 422
 - Layer 3 VPNs
 - configuration, 445–459
 - P router configuration, 462–464
 - PE route sample configuration, 459–462
 - technical overview of, 420–445
 - modes, 422
 - cell-mode, 423
 - frame-mode, 422
 - OSPF configuration, 451
 - TE tunnel configuration, 468–473
 - verifying, 484
 - VPNs
 - case studies, 536–560
 - commands, 560–571
 - troubleshooting, 473–536
- mpls ip command, 449, 589, 611
- mpls label protocol ldp command, 589
- mpls ldp advertise-labels command, 630
- MPPE (Microsoft Point-to-Point Encryption)
 - attributes not returned, 197–203
 - negotiation, 180
- MRRU (Multilink-Maximum-Reconstructed-Receive-Unit), 269
- MS-PPC (Microsoft Point-to-Point Compression), 93, 182
- MSS (Maximum Segment Size), 690
- MTI (Multicast Tunnel Interface), 442
- MTU (Maximum Transmission Unit), 387
 - AtoM, 602
 - IPSec VPNs, 689–690
 - L2TPv3, 387–388
 - mismatches, 643
- mtu command, 248
- Multicast Domains (MD), 441
- Multicast Tunnel Interface (MTI), 442
- Multicast VPNs (MVPNs), 441. *See also* VPNs
- Multicast VRF (MVRF), 442
- multicasting, enabling, 466
- Multichassis Multilink PPP (MMP), 213
- Multilink PPP (MP), 135
- Multilink-Endpoint-Discriminator (ED), 270

Multilink-Maximum-Reconstructed-Receive-Unit (MRRU), 269
 multiple sessions, tunneling, 15
 multiplex ID (MID), 14
 Multiprotocol Extensions for BGP-4 (MP-BGP), 428
 multiprotocol label switching. *See* MPLS
 MVPNs (Multicast VPNs), 441. *See also* VPNs
 CE routers, 464
 configuration, 464–468
 PE routers, 465, 467
 MVRF (Multicast VRF), 442, 466

N

names
 domains
 routers, 678
 VPDNs, 67
 hostnames, 678
 NAS (Network Access Server), 11
 call reception, 52
 L2F
 configuration, 35–43
 PPP, 58–69
 sessions, 80–84
 tunneling, 69–80
 L2F_OPEN, 22, 25
 LCP negotiation failures, 58
 PPP frames, 29
 NAT (Network Address Translation), 359, 735
 NCP (Network Control Protocol), 58, 231
 failure on LNS, 304
 troubleshooting, 91, 180–197
 negotiation
 aggressive mode, 665
 CCP, 184
 IKE
 remote VPN client failure, 740
 SAs, 712
 IPCP, 187
 L2TP
 case studies, 311
 troubleshooting, 297–311
 LCP, 18, 228, 266
 main mode, 663, 692–718
 MPPE, 180

NCP, 58, 91, 180–197, 231
 PPP, 146–148
 quick mode, 668, 719–733
 termination, 185
 troubleshooting, 58, 86, 169–176
 neighbors
 LDP, 494, 611, 637
 MP-BGP, 452
 Network Access Server. *See* NAS
 Network Control Protocol. *See* NCP
 Network Time Protocol (NTP), 678
 networks
 baselining, 3
 MPLS, 577
 no auto-summary command, 453
 no mpls ldp advertise-labels command, 504
 no vpdn softshut command, 296
 NONCE payloads, 663, 720
 NTP (Network Time Protocol), 678

O

O (Offset) bits, 360
 Oakley Key Determination Protocol (RFC 2412), 660
 OCCN (Outgoing-Call-Connected) messages, 235
 OCRP (Outgoing-Call-Reply) messages, 144, 235
 OCRQ (Outgoing-Call-Request) messages, 142–146, 235
 offload servers, L2F tunnel failures, 114, 122
 Offset pad field, 219
 Offset size field, 219
 Open Shortest Path First. *See* OSPF
 Open Systems Interconnection. *See* OSI
 optimization
 L2F management messages, 17
 MDT, 444
 options
 AAA, 44, 683
 access lists, 729
 asynchronous group interfaces, 38
 asynchronous interfaces, 240
 asynchronous lines
 L2TP, 239
 parameters, 37
 AToM, 588
 CEF, 588

- LDP Router ID, 589
- loopback interfaces, 588
- MPLS backbone IGPs, 590–591
- MPLS core interfaces, 589–590
- pseudowires, 591–597
- sample configurations, 597–605
- specifying LDP, 589
- troubleshooting, 605, 635
- VC label exchanges, 636–645
- attachment circuits, 378, 381
- backbones, 449
- CE routes, 446
- CHAP, 240
- classes, 377
- clocks, 678
- control channels, 138–142
- core interfaces, 467
- crypto access list, 673
- crypto maps, 674
- D channels, 238
- DNS addresses, 46
- dynamic crypto maps, 685
- dynamic sessions, 376–380
- E1/T1 controllers, 36, 238
- EBGP, 457
- EIGRP, 455
- Frame Relay trunks, 379
- gateways, 687
- global BGP parameters, 451
- global ISDN parameters, 37
- HDL, 596
- IKE policies, 670, 681, 683
- IP pools, 46
- IPSec VPNs, 668
 - MTU issues, 689–690
 - remote access, 682–688
 - site-to-site, 669–681
 - transform sets, 685
 - troubleshooting, 690–692
- ISDN D channels, 37
- IS-IS, 590
- L2F
 - Home Gateways, 43–48
 - maintenance, 32
 - management messages, 17–18
 - NAS, 35–43
 - PPP negotiation, 84–98
 - PPP on NAS, 58–69
 - sessions, 25–31, 80–84
 - teardown, 34–35
 - technical overview of, 12–17
 - troubleshooting, 48–58
 - tunneling, 18–25, 69–80
- L2TP
 - call reception, 260–265
 - case studies, 311
 - compulsory tunnel mode, 237, 245
 - IPSec, 252–255
 - LNS, 246, 252
 - negotiation, 297–311
 - PPP on LAC, 266–278
 - sessions, 290–297
 - troubleshooting, 255, 260
 - tunnels, 278–290
 - voluntary tunnel mode, 252
- L2TPv3, 375–388
 - MTU issues, 387–388
 - sample configurations, 382–387
 - troubleshooting, 389–410
- LAC, 237, 243
- LDP, 448
- LNS, 245
- local authentication, 44, 249
- local username databases, 682
- MDTs, 466
- Microsoft CA servers, 679
- MPLS, 451
- MPLS Layer 3 VPNs, 445–459
 - P routers, 462–464
 - PE routers, 459–462
- MVPNs, 464–468
- OSPF, 456
- P routers, 465
- PAC, 158
- PE routers, 446, 450
- PE-CE routing protocols, 454
- PFS, 667
- PIM, 467
- PPTP, 155–159
 - PPP negotiation, 146–148
 - sessions, 142–146
- preshared keys, 670
- pseudowires
 - classes, 377, 380
 - troubleshooting AttoM, 636

- remote AAA, 39
 - case studies, 98–114
 - L2TP, 241
 - LNS, 249
- routers, 767–771
- SKYDANCE_POOL, 249
- split tunneling access lists, 684
- static routes, 454, 458
- static sessions, 380–382
- TDP/LDP router IDs, 448
- TE tunnels
 - between P routers, 472
 - MPLS VPNs, 468–473
- transform sets, 253, 671
- tunneling, 40, 44
- VFRs, 454
- virtual templates, 45, 247
- VPDNs
 - groups, 40, 44
 - L2TP, 242
 - LNS, 246
- WIN addresses, 46
- ordered LSP control, 425
- OSI (Open System Interconnection), 4
- OSPF (Open Shortest Path First)
 - configuration, 456
- MPLS
 - backbone IGPs, 591
 - configuration, 451
- outbound traffic, 439
- outgoing calls, L2TP, 235–236
- Outgoing-Call-Connected (OCCN) messages, 235
- Outgoing-Call-Reply (OCRP) messages, 144, 235
- Outgoing-Call-Request (OCRQ) messages, 142–146, 235
- overlaps
 - IP address spaces, 430
 - VPI ranges, 625
- overlay VPN models, 419

P

- P (Priority) bits, 360
- P routers
 - configuration, 462–464
 - MVPN configuration, 465
 - TE tunnels, 472
- PAC (PPTP Access Concentrator), 135
 - CONFREQ, 170
 - local authentication, 158
 - PPTP termination, 153
- packets
 - AH, 657
 - control channels, 138–142
 - Echo-Reply messages, 149
 - Echo-Request messages, 148
 - ESP, 658–659
 - L2F formats, 12
 - L2TPv3, 376. *See also* L2TPv3
 - leaking, 439
 - MTU, 602
 - OCRQ messages, 142–146
 - payload options, 17
 - PPTP
 - maintenance, 148–150
 - messages, 154
 - termination, 150–153
 - SLI, 154
 - StopCCRQ fields, 152
 - TCP SYN, 690
 - tunneling, 16
- parameters
 - asynchronous lines configuration, 37, 239
 - global ISDN configuration, 37
 - interfaces, 469
- partial authentication, 228
- partial PPP authentication failures, 64, 273
- passwords
 - authentication, 624
 - LDP mismatches, 500
 - reconfiguration, 90, 107
 - tunnel reconfiguration, 79
- pasting configuration files, 771
- Path MTU Discovery (PMTUD), 689
- payloads, 662
 - asymmetric L2TPv3 types, 405
 - NONCE, 663, 720
 - packet options, 17
- PDU (protocol data units), 577
- PE (provider edge) routers, 358
 - advertisements, 512
 - AToM
 - CEF, 588
 - configuration, 588

- LDP Router ID, 589
- loopback interfaces, 588
- MPLS backbone IGPs, 590–591
- MPLS core interfaces, 589–590
- pseudowires, 591–597
- sample configurations, 597–605
- specifying LDP, 589
- troubleshooting, 605, 635
- VC label exchanges, 636–645
- CE route advertisement, 534
- configuration, 446
- import maps, 529
- installation, 520
- IS-IS configuration, 450
- MP_BGP route redistribution, 531
- MVPNs, 465–468
- routers
 - configuration, 459–462
 - IP address mismatches, 644
 - LDP, 637
 - LDP session failures, 639
- TE tunnels, 468–472
- VC label exchanges, 582–586
- VRF, 433
- PE-CE routing protocol
 - configuration, 454
 - MP-BGP redistribution, 531
 - troubleshooting, 514–516
- peer address misconfigurations, 700
- peer IP addresses reconfiguration, 704
- peer LACs, 359
- peer LCCEs
 - sample L2TPv3 configurations, 382
 - VCID mismatches, 403
- peer LSRs, 628
- peer PE routers, 644
- peers
 - adding default routes, 697
 - DN-based crypto maps, 730
 - IPSec
 - troubleshooting, 704
 - tunneling, 733–736
 - LC-ATM interfaces, 625
 - LDP authentication, 499
 - tunnel maintenance, 32
- peer-to-peer VPN model, 419
- penultimate hop popping, 421
- Perfect Forward Secrecy (PFS), 667
- permanent virtual path (PVP), 380
- PERRIS_POOL (IP pool), 46
- PFC (Protocol Field Compression), 59, 268
- PFS (Perfect Forward Secrecy), 667
- PIM (Protocol Independent Multicast), 428
 - adjacencies, 442
 - BGP, 467
 - CE routers, 464
 - PE routers, 465, 467
 - VRF interfaces, 467
- PIM Bi-directional (PIM-BIDIR), 442
- PIM Dense Mode (PIM-DM), 442
- PIM Source Specific Multicast (PIM-SSM), 442
- PIM Sparse-Mode (PIM-SM), 442
- PIM-BIDIR (PIM Bi-directional), 442
- PIM-DM (PIM Dense Mode), 442
- PIM-SM (PIM Sparse-Mode), 442
- PIM-SSM (PIM Source Specific Multicast), 442
- ping command, 6–8, 117, 704. *See also*
 - troubleshooting
 - MPLS VPNs, 476–479
 - tunnel LSP location, 607
- placement of crypto maps, verifying, 698
- platforms, routers, 767
- PMTUD (Path MTU Discovery), 689
- PNS (PPTP Network Server), 135
- Point-of-Presence (POP), 135, 213
- Point-to-Point Tunneling Protocol. *See* PPTP
- policies
 - IKE, 712
 - AAA, 686
 - configuration, 670, 681, 683
 - mismatches, 709
 - VPM client group profiles, 684
- pools (IP), 683
 - creating, 46
 - L2TP, 248
 - PPTP, 158
- POP (Point-of-Presence), 135, 213
- port mode, ATM cell relay, 596
- ports, Ethernets, 592
- port-to-port connections, Frame Relay, 593

- PPP (Point-to-Point Protocol), 11
 - authentication, 301
 - autodetection, 239
 - control words, 582
 - encapsulation, 240, 380
 - frames, 29
 - L2F negotiation, 84–98
 - LAC, 266–278
 - MMP, 213
 - MP, 135
 - NAS, 58–69
 - negotiation, 146–148
 - partial authentication failures, 64
 - PPTP, 135
 - teardown, 89
 - troubleshooting, 86, 176–180
- PPTP (Point-to-Point Tunneling Protocol), 135
 - authentication, 176–180
 - case studies
 - MPPE attributes not returned, 197–203
 - split tunnels, 203
 - commands, 204–210
 - configuration, 155–159
 - control channels
 - configuration, 138–142
 - troubleshooting, 163–168
 - debug commands, 210
 - frame forwarding, 146–148
 - keepalives, 150
 - LCP negotiation, 169–176
 - maintenance, 148–150
 - messages, 154
 - NCP negotiating, 180–197
 - PPP negotiation, 146–148
 - sessions
 - configuration, 142–146
 - troubleshooting, 163–168
 - show commands, 210
 - technical overview of, 137
 - termination, 150–153
 - troubleshooting, 159–162
 - virtual interfaces, 168–169
 - virtual templates, 156
- PPTP Access Concentrator. *See* PAC
- PPTP Network Server. *See* PNS
- preshared key authentication, 665
 - preshared keys
 - adding, 702
 - authentication, 663, 713
 - compulsory tunnel mode, 252–254
 - configuration, 670
 - L2TP, 339
 - misconfigurations, 714
 - responders, 707
 - site-to-site IPsec VPNs, 675
 - troubleshooting, 701
 - voluntary tunnel mode, 255
- PRI (Primary Rate Interface), 36, 263
- profiles, VPN client group policies, 684
- proposals
 - acceptances, 693
 - mismatches, 711
- Protocol Field Compression (PFC), 59, 268
- Protocol Independent Multicast (PIM), 428
- protocol none command, 381
- protocols
 - BGP, 447
 - CCP, 93
 - CHAP
 - configuration, 240
 - L2F tunnel establishment, 18
 - CR-LDP, 424
 - ICMP, 388
 - L2F, 11
 - L2TP, 213
 - call reception, 260–265
 - case studies, 311
 - compulsory tunnel mode, 237, 245
 - control messages, 220–227
 - establishment, 227, 229
 - IPsec, 252–255
 - LNS, 246, 252
 - maintenance, 232
 - messages, 234–235
 - outgoing calls, 235–236
 - PPP on LAC, 266–278
 - security, 236
 - sessions, 230–232, 290–311
 - teardown, 233
 - technical overview of, 215–220
 - troubleshooting, 255, 260
 - tunnels, 278–290
 - voluntary tunnel mode, 252

L2TPv3, 357
 label distribution, 428
 LCP negotiation, 18
 LDP, 424, 428, 578
 configuration, 448
 updating, 447
 NCP negotiation, 58, 91, 231
 NTP, 678
 PE-CE routing, 454, 514–516
 PPP, 11
 forwarding frames, 29
 NAS, 58–69
 partial authentication failures, 64
 PPTP, 135
 RSVP, 424
 security, 656–659. *See also* IPsec; security
 SLIP, 11
 TDP, 424, 428, 578
 VPDN mismatches, 72, 281
 provider edge. *See* PE routers,
 provisioning MPLS VPNs, 430
 Proxy LCPs, 226
 pseudowires
 AToM, 591–597
 control words, 580
 troubleshooting, 636
 classes, 377, 380
 PVP (permanent virtual path), 380

Q

quick mode negotiation, 668, 719–733

R

RA (Registration Authority), 679
 RADIUS (Remote Authentication Dial-in User Service), 241
 authentication failures, 105–109, 322–326
 authorization failures, 109–114, 326, 331
 L2TP misconfiguration, 312–322
 server unreachable from LNS, 331
 ranges, troubleshooting, 625
 RD (Route Distinguisher), 430–432

reconfiguration. *See also* configuration
 authentication, 178
 crypto access lists, 700
 hash algorithms, 724
 passwords, 90, 107
 peer IP addresses, 704
 tunnel passwords, 79
 usernames, 90
 VPDN groups, 284
 redistribute command, 533
 redistribute rip command, 458
 redistribution
 MP-BGP, 458, 531
 routes, 518
 re-enabling ISAMP, 703
 reference models, 4
 Registration Authority (RA), 679
 remote AAA, 44. *See also* AAA
 authentication failures, 105–109
 authorization failures, 109–114
 case studies, 98–114
 configuration, 39
 L2TP configuration, 241
 LNS, 249
 remote access clients. *See also* access; clients
 CONFACK, 269
 disconnections, 293
 PPP negotiation failures, 84–98
 PPTP, 137
 maintenance, 148–150
 messages, 154
 termination, 150–153
 remote access IPsec VPNs configuration, 655,
 682–688
 remote alarms, E1 controllers, 54
 Remote Authentication Dial-In User Service. *See*
 RADIUS
 remote clients, LCP negotiation failures, 58
 remote VPN clients, IKE negotiation failures, 740
 reports, alarms, 54
 Resource Reservation Protocol (RSVP), 424, 428
 responders
 preshared keys, 707
 quick mode, 720
 Result Code AVPs, 222, 364

- result codes
 - CDN
 - messages, 223
 - verifying from, 294
 - PPTP, 141
 - StopCCN messages, 223
 - retention of labels, 427
 - RIP (Routing Information Protocol), 454
 - Route Distinguisher (RD), 430
 - Route Target (RT), 434
 - router isis command, 450
 - router ospf 100 command, 451
 - routers
 - AToM
 - CEF, 588
 - configuration, 588
 - LDP ROUTER ID, 589
 - loopback interfaces, 588
 - MPLS backbone IGP, 590–591
 - MPLS core interfaces, 589–590
 - pseudowires, 591–597
 - sample configurations, 597–605
 - specifying LDP, 589
 - troubleshooting, 605, 635
 - VC label exchanges, 636–645
 - CA enrollment, 680
 - CE
 - configuration, 446
 - MVPNs, 464
 - clocks, 678
 - configuration, 767–771
 - domains, 678
 - hostnames, 678
 - ID configuration, 448
 - L2TPv3
 - configuration, 375–388
 - dynamic sessions, 376–380
 - static sessions, 380–382
 - troubleshooting, 389–410
 - LCCE configuration, 382–387
 - P
 - configuration, 462–464
 - MVPNs, 465
 - TE tunnels, 472
 - PE, 358
 - configuration, 446, 459–462
 - import maps, 529
 - IP address mismatches, 644
 - IS-IS, 450
 - LDP, 637
 - LDP session failures, 639
 - MP-BGP redistribution, 531
 - MVPNs, 464–468
 - TE tunnels, 468–472
 - VRF, 433
 - platforms, 767
 - responders, 707
 - VC label exchanges, 582–586
 - routes
 - default, 697
 - MP-BGP
 - activating, 452
 - redistribution, 458, 518
 - PE to CE advertisement, 534
 - static
 - configuration, 454, 458
 - packet leaking, 439
 - troubleshooting, 514
 - VPNs, 436, 511–536
 - routing
 - initiators, 697
 - PE-CE protocols, 454
 - VPNs, 433
 - VRF, 433
 - RSA key pairs, generating, 679
 - RSA signature authentication, 664–666
 - RSVP (Resource Reservation Protocol), 424, 428
 - RT (Route Target), 434
-
- ## S
- SAD (Security Association Database), 660
 - sample configurations, AToM, 597–605
 - SAs (security associations), 660
 - IKE, 660–668, 712
 - IPSec, 721
 - SCCCN (Start-Control-Connection-Connected), 229
 - SCCRP (Start-Control-Connection-Reply), 229, 371
 - SCCRQ (Start-Control-Connection-Request), 139, 229, 371
 - secrets, tunneling, 40, 44

security

- firewalls, 359
- IPSec, 655
 - configuration, 668
 - IKE, 660–668
 - MTU issues, 689–690
 - remote access, 682–688
 - SAs, 660
 - security protocols, 656–659
 - site-to-site, 669–681
 - technical overview of, 656–668
 - troubleshooting, 690–692

L2TP, 236

Security Association Database (SAD), 660

security associations. *See* SAs

Security Parameter Index (SPI), 660, 721

Security Policy Database (SPD), 660

sequences, PPTP tunnel setup, 162

servers

- AAA. *See also* AAA
 - misconfigurations, 99–105
 - unreachable from LNS, 331–342

addresses

- configuration, 46
- L2TP, 248
- PPTP, 158

certificate maps, 678

L2TP, 213

LNS, 5

Microsoft CA, 679

NAS, 11

offload, 114, 122

PNS, 135

service password-encryption command, 79

Session IDs, 219

sessions

- data message headers, 369
- dynamic
 - L2TPv3, 376–380
 - troubleshooting, 400
- failure codes, 35
- L2F, 25–31, 80–84
- L2TP, 230–232, 290–297
- L2TPv3, 372
 - sample configurations, 382–387
 - teardowns, 374
 - troubleshooting, 408

LDP

- blocking access lists, 622
- PE routers, 639
- troubleshooting, 493, 618
- VC label exchanges, 582–586

management AVPs, 367

PPTP

- configuration, 142–146
- messages, 154
- termination, 150–153
- troubleshooting, 163–168

static, 380–382

Set-Info-Link (SLI)

- messages, 234, 375
- packets, 154

SHA-1 authentication, 253

shim headers, 422

show adjacency detail command, 561

show atm vc command, 565

show caller user command, 64, 90, 97, 267, 311

show clock command, 716

show commands, 6–8

IPSec, 750–751

L2F, 129–130

L2TP, 351

MPLS VPNs, 569–571

show controller e1 command, 262

show crypto ca certificates command, 716

show crypto engine connections active command, 747

show crypto ipsec dynamic-map command, 748

show crypto ipsec sa command, 726

show crypto ipsec security-association lifetime command, 749

show crypto ipsec transform-set command, 724

show crypto isakmp key command, 701

show crypto isakmp sa command, 695

show crypto key mypubkey rsa command, 747

show crypto key pubkey-chain rsa command, 748

show crypto map tag command, 698–699

show ip access-lists command, 490, 530, 615, 706, 734

show ip bgp neighbors command, 522

show ip bgp vpnv4 vrf vrf_name command, 518, 524

show ip bgp vpnv4 vrf vrf_name labels command, 565

show ip cef command, 481, 609

show ip cef summary command, 509

show ip interface command, 705

show ip rip database vrf command, 532

- show ip route command, 535, 697
 - show ip route vrf vrf_name static command, 515
 - show ip vrf detail vrf_name command, 526
 - show ip vrf interfaces command, 513
 - show isdn status command, 53–54, 261
 - show l2tun session all command, 411
 - show l2tun tunnel all command, 410
 - show mpls atm-ldp capability command, 564
 - show mpls forwarding-table command, 504, 627
 - show mpls interfaces command, 609
 - show mpls l2transport binding command, 648
 - show mpls l2transport hw-capability interface interface_name command, 647
 - show mpls l2transport summary command, 647
 - show mpls l2transport vc command, 642
 - show mpls l2transport vc void detail command, 636
 - show mpls ldp bindings command, 503, 628, 630–631
 - show mpls ldp discovery command, 489, 613
 - show mpls ldp neighbor command, 494, 618, 639
 - show mpls ldp parameters command, 563
 - show ppp mppe virtual-access number command, 206
 - show ppp multilink command, 116, 121
 - show route-map command, 528
 - show running-config command, 67, 283
 - show user command, 63
 - show vpdn command, 204
 - show vpdn history failure command, 122, 342
 - show vpdn session all command, 179, 343
 - show vpdn session command, 81, 205, 292
 - show vpdn tunnel all command, 68, 70, 79, 167, 277,
 - show vpdn tunnel command, 120, 205
 - shutdown, tunnels, 283
 - signals
 - loss, 54
 - loss of alarm, 262
 - signatures, RSA authentication, 664
 - site-to-site IPsec VPN configuration, 669–681
 - site-to-site VPNs, 655
 - SKEME (Secure Key Exchange Mechanism for the Internet), 660
 - SKYDANCE_POOL, creating, 249
 - SLI (Set-Link-Info)
 - messages, 234, 375
 - packets, 154
 - SLIP (Serial Line Internet Protocol), 11
 - SMI Network Management Private Enterprise Codes (RFC 1700), 221, 363
 - solutions, troubleshooting labs, 771–775
 - SPD (Security Policy Database), 660
 - specifying LDP (AToM), 589
 - SPI (Security Parameter Index), 660, 721
 - split tunneling access lists, 684
 - split tunnels PPTP, 203–204
 - stack (S) bits, 422
 - stacks, labels, 423
 - Start-Control-Connection-Connected (SCCCN), 229, 372
 - Start-Control-Connection-Reply (SCCRP), 229, 371
 - Start-Control-Connection-Request (SCCRQ), 139, 229, 371
 - statements, deny any, 490
 - static routes
 - configuration, 454, 458
 - packet leaking, 439
 - troubleshooting, 514
 - static sessions (L2TPv3)
 - configuration, 380–382
 - troubleshooting, 408
 - StopCCN (Stop-Control-Connection-Notification) message, 234, 364
 - StopCCRQ packet fields, 152
 - sublayers, Layer 3, 371
 - switches, global ISDN parameters, 37
 - switching
 - Frame Relay, 378
 - MPLS, 577
-
- ## T
-
- T (transport type) bit, 581
 - T1, L2TP configuration, 238
 - tables
 - BGP, 520
 - CEF, 424
 - VRF, 433
 - TACACS+ (Terminal Access Controller Access Control Server plus), 241
 - Tag Distribution Protocol (TDP), 424, 428, 578
 - tail-end router configuration, 472
 - target mismatches, 525
 - TDP (Tag Distribution Protocol), 424, 428, 578
 - TDP/LDP router IDs, configuration, 448

- TE (traffic-engineering) tunnels, 423
 - MPLS VPN, 468–473
 - P routers, 472
- teardown
 - L2F tunneling, 34–35
 - L2TP, 233
 - L2TPv3, 374
 - PPP connections, 89
- templates (virtual)
 - cloning, 85
 - configuration IP addresses, 97
 - creating, 45
 - PPTP, 156
- Terminal Access Controller Access Control Server plus (TACACS+), 241
- Terminate-Acks (TERMACKs), 67, 90
- Terminate-Request (TERMREQ), 90, 275
- Terminate-Requests (TERMREQs), 67
- termination
 - negotiation, 185
 - PPTP, 150–153
- testing IP connectivity, 117
- time zone configuration, 678
- Time-to-Live (TTL), 422
- tools, 6–8
- top-down troubleshooting, 5
- topologies
 - baselining, 3
 - carrier's carrier, 419
 - IPSec VPNs, 690
 - MPLS Layer VPNs, 419
- traceroute command, 6–8, 476–479
- traffic
 - crypto access lists, 673
 - IPSec, 733–736
 - VPNs, 437
- traffic-engineering. *See* TE tunnels
- transform sets
 - configuration, 253
 - IPSec, 685, 671
 - mismatches, 723
- transparent forwarding, 11
- transports
 - AToM Layer 2 PDU, 578, 582
 - connections, 583
 - control words, 580
 - Frame Relay, 579
 - trees
 - default MDT, 443
 - MDT, 442
 - Triple DES (3DES), 658
 - troubleshooting
 - AToM, 605, 635
 - VC label exchanges, 636–645
 - troubleshooting, 645–652
 - authentication tunnels, 285
 - CAs, 736
 - certificate authentication, 714
 - clocks, 716–717
 - commands, 747–751
 - crypto maps, 698
 - IGP backbones, 479–481
 - IKE, 713
 - IPCP negotiation, 187
 - IPSec
 - tunneling, 733–736
 - VPNs, 689–692
 - ISAKMP messages, 703
 - L2F, 48–58, 122–126
 - error messages, 126
 - Home Gateway configuration, 43–48
 - maintenance, 32
 - management messages, 17–18
 - NAS configuration, 35–43
 - PPP, 58–69, 84–98
 - sessions, 25–31, 80–84
 - teardown, 34–35
 - technical overview of, 12–17
 - tunneling, 18–25, 69–80
 - L2TP, 255, 260
 - call reception, 260–265
 - case studies, 311
 - commands, 342–348
 - negotiation, 297–311
 - PPP on LAC, 266–278
 - sessions, 290–297
 - tunnels, 278–290
 - L2TPv3, 389–410, 410–417
 - lab solutions, 771–775
 - LC-ATM interfaces, 491
 - LCP negotiation, 58, 86
 - LDP sessions, 493
 - LSP, 481–511
 - MPLS VPNs, 420–445, 473–536

- case studies, 536–560
 - commands, 560–571
 - MPPE negotiation, 180
 - MTUs, 387–388
 - NCP negotiation, 91
 - partial PPP authentication, 273
 - PE-CE routing protocols, 514, 516
 - PPP partial authentication failures, 64
 - PPTP, 159–162
 - authentication, 176–180
 - commands, 204–210
 - control channels, 163–168
 - debug commands, 210
 - LCP negotiation, 169–176
 - NCP negotiation, 180–197
 - sessions, 163–168
 - show commands, 210
 - virtual interfaces, 168–169
 - preshared keys, 701
 - routing initiators, 697
 - split tunnels, 203–204
 - static routes, 514
 - tools, 6–8
 - tunneling authentication failures, 74
 - types of, 5
 - VPDN protocol mismatches, 72
 - VPN advertisements, 511–536
 - trunks
 - Frame Relay, 379
 - switching, 378
 - TTL (Time-to-Live), 422
 - Tunnel IDs, 218
 - tunnel path-mtu-discovery command, 689
 - tunnel protection command, 675
 - tunneling
 - authentication, 74, 285
 - failure codes, 35
 - IPSec
 - establishing, 732
 - traffic, 733–736
 - troubleshooting, 730
 - L2F, 18–25
 - maintenance, 32
 - multiple sessions, 15
 - teardown, 34–35
 - troubleshooting, 69–80
 - L2TP, 213
 - call reception, 260–265
 - compulsory tunnel mode, 237, 245
 - control messages, 220–227
 - establishment, 227, 229
 - IPSec, 252–255
 - LNS, 246, 252
 - maintenance, 232
 - messages, 234–235
 - outgoing calls, 235–236
 - PPP on LAC, 266–278
 - security, 236
 - sessions, 230–232
 - teardown, 233
 - technical overview of, 215–220
 - troubleshooting, 255, 260, 278–290
 - voluntary tunnel mode, 252
 - labels, 626
 - LSP
 - locating, 607
 - troubleshooting, 611
 - management, 17
 - MTI, 442
 - packets, 16
 - password reconfiguration, 79
 - PPP frames, 29
 - PPTP, 135
 - secret configuration, 40, 44
 - shutdown, 283
 - split tunneling access lists, 684
 - TE, 423, 468–473
 - types
 - of payloads, 662
 - of troubleshooting, 5
 - of VCs, 585, 640
- ## U
-
- unsolicited downstream label distribution, 426
 - updating
 - BGP, 447
 - LDP, 447
 - PIM, 467, 679
 - usernames
 - local databases, 682
 - reconfiguration, 90
 - user-to-tunnel associations, 19, 679

V

values

- cookies, 370
- Diffie-Hellman public, 667, 693
- error codes, 224
- fields, 14
- payloads, 662
- VCID, 368
- VC (virtual connection)
 - ATM cell relay, 595
 - control mismatches, 616
 - ID mismatches, 642
 - label exchanges, 636–645
 - labels, 578, 582–586
 - types, 585, 640
- VCID (Virtual Circuit) values, 368, 403
- Vendor-ID field, 221
- verification
 - access lists, 615
 - active lines, 266
 - call reception, 56
 - call setup, 55
 - CEF, 509, 608
 - crypto map placement, 698
 - label bindings, 626
 - LFIB, 504
 - MPLS, 484, 609
 - NCP negotiation, 97
 - peer IP addresses, 704
 - PPTP
 - session setup, 178
 - tunnels, 167, 175
 - PRI, 263
 - tunnel LSPs, 607
 - virtual interfaces, 175
 - VPDN groups, 169
- Virtual Circuit ID (VCID) values, 368, 403
- virtual interfaces, troubleshooting, 168–169
- virtual template interfaces, L2TP, 247
- virtual templates
 - cloning, 85, 297
 - creating, 45
 - IP address configuration, 97
 - PPTP, 156
- VLAN (802.1Q) interface encapsulation, 378

voluntary tunnel mode

- IPSec configuration, 255
- L2TP, 252
- voluntary tunnel modes, 135
 - technical overview of PPTP, 137
 - PPTP, 155
- vpdn domain-delimiter command, 19
- vpdn multihop command, 120
- vpdn search order domain command, 243
- vpdn session-limit sessions command, 297
- vpdn softshut command, 84, 296
- VPDNs (Virtual Private Data Networks)
 - enabling, 40, 44
 - error messages, 126
 - groups
 - configuration, 40, 44
 - creating virtual templates, 45
 - misconfiguration of domain names, 67
 - PPTP, 156
 - reconfiguration, 284
 - L2TP, 242
 - LNS, 246
 - mismatches, 281
 - protocol mismatches, 72
 - session limitations, 83
- VPN Routing and Forwarding (VRF), 433
- VPN-IPv4 (VPNv4) address family, troubleshooting, 522
- VPNs (virtual private networks)
 - advertisements, 511–536
 - interfaces, 440
 - Internet access, 439
 - IPSec, 655
 - configuration, 668
 - IKE, 660–668
 - MTU issues, 689–690
 - remote access, 682–688
 - SAs, 660
 - security protocols, 656–659
 - site-to-site, 669–681
 - technical overview of, 656–668
 - troubleshooting, 690–692
 - Layer 3 MPLS
 - configuration, 445–459
 - P router configuration, 462–464
 - PE router sample configuration, 459–462
 - technical overview of, 420–445

MPLS

- case studies, 536–560
- commands, 560–571
- TE tunnels, 468–473
- troubleshooting, 473–536

route distribution, 436

traffic, 437

VRF (VPN Routing and Forwarding), 433

interfaces, 467, 454

MVRF, 442

packet leaking, 439

X

XAuth (extended authentication), 682

xconnect command, 393

Z

ZLB Ack (Zero-Length-Body Acknowledgement),
216, 360

W

WEN (WAN-Error-Notify) message, 234

WINS (Windows Internet Naming System)

addresses

configuration, 46

L2TP, 248

PPTP, 158

withdraw messages, labels, 586

wizards, Create New VPN Connection Entry, 685