

## Numerics

---

- 100+-Mbps QoS policy, 470
- 6PE routers, 274
- 6VPE functionality, 327

## A

---

- ABRs (Area Border Routers), 91
- AC (Attached Circuit), 42
- access. *See also* remote access
  - dial-in, 14
  - DSL, 15
  - Internet
    - following default routes, 305, 307
    - via NAT/firewall services, 309
    - via PE-CE links, 307–308
  - IPv6, 272
  - via NAT/firewall services, 309
  - POP network structure, 280, 284–285
  - provisioning, 131
  - QoS, 470
  - VPN, 3–5
    - autonomous system boundaries, 19–22
    - Carrier's Carrier architecture, 16–18
    - CE routers, 7
    - components, 5
    - IPv6, 30–41
    - label allocating (PE routers), 8–9
    - Layer 2, 41–45
    - multicast, 22–30
    - packet delivery, 12–13
    - PE routers, 6–7
    - remote, 14–15
    - route target formats (PE routers), 10
    - VPNv4 prefix creation (PE routers), 9–10
    - WRED drop profiles, 238
- Add/Drop Multiplexers (ADMs), 118, 270
- addresses
  - autoconfiguration, 33
  - IPv6, 32
  - multicast allocation, 216
  - NAT, 30
  - SAFI, 311
- adjacencies, 28, 82–85
- ADM (Add/Drop Multiplexer), 118
- advertisements
  - inter-AS VPNv4 exchanges, 20
  - interval timers, 324
- AF (Assured Forwarding), 59
- affinities (traffic engineering), 70
- Africa Telecom, VPOPs, 421
- agents, SAA, 371
- aggregation
  - core QoS engineering, 65
  - traffic engineering (DiffServ), 86–89
- algorithms
  - Dijkstra, 74
  - exponential back-off, 102
  - load balancing, 82. *See also* load balancing
- allocation, 300
  - labels (PE-routers), 8–9
  - MAM, 345
  - multicast address, 216
  - names (VPN), 132
  - RD, 132, 201
  - routes, 300
- “Always-on” connectivity, 31
- American Registry for Internet Numbers (ARIN), 119
- anycast addresses, 33

- any-to-any connectivity, 4
- applications
  - peer-to-peer, 31
  - requirements (QoS), 49–51
- APS (Automatic Protection Switching), 121
- architecture
  - Carrier’s Carrier, 8–9, 16–18, 208
  - ICA protocol, 465
  - IPv6, 37
  - Managed Telephony Service, 452
  - national telco design study, 194
  - routing, 293–294
  - SNA, 339
  - VPN, 3–5
    - CE routers, 7
    - components, 5
    - label allocation (PE routers), 8–9
    - PE routers, 6–7
    - VPNv4 prefix creation (PE routers), 9–10
  - worldwide network, 286–292
- Area Border Routers (ABRs), 91
- ARF (Automatic Route Filtering), 297
- ARIN (American Registry for Internet Numbers), 119
- ASBR (Autonomous System Boundary Router), 5, 292
  - Fast Reroute, 420
  - inter-AS VPNv4 exchanges, 20
  - multiarea/multi-AS, 91
  - policy control at boundaries, 421
  - VPNv4 routes, 297–299
- AsiaPac, 288
  - QoS, 340–349, 351–356
  - TE, 383–385
- assignment of labels, 12
- Assured Forwarding (AF), 59
- ATM (Asynchronous Transfer Mode)
  - marking, 466
  - pseudowires
    - design, 332–333
    - PE router failures, 400
    - TE, 391–393
  - PVCs, 352–356
  - trunking, 370–371
- Attached Circuit (AC), 42
- attacks, DoS, 125, 196
- attributes, 69
  - connector formats, 312
  - inter-AS TE LSPs, 404
  - LSP, 88
  - SoO, 133
  - TE LSP, 69–72
  - traffic engineering, 73
- autoconfiguration, 33
- automatic meshing, TE LSPs, 85
- Automatic Protection Switching (APS), 121
- automatic provisioning, 376–377
- Automatic Route Filtering (ARF), 297
- automatic summarization, 145
- autonomous system boundaries, 19–22
- Autonomous System Boundary Router. *See* ASBR
- Autoroute, 76
- availability
  - networks, 95–115
  - troubleshooting, 164

**B**


---

- backbones
  - label forwarding design, 125, 194–198
  - link types, 293
  - Multicast design, 218
  - national telco design study, 191
  - packets, 12
  - USCom links, 124
- back-door links, 143
- backups
  - Fast Reroute, 112
  - path computation, 113
  - tunnels, 165, 259
    - configuration of, 395–400
    - design (level POPs), 262
    - level 1/level 2 POPs, 267
    - NHOP/NNHOP, 264
    - period of time in use, 268
- bandwidth
  - dynamic TE-LSPs, 378–379, 382
  - fish problem solutions, 77
  - fragmentation, 248
  - hierarchies, 234
  - maximum reservable, 374–375
  - QoS, 346
  - TE LSPs, 246
  - traffic engineering, 69, 86
- BASs (Broadband Access Servers), 191
- BGP (Border Gateway Protocol)
  - IPv4, 195
  - standardizing, 142
  - tuning, 324
- BLSRs (Bidirectional Line Switch Rings), 118
- bootstrap router (BSR), 217–218

- Border Gateway Protocol. *See* BGP
- boundaries, 421
- branch offices, 427–428
  - locations, 429–430
  - Layer 3 MPLS VPN design, 448
  - requirements, 441
- QoS, 470
- traffic
  - classification, 465
  - flowing, 472–475
- Broadband Access Servers (BASs), 191
- BSR (bootstrap router), 217–218

**C**


---

- call agents, 188
- Call Detail Record (CDR), 244
- Candidate BSRs (C-BSRs), 217
- capacity
  - core QoS engineering, 66
  - planning, 54
  - traffic engineering, 68
- capex (capital expenditure), 428
- Carrier Carrier's service, 207–212
  - architecture, 8–9, 16–18
  - QoS (network edge), 241
- Carrier Supporting Carrier (CSC) PE routers, 17
- C-BSRs (Candidate BSRs), 217
- CBTS (CoS-Based Tunnel Selection), 89, 385
- CBWFQ (Class-based Weighted Fair Queuing), 60
- CDR (Call Detail Record), 244
- central-site extranets, 11

- CE-router (customer edge router), 5, 7
  - egress policy, 359
  - egress QoS policies, 233
  - IP address allocation, 146
  - routing protocol design, 140–145
- CITRIX Independent Computing Architecture, 465
- class of recovery (CoR), 164
- class of service. *See* CoS
- Class-Based Weighted Fair Queuing (CBWFQ), 60
- classes
  - mapping, 334
  - services
    - large enterprise design study, 463
    - mapping, 467
- classification
  - ATMs, 466
  - CoS, 241
  - customer-specific, 241
  - traffic, 67
- classifiers, traffic, 58
- CLI (command-line interface)
  - collection of management results, 243
  - pseudowires, 44
- cloud topologies (for telephony transit), 190
- C-network (customer network), 5
- Coarse Wave Division Multiplexing (CWDM), 122
- collaboration, 279
- coloring schemes (traffic engineering), 70
- command-line interface (CLI)
  - collection of management results, 243
  - pseudowires, 44
- commands
  - ip icmp rate-limit unreachable, 315
  - maximum routes, 316
  - maximum-prefix, 316
  - neighbor maximum-prefix, 142
  - no auto-summary, 145
  - show ip bgp neighbor, 139
  - vrf upgrade-cli, 330
- commercial clauses, 52
- commitments (SLS), 52
- components
  - CE-router egress QoS policies, 236
  - pseudowire, 42
  - recovery, 95–115
  - traffic engineering, 69–72
  - VPN, 5
    - CE routers, 7
    - label allocation (PE routers), 8–9
    - PE routers, 6–7
    - route target formats (PE routers), 10
    - VPNv4 prefix creation (PE routers), 9–10
- computation
  - paths
    - backup tunnels, 113
    - inter-AS TE LSP, 406
    - multiarea/multi-AS, 90–95
    - TE LSPs, 73–74, 88, 246
  - routing tables, 180
  - SPF, 102–104
  - TE-LSP paths, 382
- conditioners, traffic, 58
- confederations (Layer 3 MPLS VPN services), 136

- configuration
  - 6PE routers, 274
  - ARF, 297
  - autoconfiguration, 33
  - automatic provisioning, 376–377
  - backup tunnels, 395–400
  - bandwidth, 70
  - Carrier’s Carrier service, 210
  - data center PE router VRF templates, 442
  - data-MDTs, 220
  - exponential back-off, 257
  - Fast IS-IS, 399
  - hold-off timers, 270, 398
  - IPv6 VPN design, 328
  - IS-IS, 180–181
  - Layer 3 MPLS VPN, 131
  - maximum reservable bandwidth, 245, 374–375
  - mVPN, 218
  - OC-3 links, 375
  - OSPF timers, 256
  - PE-routers, 134, 202
  - PHB, 56
  - preemptions (traffic engineering), 71
  - prefix prioritization, 171
  - pseudowire, 44
  - queues, 467
  - reuse limits, 142
  - routing exchanges, 7
  - SRLG memberships, 262
  - static routing, 141
  - TE LSPs
    - automatic meshing, 85
    - deployment scenarios, 77–79
    - forwarding adjacency, 82–85
    - load balancing, 82
    - reoptimization, 79–81
    - routing, 76
    - signaling, 75–76
- congestion
  - TCP, 61
  - traffic engineering, 68
- connections. *See also* access
  - Carrier’s Carrier architecture, 8–9, 16–18, 208
  - data centers, 440
  - dial-in, 215
  - DSL, 15
  - firewalls, 444
  - intercontinental, 292
  - interexchange carrier design study, 117
  - interregion, 292
  - ISDN, 213
  - Layer 3 VPN remote access, 14–15
  - metro, 434–435
  - regional services, 301
  - regions, 296
  - scaling, 4
- connectors formats, 312
- Constraint Shortest Path First (CSPF), 72
- constraints, 69
  - backup tunnels, 259, 395
  - bandwidth, 87
  - SRLG, 266
  - TE LSP, 69–72
- contiguous TE LSPs, 404
- control planes
  - mechanisms, 54–55
  - mPE-routers, 205–207
  - operations (IPv6), 37
  - PE-route requirements, 135–136
  - protection (VPN), 316

- convergence, 317
  - computing, 103
  - IS-IS, 178–180
  - points, 322
  - routing, 320–324
- CoR (class of recovery), 164
- core egress QoS service policy template, 355
- core networks
  - POPs, 431–432
  - QoS, 154–157, 224
    - across regions, 358
    - North America, 356–358
  - regions, 340–356
- core packets, 186
- core QoS engineering, 65–66
- core routing design, 437–438
- CoS (class of service)
  - classification for, 241
  - TCS, 52
- CoS-Based Tunnel Selection (CBTS), 89, 385
- cost constraints (for recovery design), 165
- CSC (Carrier Supporting Carrier) PE routers, 17
- CSPF (Constraint Shortest Path First), 72
- curves, utilization, 53–55
- custom per-CoS VPN SLA on access, 223
- customer edge router. *See* CE-router
- customer network (C-network), 5
- customer VRF naming conventions, 201
- customer-specific classification, 241
- CWDM (Coarse Wave Division Multiplexing), 122
- cycles, recovery, 97, 438

## D

---

- dampening (routes), 142
- data centers, 433–434
  - connectivity requirements, 440
  - layer 3 MPLS VPNs, 442
  - traffic classification, 465
- Data Link Connection Identifier (DLCI), 448
- data path mechanisms, 54
- data planes
  - operations (IPv6), 39
  - protection (VPN), 316–317
- data-MDTs (mVPN design), 220
- default MDT, 310
- delay, 438
  - QoS metrics, 50
  - VPN Video CoS, 339
- delivery of VPN packets, 12–13
- denial of service (DoS) attacks, 125, 196
- Dense Mode (PIM-DM), 25
- dense wavelength division multiplexing (DWDM), 118, 186
- deployment
  - DiffServ-aware TE LSPs, 89
  - EIGRP, 145
  - encryption, 451
  - IPv6 (over MPLS networks), 35–36
  - multicasting, 450
  - OSPF, 143–144
  - RR, 128
    - Internet services, 198
    - VPNv4, 136–140
  - TE LSPs, 77–79
- design. *See also* configuration
  - Globalnet service provider study, 278–289, 291–294
    - ATM pseudowire, 332–333

- design objectives, 294
- Internet services, 303–309
- IPv6 VPN, 326–332
- Layer 3 MPLS, 295–303
- MPLS traffic engineering,
  - 372–382, 385–393
- mVPN services, 310–312
- network recovery, 393–400
- QoS, 333–343, 365–372
- routing architecture, 293
- scalability, 313–325
- security, 313–325
- virtual POPs, 401–410, 413–421
- interexchange carrier study, 117
- large enterprise design study, 425–427
  - branch offices, 427–428
  - core network POPs, 431–432
  - core routing, 437–438
  - data centers, 433–434
  - Layer 3 MPLS
    - metro connections, 434–435
    - objectives, 436
    - office locations, 429–430
    - QoS, 462–470, 474–475
    - VoIP, 452–461
    - VPNs, 439–450
- national design study, 185–190
  - Carrier's Carrier service, 207–212
  - IPv6, 272, 275
  - label forwarding, 194–198
  - Layer 3 MPLS VPN, 199–206
  - mVPN service access, 216–220
  - objectives, 194
  - POP, 190–191
  - QoS, 221–244
  - recovery, 255–272
  - remote access, 212–215
  - TE, 245–255
  - OSPF, 258
  - QoS, 67. *See also* QoS
  - routing protocols, 140–145
  - static routing, 141
  - USCom (interexchange carrier study)
    - environment, 117–124
    - label forwarding, 125–129
    - Layer 3 MPLS VPN service, 129–148
    - objectives, 124
    - QoS, 162
    - recovery, 163–181
    - traffic engineering, 163
- destinations (traffic engineering), 69
- detection
  - failure, 394
    - national telco design study, 256
    - PSTN, 258
  - faults, 195
  - IS-IS time, 178
  - link failures, 176
- dial-in access. *See also* access; connections
  - national telco design study, 212
  - VPN remote access, 14
- Differentiated Services (DS) fields, 56
- Differentiated Services Codepoint (DSCP), 57
- differentiation, IETF DiffServ models (QoS),
  - 55–64
- Diffserv, 86–89
- DiffServ-aware MPLS Traffic Engineering
  - (DS-TE), 341
- Digital Subscriber Line. *See* DSL
- Dijkstra algorithm, 74
- directed LDP sessions, 42
- disabling
  - ARF, 297
  - unused services and protocols, 314

## discovery

- automatic meshing (TE LSPs), 85
- neighbors (IPv6), 33

distributed path computation, 73

## distribution

- MDT, 310
- routes, 146
- source multicast trees, 23–24
- utilization curves, 53–55

DLCI (Data Link Connection Identifier), 448

## domains

- end-customer networks, 4
- multicast, 26

DoS (denial of service) attacks, 125, 196

double booking, avoidance of, 81

drop profiles, WRED, 238

DS (Differentiated Services) fields, 56

DSCP (Differentiated Services Codepoint), 57

- mapping, 334, 473
- precedence values, 59

DSCP-to-EXP mapping, 464

DSL (Digital Subscriber Line). *See also*

- access; connections
- access, 15

- national telco design study, 212

DS-TE (DiffServ-aware MPLS Traffic

Engineering), 341

DWDM (dense wavelength division

multiplexing), 118, 186

dynamic TE LSP bandwidth adjustments,  
378–382

dynamic times, 102–104

---

## E

edge devices, 191

edge networks, 241. *See also* networks

edge QoS engineering, 66

edge routers, 324–325

EF (Expedited Forwarding), 342

- non-EF tunnels, 392

- PHB, 59

- queues, 334

egress policies

- CE routers, 359

- PE routers, 363

egress service policies (PE-to-CE QoS  
options), 161

EIGRP (Enhanced Interior Gateway Protocol),  
82

- deployment, 145

- multipath support (VPNv4), 204

E-LSPs, 62

EMEA (Europe, Middle East, Africa) region,  
287

- QoS, 340–349, 351–356

- TE, 383, 385

enabling security, 315

encapsulation

- Multicast packets, 195

- pseudowire, 45

encryption, 441, 451

end-customer network domains, 4

end-to-end control plane packet flow, 11

end-to-end convergence time, 322

end-to-end paths, 151

end-to-end QoS, 472

enforcing QoS utilization, 65

engineering guidelines, 200



Enhanced Interior Gateway Routing Protocol.

*See* EIGRP

Enterprise Resource Planning (ERP), 158

environments

branch offices, 427–430

core network POPs, 431–432

data centers, 433–434

metro connections, 434–435

networks, 278–279

ERP (Enterprise Resource Planning), 158

Ethernet

metro connections (UK), 434

national telco design study, 191

EuroBank, 427

Europe, Middle East, Africa. *See* EMEA

event-driven reoptimization, 81

exchanges

interexchange carrier design study, 117

internal/external route, 18

routing, 7

EXP

DSCP-to-EXP mapping, 464

mapping, 334

Expedited Forwarding (EF), 342

non-EF tunnels, 392

PHB, 59

queues, 334

exponential back-off, 102, 257

export policies (VPNs), 134

extensions

IGP routing, 74

traffic engineering, 88

external routes, Carrier's Carrier architecture,

17

extranets

central-site, 11

VPNs, 130, 200

## F

FA (forwarding avoidance), 173

failures

detection, 394

national telco design study, 256

PSTN, 258

links (USCom), 124

notification, 257

PE-PSTN routers, 271

recovery. *See* recovery

Fast Ethernet, 469

Fast IS-IS configuration, 180, 399

Fast Reroute, 394, 420

FRR, 125

MPLS TE, 107–115

protection by (traffic engineering), 72

faults, detection, 195

FCC (Federal Communications Commission),  
117

FEC (Forwarding Equivalence Class), 42

Federal Communications Commission (FCC),  
117

FIB (Forwarding Information Base), 196, 258

fields, DS, 56

filtering, 127

ARF, 297

LDP, 127

PE-routers, 146

RTs, 320

VPNv4 routes, 297–299

firewalls

connectivity, 444

Internet access via, 309

fish problem, the, 68, 77

flaps, penalties, 142

Flash updates, 141

## flooding

- inter-AS links, 95
- new IS-IS LSPs, 179

## flow

- pseudowire packets, 45
- traffic, 70

## formats

- connector attributes, 312
- RD, 133
- routes
  - distinguishers, 9
  - targets (PE-routers), 10

## forwarding

- AF, 59
- EF, 59
- IPv6, 34
- labels, 194–198
- LFIB, 13
- mVPN, 28–30
- packets
  - Carrier's Carrier architecture, 17
  - VPN, 12–13
- RPF, 25
- TE LSPs, 82–85
- VRFs, 6–7

## forwarding adjacency (FA), 173

## Forwarding Equivalence Class (FEC), 42

## Forwarding Information Base (FIB), 196, 258

## fragmentation, 238, 248

## Frame Relay, 428

## Frame Relay traffic shaping, 237

## FRR (fast rerouting), 125

## FRTS (Frame Relay traffic shaping), 237

## full mesh TE\_LSPs, 376–377

**G**

## Gateway Load Balancing Protocol (GLBP), 439

## gateways

- media (VoIP), 188
- VHG, 14

## generations, LSA, 256

## Gigabit Ethernet

- metro connections (UK), 434
- national telco design study, 191
- QoS, 470

## GLBP (Gateway Load Balancing Protocol), 439

## global protection, 106

## global recovery, 97

## global restorations, 105

## global routing tables, 305

## global unicast addresses, 33

## Globalnet service provider design study

- ATM pseudowire, 332–333
- design objectives, 294
- intercontinental connectivity, 292
- Internet services, 303–309
- IPv6 VPN, 326–332
- Layer 3 MPLS VPN, 295–303
- MPLS traffic engineering, 372–382, 385–393
- mVPN services, 310–312
- networks
  - environments, 278–279
  - recovery, 393–400
- POP network structure, 280, 284–285
- QoS, 333–343
- routing architecture, 293–294

- scalability, 313–325
- security, 313–325
- service portfolios, 279
- virtual POPs, 401–410, 413–421
- worldwide architecture, 286–292

- groups
  - update, 138
  - VPNs, 441

## H

- headers, IPv6, 31
- hello timers, 438

- hierarchies
  - bandwidth, 234
  - traffic engineering, 73
  - VPNs, 17, 208

- higher-priority TE LSPs, 71
- high-speed links, utilization curves, 53–55
- hold-off timer configuration, 270, 398

- hops
  - delay, 438
  - next-hop backup tunnels, 396
  - PHB, 56
  - serialization delay at, 50
- host routing, 438
- HSRP (Hot Standby Router Protocol), 438

## I

- IANA (Internet Assigned Numbers Authority), 22
- iBGP multipath support (VPNv4), 204
- ICA (Independent Computing Architecture)
  - protocol, 465

- IETF (Internet Engineering Task Force), 50, 55–64
- IGMPv3 (Internet Group Management Protocol version 3), 26
- IGP (Interior Gateway Protocol), 292
  - PE-CE routing design, 143
  - routing extensions, 74
  - TE LSP extensions, 88
- import policies (VPNs), 134
- importing remote routing information, 10
- Independent Computing Architecture (ICA)
  - protocol, 465
- infrastructure
  - branch office locations, 429
  - data centers, 433–434
  - national telco design study, 186
  - POP, 431–432
- input drops (prevention at VPNv4 RRs), 139
- instances, VRFs, 6–7
- instantiation, PHB, 161
- Integrated Services Digital Network, 14, 213
- interaction of protocols, 318
- inter-AS
  - back-to-back VRF connections, 19–20
  - connectivity, 19
  - links, flooding, 95
  - mVPNs
    - SAFI template, 312
    - system flow, 313
  - Option “A” (back-to-back VRFs), 446
  - TE LSPs
    - attributes of, 404
    - packets, 417
    - path computation, 406
    - recovery, 419, 421
    - reoptimization of, 415
    - routing, 415
  - VPNv4 exchange connections, 20

- interconnections, branch offices, 429
- intercontinental connectivity, 292
- Interexchange Carrier (IXC), 117
- interexchange carrier design study, 117
- Interface Group MIB, 131
- interfaces
  - 100+Mbps QoS, 470
  - CLI
    - collection of management results, 243
    - pseudowires, 44
  - input drops (prevention at VPNv4 RRs), 139
  - MTI, 28
  - PNNI, 278
- Interior Gateway Protocol (IGP), 292
- inter-Local Access and Transport Area (LATA), 117
- Intermediate System-to-Intermediate System (IS-IS), 98, 292
- internal routes, Carrier's Carrier architecture, 17
- Internet, 309
  - access
    - following default routes, 305–307
    - via PE-CE links, 307–308
  - IPv6, 272
  - QoS, 335–338
  - routing tables via global/VRF, 305
  - RR deployment, 128
  - services, 303–309
    - RR deployment, 198
    - separation of, 126
    - SLAs, 149
  - shared-edge services, 295
- Internet + Internet services, 200
- Internet Assigned Numbers Authority (IANA), 22
- Internet Engineering Task Force (IETF), 50
- Internet Group Management Protocol version 3 (IGMPv3), 26
- Internet Protocol. *See* IP
- Internet Protocol version 4. *See* IPv4
- Internet Protocol version 6. *See* IPv6
- Internet service provider, 185. *See also* access; connections
- interoperator partnerships, 293
- inter-POP connectivity (USCom), 123
- inter-provider connectivity, 19
- interprovider VPNs, 365–367
- interregion connectivity, 292
- intersubsidiary connectivity requirements, 440
- intra-AS mVPN solution, 311
- intranets, VPNs, 130, 200
- IP (Internet Protocol)
  - addresses, 9
  - routing
    - computing convergence time, 103
    - recovery, 98
  - tunneling, 26
  - VPN categories, 130
- ip icmp rate-limit unreachable command, 315
- IP Performance Metric Working Group (IPPM), 50
- IPv4 (Internet Protocol version 4)
  - mapped IPv6 addresses, 33
  - Unicast connectivity, 216
- IPv6 (Internet Protocol version 6)
  - over MPLS networks, 30–41
  - national telco design study, 272, 275
  - VPN
    - network recovery, 400
    - QoS, 369
    - service design, 326–332

ISDN (Integrated Services Digital Network), 14, 213

IS-IS (Intermediate System-to-Intermediate System), 292

- configuration, 180–181
- convergence, 178–180
- recovery, 98

isolation of end-customer network domains, 4

ISP (Internet service provider), 185. *See also* access; connections

IXC (Interexchange Carrier), 117

## J

jitter, 338

Johannesburg POP, conversion of, 401

## L

L2TP network server (LNS), 14

Label Distribution Protocol (LDP), 12, 125–127

Label Edge Router (LER), 63

Label Forwarding Information Base (LFIB), 13

labels

- forwarding, 194–198
- PE-router allocation, 8–9
- virtual circuit, 42
- VPN assignment, 12

Label-Switched Path. *See* LSP

large city-to-large city connectivity, 186

large customer attachments (Carrier's Carrier service), 210

large enterprise design study, 425–430

- branch offices, 427–428
- core network POPs, 431–432
- core routing, 437–438
- data centers, 433–434

Layer 3 MPLS

- VoIP, 452–461
- VPNs, 439, 443–450

metro connections, 434–435

objectives, 436

office locations, 429

QoS, 462–470, 474–475

last-resort unconstrained option (TE LSPs), 255, 390

LATA (inter-Local Access and Transport Area), 117

latency, 338

Layer 2

- VPN, 41–45
- VPNs, 194

Layer 2 Tunneling Protocol. *See* L2TP

Layer 3 (MPLS)

- VoIP, 452–461
- VPN, 295–303, 358–365, 439, 443–450
  - national telco design study, 199–206
  - separation of services, 126

layers, recovery, 95–115

LDP (Label Distribution Protocol), 12, 125, 194

- filtering, 127
- troubleshooting, 197

leased lines, six-queue policy, 468

LEC (Local Exchange Carrier), 117

LER (Label Edge Router), 63

- LFIB (Label Forwarding Information Base), 13
- link-local unicast addresses, 33
- links
  - coloring schemes (traffic engineering), 70
  - delay, 438
  - failure detection, 176
  - IGP routing extensions, 74
  - inter-AS flooding, 95
  - low-speed serialization, 238
  - maximum reservable bandwidth, 374–375
  - MPC networks, 270
  - nonrevertive/revertive, 114
  - OC-3, 375
  - PE-CE, 307–308
  - restored reuse, 175–176
  - sub-100-Mbps, 467
  - troubleshooting, 165–169
  - types, 293
  - USCom backbones, 124
- liveliness (LSP), 196
- L-LSPs, 62
- LNS (L2TP network server), 14
- load balancing
  - backup tunnels, 113
  - Carrier's Carrier service, 209
  - support, 202
  - TE LSPs, 82
- Local Exchange Carrier (LEC), 117
- local policies, marking ATMs, 466
- local recovery, 97
- locations (offices), 429–430
  - Layer 3 MPLS VPN design, 448
  - requirements, 441
- loops, temporary avoidance, 171–175
- LoS (loss of signal), 256
- loss
  - packets, 197
  - QoS metrics, 50

- lower-priority TE LSPs, 71
- lower-speed links
  - core QoS engineering, 66
  - serialization, 238
- LSA (link state advertisement)
  - dynamic timers, 102–104
  - generation, 256
- LSPs (Label-Switched Paths), 9, 88
  - last-resort unconstrained option, 255
  - TE LSPs
    - bandwidth, 246
    - provisioning, 254
    - reoptimization of, 252

---

## M

- maintenance, routers, 177
- MAM (Maximum Allocation Model), 86, 345
- Managed Telephony Service architecture, 452
- Managed Voice Service QoS, 466
- management of VPNs, 201–202
- manual reoptimization, 81
- mapping
  - DSCP, 473
  - DSCP-to-EXP, 464
  - QoS, 334
  - service classes, 467
  - traffic, 221
- MAR (Maximum Allocation Model with Reservation), 86
- marking ATMs, 466
- Maximum Allocation Model (MAM), 86, 345
- Maximum Allocation Model with Reservation (MAR), 86
  - maximum reservable bandwidth, 245, 374–375
  - maximum routes command, 316
- Maximum Segment Size (MSS), 135

- maximum-prefix command, 316
  - MDT (multicast distribution tree), 310
  - mechanisms, QoS, 53
  - media gateways (VoIP), 188
  - memberships (SRLG), 262
  - meshing (TE LSPs), 85
  - metrics
    - QoS application requirements, 49–51
    - traffic engineering optimization, 72
  - metro connections, 434–435
  - migration, VPOPs, 405–414
  - mode of operation before failure (MPLS TE Fast Reroute), 108
  - models
    - MAM, 345
    - QoS, 67
  - modification of dynamic TE-LSP bandwidth, 378–379, 382
  - Modular QoS CLI (MQC), 346
  - monitoring
    - SLAs, 242–243, 371–372
    - TE, 254–255
    - TE-LSPs, 389–390
  - MP-BGP (Multiprotocol BGP), 9
    - core design, 447
    - inter-AS mVPN solution, 311
    - scaling, 318
  - MPC (Multiservice Packet Core), 186, 270
  - mPE routers
    - control planes, 205–207
    - egress QoS policies, 240
    - ingress QoS policies, 239
  - MPLS Traffic Engineering (MPLS TE), 68.
    - See also* traffic engineering
  - MQC (Modular QoS CLI), 346
  - MSS (Maximum Segment Size), 135
  - multicast
    - addresses, 33, 216
    - distribution tree (MDT), 310
    - domains, 26
    - forwarding with mVPN, 28–30
    - packet encapsulation, 195
    - routing protocols, 217
    - traffic QoS, 368–369
    - VPNs, 22–30
  - Multicast Tunnel Interface (MTI), 28
  - multicasting, deployment of, 450
  - multiple dynamic routing protocols, PE-routers, 8
  - multiple failures, troubleshooting, 176
  - multiple preemptions (traffic engineering), 71
  - multipriority schemes, 248
  - Multiprotocol BGP. *See* MP-BGP
  - Multiservice Packet Core (MPC), 186, 270
  - multiservice PE-routers, 200
  - multi-VRF CE router-to-PE router links, 449
  - mVPN
    - design, 310–312
    - forwarding, 28–30
    - PIM adjacencies, 28
  - MYI (Multicast Tunneling Interface), 28
- 
- ## N
- naming conventions
    - customer VRF, 201
    - VRF, 132
  - NAPs (Network Access Points), 117
  - NASs (Network Access Servers), 191
  - NAT (Network Address Translation), 30, 309, 444

- national telco design study, 185–190
  - Carrier’s Carrier service, 207–212
  - IPv6, 272
  - label forwarding, 194–198
  - Layer 3 MPLS VPN, 199–206
  - mVPN service application, 216–220
  - objectives, 194
  - POP, 190–191
  - QoS, 221–244
  - recovery, 255–272
  - remote access, 212–215
  - TE, 245–255
- NBAR (Network-Based Application Recognition), 465
- neighbor maximum-prefix command, 142
- neighbor, discovery (IPv6), 33
- NetFLow, 70
- Network Access Points (NAPs), 117
- Network Access Servers (NASs), 191
- Network Address Translation (NAT), 30, 444
- network environments, 278–279
- network management system (NMS), 202
- Network Operations Center (NOC), 200
- Network Termination Units (NTUs), 434
- Network-Based Application Recognition (NBAR), 465
- network-based VPN, 4. *See also* VPN
- networks, 5
  - access. *See* access
  - availability, 95–115
  - core, 154–157, 224
  - edge, 66
    - Layer 3 MPLS VPN CsC (QoS), 241
    - QoS, 157–162, 359–365
  - end-customer domains, 4
  - environments, 278–279
    - branch offices, 427–428
    - core POPs, 431–432
    - data centers, 433–434
    - metro connections, 434–435
    - office locations, 429–430
  - Layer 3, 3–5
  - MPC links, 270
  - national telco design study, 185–190
    - Carrier’s Carrier service, 207–212
    - IPv6, 272, 275
    - label forwarding, 194–198
    - Layer 3 MPLS VPN, 199–206
    - mVPN service application, 216–220
    - objectives, 194
    - POP, 190–191
    - QoS, 221–244
    - recovery, 255–272
    - remote access, 212–215
    - TE, 245–255
  - recovery, 393–400, 419–421
  - USCom (interexchange carrier design study), 117–124
    - label forwarding, 125–129
    - Layer 3 MPLS VPN design, 129–148
    - objectives, 124
    - QoS, 162
    - recovery, 163–181
    - traffic engineering, 163
  - new IS-IS LSPs, flooding, 179
  - next-hop (NHOP) backup tunnels, 165, 396
  - next-next hop (NNHOP) backup tunnels, 165



NMS (network management system), 202  
 no auto-summary command, 145  
 NOC (Network Operations Center), 200  
 nodes  
   routing table computation, 180  
   troubleshooting, 177–178  
 nondisruptive reoptimization, 81  
 non-EF tunnels, 392  
 nonrevertive links, 114  
 North America, 289  
   QoS, 356–358  
   TE, 382–383  
 notification of failures, 257  
 NTUs (Network Termination Units), 434

## O

OAM (Operations, Administration, and Maintenance), 41  
 OC-3 configuration template, 375  
 offices  
   locations  
     Layer 3 MPLS VPN design, 448  
     requirements, 441  
   QoS, 470  
   traffic  
     classification, 465  
     flowing, 472–475  
 offline path computation, 73  
 off-net voice call, 460  
 one-hop backup tunnels, 165  
 one-way delays, 50  
 online path computation, 73  
 Open Shortest Path First (OSPF), 98  
 operational constraints (of recovery design), 164

operational expenditure (opex), 428  
 operational security (VPNs), 314–315  
 Operations, Administration, and Maintenance (OAM), 41  
 opex (operational expenditure), 428  
 optimization  
   metrics, 72  
   TE LSPs, 79–81, 92  
 options  
   last-resort unconstrained (TE LSPs), 255  
   network management VPNs, 201  
   Set of Ordered Path (traffic engineering), 73  
 OSPF (Open Shortest Path First)  
   deployment, 143–144  
   design, 258  
   recovery, 98  
 out-of-profile packets, 58  
 overlay VPN, 4

## P

Packet over SONET (PoS), 118  
 packets  
   Carrier's Carrier architecture, 17  
   core, 186  
   inter-AS TE LSPs, 417  
   loss, 197  
   Multicast encapsulation, 195  
   out-of-profile, 58  
   pseudowire flow, 45  
   QoS, 49  
     application requirements, 49–51  
     IETF DiffServ models, 55–64

- mechanisms, 53
- SLAs, 52–53, 65–68
- utilization curve comparisons, 53–55
- SPD tuning, 205
- VPN delivery, 12–13
- parameters
  - discovery, 33
  - resizing, 381
- partnerships, 293
- Path Computation Element (PCE), 92, 410
- Path MTU Discovery (PMTU), 135
- paths
  - end-to-end, 151
  - inter-AS TE LSPs, 406
  - load balancing, 82
  - protection, 106
  - recovery, 95–115
  - Set of Ordered Path option, 73
  - TE LSP, 73–74
    - computation, 246, 382
    - extensions, 88
  - traffic engineering, 90–95
- PCE (Path Computation Element), 92, 410
- PE (pseudowire edge) equipment, 42
- PE-CE data plane protection template, 317
- PE-CE links, 307–308
- peering, VPNv4 RRs, 207
- peer-to-peer applications, 31
- penalties, flaps, 142
- Penultimate Hop Popping (PHP), 13, 274
- PE-PSTN routers, failure of, 271
- PE-PSTN1 routers, TE LSPs between, 247
- performance of SLAs, 243
- per-hop behavior (PHB), 56, 161
- period of time (use of backup tunnels), 268
- PE-routers (provider edge-routers), 5–7
  - ATM pseudowires, 400
  - configuration, 134
  - control-plane requirements, 135–136
  - data center Layer 3 MPLS VPN design, 442
  - egress policy, 363
  - engineering guidelines, 131
  - filtering, 146
  - IP address allocation, 146
  - IPv6, 38
  - label allocation, 8–9
  - multiservice, 200
  - mVPN configuration, 218
  - network management VPNs, 202
  - route target formats, 10
  - routing protocol design, 140–145
  - VPNv4 prefix creation, 9–10
- PHB (per-hop behavior), 56, 161
- PhoneNet, 453
  - Layer 3 MPLS VPN design, 459
  - QoS, 466
- PHP (Penultimate Hop Popping), 13, 274
- PIM (Protocol-Independent Multicast), 25
- PIM-SM, 218
- placement of TE LSPs, 249
- planned router maintenance, 177
- planning capacity, 54, 66
- PMTU (Path MTU Discovery), 135
- P-network (provider network), 5
- PNNI (Private Network-Network Interface), 278
- POI (point of insertion), 145
- points, convergence, 322

- Points of Presence (POPs), 117
- Point-to-Point Protocol over ATM, 15
- Point-to-Point Protocol over Ethernet, 15
- Point-to-Point SLS models, 53
- policies
  - 100+Mbps QoS, 470
  - control at ASBR boundaries, 421
  - DSCP mapping, 473
  - import/export (VPN), 134
  - QoS, 419
  - six-queue, 467
  - sub-100-Mbps, 467
  - To-Fab QoS, 231
- policing, 58, 241
- POPs (Points of Presence), 117, 277
  - backup tunnels, 262
  - core network, 431–432
  - inter-POP connectivity (USCom), 123
  - Layer 3 MPLS VPN design, 446
  - level 1 design (USCom), 119
  - MPC, 186
  - national telco design study, 190–191
  - network structure, 280, 284–285
  - SLA commitments, 337
  - virtual POP design, 401–410, 413–421
- POP-to-POP SLA commitments, 335
- portfolios, services, 279
- PoS (Packet over SONET), 118
- PPPoA (Point-to-Point Protocol over ATM), 15
- PPPoE (Point-to-Point Protocol over Ethernet), 15
- PQ (Priority Queuing), 60
- preemption
  - TE LSPs, 249
  - traffic engineering, 71
- prefixes
  - discovery, 33
  - prioritization, 170–171
  - restrictions, 142
  - VPNv4, 9–10
- prioritization of prefixes, 170–171
- priority, defining (preemption), 71
- Priority Queuing (PQ), 60
- private, 441
- private autonomous system numbers, 441
- Private Network-Network Interface (PNNI), 278
- process IDs (OSPF), 144
- profiles, WRED, 350
- propagation
  - delay, 438
  - delay end-to-end, 50
- protection, 293
  - by fast reroute (traffic engineering), 72
  - comparison to restoration, 96
  - traffic engineering paths, 106
  - VPNs, 316–317
- Protocol-Independent Multicast (PIM), 25
- protocols
  - BGP, 142
  - disabling, 314
  - EIGRP, 82
  - IGP, 143
  - interaction, 318
  - LDP, 12, 125, 194
  - routing
    - design, 140–145
    - Multicast, 217
  - RSVP-TE, 12
  - RTCP, 244
  - TCP, 61
  - TDP, 12

P-router (provider router), 5  
 provider edge (PE) routers. *See* PE-routers  
 provider network (P-network), 5  
 provider router (P-router), 5  
 provisioning
 

- access, 131
- backup tunnels, 398
- services, 195
- TE LSPs, 254

 pseudowire edge (PE) equipment, 42  
 pseudowire identifier (PWid), 42  
 pseudowires, 41–45
 

- ATM
  - PE router failures, 400
  - TE, 391
- ATM design, 332–333
- QoS, 370–371

 PSTN (Public Switched Telephone Network), 185
 

- dial-in access (via L2TP VPDN), 14
- PE-PSTN router failure, 271
- recovery, 258
- TE LSPs bandwidth, 246
- trunking, 191

 PVCs (private virtual circuits)
 

- ATM QoS, 352–356
- Frame Relay, 428

 PWid (pseudowire identifier), 42

## Q

QoS (quality of service)
 

- application requirements, 49–51
- AsiaPac, 340–349, 351–356
- EMEA, 340–349, 351–356
- Globalnet service provider design study, 333–343, 368–372
- IETF DiffServ models, 55–64
- IPv6, 34, 369
- large enterprise design study, 462–470, 474–475
- mapping, 334
- mechanisms, 53
- MQC, 346
- multicast traffic, 368–369
- national telco design study, 221–244
- network edge, 359–365
- network recovery, 95
- North America, 356
- pseudowires, 370–371
- regions, 340–349, 351–358
- SLAs, 335–338, 371–372
- South America, 340–349, 351–356
- Telecom Kingland, 365–367
- USCom, 162
- utilization curve comparisons, 53–55
- VPOPs, 417, 419

 quality of service. *See* QoS  
 queues
 

- CBWFQ, 60
- delay, 438
- delay at each hop, 50
- EF, 334
- mapping, 334
- PQ, 60
- six-queue policy, 467

## R

- rainbow VPN design, 460
- Random Early Detection (RED), 61, 228, 348
- RD (route distinguisher)
  - allocation, 132, 201
  - formats, 9, 133
  - regions, 300
- RDM (Russian Doll Model), 86, 343
- real-time traffic, policing, 241
- receivers, multicast VPNs, 22
- records, CDR, 244
- recovery, 95–115, 393–400
  - cycles, 438
  - inter-AS TE LSPs, 419–421
  - national telco design study, 255–272
  - traffic engineering, 104–115
  - USCom, 163–181
- RED (Random Early Detection), 61, 228, 348
- reflectors, routes, 21
- refresh reduction, 254, 389
- regional customer attachments, 318
- Regional Internet Registry (RIR), 33
- regional service connectivity, 301–303
- regions
  - allocation between, 300
  - architecture, 286–292
    - Asian-Pacific, 288
    - EMEA, 287
    - North America, 289
    - South America, 290
  - automesh group number allocation per, 376
  - connectivity, 296
  - interregion connectivity, 292
  - IPv6 VPN design, 327–331
  - mVPN MDT between, 312
  - network recovery, 394
  - QoS, 340–349, 351–358
  - TE, 383, 385
- remote access
  - national telco design study, 212–215
  - VPN, 14–15, 200
- remote routing information, 10
- rendezvous point (RP), 24, 217
- reoptimization
  - inter-AS TE LSPs, 415
  - of TE-LSPs, 387
  - TE LSP, 79–81, 92, 252
- reporting
  - SLA, 242–243, 371–372
  - SLS, 52
- requirements
  - applications (QoS), 49–51
  - bandwidth, 70
  - control planes, 205–207
  - PE-router control-planes, 135–136
- rerouting
  - recovery, 95–115
  - TE LSPs, 249
  - traffic engineering, 105
- resizing parameters, 381
- resolution, addresses (IPv6), 33
- Resource Reservation Protocol Traffic Engineering (RSVP-TE), 12, 194
- restoration, comparison to protection, 96
- restored link reuse, 175–176
- restrictions
  - Multicast routing state (mPE routers), 220
  - prefixes, 142
- reusability, restored links, 175–176
- reuse limits, 142

- Reverse Path Forwarding (RPF), 25, 310
- revertive links, 114
- RIB (Routing Information Base), 258
- RIP (Routing Information Protocol), 445
- RIR (Regional Internet Registry), 33
- round-trip delays, 50
- round-trip time (RTT), 350
- route distinguisher (RD)
  - allocation, 132, 201
  - formats, 9, 133
  - regions, 300
- route reflection (RR), 128, 136–140, 205
- route targets (RTs)
  - allocation, 201, 441
  - filtering, 320
  - regions, 300
- RouterDead timer, 256, 438
- routers
  - 6PE, 274
  - ASBRs, 292
  - automesh configuration, 377
  - BSR, 217
  - CE-routers
    - egress QoS policies, 233
    - IP address allocation, 146
    - routing protocol design, 140–145
  - data centers, 433–434
  - edge, 324–325
  - Layer 3 MPLS VPN architecture
    - components, 5
  - LER, 63
  - maintenance, 177
  - mPE
    - control planes, 205–207
    - egress QoS policies, 240
    - ingress QoS policies, 239
  - multiarea/multi-AS, 91
  - PE-PSTN1, 247
  - PE-routers
    - ATM pseudowires, 400
    - configuration, 134
    - control-plane requirements, 135–136
    - data center Layer 3 MPLS VPN, 442
    - egress policy, 363
    - engineering guidelines, 131
    - filtering, 146
    - IP address allocation, 146
    - multiservice, 200
    - network management VPNs, 202
    - routing protocol design, 140–145
    - worldwide network architecture, 286–292
- routes
  - allocation between, 300
  - ARF, 297
  - dampening, 142
  - default, 305
  - distribution, 146
  - IGP, 292
  - reflectors, 21
  - targets, 10
    - formats (PE-routers), 10
    - selection of, 134
  - VPNv4, 297–299
- routing
  - architecture, 293–294
  - convergence, 320–324
  - core routing, 437–438
  - DiffServ-aware TE LSPs, 89
  - exchanges, 7
  - host, 438
  - IGP extensions, 74, 88

- inter-AS TE LSPs, 415
- IP, 98, 103
- IPv6, 34
- label forwarding, 125, 194–198
- multi-VRF VRF, 449
- protocols
  - design, 140–145
  - Multicast, 217
- states, 6–7
- static design, 141
- tables
  - computation, 180
  - Internet via, 305
- TE LSPs, 76
- Routing Information Base (RIB), 258
- Routing Information Protocol (RIP), 445
  - 8
- RP (rendezvous point), 24, 217
- RPF (Reverse Path Forwarding), 25, 310
- route reflection (RR), 128, 136–140, 205
- RSVP-TE (Resource Reservation Protocol Traffic Engineering), 12, 194
- RTCP (RTP Control Protocol), 244
- RTP Control Protocol (RTCP), 244
- RTs (route targets), 300
  - allocation, 201, 441
  - filtering, 320
  - regions, 300
- RTT (round-trip time), 350
- Russian Dolls Model (RDM), 86, 343

## S

- SAA (Service Assurance Agent), 242, 371
- SAFI (subaddress family), 311
- scalability
  - evaluation of technologies, 4
  - IETF DiffServ models (QoS), 55–64
  - MP-BGP, 318
  - MPLS VPN, 313–318, 320–325
  - recovery, 106
  - TE, 253, 388
- SCCP (Skinny Client Control Protocol), 456
- scheduling, CE-router egress QoS policies, 237
- SDH (Synchronous Digital Hierarchy), 186
- security
  - BGP IPv4 removal, 195
  - IPv6, 34
  - Layer 3 MPLS VPN service, 147–148
  - MPLS VPN, 313–318, 320–325
- selection
  - of CBTS, 89, 385
  - of route targets, 134
  - of VPN solutions, 4
- Selective Packet Discard (SPD) tuning, 205
- separation
  - of routing states (PE routers), 6–7
  - of services, 126
- serialization
  - delay, 50, 438
  - edge QoS engineering, 67
  - low-speed links, 238
- servers
  - BASs, 191
  - LNS, 14
  - NASs, 191
- Service Assurance Agent (SAA), 242, 371
- service level agreements. *See* SLAs

- service level specification (SLS), 52
- service portfolios, 279
- services
  - Carrier's Carrier, 207–212
  - classes
    - large enterprise design study, 463
    - mapping, 467
  - disabling, 314
  - DS fields, 56
  - firewalls, 309
  - Internet, 303–309
    - RR deployment, 128, 198
    - SLAs, 149
  - Internet + Internet, 200
  - IPv6, 326–332
  - mVPN, 310–312
  - NAT, 309
  - portfolios, 279
  - provisioning, 195
  - pseudowire, 42
  - regional connectivity, 301
  - security, 315
  - separation of service, 126
  - shared-edge Internet, 295
  - VPN, 3–5
    - autonomous system boundaries, 19–22
    - Carrier's Carrier architecture, 16–18
    - CE routers, 7
    - components, 5
    - IPv6, 30–41
    - label allocation (PE routers), 8–9
    - Layer 2, 41–45
    - multicast, 22–30
    - packet delivery, 12–13
    - PE routers, 6–7
    - remote access, 14–15
    - route target formats (PE routers), 10
    - VPNv4 prefix creation (PE routers), 9–10
- Session Initiation Protocol (SIP), 456
- Set of Ordered Path option (traffic engineering), 73
- sham links, 143
- Shared Risk Link Group (SRLG), 123
- shared-edge Internet services, 197, 295
- sharing load balancing (TE LSPs), 82
- Shortest Path First. *See* SPF
- Shortest Path Trees (SPTs), 23
- show ip bgp neighbor command, 139
- signaling
  - pseudowire, 44
  - TE LSPs, 75–76, 88
- simulations (MPLS TE), 252
- SIP (Session Initiation Protocol), 456
- site of origin (SoO), 133, 143
- six-queue policy, 467
- sizing rules (PE-router), 132
- Skinny Client Control Protocol (SCCP), 456
- SLAs (service level agreements)
  - for Internet services, 149
  - for Layer MPLS VPN services, 149–153
  - monitoring, 242–243, 371–372
  - QoS, 52–53, 335–338
  - tools, 65–68
- SLS (service level specification), 52
- SMBs (small and medium businesses), 199
- SNA (Systems Network Architecture), 339
- solutions to the fish problem, 77
- SONET, 118



SoO (site of origin) attributes, 133, 143  
 source distribution multicast trees, 23–24  
 Source-Specific Multicast (SSM), 26  
 South America, 290
 

- QoS, 340–349, 351–356
- TE, 383–385

 Sparse Mode (PIM-SM), 25  
 SPD (Selective Packet Discard) tuning, 205  
 SPF (Shortest Path First)
 

- dynamic timers, 102–104
- triggering, 257

 SPTs (Shortest Path Trees), 23  
 SRLG (Shared Risk Link Group), 123
 

- constraints, 266
- memberships, 262

 SSM (Source-Specific Multicast), 26  
 stacks, two-level label, 13  
 standardization of BGP, 142  
 static configuration of routing exchanges, 7  
 static default route template, 307  
 static routing design, 141  
 stitched TE LSPs, 404  
 sub-100-Mbps QoS policy, 467  
 subaddress family (SAFI), 311  
 summarization (automatic), 145  
 support
 

- Layer 3 MPLS VN, 26
- load balancing, 202
- SLAs, 65–68

 suppress limits, 142  
 Synchronous Digital Hierarchy (SDH), 186  
 Systems Network Architecture (SNA), 339

## T

tables
 

- MP-BGP, 9
- routing computation, 180

 Tag Distribution Protocol (TDP), 12  
 targets (route). *See* RTs  
 TCP (Transmission Control Protocol), 61  
 TCS (Traffic Conditioning Specification), 52  
 TDM (time-division multiplexing), 186  
 TDP (Tag Distribution Protocol), 12  
 TE (traffic engineering)
 

- AsiaPac, 383, 385
- ATM pseudowires, 391, 393
- DiffServ, 86–89
  - deployment, 89
  - routing, 89
- EMEA, 383, 385
- Fast Reroute, 394
- multiarea/multi-AS, 90–95
- national telco design study, 245–255
- North America, 382–383
- path protection, 106
- recovery, 95, 104–115
- regions, 383, 385
- scaling, 388
- South America, 383, 385
- USCom, 163

- telco national design study, 185–190
  - Carrier’s Carrier service, 207–212
  - IPv6, 272, 275
  - label forwarding, 194–198
  - Layer 3 MPLS VPN, 199–206
  - mVPN service access, 216–220
  - objectives, 194
  - POP, 190–191
  - QoS, 221–244
  - recovery, 255–272
  - remote access, 212–215
  - TE, 245–255
- Telecom Kingland. *See* telco national design study
- Telecommunications Act of 1996, 117
- TE-LSP (Traffic-Engineering LSP)
  - automatic meshing, 85
  - bandwidth, 246
  - deployment scenarios, 77–79
  - DiffServ-aware
    - deployment, 89
    - routing onto, 89
  - dynamic bandwidth adjustments, 378–382
  - fish problem, 77
  - forwarding adjacency, 82–85
  - full mesh, 376–377
  - inter-AS, 404
  - last-resort unconstrained option, 255, 390
  - load balancing, 82
  - monitoring, 389–390
  - multiarea/multi-AS, 90–95
  - path computation, 73–74, 382
  - provisioning, 254
  - reoptimization, 79–81, 92, 252, 387
  - routing, 76
  - signaling, 75–76
- templates
  - 6PE router configuration, 274
  - ARF, 297
  - ATM pseudowires, 370
  - automatic meshing (TE LSPs), 85
  - Carrier’s Carrier service, 210
  - CE-router egress QoS policies, 234
  - core egress QoS service policy, 355
  - data-MDTs, 220
  - EIGRP SoO attribute configuration, 145
  - Inter-AS mVPN SAFI, 312
  - IPv6 service design, 328
  - maximum routes configuration, 146
  - mVPN, 218
  - network management VPNs, 202
  - OC-3 configuration, 375
  - OSPF timer, 256
  - PE-CE
    - data plane protection, 317
    - link filter, 148
  - PE-routers
    - configuration, 134
    - PE-CE BGP links, 142
    - PMTU configuration, 136
    - VPNv4 MP-BGP configuration, 139
    - static default route, 307
  - temporary loop avoidance, 171–175
  - time-division multiplexing (TDM), 186
  - timer-based reoptimization, 81
- timers
  - advertisement interval, 324
  - dynamic, 102–104
  - hello, 438
  - hold-off, 270, 398
  - OSPF, 256
  - RouterDead, 438
- TLV (Type-Length-Value), 376

- To-Fab QoS policy, 231
- tools
  - NetFlow, 70
  - OAM, 41
  - SLAs, 65–68
- topologies
  - cloud (for telephony transit), 190
  - IGP, 143
  - packet core, 187
  - USCom, 119
  - VPNv4 RRs, 139
- traffic
  - classification stage, 57
  - classifiers, 58
  - conditioners, 58
  - engineering, 68–69
    - automatic meshing, 85
    - components, 69–72
    - deployment scenarios, 77–79
    - fish problem, 77
    - forwarding adjacency, 82–85
    - hierarchy of attributes, 73
    - IGP routing extensions, 74
    - load balancing, 82
    - reoptimization, 79–81
    - routing, 76
    - signaling, 75–76
    - TE LSP path computation, 73–74
  - flowing (branch offices), 472–475
  - mapping, 221
  - multicast, 368–369
  - office classification, 465
  - QoS
    - application requirements, 49–51
    - IETF DiffServ models, 55–64
    - mechanisms, 53
    - utilization curves, 53–55
  - real-time policing, 241
  - recovery, 95–115
  - requirements, 52–53, 65–68
  - Unicast, 194
- Traffic Conditioning Specification (TCS), 52
- traffic engineering (TE)
  - AsiaPac, 383, 385
  - ATM pseudowires, 391, 393
  - DiffServ, 86–89
    - deployment, 89
    - routing, 89
  - EMEA, 383, 385
  - Fast Reroute, 394
  - multiarea/multi-AS, 90–95
  - national telco design study, 245–255
  - North America, 382–383
  - path protection, 106
  - recovery, 95, 104–115
  - regions, 383, 385
  - scaling, 388
  - South America, 383, 385
  - USCom, 163
- Traffic-Engineered Label-Switched Path. *See* TE-LSP
- transactions, CITRIX ICA, 465
- transient routing loops, 104
- Transmission Control Protocol (TCP), 61
- transmit rings (Tx-rings), 239
- trees
  - MDT, 310
  - source distribution multicast, 23–24
- triggering SPF, 102–104, 257
- troubleshooting
  - availability, 164
  - BGP IPv4 removal, 195
  - IS-IS

- configuration, 180–181
- convergence, 178–180
- LDP, 197
- link failures, 165–169, 176
- multiple failures, 176
- node failures, 177–178
- prefix prioritization, 170–171
- recovery, 95–115
- restored link reuse, 175–176
- temporary loop avoidance, 171–175

trunking

- ATM, 370–371
- PSTN, 191

tuning BGP, 324

tunneling

- backup, 112, 165
  - configuration of, 395–400
  - design (level POPs), 262
  - level 1/level 2 POPs, 267
  - NHOP/NNHOP, 264
  - period of time in use, 268
- backups, 259
- CBTS, 89, 385
- EF, 343
- IP, 26
- MTI, 28
- non-EF tunnels, 392
- pseudowires, 392
- path computation, 113
- traffic engineering optimization, 72

two-level label stacks, 13

Tx-rings (transmit rings), 239

Type 1 POPs, 280

Type 2 POPs, 284

Type 3 POPs, 285

Type-Length-Value (TLV), 376

types

- of links, 293
- POP network structure, 280, 284–285
- of recovery, 97

---

## U

---

Unicast connectivity, 216

Unicast traffic, label forwarding, 194

unique local IPv6 unicast addresses, 33

unique RDs (route distinguishers), 133

unreachability of IPv6, 33

unused services and protocols, disabling, 314

updates

- FIB, 258
- Flash, 141
- groups, 138
- RIB, 258

URD (URL Rendezvous Directory), 26

USCom (interexchange carrier design study)

- environment, 117–124
- label forwarding, 125–129
- Layer 3 MPLS VPN service design, 129–148
- objectives, 124
- QoS design, 162
- recovery, 163–181
- traffic engineering, 163

utilization curves (QoS), 53–55

## V

- values (TLV), 376
- variable bit rate-real time (VBR-rt), 278
- variation of QoS metrics, 50
- VBR-rt (variable bit rate-real time), 278
- VHG (Virtual Home Gateway), 14, 213
- virtual circuit labels, 42
- Virtual IP Leased Line (VLL), 417
- virtual POPs (VPOPs), 401–410, 413–421
- Virtual Private Dialup Network. *See* VPDN
- Virtual Private LAN Service (VPLS), 194
- Virtual Private Network. *See* VPN
- Virtual Private Network version 4. *See* VPNv4
- Virtual Routing/Forwarding. *See* VRF
- VLANs (virtual LANs), 443
- VLL (Virtual IP Leased Line), 417
- VoIP (voice over IP), 452
  - Layer 3 MPLS, 452–461
  - media gateways, 188
- VPDN (Virtual Private Dialup Network)
  - dial-in access, 14, 213
  - DSL access, 15
- VPLS (Virtual Private LAN Service), 194
- VPN (Virtual Private Network), 3–5
  - autonomous system boundaries, 19–22
  - Business Latency CoS, 339
  - Business Throughput CoS, 340
  - Carrier's Carrier architecture, 16–18
  - CE routers, 7
  - components, 5
  - control plane protection, 316
  - data plane protection, 316–317
  - extranets, 130, 200
  - hierarchical, 17, 208
  - interprovider QoS, 365–367
  - intranets, 130, 200
  - IPv6, 30–41
    - network recovery, 400
    - QoS, 369
  - Layer 2, 194, 41–45
  - Layer 3, 439, 443–450
    - national telco design study, 199–206
    - Globalnet service, 295–303
    - separation of services, 126
  - management, 201–202
  - multicast, 22–30
  - mVPN design, 310–312
  - network edge, 359–365
  - operational security, 314–315
  - PE routers, 6–7
    - label allocation, 8–9
    - packet delivery, 12–13
    - route target formats, 10
    - VPNv4 prefix creation, 9–10
  - rainbow VPN design, 460
  - remote access, 14–15, 200
  - route target selection, 134
  - SLAs, 149–153
  - unique RDs, 133
  - VLAN allocation, 443
  - Voice CoS, 338
- VPNv4 (VPN version 4)
  - multipath support for, 204
  - prefix creation, 9–10
  - routes, 297–299
  - RRs
    - deployment, 136–140
    - placement, 205
- VPOPs (virtual POPs) design, 401–410, 413–421

- VRFs (Virtual Routing/Forwarding), 6–7
  - customer naming conventions, 201
  - multi-VRF VRF routing, 449
  - naming conventions, 132
  - remote routing information, 10
  - route targets, 10
  - routing tables, 305
- vrf upgrade-cli command, 330
- VRF-to-VRF connections, 19

## W–Z

---

- worldwide architecture, 286–292
- WRED (Weighted Random Early Detection), 61, 230
  - drop profiles, 238
  - profiles, 350
- X.25 over TCP (XOT), 466