

Numerics

1000BaseT, 112
 1000BaseX, 112
 10G multirate transponders, 357–358
 2.5 multirate transponders, 356–357
 2.5G multiservice aggregation cards, 358–360
 2-fiber BLSR operations, 201–205
 32 DMX demultiplexer cards, 347
 32 DMX-O demultiplexer cards, 346
 32 MUX-O multiplexer cards, 343
 32 WSS multiplexer cards, 344–345
 32-channel demultiplexer cards, 345–347
 32-channel multiplexer cards, 342–345
 4-fiber BLSR operations, 206–209
 4x2.5G enhanced muxponders, 358
 64-kbps circuit-switched connections, 51

A

AC (alternating current), 182
acceptance of light onto fiber, 102
acceptance testing, 433–435
access
 PCA, 205, 291
 remote, 150
 rings, 146, 160–166
 TAPs, 458
access identifier (AID), 475–476
ACO (alarm cutoff), 222
 backplane interfaces, 330
ACT LED (AIC-I), 231
activating software, 440
active, DWDM, 104
add/drop multiplexers (ADMs), 9, 167, 209
adding, 426
addresses, 151, 415–416, 455
ADMs (add/drop multiplexers), 9, 167, 209
Advanced Timing Communications and Control (TCC2) card, 410–411
AEP (Alarm Expansion Panel), 234, 339
aggregation
 2.5G multiservice cards, 358–360
 links, 278

AIC (Alarm Interface Card), 222, 410
AIC-I (Alarm Interface Controller-International) cards, 230–231, 335–341, 412
 environmental alarms, 231, 234
 orderwires, 234–235
 power supply voltage monitoring, 235
 user data channels, 235
AID (access identifier), 475–476
AINS (Automatic In-Service), 477
air gaps, 459
alarm cutoff (ACO), 222
 backplane interfaces, 330
Alarm Expansion Panel (AEP), 234, 339
Alarm Interface Card (AIC), 222, 410
Alarm Interface Controller-International cards.
 See AIC-I cards
alarms, 41
 correlation, 496
 CTM, 503
 environmental, 222
 AIC-I, 231, 234, 337–339
 backplane interfaces, 330
 local, 222, 331
 monitoring, 425–426
 nonalarmed events, 462
 profiles, 500
 reports, 332
 SNMP traps, 472
 suppression, 496
 troubleshooting, 432
Alarms tab (CTC), 448
alerts
 SNMP traps, 472
 TCA, 487
alternating current (AC), 182
AMP Champ EIA, 223
amplifiers, EDFAs, 107
applications
 BLSR, 209
 ONS 15454
 CE-Series Ethernet, 283–284
 E-Series Ethernet, 273–274
 G-Series Ethernet, 276
 UPSR, 199–200
 voice/video (bandwidth), 18–19

APS (automatic protection switching), 158, 322, 393 architecture, 511

- CORBA, 398
- CTM, 500–501
- MSPP, 135, 152
 - access rings, 160–166*
 - customer network, 174–178*
 - Frame Relay/ATM, 138–141, 150*
 - IOF rings, 153–155*
 - IP, 143, 151*
 - legacy components, 148–149*
 - MPLS, 143, 151*
 - MSSPs, 171–174*
 - NGOSS, 166–171*
 - private, 155–159*
 - PSTN, 135–138*
 - SONET, 141–142, 150*
 - transport, 144–148*
- ONS 15454 ML-Series Ethernet, 287–288
- point-to-point transport, 288
- RPR transport, 288
- SNA, 150

arrayed waveguide grating (AWG), 343**asynchronous data replication, 313–314****ATM (Asynchronous Transfer Mode), 138–141, 150, 199****A-to-Z circuit provisioning, 499****attaching telephones, 340****attenuation, manual DWDM design, 379–380****audit trails, 480, 499****automatic daily memory backups, 500****Automatic In-Service (AINS), 477****automatic protection switching (APS), 158, 322, 393****automatic routed circuits, 429–430****availability**

- bandwidth, 513
- HA, 496

AWG (arrayed waveguide grating), 343**B****backplane interfaces, 220–222**

- AIC-I cards, 339
- environmental alarm connections, 234
- ONS 15454 Shelf Assembly, 329–330

backups

- databases, 438–439, 452–453
- memory, 500

bandwidth

- available, 513
- CIR, 513
- circuits, 278
- concatenation, 61–63
- default best-effort, 513
- high-bandwidth services, 11–19
- LANs, 9–11
- Layer 2 topologies, 512
- ONS 15454, 219
- service-provider
 - management, 513
- sharing, 123
- waste of, 121
- XC cards, 229

BDFB (battery distribution fuse bay), 408**benefits**

- of DWDM, 107
- of Frame Relay, 140

BER (bit error rate), 462**bidirectional line switch ring (BLSR), 26, 197, 390****B-ISDN (Broadband Integrated Services Digital Network), 135****bit error rate (BER), 462****BITS (Building Integrated Timing Supply), 75–76, 184, 221, 330****BLANK/FILLER, 231****BLSR (bidirectional line switch ring), 26, 197, 390****BML (Business Management Layer), 498****BNC (Bayonet Neill-Concelman), 222****bridges, 292–294****Broadband Integrated Services Digital Network (B-ISDN), 135****Building Integrated Timing Supply.***See* BITS**Business Management Layer (BML), 498****bytes**

- interleaving, 61
- line overhead, 68
- path overhead, 70
- section overhead, 67

C

- cabling, 109**
 - troubleshooting, 454
- calculations, ROADM ring power, 385**
- CAM (content addressable memory), 293**
- capacity**
 - 2-fiber BLSR operations, 203
 - 4-fiber BLSR operations, 209
 - LCAS, 243, 320
- capital expense reduction, 41–43**
- cards**
 - data service, 37
 - electrical service, 33–35
 - LEDS, 453
 - optical service, 36
 - SAN, 37–38
 - sparing, 439
- carrier loss, G1K ports, 476–477**
- CCAT (contiguous concatenated) rates, 158, 320**
- CE (customer edge), 143**
- central office (CO), 137**
- CE-Series Ethernet interface cards, 240, 279–284**
- CEV (controlled-environment vault), 146, 231**
- channels, 66–71**
 - DCCs, 418
 - four-channel cards, 348–349
 - LDCC, 419
 - OADM cards, 353–354
 - overhead (SONET), 66
 - PCA, 205
 - SDCC, 418
 - substrate, 57–60
 - user data, 235, 340–341
- checklists, data gathering, 455–456**
- chromatic dispersion, 381**
- CIR (Committed Information Rate), 513–514**
- circuits, 462**
 - AIC-I, 230–231
 - environmental alarms, 231, 234*
 - orderwires, 234–235*
 - power supply voltage monitoring, 235*
 - user data channels, 235*
- A-to-Z provisioning, 499
- automatic routed, 429–430
- bandwidth, 278
- CE-Series, 281–283
- creating, 428–432
- EVC, 117
- fixed, 121
- manually routed, 431–432
- monitoring, 458
- ONS 15454 E-Series, 273
- PCA, 291
- troubleshooting, 458
- Cisco ONS 15454, 271–272**
 - 32-channel demultiplexer cards, 345–347
 - 32-channel multiplexer cards, 342–345
 - AIC-I cards, 230–231, 335–341
 - environmental alarms, 231, 234*
 - orderwires, 234–235*
 - power supply voltage monitoring, 235*
 - user data channels, 235*
 - CE-Series Ethernet interface cards, 279–284
 - channel OADM cards, 353–354
 - CTC
 - data gathering checklists, 455–456*
 - locating problems, 447–455*
 - tools, 456–457*
 - EIAs, 222–224
 - electrical interface cards, 244–247
 - E-Series Ethernet interface cards, 272–274
 - Ethernets
 - interface cards, 238–244*
 - troubleshooting, 462–463*
 - four-band OADM filters, 350
 - four-channel cards, 348–349
 - G-Series Ethernet interface cards, 275–278
 - logging on, 460–461
 - ML-Series Ethernet interface cards, 285–298, 300–307
 - MSTP
 - analysis, 385–386*
 - configurations, 365–368*
 - design, 371*
 - dispersion compensation units, 364–365*
 - DWDM design, 371–377*
 - DWDM ITU-T channel plans, 341–342*

- manual DWDM design, 377–382*
 - MetroPlanner, 382–386*
 - optical amplifiers, 360–363*
 - ROADM, 355*
 - transponder/muxponder interfaces, 356–360*
 - one-band OADM filters, 351–352
 - provisioning, 408
 - configuring, 410–418, 420–423*
 - connecting optical cards, 424*
 - documenting, 424*
 - installing shelf, 408–410*
 - resources
 - CTC Online Help, 444–446*
 - documentation, 443–444*
 - TAC, 446*
 - troubleshooting, 443*
 - rings, 462
 - SAN, 309
 - data storage mirroring, 311–314*
 - extension solutions, 314–315*
 - overview of, 309–310*
 - protection, 321–322*
 - protocols, 310–311*
 - SONET, 318–321*
 - wavelength, 315–318*
 - Shelf Assembly, 219–222, 327–330
 - signals, 462
 - SONET/SDH optical interface cards, 235–238
 - storage networking cards, 248
 - TCCs, 225–228, 331–333
 - troubleshooting, 458–460
 - XC cards, 228–229
- Cisco Transport Controller (CTC), 161, 319, 400**
- data gathering checklists, 455–456
 - locating problems, 447–455
 - Online Help, 444–446
 - tools, 456–457
- Cisco Transport Manager. See CTM**
- CISCO15 ID (Superuser), 416**
- Class of service (CoS), 513**
- CLEC (competitive local exchange carrier), 5**
- CLEI (Common Language Equipment Identification), 171**
- clients, 503–509**
- architecture, 500–501
 - management, 502
 - protection, 109
- CLIs (command-line interfaces), 39**
- clocks, 73, 185. See also timing**
- external/line-timed configuration, 186
 - internal/line-timed configuration, 188
- CNM (customer network management), 496**
- CO (central office), 137**
- command-line interfaces (CLIs), 39**
- commands**
- copy-run-start, 303
 - get, 480
 - getNext, 480
 - show cdp neighbors, 307
 - show running-config, 304
 - TL1, 483
- Committed Information Rate (CIR), 513–514**
- common equipment cards, installing, 410–412**
- Common Language Equipment Identification (CLEI), 171**
- Common Object Request Broker Architecture (CORBA), 398**
- community names, provisioning, 481**
- competition, SANs, 87**
- competitive local exchange carrier (CLEC), 5**
- components, SONET/SDH, 64–65**
- concatenation**
- SONET/SDH, 61–63
 - VCAT, 158
- concrete huts, 231**
- conditions**
- monitoring, 426
 - SNMP traps, 472
 - troubleshooting, 432
- Conditions tab (CTC), 449**
- configuration**
- circuits, 428–432
 - external/line-timed, 186
 - file management, 302
 - internal/line-timed, 188
 - ONS 15454
 - connecting optical cards, 424*
 - documenting, 424*
 - provisioning, 410–413, 415–423*
 - SNMP, 481
- connections**
- AIC-I cards, 339

backplane environmental alarms, 234
 BITS, 184
 craft-management, 331
 CTM, 501
 ESCON, 91–93, 310–311
 FICON, 91, 311
 incorrect fibers, troubleshooting, 459
 LANs, 139–140
 ONS 15454, 408
 optical cards, 424
 POP, 144
 troubleshooting, 455

constant gain mode (OPT-PRE), 361

constant power mode
 OPT-BST, 363
 OPT-PRE, 361

content addressable memory (CAM), 293

contiguous concatenated (CCAT) rates, 320

control bandwidth, avoiding, 513

control flow, 277

controlled-environment vault (CEV), 146, 231

copy-run-start command, 303

CORBA (Common Object Request Broker Architecture), 398

correlation, alarms, 496

CoS (Class of service), 513

cost, SANs, 86

course wavelength-division multiplexing (CWDM), 15, 61, 102–103

CPE (customer premises equipment), 14, 151

craft management systems, 167
 connections, 222
 backplane interfaces, 331

cross-connect (XC) cards, 183, 228–229, 411

cross-connect loopbacks, 457

Cross-Connect Virtual Tributary (XCVT), 229

cross-connecting, 22

CTC (Cisco Transport Controller), 161, 319, 400
 data gathering checklists, 455–456
 locating problems, 447–455
 Online Help, 444–446
 tools, 456–457

CTM (Cisco Transport Manager), 398
 architecture, 500–501
 HA architecture, 511
 management, 502
configuration, 504
fault, 503

HA, 509
performance, 505–506
security, 507–508

customer edge (CE), 143

customer network architecture, 174–178

customer network management (CNM), 496

customer premises equipment (CPE), 14, 151

customizing security profiles, 508

CWDM (course wavelength-division multiplexing), 15, 61, 102–103

D

daily memory backups, 500

DAS (Direct Attached Storage), 84

data communication channels (DCCs), 167, 192, 418, 472

data discovery, 496

data gathering checklists, 455–456

data service cards, 37

databases
 backups, 438–439, 452–453
 restoration, 439
 TCCs, 331

DC (direct current), 182, 409

DCCs (data communication channels), 167, 192, 418, 472

DCN (data communication network), 167

DCSs (digital cross-connect system), 9, 209

default best-effort bandwidth, 513

delay, round-trip, 319

demultiplexer cards, 345–347
 32 DMX, 347
 32 DMX-O, 346
 four-channel, 348–349

Dense Wavelength Division Multiplexing. See DWDM

density, IOF, 155

design, 371–374, 376–386. See also configuration
 MSPP, 181
case study, 249–267
methodology, 181
network management, 191–192
production, 182–186
timing, 186–191

MSTP, 371

ONS 15454, 219–222

diagnostics
 files, 452
 TCCs, 332
diagrams (faceplates)
 ACI-I, 231
 TCC2/TCC2P, 226
digital cross-connect (DSX) panels, 209
digital cross-connect systems (DCSs), 9, 209
digital loop carrier (DLC), 146, 199
digital multiplexing, SONET/SDH, 50–54
digital subscriber line (DSL), 137
digital subscriber line access multiplexer (DSLAM), 199
Direct Attached Storage (DAS), 84
direct current (DC), 182, 409
dirty fiber connectors, 459
discovery, data, 496
dispersion, 381
DLC (digital loop carrier), 146, 199
documentation, ONS 15454
 configuration, 424
downloads, software, 41
DRI (Dual Ring Interconnect), 212
drivers (market)
 capital expense reduction, 41–43
 high-bandwidth services, 11–19
 increased demand for LAN
 bandwidth, 9–11
 MSPPs, 8
 OAM&P, 39–41
 TCO, 20–24, 27–38
drops
 cards off MSPPs, 32
 service, 21
 shelf, 23
DS1 hierarchy (North American digital hierarchy), 50–52
DS1-14 interface cards, 245
DS1-56 interface cards, 246
DS1N-14 interface cards, 245
DS3 ports, 480
DS3/EC1-48 interface cards, 247
DS3-12 interface cards, 246
DS3-12E interface cards, 246
DS3N-12 interface cards, 246
DS3N-12E interface cards, 246
DS3XM-12 interface cards, 247
DS3XM-6 interface cards, 247

DSL (digital subscriber line), 137
DSLAM (digital subscriber line access multiplexer), 199
DSX (digital cross-connect) panels, 209
Dual Ring Interconnect (DRI), 212
DWDM (Dense Wavelength Division Multiplexing), 315–318, 341–342, 392–395
 access rings, 162
 fiber optic, 101–102
 history of, 98–101
 integration, 103–110
 OSC-CSM, 335
 OSCM, 334
 overview of, 98
 SAN, 311
 services, 15–16
 transport networks, 154
 WDM, 102–103

E

EC1-12 interface cards, 246
EDFAs (erbium-doped fiber amplifiers), 107
EIAs (Electrical Interface Assemblies), 221–224, 329
electrical interface cards, 244–247
electrical service cards, 33–35
electromagnetic interference (EMI), 231
electrostatic discharge (ESD), 231
Element Management Layer (EML), 498
element-management System (EMS), 495, 499–509
elements, installing NEs, 412–415
EMI (electromagnetic interference), 231
EML (Element Management Layer), 498
EMS (element-management System), 495, 499–509
end-to-end provisioning, 39
ENEs (external network elements), 192
Enterprise Systems Connection (ESCON), 5, 91–93, 310–311
environmental alarms, 222, 231, 234
 AIC-I, 231, 234
 AIC-I cards, 337–339
 backplane interfaces, 330
EOW (Express Orderwire), 235

EPL (Ethernet Private Line), 13, 156, 275
equipment, SONET/SDH, 64–65
erbium-doped fiber amplifiers (EDFAs), 107
ERS (Ethernet Relay Service), 156
ESCON (Enterprise Systems Connection), 5,
91–93, 310–311
ESD (electrostatic discharge), 231
E-Series Ethernet interface cards, 241–242,
272–274
ESF (Extended Superframe), 422
Ethernet, 510–517
 emergence of, 112–113
 FE, 111
 GigE, 112
 history of, 110–111
 interface cards, 238–244
 Layer 2 Ethernet Wizard, 514
 management, 509
 ONS 15454, 462–463
 over MSPP, 113–115
 metro services, 116–120
 point-to-point, 120–122
 RPR, 122–129
 overview of, 110
 performance, 488–492
 private MSPPs, 156
 services, 12–14
 TL1, 484
Ethernet Private Line (EPL), 13, 156, 275
Ethernet Relay Service (ERS), 156
EVC (Ethernet virtual circuit), 117
events
 logs, 41
 nonalarmed, 462
EWS (Ethernet Wire Service), 13, 156
Express Orderwire (EOW), 235
Extended Superframe (ESF), 422
extension solutions, SAN, 314–315
external network elements (ENEs), 192
external timing, 77
external/line-timed configuration, 186

F

faceplates

4MD-xx.x, 349
 AD-1C-xx.x, 354

AD2C-xx.x, 354
 AD-4C.xx.x, 354
 AIC-I, 231, 336, 340
 OSC-CSM, 335
 OSCM, 334
 TCC2/TCC2P, 226, 332
Facility (FAC), 475
facility loopbacks, 457
FAIL LED (AIC-I), 231
failures, RPR, 297–298
Fast Ethernet (FE), 111
fault management, 399
FC (Fibre Channel), 5, 90–91, 309–310
FCIP (Fibre Channel over IP), 94, 311
FC-MR-4 (Fibre Channel Multirate 4-Port)
card, 318
FE (Fast Ethernet), 111
Fiber Connection (FICON), 5, 91, 311
fiber optics, 45–49, 101–102
Fibre Channel (FC), 5, 90–91, 309–310
Fibre Channel Multirate 4-Port (Fc-MR-4)
card, 318
Fibre Channel over IP (FCIP), 94, 311
FICON (Fiber Connection), 5, 91, 311
files
 configuration, 302
 diagnostics, 452
filters
 four-band OADM, 350
 one-band OADM, 351–352
fixed circuits, 121
fixed-channel optical add/drop, 396–397
flexibility, IOF, 155
flow, control, 277
flow-through provisioning, 495
formats, AIDs, 476
four-band OADM filters, 350
four-channel multiplexer/demultiplexer
cards, 348–349
four-wave mixing (FWM), 373
Frame mode (GFP), 128
Frame Relay, 138–141, 150
frames, 277
 concatenation, 62
 GFP, 128
 ground terminals, 221, 330, 408
 SONET/SDH, 50–54
FWM (four-wave mixing), 373

G

- G1K ports, carrier loss on, 476–477**
- gateway network elements (GNEs), 192, 400, 496**
- gathering data (checklists), 455–456**
- GBICs (gigabit interface converters), 28, 239, 275, 319, 462**
- GEC (Gigabit EtherChannel), 278**
- Generic Framing Procedure (GFP), 128, 318**
- get command, 480**
- getNext command, 480**
- GFP (Generic Framing Procedure), 128, 318**
- Gigabit EtherChannel (GEC), 278**
- Gigabit Ethernet (GigE), 112, 183**
- gigabit interface converters. *See* GBICs**
- GigE (Gigabit Ethernet), 112, 183**
- Global Positioning System (GPS), 184**
- GNEs (gateway network elements), 192, 400, 496**
- GPS (Global Positioning System), 184**
- graphical user interface (GUI), 26, 39**
- grounding frames, ONS 15454, 408**
- groups, bridges, 292**
- G-Series**
 - Ethernet interface cards, 275–278
 - interface cards, 239
- GUI (graphical user interface), 26, 39**

H

- HA (high availability), 496, 511**
- HD (High-Density BNC EIA), 222**
- HD mini-BNC EIA, 223**
- HDSL (high-bit digital subscriber line), 21**
- high availability (HA), 496, 511**
- high-bandwidth services, 11–19**
- high-bit digital subscriber line (HDSL), 21**
- High-Density (HD) BNC EIA, 222**
- higher-rate signals, 60**
- high-speed optical cards, 28–32**
- History tab (CTC), 450**
- hubbed rings, 367**

I

- I/O (input/output)**
 - ports, 197
 - performance, 90
- IBM InterSystem Channel (ISC) interfaces, 316**
- ILECs (incumbent local exchange carriers), 5, 470**
- incorrect fibers, troubleshooting, 459**
- increased demand for LAN bandwidth, 9–11**
- incumbent local exchange carriers. *See* ILECs**
- indexes of refraction (Snell's Law), 47–48**
- initializing TCCs, 331**
- input/output. *See* I/O**
- installing**
 - common equipment cards, 410–412
 - cross-connect cards, 411
 - MetroPlanner, 385
 - Nes, 412–415
 - online Help, 444–446
 - ONS 15454shelf, 408–410
- integration**
 - DRI, 212
 - DWDM/MSPPs, 103–110
 - OSS, 499
 - storage cards, 96–98
- integrity, links, 278**
- interexchange carrier (IXC), 138**
- interfaces, 231–235, 272–288, 290–298, 300–307**
 - AIC-I, 230–341, 412
 - AICs, 410
 - backplane
 - AIC-I cards, 339*
 - environmental alarm connections, 234*
 - ONS 15454 Shelf Assembly, 329–330*
 - CCAT, 158
 - CLI, 39
 - EIAs, 221–224, 329
 - electrical cards, 244–247
 - Ethernet cards, 238–244
 - GBICs, 275, 319, 462
 - G-Series interface cards, 239
 - GUI, 26, 39

ISC, 316
 modules
 adding/removing, 426
 installing, 410–412
 muxponder, 356–360
 NBI, 468
 OC-N, 183
 OSCM, 334
 SCSI, 310
 SL-Series FC/FICON, 248
 SONET/SDH optical cards, 235–238
 TDM, 183
 transponder, 356–360
 UNI, 514

internal clocks, 185
internal/line-timed configuration, 188
International Telecommunications Union (ITU), 497
Internet Protocol. *See* IP
Internet Protocol Television (IPTV), 146
Internet service provider (ISP), 200
Internetwork Packet eXchange (IPX), 150
interoffice facilities. *See* IOFs
IOFs (interoffice facilities), 144, 153–155, 497
IP (Internet Protocol), 143, 151
 addresses
 configuring, 415–416
 TCCs, 331
 troubleshooting, 455
 FCIP, 94
IPT (IP-based telephony), 18
IPTV (Internet Protocol Television), 146
IPX (Internetwork Packet eXchange), 150
ISC (IBM InterSystem Channel)
 interfaces, 316
ISP (Internet service provider), 200
ITU (International Telecommunications Union), 497
IXC (interexchange carrier), 138

J–K

JRE (Java Runtime Environment), 444
 kinked fibers, 459

L

L2 Service Wizard, 512
labels, MPLS, 143
LANs (local-area network interfaces), 139
 backplane interfaces, 330
 bandwidth, 9–11
 connecting, 139–140
 SANs, 83
 terminations, 222
large-scale network management, 495–496
 EMS, 499–509
 Ethernet, 509
 Layer 1 provisioning, 510–511
 Layer 2 provisioning, 512–514, 517
 layers, 497, 499
 NBI, 517–518
LATA (local access and transport area), 138
Layer 1, Ethernet service interfaces, 238–241
Layer 2
 Ethernet service interfaces, 242–244
 Ethernet Wizard, 514
Layer 3, Ethernet service interfaces, 242–244
layers
 management, 497–499
 RPR, 124
LBO (Line Build-Out) settings, 454
LCAS (Link Capacity Adjustment Scheme), 127, 243, 320
LDCC (Line DCC), 419
LEDs (light emitting diodes), 102, 453
legacy components, 148–149
legacy optical platforms, 20
 OC-12, 21–22
 OC-48, 23
levels, FC, 92
LGX (Light Guide Cross-connect) panels, 424
light emitting diodes (LEDs), 102, 453
Light Guide Cross-connect (LGX) panels, 424
Line Build-Out (LBO) settings, 454
Line DCC (LDCC), 419
linear topologies, MSTP, 365
lines
 SONET/SDH transmission segments, 68–69
 timing, 77
line-terminating equipment (LTE), 189

Link Capacity Adjustment Scheme (LCAS), 127, 243, 320
links, 278, 459–460
LLQ (low-latency queue), 513
loading MIBs, 482
local access and transport area (LATA), 138
local alarms, 222, 331
Local Orderwire (LOW), 235
local-area networks. *See* LANs
LOF (loss of frame), 395
logging on (to ONS 15454), 460–461
logs, 41
loopbacks, 456–457
LoS (loss of service), 156
LOS (loss of signal), 478
loss of frame (LOF), 395
loss of service (LoS), 156
loss of signal (LOS), 478
LOW (Local Orderwire), 235
low light levels, 460
low-latency queue (LLQ), 513
LTE (line-terminating equipment), 189

M

maintenance, 435, 437–439
MAN (metropolitan-area network), 9
management, 302, 470–478, 480–486
 CNM, 496
 craft management systems, 167
 CTM, 502
 configuration, 504
 fault, 503
 HA, 509
 performance, 505–506
 security, 507–508
 EMS, 495
 large-scale network, 495–496
 EMS, 499–509
 Ethernets, 509–514, 517
 layers, 497, 499
 NBI, 517–518
 MSPPs, 155, 468–470, 486–492
 policies, 496
 TMN, 497
Management Interface Blocks (MIBs), 170, 482
MANs (metropolitan-area networks), 9, 163

manually routed circuits, 431–432
mapping, 55–63
market drivers
 MSPP-based DWDM, 110
 MSPPs, 8
 capital expense reduction, 41–43
 demand for LAN bandwidth, 9–11
 high-bandwidth services, 11–19
 OAM&P, 39, 41
 TCO, 20–24, 27–38
mean-time-to-repair (MTTR), 496
memory
 backups, 500
 CAM, 293
mesh topologies, private MSPPs, 165
meshed rings, 368
meshing, waste of bandwidth, 121
messages, status, 189–191
metro Ethernet services, 116–120
metropolitan-area networks (MANs), 9, 163
MIBs (Management Interface Blocks), 170, 482
mirroring, 311–314
ML-Series Ethernet interface cards, 242, 285–294, 296–307
MMF (multimode fiber), 48–49
mobile telephone switching office (MTSO), 200
modems
 backplane interfaces, 331
 terminations, 222
modes
 GFP, 128
 ONS 15454 E-Series Ethernet interface
 cards, 273
 optical fiber, 48–49
modules, 410–412
 interfaces, 426
 STM, 57
monitoring, 340
 alarms, 425–426
 circuits, 458
 conditions, 426
 MSPPs, 467
 CTC, 484–486
 fault management, 468–470
 local craft interfaces, 492
 performance, 486–492
 SNMP MIBs, 470–478, 480–482
 TL1, 482–484

- NMS, 495
- performance, 435, 437
- power supply voltage (AIC-I), 235
- RMON, 398
- thresholds, 487
- voltage, 332
- MPLS (Multiprotocol Label Switching), 143, 151**
- MSPPs (Multiservice Provisioning Platforms), 5, 8, 229**
 - acceptance testing, 433–435
 - AIC-I cards, 230–235
 - alarms, 425–426
 - architecture, 135, 152
 - access rings, 160–166*
 - customer network, 174–178*
 - Frame Relay/ATM, 138–141, 150*
 - IOF rings, 153–155*
 - IP, 143, 151*
 - legacy components, 148–149*
 - MPLS, 143, 151*
 - MSPPs, 171–174*
 - NGOSS, 166–171*
 - private, 155–159*
 - PSTN, 135–138*
 - SONET, 141–142, 150*
 - transport, 144–148*
 - conditions, 426
 - design, 181
 - case study, 249–267*
 - methodology, 181*
 - network management, 191–192*
 - production, 182–186*
 - timing, 186–191*
 - DWDM
 - fiber optic cables, 101–102*
 - integration, 103–110*
 - WDM, 102–103*
 - EIAs, 222–224
 - Ethernet over, 113–115
 - metro services, 116–120*
 - point-to-point, 120–122*
 - RPR, 122–129*
 - fault management, 468–470
 - CTC, 484–486*
 - SNMP MIBs, 470–482*
 - TL1, 482–484*
 - fiber optics, 45–49
 - local craft interfaces, 492
 - maintenance, 435–439
 - market drivers, 8
 - capital expenses reduction, 41–43*
 - demand for LAN bandwidth, 9–11*
 - high-bandwidth services, 11–19*
 - OAM&P, 39, 41*
 - TCO, 20–29, 32–38*
 - monitoring, 467
 - ONS 15454, 335–341, 355–368
 - 32-channel demultiplexer cards, 345–347*
 - 32-channel multiplexer cards, 342–345*
 - channel OADM cards, 353–354*
 - four-band OADM filters, 350*
 - four-channel cards, 348–349*
 - MSTP DWM ITU-T, 341–342*
 - one-band OADM filters, 351–352*
 - Shelf Assembly, 327–328*
 - TCCs, 331–333*
 - ONS 15454, 271–272
 - E-Series Ethernet interface cards, 272–274*
 - G-Series Ethernet interface cards, 275–284*
 - ML-Series Ethernet interface cards, 285–294, 296–307*
 - Shelf Assembly, 219*
 - overview of, 45
 - performance, 486–492
 - SAN over, 95–98
 - services, 427–432
 - software upgrades, 439–441
 - TCCS, 225–228
 - topologies, 193
 - BLSR, 200–209*
 - linear, 193–195*
 - mesh networks, 214–216*
 - ring-to-ring interconnect, 212–213*
 - subtending rings, 209–211*
 - subtending shelves, 211*
 - UPSR, 195–200*
 - XC cards, 228–229
- MS-SPR (multiplex section shared protection rings), 390**
- MSTP (Multiservice Transport Platform), 16**
 - design, 371
 - analysis, 385–386*
 - DWDM, 371–377*
 - manual DWDM, 377–382*
 - MetroPlanner, 382–386*

DWDM protection, 392–395
 wavelength services, 389
 configuring, 401
 Ethernet, 391
 implementing, 395–397
 managing, 398–399
 performance, 402
 SAN, 390–391
 security, 403
 SONET/SDH, 390
 variable bit-rate, 391

MTSO (mobile telephone switching office), 200

MTTR (mean-time-to-repair), 496

Multi Service Transport Platform (MSTP), 16

Multicard EtherSwitch mode, 273

multicast traffic, 121

multihubbed rings, 367

multimode fiber (MMF), 48–49

multiplex section shared protection rings (MS-SPR), 390

multiplexer cards, 342–345

 32 MUX-O, 343

 32 WSS, 344–345

 four-channel, 348–349

multipoint Ethernet monitoring, 491–492

Multiprotocol Label Switching (MPLS), 143, 151

Multiservice Provisioning Platforms. *See* MSPPs

Multiservice Transport Platform. *See* MSTP

muxponder cards, 322

N

names, provisioning, 481

NAS (Network Attached Storage), 85, 310

NAT (network address translation), 151

NBI (Northbound Interface), 468

 integration, 517–518

NEBS (Network Equipment Building Standards), 231

NEs (network elements), 412–415, 483, 496

 audit trails, 499

network address translation (NAT), 151

Network Attached Storage (NAS), 85, 310

network elements. *See* NEs

Network Equipment Building Standards (NEBS), 231

Network Management Layer (NML), 498

Network Monitoring and Analysis (NMA), 148

Network Operations Center (NOC), 167, 192

network-management system (NMS), 495

networks, 191–203, 205–216, 219, 311

 MSPP. *See also* MSPPs

fiber optics, 45

optical fiber, 46–49

overview of, 45

 ONS 15454, 220–222

 OSS synchronization, 497

 SAN

data storage mirroring, 311–314

extension solutions, 314–315

overview of, 309–310

protection, 321–322

protocols, 310–311

SONET, 318–321

wavelength, 315–318

 synchronization, 420–423

 topologies, 193

NGOSS (next-generation operational support systems), 166–171

NMA (Network Monitoring and Analysis), 148

NML (Network Management Layer), 498

NMS (network-management system), 495

NOC (Network Operations Center), 167, 192

nodes, 334

nonalarmed events, 462

nonzero, dispersion-shifted fiber (NZDF), 372

North American digital hierarchy, 50–52

Northbound Interface (NBI), 468

 integration, 517–518

NZDF (nonzero, dispersion-shifted fiber), 372

O

OADMs (optical add/drop multiplexers), 155

 channel cards, 353–354

 four-band filters, 350

 one-band filters, 351–352

OAM&P (operations, administration,

maintenance, and provisioning), 39, 41, 166

OC (Optical Carrier), 56, 146

OC-12 optical cards, 21–22

OC-192 interfaces, 255

OC-48 optical cards, 23

OC-N (Optical) interfaces, 183

- one-band OADM filters, 351–352**
- Online Help, 444–446**
- ONS 15454, 271–272**
 - 32-channel demultiplexer cards, 345–347
 - 32-channel multiplexer cards, 342–345
 - AIC-I, 335–341
 - AIC-I cards, 230–235
 - CE-Series Ethernet interface cards, 279–284
 - channel OADM cards, 353–354
 - CTC
 - data gathering checklists, 455–456*
 - locating problems, 447–455*
 - tools, 456–457*
 - EIAs, 222–224
 - electrical interface cards, 244–247
 - E-Series Ethernet interface cards, 272–274
 - Ethernets
 - interface cards, 238–244*
 - troubleshooting, 462–463*
 - four-band OADM filters, 350
 - four-channel cards, 348–349
 - G-Series Ethernet interface cards, 275–278
 - logging on, 460–461
 - ML-Series Ethernet interface cards, 285–294, 296–307
 - MSTP
 - configurations, 365–368*
 - dispersion compensation units, 364–365*
 - DWDM, 392–395*
 - Ethernet services, 391*
 - optical amplifiers, 360–363*
 - ROADM, 355*
 - SAN services, 390–391*
 - SONET/SDH services, 390*
 - transponder/multiplexer interfaces, 356–360*
 - variable bit-rate services, 391*
 - wavelength services, 389, 395–403*
 - MSTP DWDM ITU-T channel plans, 341–342
 - one-band OADM filters, 351–352
 - provisioning, 408
 - configuring, 410–418, 420–423*
 - connecting optical cards, 424*
 - documenting, 424*
 - installing shelf, 408–410*
 - resources
 - CTC Online Help, 444–446*
 - documentation, 443–444*
 - TAC, 446*
 - troubleshooting, 443*
 - rings, 462
 - Shelf Assembly, 219–222, 327–330
 - signals, 462
 - SONET/SDH optical interface cards, 235–238
 - storage networking cards, 248
 - TCCs, 225–228, 331–333
 - troubleshooting, 458–460
 - XC cards, 228–229
- OOS (Out-of-service), 321**
- OOS-AINS (Out of Service-Automatic in Service) state, 424**
- Open Systems Interconnection (OSI), 14 operational support system. *See* OSS**
- Operations Systems Modifications for the Integration of Network Elements (OSMINE), 148**
- operations, administration, maintenance, and provisioning. *See* OAM&P**
- OPT-BST (optical booster amplifier), 360, 362–363**
- Optical (OC-N) interfaces, 183**
- optical add/drop multiplexers. *See* OADMs**
- optical booster amplifier (OPT-BST), 360–363**
- optical cards**
 - connecting, 424
 - high-speed, 28–29, 32
- Optical Carrier (OC), 56, 146**
- optical links, troubleshooting, 459–460**
- optical preamplifier (OPT-PRE), 360–361**
- optical service cards, 36**
- optical service channel module (OSCM), 334**
- optimization**
 - MetroPlanner, 385
 - ONS 15454, 408
- OPT-PRE (optical preamplifier), 360–361**
- orderwires, 234–235, 340**
- OSC-CSM, 335**
- OSCM (optical service channel module), 334**
- OSI (Open Systems Interconnection), 14**
- OSMINE (Operations Systems Modifications for the Integration of Network Elements), 148**
- OSS (operating support systems), 8, 497, 517–518**
 - management, 499–509

Out of Service-Automatic in Service
(OOS-AINS), 424
Out-of-service (OOS), 321
overhead channels, 66–71

P

PABX (private automatic branch exchange), 137
panels, DSX, 209
passive DWDM, 104
pass-through, 294
Path Protected Mesh Networks (PPMN), 27,
152, 215
paths, SONET/SDH transmission segments,
69–71
PBX (private branch exchange) switches, 183
PCA (Protection Channel Access), 205, 291
PCM (pulse code modulation), 67
PDH (plesiochronous digital hierarchy), 138
Peak Information Rate (PIR), 514
performance
 ATM, 150
 Frame Relay, 150
 IO, 90
 monitoring, 435, 437
Performance tab (CTC), 451
phases, evolution of SANs, 88–90
pigtailling, 102
PIR (Peak Information Rate), 514
plain old telephone service (POTS), 146, 199
platforms
 legacy optical, 20
 OC-12, 21–22
 OC-48, 23
 MSPPs, 5, 8
 capital expense reduction, 41–43
 demand for LAN bandwidth, 9–11
 high-bandwidth services, 11–19
 market drivers, 8
 OAM&P, 39, 41
 TCO, 20–24, 27–38
plesiochronous digital hierarchy (PDH), 138
PLSs (Private Line Services), 116
point of presence (POP), 144, 192
point-to-point Ethernet over MSPP, 120–122
Point-to-Point Protocol (PPP), 141
point-to-point transport architecture, 288

policies, management, 496
POP (point of presence), 144, 192
Port-mapped mode, 273
ports
 DS3, 480
 G1K, 476–477
 I/O, 197
POTS (plain old telephone service), 146, 199
power supply
 connections, 409
 MSPPs, 155
 supply voltage monitoring, AIC-I, 235
 troubleshooting, 454
 voltage monitoring, 235, 332, 340
PPMN (Path Protected Mesh Networks), 27,
152, 215
PPP (Point-to-Point Protocol), 141
PRI (primary rate ISDN), 200
primary reference source (PRS), 420
prioritization, timing, 189
private architecture, 155–159
private automatic branch exchange (PABX), 137
private branch exchange (PBX) switches, 183
Private Line Services (PLSs), 116
private rings, 146–148
production design, 182–186
profiles
 alarms, 500
 security, 508
propagation, light (in fiber), 46–48
protection, 321–322
 APS, 322
 bandwidth, 121
 DWDM, 109
 mechanisms, 182–186
 switches, 478–479
Protection Channel Access (PCA), 205, 291
PROTNA (Protection Unit Not Available), 225
protocols, 310–311
 Frame Relay, 150
 IP, 94
 IPTV, 146
 PPP, 141
 SNMP, 398
 STP, 514
provisioning, 278–283, 408–410, 424
 A-to-Z circuit, 499
 community names, 481

end-to-end, 39
 E-Series Ethernet interface cards, 273–274
 flow-through, 495
 MSPPs, 155
 ONS 15454, 408–418, 420–423
 RPR, 300–307
 services, 427–432

PRS (primary reference source), 420

PSTN (public switched telephone network), 135–138, 199

pulse code modulation (PCM), 67

Q

Q-in-Q, 126

QoS (quality of service), 14

queues, 279–280

R

rates, SONET/SDH, 55–63

RBOC (Regional Bell Operating Company), 148

reconfigurable optical add/drop. *See* ROADM

reconfigurable rings, 368

reduction, capital expense, 41–43

redundancy

MSPPs, 181

cable route diversity, 185

common control redundancy, 182–183

multiple shelves, 185

redundant power feeds, 182

rings, 186

synchronization, 184–185

tributary interface protection, 183–184

RPR, 146

references, timing, 188–189

reflection, 46–48

refraction, 46–48

Regional Bell Operating Company (RBOC), 148

regulations, SANs, 86

reliability, 181

cable route diversity, 185

common control redundancy, 182–183

multiple shelves, 185

redundant power feeds, 182

rings, 186

synchronization, 184–185

tributary interface protection, 183–184

remote access, 150

remote-monitoring. *See* RMON

replication

asynchronous data, 313–314

synchronous data, 312–313

reports, alarms, 332

resiliency, 123

resilient packet ring. *See* RPR

resources, 443–446

restoring databases, 439

RET1/BAT1 terminals, 221

retrieving, 480

return on investment (ROI), 150

reversion, software, 441

rings

ONS 15454, 462

topologies, 366–368

RMON (remote-monitoring), 398, 488

Ethernets, 490

thresholds, 489–490

ROADM (reconfigurable optical add/drop), 368

DWDM, 397–398

ring power calculations, 385

ROI (return on investment), 150

round-trip delay, SAN, 319

Route Processor Redundancy (RPR), 146

routes, 205

routing circuits

automatically, 429–430

manually, 431–432

Routing Layer, 242–244

RPR (resilient packet ring), 14, 122–129

ONS 15454 ML-Series Ethernet, 288–298

provisioning, 300–307

transport architecture, 288

RPR (Route Processor Redundancy), 146

S

SANs (storage-area networks), 5, 309

data storage mirroring, 311–314

demand for, 86–88

ESCON, 91–93

evolution of, 88–90

- extension solutions, 314–315
- FC, 90–91
- FCIP, 94
- FICON, 91
- history of, 83–84
- over MSPPs, 95–98
- networking cards, 248
- overview of, 82–83, 86, 309–310
- private MSPPs, 158
- protection, 321–322
- protocols, 310–311
- service cards, 37–38
- services, 17–18
- SONET, 318–321
- wavelength, 315–318
- scalability**
 - IOF, 155
 - MPLS VPNs, 151
- scratched connectors, 459**
- SCSI (Small Computer System Interface), 310**
- SD (signal degrade), 109, 395, 462**
- SDCC (Section Data Communications Channel), 418**
- SDH (Synchronous Digital Hierarchy), 77, 184**
 - digital multiplexing/framing, 50–54
 - equipment, 64–65
 - ONS 15454 CE-Series Ethernet interface cards, 281–283
 - optical interface cards, 235–238
 - overview of, 49–50
 - rates/tributary mapping, 55–63
 - synchronization, 72
 - timing, 73–75
 - wavelength services, 390
- Section Data Communications Channel (SDCC), 418**
- sections, SONET/SDH transmissions, 66–67**
- security**
 - MPLS VPNs, 151
 - ONS 15454, 416
- selecting timing references, 188–189**
- serial numbers, retrieving, 480**
- servers, 500–502**
- Service Management Layer (SML), 498**
- service-level agreements (SLAs), 205, 398**
- service-provider management, 513**
- services, 116, 389**
 - drops, 21
 - DWDM, 15–16
 - Ethernet, 12–14
 - high-bandwidth, 11–19
 - MPLS VPNs, 151
 - provisioning, 427–432
 - SAN, 17–18
- SF (Signal Fail) LEDs, 454**
- SF (single failure), 395**
- SF (Superframe), 422**
- SFP (small form factor pluggable), 28, 316**
- shared packet ring (SPR), 273**
- sharing bandwidth, 123**
- Shelf Assembly (ONS 15454), 219–222, 327–330**
 - drops, 23
 - installing, 408–410
- show cdp neighbors command, 307**
- show running-config command, 304**
- signal degrade (SD), 109, 395, 462**
- Signal Fail (SF) LEDs, 454**
- signals, 50–54**
 - EDFAs, 107
 - higher-rate, 60
 - ONS 15454, 462
 - troubleshooting, 458–460
- Simple Network Management Protocol (SNMP), 398**
- single failure (SF), 395**
- Single-card EtherSwitch mode, 273**
- single-mode fiber (SMF), 48–49**
- SLAs (service-level agreements), 205, 398**
- SL-Series FC/FICON interface cards, 248**
- Small Computer System Interface (SCSI), 310**
- small form factor pluggable (SFP), 28, 316**
- SMB (Sub-Miniature B) EIA, 223**
- SMF (single-mode fiber), 48–49**
- SML (Service Management Layer), 498**
- SNA (Systems Network Architecture), 150**
- SNCP (subnetwork connection protection), 390**
- Snell's Law (index of refraction), 47–48**
- SNMP (Simple Network Management Protocol), 398**

software

- activation, 440
- downloads, 41
- reversion, 441
- TCCs, 331
- upgrading, 439–441, 499

SONET (Synchronous Optical Network), 9, 72, 141–142, 150, 318–321

- digital multiplexing/framing, 50–54
- equipment, 64–65
- ONS 15454 CE-Series Ethernet, 281–283
- optical interface cards, 235–238
- overhead channels, 66–71
- overview of, 49–50
- rates/tributary mapping, 55–63
- SAN, 311
- synchronization, 72
- timing, 73–77
- transport networks, 155
- wavelength services, 390

Spanning Tree Protocol (STP), 514**sparing (card), 439****spatial reuse, RPR, 298****SPE (Synchronous Payload Envelope), 54****splitting wavelengths, 109****SPR (shared packet ring), 273****SSM (synchronization status messaging), 422****standby (STBY) state, 231****status, messaging, 189–191****STBY (standby) state, 231****STM (Synchronous Transport Module), 57****storage, 331****storage-area networks. *See* SANs****STP (Spanning Tree Protocol), 514****stripping wavelength, 294****STS-1 frames, 53****STs (Synchronous Transfer Signals), 320, 457****Sub-Miniature B (Sub-Miniature) EIA, 223****subnetwork connection protection****(SNCP), 390****substrate channels, transporting, 57–60****Superframe (SF), 422****suppressing alarms, 496****switches**

- ESCON, 310–311
- FC, 309–310
- PBX, 183
- protection, 478–479

SANs, 86

switching, APS, 393**Switching Layer, 242–244****synchronization**

- networks, 420–423, 497
- SONET/SDH, 72
- status messaging, 189–191

synchronization status messaging (SSM), 422**synchronous data replication, 312–313****Synchronous Digital Hierarchy. *See* SDH****Synchronous Envelope Payload (SPE), 54****Synchronous Optical Network. *See* SONET****Synchronous Transfer Signals (STs), 320, 457****Synchronous Transport Module (STM), 57****Systems Network Architecture (SNA), 150****T****tables, alarms, 503****TAC (Technical Assistance Center), 150****TAPs (test access points), 458****TCA (Threshold Crossing Alert), 472, 487****TCC2 (Advanced Timing Communications and Control) card, 410–411, 484****TCCs (Timing, Communications, and Control) cards, 183, 225–228, 331–333, 403****TCO (total cost of ownership), 20–29, 32–38****TDM (time-division multiplexing), 5**

- private MSPPs, 159
- interfaces, 183

Technical Assistance Center (TAC), 150**telecommunications management network (TMN), 497****TEMS (Transport Element Activation Manager), 148****terminals**

- frame ground, 221, 330
- loopbacks, 457
- RET1/BAT1, 221

termination, DCCs, 419**test access points (TAPs), 458****testing, acceptance, 433–435****Threshold Crossing Alert (TCA), 472, 487****thresholds**

- monitoring, 487
- RMON, 489–490

through timing, 78

time-division frames, 50
time-division multiplexing. *See* TDM
timing
 GPS, 75–77
 SONET/SDH, 72–75
Timing Communications and Control 2 (TCC2), 410–411, 484
timing design, 186, 188–191
Timing, Communications, and Control. *See* TCCs
TIRKS (Trunk Integrated Record Keeping System), 148
TL1 (Transaction Language 1), 482–484
TMN (telecommunications management network), 497
tolerance, OSNR, 381–382
too-high light levels, 460
tools, troubleshooting, 456–457
topologies
 BLSR, 197
 Layer 2 bandwidth, 512
 linear, 365
 MSPP, 193
 BLSR, 200–209
 linear, 193–195
 mesh networks, 214–216
 ring-to-ring interconnect, 212–213
 subtending rings, 209, 211
 subtending shelves, 211
 UPSR, 195–200
 ring, 366–368
ToS (Type of Service), 9
total cost of ownership. *See* TCO
traditional DRI, 212
traditional Ethernet services, 12–14
traffic
 fiber optics, 45
 multicast, 121
 routes, 205
Transaction Language 1 (TL1), 482–484
Transparent mode (GFP), 128
Transport Element Activation Manager (TEMS), 148
Transport Layer, 238–241
transport networks, 144–148
 DWDM, 154
 ONS 15454 ML-Series, 287–288
 SONET, 155
transporting subrate channels, 57–60

traps, SNMP, 472–474
tributary mapping, 55–63
troubleshooting, 447–457, 460–463
 alarms, 432
 cabling, 454
 card LEDs, 453
 circuits, 458
 conditions, 432
 connections, 455
 maintenance, 435, 437–439
 ONS 15454, 458–460
 optical links, 459–460
 power, 454
 round-trip delay, 319
 signals, 458–460
Trunk Integrated Record Keeping System (TIRKS), 148
trunks, 399
Type of Service (ToS), 9
types of optical fiber, 48–49

U

UBIC (Universal Backplane Interface Connector), 223
UDCs (user data channels), 235, 340–341
UNI (User-to-Network Interface) ports, 514
unidirectional path switched ring. *See* UPSR
Universal Backplane Interface Connector (UBIC), 223
Universal Time Coordinated (UTC), 420
upgrading software, 439–441, 499
UPSR (unidirectional path switched ring), 26, 152, 185, 274, 390
user data channels (UDCs), 235, 340–341
users, security, 416
User-to-Network Interface (UNI) ports, 514
UTC (Universal Time Coordinated), 420

V

Variable Bindings, 474
variable optical attenuators. *See* VOAs
VCAT (virtual concatenation), 158
 rates, 320
 RPR, 126–127
VCG (VCAT Group), 320

VCI (virtual channel identifier), 166
verification, RPR, 303–307
video bandwidth, 18–19
virtual channel identifier (VCI), 166
virtual concatenated. *See* VCAT
virtual LAN (VLAN), 13
virtual path identifier (VPI), 166
Virtual Private Network (VPN), 143
Virtual Tributary (VT), 57, 475
virtual tributary group (VTG), 57–60
virtual wire operation, 339
VLAN (virtual LAN), 13
VOAs (variable optical attenuators), 343, 385, 397
voice, bandwidth, 18–19
VoIP (Voice over IP), 19, 137
voltage
 AIC-I cards, 340
 monitoring, 332
VPI (virtual path identifier), 166
VPN (Virtual Private Network), 143
VT (Virtual Tributary), 57, 475
VTG (virtual tributary group), 57–60

wavelength, 389–399, 401–403
 DWDM. *See* DWDM
 private MSPPs, 159
 splitting, 109
 storage over, 315–318
WDM (wavelength-division multiplexing), 102–103
wizards
 L2 Service Wizard, 512
 Layer 2 Ethernet Wizard, 514
WKSWPR (Working Switched to Protection), 478

XC (cross-connect) cards, 183, 228–229, 411
XCVT (Cross-Connect Virtual Tributary), 229

Y-cable protection, 109, 322

W–X–Y

WANs (wide-area networks), 9, 139
waste of bandwidth, 121