

## Numerics

---

**10-Mbps Ethernets, 269-271**

**100-Mbps Ethernets, 269, 278-279**

100BASE-FX, 281-282

design, 280-281

**1000BASE-LX, 283**

**1000BASE-SX, 283**

**1000BASE-T, 286-288**

**1000BASE-X, 283-286**

**100BASE-FX, 281-282**

**10BASE-T**

collisions, 253-254

Ethernets, 76-77, 272

design, 275-278

wiring, 272-274

**5-4-3 rule, 275**

**5-4-3-2-1 rule, 276**

## A

---

**abbreviations, bits/bytes, 45**

**AC (alternating current), 131**

**access**

network access layer (TCP/IP), 340-341

remote, history of, 23

switches, 193

VPNs, 90

**access control lists (ACLs), 407**

**access points (APs), 154-155, 209-210**

**ACK (acknowledgment)**

flags, 458

flow control through withholding, 457

**Acknowledgment Number field, 463**

**ACLs (access control lists), 407**

**active scanning, 155**

**adding analog waves to digital tests, 170**

**Address Resolution Protocol (ARP), 327, 378-384**

**addresses**

BIA, 247

broadcast, 81, 361-362

network, 434

searching, 438

shortcuts, 439-442

flooding, 302-303

IP, 31, 353

assignment, 353-362

classes, 353-362

determining assignable (in subnets), 434-444

IP routing, 344-345

managing, 373-384

networking math, 362-364

overview of, 353

public, 370

subnetting, 32, 364-368

unicast, 356

unique, 368-372

IPv4, depletion of, 370-371

MAC, 78

Destination, 245

Ethernet, 247

Source, 245

tables, 299

unknown unicast frames, 304

ranges, 438-439

unicast, 81

unknown unicast frames, 304

URLs, 35

**adjacent layer interaction, 114-115**

**administration**

IP addresses, 373

applying ARP, 378-384

comparing DHCP/static addresses, 377

dynamic IP address configuration, 375-377

static IP address configuration, 373-374

networks, 475-476

NMS, 476

out-of-band, 227

**agents, SNMP, 476**

**algorithms**

CSMA/CD, 240

Ethernet operation, 251-257

- routing protocols, 419
  - distance vector algorithms*, 419-420
  - hybrid algorithms*, 421
  - link-state algorithms*, 420
- STA, 315
- alien crosstalk**, 176
- alternating current (AC)**, 131
- American National Standards Institute (ANSI)**, 73
- American Registry for Internet Numbers (ARIN)**, 369
- American Standard Code for Information Interchange (ASCII)**, 47
- amperes**, 130
- amplitude**, 22, 167
- analog bandwidth**, 103-104, 125
- analog modems**, connecting, 21-23
- analog signals**
  - creating from digital signals, 170
  - frequency-based cable testing, 169
- analyzing IP address structures**, 358-359
- ANSI (American National Standards Institute)**, 73
- application layer (TCP/IP)**, 108, 347-349, 468
  - network management, 475-476
  - overview, 477-478
  - protocols, 469-474
- application-specific integrated circuits (ASICs)**, 298
- applications**
  - processes, 464-467
  - TCP/IP, 25
    - HTTP*, 26-28
    - IP*, 30-34
    - networking models*, 28
    - standards*, 25
    - transport layers*, 29
    - troubleshooting*, 34-44
- applying**
  - ARP, 378-384
  - powers of 2, 362
- APs (access points)**, 154-155, 209-210
- ARIN (American Registry for Internet Numbers)**, 369
- ARP (Address Resolution Protocol)**, 327, 378-384
- arp command**, 380
- AS (autonomous system)**, 418
- ASCII (American Standard Code for Information Interchange)**, 47
- ASICs (application-specific integrated circuits)**, 298

- assigning IP addresses**
  - analyzing structures, 358-359
  - classes, 359-360
  - defining classes, 356-357
  - LANs, 353-356
  - managing, 373-384
  - network numbers, 361-362
  - networking math, 362-364
  - unique, 368-372
- association, APs**, 155
- asynchronous transmission**, 271
- atoms**, 126
- attachment user interface (AUI)**, 195
- attenuation**, 132-133
  - copper cabling, 175-176
- AUI (attachment user interface)**, 195
- Auto-mdix (Automatic Medium-independent Crossover)**, 198, 288
- autonegotiation**
  - 100-Mbps Ethernet design, 280
  - duplex and speed, 257-258
- autonomous system (AS)**, 418
- auxiliary ports**, 227

## B

---

- B channels**, 220
- back-off timers**, 252
- backbones**
  - level links, 191
  - links, 280, 310
- backplanes (PCs)**, 10
- bandwidth**, 97, 416-417
  - analog, 103-104
  - data transfer time calculations, 102-103
  - LANs, 97-98
  - planning, 105
  - shared, 319-321
  - switched, 323
  - throughput, 100-101
  - WANs, 98-100
- Base 10 (decimal numbering)**, 48
  - converting, 49-56
  - IP addresses, 56-58
- Base 16 (hexadecimal numbering)**, 59
- Base 2 (binary numbering)**, 49
  - converting, 49-56
  - IP addresses, 56-58
- baseband transmissions, Ethernets**, 239

**Basic Rate Interface (BRI), 220****beacons, 155****benefits of routing and switching, 406-407****BGP (Border Gateway Protocol) metrics, 418****BIA (burned in address), 247****binary numbering (Base 2), 49**

converting, 49-56, 364

IP addresses, 56-58

**binary versions, determining subnet masks, 429-431****bits, 45-46**

determining number of host/subnet, 427-429

**blocking STP, 312-313****Bohr, Niels, 127****Boolean logic, 60-62****Border Gateway Protocol (BGP) metrics, 418****BPDU (bridge protocol data units), 315****BRI (Basic Rate Interface), 220****bridge protocol data units (BPDUs), 315****bridges, 203-204**

collisions

*domains, 206**preventing, 323-325*

Ethernet, 78-79

Layer 2, 297-301

multiport, 208

tables, 299

**broadband, 239****broadcast addresses, 81, 361-362**

network, 434

searching, 438

shortcuts, 439-442

subnets, 365

**broadcast domains**

identifying, 328-329

Layer 2, 325-328

**broadcast frames, forwarding, 304-306****broadcast subnets, 435****broadcasts, ARP, 379****browsers. See interfaces; web browsers****buffering**

fiber-optic cabling, 151

frames, 323-325

switches, 255

**building blocks, 194****burned in address (BIA), 247****bytes, 45-46****C****cable modems, 220****cables**

10BASE-T Ethernets, 272-274

Cat 5, 97

connecting, 24

copper media, 125

*digital transmission, 125-134**LANs, 134-144**signaling over, 172*

crossover cables, 274

*pinouts, 143-144**UTP, 197*

Ethernets, 141, 239

fiber-optic, 283

LANs, 189

*connecting Ethernet devices, 200-204, 206-212**connectors/media, 194-195**Ethernet physical layer, 190**PC communications models, 212-216**selecting Ethernet types, 191-193**UTP cable pinouts, 196-200*

length, 180

networks, 16-17

optical media, 146, 149-150

*comparing copper cabling, 146-147**electromagnetic spectrum, 147-148**fiber types, 151-152**transmissions, 174*

pinouts, 140

rollover cables, 144, 225

serial cables, 217

small networks (2 PCs/one cable), 4

straight-through, 141, 197, 273

testing standards, 180-182

UTP, 76

WANs, 216-217

*fixed/modular routers, 224-225**layers, 217-221**router console cabling, 225-227**selecting DCE/DTE cables, 222-223*

wireless media, 152-157

**calculating**

data transfer time, 102-103

hosts per network, 363

**CAM (Content Addressable Memory), 83, 207**

STP, 314-316

switches, 306-307

tables, 299, 302-303

unknown unicast frames, 304

**capacitors, 9**

**carrier sense multiple access collision detect (CSMA/CD), 240**

10BASE-T Ethernets, 275-276

Ethernet operation, 251-257

**carrier sense multiple access with collision avoidance (CSMA/CA), 156****Category 5 (Cat 5), 97****CATV cable connections, WANs, 220****CD-ROM drives, 11****cells, APs, 154****central processing units (CPUs), 8****channel service unit/data service unit (CSU/DSU), 218****channels**

B, 220

D, 220

**charts, conversion, 58****Cheaperternets, 137****Checksum field, 401, 463****CIDR (classless interdomain routing), 371****circuits, 133-134****cladding, 151****Class D IP addresses, 359****Class E address spaces, 359****classes**

IP addresses, 353-362

networks, 363-364

**classful routing protocols, 422****classless interdomain routing (CIDR), 371****classless routing protocols, 422****client/server network models, 213-216****clock ticks, 417****clocking, 222****coaxial cables, 136, 172. *See also* cables****collisions, 252**

10BASE-T LANs/hubs, 253-254

domains, 202, 254-257, 318

*bridges, 206**identifying, 328-329**large/long, 319-321**small, 321-323*

fragments, 275

preventing, 255, 323-325

**commands**

arp, 380

ip subnet-zero, 422

ipconfig, 38, 354

netstat -an, 467

nslookup, 38

ping, 39, 209, 380

ping 172.16.2.21, 39

tracert, 42

tracert, 42-44

**comparing**

copper cabling and fiber-optic cabling, 146-147

DHCP and static addresses, 377

routing protocols, 422-424

TCP and UDP, 455

**complex analog signals, 169****components**

fiber-optic cabling, 150-151

metrics, 416

networks, 7

*cables, 16-17**devices, 17-19**hardware, 7-13**NICs, 13-15*

WANs, 153-155

**concentrators, 202****conductors, copper media, 129-130****configuration**

10BASE-T Ethernets, 275-278

dynamic IP addresses, 375-377

static IP addresses, 373-374

**connected subnets, 411-412****connection-oriented, defining, 408****connectionless, defining, 408****connections. *See also* cables**

bandwidth, 97

*analog, 103-104**data transfer time calculations, 102-103**Ethernet LANs, 97-98**Ethernet WANs, 98-100**LANs, 97**planning, 105**throughput, 100-101*

consoles, 144

directly connected networks, 345

LANs

*cabling, 189**connectors/media, 194-195**devices, 200-204, 206-212**Ethernet physical layer, 190**PC communications models, 212-216**routing between subnets, 395-400**selecting Ethernet types, 191-193**UTP cable pinouts, 196-200*

networks, 3

*ASCII alpha-numeric code, 47**binary numbering (Base 2), 49*

*bits/bytes*, 45-46  
*Boolean logic*, 60-62  
*cables*, 16-17  
*components*, 7  
*conversion charts*, 58  
*converting binary to decimal*, 49-51  
*converting decimal to binary*, 51-56  
*converting IP addresses between decimal and binary*, 56-58  
*decimal numbering (Base 10)*, 48  
*defining*, 3-7  
*devices*, 17-19  
*enterprise*, 19-20  
*hardware*, 7-13  
*hexadecimal numbering (Base 16)*, 59  
*home connections*, 21-24  
*NICs*, 13-15  
*numbering*, 45  
*TCP/IP*, 25-32, 34-38  
*troubleshooting tools*, 38-44

servers, 465-466

TCP, 465, 458

WANs

*cabling*, 216-217

*fixed/modular routers*, 224-225

*layers*, 217-221

*router console cabling*, 225-227

*selecting DCE/DTE cables*, 222-223

## connectors, 9

Ethernets, 194-195

power, 10

RJ-11, 14

RJ-45, 140

## consoles

connections, 144

routers, 225-227

## Content Addressable Memory. *See* CAM

## convergence, rapid, 414

## conversations, 465

## conversion charts, 58

## converting

binary numbering to decimal numbering, 49-51

decimal numbering to binary numbering, 51-58, 369

## copper media, 125. *See also* cables

attenuation, 175-176

coaxial cabling transmissions, 172

digital transmission, 125-134

insertion loss, 175-176

LANs, 134-143, 145-146

noise, 176-177

optical media, 146-147

signaling over, 172

## core component, fiber-optic cabling, 151

## core switch links, 194

## cost, 417

## Coulomb's Law, 127

## CPUs (central processing units), 8

## CRC (cyclic redundancy check), 245, 401

## crossover cable, 274

pinouts, 143-144

UTP pinouts, 197

## crosstalk, 176-179

## CSMA/CA (carrier sense multiple access with collision avoidance), 156

## CSMA/CD (carrier sense multiple access collision detect), 240

10BASE-T Ethernets, 275-276

Ethernet operation, 251-257

## CSU/DSU (channel service unit/data service unit), 218

## currents, measuring, 130-131

## cut-through switching, 309

## cyclic redundancy check (CRC), 245, 401

# D

## D channels, 220

## data communication equipment (DCE), 222-223

## Data field, 463

## data flow, 329-331

## data link layer, 108, 217-221

## data terminal equipment. *See* DTE

## data transfer time calculations, 102-103

## databases, topology, 420

## DC (direct current), 131

## DCE (data communication equipment), 222-223

## de-encapsulation, 111-113

## DEC (Digital Equipment Corporation), 237

## decimal numbering (Base 10), 48

converting, 49-56

IP addresses, 56-58

## decimals, converting to binary numbers, 364

## default gateways, 36, 374

## default routers, 374

## defining

IP address classes, 356-357

networks, 3-7

**delay, 416-417**

- propagation, 180, 307
- queuing, 307
- skew, 180

**delivery, in-order (TCP), 461****depletion of IPv4 addresses, 370-371****design**

- 100-Mbps Ethernet, 280-281
- 10BASE-T Ethernet, 275-278
- LANs, 317
  - collision domains, 318-325*
  - data flow, 329-331*
  - identifying domains, 328-329*
  - Layer 2 broadcast domains, 325-328*
  - segments, 331*
- WLANs, 153-155

**desktops, 13. See also PCs****Destination MAC addresses, 245****Destination Port field, 463****destination port numbers, 465****Destination Service Access Point (DSAP), 249****detecting collisions, 253-254****detectors, 285****deterministic media access, 259-260****devices**

- collision domains, 318
  - large/long, 319-321*
  - small, 321-323*
- data flow, 329-331
- Ethernet, 200-204, 206-212
- I/O, 9
- identifying, 328-329
- LANs, 74-75
- Layer 1, 329
- Layer 2, 329
- Layer 3, 329
- networks, 17-19

**DHCP (Dynamic Host Configuration Protocol), 349, 469**

- dynamic IP address configuration, 375-377
- static IP addresses, 377

**dialogues, 468****Digital Equipment Corporation (DEC), 237****Digital Signal level 0 (DS0), 98****digital signals, 170****digital subscriber line. See DSL****digital transmission using copper wires, 125-134****Dijkstra shortest path first (SPF), 420****direct current (DC), 131****Direct Sequence Spread Spectrum (DSSS), 156, 210****directed broadcast addresses, 365****directly connected networks, 345****disks, memory, 9****distance vector algorithms, 419-420****distribution switches, 193****DIX Ethernet, 237**

- frames, 246-247
- Type field, 250

**DNS (Domain Name System), 349, 469**

- name resolution, 35-36

**domains**

- broadcast (Layer 2), 325-328
- collisions, 202, 254-257, 318
  - bridges, 206*
  - large/long, 319-321*
  - preventing, 323-325*
  - small, 321-323*
- identifying, 328-329
- names, 470
- top-level, 470

**downloading web pages, 26-28****drives**

- CD-ROM, 11
- floppy disk, 11
- hard disk, 12

**DSAP (Destination Service Access Point), 249****DSL (digital subscriber line), 220**

- connecting, 23-24

**DSO (Digital Signal level 0), 98****DSSS (Direct Sequence Spread Spectrum), 156, 210****DTE (data terminal communication), 222-223****duplex settings, autonegotiation, 257-258****Dynamic Host Configuration Protocol (DHCP), 349, 469**

- name resolution, 35-36

**dynamic IP address configuration, 375-377****dynamic port numbers, 465****dynamic ports, 467****dynamic sliding windows, flow control through, 456-457**

---

**E****e-mail, TCP/IP application layer, 472-474****E/1 circuits, 221****effort, implementation, 414****EGP (Exterior Gateway Protocol), 418-419****EIA (Electronic Industries Association), 73, 134**

**EIGRP (Enhanced IGRP), 416****electrical currents, creating, 128****electricity**

- circuits, 133-134
- currents, 130-131
- units of measurement, 132
- voltage, 130
- wattage, 131

**electricity, static, 128****electromotive force (EMF), 130****electromagnetic (EM) energy, 148, 209****electromagnetic interference (EMI), 147****electromagnetic spectrum, 147-148****electrostatic discharge (ESD), 128****Electronic Industries Alliance (EIA), 73, 134****electrons, 126****elements, atoms, 126****ELFEXT (equal-level far-end crosstalk), 180****EM (electromagnetic) energy, 148, 209****EMF (electro-motive force), 130****EMI (electromagnetic interference), 147****encapsulation, 111-112, 243****encrypted packets, 89****end-user level links, 191****Enhanced IGRP (EIGRP), 416****enterprise networks, 19-20****equal-level far-end crosstalk (ELFEXT), 180****errors**

- link error rates, 416
- recovery, 29, 459-461

**ESD (electrostatic discharge), 128****Ethernets, 237**

- 10-Mbps, 269-271
- 100-Mbps, 269, 278-279
  - 100BASE-FX, 281-282*
  - design, 280-281*
- 10Base-T, 76-77, 272
- 10BASE-T
  - design, 275-278*
  - wiring, 272-274*
- bridges, 78-79
- cabling, 141
- devices, 200-204, 206-212
- frames, 80, 247-248
- framing, 242
  - DIX, 246-247*
  - encapsulation, 243*
  - IEEE 802.3 fields, 244-245*

**Gigabit, 282-283***1000BASE-T, 286-288**1000BASE-X, 283-286**future of, 288-290***headers, 249-250****history of, 237****hubs, 76-77****LANs, 74-75***bandwidth, 97-98**connectors/media, 194-195***LLC, 248-249****MAC addresses, 247****NICs***installing, 15**searching, 14***operation, 251***autonegotiation, 257-258**CSMA/CD, 251-257**MAC processes, 259-260***physical layer, 190****repeaters, 75-76****standards, 238-242****switches, 206-208, 297***CAM, 306-307**internal processing, 307-309**Layer 2 bridging, 297-306**STP, 310-316***timing, 272****Type fields, 250****types, 191-193****WAN bandwidth, 98-100****expansion slots, 10-12****expectational acknowledgments, 460****extended shared media, 319****extended star topologies, 95****Exterior Gateway Protocol (EGP), 418-419****Extranets, VPNs, 90****F****far-end crosstalk (FEXT), 179****Fast Link Pulse (FLP), 258, 280****FCC (Federal Communications Commission), 156****FCS (Frame Check Sequence), 240, 401****FDDI (Fiber Distributed Data Interface), 281****features, routing protocols, 414-419****Federal Communications Commission (FCC), 156****FEXT (far-end crosstalk), 179****FHSS (Frequency Hopping Spread Spectrum), 156, 210**

**Fiber Distributed Data Interface (FDDI), 281****fiber-optic cabling, 146-150, 283**

copper cabling

*comparing, 146-147**electromagnetic spectrum, 147-148*

signaling over, 172

types, 151-152

**Fibre Channel, 286****fields**

Acknowledgment Number, 463

Checksum, 401, 463

Data, 463

Destination Port, 463

Flags, 463

Header Length, 463

IEEE 802.3, 244-245

IP headers, 410

Length, 246

Options, 463

Padding, 463

Reserved, 463

Sequence Number, 463

Source Port, 463

TTL, 401

Type, 246, 250

Urgent, 463

Window, 463

**File Transfer Protocol (FTP), 348, 464**

TCP/IP application layer, 474

**filtering, 78, 203, 298-301****firewire, 10****fixed routers, 224-225****Fixed-Function Cisco 2503 routers, 224****flags**

ACK, 458

SYN, 458

**Flags field, 463****flapping, route, 416****flooding unicast addresses, 302-303****floppy disk drives, 11****flow control, 456-457****FLP (Fast Link Pulse), 258, 280****Fluke Network Inspector, 288****foil twisted-pair (FTP) cables, 138****formats**

MAC addresses, 247

subnetted IP addresses, 366-367

**forward acknowledgments, 460****forwarding, 78, 203, 298-301**

bridges, 205

broadcasts, 304-306

frames, 307-309

IP routing, 393

*full IP headers, 409-411**Layer 2 protocols, 403-407**overview of, 394**reliability of, 407-409**routing between LAN subnets, 395-400**routing single routers, 401-402**WANs, 403*

multicasts, 304-306

states, 317

store-and-forward switching, 308

**fragment-free switching, 309****fragment collisions, 275****Frame Check Sequence (FCS), 240, 401****frames, 112-113**

broadcast, 304-306

buffering, 323, 325

forwarding, 307-309

multicast, 304-306

queuing, 323-325

switches

*Layer 2 bridging, 297-306**operations, 297*

troubleshooting, 401

unknown unicast, 304

**framing (Ethernet) , 80, 242, 247-248**

DIX, 246-247

encapsulation, 243

IEEE 802.3 fields, 244-245

**frequencies, 22, 148****Frequency Hopping Spread Spectrum (FHSS), 156, 210****frequency-based cable testing, 167**

analog signals, 169-170

waves, 167-168

**FTP (File Transfer Protocol), 464**

TCP/IP application layer, 474

**FTP (foil twisted-pair) cables, 138. See also cables****full duplex, CSMA/CD, 254-257****full IP headers, 409-411****full mesh topologies, 95-96****future of Ethernets, 288-290**



## G–H

gateways, 36, 274

**Gigabit Ethernet**s, 282-283

1000BASE-T, 286-288

1000BASE-X, 283-286

future of, 288-290

**half duplex**

10BASE-T Ethernets, 275-276

CSMA/CD, 254-257

**hard disk drives**, 12

**hardware**, 7-13

**Header Length field**, 463

**headers**

Ethernets, 249-250

full IP, 409-411

IEEE 802.3 Ethernet, 244

references, 462-463

**Hertz (Hz)**, 22

**hexadecimal numbering (Base 16)**, 59

**hierarchical physical topologies**, 95

**high-speed MAN services**, 85

**higher utilization (large collision domains)**, 321

**history**

of Ethernets, 237

of networks, 71-72

of remote access, 23

**home connections**

analog modems, 21-23

cable modems, 24

DSL modems, 23-24

**hop counts**, 415-417

**hostnames**, 470

**hosts**

calculating, 363

determining number of, 426-429

local, 476

parts, 356

remote, 476

resident subnets, 442-444

TCP/IP, 340

**HTTP (Hypertext Transfer Protocol)**, 25-29, 348, 471

**hubs**, 18, 201-202, 209

10BASE-T Ethernets, 275-276

collisions, 253-254

Ethernet, 76-77

types of, 202

hybrid algorithms, 421

hyperlinks, 472

**Hyperterminals**, 226

**Hypertext Transfer Protocol (HTTP)**, 25-29, 348, 471

**Hz (Hertz)**, 22

## I

**I/O (input/output) devices**, 9

**IAB (Internet Activities Board)**, 340

**IANA (Internet Assigned Numbers Authority)**, 369

**IC (integrated circuit)**, 9

**identifying domains**, 328-329

**IE (Internet Explorer)**, 26

**IEEE (Institute of Electrical and Electronic Engineers)**, 73, 135

802.1D, 313-315

802.2, 249

802.3 fields, 244-245

802.3ab, 287

802.3ae, 289

802.3z, 282

Ethernets

*OSI model*, 240-242

*types of*, 238-239

frames, 246-247

Type field, 250

**IETF (Internet Engineering Task Force)**, 73, 340

**IGP (Interior Gateway Protocol)**, 418-419

**IGRP (Interior Gateway Routing Protocol)**, 416

**impedance**, 132-133, 176

**implementation of effort**, 414

**in-order delivery**, TCP, 461

**increments**, 439

**infrared (IR)**, 209

**infrastructure mode (WLANs)**, 154

**input/output (I/O)**, 9

**insertion loss**, 175-176, 180

**installing Ethernet NICs**, 15

**Institute of Electrical and Electronic Engineers (IEEE)**, 73, 135

**insulators**, copper media, 129-130

**integrated circuit (IC)**, 9

**Integrated Services Digital Network (ISDN)**, 220

**interactions**, layers, 114-115

**interesting octets**, 432

**interfaces, 78**

- AUI, 195
- BRI, 220
- FDDI, 281
- IEEE 802.1D STP states, 313-314
- NICs, 13-15
- serial, 217-219
- switches, 299
- TCP/IP, 340-341
- WICs, 218

**Interior Gateway Protocol (IGP), 418-419****Interior Gateway Routing Protocol (IGRP), 416****internal processing, switches, 307-309****International Organization for Standardization (ISO), 106****International Telecommunications Union (ITU), 73****Internet Activities Board (IAB), 340****Internet Assigned Numbers Authority (IANA), 369****Internet connections, 3-7, 368-372****Internet Engineering Task Force (IETF), 73, 340****Internet Explorer (IE), 26****Internet Protocol. *See* IP****Internet service provider. *See* ISP****internetwork layer (TCP/IP), 341-345, 393****intranets, 89-90****IP (Internet Protocol)**

- addresses, 31, 353
  - assignment, 353-362*
  - classes, 353-362*
  - determining assignable (in subnets), 434-444*
  - managing, 373-384*
  - networking math, 362-364*
  - overview of, 353*
  - public, 370*
  - subnetting, 32, 364-368*
  - unicast, 356*
  - unique, 368-372*
- packets, 343
- private networks, 371-372
- routing, 25, 31, 34, 343
  - full IP headers, 409-411*
  - IP addresses, 344-345*
  - Layer 2 protocols, 403-407*
  - overview of, 394*
  - reliability of, 407-409*
  - routing, 342, 395-403*
- subnetting, 424
  - determining assignable IP addresses, 434-444*
  - overview of, 424-425*
  - schemes, 425-433*

- TCP/IP internetworking layer, 30-34
- troubleshooting, 34-36, 38

**ip subnet-zero command, 422****ipconfig command, 38, 354****IPv4 (Internet Protocol version 4)**

- address spaces, 359-360
- depletion of, 370-371

**IPv6 (Internet Protocol version 6), 372****IR (infrared), 209****ISDN (Integrated Services Digital Network), 220****ISO (International Organization for Standardization), 106****ISP (Internet service provider)**

- analog modems, 21-23
- cable modems, 24
- DSL modems, 23-24

**ITU (International Telecommunications Union), 73**

---

**J-K**

---

**jack punch down, RJ-45, 200****keyboards, ports, 10**

---

**L**

---

**L3PDU (Layer 3 protocol data unit), 242****LANs (local-area networks)**

- ARP, 378-384
- bandwidth, 97-98
- cabling, 189
  - connecting Ethernet devices, 200-204, 206-212*
  - connectors/media, 194-195*
  - Ethernet physical layer, 190*
  - PC communications models, 212-216*
  - selecting Ethernet types, 191-193*
  - UTP cable pinouts, 196-200*
- collisions, 253-254
- copper cabling, 134-144
- design, 317
  - collision domains, 318-325*
  - data flow, 329-331*
  - identifying domains, 328-329*
  - Layer 2 broadcast domains, 325-328*
  - segments, 331*
- devices, 74-75
- Ethernet, 74-75
- IP addresses, 353-357
- speed limitations, 289
- STP, 310-312
  - blocking, 312-313*

- CAM, 314-316*
  - states, 313-314*
  - subnets, 395-400
  - switches, 82, 208, 298, 323
  - WLANs, 153-157
  - laptops, 13**
  - large collision domains, 319-321**
  - large networks (Internet), 4, 7**
  - latency, 307**
  - Layer 1**
    - data flow, 329-331
    - devices, 329
  - Layer 2**
    - bridging, 297-306
    - broadcast domains, 325-328
    - data flow, 329-331
    - devices, 329
    - protocols, 403-407
  - Layer 3, 404**
    - data flow, 329-331
    - devices, 329
  - Layer 3 protocol data unit (L3PDU), 242**
  - layers**
    - application (TCP/IP), 347-349, 468
    - interactions, 114-115
    - internetwork (TCP/IP), 341-345
    - network access (TCP/IP), 340-341
    - OSI, 107-109, 328-329
    - physical (Ethernet), 190
    - TCP/IP
      - internetworking, 30-34*
      - overview of, 350-352*
      - transport, 29*
    - transport (TCP/IP), 345-347, 455-467
    - WANs, 217-221
  - learning**
    - IP routes, 411-413
    - states, 314-317
  - leased circuits, 84**
  - leased lines, point-to-point, 83-84**
  - LED (light emitting diode), 9**
  - length, cabling, 180**
  - Length field, 246**
  - light emitting diode (LED), 9**
  - limitations of LANs, 289**
  - link-state advertisements (LSAs), 420**
  - link-state algorithms, 420**
  - links**
    - access switches, 193
    - backbone, 191, 280, 310
    - core switches, 194
    - end-user level, 191
    - error rates, 416
    - hyperlinks, 472
    - LLC, 190
    - loading, 416
    - point-to-point WAN, 216
    - uplinks, 193
    - workgroup level, 191
  - listening states, 314-316**
  - LLC (Logical Link Control), 190, 248-249**
  - loading links, 416**
  - local hosts, 476**
  - local-area networks. See LANs**
  - logic, routing and switching, 405-406**
  - logical bus topologies, 91-92**
  - Logical Link Control (LLC), 190, 248-249**
  - long collision domains, 319-321**
  - long distances (LX), 283**
  - loopback circuits, 254**
  - loopback IP addresses, 360**
  - LSAs (link-state advertisements), 420**
  - LX (long distances), 283**
- 
- ## M
- 
- MAC (Media Access Control), 78**
    - addresses
      - Ethernets, 247*
      - tables, 299*
      - unknown unicast frames, 304*
    - Destination addresses, 245
    - Ethernet processes, 259-260
    - Source addresses, 245
  - mainframe computers, 71**
  - management**
    - IP addresses, 373
      - applying ARP, 378-384*
      - comparing DHCP, 377*
      - dynamic IP address configuration, 375-377*
      - static IP address configuration, 373-374*
    - networks, 475-476
    - NMS, 476
    - out-of-band, 227
  - MANs (metropolitan-area networks), 85**
  - mapping**
    - Layer 3-to-Layer 2, 404
    - wire maps, 180

**masks (subnet), 61-62, 367-368**

SLSM, 427

VSLM, 422

**mathematics (networks), 45, 362-364**

ASCII alpha-numeric code, 47

binary numbering (Base 2), 49

bits/bytes, 45-46

Boolean logic, 60-62

conversion charts, 58

converting binary to decimal, 49-51

converting decimal to binary, 51-56

converting IP addresses between decimal and binary, 56-58

decimal numbering (Base 10), 48

hexadecimal numbering (Base 16), 59

**maximum transmission unit (MTU), 416****measurement**

currents, 130-131

resistance, 133

units of, 132

voltage, 130

**media. *See also* cables**

copper, 125

*digital transmission, 125-134**LANs, 134-146*

Ethernets, 194-195

optical, 146-150

*comparing copper cabling, 146-147**electromagnetic spectrum, 147-148**fiber types, 151-152*

shared, 319

wireless, 152-157

**Media Access Control. *See* MAC****memory**

CAM, 207

*switches, 306-307**tables, 299-303*

disks, 9

RAM, 8

ROM, 8

**Metcalfe, Robert, 237****metrics**

components, 416

hop count, 415

robust, 414

routes, 414-418

**metropolitan-area networks (MANs), 85****microprocessors, 8****microsegmentation, 323****minicomputers, 71****MLS (multilayer switching), 394****MMF (multimode fiber), 286****models**

client/server, 213

OSI, 106-109

peer-to-peer, 213

TCP/IP networking, 28, 110, 339-340

*application layer, 347-349**de-encapsulation, 113**encapsulation, 111-112**frames, 112-113**internetwork layer, 341-345**layer interactions, 114-115**network access layer, 340-341**overview of, 349-352**packets, 112-113**PDU, 112-113**segments, 112-113**transport layer, 345-347***modems**

analog, 21-23

cable, 24, 220

DSL, 23-24

**modular routers, 224-225****motherboards, 9****mouse, ports, 10****Mozilla Firefox, 26****MTU (maximum transmission unit), 416****multicast frames, forwarding, 304-306****multilayer switching (MLS), 394****multimeters, voltage measurement, 130****multimode fiber (MMF), 286****multimode fibers, 151-152****multiplexing, 347, 465****multiport bridges, 208****multiport repeaters, 77, 202**

---

**N****names**

bits/bytes, 45

domains, 470

resolution, 35-36, 469

transmission rates, 46

**nanometer (nm), 148****NAT (Network Address Translation), 371-372****near-end crosstalk (NEXT), 178-180****Netscape, 26****netstat -an command, 467**

**Network Address Translation (NAT), 371-372**

**Network File System (NFS), 348**

**network interface cards. See NICs**

**Network Link Pulses (NLPs), 258**

**Network Management System (NMS), 476**

**network operating system (NOS), 215**

**networks**

access layer (TCP/IP), 340-341

application layer (TCP/IP), 347-349

bandwidth, 97

*analog, 103-104*

*data transfer time calculations, 102-103*

*Ethernet LANs, 97-98*

*Ethernet WANs, 98-100*

*LANs, 97*

*planning, 105*

*throughput, 100-101*

broadcast addresses, 434

classes, 363-364

components, 7

*cables, 16-17*

*devices, 17-19*

*hardware, 7-13*

*NICs, 13-15*

connections, 3

copper

*digital transmission, 125-134*

*LANs, 134-143, 145-146*

defining, 3-7

directly connected, 345

enterprise, 19-20

home connections, 23

*analog modems, 21-22*

*cable modems, 24*

*DSL modems, 23-24*

hosts, 363

internetwork layer (TCP/IP), 341-345

LANs

*cabling, 189*

*connecting Ethernet devices, 200-204, 206-212*

*connectors/media, 194-195*

*Ethernet physical layer, 190*

*PC communications models, 212-216*

*selecting Ethernet types, 191-193*

*UTP cable pinouts, 196-200*

large (Internet), 4, 7

management, 475-476

MANs, 85

math, 362-364

numbering, 45

*ASCII alpha-numeric code, 47*

*binary numbering (Base 2), 49*

*bits/bytes, 45-46*

*Boolean logic, 60-62*

*conversion charts, 58*

*converting binary to decimal, 49-51*

*converting decimal to binary, 51-56*

*converting IP addresses between decimal and binary, 56-58*

*decimal numbering (Base 10), 48*

*hexadecimal numbering (Base 16), 59*

numbers, 361-362

overview of, 71

*broadcast/unicast addresses, 81*

*Ethernet bridges, 78-79*

*Ethernet frames, 80*

*Ethernet hubs/10Base-T, 76-77*

*Ethernet LANs/LAN devices, 74-75*

*Ethernet repeaters, 75-76*

*history of, 71-72*

*LAN switches, 82*

*need for protocols/standards, 73-74*

parts, 356

private IP, 371-372

SANs, 86-87

small (two PCs/one cable), 4

TCP/IP, 25

*de-encapsulation, 113*

*encapsulation, 111-112*

*frames, 112-113*

*HTTP, 26-28*

*IP, 30-34*

*layer interactions, 114-115*

*networking model, 110*

*overview of, 349-352*

*packets, 112-113*

*PDUs, 112-113*

*segments, 112-113*

*standards, 25*

*transport layers, 29*

*troubleshooting IP, 34-38*

*troubleshooting tools, 38-44*

topologies, 91

*extended star, 95*

*full mesh, 95-96*

*hierarchical physical, 95*

*logical bus, 91-92*

*partial mesh, 95-96*

*physical bus, 91-92*

*physical star, 91-92*

*ring, 94*

transport layer (TCP/IP), 345-347

unique IP addresses, 368-372

VPNs, 87-88

*intranets*, 89-90

*types of*, 90

WANs, 83

*cabling*, 216-217

*fixed/modular routers*, 224-225

*layers*, 217-221

*point-to-point leased lines*, 83-84

*router console cabling*, 225-227

*routers*, 85

*selecting DCE/DTE cables*, 222-223

wired, 154

**neutrons, 126**

**NEXT (near-end crosstalk), 178-180**

**next-hop routers, 345, 412**

**NFS (Network File System), 348**

**NICs (network interface cards), 13-15, 135**

Ethernet, 211-212

**NLPs (Network Link Pulses), 258**

**nm (nanometer), 148**

**NMS (Network Management System), 476**

**noise, 171**

attenuation, 175-176

cabling testing standards, 180-182

coaxial cabling transmissions, 172

copper/fiber-optic cabling, 172

optical cabling transmissions, 174

sources of, 176-177

types of crosstalk, 178-179

**nondeterministic media access, 259-260**

**NOS (network operating system), 215**

**nslookup command, 38**

**number of required subnets, determining, 425-433**

**numbering**

**numbers**

ARIN, 369

IANA, 369

networks, 45, 361-362

*ASCII alpha-numeric code*, 47

*binary numbering (Base 2)*, 49

*bits/bytes*, 45-46

*Boolean logic*, 60-62

*conversion charts*, 58

*converting binary to decimal*, 49-51

*converting decimal to binary*, 51-56

*converting IP addresses between decimal and binary*, 56-58

*decimal numbering (Base 10)*, 48

*hexadecimal numbering (Base 16)*, 59

port application processes, 464-467

subnets, 434-437

---

## O

**octets, 432**

**OFDM (Orthogonal Frequency Division Multiplexing), 156**

**Ohm's law, 132**

**open networking models, 106**

**operating systems, NOS, 215**

**operations**

Ethernets, 251

*autonegotiation*, 257-258

*CSMA/CD*, 251-257

*MAC processes*, 259-260

switches, 297

*CAM*, 306-307

*internal processing*, 307-309

*Layer 2 bridging*, 297-306

*STP*, 310-316

**optical media, 146-150**

cabling transmissions, 174

copper cabling

*comparing*, 146-147

*electromagnetic spectrum*, 147-148

fiber types, 151-152

**options, 10-Mbps Ethernets, 272**

**Options field, 463**

**organization, WLANs, 155-157**

**Organizationally Unique Identifier (OUI), 247**

**Orthogonal Frequency Division Multiplexing (OFDM), 156**

**OSI model, 106**

devices, identifying, 328-329

Ethernets, 240

*comparing standards*, 241-242

*IEEE 802.2 standards*, 240

*IEEE 802.3 standards*, 240

layers, 107-109

**OUI (Organizationally Unique Identifier), 247**

**out-of-band management, 227**

**outer jackets, fiber-optic cabling, 151**

---

## P

**packets, 112-113, 399**

encapsulation inside Ethernet frames, 243

encrypted, 89

IP, 343

**Padding field, 463**

- parallel ports, 10**
- partial mesh topologies, 95-96**
- parts (network/host), 356**
- passing tokens, 259**
- passive scanning, 155**
- paths**
  - determination, 394
  - internal processing, 310
- PCB (printed circuit board), 9**
- PCMCIA (Personal Computer Memory Card International Association), 12**
- PCs (personal computers), 9**
  - backplane, 10
  - communications models, 212-216
  - history of, 72
  - home connections
    - analog modems, 21-23*
    - cable modems, 24*
    - DSL modems, 23-24*
  - small networks (2 PCs/one cable), 4
- PdUs (protocol data units), 112-113**
- peer-to-peer network models, 213-214**
- performance, broadcast domains, 326-328**
- periodic updates, 421**
- periods, 22**
  - waves, 167
- permanent memory, 9**
- permanent virtual circuits. *See* PVCs**
- Personal Computer Memory Card International Association (PCMCIA), 12**
- personal computers. *See* PCs**
- phone lines**
  - analog modems, 21-23
  - DSL modems, 23-24
- physical bus topologies, 91-92**
- physical network topologies, 91**
- physical layer, 108**
  - Ethernet (LAN cabling), 190
  - WANs, 217-221
- physical star topologies, 91-92**
- ping 172.16.2.21 command, 39**
- ping command, 39, 209, 380**
- pinouts**
  - cabling, 140
  - crossover-cable, 143-144
  - Ethernets, 141
  - selecting, 145
  - TIA/EIA-568-A, 142
  - UTP cable, 196-200
- planning bandwidth, 105**
- plug-ins, web browsers, 28**
- point-to-point leased lines, 83-84**
- Point-to-Point Protocol (PPP), 403**
- point-to-point WAN links, 216**
- POP3 (Post Office Protocol version 3), 472-474**
- ports, 78**
  - auxiliary, 227
  - dynamic, 467
  - keyboards, 10
  - mouse, 10
  - multiport repeaters, 77
  - numbers, 464-467
  - parallel, 10
  - registered, 467
  - serial, 10
  - switches, 299
  - USB, 10
  - well-known, 465-467
- Post Office Protocol version 3 (POP3), 472-474**
- power connectors, 10**
- power sum equal-level far-end crosstalk (PSELFEXT), 180**
- power sum near-end crosstalk (PSNEXT), 179-180**
- powers of 2, 428**
  - applying, 362
- PPP (Point-to-Point Protocol), 403**
- Preamble, 245, 271**
- presentation layer, 108**
- preventing collisions, 255, 323-325**
- printed circuit board (PCB), 9**
- private IP networks, 371-372**
- probabilistic, 259**
- processes, application, 464-467**
- processing internal switches, 307-309**
- processors**
  - CPUs, 8
  - microprocessors, 8
- propagation delay, 180, 307**
- protocol data units (PDUs), 112-113**
- protocols**
  - Ethernets, 248-249
  - Internet layer, 341
  - need for, 73-74
  - routing, 411
    - algorithms, 419-421*
    - classful, 422*

*classless*, 422

*comparing*, 422-424

*routers leaning IP routes*, 411-413

*selecting*, 414-419

*updates*, 421

standards, 25

TCP/IP

*application layer*, 469-474

*network management*, 475-476

*overview*, 477-478

**protons**, 126

**proxy ARPs, applying**, 378-384

**PSELFEXT (power sum equal-level far-end crosstalk)**, 180

**PSNEXT (power sum near-end crosstalk)**, 179-180

**public IP addresses**, 370

**purchasing LAN switches**, 208

**PVCs (permanent virtual circuits)**, 96

## Q–R

---

**queuing**

delay, 307

frames, 323-325

**radio frequencies (RFs)**, 209

**radio frequency interference (RFI)**, 147

**RAM (random-access memory)**, 8

**ranges, searching addresses**, 438-439

**rapid convergence**, 414

**RARP (Reverse Address Resolution Protocol)**, 375

**rates, transmission names**, 46

**read-only memory**. *See* ROM

**Realtime tab**, 39

**reassembly, TCP**, 461

**recovery, TCP errors**, 459-461

**redundancy**, 280

**references, headers**, 462-463

**registered jack 45 (RJ-45) connectors**, 140, 200

**registered ports**, 467

**reliability**, 417

IP routing, 407-409

TCP error recovery, 459-461

**remote access, history of**, 23

**remote hosts**, 476

**repeaters**, 200

Ethernet, 75-76

multiport, 202

**replies, ARP**, 380

**requests, ARP**, 379

**Requests For Comments (RFCs)**, 340

**Reserved field**, 463

**resident subnets**, 442-444

**resistance**, 132-133

**resistors**, 9

**resolution**

DNS, 35-36

names, 469

**return loss**, 180

**Reverse Address Resolution Protocol (RARP)**, 375

**reversed-pair fault**, 181

**RFCs (Request For Comments)**, 340

**RFI (radio frequency interference)**, 147

**RFs (radio frequencies)**, 209

**ring topologies**, 94

**RIP (Routing Information Protocol)**, 327, 413-415

**RJ-11 connectors**, 14

**RJ-45 (registered jack 45) connectors**, 140, 200

**robust metrics**, 414

**rollover cables**, 144, 225

**ROM (read-only memory)**, 8

**routable protocols**, 394

**routed protocols**, 394

**routers**

console cabling, 225-227

default, 374

default gateway, 36

fixed, 224-225

Fixed-Function Cisco 2503, 224

IP, 34

learning IP routes, 411-413

modular, 224-225

next-hop, 345, 412

processing overhead, 414

routing single, 401-402

serial interfaces, 217-219

WANs, 85

**routes**

flapping, 416

IP, 411-413

metrics, 414-418

static, 412



**routing**

- CIDR, 371
- IP, 31, 34, 343, 393
  - full IP headers, 409-411*
  - IP addresses, 344-345*
  - Layer 2 protocols, 403-407*
  - overview of, 394*
  - reliability of, 407-409*
  - routing between LAN subnets, 395-400*
  - routing single routers, 401-402*
  - WANs, 403*
- protocols, 411
  - algorithms, 419-421*
  - classful, 422*
  - classless, 422*
  - comparing, 422-424*
  - routers learning IP routes, 411-413*
  - selecting, 414-419*
  - updates, 421*
- switching
  - benefits of, 406-407*
  - logic, 405-406*
- tables, 395

**Routing Information Protocol (RIP), 327, 413-415****S****same layer interaction, 115****SANs (storage area networks), 85-87****scanning, 155****schemes, subnet, 425-444****ScTP (screened twisted-pair) cables, 138. *See also* cables****searching**

- address ranges, 438-439
- broadcast addresses, 438
- Ethernet NICs, 14
- resident subnets, 443-444
- subnets, 435-442

**segmentation, 321, 346**

- TCP, 461

**segments, 74, 112-113, 323, 331****selecting**

- DCE/DTE cables, 222-223
- Ethernet types (speeds), 191-193
- pinouts, 145
- routing protocols, 414-419
- UTP cable pinouts, 196-200

**semiconductors, copper media, 129-130****sending frames over Ethernets, 247-248****Sequence Number field, 463****sequence numbers, 30****serial cables, 217****serial interfaces, 217-219****serial ports, 10****servers, 213**

- connections, 465-466
- web, 26

**Service Set Identifier (SSI), 155****session layer, 108****sessions, 468****SFD (Start Frame Delimiter), 240, 245, 271****shared bandwidth, 319-321****shared media, 319****shielded twisted-pair (STP) cables, 135-138. *See also* cables****shielding, 136, 172****short distances (SX), 283****shortcuts**

- broadcast addresses, 439-442
- determining subnet masks, 432-433
- resident subnets, 444

**shortest path first (SPF), 420****signals**

- analog
  - creating digital signals from, 170*
  - frequency-based cable testing, 169*
- collisions, 252
- noise, 171
  - attenuation, 175-176*
  - cabling testing standards, 180-182*
  - coaxial cabling transmissions, 172*
  - copper/fiber-optic cabling, 172*
  - optical cabling transmissions, 174*
  - sources of, 176-177*
  - types of crosstalk, 178-179*

**simple analog signals, 169****Simple Mail Transfer Protocol (SMTP), 348, 472-474****Simple Network Management Protocol (SNMP), 349, 475-476****sine waves, 168****single routes, routing in, 401-402****single-mode fiber (SMF), 151-152, 286****sizes of networks, 7****skew, delay, 180****SLSM (subnet-length subnet masking), 427****small collision domains, 321-323****small networks (two PCs/one cable), 4****SMF (single-mode fiber), 151-152, 286**

**SMTP (Simple Mail Transfer Protocol), 348, 472-474**

**SNAP (Subnetwork Access Protocol), 250**

**SNMP (Simple Network Management Protocol), 349, 475-476**

**Source MAC address, 245**

**Source Port field, 463**

**Spanning Tree Algorithm (STA), 315**

**Spanning Tree Protocol. *See* STP**

**spectrums, spread, 210**

**speed**

100-Mbps Ethernet design, 280-281

autonegotiation, 257-258

Ethernets, 191-193, 239

LAN limitations, 289

WANs, 221

**SPF (shortest path first), 420**

**split-pair wiring fault, 182**

**spread spectrum, 210**

**square waves, 168**

**SSI (Service Set Identifier), 155**

**STA (Spanning Tree Algorithm), 315**

**stability, 414**

**standards**

1000BASE-T, 286-288

1000BASE-X, 283-286

cabling testing, 180-182

Ethernets, 238-242

need for, 73-74

support, 414

TCP/IP, 25

TIA/EIA-568-A, 142

WLANs, 155-157

**Start Frame Delimiter (SFD), 240, 245, 271**

**states**

forwarding, 317

learning, 314-317

listening, 314-316

STP, 313-314

**static electricity, 128**

**static IP addresses**

configuration, 373-374

DHCP, comparing, 377

**static routes, 412**

**static-length subnet masking (SLSM), 427**

**storage area networks (SANs), 85-87**

**store-and-forward switching, 308**

**STP (shielded twisted-pair) cables, 135-138. *See also* cables**

**STP (Spanning Tree Protocol), 310-312**

blocking, 312-313

CAM, 314-316

states, 313-314

topologies, 315

**straight-through cables, 141, 273**

UTP pinouts, 197

**strengthening material, fiber-optic cabling, 151**

**structures, IP addresses, 358-359**

**subnets, 364-368**

broadcast, 435

connected, 411-412

IP, 32, 424

*determining assignable IP addresses, 434-444*

*overview of, 424-425*

*schemes, 425-433*

LANs, 395-400

masks, 61-62, 427

numbers, 434-438

resident, 442-444

searching, 439-442

VSLM, 422

zero, 435-436

**Subnetwork Access Protocol (SNAP), 250**

**support, standards, 414**

**switched bandwidth, 323**

**switched LANs, 323**

**switches**

10BASE-T Ethernet, 276-278

access, 193

buffering, 255

collisions, 323-325

core links, 194

cut-through switching, 309

distribution, 193

Ethernet, 206-208, 297

*CAM, 306-307*

*internal processing, 307-309*

*Layer 2 bridging, 297-306*

*STP, 310-316*

fragment-free switching, 309

interfaces, 299

LANs, 82, 208, 298

ports, 299

store-and-forwarding switches, 308

**switching**

MLS, 394

routing

*benefits of, 406-407*

*logic, 405-406*

tables, 207, 299

**SX (short distances), 283**

**SYN flags, 458**

**synchronization, 222**

**system units, 12**

## T

**T/1 circuits, 221**

**tables**

- ARP, 380
- bridging, 299
- CAM, 83, 299-307
- MAC address, 299
- routing, 34, 395
- switching, 207, 299

**tabs, Realtime, 39**

**TCP (Transmission Control Protocol), 346, 455**

- application processes, 464-467
- connecting, 458
- error recovery, 29, 459-461
- header references, 462-463
- in-order delivery, 461
- multiplexing, 465
- reassemble, 461
- segmentation, 461
- UDP, 455

**TCP/IP (Transmission Control Protocol/Internet Protocol), 25, 339**

- application layer, 468
  - network management, 475-476*
  - overview, 477-478*
  - protocols, 469-474*
- HTTP, 26-28
- IP, 30-34
- models, 339-340
  - application layer, 347-349*
  - internetwork layer, 341-345*
  - network access layer, 340-341*
  - overview of, 349-352*
  - transport layer, 345-347*
- networking model, 28, 110
  - de-encapsulation, 113*
  - encapsulation, 111-112*
  - frames, 112-113*
  - layer interactions, 114-115*
  - packets, 112-113*
  - PDU, 112-113*
  - segments, 112-113*
- standards, 25
- transport layer, 29, 455
  - application processes, 464-467*
  - connection TCP, 458*

*flow control, 456-457*

*header references, 462-463*

*in-order delivery, 461*

*reassemble, 461*

*segmentation, 461*

*TCP error recovery, 459-461*

*windowing, 456-457*

troubleshooting

*IP, 34-38*

*tools, 38-44*

**telco, 219**

**Telecommunications Industry Association (TIA), 73, 134, 273**

**Telnet (Terminal Emulation), 348, 476**

**temporary memory, 8**

**terminals, 71**

**terminating TCP connections, 458**

**terminology**

MANs, 85

networks, 71

*broadcast/unicast addresses, 81*

*Ethernet bridges, 78-79*

*Ethernet frames, 80*

*Ethernet hubs/10Base-T, 76-77*

*Ethernet LANs/LAN devices, 74-75*

*Ethernet repeaters, 75-76*

*history of, 71-72*

*LAN switches, 82*

*need for protocols/standards, 73-74*

SANs, 86-87

topologies, 91

*extended star, 95*

*full mesh, 95-96*

*hierarchical physical, 95*

*logical bus, 91-92*

*partial mesh, 95-96*

*physical bus, 91-92*

*physical star, 91-92*

*ring, 94*

VPNs, 87-88

*intranets, 89-90*

*types of, 90*

WANs, 83

*point-to-point leased lines, 83-84*

*routers, 85*

**testing**

cables, 180-182

frequency-based cable, 167

*analog signals, 169-170*

*waves, 167-168*

multimeters, 130

**TFTP (Trivial File Transfer Protocol), 348, 475**

**Thicknets, 137**

**Thinnets, 137**

**three-way handshakes, 458**

**throughput versus bandwidth, 100-101**

**TIA (Telecommunications Industry Association), 73, 134, 273**

**TIA/EIA-568-A standard, 142**

**ticks, 417**

**time periods, waves, 167**

**Time to Live (TTL) fields, 401**

**timers, back-off, 252**

**timing (Ethernet), 272**

**tokens, passing mechanisms, 259**

**tools, troubleshooting, 38-44**

**top-level domains, 470**

**topologies**

- databases, 420
- networks, 91
  - extended star, 95*
  - full mesh, 95-96*
  - hierarchical physical, 95*
  - logical bus, 91-92*
  - partial mesh, 95-96*
  - physical bus, 91-92*
  - physical star, 91-92*
  - ring, 94*
- STP, 315

**traceroute command, 42**

**tracert command, 42, 44**

**transfers, data transfer time calculations, 102-103**

**transistors, 9**

**Transmission Control Protocol. *See* TCP**

**Transmission Control Protocol/Internet Protocol. *See* TCP/IP**

**transmission rates, 46**

**transmitters, 285**

**transport layer, 29, 108, 345-347, 455**

- application processes, 464-467
- connecting TCP, 458
- flow control, 456-457
- header references, 462-463
- in-order delivery, 461
- reassembly, 461
- segmentation, 461
- TCP error recovery, 459-461
- windowing, 456-457

**transposed-pair wiring fault, 182**

**triggered updates, 421**

**Trivial File Transfer Protocol (TFTP), 348, 475**

**troubleshooting**

- cable testing standards, 180-182
- frames, 401
- IP, 34-38
- noise, 171
  - attenuation, 175-176*
  - coaxial cabling transmissions, 172*
  - copper/fiber-optic cabling, 172*
  - optical cabling transmissions, 174*
  - sources of, 176-177*
  - types of crosstalk, 178-179*
- TCP error recovery, 459-461
- tools, 38-44

**trunks, 280, 310**

**TTL (Time to Live) fields, 401**

**Type field, 246, 250**

**types**

- of crosstalk, 178-179
- of current, 131
- of Ethernets, 191-193, 238-239
- of fiber-optic cabling, 151-152
- of hubs, 202

---

## U

**UDP (User Datagram Protocol), 346, 455**

- header references, 462-463
- TCP, 455

**unicast IP addresses, 81, 356**

- flooding, 302-303

**unique IP addresses, 368-372**

**units, transmission rates, 46**

**Universal Resource Locator (URL), 35, 471**

**Universal Serial Bus (USB), 10**

**unknown unicast frames, 304**

**unreliable protocols, 408**

**unshielded twisted-pair. *See also* UTP**

**updates**

- periodic, 421
- routing protocols, 421
- triggered, 421

**uplinks, 193**

**Urgent field, 463**

**URL (Universal Resource Locator), 35, 471**

**USB (Universal Serial Bus), 10**

**User Datagram Protocol (UDP), 346, 455**

header references, 462-463

TCP, 455

**UTP (unshielded twisted-pair) cables, 76, 137-146. *See also* cables**

cable pinouts, 196-200

**V****valid addresses, searching range of, 438-439****Virtual Private Networks. *See* VPNs****VLSM (variable-length subnet masking), 422****voltage, 130****VPNs (Virtual Private Networks), 87-88**

intranets, 89-90

types of, 90

**W****WANs (wide-area networks), 71, 83**

bandwidth, 98-100

cabling, 216-217

*fixed/modular routers, 224-225**layers, 217-221**router console cabling, 225-227**selecting DCE/DTE cables, 222-223*

interface cards (WICs), 218

point-to-point leased lines, 83-84

routers, 85

routing, 403

**wattage, 131****wavelengths, 148****waves, frequency-based cable testing, 167-168****web browsers, 26**

plug-ins, 28

**web pages, downloading, 26-28****web servers, 26****well-know ports, 465-467****Wi-Fi alliance, 157****WICs (WAN interface cards), 218****wide-area networks. *See* WANs****wildcards, 431****Window field, 463****windowing, 456-457****wire maps, 180****wired networks, 154****wireless LANs. *See* WLANs****wireless media, 152-157****wiring. *See also* cables**

10BASE-T Ethernets, 272-274

copper media, 125

*digital transmission, 125-134**LANs, 134-143, 145-146***WLANs (wireless LANs), 12, 153-157, 209-210****workgroup level links, 191****workstations, 215****WWW (World Wide Web), TCP/IP application layer, 471****X-Z****Xerox, 237****XNS (Xerox Network System) protocol, 422****zero subnets, 435-436**