

## A

---

**ABRs (Area Border Routers), 41**  
**access layer of hierarchical design model, 139-141**  
**acknowledgment packets, 70**  
**adaptive cut-through, 104**  
**adding**  
    switches to network, 180  
    VLANs, 223-225, 232-233  
**adjacency database, 45**  
**advertisements (VTP), 257-258**  
**age time, 101**  
**aggregation, 12-13**  
**alternate ports (RSTP), 206**  
**areas, 41**  
**AS (autonomous systems), 47**  
**ASBRs (autonomous system boundary routers), 42**  
**ASICs (application-specific integrated circuits), 101, 220**  
**assigning**  
    default gateway to Catalyst switches, 170  
    hostname to Catalyst switches, 169  
    permanent MAC addresses to interfaces, 174-175  
    ports to VLANs, 225-226  
**asymmetric switching, 102, 135**  
**attenuation, 117**  
**authentication, OSPF, 53-54**  
**automatic route summarization, 15-16**  
    disabling, 21-22  
**autonegotiation, 173**  
**availability, 128**  
    five nines, 192

## B

---

**backbone areas, 41**  
**backbone cabling, 133**  
**backbone links, 245**  
**backbone routers, 41**  
**backup ports (RSTP), 206**

## bandwidth

    of Ethernet applications, requirements, 116  
    utilization LEDs, 156  
**benefits of link-state routing, 44**  
**BIDs (bridge IDs), 200**  
**bit-time, 116**  
**blocking state (STP), 201**  
**bootup output, displaying on Catalyst switches, 157-159**  
**BPDU (bridge protocol data units), root bridge election, 201**  
**bridges, 97-98, 109**  
**broadcast domains, 106, 127, 219**  
**broadcast multiaccess networks, 55**  
**broadcast storms, 193-194**  
**broadcasting, 106, 127**  
**buffering, 103**

## C

---

### cabling

    attenuation, 117  
    crossover cables, 107  
    Layer 1 network design, 132  
    straight-through cables, 107  
**calculating OSPF cost, 48**  
**CAM (Content Addressable Memory), 102**  
**Catalyst switches**  
    2950 series switches, verifying trunk configuration, 227  
    adding to network, 180  
    bootup output, viewing, 157-159  
    configuration files, uploading to TFTP server, 181-182  
    context-sensitive help, 162  
    default configuration, 163-166  
    default gateway, assigning, 170  
    duplex operation, configuring, 172-173  
    front-panel LEDs, 154  
        *bandwidth utilization LEDs, 156*  
        *Port Mode LED, 155*  
        *Port Status LED, 155*  
        *System LED, 155*  
    HTTP support, configuring, 171  
    IOS images, upgrading, 182-183

**MAC address table**

- assigning permanent MAC addresses to interfaces, 174-175*
- deleting MAC addresses, 180*
- managing, 173*

**models, 141****naming, 169****NVRAM, clearing, 181****password recovery, 182****port security**

- configuring, 175-178*
- verifying, 178-179*

**restoring default configuration, 169****SFP slots, 153****starting up, 152****switch ports, 153**

- VLAN membership modes, 222*

**System Configuration dialog, 160****user EXEC mode, switching to privileged EXEC mode, 162****verifying configuration settings, 167-168****CDP (Cisco Discovery Protocol), 223****changing VLANs, 232-233****CIDR (classless inter-domain routing), 11****example of, 14****versus aggregation, 12****classful IP addressing, supernetting, 13****classful routing**

- automatic route summarization, 15-16, 22*
- default routes, 18*
- discontiguous subnets, 17*
- FLSM, 17*
- RIPv1, 23*

**classless IP addressing****CIDR, 11**

- example of, 14*

**subnet masking, VLSM, 2-9****classless routing, 20****and discontiguous subnets, 21****RIPv2, 24-25**

- configuring, 25-26*
- troubleshooting configuration, 29-30*
- verifying configuration, 27-29*

**clear mac-address table command, 174****clearing NVRAM on Catalyst switches, 181****Client mode (VTP), 257****CMS (Cluster Management Suite), 171****collision domains, 105, 125****collisions, 126****in Ethernet networks, 109****in half-duplex mode, 235****commands**

- clear mac-address-table, 174*
- debug ip eigrp, 80*
- debug ip igrp, 84, 87-88*
- debug ip ospf, 81-82*
- debug ip ospf packet, 58*
- debug ip rip, 29, 78-79*
- enable, 162*
- erase startup-config, 181*
- ip classless, 20*
- network, 50, 71*
- router ospf, 49*
- show flash, 167*
- show interfaces, 234*
- show interfaces switchport, 230*
- show mac-address-table, 174*
- show running-config, 27, 163-166*
- show spanning-tree vlan, 230*
- show version, 167-168*
- show vtp status, 260*
- switchport port-security, 176*

**comparing EIGRP and IGRP, 67****configuration files uploading to TFTP server, 181-182****configuration revision number, 257****configuring****Catalyst switches**

- default gateway, assigning, 170*
- duplex operation, 172-173*
- hostname, 169*
- HTTP support, 171*
- MAC address table, 174-175*
- port security, 175-178*
- with System Configuration dialog, 160*

**EIGRP, 71**

- interface bandwidth, 72*
- summarization, 73*
- verifying configuration, 75*

**IEEE 802.1Q trunking, 253-254****inter-VLAN routing, 263-265****ISL trunking, 254-255****OSPF, authentication, 54****RIPv2, 25-26****single-area OSPF, 49-50****VLANs, 223**

- static VLANs, 223-225*
  - verifying configuration, 226*
- VTP, 259-260**

**context-sensitive help on Catalyst switches, 162****convergence, 198**

- designated port selection, 200*
- EIGRP properties, 67*

- path cost, 198
- reconvergence after STP calculation, 204
- root bridge election, 199-201
- core layer of hierarchical design model, 143-144**
- COs (central offices), 244**
- cost metric, 44**
  - OSPF, modifying, 52-53
- CRC (cyclic redundancy check), 98**
- crossover cables, 107**
- CSMA/CD (carrier sense multiple access/collision detect), 125**
- cut-through switching, 104**
- CVSM (Cisco Virtual Switch Manager), 171**

## D

---

- data link layer topology, 135**
  - requirements, 135-136
- dead interval (OSPF), configuring, 56**
- debug commands, 78**
- debug ip eigrp command, 80**
- debug ip igrp command, 84, 87-88**
- debug ip ospf command, 81-82**
- debug ip ospf packet command, 58**
- debug ip rip command, 29, 78-79**
- default Catalyst switch configuration, 163-165**
  - port VLAN membership, 166
  - restoring, 169
- default gateways, assigning to Catalyst switches, 170**
- default routes, 18**
  - propagating, 56
- delay. *See* latency**
- deleting**
  - MAC addresses from MAC address table, 180
  - VLANs, 232-233
- designated ports (RSTP), 206**
  - selection process, 200
- designing LANs**
  - hierarchical design model, 139-144
  - Layer 1 design, 132
    - HCCs*, 132
    - IDFs*, 133
    - logical diagrams*, 134
    - VCCs*, 133
  - Layer 2 design, 135-136

- Layer 3 design
  - logical network addressing map*, 137
  - requirements*, 136
  - VLANs*, 137
- logical design, 129
- methodology, 127-129
- Dijkstra's algorithm, 45, 48-49**
- disabled ports (RSTP), 206**
- disabling automatic summarization, 21-22**
- discarding ports, 200**
- discontiguous subnets, 17**
  - and classful IP routing, 21
- displaying**
  - bootup output on Catalyst switches, 157-159
  - MAC address table, 174
  - OSPF configuration information, 57
  - VLAN membership on Catalyst switches, 166
- distance vector routing protocols, troubleshooting**
  - IGRP, 83-88
  - RIP, 78-79
- distribution layer, hierarchical design model, 141-143**
- documenting**
  - LAN design requirements, 128
  - logical and physical network topology, 129
- DUAL (Diffusing Update Algorithm), 67**
- duplex operation, configuring on Catalyst switches, 172-173**
- Dynamic Host Configuration Protocol, 232**
- dynamic VLAN membership mode, 222**

## E

---

- edge ports, 208**
- efficiency of full-duplex Ethernet, 114**
- EIGRP (Enhanced IGRP), 66**
  - automatic route summarization, 68
  - autosummarization, 73
  - comparing with IGRP, 67
  - configuring, 71
  - DUAL, 67
  - feasible successors, 68
  - hello interval, 70
  - interface bandwidth, setting, 72
  - neighbor table, 68
    - passive state*, 70
  - packets, 70
    - acknowledgment packets*, 70
    - query packets*, 71
    - update packets*, 71
  - show commands, 75
  - successors, 68

summarization, configuring, 73  
 topology table, 68  
 troubleshooting, 79-80  
 verifying configuration, 75

**enable command, 162**

**enterprise networks, redundancy, 192**

**enterprise servers, 125**

**erase startup-config command, 181**

**Ethernet, 108**

attenuation, 117  
 bandwidth requirements, 116  
 bit-time, 116  
 bridges, 109  
 collisions, 109  
 factors affecting performance, 111  
 frame transmission modes, 103  
 full-duplex mode, 113  
   *efficiency of, 114*  
 half-duplex mode, 112  
   *collisions, 235*  
 hubs, 108  
 latency, 116-117  
   *factors affecting, 117*  
   *of switches, 101*  
 NICs, 112-114  
 switches, 101, 110  
 transmission speeds, 112  
 VLANs, adding, 225

**examples**

of CIDR, 14  
 of VLSM, 8-9

**EXEC mode, switching to privileged EXEC mode, 162**

## F

**Fast Ethernet, transmission speed, 112**

**FCS (Frame Check Sequence) field, 98**

**feasible successors, 68**

**five nines availability, 192**

**flooding, 100**

**forward delay, 202**

**forwarding state (STP), 202**

**forwarding tables, 45**

**fragment-free switching mode, 104**

**frame filtering, 101**

**frame tagging, 246**

**frame transmission modes, 104**

**front-panel LEDs, Catalyst switches, 154**

Port Mode LED, 155  
 Port Status LED, 155  
 System LED, 155

**full-duplex mode**

configuring on Catalyst switches, 172-173  
 Ethernet, 113-114

## G-H

**Garcia-Luna-Aceves, Dr. J.J., 67**

**Gigabit Ethernet, transmission speed, 112**

**half-duplex mode**

collisions, 235  
 configuring on Catalyst switches, 172-173  
 Ethernet, 112

**HCCs (horizontal cross connects), 132**

**hello interval, 70**

OSPF, configuring, 56

**hello protocol, 51**

**help facilities on Catalyst switches, 162**

**hierarchical network design model**

access layer, 139-141  
 core layer, 143-144  
 distribution layer, 141-143

**hierarchical routing, 47**

**hostname, assigning to Catalyst switches, 169**

**HTTP support, configuring on Catalyst switches, 171**

**hubs, 108**

**hybrid routing protocols, EIGRP, 66**

automatic route summarization, 68  
 configuring, 71  
 feasible successors, 68  
 neighbor table, 68  
 routing table, 68  
 successors, 68  
 troubleshooting, 79-80

**HyperTerminal, displaying bootup output, 157-159**

## H

**IDFs (intermediate distribution frames), 133**

**IEEE 802.1Q trunking, 246-247, 250**

configuring, 253-254  
 port groups, 250

**IEEE 802.3. See Ethernet**

**IGRP (Interior Gateway Routing Protocol)**

- comparing with EIGRP, 67
- troubleshooting, 83-88

**instability in MAC address table, 194****integrated circuits, ASICs, 101****inter-VLAN routing, 218-220, 261**

- configuring, 263-265
- router-on-a-stick, 261-262

**interface bandwidth (EIGRP), configuring, 72****IOS images, upgrading on Catalyst switches, 182-183****IP addressing**

- binary notation, 6
- network prefix, 2
- slash notation, 5

**ip classless command, 20****IS-IS (Intermediate System-to-Intermediate System), 39****ISL (Inter-Switch Link), 246, 250-253**

- configuring, 254-255

**L****LAN switching, 138. See also LANs**

- asymmetric, 102
- frame transmission modes, 103-104
- segmentation, 96

**LANs**

- design goals, 124, 127-129
- hierarchical design model, 139
  - access layer, 139-141*
  - core layer, 143-144*
  - distribution layer, 141-143*
- Layer 1 design, 132-134
- Layer 2 design, 135-136
- Layer 3 design, 136-137
- logical design, 129

**latency, 101, 116-117**

- bit-time, 116
- factors affecting, 117

**Layer 1 network design**

- HCCs, 132
- IDFs, 133
- logical diagrams, 134
- VCCs, 133

**Layer 2 devices**

- disadvantages of, 110
- switches, 99. See also *Catalyst switches*
  - frame filtering, 101*
  - functions of, 99*
  - MAC address table, 100*
- versus Layer 1 devices, 109

**Layer 2 network design requirements, 135-136****Layer 2 switching, 101****Layer 3 devices**

- routers, 110
  - segmentation, 98*
- switches, 101, 136, 218

**Layer 3 network design**

- logical network addressing map, 137
- requirements, 136
- VLANs, 137

**learning state (STP), 202****LEDs, Catalyst front-panel, 154-155****Li, Tony, 9****limitations**

- of link-state routing, 45-46
- of Thick/Thin Ethernet, 108

**link-state database (OSPF), 46****link-state refreshes, 39****link-state routing protocols**

- benefits of, 44
- IS-IS, 39
- limitations of, 45-46
- OSPF
  - authentication, 53-54*
  - configuration information, displaying, 57*
  - cost metric, 44*
  - cost metric, calculating, 48*
  - default routes, propagating, 56*
  - Dijkstra's algorithm, 48-49*
  - link-state database, 46*
  - LSAs, triggered updates, 42*
  - network types, 55*
  - router roles, 41*
  - troubleshooting, 57-59, 81-82*

**listening state (STP), 202****logical network design, 129****loop-avoidance mechanisms**

- DUAL, 67
- RSTP, 206
  - port roles, 206-207*
  - port states, 207-208*
- STP, 197
  - background, 197-198*
  - convergence, 198-201*
  - port states, 201, 204*

**loopback interfaces, 52****LSAs (link-state advertisements)**

- flooding, 45
- triggered updates, 42

**M****MAC address table, 100**

- age time, 101
- assigning permanent MAC addresses to interfaces, 174-175
- instability, 194-197
- managing on Catalyst switches, 173

**MAC broadcast domains, 106****management VLANs, 170****max age timer, 202****memory**

- buffering, 103
- CAM, 102

**methodologies for effective LAN design, 127**

- documentation, 128
- topology, selecting, 129

**metrics, cost, 44**

- calculating, 48
- modifying, 52-53

**microsegmentation, 99, 127, 135****modifying**

- OSPF cost metric, 52-53
- VLAN name/number, 225

**moving MAC addresses to another switch, 180****MST (mono spanning tree), 248****MTU (maximum transmission unit), 251****multicast transmission, 106****multilayer switches, 218****multiple frame transmissions, 195-196****N****naming Catalyst switches, 169****NBMA (nonbroadcast multiaccess networks), 55****neighbor table (EIGRP), 68**

- passive state, 70

**network command, 50, 71****network layer topology**

- logical network addressing map, 137
- requirements, 136
- VLANs, 137

**network prefix, 2****network servers, 125****NICs (network interface cards), 112-114****nonbackbone areas, 41****nonbackbone internal routers, 42****nondesignated ports, 200****NVRAM, clearing on Catalyst switches, 181****O****OSPF (Open Shortest Path First)**

- authentication, 53-54
- configuration information, displaying, 57
- cost metric, 44
  - calculating, 48*
  - modifying, 52-53*
- dead interval, configuring, 56
- default routes, propagating, 56
- Dijkstra's algorithm, 48-49
- hello interval, configuring, 56
- hello protocol, 51
- hierarchical routing, 47
- link-state database, 46
- loopback interfaces, 52
- LSAs, triggered updates, 42
- network types, 55
- routers, roles of, 41
- routing process, process IDs, 50
- single-area, 46-47
  - configuring, 49-50*
- troubleshooting, 57-59, 81-82

**P-Q****packets, EIGRP, 70**

- acknowledgment packets, 70
- query packets, 71
- update packets, 71

**parameters of network command, 50****password recovery on Catalyst switches, 182****path cost, 198****physical layer topology**

- designing, 132-133
- documenting, 129
- logical diagrams, 134

**placement of enterprise/workgroup servers, 125****point-to-point networks, 55****port groups, 250****Port Mode LED, 155****port security**

- configuring on Catalyst switches, 175-178
- verifying on Catalyst switches, 178-179

**port states**

- RSTP, 207-208
- STP, 201, 204

Port Status LED, 155  
 port-based memory buffering, 103  
 PortFast, 203  
 ports, assigning to VLANs, 225-226  
 POST (power-on self test), 155  
 prefix length, 3-5  
 process ID, 50  
 purging MAC address table, 174  
 PVST (Per-VLAN Spanning Tree), 249  
 quad-zero routes, 56  
 query packets, 71

## R

reconvergence, 204  
 recovering lost passwords on Catalyst switches, 182  
 redundant topologies, 192
 

- goals of, 193
- MAC database instability, 196-197
- multiple frame transmissions, 195-196

 regions (PVST+), 249  
 removing VLANs, 232-233  
 reply packets, 70  
 requirements
 

- for Layer 2 network design, 135-136
- for Layer 3 network design, 136-137

 restoring default configuration on Catalyst switches, 169  
 restrictions on Layer 1 network design, 132  
 RIP (Routing Information Protocol)
 

- RIPv1, 23
- RIPv2, 2, 24-25
  - configuring, 25-26
  - verifying configuration, 27-29
  - troubleshooting, 29-30
- troubleshooting, 78-79

 root bridge election, 199-201  
 root ports (RSTP), 206-208  
 route summarization, 13
 

- automatic, 68
- EIGRP, configuring, 73

 router ospf command, 49  
 router-on-a-stick, 261-262  
 routers, 98, 110, 136  
 routing domains, 41  
 routing process, process ID, 50  
 routing protocols, troubleshooting, 76-77  
 RPS (Redundant Power Supply) LED, 155  
 RSTP (Rapid Spanning Tree Protocol), 206
 

- port roles, 206-207
- port states, 207-208

 RTP (Reliable Transport Protocol), 69

## S

segmentation, 96
 

- microsegmentation, 99

 selecting LAN topology, 129  
 server mode (VTP), 257  
 SFP (small-form-factor pluggable) slots, 153  
 shared memory buffering, 103  
 show commands, EIGRP-related, 75  
 show flash command, 167  
 show interfaces command, 234  
 show interfaces switchport command, 230  
 show mac-address table command, 174  
 show running-config command, 27, 163-166  
 show spanning-tree vlan command, 230  
 show version command, 167-168  
 show vtp status command, 260  
 single-area OSPF, 46-47
 

- configuring, 49-50

 slash notation, 5  
 slot time, 116  
 sources of latency, 116  
 SPF algorithm, 42, 49  
 starting Catalyst switches, 152  
 static VLANs
 

- configuring, 223-226
- membership mode, 222

 store-and-forward devices, bridges, 98  
 store-and-forward switching mode, 104  
 STP (Spanning Tree Protocol), 192, 197
 

- background, 197-198
- convergence, 198
  - designated port selection, 200
  - path cost, 198
  - root bridge election, 199-201
- max age timer, 202
- port states, 201, 204
- reconvergence, 204

 STP (shielded twisted pair), 132

**STP (Spanning Tree Protocol), 192****straight-through cables, 107****subnet masking**

- supernetting, 13
- VLSM, 2-3
  - benefits of, 6*
  - example of, 8-9*
  - prefix length, 3-5*
  - sub-subnetting, 7*

**successors, 68****summarization. See route summarization****supernetting, 13****switch ports, VLAN membership modes, 222****switched redundant topologies, 193****switches, 99, 107, 110. See also Catalyst switches**

- access layer, 140-141
- core layer, 144
- distribution layer, 142-143
- frame filtering, 101
- functions of, 99
- latency, 101
- MAC address table, 100
  - age time, 101*
  - assigning permanent MAC addresses to interfaces, 174-175*
  - instability, troubleshooting, 194-197*
  - managing on Catalyst switches, 173*
- segmentation, 99

**switchport port-security command, 176****symmetric switching, 102, 135****System Configuration dialog (Catalyst switches), 160****System LED (Catalyst switches), 155****T****Thick Ethernet, 108****Thin Ethernet, 108****TIA/EIA-568-A standard, 132****topological databases, 46, 68****topologies**

- redundancy, 192
- selecting, 129
- switched, redundancy, 193

**transmission speeds of Ethernet, 112****transparent mode (VTP), 257****triggered LSA updates, 42****troubleshooting**

- routing protocols, 76-77
  - EIGRP, 79-80*

*IGRP, 83-84, 87-88*

*OSPF, 81-82*

*RIP, 78-79*

*RIPv2 configuration, 29-30*

VLANs, 233-234

*scenarios, 236-237*

**trunking, 221, 244, 246**

frame tagging, 246

IEEE 802.1Q, 247

*configuring, 253-254*

*port groups, 250*

ISL, configuring, 250-255

VTP, 255-256

*advertisements, 257-258*

*configuring, 259-260*

**TTL (Time to Live), 194****U****update packets, 71****upgrading IOS images on Catalyst switches, 182-183****uploading configuration files to TFTP server, 181-182****uptime, 192****user EXEC mode, switching to privileged EXEC mode, 162****UTP (unshielded twisted pair), 132****V****validating VLAN parameters, 228-230****VCCs (vertical cross connects), 133****verifying**

- configuration settings on Catalyst switches, 167-168
- EIGRP configuration, 75
- port security on Catalyst switches, 178-179
- RIPv2 configuration, 27, 29
- spanning-tree information on VLANs, 230
- trunk configuration on Catalyst 2950 series switches, 227
- VLAN configuration, 226

**virtual circuits, 105****VLANs, 125, 137, 218**

- adding, 232-233
- changing, 232-233
- configuring, 223
- inter-VLAN routing, 261
  - configuring, 263-265*
  - router-on-a-stick, 261-262*
- membership modes, 222
- parameters, validating, 228-230
- removing, 232-233
- spanning-tree information, verifying, 230



- static, configuring, 223-226
- traditional implementation, 218
- troubleshooting, 233-234
  - scenarios*, 236-237
- trunking, 221, 244, 246
  - IEEE 802.1Q*, 247, 250
  - ISL*, 250-252
- verifying configuration, 226
- VTP, 255-256
  - advertisements*, 257-258
  - configuring*, 259-260
- workstations, 219

### **VLSM (variable-length subnet masking), 2-3**

- benefits of, 6
- example of, 8-9
- prefix length, 3-5
- sub-subnetting, 7
- troubleshooting, 78

### **VPMS (VLAN Management Policy Server), 222**

### **VTP (VLAN Trunking Protocol), 223, 244, 255-256**

- advertisements*, 257-258
- configuration revision number, 257
- configuring, 259-260
- domains, 256
- pruning, 258
- servers, 256

## **W-X-Y-Z**

---

**workgroup servers, 125**

**Zinn, Alex, 15**