

Index

Numerics

- 3DES (Triple DES), 191
 - IPSec tunneling, 185
- 5-4-3 Rule, 92

A

- ABR routers (OSPF), 329
- access layer
 - hierarchical LAN topologies, 51–52
 - high-availability network services, 60–66
- access points (APs), 87
- Account Manager, prototype demonstration
 - roles, 37
- accounting management, 482
- ACD routes (PSTN), 435
- acknowledgment packets (EIGRP), 309
- address allocations (IPv6), 244–249
- address assignments (IPv4), 221–224
- Address Family Identifier (AFI) field (RIPv1 messages), 294
- address subnets, IPv4, 213–214
 - design, 215
 - masks, 214
 - network portion determination, 216
- addresses
 - IPv6
 - aggregatable-global addresses*, 246
 - assignment strategies*, 251
 - IPv4-compatible addresses*, 246
 - IPX addresses*, 246
 - link-local addresses*, 247
 - loopback addresses*, 245
 - multicast addresses*, 247
 - NSAP addresses*, 246
 - prefixes*, 242–243
 - representation*, 241–242
 - site-local addresses*, 247
 - types*, 243–249
 - unspecified addresses*, 245
 - multicast, 363–364
- addressing
 - digital signaling, 430
 - IPv4, 208–209
- adjacencies (OSPF), 326–327
- administrative distance
 - BGP, 353
 - routing protocols, 273–274
- AFI field (RIPv2 messages), 298
- aggregatable-global addresses (IPv6), 246
- aggregate-address command, 359
- aggregation, channel, 66
- aggregator attribute (BGP), 356–357
- AH (Authentication Header), IPSec, 183–191
- analog signaling, 427–431
- anycast addresses (IPv6), 244
- appendixes (network design documentation), 31
- application factors, WAN design, 140–143
- application layer (OSI Layer 7), 587
- application-layer attacks, 392

applications, accessing, WANs, 140

APs (access points), 87

areas

IS-IS, 336–337

OSPF, 327–328

stub areas, 331–332

SAFE, 414–415

ARP, 221, 224–225

workstation-to-router redundancy, 61

AS external paths, 331

AS path attribute (BGP), 355

ASBR routers (OSPF), 329

assignments, addresses, IPv6, 251

ATM, WANs, 124

cells, 124

connections, 125

atomic aggregate attribute (BGP), 356–357

attacks

application-layer attacks, 392

DoS, 388

man-in-the-middle attacks, 387

passwords, 389

port-redirection attacks, 390

trojan-horse applications, 392

trust exploitation, 390

unauthorized access attacks, 391

viruses, 392

attributes (BGP)

aggregator attribute, 356–357

AS path attribute, 355

atomic aggregate attribute, 356–357

community attribute, 356

decision process attribute, 358–359

local preference attribute, 354–355

MED attribute, 356–357

next-hop attributes, 354

origin attribute, 355

path attributes, 354

weight attribute, 357–358

auditing tools, 16

authentication

IS-IS, 336–337

OSPF routers, 333

RIPv2, 297

Authentication Header (AH), IPSec, 183-191

availability

networks, 68

increasing, 63–64

AVVID, 439–444, 456

centralized WAN call-processing model,
440–442

codecs, 442–444, 456

distributed WAN call-processing model,
441–443

single-site deployment model, 440–441

VoIP, 444–451

B

backbone routers (OSPF), 329

backbones, core layer, hierarchical LAN

topologies, 50

backup links, 65**backups**

- dial backup routing, 159–160
- Internet, 161–163
- permanent secondary WAN links, 161
- shadow PVCs, 161

bandwidth metric parameters (routing protocols), 275–276**BGP (Border Gateway Protocol), 345, 348, 359**

- administrative distance, 353
- attributes
 - aggregator attribute, 356–357*
 - AS path attribute, 355*
 - atomic aggregate attribute, 356–357*
 - community attribute, 356*
 - decision process attribute, 358–359*
 - local preference attribute, 354–355*
 - MED attribute, 356–357*
 - next-hop attributes, 354*
 - origin attribute, 355*
 - path attributes, 354*
 - weight attribute, 357–358*
- confederations, 351, 353
- neighbors, 348–349
 - eBGP, 349–350*
 - iBGP, 350–351*
- route reflectors, 350–352
- routes, redistribution, 360–361

bgp confederation identifier command, 352**BGP4 Multiprotocol Extensions for IPv6, 253****Big Oil and Gas case study, 501–503****binary numbers, converting, 592–598****blueprint (SAFE), 409–410****BOOTP, 221–222, 225****Border Gateway Protocol (BGP). *See* BGP (Border Gateway Protocol)****BRI ISDNs, 120****bridges, 93, 105**

- LANs, 93
- root bridges, 94

broadcast storms, 65**C****cable, WANs, 126****Campus LANs, 106****carrier sense multiple access collision avoidance (CSMA/CA), 87****case studies**

- Big Oil and Gas, 501–503
- Cicala and Rosado Law Firm, 495–500
- Sound Masters, 505–509
- Super Consulting, 503–505

CDP (Cisco Discovery Protocol), 463, 471

- advantages, 472
- components, 471
- design, 472
- RMON, 472

cells (ATM), 124**cell-switching WANs, 118****centralized WAN call-processing model, AVVID, 440–442****centrex services (PSTN), 434****CGMP, 103, 367****channel aggregation, 66****Channelized T1 switches, 427****Cicala and Rosado Law Firm case study, 495–500****CIDR, 199, 219****circuit-switched WANs, 117****Cisco Discovery Protocol (CDP). *See* CDP (Cisco Discovery Protocol)****Class A Addresses (IPv4), 210****Class B addresses (IPv4), 210****Class C addresses (IPv4), 210****Class D addresses (IPv4), 210**

Class E addresses (IPv4), 211
Class I repeaters, 100BaseT, 82
Class II repeaters, 100BaseT, 82
classes, IPv4 addresses, 209
classful routing protocols, 272–273
classless routing protocols, 272–273
CMGP, 367
codecs, AVVID, 442–444, 456
collision delay, Fast (100 Mbps) Ethernet, 80
collision domains

- bridges, 93
- routers, 95
- switches, 96

coloring, 100
command field (RIPv1 messages), 294
Command field (RIPv2 messages), 298
commands

- aggregate-address command, 359
- bgp confederation identifier command, 352
- debug, 481
- default-metric command, 362
- maximum-paths, 63
- network command, 359
- redistribute command, 359
- redistribution command, 362
- show, 481
- show ip bgp 200.50.32.0, 356
- show ip rip database command, 293
- SNMP, 470

communications, secure management, 394
community attribute (BGP), 356
competition, prototypes, 36
compression, WANs, 145–146
confederations (BGP), 351, 353
configuration

- explicit configurations (default routers), 61
- NET, OSPF, 335–336

configuration management, 482

connections (ATM), 125
constraints, network design

- economic constraints, 15
- labor constraints, 14
- political constraints, 15
- technological constraints, 14

converting

- binary numbers, 592–598
- hexadecimal numbers, 589–592

core layer

- hierarchical LAN topologies, 50
- hierarchical network models, 50–51

CoS (Cost of Service), 100-102
cost

- hierarchical LAN topologies, 48
- network design, 15
- WANs, 144–145

cost metric parameters (routing protocols), 276–277
Cost of Service (CoS), 100-102
counting to infinity method, loop prevention, 280
CPE (customer premises equipment), 119
CQ (Custom Queuing), 148
CRC errors, bridges, 93
CRTP, 445, 451
CSMA/CA (carrier sense multiple access multiple access collision avoidance), 87
Custom Queuing (CQ), 148
customer expectations, 411
customer premises equipment (CPE), 119
customer requirements, prototypes, 34–35

D

DARPA (Defense Advanced Research Projects), 203

data compression

- FRF.9 Frame Relay payload compression, 145
- HDLC using LZS, 145
- LAPB Payload Compression using LZS, 145
- MPPC, 146
- Van Jacobson Header Compression for TCP/IP, 146
- WANs, 145–146
- X.25 Payload Compression of Encapsulated Traffic, 146
- Data Encryption Standard (DES). See DES (Data Encryption Standard)**
- data link layer (OSI Layer 2), 584–585**
- Data Over Cable Service Interface Specification (DOCSIS), 126**
- data terminal equipment (DTE), FOIRL (fiber-optic interrepeater link), 80**
- database services, PSTN, 434**
- DDR (dial-on-demand routing), 119**
- DE (Discard Eligibility), Frame Relay, 122**
- debug command, 481**
- decision process attribute, BGP, 358–359**
- default gateways, 61**
- default routers, 61**
- default-metric command, 362**
- Defense Advanced Research Projects Agency (DARPA), 203**
- delay (response times), 140**
 - components, 450
 - repeaters, 140
- delay dial protocol, 429**
- delay metric parameters (routing protocols), 277**
- demonstrations, prototypes, 37**
 - practicing, 38
- dense routing protocols, multicasting, 368**
- DES (Data Encryption Standard), 191**
 - IPSec tunneling, 185

design

- CDP, 472
- EIGRP, 309–310
- IGRP, 302–303
- IS-IS, 335–336
- LANs
 - EtherChannel, 84–85*
 - Ethernet, 79–82*
 - FDDI, 85*
 - Gigabit Ethernet, 82–84*
 - Token Ring, 85*
 - WLANs, 86–91*
- networks, 9
 - economic constraints, 15*
 - labor constraints, 14*
 - political constraints, 15*
 - technological constraints, 14*
 - top-down network design, 11–14*
- OSPF, 325
- RIPv1, 296
- RIPv2, 299
- SAFE blueprint, 412–414
- SNMP, 470
- voice architectures, 448–451
- WANs, 139
 - application factors, 140–143*
 - cost factors, 144–145*
 - technical factors, 143*
- design consultants, prototype demonstration roles, 37**
- design documents, WANs, 140**
- design methodology, 21, 25**
 - design, 27–28
 - implementation, 28
 - network documentation, 29
 - design requirements, 30*
 - design solution, 30*
 - executive summary, 30*
 - summary and appendices, 31–32*

- operability, 28–29
- optimization, 29
- PDIOO (planning, design, implementation, operation, optimization), 26
- planning, 26–27
- prototypes, 32–34
- design requirements (network design documentation), 30**
- design solution (network design documentation), 30**
- designing topologies, LANs (local area networks), 97–99**
 - hierarchical models, 48, 52
 - redundant models, 60, 66
- Destination address field (IPv4 headers), 205**
- Destination address field (IPv6 headers), 241**
- DHCP (Dynamic Host Control Protocol), 221–225, 444**
- dial backup routing, 159–160**
- dial-on-demand routing (DDR), 119**
- dial-up WANs, 119**
- diameters (hops), 50**
- Differentiated Services Control Point (DSCP), 148**
- Diffie-Hellman method**
 - IPSec tunneling, 185
 - shared secret key generation, 191
- digital signaling, 427–431**
 - addressing, 430
- digital subscriber lines (DSLs). *See* DSLs (digital subscriber lines)**
- Direct Sequence Spread Spectrum (DSSS), 86**
- distance-vector routing protocols, 271**
 - link-state protocols, compared, 272
- distributed WAN call-processing model, AVVID, 441, 443**
- distribution layer**
 - hierarchical LAN topologies, 51
 - hierarchical network models, 51–52
- DNS (Domain Name System), 221–225, 444**
- DOCSIS (Data Over Cable Service Interface Specification), 126**
- documentation, network, 29**
 - design requirements, 30
 - design solution, 30
 - executive summary, 30
 - summary and appendices, 31–32
- Domain Name System (DNS), 444**
- DoS attacks, 388**
- downtime, route redundancy, 64**
- DRs**
 - IS-IS, 336
 - OSPF, 329–330
- DSCP (Differentiated Services Control Point), 148**
- DSL**
 - WANs, 125–126
- DSLs (digital subscriber lines), 173, 176–177**
 - ADSL, 177
 - HDSL, 178
 - IDSL, 179
 - SDSL, 178
 - VDSL, 179–180
 - WANs, 125–126
- DSSS (Direct Sequence Spread Spectrum), 86**
- DTE (data terminal equipment)**
 - FOIRL (fiber-optic interrepeater link), 80
- DUAL, EIGRP, 305–306**
- dual-stack backbones, IPv6, 255**
- DVMRP, 370**
- Dynamic Host Control Protocol (DHCP), 221–225, 444**
- dynamic IP address assignments, 221**
- Dynamic NAT, 212**
- dynamic route assignments, static route assignments, compared, 268–269**

E

E&M (ear and mouth) switches, 426

E&M (ear and mouth) analog signaling, 428

eBGP, 349–350

e-commerce module (Enterprise Edge), 57

economic constraints, network design, 15

ecosystems, security, 415

EGPs (exterior gateway protocols), 270

IGPs, compared, 270

EIGRP (Enhanced Interior Gateway Routing Protocol), 271, 289, 303–304

design, 309–310

DUAL, 305–306

metrics, 307–309

neighborhood database, 305

packets, 309

protocol-dependent modules, 304–305

redistribution, 362–363

RTP, 305

timers, 306–307

updates, 307

variance, 63

Encapsulating Security Payload (ESP). *See*

ESP (Encapsulated Security Payload)

end-user host attacks, 392

Enhanced IGRP (EIGRP). *See* EIGRP (Enhanced IGRP)

Enterprise Campus, 55–56, 67, 78

Enterprise Composite Network model, 48, 54–55, 67

Enterprise Campus, 67

enterprise campus modules, 55–56

Enterprise Edge, 67

Enterprise Edge modules, 57–59

SP (service provider) Edge modules, 60

SP Edge, 67

WANs, 118–119

Enterprise Edge modules, 57–59, 67

e-commerce module, 57

Internet module, 57–58

VPN/remote access module, 58–59

WAN module, 59

enterprise infrastructure, LANs, 55

equipment preparation, prototypes, 38

erlangs, voice architectures, 433

error detection, error recovery, compared, 31–32

ESP (Encapsulating Security Payload), 191

IPSec tunneling, 184

EtherChannel, LANs, design rules, 84–85

Ethernet, 79–82

10-Mbps Ethernet, design rules, 79

100-Mbps Ethernet, design rules, 80

100BASE-FX Ethernet, 81

100BASE-T repeaters, 81

100BASE-T4 Fast Ethernet, 81

100BASE-TX Fast Ethernet, 80

EtherChannel, design rules, 84–85

Gigabit Ethernet, 82–84

IEEE 802.3, scalability constraints, 79

LANs, design rules, 79–82

executive summary (network design documentation), 30

explicit configurations (default routers), workstation-to-router redundancy, 61

F

fault management, 481–482

FCC (Federal Communication Commission), 88

FDDI, 85–86

feasible successor paths, 306

FHSS (Frequency Hopping Spread Spectrum), 86

fiber-optic interrepeater link (FOIRL), Ethernet, 80

fields, IPv4 headers, 203–206

Flags field (IPv4 headers), 204

flat routing protocols, 272

floating static routes, 65
 flooding, 93
 Flow label field (IPv6 headers), 241
 flush timers, RIPv1, 295
 FOIRL (fiber-optic interrepeater link),
 Ehernet, 80
 Foreign Exchange Office (FXO), 426
 Foreign Exchange Station (FXS), 426
 formats, messages (RIP), 293–299
 forwarding information (RIP), 292–297
 Fragment offset field (IPv4 headers), 204
 fragmentation (IPv4), 207–208
 Frame Relay, WANs, 122
 DE (Discard Eligibility), 122
 LMI (Local Management Interface), 123
 frequencies, WLANs, 88
 Frequency Hopping Spread Spectrum
 (FHSS), 86
 FRF.9 Frame Relay payload compression, 145
 full mesh networks, 63
 full-mesh topologies, 166–167
 FXO (Foreign Exchange Office), 426
 FXS (Foreign Exchange Station), 426

G

gatekeepers, 446
 gateway information (RIP), 292, 297
 gateways, 446
 default gateways, 61
 Gigabit Ethernet
 10 Gigabit Ethernet, 84
 1000BASE-CX Gigabit Ethernet over
 Coaxial Cable, 83
 1000BASE-LX Long Wavelength Gigabit
 Ethernet, 83
 1000BASE-SX Short Wave Gigabit
 Ethernet, 83

 1000BASE-T Gigabit Ethernet over UTP,
 84
 LANs, design rules, 82–84
 global network business, 10–11
 grade of service (GoS), voice architectures,
 432
 GRE (Generic Routing Encapsulation), 191
 tunneling, 181
 ground-start signaling, 428

H

H.323, 444, 446
 hardware, LANs, 96
 bridges, 93
 hubs, 92
 repeaters, 92
 routers, 95–96
 switches, 95
 hardware queues, WANs, 147
 Hash Message Authentication Code-Message
 Digest 5 (HMAC-MD5), 191
 Hash Message Authentication Code-Secure
 Hash Algorithm-1 (HMAC-SHA-1), 191
 HDLC using LZS, 145
 HDSL, 178
 Header checksum field (IPv4 headers), 205
 headers
 IPv4, 203–207
 IPv6, 240–241
 Hello packets, OSPF, 326
 hello packets (EIGRP), 309
 Hewlett-Packard OpenView (HPOV), 466
 hexadecimal numbers, converting, 589–592
 hierarchical LAN topologies, 48, 52
 hierarchical network models, 48
 access layer, high-availability network
 services, 60–66

- benefits, 48–49
- design, 49–52
- Enterprise Composite Network model, 54–55
 - enterprise campus modules*, 55–56
 - Enterprise Edge modules*, 57–59
 - SP (service provider) Edge modules*, 60
- Enterprise Composite network model, 48
- layers, 49–50
 - access layer*, 52
 - core layer*, 50–51
 - distribution layer*, 51
- routed hierarchical network model, 53
- switched hierarchical network model, 53
- hierarchical routing protocols**, 272
- high-availability network services**, 60–66
- HMAC-MD5 (Hash Message Authentication Code-Message Digest 5)**, 191
- HMACs (Hash Message Authentication Codes)**, IPsec tunneling, 185
- HMAC-SHA-1 (Hash Message Authentication Code-Secure Hash Algorithm-1)**, 191
- holddown timers (RIPv1)**, 295
- Hop limit field (IPv6 headers)**, 241
- hop-count metric parameters (routing protocols)**, 275
- hops**, diameters, 50
- HPOV (Hewlett-Packard OpenView)**, 466
- HSRP, workstation-to-router redundancy**, 61–62
- hubs**, 92, 105
- IANA**, 204, 209, 223
- iBGP**, 350–351
- ICMPv6**, 249–250
- Identification field (IPv4 headers)**, 204
- identity, ecosystems**, 415
- IDSL**, 179
- IEEE 802.1X Port-Based Authentication**, 90
- IEEE 802.3, scalability constraints**, 79
- IGMP, 365-366**
 - CGMP, 367
 - snooping, 367
- IGPs (interior gateway protocols)**, 270
 - EGPs, compared, 270
 - redistribution, 361
- IGRP (Interior Gateway Routing Protocol)**, 289, 300
 - design, 302–303
 - metrics, 301–302
 - redistribution, 362
 - timers, 300
 - variance, 63
- IHL field (IPv4 headers)**, 204
- IKE (Internet Key Exchange)**, 191
- in-band management**, 395
- Industrial, Scientific, and Medical (ISM) frequencies**, 88, 91
- infrastructure, networks**, 9
- integrated multiservice networks, voice architectures**, 435
 - AVVID, 439–444, 456
 - VoATM (Voice over ATM), 436–437
 - VoFR (Voice over Frame Relay), 435–436
 - VoIP (Voice over IP), 437–438
- interface (RIPv1)**, 293
- interface information (RIPv2)**, 297
- Intermediate System-to-Intermediate System (IS-IS) protocol**. *See* IS-IS protocol
- internal routers, OSPF**, 329
- International Organization for Standardization (ISO)**, 583
- Internet**
 - backups, 161–163
 - service levels, 484–485
 - SLAs*, 485
 - SLM*, 486–487
- Internet Key Exchange (IKE)**, 191
- Internet module (Enterprise Edge)**, 57–58

Internet Protocol Version 4 (IPv4). *See* **IPv4 (Internet Protocol Version 4)**

Inter-Switch Links (ISLs), 100

invalid timers, RIPv1, 295

inventory sheets, prototypes, 38

IP address field (RIPv1 messages), 294

IP address field (RIPv2 messages), 298

IP address information (RIPv1), 292

IP address information (RIPv2), 297

IP multicasting

addresses, 363–364

dense routing, 368

DVRMP, 370

layer mapping, 364–365

PIM, 369

PIM-SM, 369–370

shared trees, 368

source trees, 368

sparse routing protocols, 368

IP options field (IPv4 headers), 205

IP Security (IPSec) protocol. *See* **IPSec protocol**

IP spoofing, 388

IPSec (IP Security) protocol, 173, 191

AH (Authentication Header), 191

tunneling, 182

3DES, 185

AH (Authentication Header), 183

connections, 183

DES, 185

Diffie-Hellman method, 185

ESP, 184

HMACs, 185

IPv4 (Internet Protocol Version 4), 199

address assignment, 221–224

address subnets, 213–214

design, 215

masks, 214

network portion determination, 216

addressing, 208–209

fragmentation, 207–208

headers, 203–207

IPv6

compared, 256

transition strategies, 253–255

name resolution, 221–224

NAT (Network Address Translation), 212–213

private addresses, 211

VLSMs, 216–220

IPv4-compatible addresses (IPv6), 246

IPv6 (Internet Protocol Version 6), 235, 239–240

address representation, 241–242

addresses

aggregatable addresses, 246

assignment strategies, 251

IPv4-compatible addresses, 246

IPX addresses, 246

link-local addresses, 247

loopback addresses, 245

multicast addresses, 247

NSAP addresses, 246

prefixes, 242–243

site-local addresses, 247

types, 243–249

unspecified addresses, 245

dual-stack backbones, 255

headers, 240–241

ICMPv6, 249–250

IPv4

compared, 256

transition strategies, 253–255

IPv6 over dedicated WAN links, 253

IPv6 over IPv4 tunnels, 254

MTU discovery, 251

name resolution, 250

ND, 250

protocol translation mechanisms, 255

- routing protocols, 252–253

- security, 252

- upgrades to, 239

IPX addresses (IPv6), 246

ISDN Primary Rate Interface, 427

ISDN T1 PRI, 429

ISDNs

- channel aggregations, 66

- WANs, 119–121

IS-IS (Intermediate System-to-Intermediate System) protocol, 321, 334

- areas, 336–337

- authentication, 336–337

- design, 335–336

- DRs, 336

- metrics, 334–335

IS-IS for IPv6, 253

ISLs (Inter-Switch Links), 100-101

ISM (Industrial, Scientific, and Medical) frequencies, 88-91

ISO (International Organization for Standardization), 583

IVR systems, PSTN, 434

J-L

jitters (response times), 140

labels, MPLS, 187

labor constraints, network design, 14

LANs (local-area networks), 75

- bridges, 93

- campus, 97–99

- Enterprise Campus, 78

- enterprise infrastructure, 55

- FDDI, design rules, 85

- hardware, 105

- hubs, 92

- large building, 97–98

- media

- Ethernet, 79, 81*

- Fast (100 Mbps) Ethernet, 80, 82*

- FDDI, 85–86*

- Fiber Ethernet, 79–80*

- Gigabit (1000 Mbps) Ethernet, 82*

- media types, 78

- EtherChannel, 84–85*

- Ethernet, 79–82*

- Gigabit Ethernet, 82–84*

- multicast traffic, 102–104

- QoS (quality of service) considerations, 100–102

- repeaters, 92–93

- routers, 95–96

- server-farm module, 99–101

- small/remote site, 97, 99

- switches, 94–95

- Layer 3 switches, 96*

- Token Ring, design rules, 85

- topologies

- hierarchical models, 48, 52*

- redundant models, 60, 66*

- WANs, compared, 116

- WLANs, design rules, 86–91

LAPB Payload Compression using LZS, 145

large building LANs, 106

latency, repeaters, 92

Layer 3 switches, 96, 105

layers

- hierarchical LAN topologies

- access layer, 51–52*

- core layer, 50*

- distribution layer, 51*

- hierarchical network models, 49–50

- access layer, 52*

- core layer, 50–51*

- distribution layer, 51*

LANs (local area networks), **48, 52**

mapping, multicasting, 364–365

OSI

application layer (OSI Layer 7), 587

data link layer (OSI Layer 2), 584–585

network layer (OSI Layer 3), 585

physical layer (OSI Layer 1), 584

presentation layer (OSI Layer 6), 587

session layer (OSI Layer 5), 586

transport layer (OSI Layer 4), 586

LEAP (Lightweight Extensible

Authentication Protocol), 90-91

leased WANs, cost considerations, 144

leased-line WANs, 116–117

LFI, 451–452

link failures, redundant networks, 63

link-local addresses (IPv6), 247

links, backup links, redundancy, 65

link-state routing protocols, 271–272

LLQ, 453

LMI (Local Management Interface), Frame

Relay, 123

**load metric parameters (routing protocols),
277**

**local-area networks (LANs). See LANs
(local-area networks)**

local loops, voice architectures, 425–426

local preference attribute (BGP), 354–355

local trunks, voice architectures, 425–426

loopback addresses, VLSMs, 219

loopback addresses (IPv6), 245

loops

preventing

counting to infinity method, 280

routing protocols, 274–280

split horizon method, 279

*split horizon with poison reverse
method, 279*

triggered updates, 280

voice architecture, 425–426

loop-start signaling, 427

LRE, WANs, 126

LSAs, OSPF, 330–331

LSRs (Label Switch Routers), MPLS, 187

M

MAC (Mandatory Access Control), 87

MAC layer addresses, bridges, 93

management

accounting management, 482

configuration management, 482

fault management, 481–482

performance management, 483

secure management, 394

communications, 394

in-band management, 395

out-of-band management, 394

security management, 484

service levels, 484–485

SLAs, 485

SLM, 486–487

Mandatory Access Control (MAC), 87

man-in-the-middle attacks, 387

mapping layers, multicasting, 364–365

marking, 100

masks, IP subnets, 214

**maximum transmission units (MTUs),
203-204, 207–208**

maximum-paths command, 63

MCUs (Multipoint Control Units), 446

MED attribute (BGP), 356–357

media, LANs

Ethernet, 79, 81

Fast (100 Mbps) Ethernet, 80–82

FDDI, 85–86

Fiber Ethernet, 79–80

Gigabit (1000 Mbps) Ethernet, 82

Media Gateway Control Protocol (MGCP), 444-446

media redundancy, 65-68

meshed networks, 63

Message Digest 5 (MD5) authentication, RIPv2, 297

messages, formats, RIP, 293-299

Metric field (RIPv1 messages), 294

Metric field (RIPv2 messages), 299

metric information (RIPv1), 293

metric information (RIPv2), 297

metric parameters, routing protocols, 274-280

bandwidth parameters, 275-276

cost parameters, 276-277

delay parameters, 277

hop-count parameters, 275

load parameters, 277

MTU parameters, 278

reliability parameters, 278

MCUs (Multipoint Control Units), 446

metrics

EIGRP, 307-309

IGRP, 301-302

IS-IS, 334-335

OSPF, 325

redistribution, 362

MGCP (Media Gateway Control Protocol), 444-446

MIB, SNMP, 469

minimizing downtime, route redundancy, 64

modes, WLANs, 87-88

modules

LANs, server-farm module, 99-101

protocol-dependent modules, EIGRP, 304-305

SAFE, 414-415

modus operandi, 383

monitoring, secure monitoring, 393

MPLS (Multiprotocol Label Switching), 191

VPNs, 186

labels, 187

LSRs, 187

routers, 188-189

WANs, 127-128

MPPC, 146

MPPE (Microsoft Point-to-Point Encryption), 191

tunneling, 181

MPPP (Multilink Point-to-Point Protocol), 66

MTU metric parameters (routing protocols), 278

MTUs (maximum transmission units), 203-204, 207-208

multicast addresses, 244, 247, 363-364

multicast traffic, LANs, 102-104

multicasting

dense routing protocols, 368

DVMRP, 370

layer mapping, 364-365

PIM, 369

PIM-SM, 369-370

shared trees, 368

source trees, 368

sparse routing protocols, 368

Multilink Point-to-Point Protocol (MPPP), 66

Multipoint Control Units (MCUs), 446

Multiprotocol Label Switching (MPLS). *See*

MPLS (Multiprotocol Label Switching)

N

name resolution

IPv4, 221-224

IPv6, 250

NAT (Network Address Translation), 199, 208, 211-213, 225

IPv4, 212-213

types, 212

neighborhood database, EIGRP, 305

neighbors (BGP), 348–349

eBGP, 349–350

iBGP, 350–351

NET, configuring, OSPF, 335–336

Network Address Translation (NAT). See NAT

network availability, 68

network command, 359

network design methodology, 25

network documentation, 29

design requirements, 30

executive summary, 30

summary and appendixes, 31–32

network documentation, design solution, 30

PDIOO

design, 27–28

implementation, 28

operability, 28–29

optimization, 29

planning, 26–27

prototypes, 32

creating, 33–34

network documentation, 29

design requirements, 30

design solution, 30

executive summary, 30

summary and appendixes, 31–32

Network Engineers, prototype demonstration

roles, 37

network layer (OSI Layer 3), 585

network node manager (NNM), 466

network reconnaissance, 385

network-management server (NMS), 466

networks

design, 9

economic constraints, 15

labor constraints, 14

political constraints, 15

technological constraints, 14

top-down network design, 11–14

infrastructure, 9

New FOIRL, 80

Next header field (IPv6 headers), 241

next-hop attributes (BGP), 354

Next hop field (RIPv2 messages), 299

NMS (network-management server), 466

NNM (network node manager), 466

Novell routing protocols, 96

NSAP addresses (IPv6), 246

numeric conversion, 588

binary numbers, 592–598

hexadecimal numbers, 589–592

O

ODR routing protocols, 281–282

Old FOIRL, 80

organizational network policies, 9–11

organizational network procedures, 9–11

origin attribute (BGP), 355

OSI (Open Systems Interconnection), 583

introduction of, 583–584

layers

application layer (OSI Layer 7), 587

data link layer (OSI Layer 2), 584–585

network layer (OSI Layer 3), 585

physical layer (OSI Layer 1), 584

presentation layer (OSI Layer 6), 587

session layer (OSI Layer 5), 586

transport layer (OSI Layer 4), 586

Telnet, 587–588

OSPF (Open Shortest Path First) protocol,

321, 325

adjacencies, 326–327

areas, 327–328

stub areas, 331–332

costs, 326

design, 325

DRs, 329–330

- Hello packets, 326
- LSAs, 330–331
- metrics, 325
- NET, configuring, 335–336
- redistribution, 362–363
- routers, 328–329
 - authentication*, 333
- virtual links, 333

OSPFv3 for IPv6, 252

out-of-band management, 394

overlapping, 212

overloading, 212

P

packet sniffing, 386–387

packets, EIGRP, 309

packet-switched network designs, 165

packet-switched WANs, 117–118

Padding field (IPv4 headers), 205

partial mesh networks, 63

partial mesh networks, redundancies, 64

partial-mesh topologies, 165

password attacks, 389

path attributes (BGP), 354

Payload length field (IPv6 headers), 241

PBR (policy-based routing), 345, 360

**PBX (Private Branch Exchange),
421, 432–433**

**PDIOO (planning, design, implementation,
operation, optimization), 26, 39**

- design, 27–28

- implementation, 28

- operability, 28–29

- optimization, 29

- planning, 26–27

performance management, 483

perimeter security, ecosystems, 415

permanent secondary WAN links, 161

physical layer (OSI Layer 1), 584

PIM, 369

PIM-SM, 369–370

pinhole congestion, 63

planning prototypes, 36–37

**planning, design, implementation, operation,
and optimization (PDIOO). See PDIOO
(planning, design, implementation,
operation, and optimization)**

**Point-to-Point Tunneling Protocol (PPTP).
See PPTP (Point-to-Point Tunneling
Protocol)**

policies

- distribution layer, hierarchical LAN

- topologies, 51

- organizational network policies, 9–11

policing WAN traffic, 148

policy management, ecosystems, 415

policy-based routing (PBR), 345, 360

political constraints, network design, 15

port-redirection attacks, 390

ports, voice architectures, 426–427

**PPTP (Point-to-Point Tunneling Protocol),
191**

- tunneling, 181

PQ (Priority Queuing), 147, 452

PQ-WFQ, 453

practicing prototype demonstrations, 38

prefixes, addresses, IPv6, 242–243

presentation layer (OSI Layer 6), 587

PRI ISDNs, 121

Priority Queuing (PQ), 147, 452

private addresses, 208, 210–212

- IPv4, 211

**Private Branch Exchange (PBX),
421, 432–433**

**privately owned WANs, cost considerations,
144**

**procedures, organizational network
procedures, 9–11**

process switching, load balancing, 63

Project Manager, prototype demonstration roles, 37

Protocol field (IPv4 headers), 204

protocol translation mechanisms, IPv6, 255

protocol-dependent modules, EIGRP, 304–305

protocols, routing, 96, 265

- administrative distance, 273–274
- characteristics, 268–269
- classless protocols, 272–273
- distance-vector protocols, 272
- distance-vector routing protocols, 271
- EGPs, 270
- EIGRP, 271
- flat protocols, 272
- hierarchical protocols, 272
- IGPs (interior gateway protocols), 270
- link-state protocols, 272
- link-state routing protocols, 271–272
- loops, 274–280
- metric parameters, 274–280
- ODR, 281–282

prototypes, 32

- building, 34, 41
 - competition considerations, 36*
 - customer requirements, 34–35*
 - equipment preparation, 38*
 - planning, 36–37*
 - practicing demonstrations, 38*
 - sizing, 35*
- design methodology, 32
 - creating, 33–34*

provisioning backup links, 65

proxy ARP, workstation-to-router redundancy, 61

PSTN (Public Switched Telephone Network), 421, 425, 431–432, 434

- ACD routes, 435
- centrex services, 434

database services, 434

IVR systems, 434

voicemail, 434

public topologies, 246

Q

QoS (quality of service)

- distribution layer, hierarchical LAN topologies, 51
- LANs, 100–102
- VoIP, 451
 - CRTP, 451*
 - LFI, 451–452*
 - LLQ, 453*
 - PQ, 452*
 - PQ-WFQ, 453*
 - WFQ, 452*

query packets (EIGRP), 309

queuing services, WANs, 147–148

R

RDP, workstation-to-router redundancy, 61

Real-Time Streaming Protocol (RTSP), 447

redistribute command, 359

redistribution

- BGP routes, 360–361
- default metrics, 362
- EIGRP, 362–363
- IGPs, 361
- IGRP, 362
- OSPF, 362–363

redistribution command, 362

redundancy

- backup links, 65
- LAN topologies, 60, 66
 - media, 65–66*
 - route redundancy, 62,–64*

- server redundancy*, 62
 - workstation-to-router redundancy*, 60
- Regional Internet Registries (RIRs)**, 209
- reliability, WANs**, 142–143
- reliability metric parameters (routing protocols)**, 278
- remote access WANs**, 164–165
 - full-mesh topologies, 166–167
 - packet-switched network designs, 165
 - partial-mesh topologies, 165
- remote LANs**, 106
- Remote Monitoring Protocol (RMON)**. *See* RMON, 463
- repeaters**, 92, 105
 - 100BaseT, 82
 - LANs, 92–93
- Reply packets (EIGRP)**, 309
- requirements, prototypes**, 34–35
- response times, WANs**, 140
- return on investment (ROI) issues, prototypes**, 35
- Return on Investment (ROI)**, 15
- RFCs, SNMP**, 470
- RIPng for IPv6**, 252
- RIPv1 (Routing Information Protocol Version 1)**, 289, 292
 - design, 296
 - forwarding information, 292–293
 - message formats, 293–294
 - timers, 294
 - flush timers*, 295
 - holddown timers*, 295
 - invalid timers*, 295
 - update timers*, 295
 - UDP (User Datagram Protocol), 293
 - workstation-to-router redundancy, 61
- RIPv2 (Routing Information Protocol Version 2)**, 297
 - authentication, 297
 - design, 299
 - forwarding information, 297
 - message format, 298–299
 - timers, 299
- RIRs (Regional Internet Registries)**, 209
- RMON (Remote Monitoring Protocol)**, 463
 - CDP, 472
- ROI (Return on Investment)**, 15
- root bridges**, 94
- round-trip collision delay, Fast (100 Mbps) Ethernet**, 80
- route assignments**, 268–269
- route redundancy**, 62, 64, 68
- route reflectors (BGP)**, 350–352
- route summarization, hierarchical LAN topologies**, 49
- Route tag field (RIPv2 messages)**, 298
- routed hierarchical network model**, 53
- routers**, 95–96, 105
 - default routers, 61
 - hops, diameter, 50
 - LANs, 95–96
 - MPLS routers, 188–189
 - OSPF, 328–329
 - authentication*, 333
 - redistribution, BGP, 360–361
- Routing Information Protocol Version 1 (RIPv1)**. *See* RIPv1 (Routing Information Protocol Version 1)
- Routing Information Protocol Version 2 (RIPv2)**. *See* RIPv2 (Routing Information Protocol Version 2)
- routing protocols**, 96, 265
 - administrative distance, 273–274
 - characteristics, 268–269
 - classful protocols, 272–273
 - classless protocols, 272–273
 - distance-vector routing protocols, 271–272
 - EGPs, 270
 - EIGRP, 271
 - flat routing protocols, 272

- hierarchical routing protocols, 272
- IGPs (interior gateway protocols), 270
- IPv6, 252–253
- link-state routing protocols, 271–272
- loops, preventing, 274–280
- metric parameters, 274–280
 - bandwidth parameters*, 275–276
 - cost parameters*, 276–277
 - delay parameters*, 277
 - hop-count parameters*, 275
 - load parameters*, 277
 - MTU parameters*, 278
 - reliability parameters*, 278
- ODR, 281–282
- RTCP, 444–445**
- RTP, 444–445**
 - EIGRP, 305
- RTSP (Real-Time Streaming Protocol), 447**

S

- SAFE, 379, 405, 410–411**
 - areas, 414–415
 - attacks
 - application-layer attacks*, 392
 - DoS*, 388
 - man-in-the-middle attacks*, 387
 - password attacks*, 389
 - port-redirection attacks*, 390
 - trust exploitation*, 390
 - unauthorized access attacks*, 391
 - blueprint, 409–410
 - designing*, 412–414
 - customer expectations, defining, 411
 - IP spoofing, 388
 - modules, 414–415
 - network reconnaissance, 385
 - packet sniffing, 386–387

- secure management, 394
 - communications*, 394
 - in-band management*, 395
 - out-of-band management*, 394
- secure monitoring, 393
- security ecosystems, 415
 - connectivity*, 415
 - identity*, 415
 - perimeter security*, 415
 - policy management*, 415
 - security monitoring*, 415
- threats, 383–385
- trojan-horse applications, 392
- viruses, 392

- SAFE WLANs, 90**
- SAP (Session Announcement Protocol), 447**
- scope, prototypes, 35**
- SCP (Signaling Control Point), 430**
- scripts, prototype demonstrations, 37**
- SDH (Synchronous Digital Hierarchy), 167**
- SDP (Session Description Protocol), 447**
- SDSL, 178**
- secondary WAN links, 161**
- secure management**
 - communications, 394
 - in-band management, 395
 - out-of-band management, 394
- secure monitoring, 393–394**
- security**
 - attacks
 - application-layer attacks*, 392
 - DoS*, 388
 - man-in-the-middle attacks*, 387
 - password attacks*, 389
 - port-redirection attacks*, 390
 - trojan-horse applications*, 392
 - trust exploitation*, 390
 - unauthorized access attacks*, 391
 - viruses*, 392

- IP spoofing, 388
- IPv6, 252
- network reconnaissance, 385
- packet sniffing, 386–387
- SAFE, 410–411
 - areas*, 414–415
 - blueprint*, 409–410
 - customer expectations*, 411
 - designing*, 412–414
 - modules*, 414–415
 - threats*, 383–385
- secure management, 394
 - communications*, 394
 - in-band management*, 395
 - out-of-band management*, 394
- secure monitoring, 393
- WLANs, 89
- security management, 484**
- security monitoring, ecosystems, 415**
- self assessment, goals of, 45**
- Server Load Balancing (SLB), 100**
- server redundancy, 62, 68**
- server-farm module, LANs, 99–101**
- service levels**
 - Internet access and connectivity, 484–485
 - SLAs, 485
 - SLM, 486–487
- Service Set Identifier (SSID), 87**
- Session Announcement Protocol (SAP), 447**
- Session Description Protocol (SDP), 447**
- session layer (OSI Layer 5), 586**
- shadow PVCs, 161**
- shaping WAN traffic, 148**
- shared WANs, cost considerations, 144**
- show command, 481**
- show ip bgp 200.50.32.0 command, 356**
- show ip rip database command, 293**
- signaling, voice architectures, 427–431**
- Signaling Control Point (SCP), 430**
- Signaling Switching Point (SSP), 430**
- Signaling System 7 (SS7), 425**
- Signaling Transfer Point (STP), 430**
- Simple Network Management Protocol (SNMP). See SNMP (Simple Network Management Protocol)**
- single-site deployment model, AVVID, 440–441**
- SIP, 444, 447**
- site-local addresses (IPv6), 247**
- sizing prototypes, 35**
- Skinny Station Control Protocol (SSCP), 444**
- SLA service levels, 485**
- SLB (Server Load Balancing), 100**
- SLM service levels, 486–487**
- small office/home office (SOHO), access layer, hierarchical LAN topologies, 52**
- small/remote LANs, 106**
- SMDS, WANs, 123–124**
- SNCI (Strategic Networks Consulting, Inc.) , 36**
- SNCI website, 36**
- SNMP (Simple Network Management Protocol), 463, 469**
 - commands, 470
 - components, 469
 - design, 470
 - evolution of, 470–471
 - MIB, 469
 - RFCs, 470
- snooping, IGMP, 367**
- software queues, WANs, 147**
- SOHO (small office/home office), access layer, hierarchical LAN topologies, 52**
- SONET (Synchronous Optical Network), 167**
- SONET/SDH, 167**
- Sound Masters, Inc. case study, 505–509**
- Source address field (IPv4 headers), 205**
- Source address field (IPv6 headers), 241**
- source trees, multicasting, 368**
- SP (service provider) Edge modules, 60**

SP Edge, 67
Spanning Tree Protocol, 94
 bridges, 93
 switches, 95
sparse routing protocols, multicasting, 368
split horizon method, loop prevention, 279
split horizon with poison reverse method, loop prevention, 279
spoofing, IP spoofing, 388
SS7 (Signaling System 7), 425, 429-430
SSCP (Skinny Station Control Protocol), 444-445
SSID (Service Set Identifier), 87
SSP (Signaling Switching Point), 430
static IP address assignments, 221
Static NAT, 212
static route assignments, dynamic route assignments, compared, 268-269
static routes, floating static routes, 65
STP (Signaling Transfer Point), 430
Strategic Networks Consulting, Inc. (SNCI) switch test, 36
stub areas, OSPF, 331-332
Subnet mask field (RIPv2 messages), 298
subnets, IPv4, 213-214
 design, 215
 masks, 214
 network portion determination, 216
successor paths, 306
summarization, hierarchical LAN topologies, 49
summary (network design documentation), 31
Super Consulting case study, 503-505
switched hierarchical network model, 53
switched networks, media redundancy, 65
switches, 94-95, 105
 Layer 3 switches, 96
 PBX switches, 432-433
 voice switches, 426

switching modes, load balancing, 63
Synchronous Digital Hierarchy (SDH), 167
Synchronous Optical Network (SONET), 167

T

T1/E1 CAS, 429
tagging, 100
TCP window size, WANs, 146-147
TCP/IP, routing protocols, 96
technical factors, WAN design, 143
technological constraints, network design, 14
Telnet, 587-588
terminals, 446
testing prototypes, 32, 34, 41
 competition considerations, 36
 customer requirements, 34-35
 equipment preparation, 38
 planning, 36-37
 practicing demonstrations, 38
 sizing, 35
TFTP, 444
threats, SAFE, 383-385
throughput, WANs, 141
Time to live field (IPv4 headers), 204
timer information (RIPv1), 293
timer information (RIPv2), 297
timers
 EIGRP, 306-307
 IGRP, 300
 RIPv1 timers, 294
 flush timers, 295
 holddown timers, 295
 invalid timers, 295
 update timers, 295
 RIPv2, 299
Token Ring, LANs, design rules, 85
tools
 audit tools, 16

- traffic analysis tools, 16
- traffic simulation tools, 17
- top-down network design, 11–14**
- topologies**
 - full-mesh topologies, 166–167
 - LANs (local-area networks)
 - campus*, 97–99
 - hierarchical models*, 48, 52
 - large building*, 97–98
 - redundant models*, 60, 66
 - small/remote site*, 97–99
 - partial-mesh topologies, 165
- ToS, 205–207, 227**
- ToS field (IPv4 headers), 204–207**
- Total length field (IPv4 headers), 204**
- traffic**
 - WANs
 - policing*, 148
 - shaping*, 148
 - workstation-to-router redundancy, 60–62
- traffic analysis tools, 16**
- Traffic class field (IPv6 headers), 241**
- traffic simulation tools, 17**
- transition strategies, IPv4 to IPv6, 253–255**
- transport layer (OSI Layer 4), 586**
- triggered updates, loop prevention, 280**
- Triple DES (3DES). See 3DES**
- trojan-horse applications, 392**
- trunks, voice architecture, 425–426**
- trust exploitation, 390**
- tunneling**
 - GRE, 181
 - IPSec, 182
 - 3DES*, 185
 - AH (Authentication Header)*, 183
 - connections*, 183
 - DES*, 185
 - Diffie-Hellman method*, 185
 - ESP*, 184
 - HMACs*, 185

- MPPE, 181
- PPTP, 181
- VPDN, 181–182
- tunnels, VPNs, 180–189**

U-V

- UDP (User Datagram Protocol), 293**
- unauthorized access attacks, 391**
- unicast addresses (IPv6), 244**
- UNII (Unlicensed National Information Infrastructure), 89–91**
- unspecified addresses (IPv6), 245**
- Update packets (EIGRP), 309**
- update timers, RIPv1, 295**
- VAD, 448**
- Van Jacobson Header Compression for TCP/IP, 146**
- variance, 63**
- VDSL, 179–180**
- Version field (IPv4 headers), 204**
- Version field (IPv6 headers), 241**
- version field (RIPv1 messages), 294**
- Version field (RIPv2 messages), 298**
- virtual links, OSPF, 333**
- Virtual Private Dial-Up Networks (VPDNs), 191**
- virtual private networks (VPNs), 173**
- VLSMs, 199, 215–218, 225**
 - address-assignments, 217
 - loopback addresses, 219
- VoATM (Voice over ATM), 436–437**
- VoFR (Voice over Frame Relay), 435–436**
- voice architectures**
 - design, 448–451
 - erlangs, 433
 - grade of service, 432
 - integrated multiservice networks, 435
 - AVVID*, 439–444, 456

- VoATM (Voice over ATM)*, 436–437
- VoFR (Voice over Frame Relay)*, 435–436
- VoIP (Voice over IP)*, 437–438
- local loops, 425–426
- ports, 426–427
- signaling types, 427–431
- Voice over IP (VoIP)**. *See* **VoIP**
- voice switches**, 426
- voicemail, PSTN**, 434
- VoIP (Voice over IP)**, 437–438
 - AVVID, 444–451
 - QoS (quality of service), 451
 - CRTP*, 451
 - LFI*, 451–452
 - LLQ*, 453
 - PQ*, 452
 - PQ-WFQ*, 453
 - WFQ*, 452
- VPDNs (Virtual Private Dial-Up Networks)**, 191
 - tunneling, 181–182
- VPN/remote access module (Enterprise Edge)**, 58–59
- VPNs (virtual private networks)**, 173, 176, 180
 - MPLS, 186
 - labels*, 187
 - LSRs*, 187
 - routers*, 188–189
 - tunnels, 180
 - creating*, 181–189
- W**
- WAN module (Enterprise Edge)**, 59
- WANs**, 111, 115–116, 130
 - analyzing, 139
 - ATM, 124
 - cells*, 124
 - connections*, 125
 - cable, 126
 - cell-switching WANs, 118
 - characterizing, 139
 - circuit-switched WANs, 117
 - data compression, 145–146
 - designing, 139
 - application factors*, 140–143
 - cost factors*, 144–145
 - technical factors*, 143
 - dial-up, 119
 - DSL, 125–126
 - Enterprise Composite Network model, 118–119
 - Frame Relay, 122
 - DE (Discard Eligibility)*, 122
 - LMI (Local Management Interface)*, 123
 - ISDNs, 119–121
 - LANs, compared, 116
 - leased WANs, cost considerations, 144
 - leased-line WANs, 116–117
 - LRE, 126
 - MPLS, 127–128
 - packet-switched WANs, 117–118
 - privately owned WANs, cost considerations, 144
 - queuing services, 147–148
 - reliability, 142–143
 - remote access, 164–165
 - full-mesh topologies*, 166–167
 - packet-switched network designs*, 165
 - partial-mesh topologies*, 165
 - response times, 140
 - shared WANs, cost considerations, 144
 - SMDS, 123–124
 - TCP window size, 146–147
 - throughput, 141
 - traffic
 - policing*, 148
 - shaping*, 148

wireless, 127

X.25 protocol, 121–122

WECA (Wireless Ethernet Compatibility Alliance), 86

weight attribute (BGP), 357–358

WFQ (weighted fair queuing) keys, 89-90, 452

(weighted fair queuing), 147

Wi-Fi (Wireless Fidelity), 86

Wink protocol, 429

wireless WANs, 127

wiring, 85–86

WLANs (wireless LANs), 86–91

APs (access points), 87

design rules, 86–91

frequencies, 88

MAC (Mandatory Access Control), 87

modes, 87–88

SAFE WLANs, 90

security, 89

SSID (Service Set Identifier), 87

workstation-to-router redundancy, 60, 68

X

X.25 Payload Compression of Encapsulated Traffic, 146

X.25 protocol, WANs, 121–122