

# Index

---

## Numerics

- 7200 Series routers, 15
- 800 Series routers, 11
- 8-N-1 connections, 91

## A

### AAA (authentication, authorization, and auditing), 36

- access control management, 400–401
- configuring
  - access modes/interfaces*, 404
  - enabling*, 407–418
- CS-ACS, 405–407
- protocols, 402
  - RADIUS*, 403
  - TACACS*, 402–403
- servers, 404

### AA5 (ATM adaptation layer), 255

#### access

- cable, WAN, 17
- control, 400–401
- DSLAM, 246
- modes, AAA, 404
- remote
  - Cisco 1700 Series*, 12
  - Cisco 2500 Series*, 13
  - Cisco 2600 Series*, 13
  - Cisco 3600 Series*, 13–15
  - VPN 3000 Concentrator Series*, 15
  - WAN*, 37–40
- requirements, 35
- TACACS, 402
- WAN, wireless, 18

### Access Server lines, Cisco AS5000 Series router, 58–60

### access-group command, 443

### accountability, NAT, 366

### accounting. *See also* AAA

- commands, 416
- security, 401

### adaptation, rate, 168

### adaptive-shaping becn command, 303

### additional information, defining interfaces, 164–168

### Address field, PPP, 117

#### addresses

- definitions, 373
- IP
  - characteristics of NAT*, 366–373
  - scaling with NAT*, 361
- ISDN parameters, 162–164
- NAT, 372
- substitute, 368

### administrative distances, 321

### ADSL (asymmetric DSL), 245–250

#### aggregation

- BoD, 178
- Multilink PPP, 179

#### algorithms

- encryption, 431–433
  - Diffie-Hellman key exchange*, 434–435
  - ESP*, 436
  - hashing*, 433
  - transport/tunnel modes*, 436–439
- Van Jacobson, 350

### analog calls, PRI incoming on digital modems, 202–203

### analog modems, 40

### ANSI LMIs, 278

### applications, 34

#### architecture

- PPP, 115
- PPPoE, 252–255

---

## arguments

- how-to-track, 417
- rotary, 379
- stop-only, 418
- wait-start, 417

## assemblies

- connections, 66–68
- T1 framing, 196

## asymmetric DSL (ADSL), 245–250

## async dynamic address command, 118

## async mode interactive command, 97

## asynchronous configuration, 94

## asynchronous dialup (analog modems), 40

## asynchronous ports, 68

## Asynchronous Transfer Mode (ATM), 37

## AT commands, 98–99

## ATM (Asynchronous Transfer Mode), 37

- encapsulation, 255

- PPPoE, 255. *See also* PPPoE

## ATM adaptation layer 5 (AAL5), 255

## authentication, 401. *See also* AAA

- commands, 409
  - aaa authentication arap command, 411*
  - aaa authentication nasi command, 413*
  - aaa authentication ppp command, 412*

- LCP, 130

- LEAP, 236

- MAC, 236

- PAP, 119–122

- PPP, 119

  - CHAP, 120–122*

  - PAP, 119*

- RADIUS, 402

- wireless networks, 236

## authentication, authorization, and accounting. *See* AAA

## authorization, aaa authorization command, 414

## authorization, 401. *See also* AAA

## autoconfiguration, modems, 99–100

## availability, of services, 33

# B

## B channels, 39, 178

## back office services, 222

## backups, 35

- delay 5 60 command, 319

- dial, 318–320

  - primary link failures, 318–319*

  - primary link overload, 319*

## Backward Explicit Congestion Notification (BECN), 300–301

## bandwidth

- connections. *See* connections
- equipment selection, 32
- Multilink PPP, 179

## bandwidth 38 command, 96

## Bandwidth on Demand (BoD), 34, 178

## Bandwidth Reservation Protocol (BRP), 20

## Basic Rate Interface (BRI), 39, 146–162

## Be (excessive burst), 300

## bearer channel, 146

## BECN (Backward Explicit Congestion Notification), 300, 301

## BoD (Bandwidth on Demand), 34, 178

## BRI (Basic Rate Interface), 39, 146–162

## bridges, PPPoE, 252–255

## broadband connections, 220–224

- cable options, 221

- CM initialization, 224–229

- type of orbits, 230

## BRP (Bandwidth Reservation Protocol), 20

**C****cable modem (CM), 39, 222**

- broadband implementations, 221
- connection options, 68
- initialization, 224–229
- WAN, 17

**cable modem termination system (CMTS), 222****cables, 66–68, 146****call termination, 90****callback**

- LCP, 131
- PPP Callback configuration, 132
- PPP Callback option, 131

**CAP (Carrierless Amplitude Phase), 248****cast type (subinterfaces), 282****CBWFQ (Class-Based Weighted Fair Queuing), 332, 338–339**

- class-map command, 339–341
- link compression, 348
- LLQ verification, 345–347
- payload compression, 349
- policy-map command, 345
- service-policy command, 341–345
- TCP header compression, 350–351

**central-site installations, 18, 29–30****central-site routers, selection of, 56–61****channels, BRI, 146–162****CHAP (Challenge Handshake Access Protocol), 120, 122****character-based access modes, 404****characteristics of Frame Relay, configuring, 285, 286, 287****chat scripts, 101–103****CIR (committed information rate), 38****Cisco 1700 Series router, 12, 62****Cisco 2500 Series router, 13, 63****Cisco 2600 Series router, 13, 64****Cisco 3600 Series router, 13–15, 57–58****Cisco 700 Series routers, PAT (Port Address Translation), 382–384****Cisco 7200 Series router, 60****Cisco 800 Series router, 65****Cisco Aironet 1200 WAP, 234****Cisco AS5000 Series router, 58–60****Cisco LMIs, 276****Cisco Local Director, 371****Cisco Router Web Setup (CRWS), 257****Cisco Secure Access Control Server (CS-ACS), 405–407****class command, 304****Class-Based Weighted Fair Queuing (CBWFQ), 332, 338–339**

- class-map command, 339–341
- link compression, 348
- LLQ verification, 345–347
- payload compression, 349
- policy-map command, 345
- service-policy command, 341–345
- TCP header compression, 350–351

**classification, QoS, 20****clearing, NAT translation, 382****clients, VPNs, 41****CM (cable modem), 39, 222**

- broadband implementations, 221
- connection options, 68
- initialization, 224–229
- WAN, 17

**CMTS (cable modem termination system), 222****coexistence, POTS DSL, 247****commands**

- access-group, 443
- adaptive-shaping, 303
- async dynamic address, 118
- async mode interactive, 97
- authentication, 409
  - aaa authentication arap, 411*
  - aaa authentication nasi, 413*
  - aaa authentication ppp, 412*
- authorization, 414
- backup delay 5 60, 319
- bandwidth 38, 96
- class, 304
- class-map, 339–341
- controller t1 0/0, 201
- debug, 135
  - debug atm events, 263*
  - debug dialer, 206*
  - debug frame-relay lmi, 288*
  - debug ip nat, 381*
  - debug isdn q921, 207*
  - debug isdn q931, 155, 208*
  - debug ppp multilink, 206*

- dialer
  - dialer callback-secure*, 132
  - dialer hold-queue*, 133
  - dialer idle-timeout*, 164
  - dialer load-threshold*, 134, 179
- encapsulation ppp, 96
- flowcontrol hardware, 98
- frame-relay
  - frame-relay adaptive-shaping becn*, 303
  - frame-relay bc*, 303
  - frame-relay be*, 304
  - frame-relay minicir*, 304
  - frame-relay traffic-shaping*, 300
- interface serial 0.1, 284
- ip
  - ip nat inside*, 375
  - ip nat outside*, 375
  - ip porthandler*, 383
  - ip tcp header-compression passive*, 96
  - ip unnumbered*, 118
  - ip unnumbered Ethernet0*, 96
- IPX routing, 164
- isdn incoming-voice modem, 202
- login local, 98
- map-class, 303
- modem
  - modem autoconfigure*, 100
  - modem InOut*, 98
- no cdp enable, 97
- peer default ip address pool remaddpool, 97
- physical-layer async, 95–96
- policy-map, 345
- PPP
  - ppp authentication chap*, 97
  - ppp callback accept*, 132
  - ppp callback request*, 132
  - ppp context*, 117
  - ppp multilink*, 134
- queuing, 353
- service-policy, 341–345
- set ip pat on, 383
- show, 69
  - show atm interface 0*, 263
  - show cable modem*, 224
  - show controller t1*, 198
  - show dialer*, 134, 205
  - show frame-relay lmi*, 289
  - show frame-relay map*, 291
  - show frame-relay pvc*, 286, 302, 305
  - show interface atm 0*, 262
  - show interfaces ethernet*, 69
  - show interfaces serial*, 72–74
  - show ip nat statistics*, 381
  - show ip nat translation*, 380
  - show isdn status*, 153, 200, 204
  - show line*, 92, 94
  - show modemcap*, 100
  - show ppp multilink*, 204
  - show traffic-shape*, 306
- start-chap, 102
- variance 4, 320
- committed information rate (CIR)**, 38
- company sites, requirements**, 18
- components, PPP**, 116
- compression**, 20
  - LCP, 131
  - link, 348
  - payloads, 349
  - PPP, 133
  - TCP header, 350–351
- configuration**
  - AAA
    - access modes/interfaces*, 404
    - enabling*, 407–418
  - access
    - cable*, WAN, 17
    - control*, 400–401
    - DSLAM*, 246
    - modes*, AAA, 404
    - remote*, 12–15, 37–40
    - requirements*, 35
    - TACACS*, 402
    - WAN*, wireless, 18
  - addresses
    - definitions*, 373
    - IP*, 361, 366–373
    - ISDN parameters*, 162–164
    - NAT*, 372
    - substitute*, 368
  - autoconfiguration, 99
  - basic asynchronous, 94
  - cable modem (CM)

- broadband implementations*, 221
- connection options*, 68
- initialization*, 224–229
- CBWFQ, 332, 338–339
  - class-map command*, 339–341
  - link compression*, 348
  - LLQ verification*, 345–347
  - payload compression*, 349
  - policy-map command*, 345
  - service-policy command*, 341–345
  - TCP header compression*, 350–351
  - WAN, 17
- CRWS, 257
- DDR, 178
  - dialer profiles*, 181–184
  - ML-PPP*, 180
  - optimizing*, 178–180
  - rotary groups*, 184–185
  - snapshot routing*, 185–187
- DSL
  - ADSL*, 248–250
  - CAP modulation*, 248
  - Cisco 827 Series routers*, 256–260
  - connection options*, 68
  - DMT*, 249
  - limitations of*, 247
  - overview of*, 245–246
  - PPPoE*, 225. *See also* PPPoE
  - POTS coexistence*, 247
  - SDSL*, 251–252
  - troubleshooting*, 260–265
- dial backup, 319
- Frame Relay, 283–292
  - characteristics*, 285, 286, 287
  - encapsulation*, 284
  - interface selection*, 284
  - protocol-specific parameters*, 285
  - subinterfaces*, 283
  - traffic shaping*, 303–307
  - verifying*, 287, 288, 289
- IPSec, 439–447
- layers, 200
- modems (AT commands), 98–99
- NAT, 259, 373–384
- PPP callback, 132
- PRI, 194–202
- congestion**
  - BECN, 300
  - FECN, 301
- connections, 232. *See also* networks**
  - 8-N-1, 91
  - analog modems, 40
  - assembling, 66–68
  - asynchronous configuration, 94
  - BoD, 178
  - broadband, 220–224
    - CM initialization*, 224–229
    - type of orbits*, 230
  - cable modems, 39, 222
    - broadband implementations*, 221
    - connection options*, 68
    - initialization*, 224–229
    - WAN, 17
  - DDR, 34
    - configuring*, 178
    - dialer profiles*, 181–184
    - ML-PPP*, 180
    - optimizing*, 178–180
  - DLCI, 38
  - DSL, 39, 245–246
    - Cisco 827 Series routers*, 256–260
    - troubleshooting*, 260–265
  - ISDN
    - BRI*, 146
    - E1 framing (PRI)*, 199
    - installing PRI*, 194–195
    - Layer 2*, 151
    - Layer 3*, 153
    - layers (PRI)*, 200
    - PRI*, 194
    - T1 framing (PRI)*, 195–198
    - troubleshooting Multilink PPP*, 204–208
  - modems, 88–90
  - Multilink PPP, 179
  - PPP, components, 116
  - reverse Telnet, 90–91
  - security, technology assessment, 40–42
  - UTP, 146
  - WAN, 16–18. *See also* WAN
- conservation, NAT, 367**
- Control field, PPP, 117**
- controller t1 0/0 command, 201**
- cost of services, 34**
- CQ (custom queuing), 300**
- CRWS (Cisco Router Web Setup), 257**
- crypto maps, 443**

## CS-ACS (Cisco Secure Access Control Server), 405–407

### customization

#### AAA

*access modes/interfaces, 404*  
*enabling, 407–418*

#### access

*cable, WAN, 17*  
*control, 400–401*  
*DSLAM, 246*  
*modes, AAA, 404*  
*remote, 12–15, 37–40*  
*requirements, 35*  
*TACACS, 402*  
*WAN, wireless, 18*

#### addresses

*definitions, 373*  
*IP, 361, 366–373*  
*ISDN parameters, 162–164*  
*NAT, 372*  
*substitute, 368*

#### autoconfiguration, 99

#### basic asynchronous, 94

#### cable modem (CM)

*broadband implementations, 221*  
*connection options, 68*  
*initialization, 224–229*

#### CBWFQ, 332, 338–339

*class-map command, 339–341*  
*link compression, 348*  
*LLQ verification, 345–347*  
*payload compression, 349*  
*policy-map command, 345*  
*service-policy command, 341–345*  
*TCP header compression, 350–351*  
*WAN, 17*

#### CRWS, 257

#### DDR, 178

*dialer profiles, 181–184*  
*ML-PPP, 180*  
*optimizing, 178–180*  
*rotary groups, 184–185*  
*snapshot routing, 185–187*

#### DSL

*ADSL, 248–250*  
*CAP modulation, 248*  
*Cisco 827 Series routers, 256–260*  
*connection options, 68*  
*DMT, 249*

*limitations of, 247*

*overview of, 245–246*

*PPPoE, 225. See also PPPoE*

*POTS coexistence, 247*

*SDSL, 251–252*

*troubleshooting, 260–265*

#### dial backup, 319

#### Frame Relay, 283–292

*characteristics, 285, 286, 287*  
*encapsulation, 284*  
*interface selection, 284*  
*protocol-specific parameters, 285*  
*subinterfaces, 283*  
*traffic shaping, 303–307*  
*verifying, 287, 288, 289*

#### IPSec, 439–447

#### layers, 200

#### modems (AT commands), 98–99

#### NAT, 259, 373–384

#### PPP callback, 132

#### PRI, 194–202

### custom queuing (CQ), 300

## D

### D channel, 146

### D4 framing (SuperFrame), 196

### Data Link layers, troubleshooting, 262

### Data Over Cable Service Interface Specification (DOCSIS), 221

### data traffic, splitting, 246

### databases

*modemcap, 100–101*

*RDBMS, 401*

### data-link connection identifier (DLCI), 38

### DCE (data circuit-terminating equipment), 88, 90, 275

### DDR (dial-on-demand routing), 34

*configuring, 178*

*dialer profiles, 181–184*

*ML-PPP, 180*

*optimizing, 178–180*

*rotary groups, 184–185*

*snapshot routing, 185–187*

### DE (Discard Eligible), 302

### debug atm events command, 263

**debug commands**

- debug dialer command, 206
- debug frame-relay lmi command, 290
- debug ip nat command, 381
- debug isdn q921 command, 207
- debug isdn q931 command, 155, 208
- debug ppp authentication command, 135
- debug ppp multilink command, 206
- debug ppp negotiation, 135

**dedicated sessions, PPP, 117****defining**

- AAA, 401
- interfaces, 162–168

**detection, down conditions, 318****devices, Frame Relay, 278****dial backup, 318–320**

- primary link failures, 318–319
- primary link overload, 319

**dialer commands**

- dialer callback-secure command, 132
- dialer hold-queue command, 133
- dialer idle-timeout command, 164
- dialer load-threshold command, 134, 179
- dialer map statement, 181
- dialer pools, 182
- dialer profiles, 181–182, 184
- dialer-map statement, 131

**dial-on-demand routing (DDR), 34****dial-up connections, 117. *See also* connections****Diffie-Hellman key exchange, 434–435****digital modems, PRI incoming analog calls, 202–203. *See also* connections; modems****Digital Subscriber Line. *See* DSL****dialer profiles, DDR, 181–184****Discard Eligible (DE), 302****discovery**

- modems, 100
- sessions (PPPoE), 253

**Discrete MultiTone (DMT), 248, 249****displaying. *See* viewing****DLCI (data-link connection identifier), 38, 275****DMT (Discrete MultiTone), 248, 249****DOCSIS (Data Over Cable Service Interface Specification), 221****documents, MultiFrame, 199****down condition, detecting, 318****DPT (Dynamic Packet Transfer), 37****DSIR pins, 89****DSL (Digital Subscriber Line), 39, 241**

- ADSL, 248–250
- CAP modulation, 248
- Cisco 827 Series routers, 256–260
- connection options, 68
- DMT, 249
- limitations of, 247
- overview of, 245–246
- PPPoE, 225. *See also* PPPoE
- POTS coexistence, 247
- SDSL, 251–252
- troubleshooting, 260–265

**DSLAM (DASL access multiplexer), 246, 264****DTE (data terminal equipment), 88, 90, 277****DTR pins, 89****duplex values, troubleshooting, 72****Dynamic Packet Transfer (DPT), 37****dynamic redundancy, 320****E****E1 framing, PRI, 199****edge devices, Frame Relay, 278****editing modemcap, 101****EIA/TIA-232, 88****eliminated renumbering, NAT, 367****embedding NAT, 367****enabling AAA, 407–418****Encapsulating Security Payload (ESP), 436****encapsulation**

- ATM, 255
- Frame Relay, configuring, 284
- HDLC, 38
- interfaces, 162–164

**encapsulation ppp command, 96****encryption, 36**

- algorithms, 431–433
- Diffie-Hellman key exchange, 434–435
- ESP, 436
- hashing, 433
- transport/tunnel modes, 436–439

**environments (DDR)**

- configuring, 178
- dialer profiles, 181–184
- optimizing, 178–180
- rotary groups, 184–185
- snapshot routing, 185–187

**equipment selection, 24, 32–36**

- cabling, 66–68

Product Selection Tool, 56  
WAN, 55

*central-site routers*, 56–61

*ROBO*, 62–64

*SOHO*, 65–66

**ESF (Extended SuperFrame)**, 196  
**ESP (Encapsulating Security Payload)**, 436  
**Ethernet, PPPoE**, 252–255  
**excessive burst (Be)**, 300  
**expanding networks**, 400–401  
**Extended SuperFrame (ESF)**, 196

## F

**Fair Queuing**, 334  
**fast-switching paths, Frame Relay traffic shaping**, 300–302  
**FECN (Forward Explicit Congestion Notification)**, 301  
**fields, PPP**, 117  
**first calls**, 151  
**Flag field, PPP**, 117  
**flexibility of NAT**, 367  
**floating static routes**, 321  
**flowcontrol hardware command**, 98  
**formats, frames**, 117  
**Forward Explicit Congestion Notification (FECN)**, 301  
**Frame Relay**, 38  
  commands. *See* frame-relay commands  
  configuring, 283–292  
    *characteristics*, 285, 286, 287  
    *encapsulation*, 284  
    *interface*, 284  
    *protocol-specific parameters*, 285  
    *subinterfaces*, 283  
  connection options, 66  
  DCE, 277  
  devices, 278  
  DLCIs, 277  
  DTE, 277  
  LMI, 278  
  subinterfaces, 282–283  
  topologies, 279  
  traffic shaping, 297, 300–307  
  verifying configuration, 287, 289–290  
    *show frame-relay lmi comm*, 289  
    *show frame-relay map comm*, 291

*show frame-relay pvc comm*, 285

**frame-relay commands**  
  frame-relay adaptive-shaping becn command, 303  
  frame-relay bc command, 303  
  frame-relay be command, 304  
  frame-relay mincir command, 304

**frames**  
  PPP, 117  
  PPPoE, 254

**full-mesh topology, Frame Relay**, 279

**functionality**  
  DDR, 178–180  
  Multilink PPP, 179  
  NAT, 366

## G

**G.lite ADSL**, 250  
**gateway-to-gatekeeper functionality**, 257  
**geostationary orbit (GEO)**, 230  
**global addresses, NAT**, 372  
**guidelines**  
  access, 35  
  for equipment selection, 32–36

## H

**hardware, equipment selection**, 32–36  
**hashing algorithms**, 433  
**HDLC (High-Level Data Link Control)**, 38  
**HDSL (high-data-rate DSL)**, 251  
**HDSL2 (second-generation HDSL)**, 251  
**headers, packets**, 366  
**HFC (hybrid fiber-coaxial) networks**, 224  
**High-Level Data Link Control (HDLC)**, 38  
**highly elliptical orbit (HEO)**, 231  
**how-to-track argument**, 417  
**hub-and-spoke topology, Frame Relay**, 277  
**hybrid fiber-coaxial (HFC) networks**, 224

## I

**IDBs (Interface Descriptor Blocks)**, 282  
**IDSL (ISDN DSL)**, 252  
**IEEE 802.11**, 232  
**IEEE 802.11a**, 232  
**IEEE 802.11b**, 233

**IEEE 802.11g, 233****implementation**

## AAA

*access modes/interfaces, 404*

*enabling, 407–418*

## access

*cable, WAN, 17*

*control, 400–401*

*DSLAM, 246*

*modes, AAA, 404*

*remote, 12–15, 37–40*

*requirements, 35*

*TACACS, 402*

*WAN, wireless, 18*

## addresses

*definitions, 373*

*IP, 361, 366–373*

*ISDN parameters, 162–164*

*NAT, 372*

*substitute, 368*

## autoconfiguration, 99

## basic asynchronous, 94

## cable modem (CM)

*broadband implementations, 221*

*connection options, 68*

*initialization, 224–229*

## CBWFQ, 332, 338–339

*class-map command, 339–341*

*link compression, 348*

## DDR, 178

*dialer profiles, 181–184*

*optimizing, 178–180*

*rotary groups, 184–185*

*snapshot routing, 185–187*

## DSL, SOHO, 246

## QoS, 19

**incoming calls, PRI, 202–203****initializing CM, 224–229****initiating PPPoE, 253****inside global addresses (NAT), 372****inside local addresses (NAT), 372****installation**

*central-site, 29–30*

*equipment selection, 32–36*

*PRI, 194–195*

*E1 framing, 199*

*layers, 200*

*T1 framing, 195–198*

*ROBO, 30–31*

*SOHO, 31–32*

*verifying, 68–74*

**Integrated Service Digital Network, 39****integrity assurance, hashing algorithms, 433****interactive sessions, PPP, 117****interface serial 0.1 command, 284****interfaces**

AAA, 404

BRI, 39, 146–162

dialer, 181

DOCSIS, 221

encapsulation, 162–164

logical configuration, 96–97

passive, 166

per-interface compression, 348

physical, 182–185

PRI, 39, 492. *See also* PRI

status, 70

WIC, 64

**Internal Signalling Utility Protocol (ISUP), 153****Internet Protocol Security (IPSec), 439–447****Internet service provider (ISP), 42****IP (Internet Protocol) addresses**

*characteristics of NAT, 366–373*

*overlapping networks, 370*

*scaling with NAT, 361*

**ip commands**

*ip nat inside command, 375*

*ip nat outside command, 375*

*ip porthandler command, 383*

*ip tcp header-compression passive command, 96*

*ip unnumbered command, 118*

*ip unnumbered Ethernet0 command, 96*

**IPSec (Internet Protocol Security), 439–447****IPX routing command, 164****ISDN (Integrated Service Digital Network), 39**

*addressing parameters, 162–164*

*BRI, 67, 146–162*

*DDR*

*dialer profiles, 181–184*

*ML-PPP, 180*

*rotary groups, 184*

*interfaces, 164–168*

*Layer 2, 151*

*Layer 3, 153*

*Multilink PPP, 204–208*

- PRI, 194
  - configuring*, 200–202
  - E1 framing*, 199
  - incoming calls*, 202–203
  - installing*, 194–195
  - layers*, 200
  - T1 framing*, 195–198

**isdn incoming-voice modem command**, 202  
**ISDN PRI, connection options**, 67  
**ISP (Internet service provider)**, 42  
**ISUP (Internal Signalling Utility Protocol)**, 153

## K

keys, WEP, 235

## L

**LAN (local area network)**, wireless, 233  
**LAPD (Link Access Procedure on the D channel)**, 153  
**latency, NAT**, 366  
**Layer 1, DSL**, 262  
**Layer 2, ISDN**, 151  
**Layer 3, ISDN**, 153  
**layers**

- PPP layered model, 116
- PRI, 200

**LCP (Link Control Protocol)**, 127, 162
 

- negotiation, 118
- options, 130–134
- troubleshooting, 134–135

**LE (local exchange)**, 149  
**LEAP (Light Extensible Authentication Protocol)**, 236

**leased lines**

- connection options, 66
- WAN, 38

**LED lights**, 69  
**Light Extensible Authentication Protocol (LEAP)**, 236

**limitations, of DSL**, 247

**line coding**

- EI, 199
- PRI, 195–198

**line mode, physical configuration**, 97–98  
**line numbering (routers)**, 92, 94

**Link Access Procedure on the D channel (LAPD)**, 153

**Link Control Protocol**. *See* LCP

**links**

- compression, 348
- ISDN, 164–168
- WAN
  - dial backup*, 318–320
  - primary link failures*, 318–319
  - primary link overload*, 319

**LLQ (Low-Latency Queuing)**, 332, 345–347

**LMI (Local Management Interface)**, 278

**load distribution, TCP**, 370

**load-balancing, Multilink PPP**, 179

**local addresses, NAT**, 372

**Local Director (Cisco)**, 371

**local exchange (LE)**, 149

**local loops**, 38

**logical configuration, routers**, 96–97

**logical parameters, asynchronous configuration**, 94

**logical subinterfaces, Frame Relay**, 280

**login**

- AAA authentication, 409
- local command, 98

**loops, local**, 38

**low earth orbit (LEO)**, 230

**Low-Latency Queuing (LLQ)**, 332, 345–347

## M

**MAC (Media Access Control)**, 236  
**management**, 34

- access, 400–401
- databases, 401

**map-class command**, 303

**maps**

- crypto, 443
- dialer map statements, 181

**medium earth orbit (MEO)**, 230

**methods, WAN, remote access**, 37–40

**MIC (Message Integrity Check)**, 236

**models, PPP layered**, 116

**modem autoconfigure command**, 100

**modem InOut command**, 98

**modemcap, editing**, 100–101

**modems.** *See also connections*

- AT commands, 98–99
- autoconfiguration, 99–100
- cable, 39
- call termination, 90
- chat scripts, 101–103
- CM, initialization, 224–229
- discovery, 100
- DSIR pins, 89
- DTR pins, 89
- PRI incoming analog calls, 202–203
- signaling, 83, 88–90

**modes (AAA), 404****modulation**

- ADSL, 248
- CAP, 248
- DMT, 249

**MultiFrame, 199****Multilink PPP, 131–134, 179, 204–208****multiple B channels, BoD, 178****MULTIPLE\_FRAME\_ESTABLISHED state, 200****multipoint subinterfaces, 283****N****NAT (Network Address Translation)**

- configuration, 259, 373–384
- inside global addresses, 372
- inside local addresses, 372
- IP addresses
  - characteristics of, 366–373*
  - scaling with, 361*
- outside global addresses, 372
- outside local addresses, 372
- overlapping configuration, 369, 377
- overloading, 368
- PAT, 382–384
- sessions, clearing, 382
- simple dynamic configuration, 374–375
- static configuration, 375–376
- TCP load distribution, 370, 379
- translation, 367
- troubleshooting, 381
- verifying translation, 380–381

**NCP (Network Control Protocol), 162****networks.** *See also connections*

- expanding, managing, 400–401
  - HFC, 224
  - ISDN, 39
    - E1 framing, 199*
    - installing PRI, 194–195*
    - layers, 200*
    - PRI, 194*
    - T1 framing, 195–198*
    - troubleshooting Multilink PPP, 204–208*
  - overlapping, 370
  - WAN
    - central-site router selection, 56–61*
    - connections, 16–18*
    - equipment selection, 55*
    - ROBO, 62–64*
    - SOHO, 65–66*
    - wireless, 232–236
- no cdp enable command, 97**

**O****optimizing DDR, 178–180****options.** *See also customization*

- AAA servers, 404
- cable, 221
- PPP, 118, 130–134
- QoS, 35
- satellites, 229–232

**orbits, types of (satellites), 230****output, Frame Relay traffic shaping, 300–302****outside global addresses (NAT), 372****outside local addresses (NAT), 372****overlapping, 369**

- address definitions, 373
- configuring, 377
- dysfunction, 367
- NAT, 377

**overloading**

- NAT, 368, 376
- primary links, 319

**P****Packet over SONET (POS), 37****packet-based access modes, 404**

**packets**

- CBWFQ, 338–339
  - class-map command*, 339–341
  - link compression*, 348
  - LLQ verification*, 345–347
  - payload compression*, 349
  - policy-map command*, 345
  - service-policy command*, 341–345
  - TCP header compression*, 350–351

Fair Queuing, 334

headers, 366

LCP, 162

NCP, 162

PPPoE, 252–255

RST, 402

switching, 38

Weighted Fair Queuing, 335–337

**PAP (Password Authentication Protocol), 119–122**

**parameters**

Frame Relay traffic, 300

ISDN addressing, 162–164

single-connection, 407

**partial-mesh t, 279**

**passive interfaces, 166**

**Password Authentication Protocol (PAP), 119–122**

**PAT (port address translation), NAT, 382–384**

**paths, Frame Relay traffic shaping, 300–302**

**patterns, traffic, 34**

**payloads**

compression, 349

ESP, 436

**PCM (pulse code modulation), 146**

**peer default ip address pool remaddpool command, 97**

**performance, queuing. *See* queuing**

**per-interface compression, 348**

**permit statement, 374**

**physical configuration, 97–98. *See also* configuration**

**physical connections, assembling, 66–68**

**physical interfaces, 182–185**

**physical layer, troubleshooting, 95–96, 262**

**physical parameters, 94**

**ping, BRI, 155**

**plain old telephone service (POTS), 247**

**point-to-multipoint connections, Frame Relay, 285**

**Point-to-Point Protocol (PPP), 38**

**polar orbit (PO), 231**

**pools, dialer, 182**

**port address translation (PAT), NAT, 382–384**

**port-handler assignments, PAT, 383**

**ports**

asynchronous, connection options, 68

line numbering, 92, 94

**POS (Packet over SONET), 37**

**POTS (plain old telephone service), 247**

**PPoE (PPP over Ethernet), 252–255**

**PPP (Point-to-Point Protocol), 38**

architecture, 115

authentication, 119–122

components, 116

dedicated sessions, 117

interactive sessions, 117

LCP. *See* LCP

multilink PPP, 134

options, 118, 130–134

troubleshooting, 134–135

**PPP Callback**

accept command, 132

configuration, 132

option, 131

request command, 132

**ppp commands**

ppp authentication chap command, 97

ppp context command, 117

ppp multilink command, 134

**PPP Link Control Protocol. *See* LCP**

**PPPoE (PPP over Ethernet), 259**

**PQ (priority queuing), 300**

**PRI (Primary Rate Interface), 39, 194**

configuring, 200–202

E1 framing, 199

incoming calls, 202–203

installing, 194–195

layers, 200

T1 framing, 195–198

**primary links**

failures, 318

overload, 319

**priority queuing (PQ), 300**

**process-switching paths, Frame Relay traffic shaping, 300–302**

**Product Selection Tool, 56****Protocol field, PPP, 117****protocols**

AAA, 402

*RADIUS, 403**TACACS, 402–403*

addressing, 164

BRI, 148

BRP, 20

IPSec, configuring, 439–447

ISUP, 153

LCP, 127, 162

LEAP, 236

NCP, 162

PAP, 119–122

PPP, 38

*authentication, 119**components, 116**LCP, 127**options, 118, 130–134**troubleshooting, 134–135***protocol-specific parameter, 285****pulse code modulation (PCM), 146****PVCs, multipoint subinterfaces, 283****Q****Q933a LMIs, 278****QAM (Quadrature Amplitude Modulation), 249****QoS (quality of service), 19, 35****queuing, 300, 332–334**

CBWFQ, 338–339

*class-map command, 339–341**link compression, 348**LLQ verification, 345–347**payload compression, 349**policy-map command, 345**service-policy command, 341–345**TCP header compression, 350–351*

Fair Queuing, 334

Weighted Fair Queuing, 335–337

**R****rack unit (RU), 59****RADIUS (Remote Authentication Dial-In User Service), 402–404****RADSL (rate-adaptive DSL), 251****RAS (Registration, Admission, and Status), 257**

reverse Telnet connections, 90

signaling, 83, 89–90

**rate adaptation, 168****RDBMS (relational database management system), 401****receipt of a reset (RST) packet, 402****redundancy, 35**

dial backup, 318–319

dialer profiles, 181–184

strategies, 320

*dynamic, 320**static, 321–322***Registration, Admission, and Status (RAS), 257**

reverse Telnet connections, 90

signaling, 83, 89–90

**relational database management system (RDBMS), 401****reliability of services, 34****REMDEVICE chat script, 103****remote access**

Cisco 1700 Series, 12

Cisco 2500 Series, 13

Cisco 2600 Series, 13

Cisco 3600 Series, 13–15

VPN 3000 Concentrator Series, 15

WAN, 37–40

**Remote Authentication Dial-In User Service (RADIUS), 402–404****remote office (RO), 19****remote office/branch office. See ROBO****renumbering NAT, 367****requirements**

access, 35

central site installations, 18

RO installations, 19

SOHO installations, 19

**reverse Telnet connections, 90–91**

**RFC 1661, PPP, 115**  
**RO (remote office), 19**  
**ROBO (remote office/branch office), 24**  
     installing, 30–31  
     router selection, 62–64  
**rotary argument, 379**  
**rotary groups, 184–185**

#### routers

AAA, configuring, 407–418  
 central-site, selection of, 56–61  
 Cisco 3600, 57–58  
 Cisco AS5000, 58–60  
 Cisco 1700, 62  
 Cisco 1700 Series, 12  
 Cisco 2500, 63  
 Cisco 2500 Series, 13  
 Cisco 2600, 64  
 Cisco 2600 Series, 13  
 Cisco 3600 Series, 13–15  
 Cisco 800, 65  
 Cisco 827 Series, DSL, 256–260  
 Cisco7200, 60  
 CRWS, 257  
 installing, 68–74  
 interfaces  
     *logical configuration, 96–97*  
     *verifying, 69*  
 line numbering, 92, 94  
 physical configuration, 97–98  
 PPPoE, 253  
 PRI, installing, 194–195  
 ROBO, 62–64  
 SOHO, 65–66  
 uBR, 224  
 VPN 3000 Concentrator Series, 15

**routes, static, 321–322**

#### routing

DDR, 34  
 snapshot, 185–187  
 split horizon, 281

**RST (receipt of a reset) packet, 402**

**RU (rack unit), 59**

## S

**SAR (segmentation and reassembly), 255**

#### satellites

option, 229–232  
 type of orbits, 230

#### scaling

access, 400–401  
 IP addresses with NAT, 361, 366–373

**SDSL (symmetric DSL), 251–252**

#### security, 35

AAA, 36. *See also* AAA  
     *protocols, 402*  
     *RADIUS, 403*  
     *TACACS, 402–403*  
 access, 400–401  
 encryption, 36, 431–433  
     *Diffie-Hellman key exchange, 434–435*  
     *ESP, 436*  
     *hashing, 433*  
     *transport/tunnel modes, 436–439*  
 IPsec, 439–447  
 technology assessment, 40–42  
 WEP, 235  
 wireless networks, 235

**segmentation and reassembly (SAR), 255**

**selecting, interface for Frame Relay  
 configuration, 284**

#### selection of equipment, 24

cabling, 66–68  
 central-site routers, 56–61  
 Product Selection Tool, 56  
 ROBO, 62–64  
 SOHO, 65–66  
 WAN, 55

**serial interfaces, 73. *See also* interfaces**

#### servers

AAA, 404  
 security, 402  
 TACACS, 403

**server-to-server VPNs, 41**

#### services

availability of, 33  
 back office, 222  
 cost of, 34  
 QoS, 19  
 reliability of, 34

**sessions, 253, 255. *See also* PPPoE**  
**set ip pat on command, 383**  
**SF (SuperFrame), 196**  
**shaping traffic, 297. *See also* Frame Relay**  
**SHDSL (symmetric high-data-rate DSL), 251**  
**show atm interface atm 0 commands, 263**  
**show cable modem command, 224**  
**show commands, 69**

- show controllers t1 command, 198
- show dialer command, 134, 205
- show frame-relay lmi command, 289
- show frame-relay map command, 291
- show frame-relay pvc command, 288, 302, 305
- show interface atm 0 command, 262
- show interfaces ethernet command, 69
- show interfaces serial command, 72–74
- show ip nat statistics command, 381
- show ip nat translation command, 380
- show isdn status command, 153, 200, 204
- show line command, 92, 94
- show line output command, 92
- show modemcap command, 100
- show ppp multilink command, 204
- show traffic-shape command, 306

**signal pins (modems), 89**  
**signaling modems, 83, 88–90**  
**Signalling System 7 (SS7), 153**  
**simple dynamic NAT configuration, 374–375**  
**simple NAT translation, 367**  
**single-connection parameter, 407**  
**site preparation. *See also* equipment selection**

- assembling, 66–68
- central-site preparation, 29–30
- central-site router selection, 56–61
- ROBO, 30–31
- SOHO, 31–32

**site-to-site VPNs, 41**  
**small office/home office. *See* SOHO**  
**snapshot routing, 185–187**  
**sockets, NAT overloading, 368**  
**software, Cisco Local Director, 371**  
**SOHO (small office/home office), 24, 246**

- installing, 31–32
- requirements, 19
- router selection, 65–66

**SONET (Synchronous Optical Network), 37**  
**source ports, 368**  
**speed, troubleshooting, 72**  
**split horizon, 281–282**  
**splitting, traffic, 246**  
**spoofing, 162**  
**SS7 (Signalling System 7), 153**  
**standard AT commands, 98–99**  
**star topology, Frame Relay, 279**  
**start-chap command, 102**  
**statements, dialer map, 131, 181**  
**static NAT configuration, 375–376**  
**static redundancy, 321–322**  
**status, interfaces, 70**  
**stop-only argument, 418**  
**strategies, redundancy, 320–322**  
**subinterfaces. *See also* interfaces**

- cast type, 284
- Frame Relay, 282

**substitute addresses, overloading NAT, 368**  
**sun-synchronous orbit (SSO), 231**  
**SuperFrame (SF), 196**  
**switches, PRI, 194–195**  
**switching, 38**  
**symmetric DSL (SDSL), 245, 251–252. *See also* DSL**  
**Synchronous Optical Network (SONET), 37**  
**syntax, chat scripts, 101–102**

## T

**T1 framing, PRI, 195–198**  
**TACACS (Terminal Access Control Access Control System), 402–403**  
**TCP (Transmission Control Protocol)**

- headers, compression, 350–351
- load distribution, 370
- NAT, 379

**TDM (time division multiplexing), 196**  
**technological assessment of security, 40–42**  
**TEI (Terminal Endpoint Identifier), 151, 200**  
**Terminal Access Control Access Control System (TACACS), 402–403**  
**Terminal Endpoint Identifier (TEI), 151, 200**  
**time division multiplexing (TDM), 196**  
**tools**

- CRWS, 257
- Production Selection Tool, 56

**topologies, Frame Relay, 277****traffic**

- Frame Relay, 297. *See also* Frame Relay patterns, 34
- splitting, 246

**translation, configuring NAT, 367, 373–384****transmissions**

- Fair Queuing, 334
- Weighted Fair Queuing, 335–337

**transport mode, 436–439****troubleshooting**

- congestion. *See* congestion
- debug commands
  - debug dialer command, 206*
  - debug frame-relay lmi command, 290*
  - debug ip nat command, 381*
  - debug isdn q921 command, 207*
  - debug isdn q931 command, 155, 208*
  - debug ppp authentication command, 135*
  - debug ppp multilink command, 206*
  - debug ppp negotiation, 135*
- dial backup, 318–320
  - primary link failures, 318–319*
  - primary link overload, 319*
- DSL, 260–265
- duplex values, 72
- installations, 68–74
- LED lights, 69
- modems, 88–90
- Multilink PPP, 204–208
- NAT, 381
- PPP, 134–135
- queuing. *See* queuing
- redundancy, 35
- speed, 72
- split horizon, 282
- TACACS, 403

**tunnels**

- IPSec, 439–447
- mode, 436–439

**types**

- of ADSL, 250
- of connections, 66–68
- of SDSL, 251–252

**U**

- uBR (Universal Broadband Router), 224**
- unreachable DSLAM, 264. *See also* DSLAM**
- UTP (unshielded twisted pair), 146**

**V**

- Van Jacobson algorithm, 350**
- VAR (value-add reseller), 16**
- variance 4 command, 320**
- VCI (virtual circuit identifier), 255**
- VCs (virtual circuits), 38**
- VDSL (very-high-bit-rate DSL), 251**
- verification**
  - installations, 68–74
  - Frame Relay configuration, 287, 289, 290
    - show frame-relay lmi command, 289*
    - show frame-relay map command, 291*
    - show frame-relay pvc command, 288*
  - LLQ, 345–347
  - NAT translation, 380–381
- viewing modemcap settings, 101**
- virtual circuit identifier (VCI), 255**
- virtual circuits (VCs), 38**
- voice, splitting, 246**
- VPI (virtual path identifier), 255**
- VPN 3000 Concentrator Series, 15**
- VPNs (virtual private networks), 24, 41**

**W**

- wait-start argument, 417**
- WAN (wide area network), 24**
  - dial backup, 318–320
    - failures, 318–319*
    - overloading, 319*
  - connections, 16
  - cost of, 34
  - equipment selection, 55
    - central-site routers, 56–61*
    - ROBO, 62–64*
    - SOHO, 65–66*
  - methods for remote access, 37–40
- weighted fair queuing (WFC), 300, 335–337**
- well-known ports, 368**