

# Index

---

## Symbols & Numerics

? (question mark), CLI help system, 179

10Base2, 53–54, 60

LAN switching, 60–63

repeaters, 55

10Base5, 53–54, 60

LAN switching, 60–63

repeaters, 55

10BaseT

full-duplex, 71

half-duplex, 59

LAN switching, 60–63

10 Gigabit Ethernet, 299–300

10-Mbps Ethernet, 53–56, 60–61

cabling, 57–58

hubs, 59–60

switching, 60–63

802.11 WLANs, 301–302

802.1q trunking, 266–267

## A

access links, 97

access lists, 486–487

accessing CLI, 176–177, 214, 221

multiple Telnet connections, 178

on Cisco 2950 switches, 215

passwords, 177

ACK field, TCP connection

establishment, 158

active configuration, 188

adding connected routes to routing tables,  
376–379

address classes, 122–124, 319–320

addresses, 51

addressing schemes, 118

AppleTalk addresses

*grouping*, 118

*structure*, 119, 139

burned-in addresses, 65

group addresses, 64

IP addresses

*Class A networks*, 122

*Class B networks*, 122

*Class C networks*, 122

*grouping*, 118

*hostnames, displaying*, 369

*interfaces, displaying*, 369

*structure*, 119, 139

IPX addresses

*grouping*, 118

*structure*, 119, 139

MAC addresses, 64

*BIAs*, 64

*broadcast addresses*, 64, 237

*components*, 64

*LAN card addressing*, 64, 237

*multicast addresses*, 65, 237

*OUI*, 64

*unicast*, 64

network layer, 118–119

amplitude modulation, 443

analog modems

baud, 444

installing, 445–446

modulation, 442–444

PPP, 444

standards, 446–447

analog signals, 436

converting to digital, 438–439

Nyquist's theorem, 440

ANSI (American National Standards Institute), 53, 87  
AppleTalk addresses  
  cable ranges, 118  
  grouping, 118  
  structure, 119, 139  
application layer  
  OSI model, 33  
  TCP/IP model, 22–24  
APs (access points), 301  
arbitration, 50  
ARP (Address Resolution Protocol), 117, 127–129, 135  
  cache, displaying, 369  
AS (autonomous system), 410  
asynchronous data links, 95, 577  
asynchronous serial leased lines, 95, 588  
ATM (Asynchronous Transfer Mode), 101  
attenuation, 55  
autonegotiation, 244  
auxiliary ports, 177

## B

back-to-back serial connections, 88–89  
balanced hybrid protocols, 421  
  EIGRP, 419–420  
bandwidth, router configuration, 380  
BGP (Border Gateway Protocol), 410–411  
BIAs (burned-in addresses), 64  
binary values, converting to decimal and hexadecimal values, 324–326, 565, 569  
bitwise Boolean AND operation, 327  
blocking, 248  
Boolean AND operation, 326–328, 333–335  
boot field, 199  
boot sequence (Cisco IOS), 197–199  
boot system command, 199

boot system flash command, 199, 203  
boot system tftp command, 199, 203  
BOOTP, 130, 132  
BPDUs (bridge protocol data units), 248  
BRI (Basic Rate Interface), 449, 452  
bridge tables, 237–238  
bridges  
  frame filtering, 238  
  MAC address learning process, 239  
  transparent, 236  
broadcast addresses, 65  
  MAC addresses, 64, 237  
broadcast domains, 246–247, 253  
broadcast firewalls, 246  
burned-in addresses, 65

## C

cable modems, 460  
  two-way communication, 462  
  upstream data, 463  
cable ranges (AppleTalk), 118  
cabling, 287  
  10BASE-T, 57–58  
  coaxial, 291–293  
  Ethernet standards, 298  
  Fast Ethernet, 68  
  fiber-optic, 293  
    *connectors*, 295–296  
    *MM*, 294–295  
    *SM*, 294  
  interference, 288  
  shielded, 288  
  twisted pair, 288  
  UTP, 289–290  
    *connectors*, 290–291  
    *standards*, 290

- WAN standards, 85–86
    - clock rate*, 88
    - link speeds*, 89–90
    - maximum speeds*, 87
- calculating hosts per subnet, 329–332
- call setup, ISDN, 449–450
- Can't Fragment code (Destination Unreachable ICMP message), 385
- carrier sense multiple access collision detect (CSMA/CD), 50, 55
- CatOS, 214
- CATV
  - drop cable, splitting, 461
  - head-end site, 460
  - MCNS, 463
- CDP (Cisco Discovery Protocol), 392–395, 494
- cdp enable command, 393
- cdp run command, 393
- cells (ATM), reassembly, 101
- channels, ISDN, 449
- CIDR (classless interdomain routing), 351–353
- CIR (committed information rate), 99
- Cisco 2950 switches, 213
  - CatOS, 214
  - CLI, 215
  - configuring, 220
  - initial configuration mode, 218–220
  - initialization, 216
    - POST*, 216–217
- Cisco Discovery Protocol. *See* CDP
- Cisco IOS
  - boot sequence, 197–199
  - CLI
    - accessing*, 176–177
    - help system*, 179
    - setup mode*, 190–194
  - configuration files
    - managing*, 188–189
    - updating*, 182
  - example configuration, 183–185
  - IP configuration commands, 368–369
  - privileged EXEC mode, 178
  - user EXEC mode, 178
- Cisco ISL (Inter-Switch Link), 266
- Class B network masks, 320
- Class C network masks, 320
- classes of networks, 122–124, 319–320
- classifying interior routing protocols, 409–410
- classless interdomain routing (CIDR), 351–353
- CLI (command-line interface), 181, 201
  - accessing, 176–177, 214–215, 221
  - commands, recalling, 180
  - configuration mode, 182–183
  - help system, 179
  - passwords, 176–177
  - privileged EXEC mode, returning to, 183
  - setup mode, 190–194
  - user EXEC mode, 181, 201
- clock rate, 88
  - router configuration, 380
- clock sources, 95, 579
- coaxial cabling, 291–293
- codecs, 439
- collision domains, 60, 245–247, 253
- collisions, reducing with LAN switching, 60–63
- commands
  - boot system, 199
  - boot system flash, 199, 203
  - boot system tftp, 199, 203
  - cdp enable, 393
  - cdp run, 393
  - configuration mode end, 183
  - copy, 202
  - copy tftp flash, 197
  - debug ip packet, 369
  - editing in CLI, 180
  - enable secret, 372
  - global commands, 182
  - hostname, 183
  - interface, 182
  - interface ethernet 0, 183
  - ip address, 183, 368
  - ip domain-lookup, 368, 388
  - ip domain-name, 388
  - ip host, 368, 388
  - ip name-server, 368, 388
  - ip netmask-format, 368
  - ip routing, 368
  - key commands, Ctrl+z, 183
  - line aux, 177, 200
  - line console, 177, 200
  - line vty, 177–178, 200
  - login, 178

- no cdp enable, 393
- no cdp run, 393
- no debug all, 181
- no ip domain-lookup, 388
- ping, 130, 383–384, 387, 493
- recalling, 180, 201
- resume, 391
- setup, 190
- show access-lists, 489
- show cdp entry, 393
- show cdp interface, 395
- show cdp neighbor, 393
- show cdp neighbor detail, 394
- show flash, 196
- show hosts, 369
- show interface, 376, 489
- show interfaces, 369
- show ip arp, 492–493
- show ip host, 388
- show ip interface, 369, 377
- show ip interface brief, 369, 376, 379, 489
- show ip protocol, 490
- show ip route, 373, 376–379, 383, 397, 492
- show running-config, 371, 374–375, 380, 491
- subcommands, 182
- telnet, 389
- terminal history size, 179
- terminal ip netmask-format, 369, 374
- trace, 492–493
- comment lines, command output, 183**
- comparing**
  - remote access technologies, 465–466
  - TCP and UDP, 162–163
- computers, 153**
- configuration files (IOS)**
  - copying, 189–190
  - managing, 188–189
  - storing, 188
  - updating, 182
- configuration mode (IOS CLI), 182**
  - exiting, 183
- configuration mode end command, 183**
- configuration register, 198–199, 203**
- configuring**
  - Cisco 2950 switches, 220
  - Cisco IOS, example, 183–185
  - Cisco routers
    - bandwidth*, 380
    - basic administration*, 370–372
    - clock rate*, 380
    - IP address*, 372–375
    - IP configuration commands*, 368–369
    - prefix notation*, 375
    - routing table*, 376–379
  - IP addresses, 368, 371–376, 379
    - host names*, 387–388
    - naming*, 388
  - PPP, 487
  - routers
    - in setup mode*, 190–194
    - IP*, 387
    - IP RIP*, 486–487
- connectionless protocols, 159–160, 164**
- connection-oriented protocols, 159–160, 164**
- connections**
  - TCP, 158–159
  - telnet, suspended, 391
- connectors**
  - fiber cables, 295–296
  - UTP, 290–291
- console ports, 177**
- convergence, 421, 579**
  - STP, 251
- converting**
  - analog signals to digital, 438–440
  - decimal-to-hexadecimal-to-binary values, 565, 569
- copper cabling, 288**
- copy command, 202**
- copy tftp flash command, 197**
- copying**
  - configuration files, 189–190
  - images into Flash memory, 194–197
- CPs (control protocols), 93**
- CRC (cyclical redundancy check), 51**
- creating**
  - subnet chart, 340–342
  - subnet list chart, 347–350
  - VLANs, 264–265
- crosstalk, 288**

CSMA/CD (carrier sense multiple access/  
collision detect), 50, 55  
 CSU/DSU (channel service unit/data service  
unit), 84  
 Ctrl+z key sequence, 183  
 cut-through switching, 243

## D

dark fiber, 294  
 data encapsulation, 29–30  
 data link layer (OSI model), 33  
   addressing, 51  
   arbitration, 50  
   encapsulated data, identifying, 52  
   error detection, 51  
   identifying encapsulated data, 52, 66–67  
   LAN features, 50–51  
 data segmentation, 160–161  
 Data Service Unit/Channel Service Unit.  
  *See* DSU/CSU  
 data-link layer (OSI model)  
   encapsulation, 116  
   point-to-point WANs  
     HDLC, 91–92  
     PPP, 92  
     synchronization, 94  
   PPP, 444  
 data-link protocols, MCNS, 463  
 DCE/DTE (data communication equipment/  
data termination equipment), 98  
 debug ip packet command, 369  
 decimal values, converting to hexadecimal  
  and binary values, 324–326, 565, 569  
 demodulation, 441–444  
 deploying networks  
   configuration, 486–488  
   planning phase, 483–485  
   verification, 488–492  
 designated bridges, 250  
 Destination Unreachable ICMP messages,  
  382–387  
 development of OSI model, 20  
 devices  
   A/D converters, 439  
   analog modems, 441–442  
     installing, 445–446  
     modulation, 442–444

    PPP, 444  
     standards, 446–447  
   cable modems, 460  
   hubs, 56  
     10BASE-T, 59–60  
     shared Ethernet, 56  
   L3 switches, 270  
   modems  
     DSL, 455–457  
     ISDN, 448  
   repeaters, 55  
   routers  
     bandwidth, 380  
     basic administration, 370–372  
     clock rate, 380  
     IP address configuration, 372–375  
     routing table, 376–379  
   telnetting between, suspend function,  
    389–391  
 DHCP (Dynamic Host Configuration  
Protocol), 131–132  
 digital modems  
   cable modems  
     two-way communication, 462  
     upstream data, 463  
   DSL, 455–456  
     standards, 456–457  
   ISDN, 448  
     installing, 453  
 digital signals, 437  
   encoding schemes, 438  
 Dijkstra's algorithm, 416, 421, 580  
 directly connected subnets, 412  
 disabling debug options, 181  
 discovering neighbor devices, 392–395  
 displaying running configuration, 190  
 distance vector routing protocols, 135, 140,  
  407  
   IGRP, 414–416  
   RIP, 411–412  
     RIPv1, 413  
     RIPv2, 414  
 DIX (DEC, Intel, and Xerox) Ethernet, 53  
 DLCI (data-link connection identifier), 98  
 DNS (Domain Name System), 127–129, 154  
   UDP interaction, 162  
 dotted-decimal notation, 120  
 downstream data, 462

DRAM (dynamic random-access memory),  
   187, 201  
 drop cable, splitting, 461  
 DS0 (Digital Signal Level 0), 90, 440  
 DS1 (Digital Signal Level 1), 440  
 DSAP (destination service access point),  
   66–67  
 DSL (Digital Subscriber Line), 454  
   modems, 455–456  
   PPPoA, 458–459  
   standards, 456–457  
 DSLAM (DSL access multiplexer), 455–456  
 DSU/CSU (Data Service Unit/Channel  
   Service Unit), 95, 580  
   clocking, 88  
 DTE (data termination equipment)  
   clocking, 88  
 DTMF (dual-tone multifrequency), 442  
 DUAL (Diffusing Update Algorithm), 419,  
   421, 580  
 dual-ring topologies, 286  
 dynamic random-access memory (DRAM),  
   187, 201  
 dynamic routing protocols, 407–408  
   balanced hybrid, EIGRP, 419–420  
   distance vector routing protocols  
     *IGRP*, 414–415  
       metric calculation, 415–416  
       *RIP*, 411–412  
       *RIPv2*, 414  
       *RIPv6*, 413  
   exterior routing protocols, 408  
     *BGP*, 410–411  
   interior routing protocols, classifying,  
     409–410  
   link-state, 416–417  
     *integrated IS-IS*, 418–419  
     *OSPF*, 417–418

## E

E1 lines, 90  
 early Ethernet standards, 52  
 Echo ICMP message, 382, 387  
 Echo Request/Reply messages, 382–384  
 editing commands in CLI, 180  
 EIA/TIA 232 WAN cabling standard, 86  
 EIA/TIA 449 WAN cabling standard, 86

EIA/TIA 530 WAN cabling standard, 86  
 EIGRP (Enhanced IGRP), 419–420  
 enable secret command, 372  
 encapsulation, 29–30, 116  
 encoding schemes, 438  
 Enhanced IGRP (EIGRP), 419  
 enterprise networks, 6  
 error detection  
   at data-link layer, 51  
   PPP, 93  
 error recovery, TCP, 155  
 Ethernet, 6  
   10-Mbps, 56, 60–61  
     *cabling*, 57–58  
     *hubs*, 59–60  
   10Base2, 53–54, 60  
     *repeaters*, 55  
   10Base5, 53–54, 60  
     *repeaters*, 55  
   10BaseT  
     *full-duplex*, 71  
     *half-duplex*, 59  
   10 Gigabit Ethernet, 299–300  
   arbitration, 50  
   autonegotiation, 244  
   cabling standards, 298  
   collisions, reducing, 60–63  
   CSMA/CD, 50  
   early standards, 52  
   Fast Ethernet, 69  
   framing, 65–66  
   full-duplex, 242  
   Gigabit Ethernet, 69  
   group addresses, 64  
   IEEE standards, 53  
   MAC addresses, 64  
   multicast addresses, 65  
   topologies, 283–284  
     *full mesh*, 285  
 evolution of PSTN, 437  
 example configuration, Cisco IOS, 183–185  
 extended star topologies, 284  
 exterior routing protocols, *BGP*, 408–411,  
   421, 581  
 external modems, 445

## F

- Fast Ethernet, 69
- FCS (frame check sequence), 51
- FDDI (Fiber Distributed Data Interface)
  - ANSI standards, 53
- fiber-optic networking, 293
  - connectors, 295–296
  - MM, 294–295
  - SM, 294
  - SONET, 100
- FIN field, TCP connection establishment, 158
- Flash memory
  - read-only mode, 196
  - routers, 187, 202
  - storing IOS images, 194–197
  - verifying contents of, 196
- Flintstones network example, 7–13
- flow control, TCP, 156–157
- forward acknowledgment, TCP, 155
- forwarding state (STP), 251, 254
- forwarding unknown unicast frames, 240
- four-wire circuits, 95
- FragmentFree processing, 243, 253
- fragment-free switching, 243
- Frame Relay, 96–97
  - access links, 97
  - CIR, 99
  - DTE/DCE, 98
  - VCs, 98
  - versus point-to-point links, 97
- frames, 65–67, 72
  - Ethernet, 66
- frequency modulation, 443
- FTP (File Transfer Protocol), 8–10
- full mesh topologies, 285
- full-duplex, 242
- full-duplex 10BaseT Ethernet, 71
- full-duplex operation (Ethernet), 62

## G

- Get Requests (HTTP), 23
- Gigabit Ethernet, 69
- global commands, 182
- goals of routing protocols, 135–136
- group addresses, 64, 237

## H

- half-duplex 10BaseT Ethernet, 59
- half-duplex logic, 62
- HDLC (high level data-link control), 91–92
  - synchronization, 94
- head-end site (CATV), 460
- headers, TCP, 150
- help system (CLI), 179
  - IOS commands, 180, 201
- hexadecimal values, converting to decimal
  - and binary values, 565, 569
- history buffer (CLI), recalling commands, 180
- host names, configuring, 387–388
- Host Unreachable code (Destination Unreachable ICMP message), 385
- hostname command, 183
- hosts per subnet, calculating, 329–332
- HTML (Hypertext Markup Language), 23
- HTTP (HyperText Transfer Protocol)
  - headers, 23
- hub-and-spoke topologies, 283
- hubs, 56
  - 10BASE-T, 59–60
  - full-duplex 10BaseT Ethernet, 71
  - half-duplex 10BaseT Ethernet, 59
  - shared Ethernet, 56

## I-J

- IBM SNA (Systems Network Architecture), 20
- ICMP (Internet Control Message Protocol), 130–131, 381
  - messages
    - Destination Unreachable*, 382, 385–387
    - Echo*, 382, 387
    - Echo Request/Reply*, 130, 382–384
    - Parameter Problem*, 382
    - Redirect*, 382
    - Source Quench*, 382
    - Time Exceeded*, 382
  - troubleshooting IP addresses, 381, 383

**identifying**

- encapsulated data at data link layer, 52, 66–67
- IP address structure, 329–332
- subnet broadcast address, 335–336
- valid IP addresses in a subnet, 336–337

**IEEE standards**

- Ethernet, 53
- group addresses, 64, 237
- LANs, 53

**IGRP (Interior Gateway Routing Protocol), 414–415**

- features, 416, 419, 424
- metric, 415–416
- versus RIP, 416, 419, 424

**image files (IOS), 194**

- storing in Flash memory, 194–197

**initial configuration mode, Cisco 2950 switches, 218–220****initialization process, Cisco 2950 switches, 216–217****installing**

- ISDN for home-based networks, 453
- modems, 445–446

**Integrated IS-IS, 418–419****interface cable standards, WANs, 86****interface command, 182****interface ethernet 0 command, 183****interfaces**

- IP parameters, displaying settings, 369
- routers, numbering, 187
- statistics, displaying, 369

**interior routing protocols, 408, 421, 583**

- classifying, 409–410
- EIGRP, 419
- IGRP, 414–416
- Integrated IS-IS, 418
- OSPF, 417
- RIPv1, 413
- RIPv2, 414

**internal modems, 445****internal switch processing, 243, 252****internetwork layer (TCP/IP model), 26–27****IOS (Internetwork Operating System)****CLI**

- accessing*, 176–177, 214, 221
- configuration mode*, 183
- privileged EXEC mode*, 181–183, 201
- user EXEC mode*, 181, 201
- configuration file, 188
- images, 194

**IP (Internet Protocol), 135. See also IP addressing****addresses**

- Class A networks*, 122
- Class B networks*, 122
- Class C networks*, 122
- grouping*, 118
- hostnames, displaying*, 369
- interfaces, displaying*, 369
- Private Addressing*, 354
- structure*, 119, 139

**ARP cache, displaying, 369****CIDR, 351, 353****configuration, 387****interface settings, displaying, 369****NAT, 351****Private Addressing, 351****RIP, configuring, 486–487****routing protocols, 407****standard access lists, configuring, 486–487****ip address command, 183, 368****IP addressing, 120****address classes, 122–124, 319–320****Boolean AND operation, 326–328****configuring, 368–379****dotted-decimal notation, 120****grouping concepts, 121****host name configuration, 387–388****identifying address structure, 329–332****naming configuration, 388****NAT, 354****network numbers, 123, 139****prefix notation, 328****subnet list chart, creating, 347–350****subnetting, 124–127, 321***binary conversion, 324–326**Boolean AND operation, 333–335**broadcast address, identifying, 335–336*

- deriving subnet broadcast address*, 343
  - hosts per subnet, calculating*, 329–332
  - identifying valid IP addresses*, 336–337
  - subnet chart, creating*, 340–342
  - subnet masks*, 344–346
  - troubleshooting with ICMP, 381–383
  - IP configuration commands (Cisco IOS Software)**, 368–369
  - ip domain-lookup command**, 368–388
  - ip domain-name command**, 388
  - ip host command**, 368–388
  - ip name-server command**, 368–388
  - ip netmask-format command**, 368
  - ip routing command**, 368
  - IPv6**, 355
  - IPX (Internetwork Packet Exchange)**
    - access lists, configuring
      - SAP filters*, 486–487
      - standard*, 486–487
    - address structure, 118–119, 139
  - ISDN (Integrated Services Digital Network)**, 447–448
    - BRI, 449
    - call setup, 449–450
    - channels, 449
    - installing, 453
    - out-of-band signaling, 450
    - PRI, 449
    - TA, 448
    - typical uses, 451–453
  - ISL (Inter-Switch Link)**, 266
  - ISO (International Organization for Standardization)**, development of OSI model, 20
  - ITU (International Telecommunications Union)**, 86
- ## K-L
- key sequences, Ctrl+z, 183
  - L3 switches, 270
  - L3PDU (Layer 3 PDU), 36
  - LANs, 6. See also VLANs**
    - broadcast domains, 246
    - cabling, 287
      - coaxial*, 291–293
      - fiber*, 293–296
      - interference*, 288
      - twisted-pair*, 288
      - UTP*, 289–291
    - collision domains, 60, 245
    - Ethernet
      - 10 Gigabit Ethernet*, 299–300
      - 10-Mbps*, 53–61
      - autonegotiation*, 244
      - Fast Ethernet*, 69
      - framing*, 65–66
      - Gigabit Ethernet*, 69
      - group addresses*, 64
      - MAC addresses*, 64
      - switching*, 60–63
    - frames, 67, 72
    - OSI model functionality, 47
      - data link layer*, 50–51
      - physical layer*, 47–49
    - segmenting
      - with bridges*, 236
      - with switches*, 240–242, 246
    - switching, internal processing, 243, 252
  - LAPB (Link Access Procedure Balanced)**, 91, 95, 580
  - LAPD (Link Access Procedure on the D channel)**, 94, 105
  - Layer 2 switching**, 268
  - Layer 3 forwarding**, 268–270
  - Layer 4 switching**, 271
  - layers of OSI model**, 31–34
    - data link layer
      - addressing*, 51
      - arbitration*, 50
      - error detection*, 51
      - identifying encapsulated data*, 52
      - identifying encapsulated Ethernet data*, 66–67
    - network layer
      - addressing*, 118–119
      - routing*, 114–117, 135
    - transport layer
      - error recovery*, 155
      - features*, 149
      - flow control*, 156–157

- TCP*, 150–154, 158–159
- UDP*, 162
- layers of TCP/IP model
  - application layer, 22–24
  - data encapsulation, 29–30
  - internetwork layer, 26–27
  - network interface layer, 27–28
  - transport layer, 24–25
- LCP (Link Control Protocol), 93
- learning state (STP), 251
- leased lines, 82
  - connectivity, 84–85
- line aux command, 177, 200
- line console command, 177, 200
- line vty command, 177, 178, 200
- link speeds, 89–90
- link state routing protocols, 421
- link-state protocols, 416–417
  - integrated IS-IS, 418–419
  - OSPF, 417–418
- listening state (STP), 251
- logic used by routing protocols, 134–135
- logical topologies, 283
- login command, 178
- loop avoidance, STP, 248–249
  - convergence, 251
  - designated bridges, 250
  - forwarding state, 251, 254
  - root bridges, 250
- lower layers of OSI model, 32
- LQM (Link Quality Monitoring), 93

## M

- MAC addresses, 64
  - BIAs, 64
  - broadcast addresses, 64, 237
  - components, 64
  - LAN card addressing, 64, 237
  - learning process, bridges, 239
  - multicast addresses, 65, 237
  - OUI, 64
  - unicast, 64
- managing configuration files, 188–189
- MANs (metropolitan-area networks), 82
- masks
  - network masks
    - Class B networks*, 320
    - Class C networks*, 320
    - subnet masks, display types, setting, 369
- maximum WAN cable speeds, 87
- MCNS (Multimedia Cable Network Systems), 463
- memory, 187
  - Flash, 187
    - read-only mode*, 196
    - routers*, 202
    - storing IOS images*, 194–197
    - verifying contents of*, 196
  - NVRAM, 187, 202
  - RAM, 187, 201
  - ROM, 187, 201
- messages, ICMP, 381
  - Destination Unreachable, 385–387
  - Echo Request/Reply, 130, 382–384
- metallic cabling, 287
  - coaxial, 291–293
  - interference, 288
  - twisted-pair cabling, 288
  - UTP, 289–290
    - connectors*, 290–291
    - standards*, 290
- metrics, IGRP, 415–416
- MM (multimode) fiber, 294–295
- modems
  - analog
    - installing*, 445–446
    - modulation*, 442–444
    - PPP, 444
    - standards*, 446–447
  - analog analog modems, 441–442
  - cable modems, 460
    - two-way communication*, 462
    - upstream data*, 463
  - DSL, 455–456
    - standards*, 456–457
  - ISDN, 448
  - modulation, 442–444
  - MT-RJ connectors, 296
  - MTU (maximum transmission unit), 66, 160–161
- multiaccess networks, Frame Relay, 97–98

- multicast addresses, 65
  - MAC addresses,, 237
- multilayer switching, 272
- multiplexing, 151–152
  - sockets, 152, 154
  - UDP, 161
- multiplexors, T1 mux, 95, 589

## N

- naming IP addresses, 388
- NAT (Network Address Translation), 351, 354, 351
- neighboring devices
  - discovery, 392–393, 395
- Network Address Translation, *see* NAT, 351
- Network File System, *See* NFS, 162
- network interface layer (TCP/IP model), 27–28
- network layer (OSI model), 33
  - addressing, 118–119
  - ARP, 127, 129
  - BOOTP, 130, 132
  - DHCP, 131–132
  - DNS, 128–129
  - ICMP echo requests, 130
  - RARP, 130–132
  - routing, 114–116, 135
    - data-link layer interaction, 116–117*
- network numbers, 123, 139
  - aggregating with CIDR, 351, 353
  - Class A networks, 121, 123, 139
  - Class B networks, 121, 123, 139
  - Class C networks, 121, 123, 139
- Network Unreachable code (Destination Unreachable ICMP message), 385–386
- networking, 7
  - end-user perspective, 5–6
  - enterprise, 6
  - Flintstones network example, 7–13
  - Frame Relay VCs, 98
  - private Internets, 353
- networking architectures
  - Ethernet topologies, 283–285
  - OSI model, 15
    - development of, 20*
    - LAN functionality, 47–51*
    - layering, 35–36*

- TCP/IP, 20
  - application layer, 22–24*
  - data encapsulation, 29–30*
  - internetwork layer, 26–27*
  - network interface layer, 27–28*
  - same-layer interaction, 26*
  - transport layer, 24–25*
- Token Ring topologies, 286
- networks masks, 320
- NFS (Network File System), 162
  - UDP interaction, 162
- no cdp enable command, 393
- no cdp run command, 393
- no debug all command, 181
- no ip domain-lookup command, 388
- nonvolatile random-access memory.
  - See* NVRAM
- numbering router interfaces, 187
- NVRAM
  - (nonvolatile RAM), 187, 202
  - configuration files
    - erasing, 190*
  - routers, 187, 202
- Nyquist's theorem, 440

## O

- operating systems, CatOS, 214
- ordered data transfer, 160–161
- Organizationally Unique Identifier. *See* OUI
- OSI Reference model, 15, 31–34
  - data link layer
    - addressing, 51*
    - arbitration, 50*
    - error detection, 51*
    - identifying encapsulated data, 52*
    - identifying encapsulated Ethernet data, 66–67*
    - LAN features, 50–51*
    - point-to-point WANs, 91–92, 94*
  - development of, 20
  - LAN functionality, 47
  - layering, 35–36
  - network layer
    - addressing, 118–119*
    - routing, 114–117, 135*
  - PDUs, 36

- physical layer
  - LAN features*, 47–49
  - point-to-point WANs*, 81, 83
- transport layer
  - features*, 149
  - TCP*, 150–152, 154
- OSPF (Open Shortest Path First), 417–418
- OUI (Organizationally Unique Identifier), 64–65
- out-of-band signaling, ISDN, 450
- output (commands), comment lines, 183

## P

- packet-switched WANs
  - ATM, 102
  - Frame Relay, 96–97
    - access links*, 97
    - CIR*, 99
    - DTE/DCE*, 98
    - VCs*, 98
- Parameter Problem ICMP message, 382
- partial mesh topologies, 285
- passwords, accessing CLI, 177
- PCM (pulse-code modulation), converting
  - analog signals to digital, 439–440
- PDU (protocol data units), 36
- periodic updates, 412
- phase modulation. *See* modulation
- physical bus topologies, 283
- physical layer (OSI model), 34
  - LAN features*, 47–49
  - point-to-point WANs*, 81–83
    - connectivity*, 84–85
- physical star topologies, 286
- ping command, 130, 383–384, 387, 493
- planning phase of network deployment, 483–485
- point-to-point WANs, 81, 83
  - connectivity, 84–85
  - data-link protocols
    - HDLC*, 91–92
    - PPP*, 92
    - synchronization*, 94
- Port Unreachable code (Destination Unreachable ICMP message), 386
- ports, 154
  - console ports, 177
  - Layer 4 switching, 271
- POST (Power-On Self Test), Cisco 2950 switches, 216–217
- PPP (Point-to-Point Protocol), 92–94, 105, 444
  - configuring, 487
  - LCP, 93
  - synchronization, 94
- PPPoA (PPP over ATM), 458–459
- prefix notation, 328
  - show ip route command, 375
- preparing for exam, 479–494
  - IP addressing
    - creating subnet chart*, 340–342
    - deriving subnet broadcast address*, 343
    - identifying address structure*, 329–330, 332
- presentation layer (OSI model), 33
- preventing routing loops with STP, 249
  - convergence, 251
  - designated bridges, 250
  - forwarding state, 251, 254
  - root bridges, 250
- PRI (Primary Rate Interface), 449
- Private Addressing, 351, 354
- private Internets, 353
- privileged EXEC mode (Cisco IOS), 178, 181, 201
- Protocol Unreachable code (Destination Unreachable ICMP message), 385
- protocols
  - connectionless, 160
  - connection-oriented, 160
  - routed protocols, 407, 422
  - routing protocols, 407, 422
    - comparison of*, 408
    - distance vector routing protocols*, 407
    - goals of*, 140

- PSTN (Public Switched Telephone Network), 435
  - analog signals, converting to digital, 436–440
  - digital signals, 437
    - encoding schemes*, 438
  - DS0/DS1, 440
  - evolution of, 437
  - modem operation, 441–442
    - modulation*, 442–444
    - PPP*, 444
- PTT (public telephone and telegraph) companies, 83
- PVCs (permanent virtual circuits), 98

## Q-R

- QAM-256, 463
- QAM-64, 463
- RAM (random-access memory), 187, 201
- RARP (Reverse Address Resolution Protocol), 130–132
- read-only mode (Flash memory), 196
- reassembly, 102
- recalling commands, 180
- Redirect ICMP message, 382
- reducing collisions with LAN switching, 60–63
- reliability of TCP, 155
- removing configuration files from NVRAM, 190
- repeaters, 55
- resume command, 391
- ring topologies, 286
- RIP (Routing Information Protocol), 411–413
  - IP configuration, 486–487
  - versus IGRP, 416, 419, 424
- RIPv2, 414
- RJ-45 connectors, 290
- ROM (read-only memory), 187, 201
- root bridge (Spanning Tree), 250
- root port (Spanning Tree), 251, 254
- routed protocols, 407, 422

## routers

- auxiliary connections, configuring, 177, 200
  - bandwidth, configuring, 380
  - basic administration, 370–372
  - clock rate, configuring, 380
  - configuration
    - IP*, 387
    - IP RIP*, 486–487
  - configuration files, copying, 189–190
  - configuration register, 199, 203
  - configuring with setup mode, 190–194
  - console connections, configuring, 177, 200
  - interfaces, numbering, 187
  - IP address, configuring, 372–375
  - IP configuration commands, 368–369
  - memory, 187
    - Flash*, 187, 202
    - NVRAM*, 187, 202
    - RAM*, 187, 201
    - ROM*, 187, 201
  - multiple Telnet connections, 178
  - neighboring device discovery, 392–395
  - ports
    - auxiliary ports*, 177
    - console ports*, 177
  - routing table, configuring, 376–379
  - running configuration, viewing, 190
  - Telnet connections
    - configuring*, 177, 200
    - suspend function*, 389–391
- routing, 114. *See also* routing protocols**
- address resolution, 135
  - at network layer, 114–116, 135
    - data-link layer interaction*, 116–117
- routing loops, STP, 248–249**
- convergence, 251
  - designated bridges, 250
  - forwarding state, 251, 254
  - root bridges, 250
- routing protocols, 119, 133, 407, 421–422**
- balanced hybrid protocols,
    - EIGRP, 419–420
  - BGP, 410–411
  - comparison of, 408
  - decision process logic, 134–135

- distance vector, 135, 140, 407
  - IGRP*, 414–416
  - RIP*, 411–412
  - RIPv2*, 414
  - RIPv1*, 413
- dynamic, 407–408
- exterior routing protocols, 408
- goals of, 135–136, 140
- interior routing protocols, classifying, 409–410
- link-state, 416–417
  - integrated IS-IS*, 418–419
  - OSPF*, 417–418
- routing tables, 136–137
  - displaying, 369
- routing updates, 411
- running configuration, 188
  - viewing, 190

**S**

- same-layer interaction, 24–26
- SAP (Service Advertising Protocol), 67
  - filters, configuring, 486–487
- scenarios, network deployment
  - configuration, 486, 488
  - planning phase, 483, 485
  - verification, 488–490, 492
- SDH (Synchronous Digital Hierarchy), 100
- SDLC (Synchronous Data Link Control), 94, 105
- security, accessing CLI passwords, 177
- seeding routing tables with connected routes, 376–379
- segmentation, 160–161
- segmenting LANs
  - with switches, 240–241, 246
    - full-duplex*, 242
  - with transparent bridges, 236
- Service Advertising Protocol. *See* SAP
- session layer (OSI model), 33
- setup command, 190
- setup mode, router configuration, 190–194
- shared Ethernet, 56
- shielding, 288
- show access-lists command, 489
- show cdp entry command, 393

- show cdp interface command, 395
- show cdp neighbor command, 393
- show cdp neighbor detail command, 394
- show flash command, 196
- show hosts command, 369
- show interface command, 376, 489
- show interfaces command, 369
- show ip arp command, 492–493
- show ip host command, 388
- show ip interface command, 369, 377
- show ip interface brief command, 369, 376, 379, 489
- show ip protocol command, 490
- show ip route command, 373–379, 383, 397, 492
  - prefix notation, 375
- show running-config command, 371, 374–375, 380, 491
- signaling, 450
- single-ring topologies, 286
- sliding windows, 157
- SM (single-mode) fiber, 294
- SNA (Systems Network Architecture), 20
- SNAP (Subnetwork Access Protocol), 67
- SNMP (Simple Network Management Protocol), 154
- sockets
  - multiplexing, 152, 154
  - port numbers, 154
- SONET (Synchronous Optical Network), 100
- Source Quench ICMP messages, 382
- Spanning Tree. *See* STP
- SPF (shortest path first) algorithm, 416
- splitting, 461
- SS7 (Signaling System 7), 450
- ST connectors, 295
- standard IP access lists, configuring, 486–487
- standard IPX access lists, configuring, 486–487
- standards
  - DSL-related, 456–457
  - Ethernet, 52
    - 10BASE2/10BASE5*, 53–55
    - 10BASE-T*, 56–60
  - Ethernet cabling, 298
  - for modems, 446–447

- IEEE standards, LANS, 53
  - UTP, 290
  - WAN cabling, 85–86
    - clock rate*, 88
    - link speeds*, 89–90
    - maximum speeds*, 87
  - star topologies, 283
  - startup configuration, 188
  - status LEDs on Cisco 2950, 216–217
  - store-and-forward switching, 242–243, 252
  - storing IOS images in Flash memory, 194–197
  - STP (Spanning Tree Protocol), 248–249
    - convergence, 251
    - designated bridges, 250
    - forwarding state, 251, 254
    - root bridges, 250
  - straight-through cables, 49, 57
  - strand, 295
  - study tips for exam, 479–494
  - subcommands, 182
  - subnet chart, creating, 340–350
  - subnet masks, 327
    - display types, setting, 369
  - subnetting, 124–127, 321
    - binary conversion, 324–326
    - Boolean AND operation, 333–335
    - broadcast address, identifying, 335–336
    - deriving subnet broadcast address, 343
    - directly connected subnets, 412
    - identifying valid IP addresses, 336–337
    - subnet masks, 344–346
  - suspend function (Telnet), 389–391
  - switches,
    - Cisco 2950, 213
      - CatOS*, 214
      - CLI*, 215
      - configuring*, 220
      - initialization*, 216–217
      - POST*, 216–217
    - store-and-forward processing, 242,
    - VLANs, 263–264
      - creating*, 264–265
      - trunking*, 265–267
  - switching
    - autonegotiation, 244
    - cut-through, 242–243, 253
    - fragment-free, 242–243, 253
    - LANs, 240–241, 246
      - full-duplex*, 242
      - internal processing*, 243, 252
    - Layer 4 switching, 271
    - multilayer switching, 272
    - neighboring device discovery, 392–395
    - store-and-forward, 242, 253
    - VLANs
      - Layer 2 switching*, 268
      - Layer 3 forwarding*, 268–270
  - SYN field, TCP connection
    - establishment, 158
  - synchronization, 94
  - Synchronous Data Link Control. See SDLC
  - synchronous serial interfaces, 85–86
  - synchronous serial leased lines, 94
  - syslog messages, 181
- ## T
- T1 lines, 90
  - T1 mux, 95, 589
  - TA (terminal adapter), 448
  - TCP (Transmission Control Protocol), 150
    - connection establishment/termination, 158–159
    - connection-oriented nature of, 159
    - data segmentation, 160–161
    - error recovery, 155
    - features of, 150
    - flow control, 156–157
    - forward acknowledgment, 155
    - functions of, 161
    - headers, 150
    - multiplexing, 151–152
      - sockets*, 152–154
    - ports, Layer 4 switching, 271
    - versus UDP, 161–163
    - well-known port numbers, 154
  - TCP/IP, 20–21
    - application layer, 22–24
    - ICMP, 381
      - Destination Unreachable messages*, 385–387
      - Echo messages*, 382, 387
      - Echo Request/Reply messages*, 382–384
      - Parameter Problem messages*, 382
      - Redirect messages*, 382
      - Source Quench messages*, 382
      - Time Exceeded message*, 382

- internetwork layer, 26–27
- IP addressing, 120
  - address classes*, 122–124, 319–320
  - CIDR, 351
  - configuring*, 368–379
  - deriving subnet broadcast address*, 343
  - dotted-decimal notation*, 120
  - grouping concepts*, 121
  - host name configuration*, 387–388
  - identifying address structure*, 329–332
  - naming configuration*, 388
  - NAT, 354
  - network numbers*, 123, 139
  - private addressing*, 354
  - subnet list chart, creating*, 342–350
  - subnetting*, 124–127, 321–326
- network interface layer, 27–28
- network layer utilities
  - ARP, 127, 129
  - BOOTP, 130, 132
  - DHCP, 131–132
  - DNS, 128–129
  - ICMP echo, 130
  - ping command*, 130
  - RARP, 130–132
- TCP
  - features of*, 150
  - forward acknowledgement*, 155
  - functions of*, 161
  - headers*, 150
- transport layer, 24–25
- UDP
  - data transfer*, 162
  - DNS, 162
  - functions of*, 166
  - NFS, 162
- telcos, 95, 580
  - digital networks, 90
- Telnet
  - router connections
    - configuring*, 177, 200
    - multiple*, 178
  - sessions, resuming, 391
  - suspend function, 389–391
- telnet command, 389
- terminal history size command, 179
- terminal ip netmask-format command, 369, 374
- TFTP (Trivial File Transfer Protocol), 155
- TIA (Telecommunications Industry Association), 86–87
- Time Exceeded ICMP message, 382
- Token Ring
  - IEEE standards, 53
  - ring topologies, 286
- topologies, 283–284
  - full mesh, 285
  - logical, 283
  - physical star, 286
  - ring, 286
- trace command, 492–493
- transparent bridging, 236
- transport layer (OSI model), 24–25, 33
  - connection-oriented/connectionless protocols, 159, 164
  - features, 149
  - TCP, 150–152, 154
    - connection establishment/termination*, 158–159
    - data segmentation*, 160–161
    - error recovery*, 155
    - flow control*, 156–157
    - versus UDP*, 162–163
  - UDP
    - functions of*, 162
    - multiplexing*, 161
- troubleshooting TCP/IP with ICMP, 381, 383
  - destination unreachable messages, 385–386
- trunking VLANs, 265
  - 802.1q, 266–267
  - Cisco ISL, 266
- twisted-pair cabling, 288
  - UTP, 289–290
    - connectors*, 290–291
    - standards*, 290
- two-way communication, cable modems, 462
  - upstream, 463
- two-wire circuits, 95, 582

## U

- UAAs (universally administered addresses), 64
- UDP (User Datagram Protocol)
  - data transfer, 162
  - DNS, 162
  - functions of, 162, 166
  - multiplexing, 161
  - NFS, 162
  - ports, Layer 4 switching, 271
  - versus TCP, 161–163
- unicast MAC addresses, 64
- universally administered addresses (UAAs), 64
- unknown unicast frames, forwarding, 240
- unreachable codes (ICMP), 385
- updating configuration files, 182
- upgrading images into Flash memory, 194–197
- upper layers of OSI model, 32
- upstream data, 463
- user EXEC mode (Cisco IOS), 178, 181, 201
- UTP (unshielded twisted-pair), 289–290
  - connectors, 290–291
  - standards, 290

## V

- V.35 WAN cabling standard, 86
- VCI (Virtual Channel Identifier), 101
- VCs (virtual circuits), 98
- viewing running configuration, 190
- VLANs, 263–264
  - creating, 264–265
  - Layer 2 switching, 268
  - Layer 3 forwarding, 268–270
  - trunking, 265
    - 802.1q, 266–267
    - Cisco ISL, 266
- VPI (Virtual Path Identifier), 101

## W

- WANs
  - asynchronous serial leased lines, 95, 588
  - ATM, 101
    - cell reassembly, 101
    - VPI, 101
  - cabling standards, 85–86
    - clock rate, 88
    - link speeds, 89–90
    - maximum speeds, 87
  - four-wire circuits, 95
  - Frame Relay, VCs, 98
  - ISDN, 447–448
    - call setup, 449–450
    - channels, 449
    - installing, 453
    - out-of-band signaling, 450
    - typical uses, 451–453
  - leased lines, 82
  - packet-switched, Frame Relay, 96–99
  - point-to-point, 81, 83
    - connectivity, 84–85
    - HDLC, 91–92
    - PPP, 92, 94
  - PPP, 94, 105
    - LCP, 93
  - protocols
    - HDLC, 95, 580
    - LAPB, 95, 580
    - LAPD, 94, 105
    - PPP, 95, 580
    - SDLC, 94, 105
  - SONET, 100
  - synchronous serial leased lines, 94
  - two-wire circuits, 95, 582
- well-known port numbers, 154
- windowing, TCP flow control, 157
- wireless communications, 300
  - 802.11 WLANs, 301–302
- wiring. *See* cabling
- WLANs, 300
  - 802.11, 301–302
- WWW (World Wide Web), 154

## X-Z

- X.21 WAN cabling standard, 86