

---

# Index

## Symbols

“Project Angel”, 6, 7

## Numerics

1x evolution data optimized (1x EV-DO), 14,  
213, 275, 369, 387, 398, 410

3G cellular systems, 14

## A

access control, 247

access service network (ASN), 337, 357

access service network gateway (ASN-GW),  
57, 338

*See also* WiMAX Forum Network  
Working Group (NWG)

active set, 53

adaptive modulation and coding (AMC), 37,  
43, 206, 208, 289, 290, 299, 323,  
371, 377, 378, 394, 398

additive white Gaussian noise (AWGN), 25,  
105, 107, 140, 141, 153, 155, 164,  
187, 210, 365, 370, 409

adjacent subcarrier permutation, 217

admission control, 225–226

advanced antenna systems (AAS), 38, 55,  
287, 323

Advanced Encryption Standard (AES), 38,  
241–246

advanced wireless services (AWS), 21

advertised specifications (ADSpec), 229

advertised window, 260

aggregate handling, 227

AK Transfer Protocol, 349

amplitude modulation/amplitude modulation  
(AM/AM), 131

amplitude modulation/phase modulation  
(AM/PM), 131

analog-to-digital convertor (ADC), 68, 132  
*See also* digital-to-analog convertor  
(DAC)

anchor

base stations (BS), 53, 330, 331

data path function, 354

PC, 361

*See also* base station (BS)

angle of departure (AoD), 100

angular spread (AS), 90, 100, 103

antenna grouping, 297

antenna selection, 297

application

function (AF), 351, 352

programming interfaces (API), 234

service providers (ASP), 337

array, 150

array response vector, 170

association levels, 328

assured forwarding (AF), 230

asymmetric key, 242, 245

AT&T, 7

authentication, 247, 346–348

key, 348

relay protocol, 349

server, 247

authorization module, 319

automatic repeat requests (ARQ), 312, 323, 330, 355, 366, 385, 409

automatic retransmissions requests (ARQ), 38, 208, 209, 254, 262, 263, 272, 277, 307, 308

## B

backoff window, 317

back-of-the-envelope, 373

bandwidth, 313

base station, 57, 338

controller (BSC), 58, 339

transceiver (BST), 58

*See also* WiMAX Forum Network Working Group (NWG)

basic capabilities, 322

beamforming, 55, 149, 166, 169–172, 189, 190, 292, 368, 387, 389, 407–410, 419–422

direction of arrival (DOA), 169, 170

eigenbeamforming, 169–173

Bell Labs layered space/time (BLAST), 178

best-effort service (BE), 228, 318

binding update, 256

bit error probability (BEP), 140, 152–157, 164

bit error rate (BER), 191, 279, 366, 383, 389

block error rate (BLER), 105, 373

breakout gateway control function (BGCF), 239

broadband fading, 104

broadband radio services (BRS), 19

burst profile, 206, 217, 283

burst time division multiplexing (TDM), 8  
*See also* time division multiplexing

## C

cable modem technology, 3

call drop, 330

call session control functions (CSCF), 239

call-processing language (CPL), 234

care-of address (CoA), 255

colocated CoA (CCoA), 358

carrier sense multiple access (CSMA), 15, 201, 204

cell, 25, 56, 78, 183, 185, 329, 369, 401–413, 421

cellular architecture, 25, 78

certification profile, 34

challenge handshake authentication protocol (CHAP), 248

channel

coherence bandwidth, 115

coherence time, 70

estimation, 187

quality feedback (CQI), 303

quality indicator channel (CQICH), 45, 368, 376, 381

reciprocity, 189

sounding, 189, 297

state information (CSI), 287

chase combining, 56, 278

cipher-block chaining message-authentication code (CBC-MAC), 245

ciphertext, 242

circular convolution, 117

client context, 355

client-based mobile (CMIP), 259

clipping, 135, 136

closed loop, 158

closed loop-transmit diversity, 164

*See also* transmit diversity

cochannel-reuse ratio, 79

code division multiple access (CDMA), 5, 8, 108, 185, 199–201, 330, 375

codebook based feedback, 297

codecs, 239  
coherence  
    bandwidth, 86, 114, 167, 285–287, 296, 376, 377  
    distance, 90  
    time, 87, 119, 166, 167, 210, 303, 381  
colocated foreign agent, 255  
coloring matrix, 406  
common gateway interface (CGI), 234  
congestion window, 261  
congestion-avoidance, 261  
conjugate transpose, 168  
connection identifier (CID), 48, 309, 315–321, 345  
    secondary CIDs, 316  
connectivity service network (CSN), 57, 337  
    *See also* WiMAX Forum Network Working Group (NWG)  
controlled load services, 228  
conventional transpose, 168  
correspondent node (CN), 255  
COST-231-Hata model, 402, 424  
counter mode, 244  
customer premise equipment (CPE), 10, 60, 61  
cyclic prefix, 118–121, 187, 217, 276, 281, 301, 332, 371

## D

data, 108  
    path function (DPF), 354  
    region, 44, 283, 290, 312, 385  
    subcarriers, 282  
decision-feedback equalizers, 109  
decryption, 242  
delay spread (DS), 70, 86, 103, 113, 117, 121, 142, 285, 376, 383  
deployment modularity, 336

differentiated services (DiffServ), 229  
digital audio radio services (DARS), 20  
digital subscriber line (DSL), 3, 39, 199, 210, 336  
digital-enhanced cordless telephony (DECT), 5  
digital-to-analog convertor (DAC), 68, 131, 132  
    *See also* analog-to-digital convertor  
discrete Fourier transform (DFT), 40, 117–118, 136, 187, 383  
dispersion, 97  
distortion, 189  
distributed coordination function (DCF), 201  
distributed subcarrier permutation, 217  
distribution systems, 6  
diversity, 105, 150, 422  
    order, 152  
    precoding, 167  
    set, 53, 330  
domain name system (DNS), 239  
Doppler power spectrum, 87  
Doppler spread, 25, 40, 43, 71, 87–89, 188, 287, 303, 368, 381  
double space/time transmit diversity (DSTTD), 161  
    *See also* transmit diversity  
downlink channel descriptor (DCD), 291  
dropping probability, 251  
dynamic subcarrier allocation, 202

## E

edge effect, 405  
effective code rate map (ECRM), 408  
effective isotropic radiated power (EIRP), 20  
eigenbeamforming, 169–173  
eigenchannel, 171

- Electronics and Telecommunications Research Institute (ETRI), 13
  - empirical path loss formula, 72
  - encryption key, 242
  - equal gain combining (EGC), 157
  - Erceg model, 402, 424
  - Ethernet convergence sublayer (ETH-CS), 342
  - European Telecommunications Standards Institute (ETSI), 8, 33
  - expedited forwarding (EF), 230
  - exponentially effective SINR map (EESM), 408
    - See also* signal-to-interface-plus noise ratio (SINR)
  - extended real-time polling service (ertPS), 318
    - See also* polling
  - extensible authentication protocol (EAP), 39, 248, 249, 345, 346, 353
    - See also* authentication
  - extensible authentication protocol (EAP) method, 249
- F**
- fading, 84, 110, 114, 151–154, 159–163, 202, 289, 320
    - See also* multipoint fading
  - fast base station switching (FBSS), 53, 254, 353
  - fast Fourier transform (FFT), 37, 100, 117, 119–122, 128, 142, 185–186, 272, 285
  - fast recovery, 261
  - fast retransmit, 261
  - Federal Communications Commission (FCC), 6, 109
  - fiber-to-the-home (FTTH) system, 4
  - final sleep window size, 326
  - first-generation broadband systems, 6
  - fixed broadband wireless applications, 4
    - consumer and small-business broadband, 10
    - T1 emulation for business, 11
    - Wi-Fi hotspots, 12
  - fixed WiMAX, 271
  - flash-OFDM, 13
    - See also* orthogonal frequency division multiplexing
  - flow context, 264
  - FlowSpec, 228
  - foreign agent (FA), 255
  - forking, 237
  - forward equivalence class (FEC), 231
  - forward error correction (FEC), 37, 272, 293, 330, 370–373, 385, 409
  - forward information base (FIB), 232
  - frame control header (FCH), 44, 291, 301, 319, 410
  - frame error rate (FER), 105
  - free-space, 422
    - pathloss formula, 70
  - frequency
    - diversity, 107, 149
    - division duplexing (FDD), 8, 36, 38, 44
    - division multiple access (FDMA), 200–202
    - equalization, 122
    - hopping diversity code (FHDC), 295
    - planning, 78
    - reuse, 25, 55, 56, 78–82, 183, 287, 401, 413, 419, 421
    - synchronization, 124
  - full-buffer traffic model, 412
  - function context, 355
  - functional decomposition, 336

**G**

generic MAC header (GMH), 48  
*See also* media access control

generic routing encapsulation (GRE), 342

global system for mobile communications (GSM), 14, 58, 108, 109, 339

guaranteed services, 228

**H**

handoff (HO) function, 355

handoff management, 250

handoff rate, 251

hard handover, 53

hashed message authentication code, 322

Hermitian transpose, 168

high speed downlink packet access (HSDPA), 14, 60, 108, 202, 213, 275, 369, 387, 398, 410

high-definition TV (HDTV), 4

high-performance metropolitan area network (HIPERMAN), 8, 33

high-power amplifier (HPA), 131

home  
  address (HoA), 255  
  agent (HA), 255  
  subscriber server (HSS), 239

hybrid-ARQ, 56, 278  
*See also* automatic retransmissions requests

Hypertext transfer protocol (HTTP), 233

**I**

i-Burst technology, 13

idle mode, 52

incremental redundancy, 56, 278

initial ranging, 320, 321

initial sleep window size, 326

input backoff (IBO), 132

Institute of Electrical and Electronics Engineers (IEEE)  
  Globecom, 146

Institute of Electrical and Electronics Engineers (IEEE) standards, 8

802.11, 67, 271

802.15.3, 121

802.16, 33, 34, 37, 68, 223, 309, 318, 338, 342, 360

802.16 group, 8, 33, 34, 67

802.16-2004, 8, 34, 41, 271, 335

802.16-2005, 9, 34–38, 50, 52, 57, 137, 254, 271, 272, 290, 292, 324, 335, 348, 365, 392, 401

802.16a amendment, 8

802.20, 17

802.22, 17

802.3, 313

integrated services (IntServ), 227

intercarrier interference (ICI), 281

interference limited, 73

Internet group management protocol (IGMP), 339

Internet Protocol television (IP-TV), 13

intersymbol interference (ISI), 24, 39, 40, 89, 107, 109, 113, 117, 142, 281

inverse fast Fourier transform (IFFT), 40, 117, 119, 142, 204, 282, 300  
*See also* fast Fourier transform

IP convergence sublayer (IP-CS), 342

**K**

key  
  distributor, 348  
  encryption key (KEK), 339, 349  
  receiver, 348

**L**

label switching routers (LSR), 232  
 label-edge router (LER), 231  
 lightweight directory access protocol (LDAP), 225  
 linear equalizer, 109  
 linear minimum mean square error, 383  
 link-level simulations, 404  
 local multipoint distribution systems (LMDS), 6  
 local policy function (LPF), 352  
 location
 

- management, 249
- register (LR), 250, 361
- server, 235
- update, 250

 lognormal shadowing, 110

**M**

MAC service data units (MSDUs), 356  
 macro diversity handover (MOHO), 53, 353  
 master session key (MSK), 348  
 Matlab function, 100  
 maximal ratio combining (MRC), 154, 156  
 maximum
 

- backoff window, 317
- Doppler, 88
- likelihood detection, 109, 366, 396
- sum rate (MSR) algorithm, 210

 MCI WorldCom, 6  
 mean instantaneous capacity (MIC), 408  
 mean square error (MSE), 299, 394  
 media access control (MAC), 8, 33, 36, 38, 47, 48, 53, 201, 223, 271, 307, 335, 344, 360, 366, 410
 

- managements messages, 302
- protocol data units (MPDUs), 47
- service data units (MSDUs), 47

media gateway (MG), 239  
 media gateway control function (MGCF), 239  
 median pathloss models, 402
 

- COST-231-Hata model, 402, 424
- Erceg model, 402, 424
- Okumura-Hata model, 402, 422
- Walfisch-Ikegami model, 402, 426

 message digest, 246  
 minimum signal level (MSL), 251  
 mobile broadband, 4
 

- mobility, 4
- nomadicity, 4
- wireless applications, 12, 13
- See also* fixed broadband wireless

 mobile node (MN), 255  
 mobile stations, 45, 80, 150, 223, 259, 358, 401, 422  
 mobile WiMAX, 272
 

- See also* WiMAX

 mobility, 4, 28, 33, 39, 52, 89, 98, 199, 249, 254, 259, 320, 324, 327, 335, 352–358, 424
 

- handoff, 28
- management, 28, 250
- proxy agent (MPA), 259
- roaming, 28

 mode of operation, 244  
 modulus, 247  
 multiantenna processing, 8  
 multicarrier concept, 110  
 multicarrier modulation, 39, 114, 149  
 multicast and broadcast services (MBS), 54  
 multichannel multipoint distribution services (MMDS), 6  
 multipath fading, 24, 84, 104, 108, 368, 374, 403
 

- See also* fading

 multipath intensity profile

power-delay profile, 86  
multiple input/multiple output (MIMO), 149,  
366, 368, 374, 383, 387, 389, 392–  
398, 401, 406, 410, 419, 422  
multiple input/single output (MISO), 149  
multiplexing, 150, 366, 387, 392  
multiprotocol label switching (MPLS), 231,  
355  
multiuser, 199

## N

Nakagami-m fading, 95  
narrowband (flat) fading, 104, 105  
*See also* fading  
narrowband wireless local-loop system, 5  
network  
access provider (NAP), 337  
address translation (NAT), 256  
entry, 319  
reference model (NRM), 337  
service provider (NSP), 337  
timing protocol (NTP), 240  
non-line-of-sight (NLOS) system, 113, 374,  
422  
nonlinear equalizer, 109  
non-real-time polling services (nrtPS), 318  
*See also* polling  
nonrepudiation, 246  
null subcarriers, 282  
null-steering beamformer, 171  
Nyquist sampling, 134

## O

Okumura-Hata model, 402, 422  
open loop transmit-diversity, 158  
ordered successive interference cancellation,  
366, 396  
orthogonal communication, 200

orthogonal frequency division multiple access  
(OFDMA), 8, 34–41, 60, 199, 209,  
214, 216  
orthogonal frequency division multiplexing  
(OFDM), 8, 34–39, 60, 89, 97, 98,  
109, 113, 117, 128, 159, 168, 182,  
184, 199, 203, 271, 368, 375, 383,  
384, 416  
history, 9  
OFDM symbol, 117

## P

packet data unit (PDU), 48  
packet error rate (PER), 105  
packet header suppression (PHS), 309  
paging, 250  
agent (PA), 361  
controller (PC), 361  
group (PG), 327, 361  
group update, 327  
pairwise master key (PMK), 348  
partial usage of subcarriers (PUSC), 43, 285,  
286, 290, 298, 323, 371, 376, 398,  
416  
password authentication protocol (PAP), 248  
pathloss, 24, 61, 69–73, 84, 93, 110, 154,  
211, 406, 422, 424  
peak-to-average ratio (PAR), 131–134, 140,  
302  
peak-to-average-power ratio (PAPR), 131, 204  
per hop behavior (PHB), 230  
per-flow handling, 226, 228  
periodic ranging, 320  
personal communications services (PCS), 6,  
424  
personal mobility, 238  
PHY-layer data rate, 46  
pilot subcarriers, 282

pilot symbol, 130  
plaintext, 242  
point-of-attachment (PoA), 344  
point-to-multipoint applications, 10, 11, 35  
point-to-point applications, 10  
policy decision points (PDP), 225  
policy enforcement points (PEP), 225, 339  
polling, 48, 316  
portability, 29, 52, 104, 336, 360  
power-saving class, 326  
precoding codebook, 189  
primary, 316  
private key, 247  
    Privacy Key Management Version 2  
    (PKMv2), 345, 348  
probability density function (PDF), 205  
propagation models, 422  
proportional fairness (PF) scheduler, 213, 416  
proportional rate constraints (PRC) algorithm,  
    212  
protocol data unit, 307  
provisioned QoS parameter set, 319  
    *See also* quality of service (QoS)  
proxy mobile IP (PMIP), 259  
proxy server, 235  
public exponent, 247  
public key infrastructure (PKI), 245, 247  
public switched telephone network (PSTN),  
    58, 239  
pull model, 346

**Q**

quality of service (QoS), 26, 27, 38, 39, 44,  
    48, 57, 204, 223–225, 258, 265,  
    290, 307, 335, 346, 349  
    active parameter set, 319  
    policy management, 225  
quantized channel feedback, 297

**R**

radio  
    frequency (RF), 68, 117, 131, 287  
    resource agent, 359  
    resource controller (RRC), 339, 359  
    resource management (RRM), 338, 358,  
        359  
rake receivers, 108  
random-access, 201  
ranging, 217  
Rayleigh  
    distribution, 94  
    fading, 91, 93, 104, 132, 155, 164, 205,  
        206, 365, 403  
real time  
    control protocol (RTCP), 240  
    polling service (rtPS), 318  
    transport (RTP), 227  
receive diversity, 163  
    *See also* diversity  
received signal strength indicator (RSSI), 303  
receiver, 366  
redirect server, 235  
Reed Solomon (RS), 275  
reference points, 58, 336  
registrar server, 235  
relaying context function, 355  
relaying data path function, 355  
    *See also* data path  
relaying HO function, 355  
remote access dial-in user service (RADIUS),  
    242, 247  
request for comments (RFC), 230, 345–349,  
    356, 358  
resource reservation protocol (RSVP), 226,  
    228, 339  
resource-retain timer, 329  
reverse tunneling, 256

## Ricean

- distribution, 93, 94, 95
- fading, 95, 403

robust header compression (ROHC), 264

round robin (RR) scheduler, 202, 416

route optimization, 256

**S**

samples, 95

scanning intervals, 53

scheduling service, 317

second-generation broadband wireless systems, 8

*See also* wireless broadband

sectoring, 82

security, 29, 33, 39, 53, 223, 235, 241, 247, 335, 345–349

segmentation, 287

selection combining (SC), 154, 155

selection diversity, 107

*See also* diversity

selectivity, 97

semempirical channel model, 103

server context, 355

service flow, 309, 315, 318, 339, 345, 348, 350, 361

authorization (SFA), 339, 351

classes, 319

identifier (SFID), 318, 324

management (SFM), 351

service level agreements (SLA), 226, 230, 340

service mobility, 238

Service Provider Working Group (SPWG), 335

serving data path function, 354

*See also* data path

serving HO function, 355

*See also* handoff function

session, 233

description protocol (SDP), 234

initiation protocol (SIP), 233, 265

mobility, 238

shadowing, 24, 69, 74, 84, 92, 93, 103, 110, 402, 424

signaling, 225

signal-mapping techniques, 142

signal-to-interface-plus-noise ratio (SINR), 44, 55, 73, 74, 80, 81, 105, 153, 157, 172, 173, 183, 206, 209–218, 251, 300, 302, 328, 407, 408

signal-to-interference-plus-noise ratio (SINR), 26, 303

signal-to-noise-plus-distortion ratio (SNDR), 140

single input/multiple output (SIMO), 149, 387

singular-value decomposition (SVD), 179, 180

sleep mode, 51

slot, 44, 107, 290, 312, 408

slow-start threshold, 261

space/time block codes (STBC), 158, 160, 167

spatial diversity, 106, 149, 150

*See also* diversity

spatial multiplexing (SM), 55, 161, 167, 174, 175, 292

*See also* automatic retransmissions requests

*See also* multiplexing

spectral regrowth, 136

spread spectrum, 108

Sprint, 6

standards

*See also* Institute of Electrical and Electronics Engineers (IEEE)

statistical channel model, 91  
 stop and wait ARQ, 56  
 stream control transport protocol (SCTP), 234  
     *See also* transport control protocol  
 subcarrier permutation, 160, 273, 283  
 subchannelization, 43, 217, 273, 275  
 subpacket identity (SPID), 279  
 subscriber stations, 23, 43, 45, 51, 54  
 supplicant, 247  
 symmetric key, 242  
 synchronization, 126, 127, 130, 185, 200,  
     217, 240, 253, 280, 290, 300, 309,  
     319, 329, 355, 368  
 system identity information advertisement  
     (SII-ADV), 344  
 system profile, 34  
 system-level simulations, 404

## T

tap-delay line (TDL), 69  
 target data path function, 355  
 target HO function, 355  
 terminal mobility, 238  
 Third-generation Partnership Project (3GPP),  
     14, 58, 101, 102, 239, 335, 369  
 tile usage of subcarriers (TUSC), 287  
 time division  
     duplexing (TDD), 8, 16, 36–38, 44, 55,  
         158, 189, 287, 296, 323, 413  
     multiple access (TDMA), 192, 200, 201,  
         375  
     multiplexing, 33, 35  
     synchronous CDMA (TD-SCDMA), 14  
 time/frequency uncertainty principle, 88  
 timing synchronization, 124  
 traffic  
     encryption key (TEK), 339, 348  
     engineering (TE), 232

    specifications (TSPEC), 228  
 transmission, 108, 366  
 transmit  
     diversity, 55, 160, 163  
     selection diversity (TSD), 165, 167  
     spatial diversity, 157  
     *See also* diversity  
 transport control protocol (TCP), 227, 260,  
     278  
 transport-layer security (TLS), 234  
 triangular routing, 255  
 two-ray approximation, 70  
 type of service (TOS), 229

## U

ultra high frequency (UHF), 21  
     *See also* frequency  
 unicast, 316  
     *See also* polling  
 universal mobile telephone system (UMTS),  
     14  
 unlicensed national information infrastructure  
     (U-NII), 20  
 unsolicited grant services (UGS), 316, 326  
 uplink channel descriptor (UCD), 291  
 user agents (UA), 234  
 user datagram protocol (UDP), 234

## V

very high data rate digital subscriber loop  
     (VDSL) system, 4  
 video on demand (VoD), 4  
 virtual local area networking (VLAN), 343  
 virtual path identifier/virtual circuit identifier  
     (VPI/VCI), 232  
 voice telephony, 5, 223, 230  
 voice-over-internet protocol (VoIP)  
     technology, 4, 39, 44, 50, 199, 251,  
     259, 307, 309, 401

**W**

Walfisch-Ikegami model, 402, 426

Wi-Fi Alliance, 9

Wi-Fi based-systems, 15

*See also* fixed broadband wireless applications

WiMAX

adaptive modulation and coding, 26

business challenges, 21, 22

efficient multiaccess techniques, 26

fixed, 271

Forum, 7, 9, 18

Internet Protocol (IP), 30

physical layer (PHY), 37, 39, 77, 223, 271, 307, 315, 320, 335, 360, 366, 410

spatial multiplexing, 26

spectrum scarcity, 25

technical challenges, 23–25, 31

versus 3G and Wi-Fi, 16

WiMAX Forum, 410

WiMAX Forum Network Working Group (NWG), 37, 57

wireless

broadband (WiBro), 7, 43, 282

channel modeling, 402

communications services (WCS), 7

local-loop (WLL) system, 5

metropolitan area network (wireless MAN), 8, 34, 271

regional area networks (WRAN), 17

wraparound, 405

**Z**

zero prefix, 121

zero-forcing detector, 176