
INDEX

Numerics

- 1x Radio Transmission Technology (1xRTT), 371
- 3GPP (Third-Generation Partnership Project),
 - 366–367, 370
 - architecture, 379–380
 - QoS, 380
 - Release 99 (R99), 379
 - structure, 377
 - WLAN integration, 390

A

- AAL5 (ATM Adaptation Layer 5), 185
- AC (Attachment Circuit), 126
- AC System Error, 191
- Accept All Requests, authentication and, 482
- access
 - bit stream, 249–259
 - enhanced Internet, 62
 - GAN, 391–392
 - high-availability
 - broadband, 170–181
 - Ethernet architecture, 175–176
 - IGMP proxy, 102–103
 - last mile broadband, 219
 - ADSL, 220, 227
 - ADSL2, 227–230
 - ADSL2+, 227–230
 - SHDSL, 235
 - VDSL/VDSL2, 230–235
 - POTS to DSLAMs, 64
 - protocols, 186
 - DHCP, 196–207
 - IPv6 environments, 216
 - PPP, 186–196
 - selecting, 207–216
- access node (AN), 233
- Access Node Control Protocol (ANCP), 357, 467
- Access-Accept packet, 282
- Access-Request packet, 274
- Accounting-Alive packet, 274
- Accounting-Start packet, 274
- Accounting-Stop packet, 274
- acknowledgment (ACK), 314
- acquisition servers (A-servers), 43
- Address Resolution Protocol. *See* ARP
- addresses
 - allocation, 198–207
 - assigning, 454, 456
 - compatibility, 414
 - customer LANs, 427–430
 - DA, 71
 - DHCP
 - assigning, 414–417
 - static, 417–419
 - IP. *See also* IP
 - Framed-IP-Addresses, 420
 - ranges, 414
 - local pools, 407–411

- MAC
 - pseudowires, 127
 - resolving, 418
 - scaling, 154
 - NAPT, 158
 - NAT, 158
 - PPP, 412–419
 - remote pools, 411–412
 - SAs, 489
 - single source, 107–108
 - static PPP, 420–421
 - subscribers, 421–427
- address-pool-name command, 410–411
- ADSL (Asymmetric Digital Subscriber Line), 3, 5, 220, 227
- Ethernet DSLAMs, 121
- ADSL2, 227–230
- ADSL2+, 31, 227–230
- advanced dynamic service provisioning, 459–467
- Advances to IMS (A-IMS), 388–389
- advantages
 - of DHCP, 211–213
 - of PPPoE, 207–209
- advertising, targeted, 54
- aggregation
 - BNGs, 469
 - DSLAM, 122, 145–146
 - networks, 169–170
 - routes, 426
- A-IMS (Advances to IMS), 388–389
- Alcatel, 8
- algorithms
 - EPD PPD, 308
 - GCRA, 309
 - WRR, 319–322
- ALGs (Application Layer Gateways), 302
- allocating addresses, 198–207
- Amati, 8
- American National Standards Institute. *See* ANSI
- American Telephone and Telegraph Company.
See AT&T
- AN (access node), 233
- annexes
 - implementations, 239
 - series, 17
 - systems, 230
- ANCP (Access Node Control Protocol), 357, 467
- ANSI (American National Standards Institute), 6, 220
- anycast LNS, 281
- Application Layer
 - proxies, 475–477
 - SBCs as proxies, 475–477
- Application Layer Gateways (ALGs), 302
- application servers (ASs), IMS, 387
- applications
 - data rates, 31
 - wireless broadband, 365
 - CDMA evolution/3GPP2, 370–372
 - GSM evolution/3GPP, 367–370
 - IMT-2000, 365–366
- architecture
 - 3GPP, 379–380
 - BNG, 173–175
 - dialup provider-hosted L2TP, 263
 - DiffServ, 296–299
 - DSL, 21–29
 - end-to-end VoIP, 65
 - head-end, video, 41
 - high-availability
 - BNG element, 178–181
 - Ethernet access, 175–176
 - IMS, 366
 - IPTVe, 44
 - provider, 162–168
 - routers, 342–346
 - service VLANs, 157
 - triple-play QoS, 346
 - centralized BNGs, 351–355
 - distributed BNGs, 356–357
 - L2CP, 357
 - trust boundaries, 346–351
 - UMTS, 374–375
 - VLANs, 156–162
- ARIB (Association of Radio Industries and Businessmen, Japan), 370
- ARP (Address Resolution Protocol), 431, 418
- ARPU (Average Revenue Per User), 3
- ARQ (Automatic Retransmission reQuest), 401
- A-servers (acquisition servers), 43
- ASs (application servers), IMS, 387
- assigning
 - addresses, 414–417, 454–456
 - DHCP, 414–417
 - static DHCP, 417–419
 - static PPP, 420–421
 - BNG addresses, 407
 - services, 454, 456

-
- Association of Radio Industries and Businessmen, Japan (ARIB), 370
 - Asymmetric Digital Subscriber Line. *See* ADSL
 - Asynchronous Transfer Mode. *See* ATM
 - AT&T (American Telephone and Telegraph Company), 246
 - ATM (Asynchronous Transfer Mode), 2
 - bridged IP over, 198
 - DSLAMs, 13
 - interconnects, 249–253
 - PPPoA, 186, 188–190
 - PPPoE, 190–196
 - pseudowires, 123–144
 - ATM Adaptation Layer 5 (AAL5), 185
 - Attachment Circuit (AC), 126
 - attacks
 - DDoS, 488
 - DoS, 470–473
 - Attribute 242 filters, 456
 - authentication, 481
 - Accept All Requests, 482
 - DSLAM-to-BNG, 272–274
 - LAC-to-LNS, 274–276
 - optimizing, 482–483
 - RADIUS, 448
 - subscriber, 272–276
 - authorization
 - CoA, 413, 457, 480
 - line-based, 273
 - AutoDiscovery, 191
 - automated P2MP LSP provisioning, 93–96
 - automatic pool configuration, 412
 - automatic protection switching, 257
 - Automatic Retransmission reQuest (ARQ), 401
 - availability. *See also* HA
 - core networks, 106–115
 - Ethernet architecture, 175–176
 - measuring, 171–173
 - pseudowires, 177
 - troubleshooting, 171–173
 - Average Revenue Per User (ARPU), 3
- B**
- backbones (triple-play networks)
 - design, 67–68
 - highly available core networks, 106–115
 - MPLS, 68–79
 - multicast protocols, 79–96
 - running MPLS on BNGs, 96–106
 - backhaul networks, troubleshooting, 173
 - backplanes, 344
 - backward explicit congestion notification. *See* BECN
 - band plans, VDSL2, 233
 - bandpass filters, 4
 - bandwidth
 - CAC, 462–467
 - commands, 313
 - QoS, 291
 - base tunnel signaling, 142
 - basic dynamic service provisioning, 452–459
 - BE (best-effort) traffic, 292
 - BECN (backward explicit congestion notification), 298
 - Bell Telephone Company, 246
 - Bell, Alexander Graham, 245
 - Bellcore, 5
 - best-effort (BE) traffic, 292
 - BFD (Bidirectional Forwarding Detection), 97, 110, 213
 - BGCF (Breakout Gateway Control Function), 388
 - BGP (Border Gateway Protocol), route reflection, 153
 - Bidirectional Forwarding Detection. *See* BFD
 - billing platforms, 446
 - bit shifters, 29
 - bit streams, access, 249–259
 - blackhole routing, 489
 - BNGs (Broadband Network Gateways), 13, 469
 - architecture, 173–175
 - centralized, 351–355
 - connections, 97–99, 406–427
 - control plane security, 486–488
 - DHCP, 199, 206, 412–419
 - distributed, 356–357
 - DSLAMs, 38, 272–274
 - dual-stack models, 437
 - hardware, 178
 - high-availability element architecture, 178–181
 - IGMP proxy, 102–103
 - interface triggers, 480
 - L3VPNs, 69
 - Layer 3 wholesale networks, 260
 - local address pools, 407–411
 - MPLS, 96–106
 - packet filters, 489
 - PPP, 187
-

- PPPoE AutoDiscovery, 191
- rate-limiting L2TP, 265
- remote address pools, 411–412
- RPF checking, 472
- SFD, 487
- software, 179
- VoIP, 70

BOOTP (Bootstrap Protocol), 196

Border Gateway Protocol (BGP), route reflection, 153

boundaries, trust, 346–351

B-RAS (Broadband Remote Access Server), 13, 38

Breakout Gateway Control Function (BGCF), 388

bridged IP over ATM, 198

bridged mode, 192–193, 429

bridged RGs, DHCP with, 213

bridged virtual interface (BVI), 198

bridging traffic, 269

broadband access networks, L2TP, 263–269

Broadband Network Gateways. *See* BNGs

Broadband Remote Access Server (B-RAS), 13, 38

broadcast channels, 484–485

BSR (bootstrap router), 84

BT (U.K.), 389

buckets, 306

business connectivity, 59–63

business strategies, need for QoS, 292

BVI (bridged virtual interface), 198

C

cable patches, 248

CAC (Call Admission Control), 49, 300, 453, 462–467

Call Admission Control. *See* CAC

Call Session Control Function (CSCF), 386

Calling-Station-IDs, 448

CAP (Carrier Amplitude Phase), 220

Carrier-Supporting-Carrier VPNs, 78

catalogs, media, 54

CBR (constant bit rate) circuits, 197

CBWFQ (Class-Based Weighted Fair Queuing), 329

CCC (Circuit Cross Connect), 124

CCSA (China Communications Standards Association), 370

CDM (Code Division Multiplexing), 371

CE (Customer Edge) routers, 70

Central Office. *See* CO

centralized BNGs, 351–355

C-Flow, 488

CGw/CCF (Charging Gateway/Charging Collection Function), 390

Challenge Handshake Authentication Protocol. *See* CHAP

Change of Authorization (CoA), 457, 480

channels

- broadcast, 484–485
- SD-TV, 44
- Whale Channel, 485

CHAP (Challenge Handshake Authentication Protocol), 186

Charging Gateway/Charging Collection Function (CGw/CCF), 390

China Communications Standards Association (CCSA), 370

churn (routing), reducing, 423

Circuit Cross Connect (CCC), 124

circuits

- AC, 126
- CBR, 197
- crosstalk, 221
- LAD, 9
- pseudowires, 125. *See also* pseudowires
- services, 374–375

Circuit-Switched Data (CSD), 367

Cisco, 19

Cisco 10000 policing and shaping overheads, 337

Cisco IOS

- classification configuration, 305
- configuration, 410–411
- hierarchical rate-limiting, 312
- policy forwarding, 72
- PPPoA, 190
- scheduler hierarchies, 330

class of service. *See* CoS

Class-Based Weighted Fair Queuing (CBWFQ), 329

classes, traffic (UMTS), 380

classification, QoS, 306

CLECs (Competitive Local Exchange Carriers), 9

CLI (Command-Line Interface), 340, 480

clients

- BNG as DHCP, 206
- DHCP, 414–417

-
- CLP (Cell Loss Priority), 298
 - Clusters, distributed video, 48
 - CO (Central Office)
 - Ethernet DSLAMs, 118
 - POTS access to DSLAM, 64
 - residential and SME dynamic service provisioning, 445
 - CoA (Change of Authorization), 413, 457, 480
 - Coarse Wave Division Multiplexing (CWDM), 327
 - Code Division Multiplexing (CDM), 371
 - collection, statistics, 488
 - Command-Line Interface. *See* CLI
 - commands
 - address-pool-name, 410–411
 - bandwidth, 313
 - ip address-pool local, 409
 - ip helper-address, 416
 - peer default ip address pool, 411
 - set dhcp relay, 416
 - common carrier status, 350
 - Common Open Policy Service (COPS), 461
 - Communications Act of 1934, 9
 - comparing wholesale broadband networks, 283–286
 - compatibility, addresses, 414
 - Competitive Local Exchange Carriers (CLECs), 9
 - components, wireless broadband, 372–377
 - concurrency rate, 40
 - confidentiality, 481
 - configuration
 - automatic pool, 412
 - BNG
 - connections, 406–427
 - DHCP, 412–419
 - local address pools, 407–411
 - remote address pools, 411–412
 - Cisco IOS, 410–411
 - classification
 - Cisco IOS, 305
 - Juniper JUNOS, 304
 - Juniper JUNOSe, 408–410
 - networks, 423–426
 - triple-play networks, 67–68, 117
 - DSLAM aggregation, 122
 - Ethernet DSLAMs, 118–122
 - high-availability broadband access, 170–181
 - highly available core networks, 106–115
 - MPLS backbones, 68–79
 - multicast protocols in, 79–96
 - running MPLS on BNGs, 96–106
 - congestion, 329
 - connections
 - BNG, 97–99
 - configuring, 406–427
 - DHCP, 412–419
 - DSLAMs, 38
 - local address pools, 407–411
 - remote address pools, 411–412
 - business connectivity, 59–63
 - CAC, 300
 - PPP, 187. *See also* PPP
 - constant bit rate. *See* CBR
 - Constrained Shortest Path First (CSPF), 87
 - control plane security, 486–488
 - control words, 129
 - controllers, middleware, 460
 - copper
 - history of networks, 3–6
 - loop unbundling, 248
 - network reticulation, 234–235
 - COPS (Common Open Policy Service), 461
 - core networks
 - highly available, 106–115
 - IMS, 385
 - properties, 143
 - core protocols, 111, 112
 - CoS (class of service), 289
 - Cosine, 19
 - CPE (Customer Premises Equipment), 39, 158
 - DiffServ, 299
 - G.DMT, 223
 - troubleshooting, 172
 - credentials, VoIP security, 475–478
 - credits, 306
 - crosstalk, 221
 - CSCF (Call Session Control Function), 386
 - CSD (Circuit-Switched Data), 367
 - CSPF (Constrained Shortest Path First), 87
 - Customer Edge. *See* CE
 - Customer Premises Equipment. *See* CPE
 - C-VLAN shaping, 328
 - CWDM (Coarse Wave Division Multiplexing), 327
-

D

- DA (destination address), 71
- daisy-chained DSLAMs, 119–120
- DAR (Dynamic Adaptive Routing), 293
- dark fiber, 145
- data encoding, D.GMT, 223–225
- data modulation, D.GMT, 225
- data rates, applications, 31
- data services, 55–63
- databases, users, 447
- datagrams, prioritization, 294
- DDoS (Distributed Denial of Service)
 - attacks, 488
- DECT (Digital Enhanced Cordless Telecommunications), 366
- dedicated LNS load balancing, 283
- delivery
 - multicast using VPLS, 92–96
 - P2MP LSPs for, 85–86
 - SDP, 159
- denial of service attacks. *See* DoS
- Dense Wave Division Multiplexing (DWDM), 145, 327
- Department of Defense (DoD), 444
- deployment
 - DHCP, 215
 - IPv6, 436–441
 - DHCP, 439
 - L2TP, 440–441
 - PPPoE, 436–439
 - native IP multicast, 79–85
 - QoS, 289–290
 - classification, 306
 - determining need for, 290–294
 - marking, 306
 - prioritization concepts, 294–300
 - queuing, 313–318
 - rate-limiting, 306–313
 - router forwarding architectures, 342–346
 - scheduling, 318, 342
 - RSVP-TE LSPs, 108
 - VLANs, 168
- designing triple-play networks, 67–68, 117
 - DSLAM aggregation, 122
 - Ethernet DSLAMs, 118–122
 - high-availability
 - broadband access, 170–181
 - core networks, 106–115
 - MPLS backbones, 68–79
 - multicast protocols in, 79–96
 - running MPLS on BNGs, 96–106
 - designated router (DR), 81
 - DESS (Directory-Enabled Service Selection), 457
 - destination address (DA), 71
 - detection
 - BFD, 97, 110, 213
 - failure, 110
 - fault (Ethernets), 176
 - G.DMT, 226
 - IDS. *See* IDS
 - SFD, 487
 - determining need for QoS, 290–294
 - devices
 - intServ, 296
 - MRF, 388
 - DHCP (Dynamic Host Configuration Protocol), 14, 185, 196–207
 - addresses, 414–417
 - advantages of, 211–213
 - BNG, 206
 - disadvantages of, 213–216
 - IPv6 deployment, 439
 - LAN addressing, 427–428
 - negotiation, 455
 - PPP address assignment using, 412–419
 - relay-proxy, 204–206
 - selecting, 207–216
 - servers, 417
 - static addresses, 417–419
 - DHNR (Dynamic Nonhierarchical Routing), 293
 - dial-up provider-hosted L2TP architecture, 263
 - Differentiated Services Code Point (DSCP), 297
 - DiffServ (Differentiated Services), 289, 296–299
 - Digital Enhanced Cordless Telecommunications (DECT), 366
 - Digital Local Exchange (DLE), 247
 - digital mobile video broadcast, 396
 - Digital Rights Management (DRM), 51–53
 - Digital Subscriber Line Access Multiplexer.
See DSLAM
 - Digital Subscriber Line. *See* DSL
 - Digital Video Broadcast, Satellite (DVB-S)
 - standard, 41
 - Digital Video Broadcast-Handheld (DVB-H), 396

-
- Digital Video Broadcasting-Handheld (DVB-H), 397–398
 - Directory-Enabled Service Selection (DESS), 457
 - disadvantages
 - of DHCP, 213–216
 - of PPPoE, 209–211
 - discovery, VPLS topology, 177–181
 - Discrete Multitone (DMT), 6, 220
 - distributed BNGs, 356–357
 - Distributed Denial of Service attacks. *See* DDoS
 - distributed forwarding, 344
 - distributed multicast edges, running, 352–355
 - distributed video clusters, 48
 - distribution
 - routes, 423–426
 - servers (D-servers), 43
 - DLE (Digital Local Exchange), 247
 - DMH (Dual-Mode Handset), 391
 - DMT (Discrete Multitone), 6, 220
 - DoD (Department of Defense), 444
 - DoS (denial of service) attacks, 192, 470–473, 481
 - downstream carriers, 231
 - DR (designated router), 81
 - DRA (Dynamic Rate Adaptation), 228
 - DRM (Digital Rights Management), 51–53
 - dry copper loops, 9
 - dry pair, 9
 - DSCP (Differentiated Services Code Point), 297
 - D-servers (distribution servers), 43
 - DSL (Digital Subscriber Line), 3
 - architecture, 21–29
 - bit stream access, 249–259
 - early termination, 12
 - history of networks, 6–8, 10
 - Layer 2, 22
 - port identification, 276–277
 - DSL Forum (DSL-F), 8, 19–20
 - DSLAM (Digital Subscriber Line Access Multiplexer), 11, 117
 - BNGs, 38
 - centralized BNGs, 351
 - daisy-chained, 119–120
 - Ethernets, 14, 118–122
 - history of networks, 11–14
 - hub-and-spoke, 120–121
 - POTS access to, 64
 - pseudowires, 123–144
 - rate-limiting L2TP, 264
 - subtended, 119–121
 - traditional transport, 145–146
 - transport models, 121
 - DSLAM-to-BNG authentication, 272–274
 - DSL-F (DSL Forum), 8, 19–20
 - Dual-Mode handset (DMH), 391
 - dual-mode radios, 366
 - dual-stack BNG models, 437
 - duty cycles, 401
 - DVB-H (Digital Video Broadcast-Handheld), 397–398
 - DVB-S (Digital Video Broadcast) standard, 41
 - DWDM (Dense Wave Division Multiplexing), 145, 327
 - Dynamic Adaptive Routing (DAR), 293
 - Dynamic Host Configuration Protocol. *See* DHCP
 - Dynamic Nonhierarchical Routing (DHNR), 293
 - dynamic PIM joins, 100
 - Dynamic Rate Adaptation (DRA), 228
 - dynamic services
 - edges, 357
 - provisioning, 445–450
 - dynamic user session control
 - residential and SME dynamic service provisioning, 445–450
 - service provisioning flow, 451–467
- E**
- EAP (Extensible Authentication Protocol), 186
 - early DSL termination, 12
 - Early Packet Discard. *See* EPD
 - early user access implementations, 16
 - ECI Telecom, 8
 - E-DCH (Enhanced Dedicated Channel), 401
 - edge routers
 - distributed multicast, running, 352–355
 - redundancy, 114–115
 - EF (Expedited Forwarding), 297
 - efficiency
 - routing tables, 422
 - traffic routing, 153
 - electrical characteristics
 - of SHDSL, 237–239
 - of VDSL, 230–232
 - elements, services, 446–450
 - enabling DHCP relays on JUNOSe, 416
-

- encapsulation
 - Ethernets, 231
 - OSI Model, 444
- encoding G.DMT, 223–225
- encryption, video, 51–53
- endpoints, CAC, 300
- end-to-end VoIP, 64–66
- engines
 - meditation, 447
 - rating, 447
 - SPE, 449
- Enhanced Dedicated Channel (E-DCH), 401
- enhanced Internet access, 62
- entities, IMS, 385
- EPD (Early Packet Discard), 308
- error correction, G.DMT, 226
- ERX-Address-Pool-Name = pool1, 409
- Ethernets
 - BFD, 110
 - DSLAMs, 14, 118–122
 - aggregation, 122
 - daisy-chained, 119–120
 - hub-and-spoke, 120–121
 - subtended, 119–121
 - transport models, 121
 - encapsulation, 231
 - fault detection, 176
 - GELS, 154
 - high-availability access architecture, 175–176
 - interconnects, 253–256
 - metro, 175
 - pseudowires, 123–144
- ETSI (European Technical Standards Institute), 237
- evolution
 - of DSL architecture, 21–29
 - of DSLAM, 11–14
 - of service, 15–20
- exchanges, messages (VPLS), 149
- EXP (experimental) fields, 302
- Expedited Forwarding. *See* EF
- experimental (EXP) field, 302
- explicit tracking, 102
- Extensible Authentication Protocol. *See* EAP

- F**
- fabric, 344
- failover, nondeterministic, 109
- failure detection, 110

- Far-End Crosstalk. *See* FEXT
- fast reroute local protection, 109
- fault detection, Ethernet, 176
- FBF (Filter-based Forwarding), 71
- FCC (Federal Communications Commission), 9
- FDD (Frequency Division Duplexing), 221
- FDF (Fiber Distribution Frame), 145, 172
- FDM (Frequency Division Multiplexing), 220
- FEC (Forward Error Correction), 226
- FEC (Forwarding Equivalence Class), 95
- FECN (Forward Explicit Congestion Notification), 298
- Federal Communications Commission (FCC), 9
- FEXT (Far-End Crosstalk), 221
- Fiber Distribution Frame (FDF), 145
- fields
 - Diffserv, 297
 - EXP, 302
 - giaddr, 415
 - IP prioritization, 294
 - TLV, 434
- FIFO (First In/First Out), 313
- Filter-based Forwarding (FBF), 71
- filters
 - Attribute 242, 456
 - packets, 489
 - PIM-ASM, 81
- firewalls, 479, 486
- First In/First Out (FIFO), 313
- fixed bandwidths, 293
- Fixed/Mobile Convergence. *See* FMC
- FLO (Media Forward Link Only), 396, 399
- flooding
 - attacks, 470
 - MAC, 149
- Flow, service provisioning, 451–467
- FMC (Fixed Mobile Convergence), 366, 389–394
- Forward Error Correction (FEC), 226
- Forward Explicit Congestion Notification.
See FECN
- forwarding, 59
 - BFD, 97, 110, 213
 - distributed, 344
 - EF, 297
 - FBF, 71
 - integration with PIM source-specific
multicast, 90, 92
 - IPv6, 433
 - multicast, 166
 - planes, 88

- policies, 74
 - router architectures, 342–346
 - RPF, 90–92, 471–472
 - VRF address pools, 411
 - Forwarding Equivalence Class. *See* FEC
 - fragmentation, L2TP, 277–280
 - Frame Relay, 2, 123–144
 - framed routes, 420
 - Framed-IP-Addresses, 420
 - frequency, VDSL, 231
 - Frequency Division Duplexing (FDD), 221
 - Frequency Division Multiplexing (FDM), 220
 - future
 - of VPLS multicast delivery, 96
 - of wireless broadband
 - applications, 365–372
 - components, 372–377
 - evolution of, 399–403
 - FMC, 389–394
 - IMS, 381–389
 - video integration, 395–399
- ## G
- G.DMT, 222
 - data encoding, 223–225
 - data modulation, 225
 - error correction and detection, 226
 - standards and spectrum, 223
 - G.lite, 227
 - gaming, 56–57
 - GAN (Generic Access Network), 391–392
 - GANC (Generic Access Network Controller), 392
 - Gateway GPRS Support Nodes (GGSNs), 379
 - gateways
 - ALPs, 302
 - BNGs, 469. *See also* BNGs
 - LSSG, 457
 - RG
 - DHCP, 212
 - PPPoE, 190
 - SEGW, 392
 - services, 445
 - streaming, 46
 - troubleshooting, 172
 - Gaussian Minimum Shift Keying (GMSK), 367
 - GCRA (Generic Cell Rate Algorithm), 309
 - GELS (Generalized Ethernet Label Switching), 154
 - General Packet Radio Service. *See* GPRS
 - General Post Office. *See* GPO
 - General Switch Management Protocol (GSMP), 358
 - Generalized Ethernet Label Switching (GELS), 154
 - Generic Access Network (GAN), 391–392
 - Generic Access Network Controller (GANC), 392
 - Generic Cell Rate Algorithm (GCRA), 309
 - GERAN (GSM/GPRS Radio Access Network), 392
 - giaddr field, 415
 - GMSK (Gaussian Minimum Shift Keying), 367
 - Google video, 235
 - GPO (General Post Office), 245
 - GPRS (General Packet Radio Service), 368–379
 - Graceful Restart, 180
 - groups
 - DiffServ, 298
 - static IGMP, 100
 - GSM/GPRS Radio Access Network (GERAN), 392
 - GSMP (General Switch Management Protocol), 358
 - guarantees, IntServ, 296
- ## H
- HA (high availability)
 - BNG element architecture, 178–181
 - broadband access, 170–181
 - Ethernet access architecture, 175–176
 - video, 43
 - handsets, 366
 - DMH, 391
 - FMC, 389–394
 - hardware
 - BNG, 178
 - dedicated LNS load balancing, 283
 - distributed forwarding, 344
 - SAR, 339
 - HDR (high data rate), 371
 - HD-TV (High Definition Television), 145, 462
 - headers
 - IP DiffServ fields, 297
 - IPv6, 432
 - MPLS, 302
 - head-end architecture, video, 41
 - Hello (Norway), 389
 - HFC (hybrid fiber/co-axial), 2, 5, 219

- hierarchical QoS, 323–336
 - hierarchical rate-limiting, 310
 - high data rate (HDR), 371
 - high-availability. *See* HA
 - High-Definition Television (HD-TV), 145, 462
 - highly available core networks, 106–115
 - High-Speed Circuit-Switched Data (HSCSD), 367
 - High-Speed Downlink Packet Access (HSDPA), 400
 - High-Speed Downlink Shared Channel (HS-DSCH), 401
 - High-Speed Uplink Packet Access (HSUPA), 400
 - history
 - of QoS, 294–300
 - of networks
 - copper, 3–6
 - DSL, 6–10, 21–29
 - DSLAM, 11–14
 - evolution of service, 15–20
 - legacy access, 2
 - modern broadband, 30–32
 - Telecommunications Act of 1996, 9–10
 - home routers. *See* RG
 - HSCSD (High-Speed Circuit-Switched Data), 367
 - HSDPA (High-Speed Downlink Packet Access), 400
 - HS-DSCH (High-Speed Downlink Shared Channel), 401
 - HSUPA (High-Speed Uplink Packet Access), 400
 - hub-and-spoke DSLAMs, 120–121
 - hybrid fiber/co-axial (HFC), 2, 219
 - hybrid VPN models, 76
- I**
- ICA (International Copper Association), 7
 - I-CSCF (Interrogating CSCF), 387
 - identifying DSL ports, 276–277
 - IDSs (Intrusion Detection Systems), 476, 486
 - IGMP (Internet Group Management Protocol), 484–485
 - PIM-SSM mapping, 99–106
 - proxy, 102–103
 - IGPs (Interior Gateway Protocols), 433
 - IMA (inverse multiplexing), 228
 - immediate leave, 102
 - implementing Annexes, 239
 - IMS (IP Multimedia Subsystem), 366, 381–389
 - IMT-2000 (International Mobile Telecommunications 2000), 365–366
 - IMT-DS (Direct Sequence), 365
 - IMT-FT (Frequency Time), 366
 - IMT-MC (Multi-Carrier), 365
 - IMT-SC (Single Carrier), 366
 - IMT-TD (Time Division), 365
 - initializing ADSL2, 228
 - injection points, multiple, 107–108
 - Integrated Services Digital Network. *See* ISDN
 - Integrated Services. *See* IntServ
 - integration
 - core protocols with multicast, 112
 - PIM source-specific multicast, 90–92
 - video, 395–399
 - WAN, 390
 - interception (lawful), 480–481
 - interconnects
 - ATM, 249–253
 - Ethernets, 253–256
 - L2TP, 261–280
 - Layer 3, 259–261
 - redundant bit stream, 256–259
 - interfaces
 - BVI, 198
 - CLI, 480
 - loopback, 408
 - OIF, 464–465
 - protection, 177, 256
 - radio (IMT-2000), 365–366
 - southbound networks, 445, 449–450, 461–462
 - Interim Accounting packet, 274
 - Interior Gateway Protocols. *See* IGPs
 - International Copper Association (ICA), 7
 - International Mobile Telecommunications 2000. *See* IMT-2000
 - International Telecommunication Union. *See* ITU
 - Internet, 70
 - Internet Group Management Protocol. *See* IGMP
 - Internet Protocol. *See* IP
 - Internet Protocol Data Cast (IPDC), 397
 - Internet Protocol version 6. *See* IPv6
 - Internet service providers. *See* ISPs
 - Interprovider VPNs, 78
 - Interrogating CSCF (I-CSCF), 387

-
- interworking services, 160–162
 - Intrusion Detection Systems. *See* IDSs
 - IntServ (Integrated Services), 296
 - inverse multiplexing (IMA), 228
 - IOS
 - classification configuration, 305
 - hierarchical rate-limiting, 312
 - scheduler hierarchies, 330
 - IP (Internet Protocol)
 - addresses
 - Framed-IP-Addresses, 420
 - ranges, 414
 - BNGs, 469
 - bridged IP over ATM, 198
 - field prioritization, 294
 - headers in DiffServ fields, 297
 - management, 405
 - assigning static PPP addresses, 420–421
 - changes to IPv6, 431–432
 - configuring BNG connections, 406–427
 - customer LAN addressing, 427–430
 - DHCP, 412–419
 - local address pools, 407–411
 - remote address pools, 411–412
 - router/software support (IPv6), 432–434
 - routing subscriber addresses, 421–427
 - triple play with IPv6, 430, 441
 - native multicast deployment, 79–85
 - packets, 471
 - precedence, 294, 299
 - Video over, 40–55
 - ip address-pool local command, 409
 - IP control protocol (IPCP), 420
 - ip helper-address command, 416
 - IP Multimedia Subsystem. *See* IMS
 - IP over Ethernet. *See* IPoE
 - IPCP (IP control protocol), 420
 - IPDC (Internet Protocol Data Cast), 397
 - IPoE (IP over Ethernet), 185
 - IPTV services, 41–45
 - IPv6 (Internet Protocol version 6)
 - access protocols, 216
 - changes to, 431–432
 - deployment, 436–441
 - DHCP, 439
 - L2TP, 440–441
 - PPPoE, 436–439
 - router/software support, 432–434
 - triple play with, 430–441
 - ISDN (Integrated Services Digital Network), 2
 - islands (protocol), 434
 - ISPs (Internet service providers), 9
 - ISSU, 181
 - ITU (International Telecommunication Union), 220
- J**
- J-Flow, 488
 - jitter, 291
 - Juniper JUNOS
 - classification configuration, 304
 - policy forwarding, 73
 - PPPoA, 189
 - Juniper JUNOSE
 - configuration, 408–410
 - DHCP, 416
 - hierarchical rate-limiting, 310
 - scheduler hierarchies, 328
- K**
- Kompella Layer 2 VPNs, 135–142
 - selecting, 142–144
- L**
- L2TP (Layer 2 Tunneling Protocol)
 - Access Aggregation, 25
 - IPv6 deployment, 440–441
 - wholesale broadband networks, 261–283
 - L2TP Network Server. *See* LNS
 - L2TP Tunnel Switching (LTS), 270–271
 - L2VPNs (Layer 2 VPNs), 124, 128–144
 - L3VPN (MPLS VPN), 69
 - Label Distribution Protocol. *See* LDP
 - Label Switched Paths (LSPs), 76
 - labels
 - GELS, 154
 - MPLS. *See* MPLS
 - signaling, 142
 - LAC (Layer 2 Tunneling Protocol Access Concentrator), 262
 - LAC-based load balancing, 282–283
 - LAC-to-LNS authentication, 274–276
 - LAD (Local Area Data) circuits, 9
 - LANs (local-area networks)
 - customer addressing, 427–430
 - DHCP, 196
-

- last mile broadband access, 219
 - ADSL, 220, 227
 - ADSL2, 227–230
 - ADSL2+, 227–230
 - SHDSL, 235
 - troubleshooting, 172
 - VDSL/VDSL2, 230–235
 - VLANs, 168
 - last mile copper loops, 1
 - Laurel, 19
 - lawful interception, 480–481
 - Layer 2
 - DSL, 22
 - pseudowires, 123–144
 - VPNs, 62
 - wholesale broadband networks, 259–261
 - Layer 2 Control (L2C) protocol, 467
 - Layer 2 Tunneling Protocol Access Concentrator (LAC), 262
 - Layer 2 Tunneling Protocol Network Servers (LNSs), 450
 - Layer 2 Tunneling Protocol. *See* L2TP
 - Layer 2 VPNs (L2VPNs), 124, 128–144
 - Layer 3, VPNs (L3VPNs), 59
 - layers
 - IMS, 382
 - OSI Model, 444
 - SBCs as proxies, 475–477
 - LCP (Link Control Protocol), 185, 274
 - LDAP (Lightweight Directory Access Protocol), 457
 - LDP (Label Distribution Protocol), 76, 143
 - leaking, VRF route-target, 74
 - learning bridges, 175
 - leases
 - DHCO, 211
 - DHCP, 203
 - LEC (Local Exchange Carrier), 2
 - legacy access networks, 2
 - LFN (Long Fat Network), 314
 - LH (long-haul) fiber-optic transmission, 119
 - Lightweight Directory Access Protocol. *See* LDAP
 - limitations
 - of bandwidth, 291
 - of CAC, 462–467
 - of DHCP relay implementations, 416
 - of PWE3, 128
 - line-based authorization, 273
 - Link Control Protocol (LCP), 274
 - links
 - CAC, 462–467
 - protection, 177
 - VoIP, 70
 - listeners, MLD, 436
 - Livingston Systems, 17
 - LLU (Local Loop Unbundling), 246–249
 - LNS (L2TP Network Server), 411
 - anycast, 281
 - dedicated load balancing, 283
 - LAC-to-LNS authentication, 274–276
 - route aggregation, 426
 - load balancing
 - authentication, 483–484
 - dedicated LNS, 283
 - LAC-based, 282–283
 - load coils, 4
 - load distribution, multiple RPs, 82
 - local address pools, 407–411
 - Local Area Data (LAD) circuits, 9
 - local DHCP servers, 417
 - Local Exchange Carrier (LEC), 2
 - Local Loop Unbundling. *See* LLU
 - local-area networks. *See* LANs
 - Long Fat Network (LFN), 314
 - long-haul (LH) fiber-optic transmission, 119
 - Long-Term Evolution (LTE), 403
 - loopback interfaces, IP addresses, 408
 - loops
 - length, 228
 - LLU, 246–249
 - loose RPF, 92
 - low-latency scheduling, 322–323
 - LSPs (Label Switched Paths), 76
 - automated P2MP provisioning, 93–96
 - MPLS, 111
 - P2MP, 85–86
 - RSVP-TE, 108
 - LTE (Long-Term Evolution), 403
 - LTS (L2TP Tunneling Switching), 270–271
 - Lucent, 19
- ## M
- MAC (Media Access Control)
 - addresses
 - pseudowires, 127
 - resolving, 418
 - scaling, 154
 - VPLS, 149
-

- magic numbers (PPP), 187
- Main Distribution Frame (MDF), 12, 248
- management
 - DiffServ, 296–299
 - DRM, 51–53
 - IP
 - changes to IPv6, 431–432
 - customer LAN addressing, 427–430
 - router/software support (IPv6), 432–434
 - triple play with IPv6, 430–441
 - IP addresses, 405
 - assigning static PPP addresses, 420–421
 - configuring BNG connections, 406–427
 - DHCP, 412–419
 - local address pools, 407–411
 - remote address pools, 411–412
 - routing subscriber addresses, 421–427
 - services, 446–450
- Mann-Elkins act of 1910, 9
- mapping
 - OIF, 464–465
 - PIM-SSM, 99, 104–106
 - reverse OIF, 465
- marking
 - QoS, 306
 - queuing, 313–318
 - stacks, 302
- Martini Layer 2 VPNs, 130–135, 142–144
- MAX TNT, 19
- maximum attainable downstream bit rates, 252
- Maximum Receive Unit. *See* MRU
- Maximum Transmission Unit (MTU), 278
- MBGP (Multiprotocol BGP), 136
- MBMS (Multicast Broadcast Multimedia Services), 396
- MDF (Main Distribution Frame), 12, 172, 248
- Mean Time Between Failures (MTBF), 120
- measurements, availability, 171–173
- media
 - catalogs, 54
 - encoding, 51–53
- Media Access Control. *See* MAC
- Media Forward Link Only (FLO), 396, 399
- Media Gateways (MGWs), 379
- Media Resource Function (MRF), 388
- meditation engines, 447
- meet-me rooms, 248
- messages
 - CoA, 480
 - VPLS, 149
- Metallic Path Facility (MPF), 246
- metro Ethernets, 175
- MGWs (Media Gateways), 379
- MichNet, 17
- Microsoft MSTV, 43–44
- middleware, 53, 460
- MIMO (Multiple Input Multiple Output), 401
- MLD (Multicast Listener Discovery), 436
- MMD (Multimedia Domain), 383
- mobile stations (MSs), 366
- Mobile Switching Centers (MSCs), 379
- models
 - CAC. *See* CAC
 - OSI Model, 444
 - VLANs, 168
- modems, PPPoA, 188
- modes
 - bridged, 429
 - routed, 428–429
- modulation
 - G.DMT, 225
 - SHDSL, 238
- MPF (Metallic Path Facility), 246
- MPLS (Multiprotocol Label Switching), 67
 - backbone networks, 68–79
 - BNGs, 96–106
 - headers, 302
 - LSPs, 111
 - pseudowires, 177
 - PSN, 123–144
 - routing, 129
 - VPN (L3VPN), 69
- MRD (Multicast Router Discovery) protocol, 436
- MRF (Media Resource Function), 388
- MRU (Maximum Receive Unit), 192, 276
- MSCs (Mobile Switching Centers), 379
- MSDP (Multicast Source Discovery Protocol), 83, 489
- MSOs (MultiSystem Operators), 2
- MSs (mobile stations), 366
- MTBF (Mean Time Between Failures), 120
- MTU (Maximum Transmission Unit), 185, 192, 278
- MUDs (Multi-Unit Dwellings), 234
- Multicast Broadcast Multimedia Services (MBMS), 396
- multicast data delivery, P2MP LSPs for, 85–86
- multicast forwarding, 166
- multicast join state, broadcast channels, 484–485
- Multicast Listener Discovery (MLD), 436

multicast protocols, 79–89
 Multicast Router Discovery (MRD) protocol, 436
 Multicast Source Discovery Protocol (MSDP), 83, 489
 multicast trees, VPLS, 93
 multicast VLANs, 162–168
 multiclass services, L2TP, 267
 multi-endpoint PVPs, 259
 Multimedia Domain (MMD), 383
 multi-play network topologies, 36–39
 multiple injection points, 107–108
 Multiple Input Multiple Output (MIMO), 401
 multiple RPs, 82
 multiplexing, 158, 371
 Multiprotocol BGP (MBGP), 136
 Multiprotocol Label Switching. *See* MPLS
 MultiSystem Operators. *See* MSOs
 Multi-Unit Dwellings. *See* MUDs

N

NA (Neighbor Advertisement), 435
 naked DSL access, 219
 NAPT (Network Address Port Translation), 158
 narrowband networks, L2TP, 262–263
 NAS (network access server), 17
 NAS-Port-ID, 273
 NAT (Network Address Translation), 158
 native IP multicast, deploying, 79–85
 Near Video on Demand (NVoD), 45
 Near-End Cross Talk. *See* NEXT
 need for QoS, determining, 290–294
 negotiation, 454–455
 Neighbor Advertisement (NA), 435
 Neighbor Solicitation (NS), 435
 NetFlow, 488
 network access server (NAS), 17
 Network Address Port Translation (NAPT), 158
 Network Address Translation (NAT), 158
 Network Layer Reachability Information (NLRI), 136
 Network Private Video Recorder (NPVR), 40, 54
 networks. *See also* connections
 aggregation, 169–170
 broadband, 30–32
 configuration, 423–426
 core, 143, 385
 DSL architecture, 21–29
 GAN, 391–392

history of
 copper, 3–6
 DSL, 6–10
 DSLAM, 11–14
 evolution of service, 15–20
 legacy access, 2
 Telecommunications Act of 1996, 9–10
 outages, 171–173
 password-free, 483
 PSTN, 290
 selecting, 77–78
 topologies, 36–39
 triple-play
 design, 117
 DSLAM aggregation, 122
 Ethernet DSLAMs, 118–122
 high-availability broadband access, 170–181
 wholesale broadband, 245–246
 bit stream access, 249–259
 comparing, 283–286
 high-availability L2TP, 280–283
 L2TP, 261–280
 Layer 3, 259–261
 LLU, 246–249
 Network-to-Network Interconnect (NNI), 251
 Neuf Cegetel (France), 389
 NEXT (Near-End Cross Talk), 220
 NLRI (Network Layer Reachability Information), 136
 NNI (Network-to-Network Interconnect), 251
 non-Annex M systems, 230
 nondeterministic failover, 109
 non-MPLS networks, 77
 nonoptimized multicast forwarding, 165
 Nonstop Routing (NSR), 180
 non-VPN routing models, 76
 NPVR (Network Private Video Recorder), 40, 54
 NS (Neighbor Solicitation), 435
 NSR (Nonstop Routing), 180
 numbers, magic (PPP), 187
 NVoD (Near Video on Demand), 45
 Nyquist-Shannon sampling theorem, 5

O

OCS (Online Charging System), 390
 ODAP (On-Demand Address Pool), 411
 OECD (Organisation for Economic Co-operation and Development), 245

-
- OFDM (Orthogonal Frequency Division Multiplexing), 402
 - OIF (Outbound Interface) mapping, 354, 464–465
 - OLT (optical line termination), 357
 - On-Demand Address Pool. *See* ODAP
 - Online Charging System (OCS), 390
 - OOB (out-of-band) TCP communications channels, 358
 - Open Systems Interconnection Reference Model. *See* OSI Model
 - operating expenses (OpEx), 120
 - Operational Expenditure (OpEx), 483
 - optical line termination (OLT), 357
 - optimization
 - security, 482–483
 - video, 49
 - option 82 field (DHCP), 202
 - Orange (France, U.K., Netherlands, Spain, Poland), 389
 - Orckit, 8
 - Organisation for Economic Co-operation and Development. *See* OECD
 - Orthogonal Frequency Division Multiplexing (OFDM), 402
 - OSI Model (Open Systems Interconnection Reference Model), 185, 444
 - outages, networks, 171–173
 - Outbound Interface. *See* OIF
 - out-of-band (OOB) TCP communications channels, 358
 - overheads, shaping, 336–342
 - oversubscription ratios, 293
- P**
- P2MP (point-to-multipoint) LSPs, 85–86
 - automated P2MP LSP provisioning, 93–96
 - packets
 - filters, 489
 - IP
 - prioritization, 294
 - RPF, 471
 - jitter, 291
 - queuing, 313–318
 - scheduling, 318, 342
 - services, 374–375
 - tokens, 308
 - Packet-Switched Network. *See* PSN
 - PADI (PPPoE Active Discovery Initiation), 191
 - PADR (PPPoE Active Discovery Request), 191
 - PADS (PPPoE Active Discovery Session), 191
 - PAP (Password Authentication Protocol), 186
 - parameters, transmit unconditional, 313
 - Partial Packet Discard. *See* PPD
 - Passive Optical Network (PON), 154, 357
 - Password Authentication Protocol. *See* PAP
 - password-free networks, 483
 - patches, cable, 248
 - Path MTU Discovery (PMTUD), 279
 - paths
 - CSPF, 87
 - forwarding, 90, 92
 - LSPs, 76
 - PVPs, 127
 - RPF, 90–92, 471–472
 - SPT, 81
 - PBR (Policy-Based Routing), 71
 - PBXs (private branch exchanges), 235
 - PCG (Project Coordination Group), 377
 - P-CSCF (Proxy CSCF), 386
 - PDP (Policy Decision Point), 461
 - PDUs (Protocol Data Units), 197
 - PE (provider edge) routers, 37, 152
 - peer default ip address pool command, 411
 - PEP (Policy Enforcement Point), 450, 461
 - permanent virtual circuits. *See* PVCs
 - Permanent Virtual Paths. *See* PVPs
 - PHB (Per-Hop Behavior), 266, 297
 - physical characteristics
 - of SHDSL, 237–239
 - of VDSL, 230–232
 - PIM-ASM (PIM Any Source Multicast), 79, 81–83
 - mapping, 99, 104–106
 - Plain Old Telephone Service. *See* POTS
 - planes, 87–88
 - platforms
 - billing, 446
 - RADIUS, 448
 - plug-ins, middleware, 461
 - PMTUD (Path MTU Discovery), 279
 - point-to-multipoint (P2MP) LSPs, 85–86
 - Point-to-Point Protocol over ATM. *See* PPPoA
 - Point-to-Point Protocol. *See* PPP
 - policies
 - forwarding, 71
 - routing, 423–426
-

- policing traffic, 306–313, 336–342
- policy decision point (PDP), 461
- Policy Enforcement Point (PEP), 450, 461
- Policy-Based Routing (PBR), 71
- PON (Passive Optical Network), 154, 357
- pools
 - local address, 407–411
 - remote address, 411–412
- portals, 448
 - advanced dynamic service provisioning, 460
 - service provisioning flow, 451
- Portmaster, 17
- ports, DSL, 276–277
- Postel, Jon, 294
- Postes et Télégraphes (France), 245
- POTS (Plain Old Telephone Service), 64, 220
- Power Spectral Density (PSD), 222, 235
- PPD (Partial Packet Discard), 308
- PPP (Point-to-Point Protocol), 186–196, 261
 - addresses, 412–419
 - negotiation, 454
 - PPPoA, 188–190
 - PPPoE, 190–196, 207–211
 - selecting, 207–216
 - static addresses, 420–421
- PPP over Ethernet Intermediate Agent. *See* PPPoE IA
- PPP over Ethernet. *See* PPPoE
- PPP Terminated Aggregation (PTA), 25
- PPPoA (Point-to-Point Protocol over ATM), 186–190
- PPPoE (PPP over Ethernet), 185, 190–196
 - advantages of, 207–209
 - disadvantages of, 209–211
 - IPv6 deployment, 436–439
 - LAN addressing, 427–428
- PPPoE Active Discovery Initiation (PADI), 191
- PPPoE Active Discovery Request (PADR), 191
- PPPoE Active Discovery Session (PADS), 191
- PPPoE IA (PPP over Ethernet Intermediate Agent), 14
- precedence
 - IP, 294
 - DSCPs, 299
- premium gaming services, 56–57
- prioritization, QoS, 294–300
- private branch exchanges. *See* PBXs
- profiles, 233, 448
- Project Coordination Group (PCG), 377
- properties, scaling, 143
- protect interface, 256
- protection, links, 177
- Protocol Data Units. *See also* PDUs
- protocols, 374
 - access, 186, 207–216
 - ARP, 431
 - BOOTP, 196
 - CHAP, 186
 - core, 111
 - DHCP, 14, 185, 196–207
 - advantages of, 211–213
 - assigning addresses, 414–417
 - disadvantages of, 213–216
 - IPv6 deployment, 439
 - local servers, 417
 - relay-proxy, 204–206
 - selecting, 207–216
 - EAP, 186
 - GSMP, 358
 - IGMP, 99–106, 484–485
 - IGPs, 433
 - interworking, 160–162
 - IPCP, 420
 - IPv6, 434
 - islands, 434
 - L2C, 467
 - L2TP, 440–441
 - LAN addressing, 427–428
 - LCP, 185, 274
 - LDAP, 457
 - LDP, 76
 - MRD, 436
 - MSDP, 489
 - multicast, 79–89
 - PAP, 186
 - PPP, 186–196, 261
 - assigning static addresses, 420–421
 - PPPoA, 188–190
 - selecting, 207–216
 - PPPoE, 190–196
 - IPv6 deployment, 436–439
 - LAN addressing, 427–428
 - RSVP, 296
 - scheduling, 334
 - SLIP, 261
 - STP, 176
 - TCP, 314
 - VRRP, 37

provider edge (PE) routers, 37, 152
 provider VLAN architectures, 162–168
 Provider-Based Trees, 154
 provisioning

- automated P2MP LSP, 93–96
- dynamic service, 445–450
- services, 451–467
- SPE, 449

 proxies

- ARP, 418
- DHCP relay-proxy, 204–206
- LCP, 275
- SBCs, 475–477

 Proxy CSCF (P-CSCF), 386
 PSD (Power Spectral Density), 222, 235
 Pseudowire Emulation Edge to Edge (PWE3), 124
 pseudowires, 123–144, 177
 PSN (Packet Switched Network), pseudowires, 123–144
 PSTN (Public Switched Telephone Network), 290
 PTA (PPP Terminated Aggregation), 25
 Public Switched Telephone Network. *See* PSTN
 PVCs (Permanent Virtual Circuits), 13, 188
 PVPs (Permanent Virtual Paths), 127, 249
 PWE3 (Pseudowire Emulation Edge to Edge), 124, 154

Q

QAM (Quadrature Amplitude Modulation), 6
 QoS (Quality of Service)

- 3GPP, 380
- classification, 306
- deploying, 289–290
 - determining need for, 290–294
 - prioritization concepts, 294–300
- marking, 306
- profiles, 448
- queuing, 313–318
- rate-limiting, 306–313, 336–342
- router forwarding architectures, 342–346
- scheduling, 318, 342
- triple-play architectures, 346
 - centralized BNGs, 351–355
 - distributed BNGs, 356–357
 - L2CP, 357
 - trust boundaries, 346–351
- VLANs, 168
- VPLS, 154

Quadrature Amplitude Modulation (QAM), 6
 Qualcomm, FLO, 399
 quality, optimizing video, 49
 queuing, QoS, 313–318

R

R99 (3GPP Release 99), 379
 Radio Access Network (RAN), 380
 radio interfaces (IMT-2000), 365–366
 RADIUS (Remote Authentication Dial-In User Service), 274, 448

- Cisco IOS, 410
- CoA messages, 480
- local address pools, 409
- NAS-Port-IDs, 448

 RAM (Rate-Adaptive Mode), 229, 359
 RAN (Radio Access Network), 380
 Random Early Discard. *See* RED
 ranges, IP addresses, 414
 RASs (Remote Access Servers), 261
 Rate-Adaptive Mode (RAM), 229, 359
 rate-limiting

- L2TP, 264–265
- QoS, 306–313
- shaping overheads, 336–342

 rates, 40, 447
 RBOC (Regional Bell Operating Company), 7
 RD (Router Discovery), 435
 Real-Time Network Reporting (RTNR), 293
 real-time service changes, 458
 reassembly, L2TP, 277–280
 receive window (RWIN), 314
 RED (Random Early Discard), 308, 315
 Redback, 19
 Redstone, 19
 reduction of routing churn, 423
 redundancy

- bit stream interconnects, 256–259
- edge, 114–115
- multiple RPs, 82
- PWE3, 128
- VPLS, 151

 Reed-Solomon FEC codes, 226
 references, OSI model, 444
 reflection, routes, BGP, 153
 refreshing DHCP leases, 203
 Regional Bell Operating Company (RBOC), 7
 Reichspostamt (Germany), 245
 relay agents, 199, 201, 215

- relays, 416
 - releases, 3GPP, 369
 - Remote Access Servers. *See* RASs
 - remote address pools, 411–412
 - Remote Authentication Dial-In User Service.
 See RADIUS
 - Remote Line Card Shelves (RLCSs), 13
 - rendezvous point (RP), 81–82
 - renewing DHCP leases, 203
 - requests, CAC, 300
 - requirements for high-availability broadband
 access, 170–171
 - residential access servers, 15
 - Residential Gateway. *See* RG
 - residential service provisioning, 445–450
 - resolving MAC addresses, 418
 - Resource Reservation Protocol with Traffic
 Engineering (RSVP-TE), 76
 - Resource Reservation Protocol. *See* RSVP
 - resources, PPPoE, 191
 - reticulation, copper network, 234–235
 - reverse OIF mapping, 465
 - Reverse Path Forwarding (RPF), 90–92, 471–472
 - RFC 2698, 299
 - RFC 791, 294
 - RG (Residential Gateway), 39
 - DHCP, 212
 - PPPoE, 190
 - routed mode, 416
 - security, 472
 - troubleshooting, 172
 - RLCSs (Remote Line Card Shelves), 13
 - round-robin scheduling, 319–322
 - Round-Trip Time (RTT), 314
 - routed modes
 - LAN addressing, 428–429
 - PPPoE, 194–196
 - Router Discovery (RD), 435
 - routers
 - BGP, 153
 - BSR, 84
 - CE, 70
 - DR, 81
 - home. *See* RG
 - IPv6, 432–434
 - Juniper, 408–410
 - MRD, 436
 - PE, 37
 - QoS, 342–346
 - routes
 - aggregation, 426
 - distribution, 423–426
 - framed, 420
 - route-target leaking (VRF), 74
 - routing, 423
 - ARP, 418
 - blackhole/sinkhole, 489
 - control planes, 486–488
 - MPLS, 129
 - non-VPN models, 76
 - NSR, 180
 - PBR, 71
 - policies, 423–426
 - subscriber addresses, 421–427
 - tables, 422
 - VRF, 59, 411
 - RP (rendezvous point), 81–82
 - RPF (Reverse Path Forwarding), 90–92, 471–472
 - RSVP (Resource Reservation Protocol), 143, 296
 - RSVP-TE (Resource Reservation Protocol with
 Traffic Engineering), 76, 108
 - RTNR (Real-Time Network Reporting), 293
 - RTT (Round-Trip Time), 314
 - RWIN (receive window), 314
- S**
- sampling, 5
 - SAR (Segmentation and Reassembly)
 - hardware, 339
 - SAs (source addresses), 489
 - SBCs (Session Border Controllers), 65, 302, 357
 - as Application Layer proxies, 475–477
 - firewalls, 479
 - scaling
 - IGMP proxy, 102–103
 - MAC addresses, 154
 - properties, 143
 - VPLS, 152–154
 - scheduling
 - protocols, 334
 - QoS, 318, 342
 - queuing, 313–318
 - S-CSCF (Serving CSCF), 387
 - SDOs (Standards Development
 Organizations), 370
 - SDP (Service Delivery Point), 159
 - SD-TV (Standard Definition), 44, 145

- security
 - authentication, 481–483
 - blackhole/sinkhole routing, 489
 - control planes, 486–488
 - DoS attacks, 470–473
 - firewalls, 479
 - lawful interception, 480–481
 - packets, 489
 - password-free networks, 483
 - RG, 472
 - video, 51–53
 - VoD, 484–486
 - VoIP, 474–480
- Segmentation and Reassembly (SAR)
 - hardware, 339
- SEGW (Security Gateway), 392
- selecting
 - access of protocols, 207–216
 - Layer 2 VPNs, 142–144
 - networks, 77–78
- Serial Line Interface Protocol. *See* SLIP
- serialization, 265
- servers, 387
 - A-servers, 43
 - BRAS, 38
 - DHCP, 412–419
 - D-servers, 43
 - LDAP, 457
 - LNSs, 450
 - RADIUS, 448
 - RASs, 261
- Service Delivery Point (SDP), 159
- Service Level Agreement. *See* SLA
- Service Provisioning Engine (SPE), 449
- Service Selection Gateway (SSG), 457
- services
 - assigning, 454, 456
 - circuits, 374–375
 - COPS, 461
 - DiffServ, 296–299
 - dynamic provisioning, 445–450
 - FMC, 389–394
 - gateways, 445
 - history of networks, 15–20
 - IMS, 387
 - IntServ, 296
 - IPTV, 41–45
 - L2TP for narrowband networks, 262
 - LLU, 246–249
 - management elements, 446–450
 - MBMS, 396
 - Microsoft MSTV, 43–44
 - multiplexing, 158
 - packets, 374–375
 - premium gaming, 56–57
 - provisioning, 451–467
 - QoS. *See* QoS
 - RADIUS, 448
 - triple-play, 36
 - data services, 55–63
 - network topologies, 36–39
 - Video over IP, 40–55
 - voice services, 63–66
 - Unicast IPTV, 44
 - VLANs, 156–162
 - walled-garden, 58–59
- Serving CSCF (S-CSCF), 387
- Serving GPRS Support Nodes (SGSNs), 379
- Session Border Controllers. *See* SBCs
- Session Initiation Protocol. *See* SIP
- sessions, 188, 211
- set dhcp relay command, 416
- Set-Top Boxes (STBs), 39, 196
- SFD (Suspicious Flow Detection), 487
- SGSNs (Serving GPRS Support Nodes), 379
- Shannon-Hartley theorem, 224
- shaping overheads, 336–342
- Shared Metallic Path Facility (SMPF), 246
- SHDSL (Single-pair High-Speed DSL), 235
- Shortest Path Tree (SPT), 81
- signals, 87–88, 142
- single source addresses, applying multiple
 - injection points, 107–108
- single VLAN per DSLAM, 159
- Single-pair High-Speed DSL. *See* SHDSL
- SingTel (Singapore), 389
- sinkhole routing, 489
- SIP (Session Initiation Protocol), 374, 393
- SLA (Service Level Agreement), 292
- Slingbox, 235
- SLIP (Serial Line Interface Protocol), 261
- SLU (Subloop Unbundling), 246
- SME (Small and Medium Enterprise) markets,
 - 444–450
- Smoothed Round-Trip Time (SRTT), 314
- SMPF (Shared Metallic Path Facility), 246

- smurf attacks, 470
 - SNR (signal-to-noise ratio), 238
 - software. *See also* applications
 - BNG, 179
 - IPv6, 432–434
 - SONET (Synchronous Optical Network), 2
 - source addresses (SAs), 489
 - southbound network interfaces, 445, 449–450, 461–462
 - Spanning Tree Protocol. *See* STP
 - SPE (Service Provisioning Engine), 449, 451–467
 - spectrums
 - G.DMT, 223
 - SHDSL, 236
 - VDSL2, 233
 - speed, broadcast channels, 484–485
 - Springtide, 19
 - SPT (Shortest Path Tree), 81
 - SQL Slammer worm, 489
 - SRTT (Smoothed Round-Trip Time), 314
 - SSG (Service Selection Gateway), 457
 - stacked VLANs (S-VLANs), 292
 - stacks, 302, 444
 - Standard Definition (SD-TV), 44, 145
 - standards
 - G.DMT, 223
 - SHDSL, 236
 - VDSL2, 233
 - Standards Development Organizations (SDOs), 370
 - static DHCP addresses, 417–419
 - static IGMP groups, 100
 - static PPP addresses, assigning, 420–421
 - statistics, collecting, 488
 - STBs (Set-Top Boxes), 39, 101, 196
 - STP (Spanning Tree Protocol), 176
 - streams
 - bit, 249–259
 - CAC, 462–467
 - Gateways, 46
 - strict priority traffic scheduling, 322–323
 - strict RPF, 92
 - structure, 3GPP, 377
 - Subloop Unbundling (SLU), 246
 - subscriber-facing network elements, 450
 - subscribers
 - addresses, 421–427
 - authentication, 272–276
 - subtended DSLAMs, 119–121
 - support
 - protocols, 434–436
 - vendor, 144
 - Suspicious Flow Detection (SFD), 487
 - S-VLANs (stacked VLANs), 292, 355
 - switching
 - GELS, 154
 - LSPs, 76
 - MPLS. *See* MPLS
 - Synchronous Optical Network. *See* SONET
- T**
- tables, routing, 422
 - targeted advertising, 54
 - T-Com (Germany), 389
 - TCP (Transmission Control Protocol)
 - OOB communication channels, 358
 - windowing, 314
 - TC-specific (transport-convergence-specific), 237
 - TDM (Time-Division Multiplexing), 124, 291
 - Technical Specification Groups (TSGs), 370, 377
 - Telcordia, 5
 - Telebit Netblazer, 17
 - Telecom New Zealand., 268
 - Telecommunications Act of 1996, 9–10
 - Telecommunications Industry Association, North America (TIA), 370
 - Telecommunications Technology Association, Korea (TTA), 370
 - Telecommunications Technology Committee, Japan (TTC), 370
 - telephone services, coexistence with ADSL, 222
 - termination, bit stream access, 249–259
 - Third-Generation Partnership Project (3GPP), 366–367, 370
 - TIA (Telecommunications Industry Association, North America), 370
 - Time-Division Multiplexing (TDM), 124
 - Time-To-Restore (TTR), 236
 - TLS (Transport Layer Security), 477
 - TLV (Type-Length-Value) fields, 434
 - tokens, 306, 308
 - topologies
 - ATM, 251. *See also* ATM networks, 36–39
 - VPLS, 177–181

-
- ToS (Type of Service), 295
 - TR-001 Reference Model abbreviations, 21
 - tracing attacks, 471
 - tracking, CAC, 462–467
 - traditional transport, DSLAMs, 145–146
 - traffic
 - ARP, 418
 - BE, 292
 - bridging, 269
 - classes, 380
 - DiffServ, 296–299
 - policing, 306–313, 336–342
 - queuing, 313–318
 - routing, 153
 - train, 268
 - transmission, queuing, 313–318
 - Transmission Control Protocol. *See* TCP
 - Transmission Time Interval (TTI), 401
 - transmit unconditional parameter, 313
 - Transparent ATM Core Network Architecture, 25
 - transport capacity, SHDSL, 239
 - Transport Layer Security (TLS), 477
 - transport models, DSLAMs, 121
 - transport-convergence-specific (TC-specific), 237
 - trees
 - multicast, 93
 - Provider-Based, 154
 - SPT, 81
 - STP, 176
 - triggers on BNG interfaces, 480
 - triple play with IPv6, 430–441
 - triple-play networks
 - design, 67–68, 117
 - DSLAM aggregation, 122
 - Ethernet DSLAMs, 118–122
 - high-availability broadband access, 170–181
 - highly available core networks, 106–115
 - MPLS backbones, 68–79
 - multicast protocols in, 79–96
 - running MPLS on BNGs, 96–106
 - QoS, 346
 - centralized BNGs, 351–355
 - distributed BNGs, 356–357
 - L2CP, 357
 - trust boundaries, 346–351
 - services, 36
 - data services, 55–63
 - network topologies, 36–39
 - Video over IP, 40–55
 - voice services, 63–66
 - troubleshooting
 - availability, 171–173
 - back networks, 173
 - crosstalk, 221
 - trust boundaries, 346–351
 - TSG-A (Access Network Interfaces), 370
 - TSG-C (CDMA2000), 370
 - TSG-S (Services and Systems Aspects), 370
 - TSGs (Technical Specification Groups), 370, 377
 - TTA (Telecommunications Technology Association, Korea), 370
 - TTC (Telecommunications Technology Committee, Japan), 370
 - TTI (Transmission Time Interval), 401
 - TTR (Time-To-Restore), 236
 - tunneling, 142, 278
 - Type of Service (ToS), 295
 - Type-Length-Value (TLV) fields, 434
 - types of networks, selecting, 77–78
- U**
- UA (user agent), 65, 447
 - UMTS (Universal Mobile Telecommunications System), 369, 374–375, 380
 - unbundling
 - copper loop, 248
 - LLU, 246–249
 - unicast replies, VPLS, 150
 - Unicast IPTV, 44
 - Unisphere, 19
 - Universal Mobile Telecommunications System. *See* UMTS
 - Universal Wireless Communications (UWC), 366
 - unshielded twisted pair. *See* UTP
 - upstream bit rates, 252
 - user agent (UA), 65, 447
 - users
 - advanced dynamic service provisioning, 459–467
 - basic dynamic service provisioning, 452–459
 - credentials, 15
 - databases, 447
 - UTP (unshielded twisted pair), 4
 - UWC (Universal Wireless Communications), 366
-

V

- VCC (Voice Call Continuity), 394
- VCI (Virtual Circuit Identifier), 189, 250
- VCs (virtual circuits), 97, 158
- vendor support, Layer 2 VPNs, 144
- Vendor-Specific Attributes. *See* VSAs
- versions, IGMP, 101
- video
 - CAC, 462–467
 - distributed clusters, 48
 - head-end architecture, 41
 - integration, 395–399
 - middleware, 53
 - optimizing, 49
 - security, 51–53
- Video on Demand. *See* VoD
- Video over IP services, 40–55
- Virtual Circuit Identifier. *See* VCI
- virtual circuits. *See* VCs
- virtual ISPs, 270
- virtual LANs. *See* VLANs
- Virtual Path Identifier. *See* VPI
- Virtual Path Tunneling Architecture (VPTA), 25
- Virtual Private Dialup Network (VPDN), 411
- Virtual Private LAN Service. *See* VPLS
- virtual private networks. *See* VPNs
- Virtual Private Wire Service (VPWS), 124
- Virtual Router Redundancy Protocol. *See* VRRP
- Virtual Routing and Forwarding. *See* VRF
- VLANs (virtual LANs)
 - architecture, 156–162
 - feature comparisons, 168
 - hub-and-spoke DSLAMs, 121
 - multicast, 162–168
 - per-service, 158
 - provider architectures, 162–168
 - QoS, 168
 - S-VLANs, 292, 355
- VoD (video on demand), 3, 45–50, 484–486
- Voice Call Continuity (VCC), 394
- Voice over Internet Protocol. *See* VoIP
- voice services, 63–66
- VoIP (Voice over Internet Protocol), 3, 63
 - CAC, 462–467
 - jitter, 291
 - linking, 70
 - routes, 75
 - SBCs as proxies, 475
 - security, 474–480
 - TLS, 477
- VPDN (Virtual Private Dialup Network), 411
- VPI (Virtual Path Identifier), 189, 250
- VPLS (Virtual Private LAN Service), 146–156
 - multicast, delivering, 92–96
 - QoS, 154
 - scaling, 152–154
 - topology discovery, 177–181
- VPNs (virtual private networks), 14
 - hybrid models, 76
 - Interprovider, 78
 - L2VPNs, 124, 128–144
 - L3VPNs, 69
 - Layer 2, 62
 - Layer 3, 59
 - non-VPN routing models, 76
 - properties, 143
 - routes, 75
- VPTA (Virtual path Tunneling Architecture), 25
- VPWS (Virtual Private Wire Service), 124
- VRF (Virtual Routing and Forwarding), 59
 - address pools, 411
 - route-target leaking, 74
- VRRP (Virtual Router Redundancy Protocol), 37
- VSA (Vendor-Specific Attribute), 409, 456, 482

W

- walled-garden services, 58–59
- WANs (wide-area networks), 32
- web portals, 448
 - advanced dynamic service provisioning, 460
 - service provisioning flow, 451
- Weighted Random Early Discard. *See* WRED
- Weighted Round Robin (WRR), 319–322
- Westell, 8
- Whale Channel, 485
- wholesale broadband networks, 245–246
 - bit stream access, 249–259
 - comparing, 283–286
 - high-availability L2TP, 280–283
 - L2TP, 261–280
 - Layer 3, 259–261
 - LLU, 246–249
- wholesaleVoIP security, 478–480
- wide-area networks. *See* WANs

windowing, TCP, 314
Windows 95, DoS attacks, 470
WinNuke, 470
wireless broadband (future of)
 applications, 365
 CDMA evolution.3GPP2, 370–372
 components, 372–377
 evolution of, 399–403
 FMC, 389–394
 GSM evolution.3GPP, 367–370
 IMS, 381–389
 IMT-2000, 365–366
 video integration, 395–399
WLAN (wireless LAN), 390
WRED (Weighted Random Early Discard),
 308, 316

X

Xylogics, 17

Y

YouTube, 235

Z

zapping, 101
ZigBee, 366



THIS BOOK IS SAFARI ENABLED

INCLUDES FREE 45-DAY ACCESS TO THE ONLINE EDITION

The Safari® Enabled icon on the cover of your favorite technology book means the book is available through Safari Bookshelf. When you buy this book, you get free access to the online edition for 45 days.

Safari Bookshelf is an electronic reference library that lets you easily search thousands of technical books, find code samples, download chapters, and access technical information whenever and wherever you need it.

TO GAIN 45-DAY SAFARI ENABLED ACCESS TO THIS BOOK:

- Go to <http://www.prenhallprofessional.com/safarienabled>
- Complete the brief registration form
- Enter the coupon code found in the front of this book on the "Copyright" page

If you have difficulty registering on Safari Bookshelf or accessing the online edition, please e-mail customer-service@safaribooksonline.com.

