

Index

Symbols

2-D (two-dimensional) Gaussian distribution,
119

3-D BER function, 127

A

advanced link signaling, receiver testing,
329-330

**advanced serial link signaling, transmitter
testing,** 321-323

AM (amplitude modulation), 8

amplitude deviation, 3

amplitude modulation (AM), 8

for receiver driver voltage noise, LTI,
305-306

for receiver reference voltage noise,
LTI, 305

amplitude noise, 122. See also noise

amplitude noise PDF, 114-115

convolution, 116

eye diagrams, 116-118

arbitrary DJ PDF, deconvolution simulations,
143-144

architecture

clock recovery architecture, 254

link system architecture, 254

channel, 259

channel material and characteristics,
260-272

jitter budget, 276-278

performance factors, 259

subsystem architecture, 258

reference clock, 272-276

transmitter, 256

associative property, LTI properties, 66

asynchronized systems, clock jitter, 190-191

autocorrelation function, statistical estimators

for LTI systems, 68-69

averaged PWS and DDJ, 179

averages, statistical estimates, 39-40

B

band-pass filter function, 343

BER (bit error rate), 4-5

historical overview of, 20-21

jitter and, 119-122, 124-128

noise and, 119, 122-128

TJ, comparing, 158

BER CDF

DJ variation error, 159-160

jitter separation, 144

DJ PDF estimation, 151

tailfit method, 145-148

TJ estimation, 151-152

straightforward dual-Dirac method, 154-155

variation given DJ PDFs, 156-159

bit error mechanisms, 3-4

bit error rate, 4-5

historical overview of, 20-21
 jitter and, 119-122, 124-128
 noise and, 119, 122-128
 TJ, comparing, 158

bit errors, 109**bode plots, PLLs, 216-217****bounded uncorrelated jitter (BUJ), 15, 95**

PDF, 95-96
 spectrum, 96

budgets, jitter budget (link systems), 276-278**BUJ (bounded uncorrelated jitter), 15, 95**

PDF, 95-96
 spectrum, 96

BUJ separation, 172

Fourier spectrum, 173-174
 PSD, 174-175
 time-domain variance function, 175-177

C**cascading property, LTI properties, 67****Cauchy-Schwartz inequality, 45****CD (chromatic dispersion), 10****CDF (Cumulative Distribution Function),****distribution**

independent variables, 35-36
 multidimensional CDF, 34-35
 random variables, 31-34
 statistical random processes, 51-52

central limiting theory, 49-51**challenges, future challenges, 350-352****channel**

LTI, 288
channel LTI modeling, 288-289
channel transfer functions, 290-294
generic channel models, 294-299
testing, 324

reference transmitters, 326-327
 s-parameter-based channel testing, 324-326

channel (link system architecture), 259

channel material and characteristics, 260
 copper-based channels, 261-263
 crosstalk, 265-268
 optical fiber-based channels, 263-265
 reflection, 268-272

channel LTI modeling, 288-289**channel transfer functions, LTI, 290**

impulse responses, 290
 s-parameters, 291-294
 unit step responses, 291

characteristic parameters

second-order PLL analysis, 228-230
 third-order PLL analysis, 240

characteristics

channel characteristics, 260
 copper-based channels, 261-263
 crosstalk, 265-268
 optical fiber-based channels, 263-265
 reflection, 268-272

characterization, jitter, 132**Chebyshev Inequality, statistical estimates, 42-43****chromatic dispersion, optical fiber-based channels, 264****chromatic dispersion (CD), 10****clock jitter, 185**

asynchronous systems, 190-191
 defined, 186-187
 synchronized systems, 187-189

clock recovery (CR), 17

JTF (Jitter Transfer Function), 310-311

clock recovery architecture, 254**clock recovery circuit (CRC), 310****communication systems, 1-2****commutative property, TI properties, 66**

comparing

- conventional PLL analysis methods, 248-249
- time and frequency domain jitter separation methods, 181-182

components

- jitter, 15-16
- noise, 15-16

conditional probability, random variables, 29-30**continuous variables, 31****convergence**

- of estimator, 49
- sampling and estimation, 46-49

conversion

- phase jitter to phase noise, 203-204
- phase noise to phase jitter, 204-207

convolution

- amplitude noise PDFs, 116
- for jitter PDFs, 112-113

copper-based channels, 261

- dielectric loss, 262-263
- skin effect, 261-262

copper-based communication, 2**copper-based crosstalk, 11-12****correlation, statistical estimates, 44-46****CR (clock recovery), 17****CRC (clock recovery circuit), 310****cross-phase modulation (XPM), 268****crosstalk, 11**

- channels, 265
- electrical crosstalk, 265-267
- optical crosstalk, 267-268
- copper-based crosstalk, 11-12
- fiber-based crosstalk, 13

cycle-to-cycle jitter, 193-195

- interrelationships, 195
- frequency domain, 198-199
- time domain, 195-198

D**data-dependent jitter (DDJ), 15, 76-78**

- averaged PWS and, 179
- DCD (duty cycle distortion), 83-85
- estimation for RC LTI systems, 79
- model for, 85-86
- simulations, 79-82

DCD (duty cycle distortion), 7-9

- DDJ separation, 170-172

DCD (duty cycle distortion) jitter, DDJ (data-dependent jitter), 83-85**DDJ (data-dependent jitter), 15, 76-78**

- averaged PWS and, 179
- DCD (duty cycle distortion), 83-85
- estimation for RC LTI systems, 79
- model for, 85-86
- simulations, 79-82

DDJ separation, 167

- DCD and ISI separation, 170-172
- Fourier spectrum, 169-170
- jitter time function, 167-169

debugging jitter, 132**decision feedback equalizations (DFEs), 258, 314****deconvolution**

- DJ PDF determination
 - jitter separation PDFs, 140-142*
- simulations, 142
 - arbitrary DJ PDF, 143-144*
 - triangular DJ PDF, 142-143*
- theory, 141-142

deterministic jitter (DJ), 15, 76-78

- DDJ (data-dependent jitter), 76-78
- DCD (duty cycle distortion), 83-85
- estimation for RC LTI systems, 79
- model for, 85-86
- simulations, 79-80, 82
- variation error, BER CDF, 159-160

deterministic noise (DN), 114

device under test (DUT), 232
DFEs (decision feedback equalizations), 258, 314
DFT (Discrete Fourier Transformation), 164
diagnostics, jitter, 132
dielectric loss, copper-based channels, 262-263
direct FT spectrum, jitter as a function of frequency, 164-166
direct observables, jitter separation, 132
Discrete Fourier Transformation (DFT), 164
discrete variables, 31
distribution, random variables, 31

- CDF (Cumulative Distribution Function), 31-33
- CDF versus PDF, 33-34
- multidimensional PDF (Probability Density Function), 34-35
- PDF (Probability Density Function), 31, 34

distributive property, LTI properties, 66
DJ (deterministic jitter), 15, 76

- DDJ (data-dependent jitter), 76-78
- DCD (duty cycle distortion), 83-85
- estimation for RC LTI systems, 79
- model for, 85-86
- simulations, 79-82
- variation error, BER CDF, 159-160

DJ model, straightforward dual-Dirac method, 156, 158-160
DN (deterministic noise), 114
Domains, statistical domains (jitter separation), 133
DUT (device under test), 232
duty cycle distortion (DCD), 7-9
duty cycle distortion (DCD) jitter, 83-85

E

electrical crosstalk, channels, 265-267
electrical reflection, channels, 270-271

EMI (electromagnetic interference), 7

- reducing in reference clock, 273

ergodic random processes, 55-57
estimating jitter energy within certain frequency bands, 166
estimation, 46

- central limiting theory, 49-51
- peak-to-peak estimations, 47-48
- PWS, 180
- sample estimators and convergence, 46-49

estimator, convergence of, 49
expectation, statistical estimates, 39-40
eye diagrams, 110

- amplitude noise PDFs, 116-118
- for jitter PDFs, 113-114

F

f⁻² jitter, 101-104
PSD, 104
FEXT, 266-267
fiber-based communication, 2
fiber-based crosstalk, 13
filter coefficients, 285
first-order analytical model, generic channel models, 295-297
flick noise, 6
FM (frequency modulation), 8
four-wave mixing (FWM), 268
Fourier spectrum

- DDJ separation, 169-170
- PJ, RJ, and BUJ separation, 173-174

Fourier Transformation (FT), 136
frequency, time-frequency domain jitter separation

- jitter as a function of frequency, 164
 - direct FT spectrum, 164-166*
 - jitter PSD, 166-167*
- jitter as a function of time, 164

frequency domain, interrelationships (cycle-to-cycle jitter), 198-199
frequency-domain analysis, LTI systems, 63-65
frequency-domain modeling, PLLs, 212-213
frequency-domain PSD-based methodology, third-order PLL analysis, 241
frequency modulation (FM), 8
FT (Fourier Transformation), 136
functional analysis, PLLs, 214
 bode plots, 216-217
 impulse/step responses, 216
 phase and magnitude responses, 214-215
 poles and zeros, 218
future challenges, 350-352
FWM (four-wave mixing), 268

G

Gaussian distribution, 134
Gaussian jitter, 97
 PDF, 98-99
 PSD, 100-101
generic channel models, 294-295
 first-order analytical model, 295-297
 second-order analytical model, 297-299
generic two-dimensional PDFs, 118-119
GM (multiple Gaussian), 15

H

higher-order jitter processes, f^{-2}
 PDF, 101-104
 PSD, 104
historical overview of jitter, noise, BER and signal integrity, 20-21

I

IC (integrated circuit), 132
IFT (inverse Fourier Transformation), 136
implementation algorithm
 total jitter PDF, 136
 tail PDF identification, 136-137
 tailfitting, 137
impulse responses, channel transfer functions
 LTI, 290
 PLLs, 216
independent variables
 CDF, 35-36
 PDF, 35-36
integrated circuit (IC), 132
internal jitter testing, receiver testing, 330-333
interrelationships
 cycle-to-cycle jitter, 195
 frequency domain, 198-199
 time domain, 195-198
intersymbol interference (ISI), 7-10, 84
intrinsic jitter, 5
intrinsic noise, 5
 flick noise, 6
 shot noise, 6
 thermal noise, 5
inverse FT (IFT), 136
ISI (intersymbol interference), 7-10, 84
ISI separation, DDJ separation, 170-172

J

jitter, 3
 BER and, 119-122, 124-128
 BUJ. *See* BUJ (bounded uncorrelated jitter)

- clock jitter, 185
 - asynchronized systems, 190-191*
 - defined, 186-187*
 - synchronized systems, 187-189*
- components, 15-16
- cycle-to-cycle jitter, 193-195
- interrelationships, 195-199
 - DCD (duty cycle distortion), 83-85*
 - DJ (deterministic jitter), 76*
 - DDJ (data-dependent jitter), 76-86*
 - Gaussian jitter, 97*
 - historical overview of, 20-21*
 - PDF, 98-99*
 - PSD, 100-101*
- overall jitter PDFs, 110-112
 - convolution for, 112-113*
 - eye diagrams, 113-114*
- PDF, 105-106
- periodic jitter, 8, 193
- phase jitter, 191-192
- PJ. *See* PJ (periodic jitter)
- PLLs, 220
- phase jitter PSD, 221-223
- variance and PSD, 223-225
- PSD, 106
- RJ (random jitter), 15, 97
 - f^{-2} jitter,*
 - 101-104*
 - Gaussian jitter, 97*
 - PDF, 98-99*
 - PSD, 100-101*
- second-order PLL analysis, 230-232, 235-236
- sources of, 5
 - intrinsic jitter, 5*
 - nonintrinsic jitter, 7-13*
 - transfer function in serial data communication, 17-20*
 - translation from noise, 6-7*
- jitter and transfer function analysis, third-order PLL analysis, 241-247**
- jitter budget, link systems, 276-278**
- jitter energy, estimating within certain frequency bands, 166**
- jitter PDF**
 - convolution for, 112-113
 - eye diagrams, 113-114
- jitter PSD, jitter as a function of frequency, 166-167**
- jitter separation**
 - BER CDF, 144
 - DJ PDF estimation, 151
 - tailfit method, 145-148*
 - TJ estimation, 151-152*
 - direct observables, 132
 - PDFs, 133*
 - DJ PDF determination through
 - deconvolution, 140-144
 - tailfit method, 133-140
 - BER CDF, 145-148*
 - Monte Carlo simulations, 137*
 - PDF with statistical noise, 138*
 - results, 138-140*
 - theory for total jitter PDF, 134-135*
 - “transformed” BER CDF, 148-150*
 - statistical domain, 133
 - straightforward dual-Dirac method, 153
 - accuracy, 156, 158-160*
 - BER CDF, 154-155*
 - total jitter PDF, 153-154*
- time-frequency domain jitter separation. *See* time-frequency domain jitter separation

- “transformed” BER CDF
 - tailfit method, 148-150*
- jitter time function, DDJ separation, 167-169**
- joint probability, random variables, 29**
- JTF (Jitter Transfer Function)**
 - clock recovery, 310-311
 - link testing, 312-314

K

kurtosis, 42

L

Laplace Transformation. See LT, 164

law of larger numbers, 48-49

linear system theory, 61

- LTI properties, 66
 - associative property, 66*
 - cascading property, 67*
 - commutative property, 66*
 - distributive property, 66*
- LTI systems, 61
 - frequency-domain analysis, 63-65*
 - time-domain analysis, 61-63*

linear time-invariant (LTI) theory

- channel, 288
- channel LTI modeling, 288-289
- channel transfer functions, 290-294
- generic channel models, 294-299
- receiver, 299-301
 - amplitude modulation for receiver driver voltage noise, 305-306*
 - amplitude modulation for receiver reference voltage noise, 305*
 - clock recovery, 301-303*
 - drivers, 306*
 - equalization, 303-304*
 - loss, 301*

- transmitter, 282-283
 - digital data bits, 283*
 - drivers, 287*
 - equalization, 283-285*
 - jitter phase modulation, 285*
 - loss, 286*
 - noise amplitude modulation, 286*

link signaling

- loopback testing, 339-341
- PLLs, 337
- non-stimulus-based method, PLL testing, 337-338
- receiver
 - advanced link signaling, 329-330*
 - internal jitter testing, 330-333*
 - nominal link signaling, 328-329*
- receiver equalization, 322-323
- reference clock testing, 333-337
- stimulus-based method, PLL testing, 338
- testing, 310
 - advanced link signaling, 314-319*
 - nominal link signaling, 310-314*
- transmitter equalization, 321-322

link system architecture, 253-255

- channel, 259
- channel material and characteristics, 260-272
- jitter budget, 276-278
- performance factors, 259
- receiver (Rx), 257
- reference clock, 272-276
- subsystem architecture, 258
- transmitter, 256
 - performance factors, 257*
 - subsystem architecture, 256-257*

link testing, JTF (Jitter Transfer Function), 312-314

loopback testing, 339-341

LT (Laplace Transformation), 164**LTI (linear time-invariant), 281**

- channel, 288
- channel LTI modeling, 288-289
- channel transfer functions, 290-294
- generic channel models, 294-299
- receiver, 299-301
 - amplitude modulation for receiver driver voltage noise, 305-306*
 - amplitude modulation for receiver reference voltage noise, 305*
 - clock recovery, 301-303*
 - drivers, 306*
 - equalization, 303-304*
 - loss, 301*
- transmitter, 282-283
 - digital data bits, 283*
 - drivers, 287*
 - equalization, 283-285*
 - jitter phase modulation, 285*
 - loss, 286*
 - noise amplitude modulation, 286*

LTI properties, 66

- associative property, 66
- cascading property, 67
- commutative property, 66
- distributive property, 66

LTI systems, 61

- frequency-domain analysis, 63-65
- output autocorrelation function, 72
- output PSD, 71-72
- PSD (power spectrum density), 71
- statistical estimators, 68
 - autocorrelation function, 68-69*
 - mean, 68*
 - square-mean, 69-71*
- time-domain analysis, 61-63

M**magnitude responses, PLLs, 214-215****mean, 47-48**

- statistical estimators, for LTI systems, 68

medium. See channel**models**

- DDJ (data-dependent jitter), 85-86
- first-order analytical model, 295-297
- generic channel models, 294-295
- second-order analytical model, 297-299

moderately damped PLLs, 235-236**moments, statistical estimates, 41-42****Monte Carlo simulations, tailfit method, 137**

- PDF with statistical noise, 138
- results, 138-140

multidimensional CDF, 34-35**multidimensional PDF (Probability Density Function), distribution (random variables), 34-35****multiple-Gaussian (MG), 15****N****NEXT, 266-267****noise. See also amplitude noise**

- BER and, 119, 122-128
- components, 15-16
- defined, 2
- historical overview of, 20-21
- intrinsic noise
 - flick noise, 6*
 - shot noise, 6*
 - thermal noise, 5*
- overall amplitude noise PDF, 114-115
 - convolution, 116*
 - eye diagrams, 116-118*
- periodic noise, 8
- phase noise, 200-203

sources of, 5
 intrinsic noise, 5
 nonintrinsic noise, 7-13
 translating to timing jitter, 6-7

noise analysis
 PLLs, 220
 phase jitter PSD, 221-223
 variance and PSD, 223-225

nominal link signaling
 receiver testing, 328-329
 testing, 310-314

nominal serial link signaling, transmitter testing, 320-321

nonintrinsic jitter, 7-13

nonintrinsic noise, 7
 crosstalk, 11
 copper-based crosstalk, 11-12
 fiber-based crosstalk, 13
 DCD (duty cycle distortion), 8-9
 ISI (intersymbol interference), 9-10

O

observables, direct observables (jitter separation), 132

optical crosstalk, channels, 267-268

optical fiber-based channels, 263
 chromatic dispersion, 264
 polarization mode dispersion, 264-265

optical reflection, channels, 271-272

output autocorrelation function, LTI systems, 72

output PSD, LTI systems, 71-72

overall jitter PDF, 111-112

overdamped PLLs, 233
 parametric analysis, 234

P**parametric analysis**

moderately damped PLLs, 236
 overdamped PLLs, 234
 PLLs, 219-220
 underdamped PLLs, 232

pattern generator (PG), 328**PDF (Probability Density Function)**

amplitude noise PDF, 114-115
 convolution, 116
 eye diagrams, 116-118
 BER CDF variation, 156-159
 generic two-dimensional PDFs, 118-119
 jitter separation, 133
 for BUJ, 95-96
 versus CDF, 33-34
 convolution for, 112-113
 Distribution, random variables, 31, 34
 DJ PDF determination through
 deconvolution, 140-144
 tailfit method. See tailfit method
 overall jitter PDF, 111-112
 eye diagrams, 113-114
 f^{-2} jitter, 101-104
 for Gaussian jitter, 98-99
 independent variables, 35-36
 jitter, 105-106
 multidimensional PDF, 34-35
 for multiple PJs (periodic jitter), 93-94
 for single PJ (periodic jitter), 86-87
 statistical random processes, 51-52
 sum of two statistical variables, 36-38
 TJ PDFs, 113

- total jitter PDF, straightforward dual-Dirac method, 153-154
- for two PJs (periodic jitter), 88-92
- peak-to-peak estimations, 47-48**
- peak-to-peak value, 13-14**
- performance factors**
 - receiver (Rx), 259
 - transmitter, 257
- period jitter, 193**
- periodic jitter (PJ), 15, 86**
 - PDF for multiple PJs, 93-94
 - PDF for single PJ, 86-87
 - PDF for two PJs, 88-92
 - spectrum for multiple PJs, 94-95
 - spectrum for single PJ, 88
 - spectrum for two PJs, 92-93
- periodic noise and jitter, 8**
- PG (pattern generator), 328**
- phase interpolator (PI), 191**
- phase jitter, 191-192**
 - from phase noise conversion, 204-207
 - to phase noise conversion, 203-204
- phase jitter PSD, PLLs, 221-223**
- phase-locked loops. See PLLs**
- phase modulation (PM), 8**
- phase noise, 200-203**
 - from phase jitter conversion, 203-204
 - to phase jitter conversion, 204-207
- phase responses, PLLs, 214-215**
- PI (phase interpolator), 191**
- PJ (periodic jitter), 15, 86**
 - PDF for multiple PJs, 93-94
 - PDF for single PJ, 86-87
 - PDF for two PJs, 88-92
 - spectrum for multiple PJs, 94-95
 - spectrum for single PJ, 88
 - spectrum for two PJs, 92-93
- PJ separation, 172**
 - Fourier spectrum, 173-174
 - PSD, 174-175
 - time-domain variance function, 175-177
- PLLs (phase-locked loops), 17, 209**
 - bode plots, 216-217
 - comparison with conventional PLL analysis methods, 248-249
 - frequency-domain modeling, 212-213
 - functional analysis, 214
 - impulse/step responses, 216
 - phase and magnitude responses, 214-215*
 - poles and zeros, 218*
 - jitter, 220
 - variance and PSD, 223-225*
 - moderately damped PLL, 235
 - noise analysis, 220
 - phase jitter PSD, 221-223*
 - variance and PSD, 223-225*
 - overdamped PLLs, 233
 - parametric analysis, 219-220, 234
 - overview, 209-210*
 - phase jitter PSD, 221-223
 - second-order analysis, 225
 - characteristic parameters, 228-230*
 - jitter and transfer function analysis, 230-236*
 - system transfer function, 225-228
 - testing, 337
 - non-stimulus-based method, 337-338*
 - stimulus-based method, 338*
 - third-order PLL analysis, 236
 - characteristic parameters, 240*
 - jitter and transfer function analysis, 241-247*
 - system transfer function, 237-238*

- time-domain modeling, 211-212
 - underdamped PLLs, parametric analysis, 232
 - PM (phase modulation), 8**
 - PMD (polarization mode dispersion), 10**
 - optical fiber-based channels, 264-265
 - poles, PLLs, 218**
 - power spectrum density (PSD), 27**
 - BUJ separation, 174-175
 - DDJ separation, 169-170
 - f^{-2} jitter, 104
 - for Gaussian jitter, 100-101
 - jitter, 106
 - LTI systems, 71
 - output autocorrelation function, 72
 - output PSD, 71-72
 - PJ separation, 174-175
 - RJ spectrum, 174-175
 - statistical random processes, 58-59
 - variance, PLLs jitter and noise analysis, 223-225
 - Wiener-Kinchine theorem, 59-61
 - probability**
 - conditional probability, 29-30
 - joint probability, 29
 - random variables, 28
 - statistical independence, 30-31
 - properties**
 - associative property, 66
 - cascading property, 67
 - commutative property, 66
 - distributive property, 66
 - LTI properties, 66
 - PSD (power spectrum density), 27**
 - BUJ separation, 174-175
 - DDJ separation, 169-170
 - f^{-2} jitter, 104
 - for Gaussian jitter, 100-101
 - jitter, 106
 - LTI systems, 71
 - output autocorrelation function, 72
 - output PSD, 71-72
 - PJ separation, 174-175
 - RJ spectrum, 174-175
 - statistical random processes, 58-59
 - variance, PLLs jitter and noise analysis, 223-225
 - Wiener-Kinchine theorem, 59-61
 - PWS (pulse width shrinkage), 178**
 - averaged PWS and DDJ, 179
 - defined, 178-179
 - estimation, 180
- ## Q
- Q-factor**
 - BER, 152
 - DJ PDF estimation, 151
- ## R
- radio frequency (RF), 3, 200**
 - random Gaussian jitter (RGJ), 111**
 - random Gaussian noise (RGN), 115**
 - random high-order jitter (RHJ), 111**
 - random higher-order noise (RHN), 115**
 - random jitter (RJ), 15, 97**
 - f^{-2} jitter
 - PDF, 101-104
 - PSD, 104
 - Gaussian jitter, 97
 - PDF, 98-99
 - PSD, 100-101
 - random noise (RN), 114**
 - random processes**
 - relationships between, 57-58
 - statistical estimators for, 52-54

- statistical random processes
 - CDF*, 51-52
 - ergodic random processes*, 55-57
 - PDF*, 51-52
 - single power and power spectrum density (PSD)*, 58-61
 - SSS (strict-sense stationary)*, 55
 - WSS (wide-sense stationary)*, 54-55
- random variables**
 - continuous variables, 31
 - discrete variables, 31
 - distribution functions, 31
 - CDF (Cumulative Distribution Function)*, 31-33
 - CDF versus PDF*, 33-34
 - multidimensional PDF (Probability Density Function), 34-35
 - PDF (Probability Density Function), 31-34
 - probability and, 28
 - conditional probability*, 29-30
 - joint probability*, 29
 - statistical independence*, 30-31
- RC LTI systems, DDJ estimation, 79**
- receiver**
 - LTI, 299-301
 - amplitude modulation for receiver driver voltage noise*, 305-306
 - amplitude modulation for receiver reference voltage noise*, 305
 - receiver clock recovery, 301-303
 - receiver drivers, 306
 - receiver equalization, 303-304
 - receiver loss, 301
 - testing, 327
- receiver (Rx), testing**
 - advanced link signaling, 329-330
 - internal jitter testing, 330-333
 - nominal link signaling, 328-329
- receiver (Rx) (link system architecture), 257**
 - performance factors, 259
 - subsystem architecture, 258
- receiver clock recovery, LTI, 301-303**
- receiver drivers, LTI, 306**
- receiver equalization**
 - link signaling, 322-323
 - LTI, 303-304
 - testing, 317-319
- receiver loss, LTI, 301**
- reducing EMI, reference clock, 273**
- reference clock, 272-276**
 - testing, 333-337
- reference transmitters, channel testing, 326-327**
- references, 16-17**
- reflection**
 - channels, 268-270
 - electrical reflection, 270-271
 - optical reflection, 271-272
- reflection coefficient, channel transfer functions, 293**
- relationships between random processes, 57-58**
- RF (radio frequency), 3, 200**
- RGJ (random Gaussian jitter), 111**
- RGN (random Gaussian noise), 115**
- RHJ (random high-order jitter), 111**
- RHN (random higher-order noise), 115**
- RJ (random jitter), 15, 97**
 - f⁻² jitter
 - PDF*, 101-104
 - PSD*, 104
 - Gaussian jitter, 97
 - PDF, 98-99
 - PSD, 100-101

RJ (random jitter) separation, 172

- Fourier spectrum, 173-174
- PSD, 174-175
- time-domain variance function, 175-177

RMS (root-mean-square), 14-15**RN (random noise), 114****RSS, jitter budgets, 278****S****s-parameter-based channel testing, 324-326****s-parameters, channel transfer functions (LTI), 291-294****SA (spectrum analyzer), 187, 338****sampling, 46**

- central limiting theory, 49-51
- sample estimators and convergence, 46-49

SBS (stimulated Brillouin scattering), 268**second-order analytical model, generic****channel models, 297-299****second-order PLL analysis, 225**

- characteristic parameters, 228-230
- jitter and transfer function analysis, 230-236
- system transfer function, 225-228

separation

- ISI separation, from DDJ, 170-172
- jitter separation. *See* jitter separation
- RJ (random jitter) separation, 172
 - Fourier spectrum, 173-174*
 - PSD, 174-175*
 - time-domain variance function, 175-177*

serial data communication, jitter transfer function, 17-20**SG (single-Gaussian), 15****Shannon, Claude, 1****shot noise, 6****signal integrity, 3**

- historical overview of, 20-21

signal-to-noise-ratio (SNR), 219**signaling**

- advanced serial link signaling, transmitter testing, 321-323
- nominal serial link signaling, transmitter testing, 320-321

simulations

- DDJ (data-dependent jitter), 79-82
- jitter and transfer function analysis, third-order PLL analysis, 243

single-Gaussian (SG), 15**single power, statistical random processes, 58-61****skewness, 42****skin effect, copper-based channels, 261-262****slicers, 303****SNR (signal-to-noise-ratio), 219****sources**

- of jitter, 5
 - intrinsic jitter, 5*
 - nonintrinsic jitter, 7-13*
- of noise, 5
 - intrinsic noise, 5*
 - nonintrinsic noise, 7-13*

spectral analysis, 51

- CDF, 51-52
- PDF, 51-52

spectrum

- for BUJ, 96
- direct FT spectrum, jitter as a function of frequency, 164-166
- Fourier spectrum
 - for multiple PJs (periodic jitter), 94-95
 - PJ, RJ, and BUJ spectrum, 173-174
 - for single PJ (periodic jitter), 88
 - for two PJs (periodic jitter), 92-93

spectrum analyzer (SA), 187, 338

square-mean, statistical estimators for LTI systems, 69-71

SRS (stimulated Raman scattering), 268

SSS (strict-sense stationary), 55

standard deviation, 47-48

static timing reference, 16

statistical domain, jitter separation, 133

statistical estimates, 38

- Chebyshev Inequality, 42-43
- correlation, 44-46
- expectation or average, 39-40
- moments, 41-42
- variance, 40

statistical estimators

- LTI systems, 68
 - autocorrelation function*, 68-69
 - mean*, 68
 - square-mean*, 69-71
- for random processes, 52-54
- statistical independence, random variables, 30-31

statistical noise, PDFs (Monte Carlo simulations), 138

statistical random processes, 51-54

- CDF, 51-52
- ergodic random processes, 55-57
- PDF, 51-52
- single power and power spectrum density (PSD), 58-61
- SSS (strict-sense stationary), 55
- WSS (wide-sense stationary), 54-55

statistical variables, PDF (sum of), 36-38

step responses, PLLs, 216

stimulated Brillouin scattering (SBS), 268

stimulated Raman scattering (SRS), 268

straightforward dual-Dirac method, jitter separation, 153

- accuracy, 156-160
- BER CDF, 154-155
- total jitter PDF, 153-154

strict-sense stationary (SSS) random process, 55

subsystem architecture

- receiver (Rx), 258
- transmitter, 256-257

synchronized systems, clock jitter, 187-189

system transfer function

- second-order PLL analysis, 225-228
- third-order PLL analysis, 237-238

T

tail PDF identification, 136-137

tailfit method, 133-134

- BER CDF, 145-148
 - implementation algorithm*, 136
 - tail PDF identification*, 136-137
 - tailfitting*, 137
- Monte Carlo simulations, 137
- PDF with statistical noise, 138
- results, 138-140
- theory for total jitter PDF, 134-135
- “transformed” BER CDF, 148-150

tailfitting, 137

taps, 285

testing

- channels, 324
 - reference transmitters*, 326-327
 - s-parameter-based channel texting*, 324-326
- link signaling, 310
 - advanced link signaling*, 314-319
 - nominal link signaling*, 310-314

- loopback testing, 339-341
- PLLs, 337
 - non-stimulus-based method*, 337-338
 - stimulus-based method*, 338
- receiver, 327
 - advanced link signaling*, 329-330
 - internal jitter testing*, 330-333
 - nominal link signaling*, 328-329
- receiver equalization, 317-319
- reference clock testing, 333-337
- transmitter equalization, 315-317
- transmitter output testing, 319
 - advanced serial link signaling*, 321-323
 - nominal serial link signaling*, 320-321
- thermal noise, 5**
- third-order PLL analysis, 236**
 - characteristic parameters, 240
 - jitter and transfer function analysis, 241-247
 - system transfer function, 237-238
- TIA (time interval analyzer), 133**
- time and frequency domain jitter separation methods, comparing, 181-182**
- time domain, interrelationships (cycle-to-cycle jitter), 195-198**
- time-domain analysis, LTI systems, 61-63**
- time-domain measurements, jitter, 132**
- time-domain modeling, PLLs, 211-212**
- time-domain variance function-based methodology, PLLs, 230**
- time-domain variance functions**
 - BUJ separation, 175-177
 - PJ separation, 175-177
 - RJ spectrum, 175-177
- time-frequency domain jitter separation**
 - jitter as a function of frequency, 164
 - direct FT spectrum*, 164-166
 - jitter PSD*, 166-167
 - jitter as a function of time, 164
- time interval analyzer (TIA), 133**
- timing deviation, 3**
- timing jitter. See jitter**
- TJ, BER (comparing), 158**
- TJ estimation, BER CDF, 151-152**
- TJ PDF, 113**
- TN (total noise), 114**
- total jitter PDF**
 - implementation algorithm, 136
 - tail PDF identification*, 136-137
 - tailfitting*, 137
 - straightforward dual-Dirac method, 153-154
 - theory for, 134-135
- total noise (TN), 114**
- transfer function analysis, second-order PLL analysis, 230-236**
- “transformed” BER CDF, jitter separation (tailfit method), 148-150**
- translation of noise to timing jitter, 6-7**
- transmitter**
 - LTI, 282-283
 - transmitter digital data bits, 283
 - transmitter drivers, 287
 - transmitter equalization, 283-285
 - transmitter jitter phase modulation, 285
 - transmitter loss, 286
 - transmitter noise amplitude modulation, 286
- transmitter (link system architecture), 256**
 - performance factors, 257
 - subsystem architecture, 256-257
- transmitter digital data bits, LTI, 283**
- transmitter drivers, LTI, 287**
- transmitter equalization**
 - link signaling, 321-322
 - LTI, 283-285
 - testing, 315-317
- transmitter jitter phase modulation, LTI, 285**
- transmitter loss, LTI, 286**
- transmitter noise amplitude modulation, LTI, 286**

transmitter output testing, 319

advanced serial link signaling, 321-323

nominal serial link signaling, 320-321

triangular DJ PDF, deconvolution simulations, 142-143**two-dimensional (2-D) Gaussian distribution, 119****U****underdamped PLLs, parametric analysis, 232****unit step responses, channel transfer functions (LTI), 291****V****variables**

independent variables, PDF and CDF, 35-36

random variables, probability and, 28-31

variance, PSD

PLLs jitter and noise analysis, 223-225

statistical estimates, 40

variation error, BER CDF (DJ PDFs), 156, 158-159**vector network analyzer (VNA), 293****verification, jitter and transfer function analysis (third-order PLL analysis), 243****VNA (vector network analyzer), 293****W****wavelength division multiplexing (WDM), 267****WDM (wavelength division multiplexing), 267****wide-sense stationary (WSS) random process, 54-55****Wiener-Kinchine theorem, 59-61****WSS (wide-sense stationary), 54-55****X-Y-Z****XPM (cross-phase modulation), 268****zeros, PLLs, 218**