

Numerics

10BaseT, 200–18

Category 3 twisted pair model,
204–6

crosstalk models, 206–7

Manchester encoding, 207

PSD, 208–9

Simulink model, 214–18

SNR, 212–13

time domain masks, 209–10

transceiver, 211–12

100BaseT2, 250–66

Category 3 cable model, 256–57

Data constellation, 252

Decoding, 255–56

Encoding, 251–55

FEXT, 258–59

idle constellation, 255

NEXT, 256–58

PSD, 258–60

random sequence generator,
253–54

Simulink model, 263–66

SNR, 261–62

time domain mask, 259

transceiver, 261

100BaseT4, 218–34

8B6T, 225

Category 3 twisted pair, 220–23

channel equalizer, 234

crossover, 219–20

frame, 227

NEXT models, 222–23

PSD, 227

Simulink model, 231–32

SNR, 229–30

transceiver, 228–29

transmit pulse masks, 226

100BaseTX, 234–50
 4B5B encoding, 235
 Category 5 twisted pair, 236–37
 crosstalk models, 236–37
 descrambler synchronization,
 239–40
 PSD, 240–41
 scrambler, 238
 Simulink model, 245–50
 SNR, 245–46
 transceiver, 240–41

A

AAL5 (ATM Adaptation Layer
 Type 5), 515
ABCD parameters, 33–39
 of a splitter, 82–84
Adjacent TV channels, 74
ADSL end-to-end system architec-
 ture, 514
ADSL service, 513
AGC, 445
Allowed PSD, 53
Aloha protocol, 195–96
Ampacity estimation, 107–9
ANSI (American National Stan-
 dards Institute) C63.4-1992,
 129
Arbitration protocol, 343–55
ATM cell, 515
ATM (Asynchronous Transfer
 Mode), 512

Autonegotiation, 267–73
 parallel detection, 268
 priority resolution, 267–68
Available radio frequency
 spectra1, 145–51
AWG (American Wire Gauge), 23

B

Barker code, 442
Base link code word, 271
BCC, 4575–8
BCPM (Barker Code Position Mod-
 ulation), 450
Binary complementary code-
 words, 452
BOSS (Bus Owner Supervisor
 Selector), 362

C

Cable modem end-to-end system
 architecture, 518
Cable modem service, 517
Cable Television Channel Identifi-
 cation Plan, 88
Cable TV channels, 89
Cable TV hybrid fiber coaxial dis-
 tribution network, 77
Cable TV noise environment, 93–
 95
Carrier current system, 128

- Category 5 cable, 24
- CCA (Clear Channel Assessment), 445
- CCK (Complementary Code Keying), 448–75
- CEBus, 10
 - block converter, 390
 - coaxial cable physical layer, 389–91
 - history, 382–83
 - Node 0, 384
 - Node 0 coaxial cable, 389
 - packet format, 385
 - physical layers, 384
 - PL physical layer, 386–89
 - PL transceiver, 388
 - UST (Unit Symbol Time), 386
- Centralized distribution panel, 5–6
- CFP (Contention Free Period), 427–28
- Channel capacities
 - 10BaseT, 212
 - 100BaseT2, 263
 - 100BaseT4, 231
 - 100BaseTX, 245
 - DSSS environment, 446
 - FHSS environment, 439
 - for twisted pair cable, 52–61
 - for in-house power lines, 137
 - HomePNA 1.0, 315
 - HomePNA 2.0, 332
 - HomeRF 1.0, 508
 - HomeRF 2.0, 509
 - HRDSSS environment, 469
 - Indoor radio wave, 181
 - of in-house coaxial cable, 96
 - OFDM environment, 485
- Channel capacity calculation, 53
- Channel model
 - coaxial cable, 90–93
 - of in-house power lines, 123–28
 - random electrical wiring, 125
- Characteristic impedance, 27–28
 - of electrical cable, 111
- Cipher Block Chaining, 397
- CMTS (Cable Modem Termination Systems), 519
- CO (Central Office), 513
- Coaxial cable, 77–80
 - attenuation, 78
 - insertion losses, 80–81
 - primary parameters estimation, 78–80
- Code of Federal Regulation
 - Title 47 Part 2, 146–49
 - Title 47 Part 15, 150–51
 - title 47 Section 15.3, 128
- Complementary codewords, 453–56
- Complementary codes, 453
- Convolution encoder, 403–5
- Coupling Factor, 133
- CRC (Cyclical Redundancy Check), 193–94, 422
- CRC-16, 433
- Crossover
 - cable, 204
 - embedded, 203
- Crosstalk of three-conductor electrical cable, 113–17

Crosstalk noise, 45–46
CSMA/CA, 425–27
 DCF (Distributed Coordinate Function), 426
 PCF (Point Coordinate Function), 427
CSMA/CD, 194–99
 protocol, 198

D

Deployment trend, 13–14
Destination Address, 192
DHCP (Dynamic Host Configuration Protocol), 517
Dielectric properties of building materials, 152
DIFS (Distributed Interframe Space), 426, 497
Distribution transformer, sharing, 120–21
DNS (Domain Name Server), 516
DOCSIS (Data Over Cable System Interface Specification), 519
DSLAM (DSL Access Multiplexer), 513
DSSS (Direct Sequence Spread Spectrum) packet scrambling, 441–42
DSSS preamble, 440–41
DSSS Simulink model, 446–48

E

Egress, 49
Electrical cables, 105–17
 primary parameters estimation, 110–11
Electrical load, 121–22
Electrical power distribution system, 117–21
Electrical wiring
 configuration, 120
 noise environment, 134–37
Emission measurement, 129–32
Equal power conversion factor, 50
Equivalent noise temperature, 180
Ethernet, 8, 189–302
 frame, 191–92

F

Fast Link Pulse, 269–73
Fast Walsh Transform, 461–3
 modified, 463–65
FCS (Frame Check Sequence), 193
Feeder panel, 119
FEXT (Far-End Crosstalk), 46
 model, 47
FHSS (Frequency-Hopping Spread Spectrum)
 frequency channels, 435
 hopping sequence, 435
 Simulink model, 440
FireWire, 9

FLP encoding, 271
Fraction polynomial
 Category 3 cable NEXT model,
 223
 Differential Category 3 cable
 model, 222
Frequency bands, 146

G

Galois field
 log table, 400
 power representation, 399
 primitive polynomial, 399
Gaussian filter
 frequency response, 434
 time domain response, 434
GFSK (Gaussian Frequency Shift
 Keying), 433–34
Globe radio frequency regions,
 146–47

H

Hadamard matrix, 461
HFC (Hybrid Fiber Coaxial), 519
Home environment, 4–8
Home network technologies, 12–13
HomePlug, 10
 CSMA/CA, 396
 DES, 397
 history, 391–92
 MII, 397

 puncturing, 394
 Reed-Solomon code, 401
 scrambling, 394
 technology highlights, 393–96
 transceiver, 393, 395
HomePNA, 9
 history, 304
HomePNA 1.0, 304–18
 encoding, 307
 frame, 305
 in-house wiring, 311
 MAC Interface, 317
 PSD, 310
 pulse waveform, 310
 transceiver, 312
 transmission throughput, 308
HomePNA 2.0, 318–35
 compatibility mode, 322–23
 frame, 320
 MII, 334–35
 priority, 333–34
 PSD, 324
 scrambler, 321
 SNR, 332–33
 test loops, 324
 transceiver, 326
HomeRF, 11
 2FSK and 4FSK modulations,
 505–6
 Bias Suppression Encoding,
 504–5
 header type 1, 2, 3, 498–99
 history, 493
 MAC, 494–97
 MAC frame types, 498–502
 voice channel, 497

HomeRF 1.0
 encryption, 502-3
 frequency hopping, 506-7
 packet, 504
 super frame, 496
 transceiver, 507
 HomeRF 2.0, 508-9
 Home router, 524

I

ICS (Internet Connection Sharing), 523
 IEEE 1394, 9
 arbitration, 349-55
 arbitration efficiency, 353-55
 asynchronous packets, 351
 cycle, 351
 data/strobe encoding, 359
 history, 341-42
 initialization process, 346-49
 isochronous packets, 350
 packets format, 355
 plugs, 346
 PSD, 360
 shielded twisted pairs, 345
 topology, 344
 transceiver, 358
 IEEE 1394b, 361-73
 5B6B encoding, 368
 arbitration, 362-64
 capabilities, 361
 control symbol encoding, 364
 initialization, 366-67

Category 5 twisted pair, 372-73
 packet format, 367
 plug, 369
 PSD, 372
 scrambler, 364
 transceiver, 371
 Incidental radiator, 128
 Incident, reflected, and transmitted waves, 154
 Indoor radio environment, 151-63
 Indoor radio wave
 impulse response model, 167-78
 impulse response model, amplitudes, 169-70
 in-phase channel impulse response, 176
 received power, 152
 received power modified, 163
 signal strength measurements, 166-67
 Ingress, 49, 94
 noise model, 95
 In-house
 electrical wiring cable, 105-7
 electrical wiring model, 117-28
 TV wiring, 76-77
 wiring branch loss, 42-43
 wiring reflection loss, 42-44
 wiring wire loss, 41-42
 Input impedance, 40
 Insertion loss, 41
 based on propagation constant, 28
 Differential Category 3 cable model, 221-23

- of electrical wiring cable, 111
- of three-conductor electrical cable, 116–17
- Intentional radiator, 128
- IP (Internet Protocols), 511
- IP address, 516
- IP addresses, 526
- IP packet format, 526
- ISM (Industrial, Scientific, and Medical), 149
 - bands, 7
 - wavelengths, 151
- ISP (Internet Service Provider), 511

L

- Length/Type, 192
- Link test pulses, 270
- LISN (Line Impedance Stabilization Network), 135
- LLC frame structure, 520

M

- MAC bridge function, 530
- Masquerading, 528
- MBOK, 450
- MDF (Main Distribution Frame), 513
- Message page encoding, 272
- MII (Media Independent Interface), 273–76

- MII data interface, 274–75
- MII management frame structure, 275
- MII management interface, 275–76
- MII receive path timing, 275
- MII transmit path timing, 274
- MLT-3 (Multi-Level Transition), 240
- Modified Walsh codewords, 450

N

- NAP (Network Access Provider), 513
- NAPT (Network Address Port Translation), 512, 528
- NEC (National Electric Code), 117
- NBF (NetBEUI Frame or NetBIOS Frame), 522
- NetBEUI, 512, 522
- NEXT (Near-End Crosstalk), 45
 - model, 47
- NM-B, 105
- NMP (Name Management Protocol), 522
- Noise figure, 179
- Noise power at a particular temperature, 181

O

- Off-the-air TV channels, 87–8
- Original cable TV, 73

P

Packet encapsulation, 532
Parameterized models, 27
PC and consumer electronic networking, 533
Peer-to-peer networking, 521–23
Permitted service, 147
PIFS, 426–27
POTS (Plain Old Telephone Set), 30–32
POTS circuit simplified, 32
Power line noise, 134
Power loss, 166
PPM (Pulse Position Moducation), 306
Preamble, 192
Primary service, 147
Propagation constant, 28
PVC (Permanent Virtual Circuit), 512

Q

QAM Signal to Noise Ratio, 327–9
QMBOK, 450

R

Radiated emission limit, 129
Radio frequency interference, 49–52

Radio frequency usage allocation table, 146–48
RC4, 430–31
Reed-Solomon code, 398
 decoding, 402–3
 encoding, 402
 generator polynomial, 401
Reflected and penetrated radio wave, 153–63
Reflection enhancement estimation, 163–5
Residential wiring, 24
RFC 1483, 515
RFI loss, 51
RJ-45, 201
 Type A and Type B conventions, 202
RLGC primary parameters, 25
Romex, 105
RSSI (Received Signal Strength Indication), 445
RLC (Run Length Code), 307

S

SAR (Segmentation And Reassembly), 515
Secondary parameters, 27–28
Secondary service, 147
Series inductance, 25
Series resistance, 25
SFD, 192

Sharing distribution transformer,
120–1

Shunt capacitance, 25

Shunt conductance, 25

SIFS, 426–27, 496–97

Slotted Aloha, 196

SMP (Session Management Protocol), 523

SNAP (Subnetwork Access Protocol), 512

Source address, 192

Spanning tree algorithm, 532

Splitters, 80

Star daisy-chain, 21
example configuration, 30–31

Structured wiring, 5

T

Tap, 85

TCP packet format, 527

TCP (Transmission Control Protocol), 527

Technology field encoding, 271

THHN, 105

TIC (Time Interval Clock), 306

Traffic intensity

- Aloha, 195–96
- Ethernet, 198–99
- Slotted Aloha, 196

Transfer function, 40

Transmission parameters of
spread spectrum systems,
150

Twisted pair cables, 22–29

Two-port network, 33–39

- consisting of a series impedance, 35
- consisting of a shunt impedance, 36

Two-port networks

- differential Category 3 cable model, 220–22
- in parallel, 38–39
- in series, 37
- two identical in parallel, 39

U

UBR (Unspecified Bit Rate), 515

UDP (User Datagram Protocol),
528

- packet format, 528

UF-B, 105

Unintentional radiator, 128

USE-2, 105

V

Varistors, 31

VCI (Virtual Channel Identifier),
515

Viterbi decoding, 406

VPI (Virtual Path Identifier), 515

W

- Wall plate, 6
- Walsh codewords, 451
 - modified, 450
- WINS (Windows Internet Naming Service), 517
- Wire gauges, 23
- Wireless Ethernet, 11, 417–92
 - address fields, 422
 - CCK (Complementary Code Keying), 448–75
 - control frames, 423–24
 - DSSS packet, 441
 - DSSS PSD, 443
 - DSSS transceiver, 444
 - duration/ID, 422
 - FCS (Frame Control Field), 422–23
 - FHSS packet, 432
 - FHSS transceiver, 436
 - HRDSSS decision feedback equalizer, 465–66
 - HRDSSS history, 450
 - HRDSSS packet, 449
 - HRDSSS Simulink model, 469–75
 - HRDSSS transceiver, 460
 - MAC frame, 421
 - Management frame, 424–5
 - Media access control protocol, 420–31
 - Multipath channel model, 456–57
 - OFDM (Orthogonal Frequency Division Multiplex) convolution encoder, 479
 - OFDM interleaving, 479–81
 - OFDM packet, 476
 - OFDM preamble, 477
 - OFDM PSD, 482
 - OFDM scrambling, 478
 - OFDM Simulink model, 484–8
 - OFDM transceiver, 482
 - WEP (Wired Equivalent Protection), 429

X

- X-10, 10
 - encoding, 379
 - history, 376
 - implementation, 382
 - packet format, 378
 - transceiver, 381
 - waveforms, 379–80