
INDEX

2D field solvers, 139–142
accuracy, 139–140
characteristic impedance and, 261–266
cross talk and, 413–419
geometry and, 139
LaPlace's Equation and, 139
results, stripline comparison, 262

A

accuracy, approximations, 32
active nets, 401
adjacent planes, impedance and, 242–243
aggressor nets, 401
cross talk and timing, 462–464
amplitude
sine waves, 47
voltage to current ratio, 93
analytical approximations, 30, 31
antennas, EMI and, 14
approximation
characteristic impedance, 257–261
equations, 128
levels of approach, 30, 31–32
attenuation, 3
dB and, 367–372
definition, 380

FR4, 372–373
lossy lines, 372–381
napiers, 368
per length, definition, 380
AWG (American Wire Gauge), 116\

B

bandwidth
clock frequency and, 66–68
interconnects, 71–76
lossy lines and, 386–392
LC models, 269
measurement and, 68–70
models, 70–71
rise time and, 56–61
signals, 64–66
behavioral simulators, 23–24
BGAs (ball grid arrays), impedance and, 8
bounce diagrams, reflections and, 288–289
branches
discontinuities and, 295
impedance and, 6
bulk dielectric constant, 144
bulk resistivity, 114–115
sheet resistance and, 118
volume resistivity, 115

C

- Cable TV coaxial cable, 226
- cables. *See also* interconnects
 - impedance, 229
- capacitance
 - capacitively coupled currents, 426–430
 - coupling origin, cross talk and, 403–405
 - decoupling
 - ground planes, 130–133
 - power planes, 130–133
 - displacement current, 125
 - field lines, 126
 - insulating material and, 129
 - interconnects, length, 134–139
 - matrix element, even mode calculation, 542–545
 - Maxwell capacitance matrix, 413–419
 - parallel plate approximation and, 128–129
 - reflections, traces, 310–313
 - spheres, 126–127
 - SPICE capacitance matrix, cross talk and, 409–413
 - traces, reflections, 310–313
 - voltage and, 124
- capacitive coupling, cross talk and, 10
- capacitive delay adders, reflections and, 313–315
- capacitive end terminations, reflections, 307–309
- capacitive load, 3
- capacitors
 - current flow, 124–126
 - displacement current, 125
 - ideal, time domain and, 87–90
 - interconnects and, 109
 - physical characteristics, 123
- characteristic impedance, 223–225
 - approximations and, 257–261
 - calculating, 2D field solvers and, 261–266
 - famous, 225–228
 - frequency variation, 273–275
 - matrix, 546–548
 - Ohms, 223
 - return path width, 263–264
- circuit elements, real vs. ideal, 84–86
- circuit models
 - creating from calculation, 29–34
 - cross talk and, 407–409
 - n-section lumped, 263–273
- circuit simulators, 23
- circuit theory, SPICE and, 99–103
- clearance holes, fields of, loop inductance of planes, 183–184
- clock frequencies
 - bandwidth and, 66–68
 - increases, problems and, 1
- clock period, time domain and, 42
- coax transmission lines, 224
 - Cable TV, 226
 - RG58, 225
 - RG59, 226
 - RG174, 226
- coils
 - flux lines, inductance and, 147
 - inductance and, 147
- common signals
 - converting from differential signals, 525–530
 - EMI and, 530–535
 - even mode voltage components, 507–509
 - odd mode voltage components, 507–509
 - terminating, 518–525
- compensation, reflections and, 328–330
- complex dielectric constant, 381
- conductivity
 - resistivity and, 114
 - Siemens, 114
- conductors
 - capacitors and, 123
 - current flow and, 125–126
 - inductance, geometry and, 151
 - Maxwell's Equations and, 24
 - permeability, 198
 - resistance, loss and, 338–342
 - transmission lines, 205
- connectors, impedance and, 6
- constants, dielectric constants, 129–130

- controlled-impedance transmission lines, 208, 223–225
 - cross talk and, 8
 - modeling and, 252
- converting differential signals to common signals, 525–530
- coplanar lines, 208
- copper, electrons in, speed, 210–211
- corners
 - discontinuities and, 295
 - reflections and, 315–320
 - coupled transmission lines, ideal model, 515–516
- coupling
 - to adjacent traces, 336
 - capacitively coupled currents, 426–430
 - differential impedance and, 478–482
 - impact, 482–488
 - inductively coupled currents, 430–433
 - noise on victim line, 456
 - origin, cross talk and, 403–405
 - tightly, advantages/disadvantages, 540–542
- cross overs, discontinuities and, 295
- cross-sectional geometry, characteristic impedance and, 257–258
- cross sections, differential pairs, 476
- cross talk
 - 2D field solvers and, 413–419
 - capacitance coupling origin and, 403–405
 - capacitive coupling, 10
 - circuit models, 407–409
 - coupling, origin, 403–405
 - definition, 156
 - describing, 407–409
 - dielectric constants and, 459–460
 - differential pairs, 535–537
 - FEXT, 407, 436–443
 - decreasing, 443–445
 - ground bounce and, 464–465
 - guard traces, 452–459
 - inductance, coupling origin and, 403–405
 - inductive coupling, 10
 - inductive matrix and, 419–421
 - interconnects and, 8
 - Maxwell capacitance matrix and, 413–419
 - nets and, 8, 401
 - NEXT, 407, 433–436
 - noise source and, 4
 - saturation length and, 421–426
 - simulations, 445–451
 - coupled noise on victim line, 456
 - SPICE capacitance matrix, 409–413
 - SSN and, 9
 - superposition, 402–403
 - switching noise and, 464–467
 - timing and, 460–464
 - transmission lines and, 8
 - uniform transmission lines, 421–426
- CSPs (chip-scale packages), impedance and, 8
- current
 - capacitively coupled currents, 426–430
 - displacement current, capacitors and, 125
 - distribution, 238–239
 - frequency dependence, 241
 - impedance of signal return loop, 240
 - planes, 241
 - eddy currents, 200–202
 - flow
 - capacitors and, 124–126
 - conductors and, 125–126
 - image currents, 200–201
 - impedance and, 79
 - inductance, magnetic-field line loops, 147–150
 - inductively coupled currents, 430–433
 - loops and, 236
 - transmission lines, 236–237
 - microstrips, 239
 - ratio to voltage = impedance and, 35
 - return-current distribution, differential pairs and, 492–498
 - striplines, 239
- current distribution, skin depth and, 186–197
- current-voltage behavior, transmission lines, 221

D

- dB (decibel), attenuation and, 367–372
- DC path, dielectric material separation, 124–125
- decoupling capacitance
 - ground planes, 130–133
 - impedance and, return path, 250
 - loop inductance, decreasing, 178–179
 - power planes, 130–133
- delta I noise, inductance and, 157
- design, methodology, 21–22
 - new products, 22–23
- device drivers, models, 27–28
- DFT (Discrete Fourier Transform), 49, 50
 - repetitive signals, 51–53
- dI/dt, differential signaling and, 471
- dielectric constants, 129–130
 - bulk dielectric constants, 144
 - complex, 381
 - cross talk and, 459–460
 - definition, 381
 - dipoles and, 130
 - dissipation and, 350
 - effective dielectric constants, 142–145
 - FEXT and, 439–440
 - frequencies and, 130
 - imaginary part, 381
 - loss and, 342–347
 - real part, definition, 381
 - relative, 129
- dielectric loss, 337
- dielectrics, Maxwell's Equations and, 24
- differential impedance
 - calculating, 488–491
 - coupling, impact, 482–488
 - modes of the pair, 501–502
 - no coupling, 478–482
 - odd-mode impedance, 503–504
- differential mode, 502
- differential pairs
 - cross sections, 476
 - cross talk in, 535–537
 - definition, 471
 - even modes, 498–502
 - ideal differential pairs, 515–516
 - modes of the pair, 499
 - velocity, 509–514
 - odd modes, 498–502
 - return-current distribution, 492–498
 - transmission lines, 476
 - unshielded, 495–496
 - voltage, 498–502
- differential signaling
 - converting to common signals, 525–530
 - definition, 471
 - dI/dt and, 471
 - even mode voltage components, 507–509
 - LVDS, 472–475
 - odd mode voltage components, 507–509
 - propagating, 472
 - SCSI and, 472
 - terminating, 518–525
- DIP (dual in-line package), nonuniform transmission line, 208–209
- dipoles, dielectric constants and, 130
- discontinuities, 6
 - inductive, reflections and, 323–327
 - unintentional, reflections, 295–297
- displacement current, capacitors and, 125
- dissipation
 - dissipation factor, definition, 380
 - FR4, 379
 - loss and, 347–350
 - tan(), 350
- domains
 - frequency, 41
 - time, 41
- drivers
 - impedance, return path, 241
 - transmission lines, 233–236
 - line drivers, 235–236
- DUT (device under test)
 - impedance analyzer, 35
 - reflections, 293–294
 - VNA, 35

E

eddy currents, 200–202
 return path and, 240
 edge-coupled microstrips, coupling, 494
 effective dielectric constants, 142–145
 effective inductance, 152
 ground bounce and, 163–169
 electric fields
 Maxwell's Equations and, 24
 strength, measuring, 531–532
 electrical performance, physical design and, 110–111
 electromagnetic interference, noise source and, 4
 electronic products' trends, 16–21
 electrons, copper, speed, 210–211
 EM simulators, 23
 effects, 25
 embedded microstrips, dielectric constants, 145
 EMI (electromagnetic interference), 3, 13–15
 antennas and, 14
 bandwidth and, 65
 common signals and, 530–535
 noise source, 14
 PCS and, 13
 radiative loss and, 337
 radiator pathways and, 14
 sources, 14
 emissions, twisted pair cable current, 533–534
 equalization, interconnects, 398–399
 equations
 analytical approximations, 31
 approximations, 128
 equivalent circuit models, 97–99
 first-order models, 99
 equivalent inductance, 185–187
 even modes
 calculating
 from capacitance-matrix element, 542–545
 from inductance-matrix element, 542–545
 differential pairs, 498–502

 even-mode impedance, 504–507
 impedance, measuring, 516–518
 eye diagrams, transmission lines, 396–398

F

FEXT (far-end cross talk), 407, 436–443
 decreasing, 443–445
 modes of the pair velocity, 509–514
 FFT (Fast Fourier Transform), 49, 50
 FI (Fourier Integral), 49, 50
 field lines
 capacitance and, 126
 external, 189
 inductance, voltage and, 154–157
 internal, 189
 loops
 mutual inductance and, 152–153
 self-inductance and, 152–153
 magnetic-field line loops, Webers, inductance and, 150–152
 field solvers. *See* 2D field solvers
 fields, loop inductance of planes, 183–184
 first order models, transmission lines, 252–257
 flux lines, inductance and, 147
 formulas, analytical approximations, 31
 .FOUR command, 51
 Fourier Transforms
 DFT (Discrete Fourier Transform), 49
 FFT (Fast Fourier Transform), 49
 FI (Fourier Integral), 49
 FR4
 attenuation, 372–373
 dissipation factor, 379
 frequencies
 current distribution, planes, 241
 dielectric constants and, 130
 losses, 334
 lossy lines, measure properties, 381–386
 self-resonant, 177
 sine waves, 47
 variations, characteristic impedance, 273–275
 VNA, 35
 frequency domains, 41
 impedance and, 46, 92–97
 sine waves, 44–46, 55
 SNR and, 47
 VNA and, 47
 fully embedded microstrips, 145

G

gaps in return path, crossing, 537–540
 gate switching
 timing and, 3
 transmission line drivers, 234
 Gaussian edge, lossy lines in time domain, 392–393
 geometry
 2D field solvers and, 139
 characteristic impedance calculation, 261
 conductors, inductance and, 151
 cross-sectional, characteristic impedance and, 257–258
 partial self-inductance, 159
 reflections and, 280
 resistance and, 110
 parameter values, 113
 sphere capacitance, 126
 transmission lines, 208–210
 ground, transmission lines, 206–207
 ground bounce, 3
 cross talk and, 464–465
 effective inductance and, 163–169
 net inductance and, 163–169
 return path and, 245
 total inductance and, 163–169
 ground planes, decoupling capacitance, 130–133
 guard traces, 452–459

H

high frequency regime, 3
 high-permeability materials, 198–200
 high-speed regime, 3

I

I-V behavior, transmission lines, 221
 IBIS (input/output buffer interface spec), modeling and, 27
 ideal circuit elements
 capacitors, time domain and, 87–90
 inductors, time domain and, 90–92
 interconnects, electrical description, 109
 real and, 84–86
 resistors, time domain and, 86–87
 transmission lines, 205
 ideal coupled-transmission-line model, 515–516
 ideal square waves, 53–55
 image currents, 200–201

imaginary part, dielectric constants, 381

impedance

 adjacent planes, 242–243
 BGAs, 8
 branches and, 6
 cables, 229
 characteristic, 223–225
 approximations and, 257–261
 famous, 225–228
 frequency variations, 273–275
 matrix, 546–548
 return path width and, 263–264
 connectors and, 6
 constant traces and, 7
 controlled, 223–225
 controlled-impedance transmission lines, 208
 copper trace and, 111
 CSPs, 8
 current and, 79
 differential impedance
 coupling and, 478–482
 modes of the pair, 501–502
 odd-mode impedance, 503–504
 discontinuities and, 6
 drivers, return path, 241
 equivalent circuit models, 97–99
 evaluations, microstrips, 216
 even-mode impedance, 504–507
 even modes, measuring, 516–518
 frequency domain and, 46, 92–97, 111
 ideal capacitors in time domain, 87–90
 ideal inductors in time domain, 90–92
 ideal resistors in time domain, 86–87
 instantaneous
 return path and, 246
 transmission lines, 220–223
 interconnects, 229
 length and, 233
 layers, changing, 6
 line-width, changes, 6
 nets, end, 6
 odd modes, measuring, 516–518

- PDS and, 12
 - physical design and performance, 81
 - planes, 251
 - reflections and, 278–280
 - controlled interconnects, 280
 - source impedance, 286–288
 - return loop, current distribution and, 240
 - return path and, decoupling capacitors and, 250
 - return-path plane, gaps in, 6
 - signal integrity and, 80–82
 - stubs and, 6
 - tees and, 6
 - time domain and, 46, 111
 - transmission lines, 205, 228–233
 - instantaneous, 220–223
 - lossy, 363–365
 - time and, 231
 - two-terminal devices, 82–83
 - voltage ratio to current, 35, 79
- impedance analyzer, 35
- impedance miss matches, 336
- incident electromagnetic waves, Maxwell's Equations and, 24
- incident voltage, scattering parameter, 35
- induced voltage, 156
- inductance
 - conductors, geometry, 151
 - coupling origin, cross talk and, 403–405
 - currents, magnetic-field line loops, 147–150
 - definition, 147–148
 - delta I noise, 157
 - effective, 152
 - equivalent, 185–187
 - field line loops
 - voltage and, 154–157
 - Webers, 150–152
 - flux lines and, 147
 - inductively coupled currents, 430–433
 - loop, 151
 - loop mutual inductance, 185
 - PDS and, 174–179
 - matrix element, even mode calculation, 542–545
 - mutual, 151, 152–154
 - loop mutual inductance, 185
 - loop self inductance and, 169–174
 - SSO noise, 10
 - net, 152
 - partial, 151, 157–163
 - self-inductance, 151, 152–154
 - mutual inductance and, 169–174
 - spreading, 182
 - switching noise and, 157
 - total, 152
 - Webers, 150–152
- inductive coupling, cross talk and, 10
- inductive discontinuities, reflections and, 323–327
- inductive matrix, cross talk and, 419–421
- inductors
 - ideal, time domain and, 90–92
 - interconnects and, 109
- input gate capacitances
 - discontinuities and, 295
 - reflections and, 307
- insertion loss, interconnects, 73
- instantaneous impedance
 - return path and, 246
 - signal propagation and, 246
 - transmission lines, 220–223
- interconnects
 - bandwidth, 71–76
 - lossy lines and, 386–392
 - Cable TV, 226
 - cross talk and, 8
 - electrical description, 109
 - equalization, 398–399
 - impedance, 229
 - insertion loss, 73
 - length
 - capacitance, 134–139
 - impedance and, 233
 - Maxwell's Equations and, 109–110
 - models, 27–28
 - noise and, 3
 - pre-emphasis, 398–399

- interconnects (*cont.*)
 - resistance, 111
 - RG58, 225
 - RG59, 226
 - RG174, 226
 - signals and, transparency, 2
- ISI (intersymbol interference), 333
 - rise time degradation, 334–335
- ITRS (International Technology Roadmap for Semiconductors), 17
- L**
- LaPlace's Equation, 2D field solvers, 139
- layers
 - impedance and, 6
 - metallization, sheet resistance and, 118–119
- LC-lumped circuit sections
 - bandwidth of LC models, 269
 - circuit models and, 267
- leading edge, spatial extent, 215–216
- leakage current, loss and, 343
- light, Maxwell's Equations and, 212
- line drivers, 235–236
- line ends, discontinuities and, 295
- line-width, impedance and, 6
- loaded lines, reflections, 320–323
- loop inductance, 151
 - decoupling capacitors, decreasing, 178–179
 - discontinuities, 323
 - mutual inductance, 185
 - partial inductance and, 157
 - PDS (Power Distribution System) and, 174–179
 - per square of planes, 179–180
 - planes, 181–183
 - field of clearance holes, 183–184
 - series loop inductance, discontinuities, 324
 - switching noise, cross talk and, 464–465
 - via contacts, 181–183
- loops
 - current and, 236
 - transmission lines, 236–237
 - self inductance, 169–174
- loss
 - conductor loss, 337
 - coupling to adjacent traces, 336
 - definition, 380
 - dielectric loss, 337
 - dissipation factor, 347–350
 - impedance miss matches, 336
 - leakage current and, 343
 - radiative, 336
 - sources
 - conductor resistance and skin depth, 338–342
 - dielectric, 342–347
 - transmission lines, 333, 336–338
- loss angle, definition, 380
- loss-less model, 336–338
- lossy lines, 333–334
 - attenuation, 372–381
 - frequency domain, measured properties, 381–386
 - Gaussian edge, time domain and, 392–393
 - impedance, 363–365
 - interconnects, bandwidth, 386–392
 - modeling, 355–363
 - problems with, 334–336
 - signal velocity, 365–367
 - time-domain behavior, 392–396
- LVDS (low voltage differential signals), 472–475
- M**
- magnetic fields
 - circular line loops around currents, inductance and, 147–150
 - Maxwell's Equations and, 24
- material properties, resistance and, 110
 - bulk resistivity, 114–115
 - parameter values, 113
- Maxwell capacitance matrix, cross talk and, 413–419
- Maxwell's Equations, 24
 - interconnects and, 109–110
 - light and, 212–213
- measurement
 - bandwidth, 68–70
 - even mode impedance, 516–518
 - field-line loops, 149
 - frequency domain lossy line properties, 381–386
 - impedance analyzer, 35
 - odd mode impedance, 516–518
 - roles of, 37–39

TDR (time-domain reflectometer), 35
 reflections, 292–295
 types, 34–37
 VNA (vector-network analyzer), 35
 voltage launched into transmission line, 234–235

metallization, layers, sheet resistance and, 118–119

microstrips, 208
 current, 239
 embedded, dielectric constants, 145
 impedance evaluation, 216

modeling
 bandwidth, 70–71
 circuit models
 creating from calculation, 29–34
 lumped, 104
 definition, 110
 Einstein and, 103
 IBIS, 27
 loss-less, 336–338
 lossy lines, 355–363
 measurement and, 37
 output drivers, 27
 physical design and, 110
 transistors, 27
 transmission lines, 252–257
 control-impedance lines, 252
 unintentional discontinuities, 296

modes of the pair (differential pairs), 499
 velocity, FEXT, 509–514

mutual inductance, 151, 152–154
 field line loops and, 152–153
 loop mutual inductance, 185
 loop self-inductance and, 169–174
 partial mutual inductance, 158
 symmetry and, 154

N

n-section lumped circuit models, 263–273

napiers, attenuation, 368

near-end cross talk, 3

neck downs, discontinuities and, 295

net inductance, 152
 ground bounce and, 163–169

nets
 active nets, 401
 aggressor nets, 401
 cross talk and, 8
 end, impedance and, 6
 single, signal quality and, 5–8

NEXT (near-end cross talk), 407, 433–436

noise, 3
 attenuation, 3
 capacitive load, 3
 cross talk, guard traces, 452–459
 ground bounce, 3
 interconnects and, 3
 near-end cross talk, 3
 nonmonotonicity, 3
 power bounce, 3
 rail collapse, 10–13
 reflections, 3, 297
 ringing, 3
 signal quality on single net, 5–8
 sources, 4
 EMI and, 14
 SSO noise, 10
 superposition and, 402–403
 switching noise, 3

nonmonotonicity, 3

numerical simulations, 30
 verification, 33–34

O

odd modes
 calculating
 from capacitance-matrix element, 542–545
 from inductance-matrix element, 542–545

differential pairs, 498–502

impedance, measuring, 516–518

odd-mode impedance, 503–504

voltage components
 common signals and, 507–509
 differential signaling and, 507–509

Ohms, characteristic impedance and, 223
 resistance, 112

P

package leads, discontinuities and, 295

parallel plate approximation, 127–128

- partial inductance, 151, 157–163
 - geometry, 159
 - partial mutual inductance, 158
 - partial self-inductance, 158
 - passive devices, electrical description, 109
 - PCB (printed circuit board), 1–2
 - PCS (personal communications services), EMI and, 13
 - PDS (power-distribution system), 11–12
 - impedance and, 12
 - loop inductance and, 174–179
 - physical design
 - electrical performance and, 110–111
 - modeling and, 110
 - performance and, impedance and, 81
 - pi topology, termination, 521–522
 - planar interconnects, return path and, 240
 - planes
 - adjacent, impedance and, 242–243
 - impedance between, 251
 - loop inductance, 181–183
 - field of clearance holes, 183–184
 - resonance, 252
 - plates, parallel plate approximation, 127–128
 - point-to-point topology, termination strategies, 300–302
 - power bounce, 3
 - power planes, decoupling capacitance, 130–133
 - PQFP (plastic quad flat pack), 25
 - resistance and, 113
 - pre-emphasis, interconnects, 398–399
- Q–R**
- QFP (quad flat pack), nonuniform transmission line, 208–209
 - radiative loss, 336
 - EMI and, 337
 - radiators, pathways, EMI and, 14
 - rail collapse, 10–13
 - noise source and, 4
 - real circuit elements, ideal and, 84–86
 - real part, dielectric constants, 381
 - reference plane, return paths, switching plans, 240–252
 - reflected transient amplitude, TDR, 36
 - reflected voltage, scattering parameter, 35
 - reflections, 3
 - bounce diagrams, 288–289
 - capacitive delay adders, 313–315
 - capacitive end terminations, 307–309
 - capacitive loads, traces, 310–313
 - compensation, 328–330
 - corners, 315–320
 - differential impedance and, 480–482
 - geometry and, 280
 - impedance and, 278–280
 - controlled interconnects, 280
 - source impedance, 286–288
 - inductive discontinuities, 323–327
 - loaded lines, 320–323
 - noise, 297
 - reasons for, 280–283
 - resistive loads and, 283–286
 - routing topology, 280
 - SPICE and, 287
 - TDR (time domain reflectometer) measurements, 292–295
 - termination, point-to-point topology, 300–302
 - time domain and, 284
 - transmission lines and, 277–278
 - discontinuities, unintentional, 295–297
 - short series transmission lines, 302–305
 - short-stub transmission lines, 305–307
 - terminations, 280
 - vias, 315–320
 - waveforms, simulating, 289–292
 - relative dielectric constants, 129
 - repetitive signals, 51–53
 - resistance
 - bulk resistivity, 114–115
 - conductors, loss and, 338–342
 - geometry and, 110
 - increases, length and, 113
 - interconnects, 111
 - electrical description, 109

- material properties and, 110
 - Ohms, 112
 - reflections and, 283–286
 - resistance per length, 115–117
 - sheet resistance, 115
 - bulk resistivity and, 117
 - metallization of layers, 118–119
 - traces and, 117
 - volume resistivity, 115
- resistors
- ideal, time domain and, 86–87
 - interconnects and, 109
 - parameter values
 - geometry and, 113
 - material properties and, 113
- resonance in planes, 252
- return-current distribution, differential pairs and, 492–498
- return paths, 236–240
- current
 - distribution, 238–239
 - loops and, 236
 - microstrips, 239
 - striplines, 239
 - discontinuities and, 295
 - eddy currents, 240
 - gaps, crossing, 537–540
 - ground bounce, 245
 - impedance
 - decoupling capacitors and, 250
 - drivers, 241
 - transmission lines and, 8
 - loops, current and, 236
 - plane, impedance and, 6
 - reference plane, switching, 240–252
 - transmission lines, 206–207
 - current loops, 236–237
 - width, characteristic impedance and, 263–264
- RG58 interconnect, 225–226
- RG59 interconnect, 226
- RG174 interconnect, 226
- ringing, 3
- rise time
- bandwidth effect, 56–61
 - degradation
 - ISI and, 334–335
 - lossy lines and, 334–335
 - time domain and, 42
- RLC model
- electrical view and, 110–111
 - physical view and, 110–111
- RT (rise time), short series transmission lines, 302
- rules of thumb, 30–31
- approximation and, 30
- S**
- saturation length, cross talk and, 421–426
- scattering parameter
- incident voltage, 35
 - reflected voltage, 35
- SCSI (small computer scalable interface), differential signaling and, 472
- self-inductance, 151, 152–154
- field line loops and, 152–153
 - loop self-inductance, 169–174
 - partial self-inductance, 158
- self-resonant frequency, loop inductance and PDS, 177
- series loop inductance, discontinuities, 324
- sheet resistance, 115
- bulk resistivity and, 118
 - layers, metallization and, 118–119
 - traces and, 117
- short series transmission lines, reflections, 302–305
- short-stub transmission lines, reflections, 305–307
- SIA (Semiconductor Industry Association), 17
- Siemens, conductivity and, 114
- signal integrity
- defined, 2–5
 - effects, 4
 - generalizations, 15–16
 - history of, 2–5
 - impedance and, 80–82

- signal quality, noise source and, 4
 - single net, 5–8
 - signal velocity, lossy lines and, 365–367
 - signals
 - bandwidth, 64–66
 - interconnects and, transparency, 2
 - leading edge, spatial edge, 215–216
 - propagation
 - instantaneous impedance and, 246
 - voltage and, 212
 - repetitive, 51–53
 - speed, transmission lines, 211–215
 - transmission lines, 207–208
 - voltage
 - kink of field, 212
 - propagation and, 212
 - significance, 61–64
 - simulation
 - cross talk simulation, 445–451
 - reflected waveforms, 289–292
 - tools
 - behavioral simulators, 23–24
 - circuit simulators, 23
 - EM simulators, 23
 - SPICE, 26
 - sine waves
 - amplitude, 47
 - frequency, 47
 - frequency domains, 44–46, 55
 - ideal square-waves, 53–55
 - phase, 47
 - ratio, 93
 - time domains, 48–49, 55
 - skin depth
 - current distribution and, 186–197
 - loss and, 338–342
 - SNR (signal-to-noise ratio), frequency domain and, 47
 - source impedance, reflections and, 286–288
 - source-series termination, cross talk simulation, 446–447
 - sources of loss
 - conductor resistance and skin depth, 338–342
 - dielectric, 342–347
 - spatial extent of leading edge, 215–216
 - speed
 - electrons in copper, 210–211
 - light, 212–213
 - signals, transmission lines, 211–215
 - spheres, capacitance, 126–127
 - SPICE (simulation program with integrated circuit emphasis), 26
 - circuit theory and, 99–103
 - .FOUR command, 51
 - n-section lumped circuit models, 267
 - reflections and, 287
 - short-stub transmission lines, 306
 - SPICE capacitance matrix, cross talk and, 409–413
 - spreading inductance, 182
 - square of planes, loop inductance, 179–180
 - square waves, ideal square waves, 53–55
 - SSN (simultaneous switching noise), cross talk and, 9
 - SSO noise, 10
 - step edge, TDR, 292–293
 - stripline, 208, 224
 - 2D field solvers results and, 262
 - current, 239
 - effective dielectric constants and, 142
 - stubs
 - discontinuities and, 295
 - impedance and, 6
 - superposition, cross talk and, 402–403
 - switching noise, 3
 - cross talk and, 464–467
 - inductance and, 157
 - symmetry, mutual inductance and, 154
- T**
- tan (), definition, 381
 - TD (time delay), short series transmission lines, 302
 - TDR (time-domain reflectometer), 35
 - even-mode impedance, 516–518

- measurement, bandwidth and, 68
- odd-mode impedance, 516–518
- reflected transient amplitude, 36
- reflections and, 292–295
- step edge, 292–293
- tee topology, termination, 523–525
- tees, impedance and, 6
- termination
 - capacitive end terminations, reflections and, 307–309
 - common signals, 518–525
 - differential signaling, 518–525
 - pi topology, 523–525
 - point-to-point topology, 300–302
 - source-series, cross talk simulation and, 446–447
 - tee topology, 523–525
 - transmission lines, reflections and, 297–300
- test pads, discontinuities and, 295
- tightly coupling, advantages/disadvantages, 540–542
- time delay
 - impedance, transmission lines, 231
 - transmission lines, 205
- time-domain
 - lossy lines, 392–396
 - waveforms, 42–43
- time domains, 41
 - clock period and, 42
 - ideal capacitors, impedance and, 87–90
 - ideal inductors, impedance and, 90–92
 - ideal resistors and, impedance and, 86–87
 - impedance and, 46
 - rise time and, 42
 - reflections and, 284
 - sine waves, 48–49, 55
- timing, 3
 - cross talk and, 460–464
 - gate switching and, 3
- total inductance, 152
 - ground bounce and, 163–169
- traces
 - capacitive loads, reflections, 310–313
 - guard traces, 452–459
 - impedance and, 7
 - sheet resistance and, 117
- transistors, modeling, 27
- transmission lines
 - coax, 224
 - conductors and, 205
 - controlled-impedance, 208
 - cross talk and, 8
 - coupled, ideal coupled-transmission-line model, 515–516
 - cross section, 208
 - current loops, 236–237
 - differential pairs (*See* differential pairs)
 - drivers, 233–236
 - line drivers, 235–236
 - electrons in copper, speed, 210–211
 - eye diagrams, 396–398
 - geometry and, 208–210
 - ground, 206–207
 - I-V behavior, 221
 - ideal circuit elements and, 205
 - impedance, 205, 228–233
 - instantaneous, 220–223
 - time and, 231
 - interconnects, 109
 - cross talk and, 8
 - loaded, reflections and, 320–323
 - losses, 333, 336–338
 - lossy
 - impedance, 363–365
 - modeling, 355–363
 - signal velocity and, 365–367
 - models, first order model, 252–257
 - nonuniform
 - DIPs, 208–209
 - QFPs, 208–209
 - reflections and, 277–278
 - discontinuities, unintentional, 295–297
 - loaded lines, 320–323
 - short series transmission lines, 302–305
 - short-stub transmission lines, 305–307

- transmission lines (*cont.*)
 - termination, 297–300
 - terminations, 280
 - short series transmission lines, reflections and, 305–307
 - short-stub, reflections and, 305–307
 - signals, 207–208
 - speed, 211–215
 - termination, reflections and, 297–300
 - time delay, 205
 - uniform, 208–210
 - cross talk and, 421–426
 - voltage, launched, measuring, 234–235
 - trends in electronic products, 16–21
 - twin leads, 208
 - twisted pair wires, 224
 - current emissions, reducing, 533–534
- U–V**
- uniform transmission lines, 208–210
 - cross talk and, 421–426
 - unshielded differential pairs, 495–496
- velocity, modes of the pair, FEXT, 509–514
- verification, numerical simulations, 33–34
- via contacts
 - loop inductance, 181–183
 - reflections and, 315–320- VNA (vector-network analyzer), 35
 - frequencies and, 35
 - frequency domain and, 47
- voltage
 - components
 - even mode, 507–509
 - odd mode, 507–509
 - current, amplitude ratio, 93
 - differential pairs, 498–502
 - field-line loops, inductance and, 154–157
 - ground bounce, 163–169
 - impedance and, 79
 - induced, 156
 - ratio to current = impedance, 35
 - signal propagation and, 212
 - signals, kink of field, 212
 - transmission lines, measuring launched, 234–235
- volume resistivity, 115

W–Z

waveforms
 - reflections, simulating, 289–292
 - time-domain, 42–43
 - Webers, inductance and, 150–152
 - wire, AWG (American Wire Gauge), 116