
INDEX

Symbols

4-ary biorthogonal keying. *See*
4-BOK
4-BOK (4-ary biorthogonal
keying), 578
802.15.4a devices, case studies,
537–538
 Δ -K model, small-scale channel
modeling, 110–111

A

A-PAM modulation, 521
CD receivers
optimal matched filter
performance, 270–271
performance based on pilots,
273–275
simple matched filter
performance, 271–272
RAKE receivers, 285–288
nonresolvable paths, 286–288
resolvable paths, 285–286
accuracy, direct phase measurement
with VNA, 41–42
ACK (acknowledgment) packets,
476, 487, 549–550
acknowledgment packets. *See* ACK
packets
acquisition
DS-UWB PHY standard,
584–586
MB-OFDM PHY standard,
564–568

Ad Hoc On-Demand Distance Vector
Routing. *See* AODV
ADCs (Analog to Digital
Converters), 14
Additive White Gaussian Noise. *See*
AWGN
addressing schemes, 471
ADSL (Asymmetric Digital
Subscriber Line), 6
Aether Wire, 4
localizers, 229, 532–536
aggregate UWB interference
modeling, 393–403
amplitudes, 400
asymptomatic pdf of aggregate
noise, 398–400
Bernoulli model, 400–402
mean received power, 395–397
MGF received power, 397
Poisson model, 400–402
received power, 393–395
simulation samples, 402–403
Aircraft Wireless
Intercommunications
System. *See* AWICS
algorithms, hierarchical topologies
Bluenet, 492
BlueStars, 492–493
Bluetree, 492
scatternet formation, 490
two-stage distributed
clustering, 490

- allocated spectral mask, FCC
 - restrictions on UWB operations, 8–12
- Aloha (contention-based MAC scheme), 478–479
- American Electronic Laboratories model APN-101B, 185
- amplitudes
 - coexistence of UWB and NB systems, 400
 - small-scale channel modeling, 124–128
- analog phase locked loop-type UWB system. *See* APLL-type UWB system
- Analog to Digital Converters. *See* ADCs
- Anderson, Christopher R., 615
- angles-of-arrival. *See* AOAs
- Annamalai, Annamalai, 615
- Antenna Research Associates model DRG-118/A, 185
- antennas, 159–210
 - aperture, 159
 - biconical antenna model, 191
 - conjugation of \mathbf{h} , 159
 - current distribution (\mathbf{J}), 159
 - directional, 87
 - fundamental limits, 169
 - gain (G), 159
 - impact on large-scale channel modeling, 85–88
 - link budgets, 168–169
 - link model using S -parameters, 165–168
 - measurements
 - frequency and time relationships, 185–186
 - pattern concept in time, 186–187
 - responses, 169–170
 - transient responses of scatterers, 200–209
 - UWB performance, 170–185
 - monopole antenna model, 191–192
 - planar TEM horn antennas, 202–209
 - pole modeling, 189–191
 - properties, 160–169
 - directivity, 162–165
 - effective area, 164
 - effective length, 161–162
 - gain (G), 162–165
 - maximum effective area, 164
 - polarization, 159
 - polarization factor, 164
 - received power, 162–165
 - reciprocity, 161–162
 - reactance, 163
 - receiving, electromagnetic
 - simulation of UWB propagation, 58–61
 - resistance, 163
 - role in channel propagation
 - measurements, 57
 - simulation of effects, 451–459
 - model development, 455–458
 - simulation development, 458–459
 - validation, 459
 - time domain modeling, 187–200
 - frequency and time relationships, 185–186
 - pattern concept, 186–187
 - responses, 169–170
 - transient responses of scatterers, 200–209
 - UWB performance, 170–185
 - transmitting, electromagnetic
 - simulation of UWB propagation, 58–61
 - unique features of UWB signals, 13
 - unit vector, 159
 - Vivaldi antenna model, 192–200
 - wave number, 159
- antipodal PAM (biphase pulse polarity modulation), 232

- AOAs (angles-of-arrival), 104, 130, 140–144, 541
 - AODV (Ad Hoc On-Demand Distance Vector Routing), 495
 - aperture, antennas, 159
 - APLL-type UWB system (analog phase locked loop-type UWB system), 279–281
 - application layer (network protocols), 472–473
 - applications, 511–520
 - channel sounding applications, 520
 - communication applications, 513–515
 - high resolution radar applications, 511–513
 - location aware communications applications, 515–520
 - specialized applications for UWB, 509–511
 - APS (Asynchronous Power Save) mode, 550
 - architecture. *See also* design
 - DS-UWB PHY standard, 586–588
 - MB-OFDM PHY standard, 568–571
 - ARIB (Association of Radio Industries and Businesses), 603
 - ARQ (automatic repeat request), data link layer design (UWB networking), 486–487
 - Association of Radio Industries and Businesses. *See* ARIB
 - Astanin, 3
 - Asymmetric Digital Subscriber Line. *See* ADSL
 - asymptomatic pdf of aggregate noise, coexistence of UWB and NB systems, 398–400
 - Asynchronous Power Save. *See* APS mode
 - Attiya, Dr. Ahmed M., 615–616
 - August, Nathaniel J., 616
 - autocorrelation transmitted reference receivers. *See* TR-UWB receivers
 - automatic repeat request. *See* ARQ
 - avalanche pulse generators, 214–217
 - avalanche transistors, 261–263
 - average power, link budgets, 95
 - AWGN (Additive White Gaussian Noise), 19
 - AWICS (Aircraft Wireless Intercommunications System), 526–527
- B**
- bandwidth limits, FCC regulations, 593–594
 - baseband radio, 3
 - Bellman-Ford algorithm, 494
 - BER (Bit Error Rate), 434
 - BER analysis, coexistence of UWB and NB systems, 384–390
 - BGP (Border Gateway Protocol), 473
 - biconical antenna model, 191
 - biphase pulse polarity modulation (antipodal PAM), 232
 - bipolar junction transistors. *See* BJT
 - bistable operation, tunnel diode pulsers, 224
 - Bit Error Rate. *See* BER
 - BJT (bipolar junction transistors), 214–215
 - block diagrams, LED receivers, 259
 - Bluenet algorithm, 492
 - blueroot nodes, 492
 - BlueStars algorithm, 492–493
 - Bluetooth scatternet, hierarchical topologies, 489–490
 - Bluetooth Topology Construction Protocol. *See* BTCP
 - Bluetree algorithm, 492

- Border Gateway Protocol. *See* BGP
- broadcast transfer of
 - information, 471
- BTCP (Bluetooth Topology Construction Protocol), 491–492
- Buehrer, Dr. R. Michael, 616–617
- building architecture and materials, impact on UWB signal propagation, 57–58

- C**
- call for applications. *See* CFA
- canonical communication
 - system, 440
- CAP (contention access period), 537
- carrier interferometry receivers. *See* CI receivers
- Carrier Interferometry. *See* CI-UWB signals
- Carrier Sense Multiple Access with Collision Avoidance. *See* CSMA/CA
- Carrier Sense Multiple Access with Collision Detection. *See* CSMA/CD
- Carrier Sense Multiple Access. *See* CSMA protocols
- case studies, 520–540
 - 802.15.3/3a devices, 536
 - 802.15.4a devices, 537–538
 - Aether Wire and Location, Inc., localizers, 532–536
 - MSSI products, 524–532
 - AWICS, 526–527
 - Draco, 525
 - HFUWB, 526
 - MAVCAS, 532
 - Orion system, 526
 - PAL system, 527–532
 - RAKE receivers, 352–368
 - TDC—PulsON chipset, 521–524
 - XSI/Motorola Trinity Chipset, 520–521
- categories of UWB operation, First Report and Order (FCC), 8
- cavity-backed Archimedean spiral. *See* CBAS
- CBAS (cavity-backed Archimedean spiral), 173, 176–179
- CCA (clear channel assessment), 588
- CD receivers (correlation detectors), 256, 268–281
 - optimal matched filter
 - performance, 268–270
 - A-PAM modulation, 270–271
 - PPM modulation, 271
 - performance based on pilots
 - A-PAM modulation, 273–275
 - PPM modulation, 275–281
 - simple matched filter
 - performance
 - A-PAM modulation, 271–272
 - PPM modulation, 272–273
- CDMA (Code Division Multiple Access), 477, 483
- CEPT (European Conference of Postal and Telecommunications Administrations), 603
- CFA (call for applications), 551
- CFAR (constant false alarm rate) receivers, 259, 265
- channel impulse response. *See* CIR
- channel partition MAC schemes (data link layer design), 483
- channel sounding applications, 520
- channels
 - double-directional, 87
 - effects, 73
 - impulse response (small-scale channel modeling), 107–109
 - measurement and simulation, 29–68
 - electromagnetic simulation in indoor environments, 58–66
 - frequency domain
 - measurement techniques, 36–44

- results of measurements, 44–58
 - time domain measurement techniques, 30–36
 - modeling, 73–151
 - IEEE 802.15.3a PHY standard, 554–556
 - impact of frequency distortion, 144–151
 - large-scale channel modeling, 74–103
 - small-scale channel modeling, 103–130
 - spatial behavior, 130–144
 - unique features of UWB, 13, 74
 - simulation, 460–466
 - model development, 460–461
 - simulation development, 461
 - validation, 461–466
- child piconets, 547–548
- chipsets
 - TDC—PulsON chipset, 521–524
 - XSI/Motorola Trinity chipset, 520–521
- CI-UWB signals (Carrier Interferometry), 238–239
 - receivers, 334–337
- CIR (channel impulse response), 104
- CLEAN algorithm, 105–106, 145–151
- clear channel assessment. *See* CCA
- clear to send protocols. *See* CTS protocols
- cluster arrival rate, 119
- cluster decay time constant, 118
- cluster heads (hierarchical topologies), 489–490
- CMOS pulse generators, 230–232
- Code Division Multiple Access. *See* CDMA
- code sets, DS-UWB PHY standard, 583
- coexistence of UWB and NB systems, 379–416
 - aggregate UWB interference modeling
 - amplitudes, 398–400
 - Bernoulli model, 400–402
 - mean received power, 395–397
 - MGF received power, 397
 - pdf aggregate noise, 398–400
 - Poisson model, 400–402
 - received power, 393–395
 - simulation samples, 402–403
 - interference analysis, 403–416
 - waveform analysis, 381–393
 - BER analysis, 384–390
 - NB receive filter, 384
 - simulation results, 392–393
 - time-hopped case, 390–392
 - UWB pulse model, 382–384
- communication applications, 513–515
- communication systems, EIRP limits, 601–602
- component simulation, 445–466
 - antenna effects, 451–459
 - pulse generation and modulation, 445–448
 - signal amplification, 448–451
 - UWB channels, 460–466
- conjugation of \mathbf{h} (antennas), 159
- constant false alarm rate. *See* CFAR receivers
- contention access period. *See* CAP
- contention-based MAC schemes (data link layer, UWB networking), 478–483
 - Aloha, 478–479
 - CSMA protocols, 481–482
 - CSMA/CA, 482–483
 - Slotted Aloha, 479–481
- continuous wave signals. *See* CW signals
- Continuously Variable Slope Detect. *See* CVSD
- controversial issues (UWB), 8–12

- correlation
 - detectors. *See* CD receivers
 - spatial correlation, 135–140
 - techniques, Sperry Rand Corporation
 - developments, 3
- Cramer-Rao Lower Bound. *See* CRLB
- CRLB (Cramer-Rao Lower Bound), 510, 541
- CSMA (Carrier Sense Multiple Access) protocols, 481–482
- CSMA/CA (Carrier Sense Multiple Access with Collision Avoidance), 477, 482–483, 537
- CSMA/CD (Carrier Sense Multiple Access with Collision Detection), 477, 482
- CTS (clear to send) protocols, 482
- current distribution (**J**), antennas, 159
- CVSD (Continuously Variable Slope Detect), 526
- CW (continuous wave) signals, 213

- D**
- DAB (Digital Audio Broadcast), 6
- DACs (digital to analog converters), 234
- DAG (directed acyclic graph), 496
- data communication between DEVs, IEEE 802.15.3/3a standard, 549–550
- data link layer (network protocols), 472–487
 - ARQ (automatic repeat request), 486–487
 - channel partition MAC schemes, 483
 - contention-based medium access control, 478–483
 - FEC (forward error correction), 486–487
 - LLC sublayer, 475
 - MAC sublayer, 475
 - multiple access protocols, 483–486
 - objectives, 475–478
 - fair and efficient resource sharing, 477–478
 - point-to-point flow control, 476–477
 - power conservation, 477
 - reliable data delivery, 476
- Davis, Dr. William A., 617
- defining simulation products, 429
- defragmentation, 549
- Delta-K model. *See* Δ -K model
- demodulator structure, RAKE receivers, 284
- design. *See also* architecture
 - receivers, 13–14, 253–369
 - autocorrelation TR receivers, 319–326
 - CD (correlation detection) receivers, 268–281
 - CI (Carrier Interferometry) receivers, 334–337
 - digital I-UWB
 - implementation, 327–331
 - FH (frequency hopped) receivers, 337–342
 - hybrid RAKE/MUD UWB receivers, 300–310
 - IA (Integration and Averaging), 318–319
 - LED (leading edge detectors) receivers, 258–268
 - MUD (multi-user detectors) receivers, 300
 - OFDM-UWB receivers, 343–344
 - RAKE receivers, 281–299, 352–368
 - SBC (sampling bridge circuit), 310–318
 - spectral encoded UWB communication system, 348–352

- synchronization and timing
 - issues, 326–327
 - system model, 257–258
 - TMD (template match detectors), 310
- time domain requirements, 12
- transmitters, 13–14, 213–247
 - I-UWB signal generators, 213–232
 - I-UWB transmitters, 234–237
 - MC-UWB transmitters, 237–244
 - modulators, 232–234
 - spectral encoded UWB communication system, 245–247
- Destination Sequenced Distance Vector. *See* DSDV protocol
- deterministic modeling, 73
- DEV association (piconets), 549
- DEV disassociation (piconets), 549
- development, UWB simulations, 428–432
- Device Synchronized Power Save. *See* DSPS mode
- dielectric constant versus frequency, 59
- differential circuits, H bridge, 228–230
- Digital Audio Broadcast. *See* DAB
- Digital Terrestrial Television Broadcast. *See* DVB
- digital to analog converters. *See* DACs
- digital UWB receivers, 327–331
- diodes
 - SRDs (Step Recovery Diodes), 217–222
 - tunnel diodes, 222–225
- dipole radiation, resonant monopole, 174–176
- Direct Sampling, digital UWB receivers, 327–331
- direct sequence spread spectrum modulation. *See* DS-UWB signals
- direct sequence ultra wideband. *See* DS-UWB
- direct/quadrature signal
 - decomposition, 425–427
- directed acyclic graph. *See* DAG
- directional antennas, path loss, 87
- directive gain (antennas), 164
- directivity (antennas), 162–165
- discrete event simulation techniques, 435–443
 - entities, 436–438
 - events, 438–439
 - normal operation, 439–440
 - simulation development, 441–442
 - simulation performance considerations, 442–443
 - simulation sample, 440–441
- discrete-tap channel model, impact of frequency distortion
 - CLEAN algorithm, 145–151
 - frequency dependent distortion, 146
 - reflections, 146–151
- Distance Routing Effect Algorithm for Mobility. *See* DREAM
- DoD network model (U.S. Department of Defense network model), 472
- double-directional channel, 87
- Draco, 525
- DREAM (Distance Routing Effect Algorithm for Mobility), 497–498
- DS-based UWB receivers, IEEE 802.15.3/3a proposed standard, 332
- DS-UWB (direct sequence ultra wideband) PHY standard, 573–590
 - acquisition, 584–586
 - architecture, 586–588

- band plan, 579
- code sets, 583
- configurations for proposal, 581
- link margin, 591
- overview, 577–578
- performance, 588–590
- simultaneously operating
 - piconets, 578–584
- DS-UWB signals (direct sequence spread spectrum modulation), 235, 256
- DSDV (Destination Sequenced Distance Vector) protocol, 493–494
- DSP technology, unique features of UWB signals, 14
- DSPS (Device Synchronized Power Save) mode, 551
- DSR (Dynamic Source Routing), 494–495
- DVB (Digital Terrestrial Television Broadcast), 6
- Dynamic Source Routing. *See* DSR

- E**
- EC (eigen canceller), 292
 - hybrid RAKE/MUD UWB receivers, 305–306
 - versus MMSE, 306–310
- ECL (Emitter Coupled Logic), 226–228
- effective area (antennas), 162–164
- Effective Isotropic Radiated Power limits. *See* EIRP limits
- effective length (antennas), 161–162
- effects, channels
 - large-scale channel modeling, 74–103
 - better than free-space propagation, 88–89
 - free-space path loss modeling, 75–78
 - frequency dependent models, 83–84
 - impact of antennas, 85–88
 - link budget calculations, 93–103
 - partition dependent approaches, 84–85
 - path loss modeling for non-free-space environments, 78–83
 - receiver-dependent path loss models, 90–91
 - shadowing, 91–93
 - studies, 85
- small-scale channel modeling, 103–130
 - Δ -K model, 110–111
 - amplitude statistics, 124–128
 - channel impulse response, 107–109
 - effect of model parameters, 114–123
 - modified Poisson model, 112
 - Saleh-Valenzuela model, 109–110
 - split-Poisson model, 112–114
 - STDL (stochastic tapped-delay line) model, 124
 - summary of measurement campaigns, 128–130
- efficiency formula, 163
- EIRP (Effective Isotropic Radiated Power) limits, 75
- FCC regulations, 594–601
 - communication and measurement systems, 601–602
 - imaging systems, 594–596
 - vehicular radar systems, 596–601
- electromagnetic interference. *See* EMI
- electromagnetic simulation, UWB
 - propagation, 58–66
 - comparison of simulation results, 65–66

- organization of electromagnetic simulator, 63–64
- transmitting and receiving antennas, 58–61
- UWB channel simulation, 61–63
- electronic component technology, 3
- EMI (electromagnetic interference), 51
- Emitter Coupled Logic. *See* ECL
- end-to-end protocols, 472
- entities, discrete event simulation techniques, 436–438
- ETSI (European Telecommunications Standardization Institute), 603
- European Conference of Postal and Telecommunications Administrations. *See* CEPT
- European Telecommunications Standardization Institute. *See* ETSI
- events, discrete event simulation techniques, 438–439

- F**
- fading, spatial fading, 133–135
- false alarms, LED receivers, 258
- Fantasma Networks, 4
- FCC (Federal Communications Commission), 1
- First Report and Order, restrictions on UWB operation, 8–12
- Notice of Inquiry, 8
- regulations, 593–602
 - bandwidth limits, 593–594
 - EIRP limits, 594–601
 - peak power limits, 601
 - transmitter power, 475
 - unintentional radiation, 601–602
- UWB rule-making process, 2
- FDMA (Frequency Division Multiple Access), 477, 483
- FDTD (finite difference time domain), 61
- FEC (forward error correction), 430, 476, 486–487
- Federal Communications Commission. *See* FCC
- FFDs (full function devices), 537
- FH (frequency hopped) receivers, 337–342
- FH-UWB system, 239–240
- finite difference time domain. *See* FDTD
- Finite Impulse Response. *See* FIR
- FIR (Finite Impulse Response), 19
- First Report and Order (FCC), restrictions on UWB operation, 8–12
- flat network topologies (multiple hop ad hoc networks), 493–498
 - AODV (Ad Hoc On-Demand Distance Vector Routing), 495
 - DREAM (Distance Routing Effect Algorithm for Mobility), 497–498
 - DSDV (Destination Sequenced Distance Vector) protocol, 493–494
 - DSR (Dynamic Source Routing), 494–495
 - LAR (Location-Aided Routing), 497
 - routing protocols, 493–494
 - TORA (Temporally Ordered Routing Algorithm), 496
 - ZRP (Zone Routing Protocol), 496–497
- flux density, free-space path loss modeling, 76
- formulas
 - efficiency, 163
 - Friis transmission formula, 75–78, 168
- forward error correction. *See* FEC
- fragmentation, 549

frames. *See* PDUs
 free-space path loss modeling, 75–78
 flux density, 76
 Friis transmission formula, 75–78
 LOS (line-of-sight) measurements, 76
 frequency
 dependent models, large-scale channel modeling, 83–84
 distortion, impact on discrete channel modeling, 144–151
 CLEAN algorithm, 145–146
 frequency dependent distortion, 146
 reflections, 146–151
 relationships, antenna measurements and modeling in time domain, 185–186
 versus dielectric constant, 59
 versus insertion loss, 60
 Frequency Division Multiple Access. *See* FDMA
 frequency domain, measuring UWB signal propagation, 36–44
 accuracy of direct phase measurement (VNA), 41–42
 direct measurement of magnitude and phase, 39–41
 measurement results, 51–56
 phase retrieval from magnitude measurement, 42–44
 scalar frequency domain measurement, 36–39
 frequency hopped receivers. *See* FH receivers
 Friis transmission formula, 75–78, 168
 full function devices. *See* FFDs
 fundamental limits of antennas, 169
 future directions (UWB), 15–16
 FWHM (full-width half-maximum), 51

G

gain (G), antennas, 159, 162–165
 gateway nodes (hierarchical topologies), 489–490
 GDP (graphic display plans), 514
 generators, I-UWB signals, 213–232
 avalanche pulse generators, 214–217
 pulse circuits suitable for integrated circuits, 225–232
 SRDs (Step Recovery Diodes), 217–222
 tunnel diode pulsers, 222–225
 geometrical theory of diffraction. *See* GTD
 Global Positioning System. *See* GPS
 Gong, Michelle X., 617
 GPR (Ground Penetrating Radar), 513
 EIRP limits, 595–596
 GPS (Global Positioning System), 8, 520
 graphic display plans. *See* GDP
 Griggs, Stephen, 617–618
 Ground Penetrating Radar. *See* GPR
 GTD (geometrical theory of diffraction), 61
 GTS (guaranteed time slots), 538
 guaranteed time slots. *See* GTS

H

H bridge circuits, 228–230
 Ha, Dr. Dong, 618
 HBT (heterojunction bipolar transistor), 524
 heterojunction bipolar transistor. *See* HBT
 Hewlett Packard Application Note #918, 217
 HFUWB, 526
 hierarchical topologies (multiple hop ad hoc networks), 489–493
 Bluetooth scatternet, 489–490

- BTCP (Bluetooth Topology Construction Protocol), 491–492
- cluster heads, 489–490
- gateway nodes, 489–490
- ordinary nodes, 490
- scatternet formation
 - algorithm, 490
- spanning tree topologies, 492–493
- super-master nodes, 490
- two-stage distributed clustering algorithm, 490
- high resolution radar applications, 511–513
- Hilbert transform, 43
- history, UWB signals, 3–4
- Homeplug (Power Line Networking), 6
- HP (Hewlett-Packard), development of sampling oscilloscope, 3
- hybrid RAKE/MUD UWB receivers, 256, 300–310
 - EC receivers, 305–306
 - MMSE receivers, 300–305
 - MMSE versus EC, 306–310
- hybrid routing protocols, 493, 496–497

- I**
- I-UWB (Impulse UWB), 4–8, 16–22
 - modulation schemes, 17–20
 - multiple access schemes, 21
 - overview, 16
 - pulse shapes, 16–17
 - receiver decision statistic, 21–22
 - receivers
 - autocorrelation TR receivers, 319–326
 - CD (correlation detection) receivers, 256, 268–281
 - digital I-UWB
 - implementation, 327–331
 - hybrid RAKE/MUD UWB, 256, 300–310
- IA (Integration and Averaging), 318–319
- IEEE proposed standards, 331–332
- LED (leading edge detectors), 258–268
- MUD receivers, 256, 300
- RAKE, 135, 256, 281–299, 352–368
- SBC (sampling bridge circuit), 310–318
- synchronization and timing issues, 326–327
- system model, 257–258
- TMD (template match detectors), 310
- TR-UWB receivers, 256
- signal generators, 213–232
 - avalanche pulse generators, 214–217
 - pulse circuits suitable for integrated circuits, 225–232
- SRDs (Step Recovery Diodes), 217–222
- tunnel diode pulsers, 222–225
- transmitters, 234–237
 - DS-UWB signals, 235
 - OOO-PPM UWB signals, 235
 - TH-(A-PAM) UWB signals, 234–235
 - TH-PPM UWB signals, 234–235
 - TR UWB system, 236–237
 - versus MC-UWB, 6–8
- I-V characteristic, tunnel diode pulsers, 223
- IA (Integration and Averaging) receivers, 318–319
- Ibrahim, Jihad, 618
- ICI (interchannel interference), 255
- IEEE 802.15.3/3a MAC standard, 543–551
 - channel time management Beacon, 545

- contention-based access, 545–547
 - CTAP, 547
- data communication between DEVs, 549–550
- interference mitigation, 550
- piconets, 544–549
 - child and neighbor piconets, 547–548
 - DEV association and disassociation, 549
 - PNC handover, 549
 - starting, maintaining and stopping, 548
- power management, 550–551
 - APS mode, 550
 - DSPS mode, 551
 - PSPS mode, 550
- proposal for DS-based UWB receivers, 332
- proposal for MC-UWB receivers, 344–348
- proposal for OFDM-UWB receivers, 348
- proposal for PPM-based UWB receivers, 331–332
- security, 551
- superframe
 - Beacon, 545
 - contention-based access, 545–547
 - CTAP, 547
- IEEE 802.15.3a PHY standard, 551–556
 - channel model, 554–556
 - link budget, 556
 - overview of solution space, 556
 - selection criteria, 551–554
- IFFT (Inverse Fast Fourier Transform), 559
- imaging systems, EIRP limits, 594–596
- impulse generator, SRDs, 221
- Impulse UWB. *See* I-UWB
- incident power density, 162
- indoor environments
 - electromagnetic simulation of UWB propagation, 58–66
 - comparison of results, 65–66
 - organization of simulator, 63–64
 - receiving antennas, 58–61
 - transmitting antennas, 58–61
 - UWB channel simulation, 61–63
 - large-scale modeling studies, 85
- insertion loss versus frequency, 60
- integrated circuits, pulse generators, 225–232
 - CMOS, 230–232
 - differential circuits, H bridge, 228–230
 - ECL (Emitter Coupled Logic), 226–228
 - Scholtz monocycle generator, 225–226
- Integrated Services Digital Broadcasting. *See* ISDB
- Integration and Averaging receivers. *See* IA receivers
- inter-symbol interference. *See* ISI
- interchannel interference. *See* ICI
- interference analysis
 - NB system on UWB system, 403–411
 - UWB system on UWB system, 411–416
- interference mitigation, IEEE 802.15.3/3a standard, 550
- interference studies, 3
- International Organization for Standardization. *See* ISO
- International Telecommunication Union Radiocommunication Sector. *See* ITU-R
- Internet Protocol networks. *See* IP networks
- Inverse Fast Fourier Transform. *See* IFFT
- IP (Internet Protocol) networks, 473

- ISDB (Integrated Services Digital Broadcasting), 6
- ISI (inter-symbol interference), 237–238
- ISO (International Organization for Standardization), 472
- ITU-R (International Telecommunication Union Radiocommunication Sector), 603

- J–K**
- J (current distribution), antennas, 159

- L**
- LANL (Los Alamos National Laboratories), 3
- LAR (Location-Aided Routing), 497
- large-scale channel modeling, 73
 - better than free-space propagation, 88–89
 - free-space path loss modeling, 75–78
 - flux density, 76
 - Friis transmission formula, 75–78
 - LOS (line-of-sight) measurements, 76
 - frequency dependent models, 83–84
 - impact of antennas, 85–88
 - link budget calculations, 93–103
 - receiver structure dependence, 97–98
 - systems other than free-space, 98
 - UWB link budget, 94–97
 - validation, 98–103
 - partition dependent approaches, 84–85
 - path loss modeling for non-free-space environments, 78–83
 - receiver-dependent path loss models, 90–91
 - shadowing, 91–93
 - studies, 85
- leading edge detectors. *See* LED receivers
- least mean squares. *See* LMS
- LED (leading edge detectors) receivers, 256–268
 - avalanche transistors, 261–263
 - block diagram, 259
 - CFAR receivers, 265
 - false alarms, 258
 - single pulse detection, 259
 - super regenerative I-UWB receiver, 264
 - tunnel diode bistable circuits, 259–262
 - tunnel diode threshold detector, 261–262
- legal issues, 8–12
- Licul, Stanislav, 618–619
- limits
 - antennas, 169
 - EIRP (FCC regulations), 594–601
 - communication and measurement systems, 601–602
 - imaging systems, 594–596
 - vehicular radar systems, 596–601
- line-of-sight measurements. *See* LOS measurements
- link budgets
 - antennas, 168–169
 - IEEE 802.15.3a PHY standard, 556
 - large-scale channel modeling, 93–103
 - receiver structure dependence, 97–98
 - systems other than free-space, 98

- UWB link budget, 94–97
 - validation, 98–103
 - link margin, DS-UWB PHY
 - standard, 591
 - link model, antennas, 165–168
 - LLC (logical link control) sublayer,
 - data link layer, 475
 - LLNL (Los Alamos National Laboratories), 3
 - LMS (least mean squares), 302
 - LNAs (low noise amplifiers), 448
 - local fading. *See* spatial fading
 - localizers, Aether Wire and
 - Location, Inc., 532–536
 - location aware communications
 - applications, 515–520
 - Location-Aided Routing. *See* LAR
 - log-normal random variables, 110
 - log-normal variables, 124–125
 - log-periodic toothed trapezoid. *See*
 - LPTTA
 - logical link control. *See* LLC sublayer
 - LOS (line-of-sight) measurements, 76
 - Los Alamos National Laboratories.
 - See* LLNL; LANL
 - loss resistance, 163
 - low noise amplifiers. *See* LNAs
 - Low Probability of Intercept. *See*
 - LPI
 - LPI (Low Probability of Intercept),
 - 2, 15
 - LPTTA (log-periodic toothed trapezoid), 173
- M**
- MAC (Medium Access Control)
 - protocols, 15, 471, 543
 - magnitude, measuring UWB signal
 - propagation, 39–44
 - maintaining piconets, IEEE
 - 802.15.3/3a standard, 548
 - MANETs (mobile ad hoc networks),
 - 472, 493–498
 - routing protocols
 - AODV (Ad Hoc On-Demand Distance Vector Routing), 495
 - DREAM (Distance Routing Effect Algorithm for Mobility), 497–498
 - DSDV (Destination Sequenced Distance Vector), 493–494
 - DSR (Dynamic Source Routing), 494–495
 - LAR (Location-Aided Routing), 497
 - TORA (Temporally Ordered Routing Algorithm), 496
 - ZRP (Zone Routing Protocol), 496–497
 - Marconi Spark Gap Emitter, 1
 - masters. *See* cluster heads
 - matched filtering, Sperry Rand Corporation
 - developments, 3
 - material-dependent attenuation,
 - 84–85
 - MAVCAS (Micro Air Vehicle Collision Avoidance System), 532–533
 - MAVs (Micro Air Vehicles), 532
 - maximal ratio combiner. *See* MRC
 - maximum effective area
 - (antennas), 164
 - maximum likelihood detectors. *See*
 - ML detectors
 - maximum ratio combining. *See* MRC
 - MB-OFDM (multiband orthogonal frequency division multiplexing), 536
 - PHY standard
 - acquisition, 564–568
 - architecture, 568–571
 - band plan, 561

- IFTT model for
 - transmission, 560
- performance, 571–573
- simultaneously operating piconets, 564
- subcarrier mapping, 561
- time and frequency mapping, 563
- MC-UWB (Multicarrier UWB), 4–8, 22
 - receivers, 13–14, 255, 332–348
 - CI receivers, 334–337
 - FH receivers, 337–342
 - IEEE proposed standards, 344–348
 - OFDM-UWB receivers, 343–344
 - simulation, 444
 - transmitters, 237–244
 - CI-UWB signals, 238–239
 - FH-UWB system, 239–240
 - OFDM-UWB system, 22, 240–244
 - versus I-UWB, 6–8
- MCML (multichannel maximum likelihood) detectors, 333–334
- mean received power, aggregate UWB interference modeling, 395–397
- mean square error. *See* MSE
- measurement systems, EIRP limits, 601–602
- measurements
 - antennas, 169–209
 - frequency and time relationships, 185–186
 - pattern concept in time, 186–187
 - responses, 169–170
 - time domain modeling, 187–200
 - transient responses of scatterers, 200–209
 - UWB performance, 170–185
 - LOS (line-of-sight), 76
 - small-scale channel modeling, 128–130
 - UWB signal propagation, 29–58
 - frequency domain, 36–44, 51–56
 - impact of building architecture and materials, 57–58
 - role of antennas, 57
 - time domain, 30–36, 44–51
- medical imaging, 513
- medical systems, EIRP limits, 596, 599
- Medium Access Control. *See* MAC
- methodologies, UWB simulation
 - discrete event simulation techniques, 435–443
 - entities, 436–438
 - events, 438–439
 - normal operation, 439–440
 - simulation development, 441–442
 - simulation performance considerations, 442–443
 - simulation sample, 440–441
- MC-UWB, 444
- Monte Carlo simulation techniques, 432–434
- semi-analytic simulation techniques, 434–435
- MGF for received power, aggregate UWB interference modeling, 397
- Micro Air Vehicle Collision Avoidance System. *See* MAVCAS
- Micro Air Vehicles. *See* MAVs
- Midkiff, Dr. Scott F., 619
- MIMO (multiple input multiple output) applications, 135
- minimum mean square error. *See* MMSE

- Ministry of Public Management, Home Affairs, Post, and Telecommunications. *See* MPHPT
- ML (maximum likelihood) detectors, 282–283
- MMSE (minimum mean square error)
 - hybrid RAKE/MUD UWB receivers, 300–305
 - versus EC, 306–310
 - realistic RAKE receivers, 292
- mobile ad hoc networks. *See* MANETs
- model development, UWB
 - simulations, 427–428
- models
 - American Electronic Laboratories model
 - APN-101B, 185
 - Antenna Research Associates model DRG-118/A, 185
 - antennas in time domain, 169–209
 - frequency and time relationships, 185–186
 - pattern concept in time, 186–187
 - time domain modeling, 187–200
 - transient responses to scatterers, 200–209
 - UWB performance, 170–185
 - channel modeling
 - impact of frequency distortion, 144–151
 - large-scale channel modeling, 74–103
 - small-scale channel modeling, 103–130
 - spatial behavior, 130–144
 - unique features of UWB, 13, 74
 - deterministic modeling, 73
 - DoD network model, 472
 - I-UWB system, 16–22
 - overview, 16
 - pulse shapes, 16–17
 - MC-UWB system, 22
 - site-specific modeling, 73
 - TCP/IP reference model, 472–473
- modified Poisson model, small-scale channel modeling, 112
- modulation schemes, 445–448
 - I-UWB system, 17–20
- modulators, 232–234
- monocycle generator
 - Scholtz, 225–226
 - SRDs, 221
- monopole antenna model, 191–192
- Monte Carlo simulation techniques, 432–434
 - pulse generation and modulation, 448
- Motorola Trinity Chipset (XSI), 520–521
- MPHPT (Ministry of Public Management, Home Affairs, Post, and Telecommunications), 603
- MRC (maximal ratio combiner), 291, 404
- MSE (mean square error), 236
- MSS (maximum segment size), 498
- MSSI (Multispectral Solutions Incorporated) products, 4, 524–532
 - AWICS, 526–527
 - Draco, 525
 - HFUWB, 526
 - MAVCAS, 532
 - Orion system, 526
 - PAL system, 527–532
- MUD (multi-user detectors)
 - receivers, 256, 300
- multi-user detectors. *See* MUD receivers

- multiband orthogonal frequency
 - division multiplexing. *See* MB-OFDM
 - Multicarrier UWB. *See* MC-UWB
 - multicast transfer of information, 471
 - multichannel maximum likelihood
 - detectors. *See* MCML detectors
 - multiple access protocols
 - data link layer design (UWB networking), 483–486
 - collision-free schemes, 483–484
 - random access schemes, 484–486
 - I-UWB system, 21
 - multiple hop ad hoc networks, 487–498
 - flat network topologies, 493–498
 - AODV (Ad Hoc On-Demand Distance Vector Routing), 495
 - DREAM (Distance Routing Effect Algorithm for Mobility), 497–498
 - DSDV (Destination Sequenced Distance Vector) protocol, 493–494
 - DSR (Dynamic Source Routing), 494–495
 - LAR (Location-Aided Routing), 497
 - routing protocols, 493–494
 - TORA (Temporally Ordered Routing Algorithm), 496
 - ZRP (Zone Routing Protocol), 496–497
 - hierarchical topologies, 489–493
 - multiple hop communication, 472
 - multiple input multiple output
 - applications. *See* MIMO applications
 - Multispectral Solutions
 - Incorporated. *See* MSSI products
 - Muthuswamy, Sridharan, 619
- N**
- N-tone Sigma-Delta modulators, 242–244
 - N-tone Sigma-Delta OFDM-UWB receivers, 344
 - NACK (negative acknowledgment) packets, 476, 487
 - Nakagami distribution, 124–125
 - narrowband interference. *See* NBI
 - narrowband systems. *See* NB systems, 379
 - National Telecommunications and Information Administration. *See* NTIA
 - NB systems (narrowband systems), 379
 - coexistence with UWB signals, 379–416
 - aggregate UWB interference modeling, 393–403
 - interference analysis, 403–416
 - waveform analysis, 381–393
 - versus UWB systems, 2
 - NBI (narrowband interference), 380
 - Neel, James O., 619–620
 - negative acknowledgment packets. *See* NACK packets
 - neighbor piconets, 547–548
 - NETEX (Networking in Extreme Environments), 4
 - network layer (network protocols), 472–473
 - networks, 471–503
 - data link layer design, 475–487
 - ARQ (automatic repeat request), 486–487
 - channel partition medium access control, 483
 - contention-based medium access control, 478–483
 - FEC (forward error correction), 486–487
 - multiple access protocols, 483–486
 - objectives, 475–478

- multiple hop ad hoc networks, 487–498
 - flat network topologies, 493–498
 - hierarchical topologies, 489–493
 - physical layer issues, 474–475
 - QoS management, 500–502
 - TCP performance in wireless environments, 498–500
 - unique features, 14–15, 474
 - NLOS (non line-of-sight) conditions, 526
 - non line-of-sight conditions. *See* NLOS conditions
 - non-free-space environments
 - large-scale channel modeling, link budgets, 98
 - path loss modeling, 78–83
 - nonresolvable paths, RAKE receivers
 - A-PAM modulation, 286–288
 - PPM modulation, 289
 - normalized load voltage, 165
 - NTIA (National Telecommunications and Information Administration), 4
- O**
- objectives, data link layer design (UWB networking)
 - point-to-point flow control, 476–477
 - power conservation, 477
 - reliable data delivery, 476
 - resource sharing, 477–478
 - OC (optimal combining), realistic RAKE receivers, 292
 - OFDM-UWB system (Orthogonal Frequency Division Multiplexing), 4–5, 22, 24–244
 - receivers, 343–344
 - IEEE proposed standard, 348
 - office environment, large-scale modeling studies, 85
 - omni-directional antennas, path loss, 87
 - OOO-PPM (optical orthogonal coded pulse position modulation) UWB signals, 235
 - Open Shortest Path First protocol. *See* OSPF
 - open-circuit voltage, 163
 - optical orthogonal coded pulse position modulation. *See* OOC-PPM UWB signals
 - optimal combining. *See* OC
 - optimal matched filter performance, CD receivers, 268–271
 - A-PAM modulation, 270–271
 - PPM modulation, 271
 - ordinary nodes, hierarchical topologies, 490
 - Orion system, 526
 - Orthogonal Frequency Division Multiplexing. *See* OFDM-UWB system
 - oscilloscopes, development in 1960s, 3
 - OSPF (Open Shortest Path First protocol), 473
- P**
- PAL (Precision Asset Location) system, 527–532
 - PAL650, 527–531
 - PAM (Pulse Amplitude Modulation), 17
 - PAPR (peak-to-average power ratio), 14
 - parameters
 - model parameters, small-scale channel modeling, 114–123
 - S-parameters, antennas, 165–168
 - partial band interference. *See* PBI
 - partition dependent approaches, large-scale channel modeling, 84–85

- path loss modeling
 - better than free-space propagation, 88–89
 - directional antennas, 87
 - free-space, 75–78
 - large-scale modeling studies, 85
 - non-free-space environments, 78–83
 - receiver-dependent models, 90–91
- pattern concept, antenna
 - measurements and modeling in time domain, 186–187
- PBI (partial band interference), 380
- PDUs (protocol data units), 472
- peak path loss, 90
- peak power limits, FCC
 - regulations, 601
- peak-to-average power ratio. *See* PAPR
- performance
 - DS-UWB PHY standard, 588–590
 - MB-OFDM PHY standard, 571–573
 - UWB, antenna measurements and modeling in time domain, 170–185
 - CBAS, 176–179
 - potential structures, 181–185
 - resonant monopole, 174–176
 - TEM horn, 180–181
- phase, measuring UWB signal
 - propagation, 39–44
- phase-locked loop. *See* PLL
- PHY layer (physical layer), 543
 - networks, 472–475
- physical layer convergence protocol. *See* PLCP
- physical layer. *See* PHY layer
- Piconet Synchronized Power Save. *See* PSPS mode
- piconets
 - DS-UWB PHY standard, 578–584
 - IEEE 802.15.3/3a standard
 - child and neighbor piconets, 547–548
 - DEV association and disassociation, 549
 - PNC handover, 549
 - starting, maintaining and stopping, 548
 - MB-OFDM PHY standard, 564
- pilot waveform assisted modulation. *See* PWAM
- pilots, CD receivers
 - A-PAM modulation, 273–275
 - PPM modulation, 275–281
- PLCP (physical layer convergence protocol), 564
- PLL (phase-locked loop), 233
- PNC handover, 549
- point-to-point flow control, data link
 - layer design (UWB networking), 476–477
- point-to-point protocols, 472
- Poisson arrival rate, 115
- Poisson models
 - modified Poisson model, 112
 - single Poisson model, 112
 - split-Poisson model, 112–114
- polarization factor, 164–165
- polarization properties, antennas, 159, 164
- pole modeling, antenna systems, 187–200
 - biconic antenna model, 191
 - monopole antenna model, 191–192
 - Vivaldi antenna model, 192–200
- positive going avalanche pulse generators, 216
- power
 - amplifiers, 448

- conservation, data link layer
 - design (UWB networking), 477
 - management, IEEE 802.15.3/3a
 - standard, 550–551
 - APS mode, 550
 - DSPS mode, 551
 - PSPS mode, 550
 - Power Line Networking (Homeplug), 6
 - power spectral density. *See* PSD
 - PPM (Pulse Position Modulation), 17
 - CD receivers
 - optimal matched filter performance, 271
 - performance based on pilots, 275–281
 - simple matched filter performance, 272–273
 - RAKE receivers, 288–289
 - nonresolvable paths, 289
 - resolvable paths, 288–289
 - PPM-based UWB receivers, IEEE 802.15.3/3a proposed standard, 331–332
 - Precision Asset Location. *See* PAL system
 - precision position location capability, 510
 - presentation layer (network protocols), 472
 - PRF (pulse repetition frequency), 380
 - proactive routing protocols, DSDV, 493–494
 - programmable CMOS pulse generators, 230–232
 - propagation (UWB signals), 29–68
 - electromagnetic simulation in
 - indoor environments, 58–66
 - comparison of results, 65–66
 - organization of simulator, 63–64
 - receiving antennas, 58–61
 - transmitting antennas, 58–61
 - UWB channel simulation, 61–63
 - measurement, 29–68
 - frequency domain, 36–44
 - impact of building
 - architecture and materials, 57–58
 - results of measurements, 44–58
 - role of antennas, 57
 - time domain, 30–36, 44–51
 - studies, 4
 - two-dimensional channel model for indoor propagation, 140–144
 - unique features of UWB signals, 13
- properties, antennas, 160–169
 - directivity, 162–165
 - effective area, 164
 - effective length, 161–162
 - gain (G), 162–165
 - maximum effective area, 164
 - polarization, 159, 164
 - received power, 162–165
 - reciprocity, 161–162
- proposal, MB-OFDM PHY standard, 559–564
- protocol data units. *See* PDUs
- protocols
 - BGP (Border Gateway Protocol), 473
 - CTS (clear to send), 482
 - hybrid protocols (MANET protocol), 493
 - Internet Protocol, 473
 - MAC. *See* MAC protocols
 - OSPF (Open Shortest Path First protocol), 473
 - PLCP (physical layer convergence protocol), 564
 - point-to-point, 472
 - proactive protocols (MANET protocol), 493–494

- reactive protocols (MANET protocol), 493–498
 - AODV (Ad Hoc On-Demand Distance Vector Routing), 494
 - DREAM (Distance Routing Effect Algorithm for Mobility), 497–498
 - DSR (Dynamic Source Routing), 494–495
 - LAR (Location-Aided Routing), 497
 - TORA (Temporally Ordered Routing Algorithm), 496
 - RTS (request to send), 482
 - UDP (User Datagram Protocol), 473
 - PSD (power spectral density), 19
 - PSPS (Piconet Synchronized Power Save) mode, 550
 - Pulse Amplitude Modulation. *See* PAM
 - pulse compression, Sperry Rand Corporation
 - developments, 3
 - pulse generators, 445–448
 - avalanche, 214–217
 - integrated circuits, 225–232
 - CMOS, 230–232
 - differential circuits, H bridge, 228–230
 - ECL (Emitter Coupled Logic), 226–228
 - Scholtz monocycle generator, 225–226
 - SRDs (Step Recovery Diodes), 217–222
 - tunnel diode pulsers, 222–225
 - Pulse Position Modulation. *See* PPM
 - pulse repetition frequency. *See* PRF
 - pulse shapes, I-UWB system, 16–17
 - pulse width modulation. *See* PWM
 - PulsON 100 chipset (TDC), 521–524
 - pure impulse radio, 4
 - PWAM (pilot waveform assisted modulation), 236–237
 - PWM (pulse width modulation), 232
- Q**
- Q (unloaded quality factor), 169
 - QoS (Quality of Service)
 - requirements, 15
 - network management, 500–502
 - Query messages (TORA), 496
- R**
- R-C differentiator, 219
 - radiation resistance, 163
 - radio receivers (I-UWB), 256–332
 - Radioelectronics Institute of the USSR Academy of Science, 3
 - RAKE receivers, 135, 256, 281–299
 - A-PAM modulation, 285–288
 - nonresolvable paths, 286–288
 - resolvable paths, 285–286
 - case study, 352–368
 - demodulator structure, 284
 - drawbacks, 282
 - PPM modulation, 288–289
 - realistic RAKE receivers, 289–299
 - MMSE (minimum mean square error), 292
 - MRC (maximum ratio combining), 291
 - OC (optimal combining), 292
 - SINR (signal-to-interference plus noise ratio), 292
 - random access MAC schemes. *See* contention-based MAC schemes
 - range analysis of UWB signals, TOA (Time of Arrival), 541–542
 - Rayleigh distribution, 124–125
 - RBW (resolution bandwidth), 601

- reactive routing protocols, 493–498
 - AODV (Ad Hoc On-Demand Distance Vector Routing), 494
 - DREAM (Distance Routing Effect Algorithm for Mobility), 497–498
 - DSR (Dynamic Source Routing), 494–495
 - LAR (Location-Aided Routing), 497
 - TORA (Temporally Ordered Routing Algorithm), 496
- realistic RAKE receivers, 289–299
 - MRC (maximum ratio combining), 291
 - OC (optimal combining), 292
 - SINR (signal-to-interference plus noise ratio), 292
- received power, 165
 - aggregate UWB interference modeling, 393–395
 - antennas, 162–165
- receiver decision statistic, I-UWB system, 21–22
- receiver structure dependence,
 - large-scale channel modeling link budgets, 97–98
- receiver-dependent path loss models,
 - large-scale channel modeling, 90–91
- receivers, 13–14
 - I-UWB, 256–332
 - autocorrelation TR receivers, 319–326
 - CD (correlation detection) receivers, 256, 268–281
 - digital I-UWB implementation, 327–331
 - hybrid RAKE/MUD UWB, 256, 300–310
 - IA (Integration and Averaging), 318–319
 - IEEE proposed standards, 331–332
 - LED (leading edge detectors), 256, 258–268
 - MUD receivers, 256, 300
 - RAKE, 135, 255, 256, 281–299, 352–368
 - SBC (sampling bridge circuit), 310–318
 - synchronization and timing issues, 326–327
 - system model, 257–258
 - TMD (template match detectors), 310
 - TR-UWB receivers, 256
 - impedance, 163
 - MC-UWB, 13–14, 255, 332–348
 - CI (Carrier Interferometry) receivers, 334–337
 - FH (frequency hopped) receivers, 337–342
 - IEEE proposed standards, 344–348
 - OFDM-UWB receivers, 343–344
 - spectral encoded UWB communication system, 348–352
 - threshold. *See* LED receivers, 256
- receiving antennas, electromagnetic simulation of UWB propagation, 58–61
- reciprocity, antennas, 161–162
- recursive least squares. *See* RLS
- reduced function devices. *See* RFDs
- Reed, Dr. Jeffrey H., 613
- reflections, impact of frequency distortion on discrete channel modeling, 146–151
- regulations, 8–12
 - FCC, 593–602
 - bandwidth limits, 593–594
 - EIRP limits, 594–601

- peak power limits, 601
 - unintentional radiation, 601–602
 - world, 603
 - reliable data delivery, data link layer
 - design (UWB networking), 476
 - request to send protocols. *See* RTS protocols
 - residue number systems. *See* RNS
 - resolution bandwidth. *See* RBW
 - resolvable paths, RAKE receivers
 - A-PAM modulation, 285–286
 - PPM modulation, 288–289
 - resonant monopole, 174–176
 - resource sharing, data link layer
 - design (UWB networking), 477–478
 - responses, antenna measurements
 - and modeling in time domain, 169–170
 - restrictions on UWB operation, First Report and Order (FCC), 8–12
 - retransmission, 549–550
 - retransmission time-out interval. *See* RTO interval
 - RFDs (reduced function devices), 537
 - Riad, Dr. Sedki, 620
 - RLS (recursive least squares), 302
 - RMS delay spread, 108
 - RNS (residue number systems), 239, 337
 - root raised cosine. *See* RRC pulses
 - round-trip time. *See* RTT
 - Route Error messages (DSR), 495
 - Route Reply messages
 - AODV (Ad Hoc On-Demand Distance Vector Routing), 495
 - DSR (Dynamic Source Routing), 495
 - Route Request messages
 - AODV (Ad Hoc On-Demand Distance Vector Routing), 495
 - DSR (Dynamic Source Routing), 494–495
 - routing algorithms, 473
 - routing protocols, 493–494
 - RRC (root raised cosine) pulses, 577
 - RTO (retransmission time-out) interval, 499
 - RTS (request to send) protocols, 482
 - RTT (round-trip time), 499
- S**
- S*-parameters, antennas, 165–168
 - Sadler, Brian M., 620
 - Safaa-Jazi, Dr. Ahmad, 621
 - safe operating active region. *See* SOAR
 - Saleh-Valenzuela Channel model
 - simulation, 463–466
 - small-scale channel modeling, 109–110
 - sampling bridge circuit. *See* SBC
 - sampling issues, measuring UWB signal propagation, 33–36
 - sampling oscilloscope, development in 1960s, 3
 - sanity checking, simulation development, 430
 - SAW (surface acoustic wave) devices, 349
 - SBC (sampling bridge circuit), 310–318
 - scalar frequency domain measurement, 36–39
 - scalar network analyzer. *See* SNA
 - scatterers, transient responses, 200–209
 - scatternet (Bluetooth)
 - formation algorithm, 490
 - hierarchical topologies, 489–490
 - Scholtz monocycle generator, 225–226

- Scholtz, Robert, multiple access
 - technique for UWB
 - communication systems, 3
- Security, IEEE 802.15.3/3a
 - standard, 551
- selection criteria, IEEE 802.15.3a
 - PHY standard, 551–554
- SEM (singularity expansion model), 200
- semi-analytic simulation techniques, 434–435, 448
- session layer (network protocols), 472
- shadowing, large-scale channel modeling, 91–93
- SiGe technology, PulsOn chips, 524
- signal amplification, 448–451
- signal generators, I-UWB, 213–232
 - avalanche pulse generators, 214–217
 - pulse circuits suitable for integrated circuits, 225–232
 - SRDs (Step Recovery Diodes), 217–222
 - tunnel diode pulsers, 222–225
- signal-to-interference plus noise ratio. *See* SINR
- signal-to-interference ratio. *See* SIR
- signal-to-noise ratio. *See* SNR
- signals (UWB). *See* UWB signals
- simple matched filter performance, CD receivers
 - A-PAM modulation, 271–272
 - PPM modulation, 272–273
- simulation (UWB propagation), 58–66, 423–467
 - component simulation, 445–466
 - antenna effects, 451–459
 - pulse generation and modulation, 445–448
 - signal amplification, 448–451
 - UWB channels, 460–466
 - development, 428–432
 - discrete event simulation techniques, 435–443
 - entities, 436–438
 - events, 438–439
 - normal operation, 439–440
 - simulation development, 441–442
 - simulation performance considerations, 442–443
 - simulation sample, 440–441
- electromagnetic simulation, 58–66
 - comparison of simulation results, 65–66
 - organization of electromagnetic simulator, 63–64
 - transmitting and receiving antennas, 58–61
 - UWB channel simulation, 61–63
- FH receivers, 338–340
- MC-UWB simulation, 444
- Monte Carlo simulation techniques, 432–434
- semi-analytic simulation techniques, 434–435
- unique features of UWB, 425–428
 - development challenges, 428
 - direct/quadrature signal decomposition, 425–427
 - model development, 427–428
- single hop communication, 471
- single Poisson model, small-scale channel modeling, 112
- single pulse detection, LED receivers, 259
- singularity expansion model. *See* SEM
- SINR (signal-to-interference plus noise ratio), realistic RAKE receivers, 292
- sinusoidal Gaussian pulse, 18
- SIR (signal-to-interference ratio), 498
- site-specific modeling, 73
- slaves. *See* ordinary nodes

- sleep modes (data link layer standard), 477
- Slotted Aloha (contention-based MAC scheme), 479–481
- small-scale channel modeling, 73, 103–130
 - Δ -K model, 110–111
 - amplitude statistics, 124–128
 - channel impulse response, 107–109
 - effect of model parameters, 114–123
 - modified Poisson model, 112
 - Saleh-Valenzuela model, 109–110
 - split-Poisson model, 112–114
 - STDL (stochastic tapped-delay line) model, 124
 - summary of measurement campaigns, 128–130
- SNA (scalar network analyzer), 36
- snap off diodes. *See* SRDs
- snooze modes (data link layer standard), 477
- SNR (signal-to-noise ratio), 267
- SOAR (safe operating active region), 214–215
- Software Radio: A Modern Approach to Radio Engineering* (Reed), 613
- solution space, IEEE 802.15.3a PHY standard, 556
- Soviet Union developments, history of UWB signals, 3
- spanning tree topologies, 492–493
- spatial behavior, statistical modeling
 - spatial correlation, 135–140
 - spatial fading, 133–135
 - spatial fading of significant components, 135
 - two-dimensional channel model for indoor propagation, 140–144
- specialized applications for UWB, 509–511
- spectral encoded UWB
 - communication system, 245–247, 348–352
- spectral mask, FCC restrictions on UWB operations, 8–12
- Sperry Rand Corporation
 - developments, 3
- split-Poisson model, small-scale channel modeling, 112–114
- spread spectrum techniques, 256
- square pulse avalanche pulse generator, 217
- SRDs (Step Recovery Diodes), 217–222
- standards (UWB standards for WPANs), 543–592
 - DS-UWB PHY, 573–590
 - acquisition, 584–586
 - architecture, 586–588
 - overview, 577–578
 - performance, 588–590
 - simultaneously operating piconets, 578–584
 - IEEE 802.15.3/3a MAC, 543–551
 - data communication between DEVs, 549–550
 - interference mitigation, 550
 - piconets, 547–549
 - power management, 550–551
 - security, 551
 - superframe and channel time management, 545–547
 - IEEE 802.15.3a PHY, 551–556
 - channel model, 554–556
 - link budget, 556
 - overview of solution space, 556
 - selection criteria, 551–554
 - MB-OFDM PHY, 556–573
 - acquisition, 564–568
 - architecture, 568–571
 - performance, 571–573

- proposal, 559–564
- simultaneously operating piconets, 564
- starting piconets, IEEE 802.15.3/3a standard, 548
- statistical modeling (channel modeling), 73–151
 - Δ -K model, 110–111
 - impact of frequency distortion, 144–151
 - large-scale channel modeling
 - better than free-space propagation, 88–89
 - free-space path loss modeling, 75–78
 - frequency dependent models, 83–84
 - impact of antennas, 85–88
 - link budget calculations, 93–103
 - non-free-space environments, 78–83
 - partition dependent approaches, 84–85
 - receiver-dependent path loss models, 90–91
 - shadowing, 91–93
 - studies, 85
 - small-scale channel modeling, 103–130
 - amplitude statistics, 124–128
 - channel impulse response, 107–109
 - effect of model parameters, 114–123
 - modified Poisson model, 112
 - Saleh-Valenzuela model, 109–110
 - single Poisson model, 112
 - split-Poisson model, 112–114
 - STDL (stochastic tapped-delay line), 124
 - summary of measurement campaigns, 128–130
 - spatial behavior, 130–144
 - spatial correlation, 135–140
 - spatial fading, 133–135
 - spatial fading of significant components, 135
 - two-dimensional channel model for indoor propagation, 140–144
 - unique features of UWB systems, 74
- STDL model (stochastic tapped-delay line), 124
- Step Recovery Diodes. *See* SRDs
- steps in simulation development, 429
- stochastic tapped-delay line model. *See* STDL model
- stopping piconets, IEEE 802.15.3/3a standard, 548
- studies
 - case studies, 520–540
 - 802.15.3/3a devices, 536
 - 802.15.4a devices, 537–538
 - Aether Wire and Location, Inc., localizers, 532–536
 - MSSI products, 524–532
 - RAKE receivers, 352–368
 - TDC-PulsON chipset, 521–524
 - XSI/Motorola Trinity Chipset, 520–521
 - large-scale channel modeling, 85
 - propagation, 4
- super regenerative I-UWB receiver, LED receivers, 264
- super-master nodes, hierarchical topologies, 490
- surveillance systems, EIRP limits, 596, 598
- surface acoustic wave devices. *See* SAW devices
- Swami, Dr. Ananthram, 621
- Sweeney, Dr. Dennis, 621–622

synchronization, I-UWB receivers,
326–327
system model, I-UWB receivers,
257–258

T

tapped-delay line models
Saleh-Valenzuela model,
109–110
stochastic, 124
Task Group 31a (ETSI), 603
TCP (Transmission Control
Protocol), 473, 498–500
TCP/IP reference model, 472–473
TDC (Time Domain Corporation), 4
PulsON chipset, 521–524
SiGe technology, 524
TH-PPM-based channel
sounder, 129
TDMA (Time Division Multiple
Access), 15, 477, 483, 521
TDOA (time difference of
arrival), 541
Tektronix, development of sampling
oscilloscope, 3
TEM (transverse electric and
magnetic) horn antennas,
180–185, 202–209
template match detectors. *See* TMD
Temporally Ordered Routing
Algorithm. *See* TORA
ternary random process model, 414
TFC (time frequency codes), 564
TH-(A-PAM) (time-hopped
antipodal pulse amplitude
modulation), 234–235
TH-PPM (time-hopped pulse
position modulation), 129,
234–235, 256
TH-PSK (time hopped phase shift
keying), 256
threshold receivers. *See* LED
receivers
Through-Walls imaging devices,
EIRP limits, 596, 597

TIC (time integrating
correlator), 535
time constant of exponential energy
decay, 116
time difference of arrival. *See* TDOA
Time Division Multiple Access. *See*
TDMA
time domain
design, unique features of UWB
signals, 12
measuring UWB signal
propagation, 30–36, 44–51
channel measurement, 31–33
measurement results, 44–51
sampling and triggering
issues, 33–36
modeling, 187–200
antennas, 169–209
Time Domain Corporation. *See* TDC
time frequency codes. *See* TFC
time hopped phase shift keying. *See*
TH-PSK
time integrating correlator. *See* TIC
Time Interleaved Sampling, digital
UWB receivers, 327–331
Time Modulated UWB. *See*
TM-UWB
time-hopped antipodal pulse
amplitude modulation. *See*
TH-(A-PAM) UWB signals
time-hopped case
coexistence of UWB and NB
systems, 390–392
time-hopped pulse position
modulation. *See* TH-PPM
times-of-arrival. *See* TOAs
timing issues, I-UWB receivers,
326–327
TM-UWB (Time Modulated
UWB), 524
TMD (template match detectors),
310, 314
TOAs (times-of-arrival), 140–141,
541–542

- TORA (Temporally Ordered Routing Algorithm), 496
- TR (Transmitter Reference) UWB system, 236–237
 - PWAM optimization, 236–237
 - receivers, 256, 319–326
 - TR system model, 236
- transient responses, scatterers, 200–209
- Transmission Control Protocol. *See* TCP
- transmitted reference model. *See* TR UWB system
- Transmitter Reference UWB system. *See* TR UWB system
- transmitters, 213–247
 - design, 13–14
 - I-UWB signal generators, 213–232
 - avalanche pulse generators, 214–217
 - pulse circuits suitable for integrated circuits, 225–232
 - SRDs (Step Recovery Diodes), 217–222
 - tunnel diode pulsers, 222–225
 - I-UWB transmitters, 234–237
 - DS-UWB signals, 235
 - OOC-PPM UWB signals, 235
 - TH-(A-PAM) UWB signals, 234–235
 - TH-PPM UWB signals, 234–235
 - TR UWB system, 236–237
 - MC-UWB transmitters, 237–244
 - CI-UWB signals, 238–239
 - FH-UWB system, 239–240
 - OFDM-UWB system, 240–244
 - modulators, 232–234
 - power regulations (FCC), 475
 - spectral encoded UWB communication system, 245–247
 - transmitting antennas,
 - electromagnetic simulation of UWB propagation, 58–61
 - transport layer (network protocols), 472–473
 - transverse electric and magnetic horn. *See* TEM horn antennas
 - Tranter, Dr. William H., 622
 - triggering issues, measuring UWB signal propagation, 33–36
 - Trinity chipset (XSI), 520–521
 - tunnel diode bistable circuits, LED receivers, 259–262
 - tunnel diode pulsers, 222–225
 - tunnel diode threshold detector, LED receivers, 261–262
 - two cluster model, 114
 - two-dimensional channel model, indoor propagation, 140–144
 - two-stage distributed clustering algorithm, hierarchical topologies, 490
- U**
- U.S. Department of Defense network model. *See* DoD network model
- UDP (User Datagram Protocol), 473
- undesired signals (channels), 73
- unicast transfer of information, 471
- uniform theory of diffraction. *See* UTD
- unintentional radiation, FCC regulations, 601–602
- unique features (UWB)
 - networking, 474
 - signals, 12–16
 - antennas, 13
 - difficulties using DSP technology, 14
 - future directions, 15–16
 - networking issues, 14–15
 - time domain design, 12

- transmitter and receiver design, 13–14
- systems, 2
- unit vector, antennas, 159
- University of Southern California. *See* USC group
- unloaded quality factor (Q), 169
- Update messages (TORA), 496
- USC (University of Southern California) group, wireless communication research, 44–58
- User Datagram Protocol. *See* UDP
- UTD (uniform theory of diffraction), 61
- UWB networking, 471–503
 - data link layer design, 475–487
 - ARQ (automatic repeat request), 486–487
 - channel partition medium access control, 483
 - contention-based medium access control, 478–483
 - FEC (forward error correction), 486–487
 - multiple access protocols, 483–486
 - objectives, 475–478
 - multiple hop ad hoc networks, 487–498
 - flat network topologies, 493–498
 - hierarchical topologies, 489–493
 - physical layer issues, 474–475
 - QoS management, 500–502
 - TCP performance in wireless environments, 498–500
 - unique features, 474
- UWB pulse model, coexistence of UWB and NB systems, 382–384
- UWB signals
 - coexistence with NB systems, 379–416
 - aggregate UWB interference modeling, 393–403
 - interference analysis, 403–416
 - waveform analysis, 381–393
 - I-UWB, 4–8, 16–22
 - channel modeling, 73–151
 - history, 3–4
 - modulation schemes, 17–20
 - multiple access schemes, 21
 - overview, 16
 - pulse shapes, 16–17
 - receiver decision statistic, 21–22
 - MC-UWB, 4–8, 22
 - propagation
 - electromagnetic simulation in indoor environments, 58–66
 - measurement, 29–58
 - studies, 4
 - two-dimensional channel model for indoor propagation, 140–144
 - unique features of UWB signals, 13
 - range analysis using TOA (Time of Arrival), 541–542
 - unique features, 12–16
 - antennas, 13
 - difficulties using DSP technology, 14
 - future directions, 15–16
 - networking issues, 14–15
 - propagation and channel models, 13
 - time domain design, 12
 - transmitter and receiver design, 13–14
- UWB simulations, 423–467
 - component simulation, 445–466
 - antenna effects, 451–459
 - pulse generation and modulation, 445–448

- signal amplification, 448–451
 - UWB channels, 460–466
 - development, 428–432
 - discrete event simulation
 - techniques, 435–443
 - entities, 436–438
 - events, 438–439
 - normal operation, 439–440
 - simulation development, 441–442
 - simulation performance
 - considerations, 442–443
 - simulation sample, 440–441
 - MC-UWB simulation, 444
 - Monte Carlo simulation
 - techniques, 432–434
 - semi-analytic simulation
 - techniques, 434–435
 - unique features, 425–428
 - development challenges, 428
 - direct/quadrature signal decomposition, 425–427
 - model development, 427–428
 - UWB standards (WPANs), 543–592
 - DS-UWB PHY, 573–590
 - acquisition, 584–586
 - architecture, 586–588
 - overview, 577–578
 - performance, 588–590
 - simultaneously operating piconets, 578–584
 - IEEE 802.15.3/3a MAC, 543–551
 - data communication between DEVs, 549–550
 - interference mitigation, 550
 - piconets, 547–549
 - power management, 550–551
 - security, 551
 - superframe and channel time management, 545–547
 - IEEE 802.15.3a PHY, 551–556
 - channel model, 554–556
 - link budget, 556
 - overview of solution space, 556
 - selection criteria, 551–554
 - MB-OFDM PHY, 556–573
 - acquisition, 564–568
 - architecture, 568–571
 - performance, 571–573
 - proposal, 559–564
 - simultaneously operating piconets, 564
- V**
- validation
 - large-scale channel modeling, link budgets, 98–103
 - simulation development, 430
 - vector network analyzer. *See* VNA
 - vehicular radar, 512
 - Very Large-Scale Integration. *See* VLSI
 - Virginia Tech (Department of Electrical and Computer Engineering). *See* VT group
 - Vivaldi antenna model, 192–200
 - VLSI (Very Large-Scale Integration), 5
 - VNA (vector network analyzer), 36, 41–42, 85
 - Voltage Standing Wave Ratio. *See* VSWR
 - voltage tuned oscillator. *See* VTO
 - VSWR (Voltage Standing Wave Ratio), 13, 170
 - VT group (Virginia Tech Department of Electrical and Computer Engineering), wireless communication research, 44–58
 - VTO (voltage tuned oscillator), 41

W

wave number, antennas, 159
waveform analysis, coexistence of
 UWB and narrowband
 radio systems, 381–393
 BER analysis, 384–390
 NB receive filter, 384
 simulation results, 392–393
 time-hopped case, 390–392
 UWB pulse model, 382–384
waveform specificity, 96–97
WB systems (wideband
 systems), 379
Weibull distribution, 124–125
wideband systems. *See* WB systems
Wireless Personal Area Networks.
 See WPANs
world regulations, 603

WPANs (Wireless Personal Area
 Networks), 14
UWB standards, 543–592
 DS-UWB PHY, 573–590
 IEEE 802.15.3/3a MAC,
 543–551
 IEEE 802.15.3a PHY, 551–556
 MB-OFDM PHY, 556–573

X–Z

XSI (XtremeSpectrum
 Incorporated), Motorola
 Trinity Chipset, 520–521
XtremeSpectrum Incorporated. *See*
 XSI
Zone Routing Protocol. *See* ZRP
ZRP (Zone Routing Protocol), 496–497