

---

# Index

---

- ~/id\_rsa.pub file, 330
- ~/rhosts file, 314
- ~/ssh/known\_hosts file, 329
- ~/ssh/known\_hosts2 file, 329
- ~/vnc/xstartup script, 367
- 2.4.x kernel optional features, 9
- 8.3 filenames, 181, 431–432
- 802.11 standard, 21
- 802.11b standard, 21
- A
- <A HREF> tag, 561
- Access file, 296–297
- access.conf file, 533
- AccessConfig directive, 533
- access.db file, 493, 496–497
- account service, 164
- ACCOUNT variable, 58, 59
- Accounts
  - creation procedures and policies, 607–608
  - FTP servers, 576
  - inactive, 608–609
  - monitoring usage, 608–610
- ACLs (Access Control Lists), 149, 183
- Active file, 292–293
- add command, 343, 344
- AddModule directive, 541, 554
- addprinc command, 150, 151, 154
- Address masquerading
  - Exim, 501–502
  - Postfix, 509–510
  - sendmail, 494
- Address A record, 469
- Address rewriting, 510
- Address spoofing, 673
- Administrative principal, 150–151
- Administrative servers, 409–410
- Adobe PostScript drivers, 188
- Adobe Web site, 187
- ADSL (Asymmetric DSL), 19
- adsl-start dialing script, 52
- Advanced router configurations, 642–643
  - advanced kernel options, 643–647
- afpd program, 70
- afpd.conf file, 70
- afpfs package, 71
- Alcatel Web site, 20
- Aliases
  - e-mail, 494
  - ProFTPd, 590
- aliases file, 508
- aliases.db file, 494

## INDEX

- alien utility, 695
- Allow directive, 233
- Alternative local network devices, 17–18
- AMANDA (Advanced Maryland Automatic Network Disk Archiver), 415, 416, 436
  - backup client software, 436–437
  - backup server, 436–437
  - client-based restore tools, 446
  - configuring, 439–444
  - configuring clients for, 437–438
  - defining backup set, 442–444
  - defining dump types, 442–443
  - distributions, 436
  - dump cycle, 440
  - e-mailing reports, 440
  - functions of, 436–437
  - holding area for data, 441–442
  - index of files in backup set, 442
  - Kerberos, 442
  - log file locations, 441
  - maximum network bandwidth, 441
  - naming backup tapes, 441
  - number of tapes in dump cycle, 440
  - preparing tapes, 441–442
    - as scheduling tool, 437
  - type of tape device, 440–441
  - usernames, 440
- AMANDA backup servers
  - configuring, 439
  - large hard disk, 437
  - running, 444–445
- AMANDA clients, configuring, 437–438
- amanda.conf file, 439–444
- amandad, 437–438
- .amandahosts file, 438
- amdump program, 444–445
- amlabel utility, 441–442
- amrecover, 446
- analog, 567–570
- analog.cfg file, 567–568
- <Anonymous dirname> directive, 586
- Anonymous FTP servers, 591
  - anonymous directory tree, 593–594
  - chroot jails, 631
  - security, 592–593
  - special needs, 591–592
- Anonymous FTP sites, 586, 591–592
- Anti-aliasing, 380
- Apache, 527, 530–531
  - binary files, 539
  - binding to ports, 537
  - CGI scripts, 547–548, 550
  - configuration files, 532–534
  - configuration options, 535–538
  - default number of clients, 536
  - directory options, 538–540
  - enabling SSL, 553–555
  - hostnames, 538
  - listening port, 537
  - loading modules, 540–541
  - log file format, 565–567
  - logs, 538
  - MIME type, 537
  - modules, 532
  - multiple instances of, 536
  - network interfaces, 537
  - platform information, 536
  - run as user and group, 535
  - SSL-enabled versions, 554
  - standalone configuration, 534–535
  - static Web pages, 12, 532, 539
  - super server configuration, 534–535
  - URL ending in directory name, 540
  - Web browsers supported by, 537
  - workstation for local use only, 537
- Apache Desktop Reference*, 527
- Apache Web site, 531, 551
- Apache-SSL project Web site, 550
- Apple LaserWriter drivers, 190
- AppleTalk, 13, 17
  - 32-bit machine address, 69
  - Apple's file-sharing protocols, 68
  - features and capabilities, 69–70
  - file and printer sharing, 69–70
  - file shares, 71
  - Linux software, 70–72
  - MacOS X, 70
  - names, 69
  - negotiating AppleTalk addresses, 69
  - network stack, 64
  - over Ethernet hardware, 69
  - print client, 71
  - print server, 70–71
  - security, 70
  - support, 15
  - two-tiered alphabetic naming system, 69
  - zones, 69
- AppleTalk Devices submenu, 17
- AppleTalk file server, 70
- AppleVolumes.default file, 70, 71

- AppleVolumes.system file, 70
- Application layer, 64
- Application server, 139
- Applications
  - Kerberized, 138, 141
  - multiple network stacks, 67
  - non-Kerberized, 141
- Applix Words, 563
- ApplixWare Office, 389
- apt-get program, 615
- ARCnet, 17
- ARP (Address Resolution Protocol), 40
- arp command, 127
- Articles, 286
- .asc file extensions, 533–534
- ASHE, 564
- atalkd program, 71
- atalkd.conf file, 71
- ATM (Adobe Type Manager), 378
- ATM (Asynchronous Transfer Mode), 14
- August, 564
- auth service, 164
- AuthClass directive, 233–234
- Authentication
  - client and server users, 217
  - FTP servers, 576
  - Kerberos, 158
  - localized, 135
  - network, 139
  - passwords, 328
  - POP servers, 269
  - RSA, 328
  - server identity file, 328
  - SSH, 327–333
  - ssh-agent, 331–333
  - SSL, 551
  - transparent system for X connections, 342–344
  - trusted-hosts, 328
- Authorization file, 161
- Automatic software update procedures, 615–616
- backslash (line continuation character), 293–294
- Backup clients, 413
- Backup DHCP servers, 115
- Backup KDC, 142
- Backup servers, 413
  - client-initiated backups, 414
  - client-initiated network configuration, 421–422
  - performing backup, 422–423
  - rshd daemon, 421–422
- Backup shares, 432–436
- Backups, 411
  - client-initiated, 414
  - full, 418
  - hardware options, 412
  - local, 419
  - partial, 418
  - policy, 413
  - restoring data, 445–447
  - scheduling, 437
  - server-initiated, 414–415
  - vncserver script, 366
  - Windows clients from Linux, 426–432
- Bandwidth and VPNs (Virtual Private Networks), 689–690
- Bash shell scripting language, 100–101
- Batch files, 200
- BDCs (backup domain controllers), 177
- BDF (Bitmap Distribution Format), 376
- bdfptpcf, 376
- BGP (Border Gateway Protocol), 657
- /bin directory, 594
- Binary newsgroups, 290
- BIND (Berkeley Internet Name Domain), 458, 459
  - caching-only name server, 471–472
  - communicating with DHCP servers, 473–475
  - configuration files, 459–461, 467
  - configuring, 459–465
  - configuring reverse DNS zone, 470–471
  - domain administration options, 465–471
  - forwarding server, 461–462
  - locating other name servers, 461
  - looking up addresses recursively, 472
  - lookups, 461–462
  - master zone options, 467–468
  - running in chroot jail, 635–638
  - SOA (start of authority) record, 467
  - specifying addresses and aliases, 468–470
  - Web site, 458
  - zone configuration file, 466–467
  - zones, 462–464
- BindAddress directive, 537
- bind-utils package, 474
- /bin/login program, 160, 320

## INDEX

- Bit Wizard Web site, 27
- Bitmapped font formats, 373–376
- Black and white printers, 373–374
- Blackhole lists, 489
  - Exim, 506
  - Postfix, 514
  - sendmail, 498–499
- Bluefish, 564
- Bluetooth, 21
- <BODY> tag, 560
- /boot directory, 28
- Boot loader
  - handling larger kernels, 26
  - modifying, 28–29
- boot.local script, 101
- Booting Linux, 29–30
- Broadband, 18–20
- Broadband Internet Connections: A User's Guide to DSL and Cable*, 19
- Broadband modems, 19–20
- Broadcasts
  - DHCP clients, 646
  - Directed subnet, 646
  - local subnet, 646
  - name resolution, 173
  - NetBIOS computers, 130
  - routing table, 41
  - unusual addresses, 120
- BrowseAddress directive, 234
- BrowseAllow directive, 234
- BrowseDeny directive, 234
- BrowseInterval directive, 234
- BrowseOrder directive, 234
- BrowsePoll directive, 234
- BrowsePort directive, 234
- BrowseTimeout directive, 234
- Browsing directive, 234
- BRU, 419
- BSD FTPD, 578–579
- BSD LPD, 224, 226
  - /etc/printcap file, 227–228
- BSD LPD servers, configuring, 226–228
- BSD (Berkeley Software Distribution) UNIX, 206, 221
- Bugs, 613
- Bugtraq mailing list, 626
- Building Linux OpenBSD Firewalls*, 661
- Built-in drivers, 24–25
- Burning CDs
  - postexec script, 197–199
  - preexec script, 197–199
  - pseudo-printer, 199–200
  - scripts, 197–200
  - Windows, 198–199
- bzip2, 419
- CA (certificate authority), 551
- Cable modems, 19–20, 134
- Caching-only name server, 471–472
- Caldera COAS (Caldera Open Administration System), 50
- Caldera OpenLinux Server 3.1, 35
- Caldera Systems Web site, 73
- Card Services, 22
- Case-sensitive filenames, 180
- Catalogue keyword, 385
- CBQ (Class-Based-Queueing) method, 650
- [cd-create] share, 198
- CDDI (Copper Distributed Data Interface), 18
- CD-R (CD Recordable) drive, 412
- cdrecord command, 198–199
- CD-RW (CD Rewriteable) drives, 412
- Center for Parallel Computers, 143
- <CENTER> tag, 561
- Cerberus, 135
- CERT/CC mailing list, 625
- CERT/CC (Computer Emergency Response Team Coordination Center) Web site, 624
- CGI (Common Gateway Interface), 546
- CGI scripts, 546
  - Apache, 547–548, 550
  - MIME type, 548–549
  - permissions, 548
  - security, 549–550
  - setting options, 547–548
  - writing, 548–549
- CGI-enabled Web servers, 549–550
- CGI::Lite scripting libraries, 550
- CGI.pm scripting libraries, 550
- chage command, 609
- Chains, 661–662, 671
- CHAP (Challenge Handshake Authentication Protocol), 55, 59
- chat utility, 58–59
- chkconfig command, 84–86, 104
- chksession, 353
- chroot jails, 592
  - anonymous FTP servers, 631
  - basics, 627–630

- configuring servers to operate in, 633–638
- controlling local access to environment, 634–635
- copying system files, 631–633
  - environment, 584
  - file availability, 639
  - files required to exist in, 628
  - hard links, 631
  - intrusions, 629
  - log files, 633
  - log rotation, 639
  - maintaining environment, 638–639
  - necessary environment files, 630–633
  - new support files, 639
  - ownership, 634–635
  - preparing directory tree, 630
  - program updates, 639
  - programs outside of, 629
  - root privileges, 629
  - running BIND in, 635–638
  - separating servers in, 628–629
  - server problems with, 629
  - servers residing in, 628
  - upgrades and, 629
- chroot program, 628, 631
- chroot() command, 592, 631
- CIAC mailing list, 626
- CIAC (Computer Incident Advisory Capability) Web site, 624
- CIDR (Classless Inter-Domain Routing), 39
- CIFS (Common Internet Filesystem), 14, 167, 425–426
- Classes
  - defining for networks, 651–652
  - IP addresses, 39
- Cleanfeed, 289
- Clartext, 171, 267
- Client for Microsoft Networks Properties
  - dialog box, 178
- Client programs and X, 338
- Client-initiated backups, 414
  - tar, 421–423
- Clients
  - ad-hoc method of obtaining hostname, 132–133
  - attempting to interpret character or block special devices on export, 214
  - broadcast name resolution, 130
  - connected to export, 209
  - dynamic IP addresses, 128
  - fixed IP addresses, 128
  - locating MAC address from, 124–126
  - verifying server identity, 139
  - WINS server, 130
- Client-side mapping daemon, 219
- Client-specific parameters, customizing, 128–129
- Clocks, internal, 251
- CML2, 5
- CNAME (canonical name) records, 469
- COAS (Caldera Open Administration System), 33, 50
- Coaxial cabling, 16
- Colocation, 530
- Color printers, 374
- Command not found error, 636
- Compiler errors, 27
- Compile-time kernel options, 4–6
- Compiling kernel, 23–28
- comp.os.linux.misc newsgroup, 27
- comp.os.linux.security newsgroup, 626
- Compression and SSH, 346–347
- Compromised passwords, 408
- comp.security newsgroups, 626
- CompuArt Web site, 73
- config file, 301–303, 401
- Config>Networking>Misc>Linuxconf
  - Network Access Options
    - command, 395
- Configuration, 5
- Configuration files
  - editing, 49–51
  - environment variables, 51
- Configuration scripts
  - adjusting for PPP, 56–60
  - setting PPP authentication options, 56–57
- configure script, 144
- Connection State Match Support, 8–9
- Connectiva Web site, 615
- Console logins and /etc/issue file, 318
- Control > Control Panel > Control Service
  - Activity module, 103
- Cookies, 546
- Copper wiring, 18
- Copying
  - kernel to /boot, 28
  - modules to appropriate place, 26
- Courier, 268, 480
- Courier IMAP, 269, 270
- Courier server Web site, 268

## INDEX

- CPAN Web site, 550
- Crack, 612
- Crackers, 605, 611
- create-cd script, 198
- Cron jobs, 298
  - automatically rotating log files, 567
  - scheduling Fetchmail runs, 273
- Crontab files, 298
- Cross posting, 286
- Cross-distribution configuration tool, 392–393
- CSZ (Clark-Shenker-Zhang) algorithm, 647
- ctlindd utility, 298
- CUPS (Common UNIX Printing System), 186, 225, 232–233
  - accepting jobs from BSD LPD or LPRng clients, 236–237
  - adding printers, 237–238
  - clients, 237–239
  - configuring, 232–239
  - /etc/cups/cupsd.conf file, 233–236
  - IPP (Internet Printing Protocol), 223
  - Web site, 233
- cupsd.conf file, 233–235
- cups-lpd program, 236–237
- Customizing client-specific parameters, 128–129
- CustomLog directive, 538, 565
- Cyrus IMAP, 268, 269, 270
- Cyrus IMAP Web site, 268
  
- Daemon mode, 101
- Daemons, 80
- DAT (Digital Audio Tape), 412
- Data, 66–67
- DATA command, 483, 484
- Data files, packaging in carrier, 196
- DAVE, 71
- .db filename extensions, 508
- db.cache file, 461
- Debian GNU/Linux 2.2, 35, 81, 500
- Debian Web site, 61
- Debugging
  - PPP (Point-to-Point Protocol), 59–60
  - Telnet, 317
- Decenders, 375
- Declarations, 117–118
- DECnet support, 15
- Dedicated print server, 224
  
- Default
  - domain, 47
  - kernel, 29
  - route, 41–42, 44
- \$DEFAULT environment variable, 517
- \$defaultXStartup variable, 365
- default keyword, 44
- Defaulttype directive, 537
- Delivering recipes, 517
- Deny directive, 234
- \$depth variable, 365
- /dev export, 208
- Development kernels, 4, 27
- devfs, 53
- Device files, 632
- dgram (datagram) socket types, 90
- dhclient DHCP client, 33
- DHCP (Dynamic Host Configuration Protocol), 31
  - dynamic DNS features, 134
  - incompatible DHCP clients, 33–34
  - incompatible DHCP options, 34
  - multi-NIC configurations, 34
  - socket filtering, 8
- DHCP clients, 114, 115
  - alternative packages, 34–35
  - broadcasts, 646
  - customizing client-specific parameters, 128–129
  - default package, 34–35
  - Ethernet addresses, 117
  - fixed IP addresses, 123
  - global parameters passed to, 120–121
  - incompatible, 33–34
  - isolated on separate physical or logical subnets, 128
  - leases, 117
  - locating MAC addresses, 123–127
  - MAC (media access control) address, 117
  - responses from DHCP server, 116
  - as server for other protocols, 114
  - startup scripts, 35–36
- The DHCP Handbook: Understanding, Deploying, and Managing Automated Configuration Services*, 114
- DHCP leases file, 126
- DHCP servers, 33, 113
  - assigning dynamic IP addresses, 118–122
  - backup, 115

- as boot server, 120
- communicating with, 473–475
- communicating with DNS server, 131–134
- configuration files, 116–118
- configuring, 115
- dhcpd.conf file, 117–118
- dhcp.leases file, 117
- explicit route to routing table, 116
- importance of, 115
- including NetBIOS information, 129–131
- integrating with other protocols, 129–134
- interim update method, 133
- IP addresses, 114
- ISC (Internet Software Consortium), 116–117
- kernel and network interface issues, 116
- length of lease time, 119–120
- locating MAC address from, 126–127
- multiple, 121
- name of computer which has boot file, 120
- non-Linux DHCP options, 115–116
- setting client hostname on client, 121
- static IP address, 33, 115
- SysV scripts, 116
- when to run, 114–116
- dhcpd client, 33
- dhcpd
  - ad-hoc update method, 132–133
  - interim update method, 132
  - issuing IP addresses, 120
  - leases, 117
  - MAC address to assign specific IP address, 124
  - methods of DNS updates, 131–134
  - most recent log entry, 126
  - passing hostname as set in host declaration, 121
- dhcpd.conf file
  - assigning dynamic IP addresses, 119–121
  - comments, 117
  - declarations, 117–118
  - global options, 119–121
  - NetBIOS parameters, 129–130
  - parameters, 117–118
  - statements, 117
  - subnet declarations, 121–122
- dhcp.leases file, 117
- dhcpxd DHCP client, 33
- diald program, 60–62
- diald Web site, 61
- DIALER\_SCRIPT variable, 58
- Dialing scripts
  - configuring, 57–59
  - usage, 59–60
- Dial-on-demand
  - configuring, 60–62
  - utilities, 23
- Dial-up devices, 15–16, 22–23
- Dial-up Linux systems, 271
- Diamond 1MM DSL modem, 20
- Differentiated Services, 11
- Differentiated Services on Linux Web site, 11–12
- dig program, 461
- Digital video recorders, 641
- Direct addressing, 481
- Directed subnet broadcasts, 646
- Directives, 233–235
- <Directory dirname> directive, 586
- DirectoryIndex directive, 540
- Disabling servers, 606
- disklist file, 442–444
- DISPLAY environment variable, 345, 346, 347, 349
- DISPLAYMANAGER environment variable, 355
- Displays, 375
- Distance vector algorithms, 655
- Distributions
  - AMANDA, 436
  - default ntp.conf file, 247
  - default XDMCP server, 354–355
  - DHCP client information, 35
  - fetchmailconf file, 273
  - font servers, 373
  - fonts, 381
  - Kerberos support, 143
  - Linuxconf, 393
  - LPRng, 231
  - names and numbers of startup and shutdown links, 82
  - package management systems, 600–601
  - PAM (Pluggable Authentication Module), 311
  - printing systems, 225
  - sendmail, 491–492
  - SMTP servers, 479
  - startup scripts, 80–81
  - super servers, 109

## INDEX

- Distributions (*continued*)
  - VNC server and client, 361
  - Web sites for, 614, 624
  - Webmin, 393, 399
- djbdns, 458–459
- djbdns Web page, 458
- DLLs (dynamic linked libraries)
  - and servers, 632
- dlocate program, 617
- DLT (Digital Linear Tape), 412
- DNS (Domain Name System)
  - configuring, 46–48, 459–465
  - dynamic DNS features, 134
  - dynamic services, 36, 134
  - dynamic updates, 132
  - hostnames, 466
  - MX (mail exchanger) records, 481–482
  - unreliability, 94
- DNS and BIND, 4th Edition*, 452
- DNS servers, 47, 451–452
  - caching lookup results, 454
  - CNAME entry, 146
  - communicating with DHCP servers, 131–134, 473–475
  - externally-accessible, 452–455
  - KDC hostnames, 146
  - list of root name servers, 461
  - local, 455–456
  - options for Linux, 458–459
  - starting and testing, 474–475
  - updating, 473
  - when to run, 452–456
- dnscache, 459
- dnsutils package, 636
- Document files, 545
- DocumentRoot directive, 539
- Domain addressing, 481
- Domain controllers, 175–178
- domain keyword, 47
- Domain master browsers, 175–176
- Domain name registrar, 454, 457
- Domain names, 457–458
- Domains, 170
  - administration options, 465–471
  - default, 47
  - encrypted passwords, 177
  - identically named computers, 47
  - NetBEUI, 75
  - NetBIOS, 176
  - number of DNS servers, 454
  - searching, 47
- DOS
  - attribute bits, 182–183
  - case-insensitive filenames, 180
  - FDISK, 446
  - filename requirements, 180–181
  - Samba, 168
- DoS (denial-of-service) attacks, 98, 645
- Dot files, hidden bit, 183
- dpi (dots per inch), 375
- dpkg, 206
- Drivers, 27
- DSL (Digital Subscriber Line), 19, 134
- DUL (Dial-Up List) Web site, 490
- dump, 442
- Dynamic Content with CGI Web page, 548
- Dynamic DNS services, 36, 134, 455
- Dynamic IP addresses
  - defining subnet range, 121–122
  - DHCP servers, 118–122
  - dhcpcd.conf file, 119–121
  - length of lease time, 119–120
  - temporary, 124
- Dynamic newsgroup configuration, 299–300
- Dynamic Web pages, 12
- eBay Web site, 20
- eBones, 143
- eBones Web site, 143
- e-commerce sites, 545
- Econet, 15
- Editing
  - configuration files, 49–51
  - /etc/inetd.conf file, 91–92
- EHLO command, 483, 507
- EISA (Extended ISA) cards, 16
- E-mail
  - aliases, 494
  - AUP (acceptable use policy), 491
  - difficulty in determining sender, 264
  - envelope headers, 482
  - GUI programs, 258
  - message headers, 482, 483
  - multiple recipients, 284
  - one mailbox, multiple users, 271
  - pull mail protocols, 251–258
  - push mail protocols, 251
  - retrieving, 261



- scheduling mail retrieval, 272
- sending, 261
- spam, 488–491
  - text of message, 483
- E-mail readers, 258–259
- E-mail system relay, 259–260
- Emergency restore system, 446
- Encrypted passwords, 171–172, 177, 610–611
- Encryption
  - FTP servers, 576
  - Kerberized clients, 159
  - security, 346
  - SSH, 346
  - SSL, 551
- Envelope headers, 482
- Environment variables, 51, 517
- EPS (Encapsulated PostScript) files, 192
- ESP Print Pro, 232–233
- /etc directory, 143, 594
- /etc directory tree, 350
- /etc export, 208
- /etc/aliases file, 500, 501
- /etc/apache file, 554
- /etc/apache-ssl file, 554
- /etc/cups/classes.conf file, 233
- /etc/cups/cupsd.conf file, 233–236
- /etc/cups/printers.conf file, 233
- /etc/diald.conf file, 61
- /etc/email-addresses file, 501, 502
- /etc/exports file, 208–210, 212
- /etc/fstab file, 213
- /etc/ftpaccess file, 594–595
- /etc/gateways file, 656
- /etc/group file, 215
- /etc/hosts file, 48, 49, 456
- /etc/hosts.allow file, 92, 94, 207
- /etc/hosts.deny file, 92
- /etc/hosts.equiv file, 227, 313, 315
- /etc/hosts.lpd file, 226–227
- /etc/inetd.conf file
  - editing, 91–92
  - examining for unnecessary servers, 601–602
  - fields, 90–92
  - FTP servers, 580
  - modifying, 152
  - rlogind, 311
- /etc/inittab file, 87–89, 354
- /etc/ipsec.conf file, 705–709
- /etc/ipsec.secrets file, 704–705
- /etc/issue file, 318, 319
- /etc/issue.net, 318–319
- /etc/krb5.conf file, 144–145
- /etc/krb5.keytab file, 154
- /etc/leafnode/config file, 306
- /etc/leafnode/filters file, 306
- /etc/lilo.conf file, 29
- /etc/lpd.perms file, 229–232
- /etc/mail/local-host names file, 495
- /etc/modules.conf file, 32
- /etc/named.conf file, 461, 464
- /etc/nets/nnrp.access file, 296–297
- /etc/network/interfaces configuration file, 34–35
- /etc/news/expire/ctl file, 297–298
- /etc/nwsvr.conf file, 73
- /etc/nwsvr/nwsvr.conf file, 73
- /etc/pan.d configuration files, 163–166
- /etc/passwd file, 215–216
- /etc/ppp/chap-secrets file, 56, 61
- /etc/ppp/diald-dialer file, 61
- /etc/ppp/pap-secrets file, 56–57, 61
- /etc/printcap file, 190, 227–229, 232
- /etc/procmailrc file, 517
- /etc/rc.config file, 82, 105
- /etc/rc.d/boot.local script, 32, 51
- /etc/rc.d/rc.4 script, 81, 355
- /etc/rc.d/rc.gui script, 355
- /etc/rc.d/rc.local script, 32, 51, 319
- /etc/resolv.conf file, 47–48, 61
- /etc/sendmail.cw file, 495
- /etc/services file, 93, 152, 405
- /etc/shadow file, 610
- /etc/ssh/ssh\_config, 346
- /etc/ssh/sshd\_config file, 324, 331, 346
- /etc/sysconfig/desktop file, 355
- /etc/tripwire/tw.config file, 618–619
- /etc/webmin/start script, 401
- /etc/X11 file, 350
- /etc/X11/fs/config file, 383
- /etc/X11/gdm/Sessions directory, 354
- /etc/X11/xdm/Xaccess file, 350–351
- /etc/X11/xdm/xdm-config file, 350
- /etc/X11/xdm/Xservers file, 351, 357
- /etc/X11/Xsession script, 367
- /etc/XF86Config file, 383
- /etc/xinetd.conf file
  - examining for unnecessary servers, 601–602
  - xinetd, 96

## INDEX

- /etc/xinetd.d directory, 96
  - FTP servers, 580
  - rlogind, 311
  - SWAT, 404
- Ethernet, 18
  - cabling, 16
  - devices, 16–17
  - MAC addresses, 123
  - NetBEUI, 75
  - speeds, 16
- Ethernet cards, 16, 23, 123
- Ethernet-interfaced modem, 20
- EtherTalk, 69
- Eudora Web site, 268
- Exceed for Windows, 340
- EXCEPT operator, 95
- Exim, 479–480, 499
  - address masquerading, 501–502
  - anti-spam configuration, 504–507
  - blackhole lists, 506
  - calling Procmal, 525
  - configuration files, 500–501
  - configuring to accept mail, 502–503
  - configuring to relay mail, 503–504
  - filter.txt.gz documentation file, 505
  - filtering options, 504–505
  - mbox, 267
  - relay configuration, 503–504
  - sending through relay, 504
  - Web sites, 480, 502
- exim.conf file, 500–501, 525
- eximconfig script, 500, 502–503
- Exim: The Mail Transfer Agent*, 478
- Expanded font servers, 388–390
- Exports
  - IP addresses, 209
  - lax permissions, 214
  - no\_root\_squash option, 424
  - preventing superuser access, 214
  - unable to run programs from, 214
- External font servers, 384
- External scanner programs, 604–605
- Externally-accessible DNS servers, 452–455
  
- Fallback, 21
- Fast NAT, 644
- FAT (File Allocation Table) filesystem, 430
- Fax software, 196
- FDDI (Fiber Distributed Data Interface), 18
  
- FDISK, 446
- Fenrus Web site, 542
- Fetchmail
  - batch mode, 273
  - challenge/response password authentication, 273
  - as client, 272–273
  - configuring, 273–278
  - configuring and running as ordinary user, 274
  - daemon mode, 273, 279, 280–281
  - .fetchmailrc file, 278–282
  - forwarding mail, 270
  - global options, 279–280
  - logging activities, 279–280
  - multidrop mode, 282
  - network interface that must be up, 280
  - passwords, 281
  - place in mail delivery systems, 270–273
  - pull mail protocol to be used, 280
  - retaining messages, 281
  - retrieving all messages, 281
  - scheduling e-mail retrieval, 272
  - sending error messages to mail's sender, 279
  - server options, 280–281
  - storing mail retrieval password in cleartext, 277
  - testing setup, 277–278
  - use of another server, 281
  - user options, 281
  - username, 279, 281
- Fetchmail Configurator dialog box, 274
- Fetchmail Expert Configurator dialog box, 274–275, 277, 279
- Fetchmail Host Hostname dialog box, 275–276, 279
- Fetchmail Launcher window, 273
- Fetchmail User Username Querying Hostname dialog box, 276–277, 279
- .fetchmailconf file, 270, 273
- .fetchmailrc file, 277, 278–282
- fetchnews, 299
  - arguments, 304
  - as Cron job, 305
  - as part of PPP connect script, 305
  - time interval, 302
- Fiber-optic cabling, 16, 18
- Fibre Channel, 18
- File ➤ Act/Changes, 103

- File servers, Samba as, 179–184
- File shares
  - accessing, 181–182
  - creation of, 179–180
  - limiting access to, 184
  - NFS server, 222
  - overriding read-only or read/write settings, 184
  - passwords, 182
- File sharing, 168
- Filenames, 180–181
- Files
  - configuring ownership and permissions, 181–183
  - group associations, 182
  - overwriting existing, 588
  - sharing, 12–13
- Filesystems
  - ACLs (Access Control Lists), 148
  - backup shares, 434
  - root directory, 24
- Filters, 8
  - filter.txt.gz documentation file, 505
- Firewalls, 8–9, 93, 345–346
  - ACCEPT policy, 670
  - blocking NFS servers, 210
  - between client and server, 339
  - configuring with iptables, 667–677
  - default policy, 669–670
  - defining, 667–669
  - DROP policy, 670
  - filtering by interface, 673–674
  - FORWARD chain, 669
  - INPUT chain, 669
  - ipfwadm-based script, 9
  - logging activity, 684
  - older scripts, 9
  - opening and closing specific ports, 671–672
  - OUTPUT chain, 669
  - Packet filter firewall script, 675–677
  - packet-filter, 667–668
  - proxy server, 667
  - QUEUE policy, 670
  - redirecting connection attempts, 668
  - RETURN policy, 670
  - rule creation, 670–677
  - source and destination IP addresses, 672–673
  - stateful inspection, 674–675
- Fixed IP addresses and DHCP clients, 123
- Font directories
  - adding fonts, 386–388
  - adding or deleting, 385–386
- Font formats
  - bitmapped, 373–376
  - outline, 376–379
- Font path, 372, 385–388
- Font servers, 339, 371–372
  - adjusting font availability, 385–388
  - adjusting for LANs, 382–385
  - changing font path, 385–388
  - configuration files, 382
  - default configurations, 381–382
  - distributions, 373
  - expanded, 388–390
  - external, 384
  - FontTastic, 389–390
  - local startup files, 382
  - network, 381–382
  - options for Linux, 379–381
  - ports, 382
  - restricting access to, 383
  - security, 382, 384–385
  - systems currently running X, 384
  - SysV startup scripts, 382
  - traditional, 379–388
  - TrueType-only, 380
  - when to run, 372–373
- Font smoothing, 380
- Fonts, 371–372, 377
  - adding to font directory, 386–388
  - availability, 385–388
  - copyrighted, 373
  - descenders, 375
  - distributions, 381
  - printers, 375
  - proportionally-spaced, 374–375
  - sizes, 375–376
  - storing on disk, 372
  - variable grid widths, 375
  - X, 372
  - XLFD (X Logical Font Descriptor), 386–387
- fonts.dir file, 386–388
- FontTastic, 389–390
- Footers, 66–67
- Forms, setting options, 547–548
- FORWARD chain, 669
- .forward files, 505
- Forward lookups, 132–133

## INDEX

- Forward zone, 464
- Forwarding, 653
- FQDN (Fully-Qualified Domain Name), 48, 132, 515
- Frames, 66
- Free SSH Web site, 323
- FreeDOS, 29
- FreeDOS Web site, 29
- FreeS/WAN, 691
  - configuring, 701–710
  - editing configuration files, 704–709
  - editing IPsec settings, 705–709
  - establishing router links, 709–710
  - /etc/ipsec.secrets file, 704–705
  - obtaining and installing, 702–704
  - RSA authentication, 706
  - setting default remote options, 706
  - setting up keys, 704–705
  - system-specific remote options, 706–709
  - Web site, 702
- From: message header, 485
- FTP (File Transfer Protocol), 68, 575, 578, 588
- ftp program, 158
- FTP servers
  - accounts, 576
  - anonymous access for remote users, 578
  - authenticated logins, 580
  - authentication, 576
  - chroot jail, 592
  - configuring, 579–589
  - connections, 576–577
  - cross-platform clients, 577
  - ease of configuration, 577
  - encryption, 576
  - /etc/inetd.conf file, 580
  - /etc/xinetd.d directory, 580
  - local access for local users, 578
  - no direct file editing, 577
  - options for Linux, 578–579
  - running, 580–581
  - two-way transfers, 577
  - when to run, 575–578
- FTP sites, anonymous, 586
- ftpaccess file, 581, 582–585
- ftpconversions file, 581
- ftphosts file, 581
- ftpservers file, 582
- ftpusers file, 582
- Full backups, 418
- Full restores, 445–446
- GateD, 657
- Gateways, 9–10
  - multiple with multiple interfaces, 45–46
  - one with multiple interfaces, 44–45
  - routing tables, 41, 43
- Gateways system, 40–41
- GCC (GNU C Compiler), 27
- GDM (GNOME Display Manager), 163, 350, 353–354
  - gdm program, 163
  - gdm.conf file, 353
- General Instruments Surfboard 1000, 20
- Geo Cities Web site, 134
- \$geometry variable, 365
- getty program, 160
- &GetXDisplayDefaults() function, 365
- gFTP, 324
- Ghostsript, 70, 189, 191–192, 379
- Ghostsript Web site, 189, 221
- GIDs (group IDs)
  - NFS, 212–213
  - synchronization, 216–217
- GIF (Graphics Interchange Format), 562
- Gigabit Ethernet, 16, 18
- Giganews, 285
- The GIMP, 335, 563
- <Global> directive, 586
- Global hostname setting, 48
- GMP (GNU Multi-Precision) library, 702
- GMT (Greenwich Mean Time), 245
- GNOME (GNU Network Object Model Environment), 52, 102
- GNOME PPP, 52
- GNOME RPM, 601
- gnome-linux-conf package, 102
- GNU Zebra, 657–659
- Google Web site, 59
- GPS (Global Positioning System) receivers, 243
- Granite Canyon Web site, 454
- Graphics
  - compression levels, 562–563
  - files, 544–545
  - modifying files, 194
  - Web pages, 561, 562–563
- groupadd command, 178
- groupmod command, 216
- Groups, 295
- GRUB (Grand Unified Boot Loader), 29
- GTK+ library, 340
- GUI (graphical user interface), 335

- GUI access servers, 336–337
  - comparison, 369–370
  - VNC servers, 358
  - X, 337–348
  - XDMCP servers, 348–357
- GUI configuration tools, 50–51
- GUI dialers, 52–56, 57, 60
- GUI servers, 335
- GUI Seyon, 53
- GUI tools, 101–102, 335
  - GNOME (GNU Network Object Model Environment) desktop, 102
  - KDE (K Desktop Environment), 102
  - ksysv, 106–108
  - launching, 102
  - Linuxconf, 102–104
  - tksysv, 106–108
  - YaST (Yet Another Setup Tool), 104–106
  - YaST2, 104–106
- A Guide to Dynamic TCP/IP Network Configuration*, 114
- gzip, 419
- %H variable, 196
- <H1> tag, 560–561
- Hackers, 605
- Hacking Exposed, 3rd Edition*, 600
- Hardware
  - alternative local network devices, 17–18
  - associated with PPP connection, 54
  - backups, 412
  - Broadband and WAN devices, 18–20
  - dial-up devices, 15–16, 22–23
  - Ethernet devices, 16–17
  - frame type, 72
  - identifying, 123–127
  - Interphase 5526 Tachyon, 18
  - KDC requirements, 142
  - LocalTalk, 17
  - MAC addresses, 123–127
  - options, 15–23
  - PC Card devices, 15, 17, 21–22
  - problems and kernel, 27
  - Token Ring cards, 17
  - USB devices, 17
  - wireless devices, 20–21
- Hash algorithm, 610
- <HEAD> tag, 560
- Headers, 66–67
- Heimdal, 143
- HELO command, 483, 484, 507
- Hewlett Packard Web site, 340
- High-level protocol support, 12–14
- HighSynth Web site, 134
- Hint zone, 464
- Hints, 377
- HIPPI (High-Performance Parallel Interface), 18
- Home directories, 556–557
- \$HOME environment variable, 517
- [homes] share, 179–180, 407
- host command, 636
- host declaration, 127–129
- host keyword, 118, 127
- Host utility, 474
- hostname command, 48, 49, 51, 485
- HostnameLockups directive, 235, 538
- Hostnames
  - Apache, 538
  - DNS, 466
  - FQDNs (Fully-Qualified Domain Names), 48, 466
  - global setting, 48
  - mapping to IP addresses, 36
  - matching IP addresses, 120–121
  - nicknames for, 48
  - setting, 48–49
  - URLs, 538
  - without associated domain, 466
- hostname-specific home directories, 556–557
- Hosts, defining with MAC addresses, 127–128
- .htaccess files, 547–548
- .htm file extension, 544
- HTML (Hypertext Markup Language), 544
- HTML file, 544
- .html file extension, 544
- <HTML> tag, 560
- HTML text file, 559–561
- HTTP (Hypertext Transfer Protocol), 68, 528
  - acceleration, 12
  - ports, 89
- HTTP clients, 528
- HTTP servers, 207, 528
- httpd.conf file, 532–533
- HTTPS (secure HTTP), 551
- Hybrid of trusted-hosts with Rivest/Shamir/Adleman (RSA) authentication, 328

## INDEX

- ICANN Web site, 457
- icewm, 366
- ifconfig utility, 36–38, 40, 44, 51, 124
- ifup tool, 34
- images, converting into bitmap, 191
- IMAP (Internet Message Access Protocol), 259
  - cleartext, 267
  - client to submit numbered commands, 266
  - converting POP to, 271
  - examining headers before retrieving messages, 264
  - message bodies, 262
  - message headers, 262
  - versus* POP, 266–267
  - retaining original e-mail, 262
  - sample session, 264–266
  - secure variants, 267
  - security, 267
  - use of folders, 266
- imap package, 269, 270
- IMAP servers
  - configuring, 269–270
  - installing, 270
  - large hard drives on, 261
  - Linux, 269–270
  - requiring more disk space, 267
- <IMG> tag, 561
- Inactive accounts, 608–609
- incoming.conf file, 295–296
- inetd server
  - starting servers, 89–96, 96–100
- inetd.conf file, 303
- init process, restarting, 89
- INN (InterNetNews), 288
  - active file, 292–293
  - computer name, 291
  - configuring, 290–298
  - contact information, 291
  - as daemon, 298
  - domain name, 291
  - /etc/nets/nnrp.access file, 296–297
  - /etc/news/expire/ctl file, 297–298
  - /etc/news/inn.conf file, 290–292
  - feeding news to other sites, 293–295
  - From header, 291
  - incoming.conf file, 295–296
  - local post number, 292
  - message expiration options, 297–298
  - method of contacting other sites, 294–295
  - news feeds file, 293–295
  - news reader access, 296–297
  - newsgroups file, 293
  - server's fully-qualified domain name, 291
  - setting up newsgroups, 292–293
  - Sys V startup scripts, 298
- inn package, 289
- innd program, 288, 295
- innxmit program, 288
- INPUT chain, 661, 669
- insmod command, 32
- Instance, 139
- Interfaces, filtering packets by, 673–674
- Internal security tool, 136
- Internet
  - broadcasts, 646
  - DNS servers, 452
  - IPv4 addresses, 10
  - multicasts, 646–647
  - point-to-point traffic, 646
- Internet Explorer, 564, 565
- Internet Software Consortium Web site, 116
- Internetworking IPX/SPX, 72–73
- Interphase 5526 Tachyon, 18
- Intrusion-detection tools, 616–621
- Intrusions
  - backing up vital data, 623
  - chroot jails, 629
  - disconnecting computer from network, 622
  - general detection procedures, 621–622
  - modifying files and, 616–617
  - monitoring for attempts, 616–623
  - monitoring log files, 621
  - monitoring system health, 621
  - package databases, 617–618
  - restoring clean system, 623
  - restoring data files, 623
  - strange files and, 621
  - tracing back to Web site, 623
  - Tripwire, 617–621
  - unusual network traffic, 621–622
  - user complaints, 621
  - verifying nature of compromise, 622–623
- IP addresses, 8
  - assigning to network interfaces, 36
  - as basis for blocking e-mail, 489
  - classes, 39
  - converting alphanumeric names to, 46–48
  - DHCP servers, 114

- exports, 209
- hostnames matching, 120–121
- mapping hostnames to, 36
- multicasts, 39
- portmapper, 207
- private, 39
- source and destination, 672–673
- static, 114
- TLDs (top-level domains), 452
- ip command, 648–649
- IP forwarding, 44
- IP masquerading, 8–9, 679
  - See also Network Address Translation
- ip route command, 649
- ip utility, 11
- ipchains utility, 9, 664
- IPCONFIG program, 124
- ipfwadm utility, 9, 664, 666
- IPP (Internet Printing Protocol), 223, 232
- iproute2 package, 644
  - ip utility, 648–649
  - tc utility, 649–653
- iproute2 utility + tc Notes utility, 11
- ip\_tables module, 666
- iptables utility, 8–9, 97
  - checking configuration, 666–667
  - configuring firewalls, 667–677
  - configuring NAT, 677–682
  - description of, 661–662
  - forwarding ports, 682–684
  - ip\_tables module, 666
  - kernel configuration for, 664–666
  - logging activity, 684–686
  - packet filter firewall script, 675–677
  - rule creation for firewalls, 670–677
  - setting firewall default policy, 669–670
- IPv4, 10
- IPv6, 10
- IPX (Internetwork Packet Exchange), 14–15, 72
- IPX routers, 72
- ipx\_configure command, 74
- IPX/SPX, 13–14, 72–74
- IPX/SPX servers, 73
- ipxutils package, 74
- ISA (Industry Standard Architecture) bus
  - cards, 16
- ISPs (Internet Service Providers), 454
  - broadband technologies, 19
  - news feeds, 289
  - Usenet news servers, 284
  - username, 57
- JPEG (Joint Photographic Experts Group)
  - format, 562
- .k5login file, 160, 161
- .k5users file, 160, 161
- kadmin man page, 150
- kadmin program, 150, 152, 154
- kadmin/admin principal, 151
- kadmin/changepw principal, 151
- kadmin.local program, 150, 154
- kdb5\_util command, 147, 152
- KDC, 142, 143
  - configuring, 143–144
  - hardware requirements, 142
  - kdc.conf configuration file, 145
  - Kerberos package, 144
  - listing, 152
  - port number, 145–146
  - principals, 151
  - session key, 141
  - starting, 151–152
- kdc.conf file, 152
  - acl\_file entry, 148
  - admin\_keytab entry, 151
  - [kdcdefaults] section, 146
  - modifying, 146–147
  - [realms] section, 146
  - realm-specific entries, 145
- KDE (K Desktop Environment), 52, 102
- kdestroy program, 156–157
- KDM, 352–353
- kdmrc file, 352
- Kerberized applications, 141
- Kerberized clients, 155, 157–159
- Kerberized networks, 143
- Kerberized servers, 154–155
- Kerberos, 135, 136, 217, 337
  - ACLs (Access Control Lists), 148
  - administering realms, 148–151
  - administrating user database, 150
  - AMANDA, 442
  - application server, 139
  - basic principles, 138–141
  - configuring, 153–154
  - configuring slave KDCs, 152–153
  - creation of principals, 150–151

## INDEX

- Kerberos, (*continued*)
  - cross-platform compatibility, 136–137
  - design goals, 139–141
  - domain name associated with
    - principals, 146
  - explicit support, 137
  - instance, 139
  - license, 142
  - master key, 147–148
  - network authentication, 139
  - network utilities, 155–157
  - operation, 138–143
  - PAM (Pluggable Authentication Module), 161–166
  - primary, 139
  - principals, 139, 155
  - protecting passwords, 139
  - realm, 138, 139
  - setting up realms, 145–147
  - single-login operation, 139–140
  - starting KDC, 151–152
  - stash file, 147–148
  - SysV startup scripts, 152
  - text-mode login authentication, 160
  - TGS (ticket-granting service), 140
  - TGT (ticket-granting ticket), 140
  - tickets, 138, 140–141
  - user logins, 159–166
  - user programs, 159
  - versions and variants, 142–143
- Kerberos application servers, 145
  - configuring, 143, 153–155
  - configuring Kerberos, 153–154
  - installing, 144
  - keytab files, 153–154
- Kerberos clients, 138–139, 145
  - configuring, 143, 155–166
  - installing, 144
- Kerberos for Windows, 137
- Kerberos networks, 138–139, 141
- Kerberos password server, 138
- Kerberos servers, 138, 139
  - accessing, 155–159
  - installing, 144
  - KDC, 142
  - modifying configuration files, 144–145
  - requirements, 142
  - setting up, 143–144
  - when to run, 136–137
- Kerberos Web site, 136
- Kernel, 3
  - advanced router options, 643–647
  - buggy or incompatible code, 27
  - building main file, 26
  - built-in drivers, 24–25
  - common compilation problems, 26–28
  - compiler errors, 27
  - compile-time options, 4–6
  - compiling, 23–28
  - compiling modules, 26
  - compressed, 26
  - configuration for iptables, 664–666
  - default, 29
  - development, 4
  - DHCP server issues, 116
  - differentiating traffic, 652
  - features compiled into, 24
  - hardware problems, 27
  - HTTP server, 12
  - installing, 23–30
  - modules, 24–26
  - network options, 5
  - NFS File System Support option, 205
  - NFS Server Support option, 205
  - obtaining patches, 696
  - old object files, 27
  - options, 5
  - Packet Socket option, 116
  - PC Card devices, 22
  - policy routing, 643–644
  - prepatched, 694–695
  - processes, 603
  - reading rules in chains, 671
  - release, 4
  - Socket Filtering option, 116
  - stable, 4
  - symbolic link to, 4–5
  - too large to boot, 25
  - tracking network connections, 8
  - typical configuration, 25–26
  - uncompressed, 26
  - unfulfilled dependencies, 27
  - usage, 28–30
  - version number, 4
  - Web site, 4, 76
- Kernel space processes, 541–541
- Kernel-based Web servers, 531
- Kernel-mode NFS servers, 205
- Keytab, 150–151
- Key/value pair, 295



- kHTTPd, 532, 541–544
- kill command, 101, 354
- killall command, 101, 354
- Killing processes, 88
- kinit program, 156–157, 159
- KLIPS (Kernel IP Security) kernel features, 705
- klist program, 156–157
- klogind server, 152
- KMail, 258
- knfsd server, 205
- kpasswd program, 156–157
- KPPP dialer, 52–56
  - configuration dialog box, 53–55
  - configuring, 53–55
  - Show Log Window button, 56
  - starting, 53
- kproxd server, 152
- kpropd.acl file, 152
- krb5.conf file, 144–145, 152
  - [domain\_realm] section, 145–146, 153
  - multiple realms, 146
  - [realms] section, 145–146, 153
  - realm-specific entries, 145
- krb5kdc program, 152
- krb5-libs package, 144
- krb5-server package, 144
- krb5-workstation package, 144
- ksu package, 159, 160–161
- ksysv, 106–108
- ktadd command, 150–152, 154
- KUPS, 232
  
- LANA Web site, 457
- LANs (local area networks)
  - adjusting font server for, 382–385
  - dial-up accounts, 271
- last command, 609
- Leafnode program, 285–286, 299
  - access-control features, 304
  - anti-spam measure, 302
  - capabilities, 299–301
  - config file, 301–303
  - configuring, 301–306
  - delayed message appearance, 305
  - dropping messages, 300–301
  - expiring old news, 305–306
  - fetching news, 304–305
  - fetchnews program, 304–305
  - filtering articles, 306
  - general configuration settings, 301–303
  - ignoring old messages, 302
  - inetd.conf, 303
  - leafnode server program, 303–304
  - limiting number of new articles fetched, 302
  - message IDs, 303
  - newsgroup descriptions file, 302
  - as ordinary news reader, 300
  - passwords, 301
  - refreshing list of available newsgroups, 303
  - rejecting messages, 303
  - resources, 300
  - setting up server, 303–304
  - small sites, 300
  - texpire program, 305–306
  - versions, 300
  - Web site, 299
- Leap second, 245
- Leased lines, 20
- Leases, DHCP, 117, 119–120
- /lib directory, 594
- /lib/modules directory, 26
- LILO (Linux Loader), 28–29, 32
- <Limit command-group> directive, 586–587
- Limited administrative servers, 410
- Link state algorithms, 655–656
- Link-local multicasts, 646
- Links, 561
- Linux Kernel HOWTO, 24
- Linux Apache Server Administration*, 527
- Linux computers as dedicated X terminal, 358
- Linux DNS Server Administration*, 452
- Linux Firewalls*, 600
- Linux Firewalls, 2nd Edition*, 661
- Linux IPv6, 10
- Linux Kernel HOWTO Web site, 4
- Linux Mandrake 8.1, 35
  - Postfix, 507–508
  - startup script locations, 81
- Linux Printing database and Web site, 189, 237
- Linux Routing*, 642
- Linux Samba Server Administration*, 168
- Linux Sendmail Administration*, 478
- Linux System Security: The Administrator's Guide to Open Source Security Tools*, 600
- Linux Tools Web site, 21
- Linux Weekly News Security Section Web site, 624
- Linuxconf, 33, 50, 391, 392, 410
  - configuration areas, 103
  - configuration modules, 103

## INDEX

- Linuxconf, (*continued*)
  - configuring, 394–397
  - configuring servers, 104
  - Control ► Control Panel ► Control Service
    - Activity module, 103
  - distributions, 393
  - GUI mode, 102, 394
  - hierarchical structure for configuration
    - modules, 399
  - Java-based GUI, 394
  - linuxconf=gui package, 102
  - port, 394
  - remotely running, 394–399
  - servers, 394–397
  - super server, 394
  - text mode, 102, 394
  - unencrypted passwords, 409
  - Web-based interface, 102, 397–399
  - Web site, 102
  - xinetd, 394–395
- LinWare, 73
- The List Web site, 53
- Listen directive, 235
- lld, 637
- lmhosts file name resolution, 172
- Loading network drivers, 31–33
- LOADLIN, 25, 29–30
- LoadModule directive, 540–541, 554
- Local backups, 419
- Local DNS servers, 455–456
- Local domain, 463
- Local mail reader, 258
- Local master browsers, 174–175
- Local networks
  - alternative devices, 17–18
  - routing table, 41
- Local printer queue, 186
- Local processes, 661
- Local startup files and font servers, 832
- Local startup scripts, 79, 100–101, 108
  - examining for unnecessary servers, 602
  - pros and cons, 109
  - usage, 109–110
- Local subnet broadcasts, 646
- Localhost interface, 40–41
- LOCAL\_IP variable, 58
- Localized authentication, 135
- LocalTalk, 17
- Location directive, 235
- Lock file, 518
- Log files, 126
- Log files, monitoring, 621
- Logging xinetd, 97–98
- login command, 193–195
- login program, 163
- login.krb5 program, 160
- Logins
  - changing account after, 160–161
  - Kerberos, 159–166
  - peer-to-peer, 337
  - shutting down processes related to, 605
  - smaller-scale, 337
- LogLevel directive, 538
- logout command, 193
- loopback interface, 40
- Lossless compression, 562
- Lossy compression, 562
- LPD (Line Printer Daemon), 221–223
- LPD servers
  - Linux options, 224–226
  - network printing, 222–224
  - when to run, 222–224
- lpd.perms file, 230
- LPD-style print server, 228
- lpr printing system, 186
- LPRng
  - distributions, 231
  - /etc/lpd.perms file, 229–232
  - /etc/printcap file, 228–229, 232
  - redundant protections, 231
  - sending job to spooler, 229
  - system default policy, 229
- LPRng printing system, 186, 228–232
  - clients, 232
  - package, 224
  - servers, configuring, 228–232
- Lynx, 565
- m4 configuration file, 525
- m4 macro processing utility, 492
- MAC (media access control) addresses, 117
  - from clients, 124–126
  - defining hosts, 127–128
  - Ethernet, 123
  - locating for DHCP clients, 123–127
  - Macintoshes, 125
  - Windows 2000, 124
  - Windows Me, 124
- Macintosh, 17
  - file and printer sharing, 15

- LocalTalk hardware, 69
- MAC addresses, 125
- MacOS
  - VNC clients, 364
  - VNC servers, 360–361
  - X servers, 356
- MacOS Classic and MAC addresses, 125
- MacOS X
  - AppleTalk, 70
  - LPD (Line Printer Daemon), 223
  - MAC addresses, 125
  - native NFS server, 71
  - NFS, 70
  - UNIX, 204
- magic file, 534
- Mail aliases, 494
- mail command, 193
- Mail delivery systems
  - Fetchmail's place in, 270–273
  - pull mail servers, 259–261
- Mail domain administration, 481–482
- MAIL FROM: command, 483–485
- Mail headers, altering, 486
- Mail relays, 487
- Mail retrieval, scheduling, 272
- Mail servers
  - blackhole lists, 489
  - direct addressing, 481
  - distributed pattern matching, 489
  - domain addressing, 481
  - mail domain administration, 481–482
  - maildir, 267
  - mbox, 267
  - as open relay, 491
  - pattern-matching blocks, 489
  - relaying mail, 495
- maildir, 267
- \$MAILDIR environment variable, 517
- mailing lists, 284, 625–626
- Mail-to-news gateway, 516
- main.cf file, 508–509, 513, 525
- make bzImage command, 26
- make clean command, 27
- make command, 27, 144
- make config command, 5
- make dep command, 25–26
- make install command, 144
- make menuconfig command, 5
- make modules command, 26
- make modules\_install command, 26, 28
- make vmlinux command, 26
- make xconfig command, 5
- Makefile and NetBEUI, 76
- makemap command, 493, 497
- Mandrake, 50
  - See also* Linux Mandrake
- mangle, 662
- Mapping files, 217–219
- MAPS (Mail Abuse Prevention System), 491
- Mark filtering, 644
- Mars\_nwe, 14, 73–74
  - HOWTO document, 73
- Master browsers, 174–176
- Master KDC, 142, 145, 153
- Master key, 147–148, 150
- Master name server, 468
- Master server, 463
- Master zones, 467
- MaxClients directive, 235, 536
- MaxSpareServers directive, 536
- mbox, 267
  - .message file, 584, 589
- Message headers, 482
- Messages, 286
  - cross-posting, 286
  - expiration options, 297–298
- mgetty program, 160
- MicroImages Web site, 340
- Microsoft Web site, 378
- MIME (Multipurpose Internet Mail Extensions), 533–534
- MIME types, 533–534
  - Web pages, 561–562
- mingetty program, 160
- minicom, 53
- miniserv.conf file, 401
- miniserv.users file, 401
- MinSpaceServers directive, 536
- MIT Kerberos Web page, 137, 143
- MI/X for windows and MacOS Classic, 340
- mkisofs command, 199
- Modems, 55
- Moderated newsgroups, 291
- Modules, 24–26
- Monitoring for intrusion attempts, 616–623
- mount command, 205–208, 212–214
- Mozilla, 565
- MPPE (Microsoft Point-to-Point Encryption), 692
- MSS (Maximum Segment Size), 43

## INDEX

- mt utility, 420
- MTU (Maximum Transfer Unit), 38
- MUAs (mail user agents), 258
- Multicast Backbone Web site, 646
- Multicast routing, 646–647
- Multicasts, 39, 646–647
- Multi-NIC configurations, 34
- Multipath routing, 644–645
- Multiple network interfaces
  - configuring, 40
  - with multiple gateways, 45–46
  - with one gateway, 44–45
- Multiple pull mail accounts, 271
- Multi-threaded servers, 90
- mutt mail reader, 258, 478
- MX (mail exchanger) records, 469–470, 481–482
- \$mydomain variable, 509–510
- \$myhostname variable, 508, 509
- \$mynetworks variable, 511–512
- My Network Places, 174
  
- Name resolution, 48, 172–174, 451
- Name server, 451
- named.ca file, 461
- named.conf file, 459–461
- nameserver keyword, 47
- NameVirtualHost directive, 558
- NAT (Network Address Translation), 45, 146, 345–346
  - configuring with iptables, 677–682
  - firewall-like protection, 679–680
  - protocols and, 680–681
  - router redirection, 97
  - routers, 679
  - setting iptables options, 681–682
- Native drivers, 191–192
- nbadmin command, 77
- NBDD (NetBIOS Datagram Distribution) server, 130
- NBNS (NetBIOS Name Service) servers, 130, 173–174
- nbstatus command, 77
- NBT (NetBIOS over TCP/IP), 75
- nbview command, 77
- NCP (NetWare Core Protocol), 72
- ncpfs package, 73
- ncpmount command, 73–74
- ncurses library, 702
- NEdit editor, 364
  
- Nessus, 604
- Nesting block, 521
- Netatalk package, 15, 69–72
- netb command, 76–77
- NetBEUI (NetBIOS Extended User Interface), 15, 68, 75–78
  - network stack, 64, 76
  - SMB/CIFS server, 77
- NetBIOS (Network Basic Input/Output System), 68
  - computers, 130
  - domain controller, 176
  - domain master browsers, 175
  - domains, 176
  - including information on DHCP servers, 129–131
  - local master browser, 174–175
  - name resolution systems, 129–130
  - networks, 170–172
  - scope, 130
  - workgroups, 176
  - workgroups and domains, 170
- Netcraft Web site, 530
- netkit-telnet package, 316
- Netmasks, 36, 39–40, 43
- Netscape Navigator, 335, 564
  - for Linux, 563
- netstat, 603–604
- NetWare, 15
- NetWare Web site, 15
- Network authentication, 139
- Network backup servers, 412–413
- Network backups, 411
  - AMANDA, 436–445
  - NFS (Network Filesystem) server, 423
  - security, 415
  - SMB/CIFS, 425–436
  - tar, 415–425
  - types of solutions, 413–425
- Network cards
  - controlling hardware address, 38
  - loading network drivers, 31–33
  - media connectors, 38
  - promiscuous mode, 37–38
- Network Computing Devices Web site, 340
- Network Device Support kernel menu, 15, 17–18, 20, 22–23
- Network drivers, 31–33
- Network File Systems submenu, 13
- Network filter options, 7–9

- Network font servers, 381–382
- Network interfaces
  - activating, 37, 38–40
  - adding and removing IPv6 IP addresses, 38
  - Apache, 537
  - assigning IP address to, 36
  - availability, 36
  - closing, 37
  - configuring, 36–40
  - DHCP issues, 116
  - information about, 37
  - modifying operation, 37
  - MTU (Maximum Transfer Unit), 38
  - multiple with multiple gateways, 45–46
  - multiple with one gateway, 44–45
  - network mask, 36–40
  - nonpromiscuous mode, 38
  - status of active, 37
- Network mask, 36–40
- Network Neighborhood, 174
- Network Options kernel menu, 9
- Network print queue, converting local print queue to, 228
- Network printing, 222–224
- Network protocol stacks, 63
- Network protocols
  - support, 6–15
  - within-computer communication, 7
  - X programs, 337–338
- Network stacks
  - AppleTalk, 68–72
  - footers, 66–67
  - headers, 66–67
  - IPX/SPX, 72–74
  - layers, 64–65
  - NetBEUI, 75–78
  - OSI (Open System Interconnection)
    - model, 64–66
  - overview, 63–68
  - routable, 67–68
  - TCP/IP role, 67–68
  - wrapping and unwrapping data, 66–67
- Networking Options menu, 6–15
- Networks
  - alternative stack options, 14–15
  - backup drives, 413
  - centralized computing model, 137
  - configuring, 105
  - decentralized computing model, 137
  - defining classes, 651–652
  - hardware options, 15–23
  - managing outgoing bandwidth, 649–653
  - PPP links, 51–62
  - security flaws, 9
  - subnets, 651–652
  - unusual traffic, 621–622
  - zoneless, 69
  - zones, 69
- Network-wide multicasts, 646
- New Account dialog box, 53, 55, 56
- New Registrars Web site, 457
- News feeds, 287–290
- News readers, 286, 296–297
- News servers, 283
  - binary newsgroups, 290
  - computer name, 291
  - disk space, 285
  - feeding news to other sites, 293–295
  - INN (InterNetNews), 288–298
  - internal communications, 284
  - Leafnode, 298–306
  - message IDs, 286–287
  - news feeds, 287–288
  - NNTP, 286–288, 289
  - obtaining news feed, 289–290
  - offline news reading, 283, 284, 285–286
  - ongoing maintenance, 298
  - organization name, 291
  - purging old messages, 287
  - push and pull protocols, 287
  - removing spam, 289
  - restricting access, 293
  - supporting local operations, 292
  - temporarily disabling, 298
  - third-party, 285
  - /var/spool/news directory tree, 285
  - when to run, 284–286
- newsfeeds file, 293–295
- Newsgroups, 284
  - binary, 290
  - cross-posted messages, 294
  - cross-posting messages, 286
  - deleting, 298
  - dynamic configuration, 299–300
  - hierarchy, 286, 293
  - moderated, 291
  - passing on news feeds from, 294
  - security, 625–626
  - setting up, 292–293
- newsgroups file, 293

## INDEX

- NewsGuy, 285, 289
- newsq command, 299, 304
- NFS (Network File System), 68, 203
  - client-side mapping daemon, 219
  - defining exports, 208–210
  - GIDs (group IDs), 213
  - Linux, 13
  - MacOS X, 70
  - mount transfer size, 214–215
  - non-NFS performance issues, 215
  - number of running NFS servers, 215
  - operations on mounted exports, 213
  - optimizing performance, 214–215
  - options, 12–13
  - ownership, 213
  - permissions, 213
  - portmapper, 207–208
  - security, 204
  - server-side user ID map, 217–219
  - support utilities, 206
  - time access, 215
  - trusted hosts security model, 204, 210
  - UIDs (user IDs), 213
  - Unix, 13
  - username mapping options, 215–219
  - usernames, 217
  - (NFSv3) version 3, 13
  - versions 2 and 3, 206–207
- NFS clients
  - basic support, 13
  - synchronization of UIDs, 216–217
- NFS servers
  - access control mechanisms, 210–212
  - access from secure ports, 211
  - asynchronous writes, 210
  - as centralized server, 203–204
  - delaying writing to disk, 210
  - disabling directory access, 211
  - /etc/exports file, 208–210
  - exporting directories, 208–215
  - file sharing, 222
  - firewalls blocking, 210
  - GID (group ID), 212
  - hiding or unhiding mounted partition, 211
  - kernel-mode, 205
  - Linux, 203, 204–207
  - Linux functioning as, 13
  - mounting exports, 212–214
  - network backups, 423
  - number of running, 215
  - read-only access, 211
  - read-write access, 211
  - squashing access attempts, 212
  - subtree checks, 211
  - synchronization of UIDs, 216–217
  - synchronous writes, 210
  - SysV startup script, 208
  - UID (user ID), 212
  - UNIX, 203
  - user-mode, 205
  - when to run, 203–204
- nfsd server, 205
- nfs-utils, 206
- NFSv4 Web site, 206
- NIC Web site, 457
- nice program, 98
- NICs (network interface cards), 34
- NIS (Network Information Service)
  - server, 209
- nkitserv, 316
- NLS (National Language Support) character sets, 14
- nmap, 604
- nmbd program, 77, 108
- nnrpd program, 288
- NNTP (Network News Transfer Protocol), 68, 286–289
  - servers, 286
- NNTPCache, 299
- nntpsend program, 288
- nntpsend.ctl file, 294–295
- Noffle, 299
- Non-delivering recipes (Procmail), 517
- Non-Kerberized applications, 141
- Non-PostScript data, directly printing, 196
- Non-PostScript files, 187
- Non-PostScript printer queues, 190–191
- Non-PostScript printers
  - Ghostscript, 189–190
  - native drivers, 191–192
  - PostScript driver, 191–192
  - printer shares, 189–192
  - sharing, 189–192
- Non-standard driver, 27
- Non-traditional Web servers, 531
- Non-UNIX systems and X servers, 341
- Notebook computers, 21–22
- NQNFS (Not Quite NFS), 206
- nslookup, 475

- NS (name server) records, 469
- NT/2000/XP client trust accounts, 177–178
- NTFS (New Technology Filesystem), 432
- NTP (Network Time Protocol), 242
  - ntp.conf file, 246–248
  - UTC (Coordinated Universal Time), 245
- NTP client package, 252–254
- NTP servers, 141
  - monitoring operation, 248–252
  - network delays reaching, 248
  - ntpdate program, 244
  - operation, 243–245
  - slewing the clock, 244
  - time server programs, 245–246
- NTP Web page, 243
- NTP Web site, 242
- ntp.conf file, 246–248
- ntpd program, 245–246
- ntpdate program, 244, 246, 252–254
- ntpq program, 246, 248–252
- ntptrace program, 246
- ntsysv program and SysV startup
  - scripts, 86–87
- nupop, 268
- nupop Web site, 268
  
- Offline news reading, 283, 284, 285–286
- One-way cable modem, 20
- OpenBSD FTPD, 578
- OpenMail, 480
- OpenSSH, 322–323, 550–551
  - packages, 323
  - Web site, 322
- OpenSSL package, 550–551, 552–553, 695
- Opera Web browser, 565
- Operating systems and X servers, 340
- Optical media, 412
- option keyword, 121
- Options directive, 547
- ORDB (Open Relay Database) Web site, 490
- Order directive, 235
- Oscillators, 251
- OSI (Open System Interconnection) model, 64–66
- OSPF (Open Shortest Path First) protocol, 656–657
- Outline font formats, 376–379
- OUTPUT chain, 661, 669, 681–682
- Outsourcing news feeds, 290
- Ownership, 181–183, 213
  
- <P> tag, 561
- Package databases, 617–618
- Packages, information about, 600–601
- Packed Font format, 376
- Packet filter firewall rule, 231
- Packet filter firewall script, 675–677
- Packet sniffers, 37–38
- Packet-filter firewalls, 667–668
- Packets, 66
  - adjusting priorities, 11–12
  - average size, 651
  - blocking or modifying, 7–9
  - chains, 661–662
  - filtering by interface, 673–674
  - (FIFO) First-in/first-out strategy, 11
  - forwarding, 653
  - INPUT chain, 661
  - internal/external translation, 678
  - IP address extension, 678
  - load balancing, 678
  - manipulating, 661–662
  - mark values, 644
  - opening and closing specific ports, 671–672
  - OUTPUT chain, 661
  - prioritizing, 647
  - routing, 653
  - scheduling transmission of outgoing, 11–12
  - source and destination IP addresses, 672–673
  - stateful inspection, 9, 664, 674–675
  - temporary address changes, 678
  - Type-of-Service values, 644
- Palmtop computers, 641
- PAM (Pluggable Authentication Module), 311, 633
  - configuring, 163–166
  - Curtis King’s module, 162
  - Debian modules, 163
  - Derrick Brashier’s module, 162
  - distributions, 162
  - Frank Cusack’s module, 162
  - Kerberos, 161–166
  - Red Hat’s module, 163
- PAP (Password Authentication Protocol), 55, 56, 59
- pap program, 71
- papd program, 70–71
- pap-secrets file and security, 57
- Paragraphs, 561
- Parallel-to-Ethernet adapters, 16

## INDEX

- Partial backups, 418
- Partial restores, 445
- passwd program, 164
- Password cracking programs, 612
- password service, 164
- Password sniffing, 409
- PASSWORD variable, 58, 59
- Passwords
  - accessing remote servers, 140
  - authentication, 328
  - building base, 611
  - cleartext, 171
  - compromised, 408
  - digits and punctuation, 611
  - encrypted, 171–172, 408–409, 610–611
  - Fetchmail, 281
  - file shares, 182
  - Kerberos principals, 156
  - Kerberos tickets, 140
  - Leafnode, 301
  - master key, 150
  - mixing case, 611
  - protecting, 139
  - pull mail account, 281
  - randomized strings, 611
  - reversing words, 611
  - saving to disk, 140
  - server-required, 135
  - setting, 610–612
  - shoulder surfing, 612
  - single-login operation, 139–140
  - sniffing, 612
  - SWAT, 405
  - Telnet, 320
  - unencrypted, 139, 408–409
- PC Card devices, 15, 17, 21–22
- PCF (Portable Compiled Font) format, 376
- .pcf.gz file extension, 376
- PCI (Peripheral Component Interconnect)
  - cards, 16
- PCMCIA (Personal Computer Memory Card International Association), 22
- PCMCIA Network Device Support
  - submenu, 22
- PDCs (primary domain controllers), 177
- PDF files and scripts, 200–201
- pdnsd, 458–459
- Peers, 295
- Peer-to-peer logins, 337
- Perl, 400
- Permissions, 181–183, 213
- Personalized Web sites, 545–546
- PFA (Printer Font ASCII) file, 386
- PFB (Printer Font Binary) file, 386
- physical interface, rules for, 40
- Picture element (pixel), 373
- PID (process ID), 97
- Pine, 258, 478
- ping, 248
- Pixels, 373
- .pk file extension, 376
- PLIP (Parallel Line Internet Protocol), 23
- PLIP Mini-HOWTO, 23
- Pluto daemon, 705–706
- PNG (Portable Network Graphics) file
  - format, 562
- PNG Web site, 562
- Points, 375
- Policy routing, 643–644
- POP (Post Office Protocol), 259
  - cleartext, 267
  - commands, 262–263
  - converting to IMAP, 271
  - headers, 264
  - versus* IMAP, 266–267
  - retaining original e-mail, 262
  - retrieving and deleting messages, 264
  - sample session, 262–264
  - secure variants, 267
  - security, 267
  - servers, 267–269
- POP-2, 262
- POP-3, 262, 263–264
- PoPToP
  - clients, 696–698
  - enabling encryption features, 694–696
  - MPPE (Microsoft Point-to-Point Encryption), 692
  - obtaining and installing, 692
  - server configuration, 692–694
- Port directive, 235, 537
- Port scanners, 604
- portmap program, 207
- Portmapper, 207–208
- Ports, 8
  - forwarding, 682–684
  - HTTP (Hypertext Transfer Protocol), 89
  - servers, 89



- SMTP (Simple Mail Transfer Protocol) mail servers, 89
- Post, 286
- postexec command, 193
- postexec scripts, 193–196, 196
  - burning CD-Rs, 197–199
- Postfix*, 478
- Postfix, 480, 507
  - accepting mail, 510–511
  - address masquerading, 509–510
  - address rewriting, 510
  - anti-spam configuration, 513–515
  - blackhole list, 514
  - calling Procmail, 525
  - configuration files, 508–509
  - DNS lookups, 513
  - finding all links to, 83
  - intruder changes to, 617
  - mbox, 267
  - relay configuration, 511–513
  - relaying mail, 511–512
  - remapping usernames, 510
  - sending through relay, 512–513
  - Web site, 480
- POSTROUTING chain, 681–682
- PostScript, 187
- PostScript drivers
  - Ctrl+D character, 188–189
  - faxes, 196
  - Non-PostScript printers, 191–192
  - Windows, 188
- PostScript files, converting to other formats, 196
- PostScript printers, sharing, 186–189
- PPD (PostScript Printer Description) (files), 232, 237–238
- PPP (Point-to-Point Protocol), 22–23, 31
  - accepting any hostnames, 57
  - configuring dialing scripts, 57–59
  - debugging, 59–60
  - dialing script usage, 59–60
  - dial-up connections, 271
  - hardware associated with connection, 54
  - initial communication with ISP, 58
  - ISP username, 57
  - passwords, 57
  - security, 60
  - setting authentication options, 56–57
  - setting variables, 58
  - storing dialup password, 56
  - terminating session, 58
- PPP HOWTO document, 55, 60
- PPP links
  - adjusting configuration scripts, 56–60
  - configuring dial-on demand, 60–62
  - GUI dialers, 52–56
- pppd, 58–59, 695–696
- PPPoE (Point-to-Point Protocol over Ethernet), 19, 52
- ppp-off script, 58
- ppp-on script, 58
- ppp-on-dialer script, 58–59
- PPTP (Point-to-Point Tunneling Protocol), 691–701
  - clients, configuring, 696–701
  - servers, 696–698
- pptp-command startup script, 697
- PPTP-Linux Web site, 695
- Practical UNIX & Internet Security, 2nd Edition*, 600
- preexec scripts, 193–196
  - burning CD-Rs, 197–199
- prefdm script, 355
- PREROUTING chain, 681–682
- Presentation layer, 64
- Primary (Kerberos), 139
- principal file, 148
- principal.db file, 148
- principal.kadm5 file, 148
- principal.kadm5.lock file, 148
- principal.ok file, 148
- Principals (Kerberos), 139, 155
  - ACLs granted to, 149
  - administrative, 150
  - changing password, 156
  - creation of, 150–151
  - domain name associated with, 146
  - KDCs, 151
  - modifying name, 150
  - name of, 149
  - permissions, 149
  - randomized key, 151
- print command, 196
- Print jobs, 189
- Print queues, modifying, 237
- Print servers, 185–192
- print-cd script, 199–200
- Printer drivers, 186–187

## INDEX

- Printer queues, 187
  - Ghostscript, 189
  - non-PostScript, 190–191
- Printer shares
  - creation of, 185–186
  - definitions, 185–186
  - local printer queue, 186
  - non-PostScript files, 187
  - non-PostScript printers, 189–192
  - PostScript printers, 186–189
  - printer drivers, 187
  - raw queue, 191
  - temporary spool directory, 185
- Printer sharing, 168
  - LPD (Line Printer Daemon), 222
  - single printer share, 186
- Printers
  - black and white, 373–374
  - color, 374
  - fonts, 375
  - PostScript clones, 187
  - PostScript interpreter, 187
  - PPD files, 237–238
  - resolutions, 375
- [printers] share, 407
- Printing, WYSIWYG (what-you-see-is-what-you-get), 373
- Printing systems
  - controlling access, 229–232
  - distributions, 225
  - selecting, 186
  - standard and alternative, 225
- Private IP addresses, 39
- Private key, 325, 327–328, 330, 551
- Processes
  - examining running, 602–603
  - kernel, 603
  - killing, 88
- Procmail, 477
  - calling, 524–525
  - designing recipes, 518–513
  - environment variables, 517
  - filter for individual accounts, 516
  - lock file, 518
  - piping mail through other programs, 516
  - post-MTA pattern matches, 489
  - recipes, 517
  - regular expressions, 516
  - sorting mail, 516
  - spam filters, 516
    - as system-wide filter, 516
  - The Procmail Companion*, 478
- Procmail filters
  - customization, 524
  - predesigned, 523–524
  - role, 515–517
  - Sample Procmail Recipes with Comments
    - Web site, 524
  - security mailing lists, 625
  - SmartList package, 524
  - SpamBouncer package, 523
  - testing, 524
  - Timo's Tips and Recipes, 524
- Procmail Web site, 524
- .procmailrc file, 521
- procmailrc man page, 518
- Procom Technologies Web site, 75–76
- /proc/sys/net/khttpd directory, 12
- Profiles, 176–177
- ProFTPd, 579, 580
  - aliases, 590
  - anonymous options, 595–596
  - configuring, 585–590
- proftpd.conf file, 585–586, 595–596
- Programs, 214
- Promiscuous mode, 37–38
- Proportionally-spaced fonts, 374–375
- Protecting passwords, 139
- Protocol stacks, 7, 63
- Protocols
  - high-level support, 12–14
  - integrating with DHCP, 129–134
  - name of, 90
  - NAT (Network Address Translation) and,
    - 680–681
  - network socket type, 90
  - URLs, 538
- Proxy server firewalls, 667
- ps command, 602–603
- Pseudo printers, 195–196
  - backup system, 434–435
  - burning CD-Rs, 199–200
- PTR (pointer) records, 469
- pub directory, 594
- Public key, 325, 551
- Public key authentication, 330, 331
- Public keys, 327–328
- Public-key cryptography, 551

- Pull mail accounts, 271–272, 281
- Pull mail protocols, 251–258
  - IMAP, 264–266
  - POP, 262–264
  - POP *versus* IMAP, 266–267
- Pull mail servers
  - Fetchmail, 270–282
  - large hard drives on, 261
  - mail delivery system, 259–261
  - retaining copy of e-mail, 261–262
  - retrieving mail, 261
  - storing e-mail, 261
  - when to run, 258–259
- pump DHCP client, 33
- Push mail protocols, 251
  - SMTP (Simple Mail Transfer Protocol), 260, 477
- Push mail servers, 258
- qmail, 267, 281, 480
- qmail-pop 3d, 268
- The qmail Handbook*, 478
- qmail Web site, 268, 480
- QMS magicolor driver, 190
- QoS (quality of service), 11–12, 647
- QPopper, 268
- Qt library, 340
- range declaration, 122, 128
- Raw queue, 190–191
- Razor, 489
- RBL (Realtime Blackhole List) Web site, 490
- RC-Config Editor tool, 105
- rc.local script, 101
- r-command servers, 314
- r-commands, 310, 312–313
- rcp program, 158
- RCPT TO: command, 483, 484, 485
- Read-only shares, 179
- Realms, 138, 139
  - administering, 148–151
  - computer administering, 146
  - mapping computers into, 146
  - setting up, 145–147
- Recipes (Procmail), 517
  - actions, 520–521
  - conditions, 519–520
  - copying message, 523
  - delivering, 517
  - examples, 521–523
  - identification line, 518–519
  - nested, 521–522
  - non-delivering, 517
  - regular expressions, 519–520
  - sorting message, 523
  - spam conditions, 522–523
- Recordable DVDs, 412
- Red Hat Linux 7.2, 35
  - GUI configuration tool, 50
  - Linuxconf, 50
  - startup script locations, 81
- Red Hat Web site, 615
- Redirection, 97
- Reference time server, 243
- Regular expressions
  - PCRE-style, 513
  - POSIX-style, 513
  - Procmail, 516
  - recipes, 519–520
- ReiserFS, 285
- Relay, 259–260
- Relay configurations
  - Exim, 503–504
  - sendmail, 495–498
- \$relay\_domains variable, 511–512
- Release kernels, 4
- Remote administration and security, 408–410
- Remote login servers, 309
  - rlogind program, 310–316
  - security, 310
  - SSH (Secure Shell), 321–333
  - Telnet, 316–321
  - when to run, 310
- Remote logins and XDMCP servers, 350
- Remote print queue, 228
- Remote system maintenance tools, 391–392
- REMOTE\_IP variable, 58
- Remote-login X access, 347–348
- Removable-media device, 194
- Report Magic Web site, 570
- Resolutions, 375
- Resources, access to, 588
- Respond (fax software), 196
- restarting init process, 89
- Restoring
  - clean system after intrusions, 623
  - data, 445–447
- Reverse DNS lookup, 463

## INDEX

- Reverse DNS zones, 463, 470–471
- Reverse lookups, 133
- RFC Ignorant Web site, 490
- .rhosts files
  - rlogind, 311, 313
- RIP (Routing Information Protocol), 655, 656–657
- RIP: An Intra-Domain Routing Protocol*, 642
- RIPng, 657
- RIPv2 (RIP version 2) protocol, 657
- rlogin program, 158, 314–315
- rlogind program
  - configuring, 310–316
  - controlling access, 313–315
  - /etc/inetd.conf file, 311
  - /etc/xinetd.d files, 311
  - .rhosts files, 311, 313
  - security, 313–313
  - trusted hosts security model, 312, 313
  - unencrypted data transfers, 313, 320–321
- rlogind server, 311–313, 513
- Roaring Penguin PPPoE, 19, 23, 52
- Roaring Penguin Web site, 19, 52
- rodsBooks Web site, 20
- Root (/) directory
  - filesystem, 24
  - renaming, 627
- Root filesystem, mounting from NFS
  - export, 13
- Root server, 452
- Root zone, 463
- Routable network stacks, 67–68
- route command, 41–44, 46, 51, 655
- route -n command, 41
- routed package, 656
- Routers, 9–10, 40–41, 641–642
  - See also* advanced router configurations
  - destination address, 644
  - DoS (denial-of-service) attacks, 645
  - fast NAT, 644
  - iproute2 package, 648–653
  - large routing tables, 645–646
  - logging options, 654
  - mark filtering, 644
  - multipath routing, 644–645
  - NAT (Network Address Translation), 679
  - non-routing tasks, 44
  - QoS (Quality of Service), 647
  - security, 44
  - source address, 644
  - Type-of-Service values, 644
- Routing, 653
  - multicast, 646–647
- Routing protocols, 653–655
  - BGP (Border Gateway Protocol), 657
  - costs, 653–655
  - distance vector algorithms, 655
  - GateD, 657
  - GNU Zebra, 657–659
  - link state algorithms, 655–656
  - OSPF, 657
  - RIP (Routing Information Protocol), 655, 656–657
  - RIPng, 657
  - RIPv2 (RIP version 2) protocol, 657
  - slow convergence, 657
  - Zebra, 658
- Routing tables, 40–44, 645–646
  - manipulating, 648–649
  - multiple, 649
- Roxen, 531
- Royal Institute of Technology in Sweden Web site, 143
- RPC (Remote Procedure Call) services, 207
- rpm, 206, 617
- RPM (Red Hat Package Manager), 600
- RPM Find Web site, 61
- RSA authentication, 328, 706
- rsh program, 158
- rshd daemon, 421–422
- RSS (Relay Spam Stopper) Web site, 490
- RSVP (Resource Reservation Protocol), 11
- rule command, 648
- Runlevels, 80–81
  - 0 or 6, 88
  - killing processes, 88
  - meanings, 87–88
  - returning to default, 85–86
  - setting and changing, 87–89
  - single-character code or number, 88
  - special-purpose, 88
  - temporarily changing, 88
  - text-mode, 354
  - X, 354
  - XDMCP servers, 354
- SAINT, 604
- Salmi, Timo, 524

- Samba, 14, 167–168, 204
  - ACLs (Access Control Lists), 183
  - backup shares, 432–436
  - by-share authentication, 184
  - by-user authentication, 184
  - case-insensitive files, 168
  - domain controllers, 176–178
  - DOS, 168
  - encrypted passwords, 171–172, 177
  - as file server, 179–184
  - file shares, 179–180
  - filename requirements, 180–181
  - functioning as WINS (Windows Internet Name Service) servers, 173–174
  - general configuration, 169–178
  - hidden bit on Linux dot files, 183
  - limiting access to file shares, 184
  - logging information, 194
  - mapping DOS and Windows attribute bits, 182–186
  - master browser, 174–176
  - NetBIOS name requests, 405
  - non-PostScript printers, 189–192
  - NT/2000 domain client support, 177
  - parameters, 169–170
  - password database, 171
  - patches to, 76
  - as PDC, 177
  - postexec scripts, 193–195
  - PostScript printers, 186–189
  - preexec scripts, 193–195
  - print servers, 185–192
  - printer shares, 185–192
  - processing its own share-access requests, 177
  - scripts, 192–201
  - security options, 171–172
  - server identification, 170–171
  - SMB/CIFS, 168–169
  - smb.conf file, 169–170
  - smbtar, 428–429
  - SWAT, 404
  - time servers, 254–255
  - user accounts, 181
  - variables, 193–194
  - Web site, 76
  - Windows, 168
- Samba servers
  - file storage space, 179–180
  - identification, 170–171
  - lists of hosts explicitly allowed to connect, 172
  - NetBIOS name server, 172–174
  - setting Windows client time, 255
  - when to run, 168–169
- Sample Procmail Recipes with Comments
  - Web site, 524
- [sample] share, 179
- Sample zone configuration file, 466–467
- SAP (Service Advertisement Protocol), 73
- Saving passwords to disk, 140
- sawmill, 366
- Scientific data acquisition systems, 17
- scp program, 204, 323, 330
- Script kiddies, 622
- ScriptAlias directive, 547
- Scripts
  - burning CD-R, 197–200
  - PDF files, 200–201
  - pseudo printers, 195–196
  - Samba, 192–201
  - Samba server as CD-R creation platform, 197
- SDSL (Single-Line (or Symmetric) DSL), 19
- Search engines, 545
- search keyword, 47
- Searching domains, 47
- secret key, 327–328
- Secure Web sites, 550–555
- Security, 599–600
  - accounts, 606–610
  - anonymous FTP servers, 592–593
  - Apache binaries, 535
  - AppleTalk, 70
  - automatic software update procedures, 615–616
  - CGI scripts, 549–550
  - chroot jail, 627–639
  - client-initiated backups, 414
  - compromised passwords, 408
  - correcting problem after intrusion, 623
  - delegating to users, 314
  - djbdns, 459
  - DoS (denial-of-service) attacks, 645
  - encryption, 346
  - font servers, 382, 384–385
  - FTP, 578
  - general procedures, 624–626

## INDEX

Security, (*continued*)

- IMAP, 267
  - information sources, 614
  - internal tool, 136
  - keeping system up to date, 612–616
  - mailing lists, 625–626
  - monitoring for intrusion attempts, 616–623
  - monitoring for updated software, 614
  - network backups, 415
  - newsgroups, 625–626
  - NFS (Network Filesystem), 204
  - pap-secrets file, 57
  - passwords, 610–612
  - plus sign (+) in .rhosts file, 314
  - POP, 267
  - portmapper, 207
  - PPP (Point-to-Point Protocol), 60
  - remote administration, 408–410
  - remote login servers, 310
  - rlogind, 313–313
  - routers, 44
  - Samba options, 171–172
  - server bugs, 408
  - server updates, 613
  - server-initiated backups, 415
  - shutting down unnecessary servers, 600–606
  - specific user privileges, 90–91
  - storing PPP dialup password, 56
  - TCP Wrappers, 92–95, 421
  - Telnet, 320–321
  - time stamps, 141
  - Tripwire, 617–621
  - verbose router logging, 654
  - VNC, 360
  - VPNs (Virtual Private Networks), 690, 710–712
  - Web sites, 624–625
  - xauth program, 344
  - xinetd, 421
- Security cameras, 17
- Security Focus Web site, 624–625
- sed, 343
- sender\_canonical file, 510
- Sendmail*, 478
- sendmail, 49, 479, 480
- accepting mail, 495–496
  - access database, 496–497
  - address masquerading, 494
  - allowing access to, 493
  - another system as mail relay, 498
  - anti-spam configuration, 498–499
  - blackhole lists, 498–499
  - calling Procmail, 525
  - configuration files, 492–494
  - configuring to relay mail, 495–497
  - distributions, 491–492
  - as mail exchanger, 496
  - mail originating from its own domain, 496
  - mbox format, 480–481
  - message with From: address within local domain, 496
  - relay configuration, 495–498
  - SysV scripts, 493
  - Web site, 479
- sendmail.cf file, 492–494
- sendmail.cf package, 492
- Server protocols, name of, 90
- ServerAdmin directive, 537
- Server-initiated backups
- backup server's root user, 423–424
  - scheduling issues, 414–415
  - security, 415
  - tar, 423–425
  - user control, 415
- ServerName directive, 537
- ServerRoot directive, 539
- Servers, 79
- authenticating users, 139
  - behaving strangely, 621
  - buggy, 408, 613
  - changing automatic startup, 107
  - configuring, 104, 106
  - configuring to operate in chroot jails, 633–638
  - connection load limits, 98
  - controlling startup through xinetd, 103
  - copying files into chroot jails, 631
  - current status, 103
  - daemon mode, 101
  - disabling, 97, 606
  - DLLs (dynamic linked libraries), 632
  - enabling or disabling, 85
  - enabling or disabling run levels, 103–104
  - finding all links to, 83
  - hardware device files, 632
  - host-based restrictions, 99
  - identify file authentication, 328
  - importance of updates, 613
  - incoming connection, 91
  - indirectly running, 89

- interface restrictions, 99
- locating MAC address from, 126–127
- manually enabling or disabling, 82–84
- manually starting, 110
- methods of shutting down, 606
- multi-threaded, 90
- ports, 89
- problems with chroot jails, 629
- program arguments, 91
- protecting from unwanted accesses, 92–95
- required passwords, 135
- residing in chroot jail, 628
- returning to default runlevel, 85–86
- run as root, 613
- running in background, 101
- Samba identification, 170–171
- separating in chroot jails, 628–629
- shutting down unnecessary, 600–606
- single-threaded, 90
- special filesystems, 632
- starting, 80–96, 105
- startup methods, 108–110
- static IP address assignment, 36
- support programs, 632
- temporal restrictions, 99
- temporarily starting or stopping, 83
- unaffected by TCP Wrappers, 93
- unreliability with super servers, 108–109
- user accounts, 607
- user database files, 632–633
- Web sites for, 614
- to which rule applies, 93–94
- X, 338
- Server-side user ID map, 217–219
- Server-specific configuration packages, 393
- ServerTokens directive, 536
- ServerType directive, 535
- Services, 80, 106–107
- Session key, 141
- session service, 164
- Setting news feed access, 295–297
- SFQ (Stochastic Fairness Queueing)
  - discipline, 652
- sftp program, 324
- SHA (Secure Hash Algorithm) codes, 489
- Shares
  - copying files to backup device, 195
  - as if local, 12–13
  - limiting number of users, 195
  - logging in or out, 193–195
  - pseudo printers, 195–196
  - restricted access, 195
- Shells and dot files, 183
- Shoulder surfing, 612
- Shutting down unnecessary servers, 600–606
- SIGHUP signal, 354
- SIGKILL signal, 88
- signal 11 errors, 27
- SIGTERM signal, 88
- Single-threaded servers, 90
- single-user mode, 89
- Slackware Linux 8.0, 35
  - editing single startup script file, 84
  - starting servers, 100
  - startup script locations, 81
- Slashdot Web site, 545, 622
- Slave KDCs, 142, 145, 152–153
- Slave servers, 463
  - configuring, 464–465
  - timing information, 468
- Slave zones, 465
- SLIP (Serial Line Internet Protocol), 23, 61
- Slow convergence, 657
- Smail, 480
- Smaller-scale logins, 337
- SmartList package, 524
- SMB (Server Message Block) protocol, 14, 167, 425
- SMB/CIFS (Server Message Block/Common Internet Filesystem) file-sharing
  - protocols, 68, 167
  - cleartext passwords, 171
  - file- and printer-sharing protocols, 75, 129
  - network backups, 425–436
  - options, 13–14
  - ownership, 181–183
  - password encryption, 171
  - permissions, 181–183
  - protocols, 222
  - Samba, 168–169
  - sharing files to backup, 426–429
  - smbmount, 429–430
  - usernames, 182
  - Windows, 223
  - Windows clients backups from Linux, 426–423
- SMB/CIFS clients, 434
- SMB/CIFS servers
  - browsing, 174
  - sharing hard disks, 426–428

## INDEX

- smbclient program, 14, 77
- smbclient tool, 428
- smb.conf file, 169–170, 404
  - [global] section, 177
  - [homes] share definition, 180
  - time server option, 254–255
- smbd, 77
- smbmount, 429–430
- smbpasswd command, 178
- smbpasswd database, 171–172
- smbpasswd file, 177, 178
- smbtar program, 416, 428–429, 431
- SM-PIM (Sparse Mode - Protocol Independent Multicast), 646–647
- SMTP (Simple Mail Transfer Protocol), 68, 207, 260, 477
  - envelope and message headers, 484
  - envelope headers, 482
  - mail delivery, 482–485
  - mail server ports, 89
  - sender identification, 484
- SMTP servers, 477
  - accepting mail as local, 486
  - address masquerading, 485–486
  - anti-spam configuration, 488–491
  - configuration options, 485–491
  - delivery of e-mail through another SMTP server, 487–488
  - distributions, 479
  - Exim, 479–480, 499–507
  - information delivery by, 484–485
  - local mail organization, 478
  - mail relays, 486–488
  - maildir format, 482
  - multiple configuration files, 488
  - network mail recipient, 478
  - network mail relay, 478
  - options for aborting messages, 484
  - options for Linux, 479–481
  - Postfix, 480, 507–515
  - Procmail filters, 515–525
  - qmail, 480
  - sendmail, 479, 491–499
- SMTP transactions, 483–485
- SNF (Server Normal Format), 376
- Sniffing, 612
- SOA (start of authority) record, 467
- sockets, 6–7
- Software
  - Automatic update procedures, 615–616
  - bugs, 613
    - monitoring for updated, 614
    - Web sites and mailing lists, 614
  - SoluCorp Web site, 394
  - Source code dependent files, 25–26
  - Sourceforge Web site, 15, 22, 268, 269
  - Spam
    - blocking incoming, 488–491
    - Exim, 504–507
    - filters, 516
    - mail relays, 487
    - Postfix, 513–515
    - preventing transmission of, 491
    - recipes, 521–523
    - sendmail, 498–499
    - SHA (Secure Hash Algorithm) codes, 489
    - SMTP servers, 488–491
  - SpamBouncer package, 489, 523
  - Spam-filter recipes, 521–522
  - Special-purpose runlevels, 88
  - Speed Touch USB DSL modem, 20
  - Speedo fonts, 378
  - Spoofing, 673
  - SPX (Sequenced Packet Exchange) protocol, 72
  - SSH (Secure Shell), 68, 204, 322–323, 345–346, 691
    - authentication, 327–333
    - capabilities, 323–324
    - compression, 346–347
    - configuring, 321–333
    - direct implementation of non-login tools, 323–324
    - DISPLAY environment variable, 346
    - encryption, 346
    - encryption key files, 325
    - file transfers, 323–324
    - forwarding or tunneling network ports, 323
    - generating keys to automate logins or improve security, 329–331
    - hybrid of trusted-hosts with Rivest/Shamir/Ableman (RSA) authentication, 328
    - packages, 322–323
    - PKI (Public Key Infrastructure) support, 322
    - private key, 325, 327–328
    - public key, 325, 327–328
    - public key authentication, 327, 331
    - running VNC servers from, 363
    - scp program, 323
    - secret key, 327–328



- ssh-agent, 331–333
- ssh config file, 346
- sshd\_config file, 325–327, 346
- SSL, 550
- startup options, 324–325
- stfp program, 324
- super server, 324
- SysV startup script, 324
- text mode login client, 324
- trademark status, 321
- trusted-hosts authentication, 328
- tunneling X connections, 327, 345–347
- xauth program, 343–344
- Web site, 322
- SSH clients
  - DISPLAY environment variable, 346
  - /etc/ssh/ssh\_config, 346
- SSH servers, 321
  - accepting logins from root, 326
  - as daemon, 324
  - debug mode, 324
  - disabling logging, 325
  - encryption key, 326
  - error output to standard error, 324
  - /etc/ssh/sshd\_config, 346
  - host keys, 326
  - IPv4 or IPv6 addresses, 325
  - port, 325
  - as stand-in for local X server, 346
  - super server, 325
  - trusted hosts authentication, 326–327
- ssh-agent, 331–333
- ssh config file, 346
- sshd program, 324–326
- sshd\_config file, 325–327
- SSIs (Server Side Includes), 546
- SSL (Secure Sockets Layer), 167, 550–555
  - authentication, 551
  - configuring, 552–553
  - enabling in Apache, 553–554
  - encryption, 551
  - SSH (Secure Shell), 550
  - Webmin, 409
- SSLCertificatePath directive, 554
- SSLCertificateFile directive, 554
- SSLLeay, 552
- SSLEnable directive, 554
- SSLRequireSSL directive, 554
- Stable kernels, 4
- Standalone Web page creation tools, 564
- Standard kernel, 4
- StarOffice, 335, 563
- startkde, 366
- Startup files
  - examining for unnecessary servers, 601–602
- Startup methods, 108–110
- Startup scripts, 51
  - GUI tools, 84
  - link directories, 82
  - local, 100–101
  - manually enabling or disabling, 82–84
  - start or stop parameters, 83
  - text-based tools, 84
  - utilities, 84–87
  - XDMCP servers, 355
- Stash file, 147–148
- Stateful packet inspection, 9, 664, 674–675
- Static IP addresses, 114, 122
  - configuring, 36–51
  - DHCP servers, 115
- Static Web pages, 12, 539
- Storm Package Manager, 601
- strace program, 631
- Strange files and intrusions, 621
- Stratum 0 time servers, 243
- Stratum 1 time servers, 243
- Stratum 2 time servers, 243
- Stub server, 463–464
- su program, 164
- subnet declaration, 121–122
- Subnet mask, 36
- Subnets, 121–122, 651–652
- sudo program, 164
- SUID (set user ID)
  - GUI dialers, 60
- SUID root program
  - ksu binary, 160
  - preventing creation of, 214
- Sunsite Web site, 4, 73
- Super servers, 79, 89, 96
  - distributions, 109
  - Linuxconf, 394
  - pros and cons, 109
  - server unreliability with, 108–109
- SSH (Secure Shell), 324
- SSH server, 325
- SWAT, 404
- usage, 109
- Web servers, 534

## INDEX

- SuSE Linux, 35
  - /etc/rc.config file, 82, 105
  - startup script locations, 81
  - YaST (Yet Another Setup Tool), 50
  - YaST2, 50
- swat program, 405
- SWAT (Samba Web Administration Tool),
  - 102, 393, 404, 410
  - Advanced View, 407–408
  - configuring, 404–405
  - default port, 405
  - deleting share, 407
  - editing existing share, 406
  - Globals page, 405, 406
  - Home page, 405
  - Password page, 406
  - passwords, 405
  - Printers page, 405, 406
  - share creation, 407
  - Shares page, 405, 406
  - Status page, 405–406
  - super server, 404
  - unencrypted passwords, 409
  - usage, 405–408
  - username, 405
  - View page, 406
  - writing out changes to smb.conf, 408
- SWATCH, 621
- Symbolic links, 194
- syslogd, 7
- System
  - keeping up to date, 612–616
  - monitoring health of, 621
- System files
  - checking for account abuse, 610
  - copying to chroot jails, 632–633
- System services, starting, 80–89
- SysV printing system, 225
- SysV (System V) startup scripts, 62, 79, 80,
  - 100, 108, 109, 298
  - bash shell scripting language, 100
  - chkconfig, 84–86
  - controlling, 103
  - DHCP servers, 116
  - directories, 81
  - enabling and disabling, 84–86
  - examining for unnecessary servers, 602
  - font servers, 382
  - Kerberos, 152
  - link directories, 81
  - listing of, 106
  - locations, 80–82
  - manually enabling or disabling, 82–84
  - modifying, 100
  - modifying runlevels, 86
  - naming conventions, 80–82
  - NFS server, 208
  - ntsysv program, 86–87
  - obtaining information on current
    - configuration, 84–85
  - pros and cons, 109
  - removing from script directory, 83
  - renaming to prevent use, 83
  - sendmail, 493
  - setting and changing runlevels, 87–89
  - SSH (Secure Shell), 324
  - start parameter, 87
  - startup script link directories, 82
  - status, 85
  - stop parameter, 87
  - utilities, 84–87
  - Webmin, 401
  - XDMCP servers, 355
  - xinetd, 98
- Tables and chains, 662
- Tape drives, 412, 413
  - built-in compression, 418–419
  - changer model, 441
  - controlling, 420
  - nonrewinding devices, 419, 441
  - rewinding devices, 419
  - testing, 419–420
- Tapetype utility, 440–441
- tar, 415, 428, 442
  - accuracy of backup, 418
  - backing up only specified directories or
    - files, 418
  - backing up system files, 428
  - basic features, 416–419
  - client-initiated backups, 421–423
  - commands, 416–419
  - device files, 419
  - one-file-system option, 417–418
  - partial backups, 418
  - qualifiers, 416–419
  - recording information on backed up
    - files, 418
  - same-permissions option, 428
  - server-initiated backups, 423–425

- testing backups, 419–420
  - verify option, 418
- tar command, 425
- tc utility, 11, 649–653
- TCP Wrappers, 91
  - comments, 93
  - /etc/hosts.allow file, 92
  - /etc/hosts.deny file, 92
  - exceptions, 95
  - portmapper, 207
  - rlogind server, 315
  - security, 421
  - servers to which rule applies, 93–94
  - unaffected servers, 93
- tcpdump, 7
- TCP/IP (Transmission Control Protocol/Internet Protocol), 9–10, 63, 67–68
  - and DHCP (Dynamic Host Configuration Protocol) server, 113
  - name resolution, 172
  - network stack, 64
  - packets, 677–682
  - routers, 649–653
  - servers, 207
  - stack, role of, 67–68
- TCP/IP Control Panel, 125, 178
- TCP/IP Info dialog box, 125
- TCP/IP Properties dialog box, 130–131, 173
- tcpipl, 316
- Techno Pagan Web site, 134
- TELEPHONE variable, 58
- telinit command, 354
- Telnet, 68
- telnet, 158, 316
  - adjusting login display, 317–319
  - compromised data, 320
  - debugging, 317
  - passwords, 320
  - security, 320–321
  - sensitive data, 321
  - startup options, 316–317
  - unencrypted nature, 320–321
  - usernames, 320
  - xclock program, 345
- Telnet servers
  - arguments, 316–317
  - encrypting data transfers, 320
  - starting, 101
- telnetd, 316–317
- telnetd server and /etc/issue.net file, 317–318
- telnet-server, 316
- Temporary spool directory, 185
- Terminal programs, 53
- TeX, 376, 379, 390
- texpire program, 299, 305
- Text, converted into bitmap, 191
- Text files, 544
- Text-mode Kerberos login authentication, 160
- Text-mode remote-access server, 347
- Text-mode runlevel, 354
- TFTP (Trivial File Transfer Protocol) server, 340
- TGS (ticket-granting service) (Kerberos), 140
- TGT (ticket-granting ticket) (Kerberos), 140, 155–157
- Third-party mail relays, 487
- Third-party news servers, 285
- Threads and texpire, 305
- thttpd, 531
- Thursby Web site, 71
- Tickets (Kerberos), 138
  - destroying, 156
  - encrypted with target server's password, 141
  - listing, 156
  - passwords, 140
- TightVNC, 360, 361
- Time servers, 241, 245–246
  - NTP servers, 242–254
  - operation of, 243–245
  - Samba, 254–255
  - synchronization, 243
  - veridical time source, 243
  - when to run, 242
- Time stamps, 141
- Timo's Tips and Recipes, 524
- <TITLE> tag, 560
- tksysv, 106–108
- TLDs (top-level domains), 452, 457
- Token Ring, 17
- Tools for packet socket connections, 7
- Traditional font servers, 379–388
- Transmit queue, 38
- Traveling users' mail relays, 487
- TridiaVNC, 360, 361
- Tripwire, 617–621
- TrueType fonts, 372, 378–379, 387–388
- TrueType-only font servers, 380
- Trust accounts and NT/2000/XP client, 177–178
- Trusted hosts security model, 204, 312, 313

## INDEX

- Trusted-hosts authentication, 328
- TSI (MAPS Transport Security Initiative) Web page, 491
- TTL (time to live), 468
- ttmkfdir, 387–388
- Tunneling X connections through SSH, 345–347
- TurboLinux 7.0, 35, 50, 81
- TurboLinux Configuration Center, 50
- TUX, 543–544
- Tuxedo Web site, 5
- Twisted-pair cabling, 16, 18
- twm, 366
- .txt file extension, 533–534, 544
- Type 1 fonts, 378, 386–387
- Type 3 fonts, 378
- Type 5 fonts, 378
- Type 42 fonts, 378
- Typefaces, 377
- typelinst utility, 387
- Type-of-Service values, 644
  
- u32 algorithm, 652
- ugidd server, 219
- UIDs (user IDs)
  - NFS, 213
  - NFS servers, 212
  - synchronization, 216–217
- Uncompressed kernel, 26
- Unencrypted data transfers, 313
- Unencrypted passwords, 139
- University of Washington IMAP Web site, 266, 268
- UNIX, 137
  - MacOS X, 204
  - NFS (Network File System), 13
  - NFS servers, 203
- Unix Backup & Recovery*, 411
- Unix Domain Sockets option, 7
- Unnecessary servers
  - decisions on, 605–606
  - examining running processes, 602–603
  - examining startup files, 601–602
  - external scanners, 604–605
  - locating, 600–606
  - netstat, 603–604
  - package management systems, 600–601
  - shutting down, 600–606
- Update Agent, 615
  
- Updating DNS server, 473
- URLs (Uniform Resource Locators), 538–539
- URLs (uniform resource locators), 528
- USB devices, 17
- Usenet, 284
- Usenet news servers, 284
- User accounts, 216
  - automated processes, 608–609
  - checking for abuse, 609–610
  - creation procedures and policies, 607–608
  - inactive, 608–609
- User and Group directive, 535
- User logins and Kerberos, 159–166
- User principals (Kerberos), 155
- User space processes, 541
- useradd command, 178
- UserDir directive, 539–540
- User-level programs, 48
- usermod command, 216
- User-mode NFS servers, 205
- Usernames
  - AMANDA, 440
  - Fetchmail, 281
  - Linux, 182
  - for mail delivery, 279
  - NFS (Network Filesystem), 217
  - NFS mapping options, 215–219
  - SMB/CIFS, 182
  - SWAT, 405
  - Telnet, 320
- Users
  - complaints and intrusions, 621
  - linking pull mail account to, 281
  - specific privileges for, 90–91
- Using Samba*, 168
- /usr/lib/diald/standard.filter file, 61
- /usr/src directory, 4
- /usr/src/linux directory, 4, 5
- /usr/src/linux symbolic link, 4
- /usr/src/linux/arch/i386/boot directory, 28
- UTC (Coordinated Universal Time), 245
- Utilities and startup scripts, 84–87
- UW IMAP, 268, 269–270
  
- Variables, 193–194, 196
  - /var/kerberos/krb5kdc directory, 148
  - /var/lib/dhcp/dhcpd.leases file, 126
  - /var/spool/news directory tree, 285
- Verbose router logging, 654

- vgetty program, 160
- Virtual domains, 555
  - VirtualHost directive, 558–559
    - configuration options, 556–559
    - explicitly defining each virtual host, 558–559
  - VirtualDocumentRoot directive, 556–557
- Virtual IP addresses, 146
- <VirtualHost address> directive, 587
- VistaSource Web site, 389
- VLB (VESA Local Bus) cards, 16
- vlock program, 161, 164
- VNC (Virtual Network Computing), 335
  - bitmap-oriented, 360
  - client/server relationship, 339, 358–361
  - controlling Windows or MacOS system, 360–361
  - Java server mode, 362
  - multiple logins to same port, 368
  - port numbers, 368
  - problems with, 364
  - running XDMCP login server, 367–369
  - security, 360
  - single connection between two computers, 368
  - speed, 360
- VNC clients, 358, 363–365, 368
- .vnc directory, 361
- VNC protocols, 369
- VNC server script, 365
- VNC servers, 358
  - accessing from VNC client, 363–364
  - adjusting basic features, 364–366
  - as binary tarball, 361–362
  - customized startup script, 366
  - customizing users' settings, 366
  - global settings, 366
  - individualized option files, 367
  - installing, 361–362
  - modifying configuration, 364–369
  - network connection, 359
  - running, 362–363
- VNC Web site, 361
- vnconnect file, 361
- vncpasswd program, 361–362
- vncserver script, 361, 364–366
- vncviewer file, 361, 363
- VPN HOWTO document, 323
- VPNs (Virtual Private Networks), 323, 687–688
  - bandwidth, 689–690
  - encrypting nonencrypted protocols, 688
  - FreeS/WAN, 691, 701–710
  - granting access to larger networks, 689
  - illusion of local access, 688
  - Linux options, 691
  - PPTP (Point-to-Point Tunneling Protocol), 691–701
  - routers, 688
  - security, 690
  - security risks, 710–712
  - SSH (Secure Shell), 691
  - when to use, 688–691
- WAN devices, 18–20
- WAN Interfaces submenu, 20
- WAN routers, 20
- WANs (Wide-Area Networks), 20
- Web browsers, 528, 563–565
- Web forms, 546
- Web hosting, 529
- Web log file analyzers
  - Analog, 567–570
  - Webalizer, 570–573
- Web pages
  - body, 560
  - centering text, 561
  - design tips, 564–565
  - dynamic, 12
  - graphics, 561, 562–563
  - header, 560
  - headings, 560–561
  - HTML text file, 559–561
  - identifying as HTML, 560
  - links, 561
  - MIME type, 561–562
  - paragraphs, 561
  - static, 12
  - title, 560
  - tools for producing, 563–564
- Web search engines, 545
- Web servers, 528–529
  - Apache, 530–531, 532–541
  - CGI-enabled, 549–550
  - colocation, 530
  - document types, 561
  - dynamic content, 545–546
  - extensible, 540
  - kernel-based, 531

## INDEX

- Web servers, (*continued*)
  - kHTTPd, 541–544
  - log files, 565–573
  - non-traditional, 531
  - options for Linux, 530–532
  - Roxen, 531
  - static content, 544–545
  - super servers, 534
  - thttpd, 531
  - virtual domains, 555–559
  - when to run, 528–530
  - Zeus, 531
- Web sites, 528–529
  - distributions, 614
  - secure, 550–555
  - security, 624–625
  - SSL (Secure Sockets Layer), 550–555
- Webalizer, 570–573
- webalizer.conf file, 570–571
- Web-based administration tools, 102
- Web-based Linuxconf, 397–399
- Webmin, 50, 102, 392, 410
  - configuration modules, 401, 403
  - configuring, 400–401
  - distributions, 393, 399
  - non-Linux UNIX-like systems, 399
  - Perl, 400
  - SSL (Secure Sockets Layer), 409
  - SysV scripts, 401
  - usage, 401–403
- Webmin Web site, 50, 399
- WebSphere, 564
- Wildcards, 209
- Windows
  - 8.3 filenames, 430–431
  - attribute bits, 182–183
  - burning CD-Rs, 198–199
  - case-retentive filenames, 180
  - filename considerations, 430–432
  - generic PostScript driver, 190
  - long filenames, 430–432
  - My Network Places, 174
  - Network Neighborhood, 174
  - PostScript drivers, 188, 190
  - printer drivers, 186–187
  - profiles, 176–177
  - Samba, 168
  - short directory names, 432
  - SMB/CIFS (Server Message Block/
    - Common Internet Filesystem), 223
  - SMB/CIFS server software, 426
  - VNC clients, 364
  - VNC servers, 360–361
  - X servers, 356
- Windows 9x/Me
  - FAT (File Allocation Table) filesystem, 430
  - internal security model, 183
  - MAC addresses, 124
  - TCP/IP Control Panel, 178
- Windows 2000
  - MAC addresses, 124
  - System Properties dialog box, 178
- Windows clients
  - backups from Linux, 426–423
  - setting time, 255
- Windows NT/2000/XP
  - ACLs (Access Control Lists), 183
  - FAT (File Allocation Table) filesystem, 430
  - internal security model, 183
- Windows PPTP clients, 699–701
- WINIPCFG program, 124
- WINS (Windows Internet Name Service)
  - servers, 130, 173–174
- Wireless devices and networks, 20–21
- Wireless LAN (Non-Hamradio) submenu,
  - 21, 22
- Wireless Tools, 21
- Word processors, 563
- WordPerfect, 563
- WordPerfect 8, 390
- WordPerfect Office 2000, 389
- Workgroups, 170
  - NetBEUI, 75
  - NetBIOS, 176
- World Wide Web, 12
- wrapping and unwrapping data, 66–67
- Writing CGI Applications with Perl*, 528
- WU-FTPD (Washington University FTP
  - Daemon), 579
    - anonymous options, 594–595
    - configuring, 581–585
    - user class, 582–583
- WWW (World Wide Web), 527
- WYSIWYG (what-you-see-is-what-you-get)
  - printing, 373
- X (X Window System), 7, 68, 335, 370
  - bitmapped fonts, 376
  - client programs, 338
  - client/server relationship, 338–341

- configuring access, 337–348
  - font path, 372
  - fonts, 372
  - network operations, 360
  - remote-login access, 347–348
  - runlevel, 354
  - server programs, 338
  - tunneling connections through SSH, 345
- X clients, 340, 344–345, 347
- X Display Manager, 163
- X font server, 387
- X programs
  - DISPLAY environment variable, 345
  - network protocols, 337–338
  - running, 347
- X servers, 340–341
  - as client, 338–339
  - configuring, 339–340
  - configuring to accept X client access, 341–345
  - GUI display device, 338
  - input devices, 338
  - MacOS, 356
  - non-UNIX systems, 341
  - operating systems, 340
  - running on VNC server system, 359–360
  - setting client options to use, 334–335
  - starting, 347, 348
  - starting servers, 100
  - text-mode remote login client, 345
  - transferring authorization key to, 342–343
  - as VNC server, 362
  - Windows, 356
  - xauth program, 342–344
  - xhost program, 341
- X terminals, 336, 340
- xauth program, 342–344, 349
- .Xauthority file, 342–343
- xclock program, 345
- xdm program, 163
  - adjusting availability, 350–351
  - configuration, 350–352
  - displays managed by, 351–352
  - /etc/X11/xdm/Xaccess file, 350–351
  - /etc/X11/xdm/xdm-config file, 350
  - /etc/X11/xdm/Xservers file, 351
  - .xsession files, 350
- XDMCP (X Display Manager Control Protocol), 348
  - GDM (GNOME Display Manager), 350
  - listing available, 357
  - remote logins, 350
- XDMCP clients
  - configuring, 355–357
  - indirect query, 351
  - initial connection to XDMCP server, 356–357
- XDMCP servers, 348–357
  - default, 354–355
  - GDM, 353
  - KDM, 350, 352–353
  - operation, 349
  - remote logins, 350
  - runlevels, 354
  - running, 354–355
  - running in VNC, 367–369
  - session types displayed for users, 352–353
  - startup scripts, 355
  - SysV startup scripts, 355
  - XDM (X Display Manager), 350–352
- XF86Config file, 372, 381, 384
- xfer-auth file, 343
- XFree86, 340, 372
  - PCF fonts, 376
  - TrueType fonts, 379
- XFree86.xfs package, 379
- XFS, 285
- xfs package, 379
- xfst font server, 380
- xhost program, 341
- xinetd, 367–368, 421
  - access control features, 98–100
  - chkconfig, 86
  - connection load limits, 98
  - cups-lpd program, 236
  - disabling servers, 97
  - editing configuration files, 92
  - /etc/xinetd.conf file, 96
  - host-based restrictions, 99
  - Linuxconf, 394–395
  - logging, 97–98
  - redirection, 97
  - rlogind server, 315
  - security, 421
  - security features, 97
  - server control files, 96
  - server definition, 96–98
  - servers, 99
  - startup script status, 85
  - SysV startup script, 98
  - temporal restrictions, 99

## INDEX

- X-ISP Web site, 52
- XLFD (X Logical Font Descriptor), 386–387
- xlock program, 164
- Xmanager for Windows, 340, 355
- xntpd program, 245–246
- xntpd program, 246
- xscreensaver, 161, 164
- .xsession files, 332, 350
- Xsession script, 350, 353
- Xsession.d directory, 353
- Xtools for MacOS X, 340
- Xvnc, 361, 364–366
- Xvnc-help.txt file, 366
- YaST (Yet Another Setup Tool), 33, 50, 104–106, 601
- YaST2, 33, 50, 104–106
- Zebra, 658
- Zeus, 531
- Zone configuration file, 466–467
- Zone files, 468–470
- Zones, 462–464, 468