



Index

Symbols and Numbers

. (period), 65–66
 / (slash), 65
 : (colon), 65
 [] (square brackets), 65
 ~ (tilde), 82
 <> (angle brackets), 65, 82
 = (equals sign), 82
 0 (success) status class, 234
 1 (redirection), status classes, 234
 10Gb link support, 215
 2 (initiator error), status classes, 234
 3 (target error), status classes, 234
 3DES, 185
 40Gb link support, 215

A

A (acknowledge bit), 269

Abort Task function
 error recovery level 0 and, 159
 overview of, 154
 task management function request
 PDU, 281–284
 task management function response
 PDU, 286–288

Abort Task Set function
 execution of, 283–284
 overview of, 154
 task management function request
 PDU, 281
 task management function response
 PDU, 286–288

ACA (auto contingency allegiance), 151, 154, 282

Access control lists (ACLs)
 discovery process and, 174
 SLP and, 177

Access controls, 144–146

ACK (acknowledgement), 109

Acknowledge bit (A), 269

Acknowledgement (ACK), 109

ACLs (access control lists)
 discovery process and, 174
 SLP and, 177

Acronyms, list of, 317–321

Adaptec, 46

Additional header segments (AHS)
 AHSLength, 259–261
 AHSType, 259–261
 overview of, 58–60, 259–261

Addressing, iSCSI, 63–68. *see also* IP addresses

Administration, iSCSI networks, 212–213

Administrative approach, to discovery, 172–173

Advanced technology attachment (ATA) drives
 home offices using serial, 17–18
 storage with, 1

AES (Advanced Encryption Standard), 186

AES in CBC MAC mode with XCBC extensions, 186

AHS (additional header segments), 58–60, 259–261

AHSLength, 259–261

AHSType, 259–261

- Alacritech, 47
 - Algorithms, security, 185
 - Aliases, 313
 - angle brackets (<>), 65, 82
 - Application layer, 53–55
 - Architecture, iSCSI, 139–150
 - access controls and, 144–146
 - initiator nodes, 139
 - initiator ports, 139–140
 - naming initiator and target nodes, 141
 - naming ports, 141–143
 - naming target ports, 142–144
 - portals, 141
 - target nodes, 141, 146–147
 - wedge drivers and, 144
 - AsyncEvent, 221
 - Asynchronous message PDU, 220–223
 - AsyncVCode, 221
 - At-distance environments, 31–33, 209
 - At-distance interconnect, 215
 - ATA (advanced technology attachment) drives
 - home offices using serial, 17–18
 - storage with, 1
 - ATTR (task attributes), 258
 - Authentication
 - IKE and, 182
 - IPSec and, 185
 - peer authentication, 186
 - Authentication login routines
 - discovery sessions, 88
 - introduction, 72–73
 - iSCSI sessions, 81
 - keywords and, 83
 - AuthMethod, 298
 - Auto contingency allegiance (ACA), 151, 154, 282
- B**
- Backup tape drives
 - high-end environments and, 27
 - satellite environment and, 31
 - Backups, iSCSI networks, 213–214
 - Base64-constant, 310–311
 - Basic Input Output Service (BIOS), 172
 - BegRun, 278
 - BHS (basic header segment)
 - markers and, 195
 - PDU structure and, 58–60
 - Bidirectional Expected Read-Data Length AHS, 261
 - Bidirectional Read Residual Count, 265
 - Binary-value, 311
 - BIOS (Basic Input Output Service), 172
 - BIS (Boot Integrity Services), 172
 - Bit encodings, 309–311
 - Boolean negotiations, 98–99
 - Boolean-value, defined, 310
 - Boot Integrity Services (BIS), 172
 - Boot process, 171–172
 - Bridge boxes, 35
 - Buffer management
 - command windowing and, 123–124
 - eddy buffers, 196
 - Buffer Offset
 - R2T PDU, 251–252
 - SCSI Data-In PDU, 272
 - SCSI Data-Out PDU, 274–275
 - Bus, SCSI, 1–4
- C**
- C (continue) bit
 - login request PDU, 225
 - login response PDU, 232
 - text request PDU, 94, 290
 - text response PDU, 94, 294
 - Campus, high-end environment, 27–30
 - Case sensitivity, login keywords, 81
 - Cat 5 cables, 7–8
 - CDBs (command description blocks)
 - defined, 1
 - Ethernet transport encapsulation and, 51–52
 - Extended CDB, 260
 - SCSI Command Request PDU and, 259
 - SCSI commands carried in, 49–50
 - tasks and, 151
 - Central environment, high-end environments, 33–35, 209
 - Certification, 182
 - CHAP (Challenge Handshake Authentication Protocol), 81, 184, 187
 - Characters, 309–311
 - Checksums, CRC Digests, 61–63
 - CID (connection ID)
 - defined, 313
 - login request PDU, 75, 228

- logout request PDU, 238–239
 - nonleading login process and, 86
 - session establishment, 107–108
 - session login process, 103
 - table of values, 230
 - CIFS (Common Internet File System), 11
 - Cisco, 45–46
 - Clear ACA function, 154, 282
 - Clear Task Set function, 154–155, 282, 285
 - CmdSN (command sequence number)
 - error recovery process and, 163
 - ExpCmdSN and, 120
 - list of PDUs containing, 121, 136
 - login request PDU, 76, 119–120, 228–229
 - login response PDU, 78
 - logout request PDU, 238
 - nonleading login process, 86
 - NOP-Out PDU and, 248
 - overview of, 109–111
 - SCSI Command Request PDU, 259
 - task management function request PDU, 282, 283
 - text request PDU, 291
 - colon (:), 65
 - Command data (data segment), 261
 - Command queue entry (CQE), 125–126
 - Command sequence number. *see* CmdSN (command sequence number)
 - Command windowing
 - buffer consumption and, 123
 - overview of, 136
 - relationship of MaxCmdSN to ExpCmdSN, 122–123
 - TCP/IP connection windowing and, 123
 - Commands
 - data and status related to, 132
 - description blocks. *see* CDBs (command description blocks)
 - immediate vs. nonimmediate, 119–120
 - iSCSI sessions and, 56–57
 - linked as single task, 152
 - order of, 119–122
 - SCSI, 49–50
 - SCSI bus, 1
 - sequence numbers. *see* CmdSN (command sequence number)
 - task management, 156
 - text. *see* Text commands
 - Common Internet File System (CIFS), 11
 - Companion processes
 - boot process, 171–172
 - discovery using administrative specifications, 172–173
 - discovery using iSNS, 179–182
 - discovery using SendTargets, 173–175
 - discovery using SLP, 176–179
 - MIB and SNMP, 187–188
 - overview of, 171
 - security, 182–187
 - Company id values, 64
 - Confidentiality, IPSec, 185
 - Connection
 - allegiance, 107
 - defined, 313
 - failure recovery, 158
 - session management, 106–108
 - windowing, 123
 - Connection ID. *see* CID (connection ID)
 - Connection points, 141
 - Continue bit. *see* C (continue) bit
 - CQE (command queue entry), 125–126
 - CRC-detected errors
 - as error class, 157
 - ErrorRecoverylevel=1, 160–161
 - recovering from, 158
 - CRC digests
 - checksums and, 61–63
 - PDU structure and, 59–60
 - resending data or status, 112–117
 - value of, 196
 - CSG (current stage) field
 - login authentication and, 83–85
 - login request PDU, 77, 225
 - login response PDU, 232
 - Cyclic redundancy check. *see* CRC digests; CRC-detected errors
- ## D
- DA (directory agent), SLP, 176–178
 - Data
 - options for unsolicited, 304
 - related commands and status, 132
 - resending, 112–117
 - sequencing, 108–112
 - travel directions for read or write, 108

- Data digests
 - errors, 161
 - login authentication, 84–86
 - overview of, 299
 - PDU structure and, 58–60
 - protecting Data part of PDU headers, 62–63
 - recovery, 165–166
- Data-In PDUs
 - data placement with, 134–135
 - read data travel direction, 108
 - resending data or status, 112–117
 - sequence numbers for, 109
- Data ordering
 - DataPDUInOrder and
 - DataSequenceInOrderan, 129–132
 - FirstBurstLength, MaxBurstLength, and MaxRecvDataSegmentLength, 127–129
 - MaxCmdSN (maximum CmdSN), 131
 - R2T data and, 131
 - score boarding arrived data, 130
- Data-Out PDUs
 - resending data or status, 113–114
 - sequence numbers for, 109
 - write data travel direction, 108
- Data segments, 59, 261. *see also*
 - DataSegment
- Data sequence number. *see* DataSN (data sequence number)
- Data SNACK
 - DataACK, 277–280
 - level 1 errors and, 161
 - R2T, 276–277
- DataACK, 277–280
- Databases, 20–21
- DataPDUInOrder
 - data out order, 252, 274–275
 - negotiated value of, 129–132
 - overview of, 137, 299
- DataSegment
 - Reject PDU and, 255
 - SCSI Data-In PDU, 272
 - SCSI Data-Out PDU, 275
 - text request PDU, 291
 - text response PDU, 295
- DataSegment (ping data), 249
- DataSegment (sense and response data), 266
- DataSegment (text-login parameters)
 - asynchronous message PDU, 224
 - login request PDU, 229
 - login response PDU, 236
 - NOP-In PDU, 246
- DataSegmentLength
 - asynchronous message PDU, 221
 - login request PDU, 225–226
 - login response PDU, 233
 - NOP-In PDU, 245
 - NOP-Out PDU, 248
 - Reject PDU, 254
 - SCSI Command Request PDU, 258
 - SCSI Command Response PDUs, 264
 - SCSI Data-In PDU, 270
 - SCSI Data-Out PDU, 273–274
 - text request PDU, 290
 - text response PDU, 294
- DataSequenceInOrder
 - consecutive R2Ts and, 252
 - negotiated value when sending data, 130–132
 - overview of, 137, 299
 - SCSI Data-Out PDU, 275
- DataSN (data sequence number)
 - overview of, 111–112
 - Reject PDU, 255, 256
 - SCSI Data-In PDU, 271
 - SCSI Data-Out PDU, 274
- Date field, naming formats, 64
- DDP (direct data placement)
 - IETF and, 199
 - iSCSI performance and, 215
 - ITT and, 126, 136–137
- DDs (discovery domains), 179
- Decimal-constant, defined, 310
- DefaultTime2Retain, 167, 299
- DefaultTime2Wait, 160, 167, 299–300
- Definitions, in glossary, 313–316
- Desired data transfer length, R2T PDU, 251
- Desktop computers
 - ATA hard drives and, 1
 - campus companies, 29–30
 - iSCSI for, 7–8
 - midrange companies, 25, 29–30
- Development history, iSCSI, 210–211

- DHCP (Dynamic Host Connection Protocol)
 - boot process, 171
 - discovery process, 178
 - Digests. *see also* CRC digests; Data digests; Header digests
 - defined, 59
 - support for, 224
 - Direct data placement. *see* DDP (direct data placement)
 - Direct Memory Accessing (DMAing), 125
 - Direct memory placement, 194
 - Directory agent (DA), SLP, 176–178
 - Disaster preparation, iSCSI networks, 213–214
 - Discovery domains (DDs), 179
 - Discovery process
 - administrative approach, 173
 - iSNS, 179–182
 - SendTargets, 173–175
 - SLP, 176–179
 - Discovery session
 - defined, 73
 - overview of, 88–90
 - Distance limitations, SCSI bus, 3
 - DMAing (Direct Memory Accessing), 125
 - DNS (Domain Name Service), 64–65
 - Dual dialect storage server systems, 22
 - Dynamic Host Connection Protocol (DHCP)
 - boot process, 171
 - discovery process, 178
- E**
- Eddy buffers, 196
 - Edge connect devices, 214
 - Effective maximum segment size (EMSS), 199–200
 - EMSS (effective maximum segment size), 199–200
 - EN (enterprise number), 226–227
 - Encapsulating Security Payload (ESP), 185
 - Encryption, 184, 185
 - Endpoints, 182, 183
 - Engineering environments, file sharing in, 21
 - Enterprise number (EN), 226–227
 - Enterprise unique identifier (EUI), 63, 64, 67
 - Environments, iSCSI, 206–210
 - high-end, 208–209
 - midrange, 207
 - SoHo, 206–207
 - equals sign (=), 81–82
 - Error handling, 157–169
 - classes of detected errors, 157
 - hierarchy of error recovery, 158
 - recovery level 0, 159–160
 - recovery level 1, 160–166
 - recovery level 2, 166–168
 - recovery level keys and values, 300
 - recovery techniques, 158–159, 194–195
 - ErrorRecoverylevel=0
 - overview of, 159–160
 - session restart and, 158
 - summary of, 168
 - ErrorRecoverylevel=1, 160–166
 - CRC failure and, 158
 - DataDigest recovery, 165–166
 - HeaderDigest recovery at initiator side, 161–163
 - HeaderDigest recovery at target side, 163–165
 - recovery approaches in, 160–161
 - summary of, 168–169
 - ErrorRecoverylevel=2
 - connection failure recovery, 158
 - overview of, 166–168
 - summary of, 169
 - ESP (Encapsulating Security Payload), 185
 - Ethernet
 - 10Gb and 40Gb link support, 215
 - home office systems and, 16
 - iSCSI desktop and laptop computer and, 7–8
 - iSCSI-related protocol layers and, 53–55
 - protection by CRC-32, 61–63
 - EUI-64 (extended unique identifier)
 - format, 64
 - Eui (enterprise unique identifier), 63, 64, 67

- ExpCmdSN
 - asynchronous message PDUs, 221
 - CmdSN and, 120
 - error recovery process and, 163
 - login response PDUs, 77–78, 233–234, 242
 - MaxCmdSN and, 123
 - NOP-In PDUs, 246
 - overview of, 109–111
 - PDUs returned on, 121–122, 136
 - R2T PDUs, 251
 - Reject PDUs, 255
 - SCSI Command Response PDUs, 265
 - SCSI Data-In PDUs, 271
 - task management function response PDUs, 287
 - text response PDUs, 295
- ExpDataSN
 - overview of, 112
 - Reject PDUs, 256
 - SCSI command response PDUs, 265
 - task management function request PDUs, 283
- Expected command sequence number. *see* ExpCmdSN
- Expected data sequence number. *see* ExpDataSN
- Expected Data Transfer Length field, 258–259
- Expected status sequence number. *see* ExpStatSN
- ExpStatSN
 - error recovery process and, 163
 - login request PDU, 76, 229
 - logout request PDUs, 238
 - NOP-Out PDUs, 249
 - overview of, 110
 - resending data or status, 113
 - SCSI Command Request PDUs, 259
 - SCSI Data-Out PDUs, 274
 - SNACK request PDUs, 277
 - task management function request PDUs, 282
 - text request PDUs, 291
- Extended CDBs, 260. *see also* CDBs (command description blocks)
- Extended unique identifier (EUI-64)
 - format, 64
- F
- F (final) bit
 - SCSI Command Request PDU, 257
 - SCSI Data-In PDU, 269
 - SCSI Data-Out PDU, 273
 - text request PDU, 94, 99–100, 290
 - text response PDU, 94, 99–100, 294
- FC (Fibre Channel)
 - central sites including, 34
 - compared with iSCSI, 8–9, 206, 215
 - iSCSI development and, 210–211
 - iSCSI outselling, 36
 - iSNS and, 181–182
 - overview of, 5–7
 - storage controllers, 123–124
 - TOE chips and, 24–25
 - wedge drivers, 144, 147–149
- FFP (full-feature phase)
 - CmdSN and, 119
 - defined, 72
 - login authentication and, 83–85
 - negotiation flow rules, 101
 - sessions and, 106
- Fibre Channel. *see* FC (Fibre Channel)
- File servers
 - NAS and, 11
 - small offices and, 18
- File sharing
 - home offices, 16–17
 - SCSI bus and, 3–4
 - small offices, 21–22
- FIM (Fixed Interval Marking)
 - header digest recovery and, 161
 - marker implementation, 197
 - overview, 195–196
 - overview of, 61
 - pointers, 196–197
 - synchronization, 197–198
 - TUF/FIM combination, 201–202
- Final bit. *see* F (final) bit
- FirstBurstLength
 - limit on session-wide data, 127–129
 - overview of, 137, 300
- Fixed Interval Marking. *see* FIM (Fixed Interval Marking)
- FQDN (fully qualified domain name)
 - vs. address resolution, 66–67
 - defined, 64
 - reverse name format vs., 65

- Full-feature phase. *see* FFP (full-feature phase)
- Fully qualified domain names. *see* FQDN (fully qualified domain name)
- Function. *see* Task management
- Future, of iSCSI, 210–211
- H**
- Hard disk drives. *see* HDDs (hard disk drives)
- Hashed Message Authentication (HMAC-SHA-1), 185
- HBAs (host bus adapters)
 - boot process and, 172
 - buffer control on, 124–126
 - central sites use of, 33–34
 - comparing iSCSI with FC, 9
 - cost of, 26
 - functioning of iSCSI and, 49–50
 - ISID and, 105–106
 - login process and, 87
 - midrange companies use of, 23–24
 - session-wide vs. connection-specific values, 127
 - TOE integration on, 60–61
- HDDs (hard disk drives)
 - assigning logical or physical, 16
 - ATA, 1
 - SCSI bus and, 1–5
- Head of queue, 151
- Header digests
 - errors, 161
 - login authentication phase, 84–86
 - overview of, 300
 - PDU structure and, 58–60
 - protecting PDU headers, 62–63
 - recovery at initiator side, 161–163
 - recovery at target side, 163–165
- Hex-constant, defined, 310
- Hexadecimal numbers, 82
- High-end environments, 27–35
 - at-distance locations, 31–33, 209
 - campus, 27–30, 208
 - central location, 33–35, 209
 - cohabitation of FC and iSCSI, 27
 - latency in, 27
 - satellite locations, 30–31, 208–209
- History, iSCSI, 41–48, 47–48
 - chronology of, 47–48
 - Cisco and IBM’s joint effort, 45
 - end of story, 46–47
 - IEFT and, 45–46
 - measurements, 43–45
 - SCSI over TCP/IP and, 41–45
- History, SCSI. *see* SCSI (Small Computer System Interface), background of
- HMAC-SHA-1 (Hashed Message Authentication), 185
- Home office environments
 - campus similarities to, 29
 - Ethernet in, 16
 - file sharing in, 16–17
 - list of, 206–207
 - purchasing software for, 16
 - serial ATA drives in, 17–18
- Host bus adapters. *see* HBAs (host bus adapters)
- Host systems
 - converting storage connections, 34
 - home office, 16–17
- I**
- I (immediate bit)
 - logout request PDU, 237
 - NOP-Out PDU, 248
 - text request PDU, 290
- I-T nexus state
 - consequences of, 307
 - defined, 306
 - overview of, 307
 - SCSI nexus and, 147–148
- IBM
 - development of iSCSI, 46–47, 210
 - file servers, 11
 - history of iSCSI and, 41–45
- IEEE naming, 64
- IETF (Internet Engineering Task Force)
 - authentication protocols, 81
 - DDP and RDMA and, 199
 - history of iSCSI and, 45–47
 - iSCSI development and, 7, 210–211
 - as last word, 219
- IFMarker, 300
- IFMarkInt, 300–301

- IKE (Internet Key Exchange)
 - combined with IPSec, 182
 - iSCSI sessions and, 80
 - peer authentication with, 186
 - references, 326–327
- Immediate bit. *see* I (immediate bit)
- Immediate commands, 119–120, 153
- ImmediateData, 301
- InitialR2T, 301
- Initiator error status class, 234–235
- Initiator nodes, iSCSI, 141
- Initiator ports, iSCSI sessions, 103
- initiator session ID. *see* ISID (initiator session ID)
- initiator task tag. *see* ITT (initiator task tag)
- InitiatorAlias, 301
- InitiatorName, 301
- Intel, 46
- Intellectual property rights (IPRs), 81
- Internet Engineering Task Force. *see* IETF (Internet Engineering Task Force)
- Internet Key Exchange. *see* IKE (Internet Key Exchange)
- Internet Protocol. *see* IP (Internet Protocol)
- Internet SCSI. *see* iSCSI
- Internet Storage Name Service. *see* iSNS (Internet Storage Name Service)
- Intranets. *see* LANs (local area networks)
- IP addresses
 - addressing conventions, 65–67
 - boot process and, 172
 - discovery process and, 173–174
- IP (Internet Protocol)
 - comparing FC with IP networks, 5–7
 - overview of, 52–53
- IP SAN (IP storage area network), 174
- IP Security (IPSec)
 - built into iSCSI, 11
 - combined with IKE, 182
 - references, 326–327
- IP Storage (ips) workgroup, 46
- IPRs (intellectual property rights), 81
- ips (IP Storage) workgroup, 46
- IPSec (IP Security)
 - built into iSCSI, 11
 - combined with IKE, 182
 - references, 326–327
- iqn (iSCSI qualified names), 63, 65, 67
- iSANs, 25–26
- iSCSI, 49–70
 - addressing and naming conventions, 63–68
 - architecture. *see* architecture, iSCSI
 - checksums and CRC Digests, 61–63
 - client network entity, 314
 - devices, 313
 - environments, 206–209
 - future of, 210–211
 - history of. *see* History, iSCSI
 - I-T-L nexus, 147
 - mappings, 306–307
 - names, 314
 - network management. *see* Network management, iSCSI
 - nodes, 314
 - overview, 68–69, 205–206
 - PDU structure, 58–60
 - portals, 141
 - protocol layers related to, 52–55
 - RDMA. *see* RDMA (remote direct memory access)
 - references, 323–326
 - SCSI commands and, 49–50
 - server network entity, 314
 - sessions, 56–57
 - storage controllers, 123–124
 - summary conclusions, 216–218
 - tasks, 314
 - TCP/IP and, 50–52
 - TOE integration on chip or HBA, 60–61
 - transfer direction, 108, 314
- iSCSI, advantages, 7–11, 15–40
 - compared with Fibre Channel, 8–9, 36
 - cost reduction, 7, 9–10
 - desktop and laptop deployment, 7–8
 - at distance tape backup, 9–10
 - high end environments, 26–35
 - home office environments, 15–18
 - latency, 9
 - midrange environments, 23–26
 - security features, 11
 - small office environments, 18–23
 - summary of, 36–39

- iSCSI initiator
 - command sequence, 119–120
 - names, 313
 - nodes, 139, 141, 313
 - ports, 139–143, 313
 - iSCSI layer, 313
 - iSCSI-local-name-value, 310
 - iSCSI-name-value, 310
 - iSCSI qualified names (iqn), 63, 65, 67
 - iSCSI target
 - in-order delivery requirements of, 121
 - nodes, 139, 141, 146–147, 314
 - ports, 142–144, 313
 - iSER, 216
 - ISID (initiator session ID)
 - defined, 314
 - error recovery level 0 and, 160
 - login request PDU, 76, 226–227
 - login response PDU, 79, 233
 - naming initiator nodes and ports, 141–142
 - nonleading login process, 86
 - overview of, 103–106
 - rule, 307
 - SSID and, 107
 - table of values, 230
 - iSNS (Internet Storage Name Service)
 - boot process and, 171
 - discovery process and, 179–182
 - storage management and, 35
 - ITT (initiator task tag)
 - data placement with, 136–137
 - HBA buffer control, 124–126
 - login request PDU, 75–76, 228
 - login response PDU, 75–76, 233
 - logout request PDU, 238
 - logout response PDU, 242
 - NOP-In PDU, 245
 - NOP-Out PDU, 248
 - R2T PDU, 251
 - relating data to appropriate commands, 132–133
 - SCSI Command Request PDU, 258
 - SCSI Command Response PDUs, 264
 - SCSI Data-In PDU, 271
 - SCSI Data-Out PDU, 274
 - SNACK request PDU, 277
 - task management function request PDU, 282
 - task management function response PDU, 287
 - text request PDU, 94–95, 290
 - text response PDU, 94–95, 294
 - untagged tasks and, 152
- J**
- JBODs (just a bunch of disks), 19
- K**
- Kerberos version 5, 81, 184
 - Key, defined, 309
 - Key-name, defined, 309
 - Key pairs, security, 182–183
 - Key=list, 82
 - Key=value pairs. *see also* Text commands
 - definitions, 309–311
 - iSCSI keywords, 81
 - login authentication, 86–87
 - login keywords, 82
 - login PDUs and, 83
 - Keywords. *see also* Text commands
 - login keywords, 72, 81–88
 - session establishment and, 74
 - values and, 297–304
- L**
- LAN Manager, 11
 - LAN Server, 11
 - LANs (local area networks), 7
 - Laptop computers
 - ATA hard drives, 1
 - company environments and, 29–30
 - iSCSI for, 7–8
 - iSCSI software device drivers, 25
 - Large-binary-value, defined, 311
 - Large numerical-value, defined, 311
 - Latency
 - high-end environments and, 26–27
 - iSCSI partnering with VPN, 31
 - iSCSI vs. Fibre Channel, 9
 - midrange environments and, 24
 - Leading login process, 86
 - Link failures, 158
 - Linked commands, 152
 - List-of-values, 311
 - Load balancing, 132
 - Local area networks (LANs), 7, 11
 - Logical connections, Fibre Channel, 5

- Logical portals, 87
- Logical unit number. *see* LUN (logical unit number)
- Logical Unit Reset function, 155, 282
- Logical units. *see* LUs (logical units)
- Login operational negotiation phase (LONP), 74
- Login process, 71–92
 - introduction to, 71–73
 - iSCSI sessions and, 103
 - keywords, 81–88
 - login request PDU, 75–77, 224–230
 - login response PDUs, 77–79, 233, 242
 - session establishment and, 73–74
 - as single immediate command, 119
 - summary of, 90–91
- Login request PDU
 - CmdSN and, 119–120
 - login process and, 75–77
 - overview of, 224–230
 - session establishment and, 75–77
- Login response PDU
 - authentication phase and, 83–85
 - overview of, 231–236
 - session establishment and, 77–79
- Logout request PDU, 237–240
 - implicit termination of tasks, 240
 - notes on, 238–239
 - overview of, 237–238
- Logout response PDU, 241–243
- LONP (login operational negotiation phase), 74
- LUN (logical unit number)
 - asynchronous message PDU, 221
 - boot process and, 172
 - defined, 2
 - Ethernet transport encapsulation and, 51–52
 - in-order delivery and, 121
 - NOP-In PDU, 245
 - NOP-Out PDU, 248
 - SCSI Command Request PDU, 258
 - SCSI Data-In PDU, 271
 - SCSI Data-Out PDU, 274
 - SNACK request PDU, 277
 - task management function request PDU, 282
 - text request PDU, 290
 - text response PDU, 294
- LUs (logical units)
 - defined, 2
 - in-order delivery and, 121
 - iSCSI-related protocol layers and, 53–55
 - multiple SCSI devices and, 139
- M**
- Main memory placement, 194–195
- Man in the middle attacks, 182
- MAN (metropolitan area networks), 31
- Management
 - buffer management, 123–124, 196
 - FC networking vs. IP networking, 5–7
 - iSCSI networks. *see* Network management, iSCSI
 - resources, 123–124
 - sessions. *see* Sessions, managing
 - software for, 35
 - tasks. *see* Task management
- Management Information Base (MIB), 187–188
- Markers, FIM
 - implementing, 197–198
 - missing TCP segments and, 195
 - pointers, 196–197
- Max difference, serial numbers, 219
- MaxBurstLength
 - data payload limits and, 127–128
 - error recovery and, 164–165
 - overview of, 137, 301
- MaxCmdSN
 - asynchronous message PDU, 221
 - command windowing and, 122
 - ExpCmdSN and, 123
 - login response PDU, 234
 - logout response PDU, 242
 - NOP-In PDU, 246
 - overview of, 110–111
 - R2T PDU, 251
 - Reject PDU, 255
 - SCSI Command Response PDUs, 265
 - SCSI Data-In PDU, 271
 - task management function response PDU, 287
 - text response PDU, 295
- MaxConnections, 302
- Maximum CmdSN. *see* MaxCmdSN
- MaxOutstandingR2T, 131, 302

- MaxRecvDataSegmentLength
 - data payload limits and, 127–128
 - missing TCP segments and, 195
 - overview of, 137, 302
- Mb/s (megabit-per-second), 7
- MC/S (multiple connections per second)
 - compared with wedge drivers, 147–149
 - defined, 34
 - enabling for iSCSI sessions, 56
 - iSCSI development and, 210
- Measurements, history of iSCSI, 42–45
- Megabit-per-second (Mb/s), 7
- Memory. *see also* RDMA (remote direct memory access)
 - direct memory placement and, 194
 - DMAing (Direct Memory Accessing), 125
 - main memory placement, 194–195
 - TOE integration on HBAs and, 60–61
- Metropolitan area networks (MANs), 31
- MIB (Management Information Base), 187–188
- Microsoft file servers, 11
- Midrange environments, 23–26
 - campus similarities to, 29
 - dedicated server systems in, 23
 - desktops and laptops in, 25
 - iSANs in, 25–26
 - iSCSI TOE chips in, 24
 - list of, 207
 - total cost of ownership, 24–25
- Mirroring, 214
- mode pages, SCSI, 308
- Multiple connections per second. *see* MC/S (Multiple Connections per second)
- Multiple SCSI devices, 139
- N**
- Names. *see also* FQDN (fully qualified domain name)
 - DNS (Domain Name Service), 64–65
 - InitiatorName, 301
 - iqn (iSCSI qualified names), 63, 65, 67
 - iSCSI, 63–68, 314
 - iSCSI initiator, 313
 - nodes, 63, 67
 - SCSI port name, 306, 313
 - target node names, 146
 - TargetName, 303
 - WWNs (world wide names), 181–182
- Naming authority field, login request PDU, 226–227
- NAS (network attached storage)
 - iSCSI capabilities with, 11
 - midrange companies and, 25
 - small offices and, 18–23
- Negotiation, text keywords, 95–102
 - failure rules, 101–102
 - flow rules, 99–101
 - key=value pair rules, 96–97
 - keyword value rules, 97–99
 - summary of, 102
- Network attached storage. *see* NAS (network attached storage)
- Network entity, 314
- Network File System (NFS), 11, 43–45
- Network interface cards. *see* NICs (network interface cards)
- Network management, iSCSI, 212–216
 - backup and disaster preparation, 213–214
 - ease of administration, 212–213
 - overview of, 212
 - performance, 215–216
- Network portal, 314
- Network storage, 205. *see also* SANs (storage area networks)
- Next stage field. *see* NSG (next stage) field
- NFS (Network File System), 11, 43–45
- NICs (network interface cards)
 - boot process and, 172
 - desktops and laptops and, 7–8
 - IP addresses and TCP ports and, 141
- Nishan Systems, 46, 182
- no-operation PDUs. *see* NOP (no-operation) PDU
- Nodes
 - initiator, 139, 141, 313
 - iSCSI, 314
 - naming, 63, 67, 146
 - target, 139, 141, 146–147, 314
- Nonimmediate commands, 119–120
- Nonleading logins, 86

- NOP (no-operation) PDUs
 - NOP-In PDU, 110–111, 113–114, 244–246
 - NOP-Out PDU, 110, 247–249
 - verifying network clogs, 120
- Novell file server, 11
- Nozzle, defined, 87
- NSG (next stage) field
 - authentication phase and, 83–85
 - login request PDU, 77, 225
 - login response PDU, 232
- Null encryption, 185
- Numbers, 309–311
- Numeric-range, defined, 311
- Numerical-value, defined, 311

- O**
- O (residual overflow bit), 270
- OFMarker, 302
- OFMarkInt, 302–303
- Ordered queueing, 151
- Originator, 315
- OUI, 226

- P**
- Parameter fields, asynchronous message PDU, 221–223
- PDUs (protocol data units), 219–296
 - asynchronous message PDU, 220–223
 - CmdSN and, 121
 - defined, 315
 - Ethernet transport encapsulation and, 51–52
 - ExpCmdSN and, 121
 - iSCSI-related protocol layers and, 54–55
 - login request, 75–77, 224–230
 - login response, 77–79, 231–236
 - logout request, 237–240
 - logout response, 241–243
 - NOP-In, 244–246
 - NOP-Out, 247–249
 - order processing errors and, 120–121
 - R2T, 250–252
 - recovering, 161
 - Reject, 253–256
 - SCSI Command Request, 257–261
 - SCSI Command Response, 262–267
 - SCSI Data-In, 268–272
 - SCSI Data-Out, 273–275
 - serial number arithmetic and, 219–220
 - SNACK request, 276–280
 - structure of, 58–60
 - task management function request, 281–284
 - task management function response, 285–288
 - text request, 93–95, 289–292
 - text response, 93–95, 293–296
 - wrapped in TCP segments, 205
- Peer to peer file sharing, 16–17
- Performance, iSCSI networks, 215–216
- period (.), 65–66
- Personnel training, Fibre Channel, 5–7
- Phase collapse, 110
- Physical portals, 87
- Ping, 120, 249
- Pooled storage
 - advantages of, 206
 - midrange companies and, 25
 - small offices and, 18
- Portal Group Tag, 315
- Portal Groups
 - defined, 315
 - login request PDU, 76
 - nonleading login process, 86
 - overview of, 87
- Portals
 - iSCSI architecture, 141
 - logical and physical, 87–88
 - login request PDU, 76
- Ports
 - initiator, 139–143, 305–306, 313, 316
 - naming, 141–144
 - numbers, 65–67
 - target, 103, 142–144, 306, 313
 - TCP/IP, 142
- Preboot Execution Environment (PXE), 172
- Privacy, 183
- Protocol data units. *see* PDUs (protocol data units)
- Protocol errors, 157
- Protocol layers, iSCSI, 52–55
- PXE (Preboot Execution Environment), 172

Q

Qualifier field, login request PDU, 226–227
 queuing order, task management, 151–152

R

R (read bit), 258
 R-Data SNACK, 277–279
 R2T (Ready To Transfer) PDU
 Data SNACK, 277
 InitialR2T, 301
 MaxOutstandingR2T, 131, 302
 overview of, 250–252
 Recovery R2T, 315
 resending data or status, 114
 sequence number of, 131, 251, 255
 TTT field and, 133
 R2TSN
 ordering R2T data, 131
 R2T PDU and, 251
 Reject PDU and, 255
 RADIUS, 184
 RAID (redundant array of independent disks)
 at-distance environments and, 32
 pooled storage and, 18–19
 RAM
 HBA requirements, 126
 TOE integration on HBAs and, 60–61
 RAS (remote access storage), 31–33
 RDMA (remote direct memory access)
 data placement with, 134–137
 IETF and, 199
 iSCSI RDMA, 134–135
 performance and, 215–216
 Read operations
 data sequencing, 114–115
 SCSI Data-In PDU and, 268–272
 travel directions, 108
 Reason codes
 logout request PDU, 237–238
 Reject PDU, 254
 Reassembly buffers, 196
 Recovery. *see* Error handling
 Recovery R2T, 315
 Redirection status class, 234–236

Redundant array of independent disks (RAID)

 at-distance environments and, 31
 pooled storage and, 18–19
 RefCmdSN, 282
 Referenced Task Tag, 282, 286
 Referenced task tag (RTT), 153
 References, 323–327
 basic iSCSI, 323–324
 indirect iSCSI, 326–327
 SCSI-related, 325
 security, 325–326
 Regular-binary-value, defined, 311
 Reject PDU, 253–256
 DataSegment, 255
 DataSegmentLength, 254
 DataSN, 255, 226
 ExpCmdSN, 255
 ExpDataSN, 256
 MaxCmdSN, 255
 R2TSN, 255
 Reason codes, 254
 StatSN, 255
 Remote access storage (RAS), 31–33
 Remote backup, 213
 Remote direct memory access. *see* RDMA (remote direct memory access)
 Request for Comment (RFC) number
 authentication protocols, 81
 iSCSI and IETF, 46–47
 Request PDUs. *see* Login request PDU; SCSI Command Request PDU; SNACK request PDU; Task management function request PDU
 Resegmentation, SNACK request PDU, 278–279
 Resending data or status, 112–117
 Residual Count
 SCSI Command Response PDU, 265
 SCSI Data-In PDU, 270, 272
 Residual overflow bit (O), 270
 Residual underflow bit (U), 270
 Resource management, 123–124
 Responder, defined, 315
 Response codes, SCSI Command Response PDU, 263

- Response data, SCSI Command Response PDU, 266
- Response PDUs
 - login. *see* Login response PDU
 - logout. *see* Logout response PDU
 - SCSI command. *see* SCSI Command Response PDU
 - task management function, Task management function response PDU
 - text. *see* Text response PDU
- Return codes, login response, 79
- RFC (Request for Comment) number
 - authentication protocols, 81
 - iSCSI and IETF, 46–47
- RTT (referenced task tag), 153
- RunLength, SNACK request PDU, 278

- S**
- S-ATA (serial ATA), 17–18
- S (status) bit, 270
- SA (service agent), SLP, 176–178
- SANs (storage area networks)
 - IP SANs, 174
 - iSANs, 25–26, 212
 - overview of, 5
 - satellite locations having own, 31
- Satellite locations, 30–31, 208–209
- Sawing, 7
- SCSI architecture, 305–308
 - consequences of, 306–307
 - I-T nexus state, 307
 - initiator ports, 140
 - parallel bus, 1
 - references, 325
 - SCSI devices, 139
 - SCSI-iSCSI mappings, 305–306
 - SCSI mode pages, 308
 - Service Delivery Subsystem, 140–141
 - target ports, 140
- SCSI Command Request PDU, 257–261
- SCSI Command Response PDU, 262–267
- SCSI Data-In PDU, 268–272
- SCSI Data-Out PDU, 273–275
- SCSI device
 - connection between host and, 139
 - defined, 315
 - multiple devices, 139
 - overview of, 305
- SCSI nexus
 - error recovery level 0 and, 160
 - I-T nexus state, 147–148, 306–307
 - iSCSI I-T-L nexus, 147
 - SCSI I-T nexus, 147–148
- SCSI ports
 - names, 306, 316
 - overview of, 103, 305–306
 - target ports, 306, 316
- SCSI (Small Computer System Interface), 1–14
 - background of, 11–13
 - bus interconnect, 1–4
 - class drivers, 53–55
 - Fibre Channel interconnect, 5–7
 - file servers, 11
 - initiators, 153
 - iSCSI interconnect, 7–11, 41–45, 49–50
 - layer, 315
 - summary, 11–13
- SCTP/IP (stream control transmission protocol), 215
- Secure Remote Password (SRP), 81, 84–85, 184
- Security, 182–187
 - ACLs, 187
 - authentication routines, 80–81
 - FC vs. iSCSI, 27–28
 - IPSec features, 184–186
 - login authentication phase and, 83–85
 - privacy and, 183
 - protocols for, 182–187
 - threats and, 182
 - trustworthiness and, 184
- Security negotiation phase (SNP), 74
- Selective negative acknowledgement request PDU. *see* SNACK request PDU
- SendTargets
 - discovery process and, 89–90, 173–175
 - iSCSI target node names and, 146
 - overview of, 303
 - text request/response PDUs, 95
- Sense data, 266. *see also* DataSegment
- SenseLength, 266

- Sequence numbers
 - command. *see* CmdSN
 - data. *see* DataSN
 - R2T, R2TSN
 - status, StatSN
- Serial number arithmetic, 219–220
- Serial sharing, 16
- Server-class systems, 8–9
- Server Message Block (SMB), 11
- Service agent (SA), SLP, 176–178
- Service Delivery Subsystem, SCSI, 140–141
- Service Location Protocol. *see* SLP (Service Location Protocol)
- Session identifier (SSID), 107, 316
- Sessions
 - defined, 315–316
 - FFP (full-feature phase) and, 106
 - introduction, 72
 - iSCSI, 56–57, 81
 - restarting after protocol errors, 157–160
 - single/multiple connection, 80–81, 120
- Sessions, establishing, 71–92
 - authentication routines and, 80–81
 - discovery sessions, 88–90
 - login keywords, 81–88
 - login process and, 71–74
 - login request PDUs, 75–77
 - login response PDUs, 77–79
 - summary, 90–91
- Sessions, managing, 103–118
 - connection establishment, 106–108
 - data travel direction, 108
 - initiator session ID, 103–106
 - overview of, 103
 - resending data or status, 112–117
 - sequencing, 108–112
 - summary, 117–118
- SessionType, 303
- Sharing files. *see* File sharing
- Simple Network Management Protocol (SNMP), 187–188
- Simple Public Key Mechanism (SPKM), 81, 184
- Simple queuing, 151
- Simple-value, defined, 311
- Single-connection sessions, 120
- slash (/), 65
- SLP (Service Location Protocol)
 - boot process and, 171
 - discovery process and, 176–179
 - iSCSI development and, 210–211
- Small Computer System Interface. *see* SCSI (Small Computer System Interface)
- Small office environments, 18–23
 - example of, 18
 - I/O requirements, 26
 - list of, 206–207
 - NAS and, 19–20
 - pooled storage in, 18–19
 - specialty software for, 20–21
- SMB (Server Message Block), 11
- SNACK request PDU, 276–280
 - error recovery level 1 and, 161
 - notes on, 279–280
 - overview of, 276–280
 - resegmentation, 278–279
 - resending data or status with, 112–117
- SNACK Tag
 - SCSI Command Response PDUs, 264
 - SCSI Data-In PDU, 269
- Snapshots, disaster preparation, 214
- SNIA (Storage Networking Industry Association), 46, 212
- SNMP (Simple Network Management Protocol), 187–188
- SNP (security negotiation phase), 74
- Socket, TCP/IP, 80
- Software
 - home offices, 16
 - small offices, 20–21
 - storage management, 35
- SoHo (Small office, Home office). *see* Home office environments; Small office environments
- SPKM (Simple Public Key Mechanism), 81, 184
- square brackets ([]), 65
- SRP (Secure Remote Password), 81, 84–85, 184
- SSID (session identifier), 107, 316
- Standard-label, defined, 309
- StatSN
 - asynchronous message PDU, 221
 - login response PDU, 77, 233
 - logout response PDU, 242

- StatSN (*cont.*)
 - NOP-In PDU, 245
 - overview of, 108–110
 - R2T PDU, 251
 - Reject PDU, 255
 - SCSI Command Response PDU, 265
 - SCSI Data-In PDU, 270
 - task management function response PDU, 287
 - text response PDU, 295
- Status
 - error recovery level 0 and, 159
 - linked commands and, 152
 - related commands and data, 132
 - resending, 112–117
 - SCSI Command Response PDU, 264
 - SCSI Data-In PDU, 270
- Status classes, login response, 234–236
 - 0 (success), 234
 - 1 (redirection), 234
 - 2 (initiator error), 234
 - 3 (target error), 234
- Status-Detail, 234–236
- Status (S) bit, 2670
- Status sequence number. *see* StatSN
- Status SNACK, 161, 277
- Steering. *see* Synchronization/steering
- Storage area networks. *see* SANs (storage area networks)
- storage controllers, 123–124
- Storage limitations, SCSI bus, 2–3
- Storage Networking Industry Association (SNIA), 46, 212
- Storage server systems, 22
- Stream control transmission protocol (SCTP/IP), 215
- Success status class, 234
- SUN file servers, 11
- Synchronization/steering
 - FIM markers, 196–197
 - FIM overview, 195–196
 - FIM synchronization, 197–198
 - main memory placement, 194–195
 - marker implementation, 197
 - techniques for, 193–194
 - TUF/FIM combination, 201–202
 - TUF header, 200
 - TUF overview, 199–200
 - TUF pros and cons, 200–201
- T
 - T (transit) bit, 77, 225, 232
 - T (type) field, 226–227
 - Tagged tasks, 151, 152
 - Tape backup, 9–10
 - Tape libraries
 - accessing, 27
 - at-distance environments and, 32
 - satellite locations and, 32
 - Target Cold Reset function, 155, 282, 284
 - Target error status class, 234–235
 - Target nodes, 139, 141, 146–147, 314
 - Target portal group tag. *see* TPGT (target portal group tag)
 - Target ports
 - iSCSI, 103, 313
 - naming, 142–144
 - SCSI, 306, 316
 - Target session identifying handle. *see* TSIH (target session identifying handle)
 - Target task tag. *see* TTT (target task tag)
 - Target Warm Reset function, 155, 282, 284
 - TargetAddress, 303
 - TargetAlias, 303
 - TargetAuth, 299
 - TargetName, 303
 - Targets. *see also* SendTargets
 - in-order delivery requirements of, 121
 - nodes, 139, 141, 146–147, 314
 - ports, 103, 142–144, 306, 313, 316
 - TTT (target task tag) and, 133–134
 - Task attributes (ATTR), 258
 - Task management, 151–156
 - Abort Task function, 154
 - Abort Task Set function, 154
 - Clear ACA function, 154
 - Clear Task Set function, 154–155
 - controlling untagged tasks with ITTs, 152
 - error recovery process and, 166
 - immediate commands, 153
 - invoking management functions, 153
 - key commands, 156
 - linked commands, 152
 - Logical Unit Reset function, 155
 - queueing order and, 151–152
 - Target Cold Reset function, 155

- Target Warm Reset function, 155
- Task Reassign function, 155–156
- Task management function request PDU
 - error recovery process and, 166–167
 - overview of, 281–284
 - RTT (referenced task tag), 153
- Task management function response PDU, 285–288
- Task Reassign function, 155–156, 282, 284
- Tasks
 - defined, 151
 - implicit termination of, 240
- TCO (total cost of ownership)
 - FC networking vs. IP networking, 7
 - iSCSI vs. Fibre Channel, 24–25
 - JBODs and RAID controllers and, 19
 - reducing, 7, 9, 10
- TCP/IP offload engines. *see* TOEs (TCP/IP offload engines)
- TCP/IP (Transmission Control Protocol/Internet Protocol)
 - building iSCSI on, 50–52, 205
 - checksums, CRC Digests and, 61–63
 - connection failures, 166
 - connection windowing, 123
 - history of iSCSI and, 41–45
 - iSCSI-related protocol layers, 53–55
 - link failures, 157
 - ports, 142
 - sessions, 56–57, 80
- TCP segments, 194–195
- TCP upper-level-protocol framing. *see* TUF (TCP upper-level-protocol framing)
- Text commands, 93–102
 - requests and responses, 93–95
 - rules for key=value pairs, 96–97
 - rules for keyword value negotiation, 97–99
 - rules for negotiation failure, 101–102
 - rules for negotiation flow, 99–101
 - summary, 102
- Text formats, 309–311
- Text request format, 72
- Text request PDUs
 - asynchronous message PDU and, 223
 - negotiation failure rules and, 101–102
 - overview of, 93–95, 289–292
- Text response PDUs
 - negotiation failure rules and, 101–102
 - overview of, 93–95, 293–296
- Text-value, defined, 310
- tilde (~), 82
- Time2Retain, 222–223, 243
- Time2Wait, 222–223, 242
- TOEs (TCP/IP offload engines)
 - history of iSCSI and, 42–43
 - iSCSI development and, 210
 - iSCSI servers using, 9
 - midrange companies using, 24
 - overview of, 60–61
- Total cost of ownership. *see* TCO (total cost of ownership)
- TotalAHSLength, 161, 258
- TPGT (target portal group tag)
 - defined, 316
 - error recovery level 0 and, 160
 - iSCSI architecture and, 141
 - keys and values, 304
 - login request PDU, 76
 - login response PDU, 79
 - SSID composed of, 107
- Training, Fibre Channel, 5–7
- Transfer direction, iSCSI, 108
- Transit (T) bits, 77, 225, 232
- Transmission Control Protocol/Internet Protocol. *see* TCP/IP (Transmission Control Protocol/Internet Protocol)
- Transport mode, support for ESP, 185
- TSIH (target session identifying handle)
 - defined, 316
 - establishing sessions, 106–107
 - login request PDU, 76, 227–228
 - login response PDU, 78–79, 233
 - nonleading login process, 86
 - rules for negotiation flow, 307
 - table of values, 230
- TTT (target transfer tag)
 - negotiation flow rules, 100–101
 - NOP-In PDU, 245
 - NOP-Out PDU, 248
 - R2T PDU, 251
 - SCSI Data-In PDU, 271
 - SCSI Data-Out PDU, 274
 - setting value for, 133–134
 - SNACK request PDU, 277

- TTT (target transfer tag) (*cont.*)
 task management function request PDU, 283
 text request PDU, 94–95, 290
 text response PDU, 94–95, 294
- TUF (TCP upper-level-protocol framing)
 experimental nature of, 193–194
 header, 200
 overview, 199–200
 pros and cons, 200–201
 TUF/FIM combination, 201–202
- Tunnel mode, support for ESP, 185
- Type, SNACK request PDU, 277
- U**
- U (residual underflow bit), 270
- UA (user agent), SLP, 176–178
- UDP/IP (User Datagram Protocol over Internet Protocol), 51
- ULPs (upper layer protocols), 152, 193
- Uniform resource locators (URLs), 65, 67–68
- Untagged tasks, 151, 152
- Upgrades
 campus, 29–30
 small office, 19
- Upper layer protocols (ULPs), 152, 193
- URLs (uniform resource locators), 65, 67–68
- User agent (UA), SLP, 176–178
- User Datagram Protocol over Internet Protocol (UDP/IP), 51
- V**
- value(list) string, login keywords, 82
- Values
 defined, 309
 negotiating keyword, 98–99
- Vendor-specific iSCSI event, 223
- Vendor type field, ISID, 103–105
- Version-Max, 225, 232
- Version-Min, 225, 232–233
- VPNs (virtual private networks), 31, 214
- W**
- W (write bit), 258
- WANs (wide area networks), 9–10
- Web pointers, 323–327
- Wedge drivers
 iSCSI architecture and, 144
 iSCSI development and, 210
 iSCSI sessions, 56
 SCSI nexus and, 147–149
- Wide area networks (WANs), 9–10
- World wide names (WWNs), 181–182
- Write operation
 data sequencing, 114–117
 travel directions for, 108
- WWNs (world wide names), 181–182
- X**
- X-<Vendor-SpecificKey>, 304