

# Index

- . (period), dot-stuffed messages, 128
- # (pound sign), m4 comment indicator, 23
  
- A**
- Accounting information, analyzing, 181–182
- Advanced Technology Attachment (ATA), 92
- Asynchronous journaling, 41–42
- Asynchronous mode *vs.* synchronous, 38–39, 40–42
- ATA (Advanced Technology Attachment), 92
- Authentication. *See also* verifying recipients.
  - alternatives, 73–79
  - warning message, 153
- authwarnings option, 153
  
- B**
- B-tree structures, 38
- Baselining, 168–169, 181–182
- Benchmarks, I/O, 33
- Blacklists, 153–154
- Books. *See* reference material.
- Bottlenecks. *See also* performance.
  - analysis tools
    - iostat utility, 178–180
    - netstat utility, 180–181
    - ps utility, 173–174
    - sar utility, 181–182
    - syslog facility, 183–186
    - top utility, 174–176
    - vmstat utility, 176–178
  - analyzing
    - accounting information, 181–182
    - baselining, 168–169, 181–182
    - counting message throughput, 184
    - CPU consumers, 174–176
    - desperation swapping, 178
    - logging system activity, 183–186
    - memory thrashing, 178
    - network statistics, 180–181
    - paging, 178
    - swapping, 178
    - system I/O statistics, 178–180
    - system information, 173–174, 181–182
    - trend analysis, 169
    - troubleshooting, 167–169
    - virtual memory statistics, 176–178
  - removing
    - CPU-bound systems, 186–187
    - disk-bound systems, 190–191
    - I/O controller-bound systems, 189–190
    - memory-bound systems, 187–189
    - network-bound systems, 192
    - queue sort order, 170
    - quick fixes, 169–172
    - reducing disk load, 170–171
    - rotating the queue, 170
    - suspending processes, 170–172
  - sources
    - DNLC (Directory Name Lookup Cache), 165–167
    - kernel parameters, 165–169
    - server saturation, 170–172
- Bourke, Tony, 163
- Buffering
  - dirty data buffers, 32–33
  - synchronization, 32–36
- Build script, 21
- Building sendmail, 20–21
- Bulk mail. *See* mailing lists.
- Bulkmail module, 210

**C**

- c-client library, 207–208
- Caching-forwarding name servers, 16–17
- Caching-only name servers, 14–15
- Canonification, 68–69
- Carriage return characters, 72
- Centralizing outbound mail, 162
- cf directory (sendmail Distribution), 20
- cf files
  - creating, 22–23
  - location, 23
  - modifying, 22, 24–25
- Checkpoint interval, 115–116
- CheckpointInterval variable, 115
- Collision avoidance, mail queues, 52
- Command-line message generation, 116–118, 127–128
- Comments, m4 language, 23
- Concatenating disks, 84–86
- Configuration files. *See* cf files.
- Configuration templates, 22–25
- Configuring DNS services, 14–17
- Configuring sendmail
  - centralizing user data, 150
  - connection limits, 139–140
  - connection timeout, 133
  - ConnectionCacheSize parameter, 142–143
  - ConnectionCacheTimeout parameter, 142–143
  - ConnectionRateThrottle parameter, 143
  - forward files, 148–151
  - hoststat command, 149
  - IDENT query timeout, 132–133
  - LDAP (Lightweight Directory Access Protocol), 150
  - ldapsearch command, 150
  - MaxDaemonChildren parameter, 143
  - MaxQueueRunSize parameter, 143
  - message size limits, 137–138
  - noncanonify feature, 147
  - number of processes, 143
  - queue operations, 144–146
  - queue processing timeout, 133–134
  - queue run size, 143
  - QueueLA variable, 141–142
  - QueueSortOrder parameter, 144–146
  - RefuseLA variable, 139–140
  - resolver timeouts, 134–136
  - Resolver.\*.first parameters, 136
  - Resolver.retrans.\* parameters, 135–136
  - Resolver.retry.\* parameters, 135–136
  - retransmission interval, 135–136
  - retries, number of, 135–136
  - ruleset tuning, 147–148
  - SMTP connection cache, 142–143
  - SMTP sessions, 143
  - statistics file, 149–150
  - suspending mail delivery, 141–142
  - system load averages, 138–142
  - system setup, 25–27
  - table lookups, 148–151
  - Timeout.icconnect variable, 133
  - Timeout.ident variable, 132–133
  - Timeout.queuereturn variable, 133–134
  - Timeout.queuwarn variable, 133–134
- Connection limits, configuring, 139–140
- Connection timeout, configuring, 133
- ConnectionCacheSize parameter, 142–143
- ConnectionCacheTimeout parameter, 142–143
- ConnectionRateThrottle parameter, 143
- Controller cards, RAID, 89, 90–91
- Courier IMAP, 108, 111
- CPU-bound systems, removing bottlenecks, 186–187
- CPU usage, analyzing, 174–176
- Creating
  - cf files, 22–23
  - files, 38, 44–46
  - df files, 30, 66, 114
  - qf files, 30, 66, 114, 119
  - tf files, 31, 115
  - xf files, 30
- CRLF, 72
- Cyrus IMAP, 83, 108, 111
- Cyrus message store, 102–104

**D**

Data storage issues. *See* file space.  
 DataFileBufferSize parameter, 34  
 Dead Letter Drop, 201  
 DelayLA, 141–142  
 Delay times, logging, 45–46  
 Deleting files, 38, 44–46  
 deliver LDA, 83  
 Delivery mode, 36–37  
 Delivery return receipts, 153  
 Delivery Status Notification (DSN), 53, 121, 133, 134, 153, 199  
 Desperation swapping, 178  
 Destination Unreachable message, 61  
 Directories
 

- permissions, 27–28
- size issues, 37–40, 48–50
- Soft Updates, 39, 104–105

 Directory lookup, 38  
 Directory Name Lookup Cache (DNLS)
 

- bottleneck, 165–167

 Disk-bound systems, removing bottlenecks, 190–191  
 Disk load, removing bottlenecks, 170–171  
 Disk space. *See also* file space; RAID (Redundant Array of Independent Disks).
 

- mailbox quotas, 79–82
- and server performance, 93

 Disks
 

- access speeds, 94–96
- ATA (Advanced Technology Attachment), 92
- capacity, 91–92
- concatenating, 84–86
- IDE, 92
- mirroring, 86–88
- multiple per server, 17–18
- non-uniform file distribution, 85–86
- partial formatting, 93–94
- partitioning, 93–94
- RAID. *See* RAID (Redundant Array of Independent Disks).
- SCSI, 92
- SSDs (solid-state disks), 94–96
- striping, 84–85, 86–88
- Winchester, 95

 dnl (m4 language), 23

DNLS (Directory Name Lookup Cache)
 

- bottleneck, 165–167

 DNS cache, priming, 136  
 DNS (Domain Name Service)
 

- caching-forwarding name servers, 16–17
- caching-only name servers, 14–15
- configuring, 14–17
- latency, reducing, 14
- in a test setup, 197

 DNS lookups, 31–32  
 doc directory, 20  
 Documentation. *See* reference material.  
 Domain Name Service (DNS). *See* DNS.  
 DontBlameSendmail option, 151–152  
 Dot (.), dot-stuffed messages, 128  
 Downloading sendmail, 19–20  
 Draining mail queues, 119–121  
 DSN. *See* Delivery Status Notification.  
 Duplicate messages, 35–36

**E**

Email
 

- address verification, disabling, 153
- counting message throughput, 184
- duplicate messages, 35–36
- injectors, 117–118, 127–128
- losing, RFC 2821, 32
- message body returns, disabling, 153
- message size limits, configuring, 137–138
- receiving. *See* receiving email.
- privacy and, 152–153
- reference material, 222
- relaying. *See* relaying email.
- sending. *See* sending email.
- suspending delivery, 141–142

 Email queues. *See* mail queues.  
 Email servers
 

- arranging disk storage, 17–18
- caching-forwarding name servers, 16–17
- caching-only name servers, 14–15
- common tasks, 6
- disk space, and performance, 94
- I/O-bound, 64
- parallelism, 162–163
- saturation bottlenecks, 170–172
- saturation response, 140–141
- saturation thresholds, 139–140

- Email systems
  - evaluating service load, 10–13
  - per capita usage, 12–13
  - testing. *See* testing.
- Encryption, 154–155
- Error messages, redirecting, 128
- EXPN SMTP command, 152
- ext2 fs, 40, 42–43
- ext3 fs, 41–44
- F**
- FallbackMX host, 156–158
- Fault protection. *See* RAID (Redundant Array of Independent Disks).
- fcntl ( ), 98
- File locking, 98
- file sort order, 145
- File space. *See also* disk space; RAID (Redundant Array of Independent Disks).
  - large directories, 48–50
  - parallelism, 52
  - queues
    - collision avoidance, 52
    - housecleaning, 57
    - migration, 52–53
    - mount points, 55–56
    - multiple, 51–52
    - renaming, 53–57
    - rotation, 53–57
    - symbolic links, 56
- Files
  - creation/deletion, 38, 44–46
  - non-uniform distribution, 85–86
  - permissions, 27–28
- Filesystems, performance
  - asynchronous journaling, 41–42
  - B-tree structures, 38
  - comparison of, 42–44
  - delay times, logging, 45–46
  - directory lookup, 38
  - ext2 fs, 40, 42–43
  - ext3 fs, 41–44
  - file creation/deletion, 38, 44–46
  - hardware-based acceleration, 44–46
  - hash directory tables, 38
  - inode updates, 39–40
  - JFS, 41
  - journaling file systems, 41–42
  - large directories, 37–40
  - logging metadata operations, 41–42
  - metadata operations, 39
  - NVRAM (non-volatile RAM), 44–46
  - pre-fetching data, 46–48
  - ReiserFS, 40–43
  - rolling back directory updates, 39
  - synchronous journaling, 41
  - synchronous mode *vs.* asynchronous, 38–39, 40–42
  - VxFS, 38, 41
  - XFS, 38, 41
- flock ( ) system call, 98
- Formatting disks, 93–94
- forward files, 148–151
- 4.4 BSD Programmer's Supplementary Documents*, 25
- G**
- Gigabit Ethernet, 60
- H**
- Hardware configuration, evaluating, 10–13
- Hardware RAID, 89
- Hash directory tables, 38
- Hashing message stores, 105–108
- Host names, confirming, 68–69
- Host sort order, 145
- hoststat command, 149
- Housecleaning, mail queues, 57
- I**
- I/O benchmarks, 33
- I/O controller-bound systems, removing
  - bottlenecks, 189–190
- IDE disks, 92
- IDENT query timeout, 132–133
- IMAP, testing, 208–209, 211
- IMAP, tuning
  - Courier IMAP, 108, 111
  - Cyrus, 108, 111
  - populating RAID systems, 110
  - reference implementation, 110
  - UW (University of Washington), 108, 110
  - vs.* POP, 109
- IMAPClient module, 211

## Inodes

- calculating usage, 101–102
- converting path names to, 106
- and message store hashing, 106
- updating, 39–40

INSTALL file, 20–21

Installing sendmail, 19–21. *See also* configuring sendmail.

interactive mail delivery, 34–37, 116–118

iostat utility, 178–180

**J**

Journaling file systems, 41–42, 95–96

**K**

Kernel data copying, 62–63

Kernel networking, 62–63

Kernel parameter bottlenecks, 165–169

Kolstad, Rob, 116

**L**

Latency

- effect on performance, 63–64
- reducing, DNS services, 14
- in a test setup, 216–219
- vs.* throughput, 63–64

Layer 4 switches, 163

LDA (Local Delivery Agent)

- alternative, 82–83
- canonification, 68–69
- definition, 5
- deliver, 83
- mail.local, 20, 65, 67–72, 78, 81–82, 202
- procmail, 82–83
- source code directory, 20
- temporary files, 67–69

LDAP (Lightweight Directory Access Protocol), 150

ldapsearch command, 150

Lightweight Directory Access Protocol (LDAP), 150

Line feed characters, 72

Line termination, 72

*Linux Sendmail Administration*, 222

LMTP (Local Mail Transfer Protocol), 70–72

Load generation. *See* testing.

## Load limits

connection limits, 139–140

ConnectionCacheSize parameter, 142–143

ConnectionCacheTimeout parameter, 142–143

ConnectionRateThrottle parameter, 143

DelayLA, 141–142

MaxDaemonChildren parameter, 143

MaxQueueRunSize parameter, 143

number of processes, 143

queue run size, 143

QueueLA variable, 141–142

RefuseLA variable, 139–140

SMTP connection cache, 142–143

SMTP sessions, 143

suspending mail delivery, 141–142

system load averages, 138–142

Local Delivery Agent (LDA). *See* LDA (Local Delivery Agent).

Local Mail Transfer Protocol (LMTP), 70–72

delivery performance of, 71–72, 82–83

Lock files, 98

lockf(), 53, 66, 98

Locking mailboxes, 98–100

Logging

delay times, 45–46

metadata operations, 41–42

system activity, 183–186

**M**

M4 language, 22–25

Macros, m4 utility, 22–25

Mail bombs, 137

Mail filters, 155–156

Mail queues

- bypassing, 34
- collision avoidance, 52
- configuring, 144–146
- draining, 119–121
- housecleaning, 57
- migration, 52–53
- mount points, 55–56
- multiple, 51–52
- priority, 144–146
- processing timeout, 133–134
- queue groups feature, 123–124, 146

- Mail queues (*cont.*)
    - queue-only mode, 122–123
    - removing bottlenecks, 170
    - removing files in, 57
    - renaming, 53–57
    - restricting access, 153
    - rotation, 53–57, 116, 170
    - run size, 143
    - setting up, 25–26
    - sort order, 144–146, 170
    - storage space. *See* file space.
    - symbolic links, 56
    - system setup, 25–26
    - temporary queuing, inbound, 159–161
    - temporary queuing, outbound, 156–158
    - unique identifiers, 31
    - viewing contents of, 25–26
  - Mail spool, permissions, 27–28
  - Mail Transfer Agent (MTA), 5
  - Mailbox Database (mbdb) API, 74–79
  - Mailboxes
    - extracting a list of, 107
    - locking, 98–100
    - names, 27
    - permissions, 27–28
    - quotas, 79–82
  - maildir message store, 100–102, 104–105
  - Mailing lists
    - checkpoint interval, 115–116
    - definition, 113–114
    - maximum recipients per message, 121
    - precreating qf files, 119
    - spamming, 113, 121
    - splitting the qf file, 114–115
    - SuperSafe option, 127
  - mail.local directory, 20
  - mailq command
    - restricting, 152–153
    - viewing queue contents, 25–26
  - Mailstone, 211–212
  - Managing IMAP*, 5, 104, 222
  - Manuals. *See* reference material.
  - Mass mailings. *See* mailing lists.
  - MaxDaemonChildren parameter, 143
  - MaxQueueRunSize parameter, 143
  - MaxRecipientsPerMessage parameter, 121
  - mbdb (Mailbox Database) API, 74–79
  - mbox Message Store. *See* 7th Edition message store.
  - MD5 hashing algorithm, 107–108
  - Memory
    - bound systems, 187–189
    - consumption and latency, 218
    - paging, 178
    - swapping, 178
    - thrashing, 178
  - Message stores
    - 7th Edition message store, 97–100
    - all messages in one file, 97–100
    - comparison of, 104–105
    - Cyrus message store, 102–104
    - hashing, 105–108
    - maildir message store, 100–102, 104–105
    - one file per message, 100–102, 102–104
    - permissions, 27–28
    - system setup, 27
  - Metadata operations
    - logging, 41–42
    - rolling back, 39
  - Migration, mail queues, 52–53
  - Milters, 155–156
  - Mirroring disks, 86–88
  - modification sort order, 145
  - Moore's law, 94
  - Mount points, mail queues, 55–56
  - Mstone, 211–212
  - MTA (Mail Transfer Agent), 5
  - Myrinet, 63
- N**
- namei () function, 106
  - netstat utility, 180–181
  - Network-bound systems, removing
    - bottlenecks, 192
  - Network interface cards (NICs), 59–60
  - Networks
    - analyzing statistics, 180–181
    - relaying email
      - bandwidth, 63–64
      - Destination Unreachable message, 61
      - different MTUs, 60–61
      - Gigabit Ethernet, 60
      - kernel data copying, 62–63
      - kernel networking, 62–63
      - large packets, 60–61

- latency, 63–64
  - Myrinet, 63
  - NICs (network interface cards), 59–60
  - Path MTU Discovery, 61
  - reliability, 57–59
  - VI (Virtual Interface Architecture), 63
  - zero-copy implementations, 62–63
- NICs (network interface cards), 59–60
- nobodyreturn option, 153
- noexpn option, 152
- Non-volatile RAM (NVRAM), 44–46
- noncanonify feature, 147
- noreceipts option, 153
- noverb option, 152
- novrfy option, 152
- NVRAM (non-volatile RAM), 44–46
- O**
- Obtaining sendmail, 19–20
- P**
- Packets, size issues, 60–61
- Paging, 178
- PAM (Pluggable Authentication Module), 74
- Parallelism, 52, 162–163
- Parity, RAID, 86
- Partitioning disks, 93–94
- Path MTU Discovery, 61
- Performance, analyzing. *See also* bottlenecks.
  - centralizing outbound mail, 162
  - FallbackMX host, 156–158
  - I/O benchmarks, 33
  - I/O-bound servers, 64
  - latency, effects of, 63–64
  - layer 4 switches, 163
  - receiving email, 67–70
  - reference material, 222–223
  - and security. *See* security, and performance.
  - server disk space, 94
  - server parallelism, 162–163
  - smart host, 162
  - Spillover host, 159–161
  - synchronization, 36–37
  - syslog facility and, 185–186
  - temporary queuing, inbound, 159–161
  - temporary queuing, outbound, 156–158
  - throughput, 36–37
- Performance, tuning
  - determining need for, 6–10
- IMAP
  - Courier IMAP, 108, 111
  - Cyrus, 108, 111
  - header information, 110
  - populating RAID systems, 110
  - reference implementation, 110
  - UW (University of Washington), 108, 110
  - vs.* POP, 109
- POP protocol
  - 7th Edition message store, 97–100, 105
  - bugs, 100
  - Cyrus message store, 102–104
  - maildir message store, 100–102, 104–105
  - qmail format, 100–102
  - two sessions, same mailbox, 99
  - vs.* IMAP, 109
  - reference material, 222–223
  - rulesets, 147–148
- Period (.), dot-stuffed messages, 128
- Perl modules, 209–211
- Permissions
  - directories, 27–28
  - files, 27–28
  - mail queues, 25–26
  - mail spool, 27–28
  - mailboxes, 27–28
  - message store, 27
  - sticky bit, 27
- PIPELINING, SMTP, 124–127
- Pluggable Authentication Module (PAM), 74
- POP protocol
  - testing, 207–208
  - tuning
    - 7th Edition message store, 97–100, 105
    - bugs, 100
    - Cyrus message store, 102–104
    - maildir message store, 100–102, 104–105
    - qmail format, 100–102
    - two sessions, same mailbox, 99
    - vs.* IMAP, 109
- POP3 protocol, testing, 210–211
- POP3Client module, 210–211
- popclient utility, 207–208
- postfix tools, 207

*Practice of System and Network Administration, The*, 221

Pre-fetching data, 46–48

priority sort order, 145

Privacy, 152–153

PrivacyOptions option, 152–153

Processes

  limiting number of, 143

  removing bottlenecks, 170–172

procmail LDA, 82–83

*Programming Internet Email*, 5, 222

ps utility, 173–174

## Q

qf files

  example, 119–120

  precreating, 119

  splitting, 114–115

qmail format, 100–102

Queue groups feature, 123–124, 146

Queue-only mode, 122–123

QueueLA variable, 141–142

Queues. *See* mail queues.

QueueSortOrder parameter, 144–146

Quotas, 79–82

## R

*RAID Book, The*, 86

RAID (Redundant Array of Independent Disks). *See also* disk space; file space.

  bottlenecks, 191

  controller cards, 89, 90–91

  determining need for, 88

  evaluating, 89–91

  hardware implementation, 89

  level descriptions, 86–88

  mirroring disks, 86–88

  multiple systems, 91

  overview, 83–84

  parity, 86

  populating, 110

  redundancy, 86

  self-contained systems, 89

  software implementation, 88–89

  striping disks, 86–88

README files, 20, 21

Receiving email

  canonification, 68–69

carriage return characters, 72

CRLFs, 72

disks

  access speeds, 94–96

  ATA (Advanced Technology Attachment), 92

  capacity, 91–92

  concatenating, 84–86

  IDE, 92

  mirroring, 86–88

  non-uniform file distribution, 85–86

  partial formatting, 93–94

  partitioning, 93–94

  SCSI, 92

  SSDs (solid-state disks), 94–96

  striping, 84–85, 86–88

host names, confirming, 68–69

IMAP, tuning

  Courier IMAP, 108, 111

  Cyrus, 108, 111

  header information, 110

  populating RAID systems, 110

  reference implementation, 110

  UW (University of Washington), 108, 110

*vs.* POP, 109

LDA (Local Delivery Agent), 67–70

line feed characters, 72

line termination, 72

LMTP (Local Mail Transfer Protocol), 70–72

message stores

  7th Edition message store, 97–100

  comparison of, 104–105

  Cyrus message store, 102–104

  hashing, 105–108

  maildir message store, 100–102, 104–105

  mbox message store, 97–100

  one file per message, 100–102, 102–104

overview, 65–67

performance

  multiple recipients, 70

  temporary files, 67–70

POP protocol, tuning

  7th Edition message store, 97–100, 105

  bugs, 100

  Cyrus message store, 102–104



- maildir message store, 100–102, 104–105
- qmail format, 100–102
- two sessions, same mailbox, 99
- vs. IMAP, 109
- RAID (Redundant Array of Independent Disks)
  - controller cards, 89, 90–91
  - determining need for, 88
  - evaluating, 89–91
  - hardware implementation, 89
  - level descriptions, 86–88
  - mirroring disks, 86–88
  - multiple systems, 91
  - overview, 83–84
  - parity, 86
  - redundancy, 86
  - self-contained systems, 89
  - software implementation, 88–89
  - striping disks, 86–88
- verifying recipients
  - authentication alternatives, 73–79
  - deliver, 83
  - disabling checking, 73
  - LDA alternatives, 82–83
  - mailbox quotas, 79–82
  - mbdb (Mailbox Database) API, 74–79
  - modifying sendmail source code, 73–74
  - overview, 72–73
  - PAM (Pluggable Authentication Module), 74
  - procmail LDA, 82–83
- Redirecting error messages, 128
- Redundant Array of Independent Disks (RAID). *See* RAID (Redundant Array of Independent Disks).
- Reference material
  - 4.4 BSD Programmer's Supplementary Documents*, 25
  - CPAN (Comprehensive Perl Archive Network), 210
  - doc directory, 20
  - email, 222
  - general performance tuning, 222–223
  - general system administration, 221
  - Linux Sendmail Administration*, 222
  - m4 utility, 25
  - Managing IMAP*, 5, 104, 222
  - Practice of System and Network Administration, The*, 221
  - Programming Internet Email*, 5, 222
  - RAID Book, The*, 86
  - README files, 20, 21
  - RELEASE\_NOTES file, 20
  - sendmail, 222
  - Sendmail Installation and Operation Guide*, 20
  - Sun Performance and Tuning: Java and the Internet*, 222
  - System Performance Tuning*, 223
  - UNIX System Administration Handbook*, 221
- RefuseLA variable, 139–140
- ReiserFS, 40–43
- Relaying email
  - bandwidth, 63–64
  - DNS lookups, 31–32
  - file space
    - large directories, 48–50
  - file space, queues
    - collision avoidance, 52
    - housecleaning, 57
    - migration, 52–53
    - mount points, 55–56
    - multiple, 51–52
    - renaming, 53–57
    - rotation, 53–57
    - symbolic links, 56
  - filesystems, performance
    - asynchronous journaling, 41–42
    - B-tree structures, 38
    - comparison of, 42–44
    - directory lookup, 38
    - ext2fs, 40, 42–43
    - ext3fs, 41–44
    - file creation/deletion, 38, 44–46
    - hardware-based acceleration, 44–46
    - hash tables, 38
    - inode updates, 39–40
    - journaling file systems, 41–42
    - large directories, 37–40
    - logging metadata operations, 41–42
    - metadata operations, 39
    - NVRAM (non-volatile RAM), 44–46
    - pre-fetching data, 46–48

- Relaying email (*cont.*)
  - ReiserFS, 40–43
  - rolling back directory updates, 39
  - synchronous journaling, 41
  - synchronous mode *vs.* asynchronous, 38–39, 40–42
  - overview, 29–32
  - synchronization
    - buffering, 32–36
    - bypassing the queue, 34
    - DataFileBufferSize parameter, 34
    - delivery mode, changing, 36–37
    - dirty data buffers, 32–33
    - duplicate messages, 35–36
    - I/O benchmarks, 33
    - interactive mode, 34–37
    - lost mail, RFC 2821, 32
    - performance, 36–37
    - SuperSafe parameter, 33–34, 37
    - XScriptFileBufferSize parameter, 34
    - unique queue identifiers, 31
  - RELEASE\_NOTES file, 20
  - Reliability, networks, 57–59
  - Renaming, mail queues, 53–57
  - Resolver timeouts, 134–136
  - Resolver.\*.first parameters, 136
  - Resolver.retrans.\* parameters, 135–136
  - Resolver.retry.\* parameters, 135–136
  - restrictmailq option, 152–153
  - restrictqrun option, 153
  - Retransmission interval, 135–136
  - Retries, setting number of, 135–136
  - Rolling back directory updates, 39
  - Rotating mail queues, 53–57, 116, 170
  - Ruleset tuning, 147–148
- S**
  - sar utility, 181–182
  - SCSI disks, 92
  - Security, and performance
    - authwarnings option, 153
    - blacklists, 153–154
    - delivery return receipts, 153. *See also* Delivery Status Notification (DSN).
    - DontBlameSendmail option, 151–152
    - email address verification, 153
    - encryption, 154–155
    - EXPN command, 152
    - mail filters, 155–156
    - mailq command, 152–153
    - message body returns, 153
    - mitlers, 155–156
    - nobodyreturn option, 153
    - noexpn option, 152
    - noreceipts option, 153
    - noverb option, 152
    - novrfy option, 152
    - privacy, 152–153
    - PrivacyOptions option, 152–153
    - queue restrictions, 153
    - responding to SMTP queries, 152–153
    - restrictmailq option, 152–153
    - restrictqrun option, 153
    - STARTTLS, 155
    - VERB command, 152
    - VERFY command, 152
    - X-Authentication-Warning: messages, 153
  - Sending email
    - from the command line, 116–118, 127–128
    - injectors, 117–118, 127–128
    - interactive mail delivery, 116–118
    - mailing lists
      - checkpoint interval, 115–116
      - definition, 113–114
      - maximum recipients per message, 121
      - precreating qf files, 119
      - spamming, 113, 121
      - splitting the qf file, 114–115
      - SuperSafe option, 127
    - redirecting error messages, 128
    - SMTP PIPELINING, 124–127
  - sendmail*, 222
  - sendmail
    - building, 20–21
    - connection cache, 142–143
    - configuring. *See* configuring sendmail.
    - history of, 4–5
    - installing, 19–21
    - obtaining, 19–20
    - README files, 20, 21
    - reference material, 222
    - as a test sink, 205–207

- as a test source, 198–205
    - testing. *See* testing.
  - sendmail directory, 20
  - Sendmail Installation and Operation Guide*, 20
  - sendmail/README files, 21
  - Servers. *See* email servers.
  - 7th Edition message store, 97–100, 105
  - Size, message limits, 137–138
  - Sleepycat DP package, 80
  - Smart host, 162
  - smsm user/group, 26
  - SMTP
    - pipelining, 124–127
    - queries, responding to, 152–153
    - sessions, limiting, 143
  - smtp-sink, 207
  - smtp-source, 207
  - Soft Updates
    - description, 39
    - and maildir message store, 104–105
  - Software configuration, evaluating, 10–13
  - Software RAID, 88–89
  - Solid-state disks (SSDs), 94–96
  - Spam
    - blacklists, 153–154
    - limiting maximum recipients, 121
    - protecting user names, 152
    - verifying sender address, 147
    - vs.* legitimate mass mailings, 113
  - Spillover host, 159–161
  - SplitAcrossQueueGroups feature, 123
  - SQL and authentication, 151
  - SSDs (solid-state disks), 94–96
  - STARTTLS, 155
  - stat shell script, 182–183
  - statistics file, 149–150
  - Sticky bit, 27
  - Storage systems. *See* disks; file space; RAID (Redundant Array of Independent Disks).
  - Striping disks, 84–85, 86–88
  - Sun Performance and Tuning: Java and the Internet*, 222
  - SuperSafe parameter
    - and mailing lists, 127
    - throughput, 37
    - turning off, 33–34
  - Swapping, 178
  - Symbolic links, mail queues, 56
  - Synchronization
    - buffering, 32–36
    - bypassing the queue, 34
    - DataFileBufferSize parameter, 34
    - delivery mode, changing, 36–37
    - dirty data buffers, 32–33
    - duplicate messages, 35–36
    - I/O benchmarks, 33
    - interactive mode, 34–37
    - lost mail, RFC 2821, 32
    - performance, 36–37
    - SuperSafe parameter, 33–34, 37
    - XScriptFileBufferSize parameter, 34
  - Synchronous journaling, 41
  - Synchronous mode *vs.* asynchronous, 38–39, 40–42
  - syslog facility, 183–186
  - System administration, reference material, 221
  - System I/O statistics, analyzing, 178–180
  - System information, analyzing, 173–174, 181–182
  - System load averages, 138–142
  - System Performance Tuning*, 223
  - System setup. *See* configuring sendmail.
- T**
- Table lookups, configuring, 148–151
  - Targets, 195
  - Templates, 22–25
  - Temporary files, 67–70
  - Testing
    - IMAP, 208–209, 211
    - pitfalls, 212–215
    - POP access, 207–208
    - POP3 protocol, 210–211
    - sending bulk mail, 210
    - simulating multiple users, 203–205
    - system setup
      - anticipating the unexpected, 216
      - approximating the real world, 194–195, 215–219
      - DNS (Domain Name Service), 197
      - hardware, appropriate, 200–201
      - Internet connections, 196
      - latency, 216–219

Testing (*cont.*)

- number of hosts, 215–216
- number of user accounts, 215
- private IP addresses, 196–197
- sinks, 195
- sources, 195
- spare computer, 197–198
- targets, 195
- tools for
  - Bulkmail module, 210
  - c-client, 207–208
  - Dead Letter Drop, 201
  - IMAPClient module, 211
  - Mailstone, 211–212
  - Mstone, 211–212
  - Perl modules, 209–211
  - POP3Client module, 210–211
  - popclient, 207–208
  - postfix tools, 207
  - sendmail, as a sink, 205–207
  - sendmail, as a source, 198–205
  - smtp-sink, as sink, 207
  - smtp-source, as source, 207
- Timeout.iconnect variable, 133
- Timeout.ident variable, 132–133
- Timeout.queuereturn variable, 133–134
- Timeout.queuewarn variable, 133–134
- Tools. *See* bottlenecks, analysis tools; testing, tools for.
- top utility, 174–176
- Trend analysis, 169
- Troubleshooting, 167–169. *See also* bottlenecks.
- Tuning. *See* performance, tuning.

## U

- UIDs (user identifiers), maximum number of, 28
- University of Washington (UW) IMAP, 108, 110
- UNIX System Administration Handbook*, 221
- UW (University of Washington) IMAP, 108, 110

## V

- VERB SMTP command, 152
- Verifying recipients
  - authentication alternatives, 73–79
  - deliver LDA, 83
  - disabling checking, 73
  - LDA alternatives, 82–83
  - mailbox quotas, 79–82
  - mbdb (Mailbox Database) API, 74–79
  - modifying sendmail source code, 73–74
  - overview, 72–73
  - PAM (Pluggable Authentication Module), 74
  - procmail LDA, 82–83
- VI (Virtual Interface Architecture), 63
- Virtual memory statistics, analyzing, 176–178
- vmstat utility, 176–178
- VERFY SMTP command, 152

## X

- X-Authentication-Warning:
  - messages, 153
- XScriptFileBufferSize parameter, 34

## Z

- Zero-copy networking, 62–63