

INDEX

A

Absolute location paths (XPath), 27–28

Accelerator keys, navigation, 17. *See also*
XForms attributes, accesskey

Accessibility

access aids, 212

adaptive technologies, 222

content, 212, 218

design, 213

encapsulating relevant metadata, 213

graceful degradation, 214

refactoring and filtering, 214

separating from layout and presentation,
213–214

CSS, 218–220

pseudo-elements, 221

events

device-specific, 215

handlers, centralized handling, 216

handlers, declarative *versus* scripts, 217

notifications of state changes, 216

grouping UI controls, labeling, 93

multimodal access

adaptation to user environment, 206

basics, 201–202

graceful degradation, 203

interaction manager, 207, 208

interactors, 204

predictability, 205–206

sharing common states, 204–205

synchronization, 202–203

UIs, creating, 206–209

UI principles, 202–206

voice dialogs, 209

UI

hooks for attaching special behaviors,
216–217

late binding of behaviors, 215–216

predictable behaviors, 215

universal access, 211–213

user agents, 212, 221–222

Active Server Pages (ASP), 9

Adaptive technologies, 222. *See also*

Accessibility

Aggregation constructs. *See also* XForms UI

component; XForms UI controls

defining with complex types, 40–42

UI controls

grouping, 92–95

growing/shrinking during interaction,
102–118

hiding/showing, 95–102

Anonymous groups, 114–118

AnyURI data type (XML Schema), 37

Apache, Xerces XML processor, 14

ASP (Active Server Pages), 9

Atomic selection controls, 65–66

Attributes. *See* XForms attributes

Avg expression (XPath), 30

Axis, location paths, 28

B

Base64Binary data type (XML Schema), 37

Beebe, Nelson, 224

Binding

accessibility, 215–216

definition, 16

model constraints, 139–140

multimodal access UIs, 206–207

UI controls

attributes, 53–56

DOM events, 51

example, 129

grouping, 94–95

Web services, 199

XML Schema, 36

XPath, 26–27

Boolean data type

XForms functions, 152–153

XML Schema, 37

XPath functions, 29, 151

C

Cascading Style Sheet (CSS)

accessibility, 218–221

customizing input controls, 60–63

definition, 17

model component properties, 136–139

pseudo-classes, 137–139, 183, 184

pseudo-elements, 221

UI controls, 51

X-Smiles, 42–43

CGI (Common Gateway Interface),

processing input values, 4

Champion, Mike, xxiii

Child elements, declaring, 42

Closed selection controls, 66

Collection of text input, 59–63

Complex data types, 40–42

Conditional user interface, 141

Constraints, model component,

139–140

Constraints, XPath, 27

Constructs. *See* Aggregation constructs

Content

accessibility, 212, 218

encapsulating relevant metadata, 213

graceful degradation, 214

refactoring and filtering, 214

separating from layout and presentation,
213–214

UI controls, 51

Context nodes, XPath expressions, 27

binding, 160–161

set unions, 27

Count expression (XPath), 30

CSS (Cascading Style Sheet)

accessibility, 218–221

customizing input controls, 60–63

definition, 17

model component properties, 136–139

pseudo-classes, 137–139, 183, 184

pseudo-elements, 221

UI controls, 51

X-Smiles, 42–43

D

Data binding. *See* Binding

Date picker controls, 62

Data types

defining aggregations with complex types,
40–42

XML Schema, 37

built-in types, 38–40

checking, 33

facets, 38–39

IDL, 36, 41

type derivations, 38–40

Data types (XPath), 29

Date data type (XML Schema), 37

Date-time data type (XForms core library),
157–159

DateTime data type (XML Schema), 37

Decimal data type (XML Schema), 37

Declarations, XML Schema, 40–42

Declarative authoring, 21

Default pseudo class (CSS), 184

Definitions, XML Schema, 40–42

Degradation, graceful, 203

accessibility, 214

Device independence, 22

Dialog managers, 207

:disabled pseudo-class (CSS), 138–139, 184

DOM (Document Object Model)/DOM2

Events, 17

basics, 30–31

DOMActivate, 81, 181

- implementations using W3C standards, 45
- role in XForms, 44
- Double data type (XML Schema), 37
- Duration data type (XML Schema), 37
- Dynamic computation, 147–148
- Dynamic selection controls, set of values, 68–70
- Dynamic validation, 144–145

E

- E-commerce, background, 4–6
- ECMAScript event handlers, 30
- Electronic commerce. *See* E-commerce
- Elements. *See* HTML elements; XForms elements; XHTML, elements; XML, elements
- :enabled pseudo-class (CSS), 138–139, 184
- Enumeration facets, 39
- Environment, XPath expressions, 27
- Error events, 176
- Events. *See* XForms Events
- Extensible Hypertext Markup Language. *See* XHTML
- Extensible Markup Language. *See* XML

F

- Facets, 38–39
- Filters, 28
 - accessibility, 214
- Float data type (XML Schema), 37
- FormsPlayer plug-in, 43
- Functions. *See* XForms functions; XPath, functions

G

- GDay data type (XML Schema), 37
- GET method (HTTP), 8–9
- Global part, namespaces (XML), 35
- GMonth data type (XML Schema), 37
- GMonthDay data type (XML Schema), 37
- Graceful degradation, 203
 - accessibility, 214
- Grouping UI controls
 - anonymous, 114–118
 - basics, 92
 - binding expressions, 94–95

- event handlers used with <repeat> element, 112, 114–117
- hiding/showing controls, 95–102
- labeling, 92–94
- navigating, 94
- navigating among, 94
- Gurari, Etian, 223
- GYear data type (XML Schema), 37
- GYearMonth data type (XML Schema), 37

H

- Help events, 180
- HTML elements, <form> and <input>, 8
- HTML forms
 - Questionnaire Web application example, 6–10
 - Web applications, background, 4–6
- HTTP (Hypertext Transfer Protocol), 4–5

I

- IBM XForms, 43
- IDL (Interface Definition Language), 36, 41
- Initialization events, 176–178
- Integer data type (XML Schema), 37
- Intent-based authoring, UI controls, 51
- Interaction, UI controls, 51
- Interaction attributes and child elements, 54, 58–59
- Interaction events, 176, 178–181
- Interaction manager, 207, 208
- Interface Definition Language (IDL), 36, 41
- Internationalization, 22
- :invalid pseudo-class (CSS), 138–139, 144, 184

J

- JSP (Java Server Pages), 9

K

- King, James C., xxiii
- Klotz, Leigh, xxiii, 224
- Knuth, Donald, 224
- Krishnamoorthy, xxiii

L

- Length facets, 39
- List selection controls, 65–66
- Local part, namespaces (XML), 35

Local prefixes, namespaces, 35
 Localization, 22
 Location paths (XPath), 27–28
 locators, relative or absolute, 27–28
 syntax, 28–29
 Location steps (XPath), 27

M

Maler, Eve L., xxiii
 MaxExclusive facets, 39
 MaxInclusive facets, 39
 MaxLength facets, 39
 Merrick, Roland, xxiii
 Metadata
 definition, 16
 encapsulating, 213
 Middleware, 5–6
 MinExclusive facets, 39
 MinInclusive facets, 39
 MinLength facets, 39
 Model-based switching, 140–142
 Model-view separation
 multimodal access, 201
 Web services, 194, 197
 Multimodal access. *See* Accessibility
 MVC (Model-View-Controller)
 decomposition, 9–10
 XForms architecture, 9

N

Namespaces (XHTML), 130–132
 Namespaces (XML), 34–35
 global and local parts, attributes and
 elements, 35, 131–132
 namespace qualification, 121
 role in XForms, 44
 Navigation
 accelerator keys, 17. *See also* XForms
 attributes, accesskey
 definition, 17
 Navigation events, 179–180
 Node-set data type, 159, 160
 Node tests, location paths, 28
 Nodeset data type (XPath)
 filters, 28
 functions, 29
 ordered and unordered, 28
 Notification events, 176, 181–184

 signaling state changes, 183, 184
 state changes, accessibility, 216
 Novell XForms, 43
 Number data type, functions
 XForms, 153–156
 XPath, 29, 151

O

Observers, events, 31
 OMA (Open Mobile Alliance), 210
 Open selection controls, 66
 :optional pseudo-class (CSS), 137–139, 143,
 184
 :out-of-range pseudo-class (CSS), 137–139

P

Pattern facets, 39
 Pemberton, Steven, xxiii
 Perry, William, 224
 PHP (Hypertext Preprocessor), 9
 Platform For Privacy Preferences, 149
 Portal servers, 196
 Portals, 195–196
 Portlets, 196
 POST method (HTTP), 8
 Presentation
 attributes and child elements, 54,
 56–58
 definition, 17
 UI controls, 51
 Price * tax-table expression (XPath), 30
 Processing events, 178–179
 Properties. *See* XForms properties; XML,
 properties
 Pseudo-classes (CSS), 137–139, 143
 notification events signaling state changes,
 183, 184
 Pseudo-elements (CSS), 221

R

Rahitz, Sabastian, 224
 Range selection controls, 74–75
 Readonly, for controlling changes,
 143–144
 :readonly pseudo-class (CSS), 138–139,
 184
 :readwrite pseudo-class (CSS), 138–139,
 143, 184

- Refactoring
 - accessibility, 214
 - grouping UI controls, labeling, 93–94
- Relative location paths (XPath), 27–28
- :repeat-index pseudo-element (CSS), 221
- :repeat-item pseudo-element (CSS), 221
- :required pseudo-class (CSS), 137–139, 184
- Reset events, 180
- Restrictions, facets, 38
- RSS (Rich Site Syndication), 196–197, 198

- S**
- Schnitzenbaumer, Sebastian, xxiii
- Selection controls
 - basics, 17–18
 - range of values, 74–75
 - set of values
 - appearance attribute values, 72–73
 - atomic and list, 65–66
 - basics, 63–65
 - default selections, 66–67
 - dynamic, 68–70
 - grouping available choices, 72, 73
 - open and closed, 66
 - static choices, 67–68
 - XML structures, 70–72
- Server-side technologies, 4–6
- SMIL, X-Smiles, 43
- SOAP (Simple Object Access Protocol), 191, 192
- Spatial interactions, 202
- Static choices, selection controls, 67–68
- Sticky fields, 8
- String data type
 - XForms functions, 156–157
 - XML Schema, 37
 - XPath functions, 29, 151
- Strong data typing, 21–22
- Sub-types of data types, 38
- Submit component, 11–12, 18–19
- Submit events, 180
- Sum expression (XPath), 30
- SVG support, X-Smiles, 43
- Synchronization, multimodal access, 202–203
 - UI views, 208–209
- Syndication, Web services, 196–199
- Syntax, location paths, 28
 - abbreviated and unabbreviated, 29

- T**
- Target, events, 31
- Templates, <repeat> element, 104
- Temporal interactions, 202
- Tightly bound UI controls, 16
- Time data type (XML Schema), 37
- Time/date data type, 157–159
- Triggering actions
 - basics, 78–79
 - process, 79–81
- Type, for augmenting schemas, 148–149
- Types. *See* Data types

- U**
- UI aggregation constructs. *See* Aggregation constructs
- Uploading data, 76–78
- URIs (Universal Resource Identifiers), 35
- User agents, accessibility, 212, 221–222
- User interface. *See* XForms UI component; XForms UI controls

- V**
- :valid pseudo-class (CSS), 138–139, 144, 184
- :value pseudo-element (CSS), 221
- Variables (XPath), 29–30
- Voice dialogs, 209
- VoiceXML (Voice Extensible Markup Language), 209

- W**
- W3C
 - implementations, 45
 - reusable forms, 210
 - URIs (Universal Resource Identifiers), 35
 - XForms, growth, 25
 - XForms, origin, 1
 - XML Schema, 13–14
- Web applications
 - accessibility from variety of devices, 6
 - background, 4–6
 - definition, 4
 - server-side components, 4

- Web services
 - access to weather service example, 190–192
 - basics, 189–190
 - collecting information with XML, 192–194
 - portal servers, 196
 - portals, 195–196
 - portlets, 196
 - RSS (Rich Site Syndication), 196–197, 198
 - SOAP (Simple Object Access Protocol), 191, 192
 - standards, 189
 - syndication, content, 196–197, 198
 - syndication, UI, 197, 199
 - WRSP (Web Services for Remote Portals), 197, 199
 - WSDL (Web Services Description Language), 190–191
 - XForms
 - collecting of structured data, 194–195
 - model-view separation, 194, 197
 - Web Services Description Language (WSDL), 190–191
 - Web Services for Remote Portals (WRSP), 197, 199
 - Well-formed XML documents, 34
 - World Wide Web Consortium. *See* W3C
 - WRSP (Web Services for Remote Portals), 197, 199
 - WSDL (Web Services Description Language), 190–191
- X**
- Xerces (Apache) XML processor, 14
 - XForms
 - architecture, 9
 - components, 23. *See also* XForms UI controls
 - model, 11–14
 - submit, 11–12, 18–19
 - UI, 11, 14–18
 - features, 21–22
 - FormsPlayer, 43
 - iBM XForms, 43
 - implementations, 26, 42–43
 - list at XForms WG, 42
 - using W3C standards, 45
 - Novell XForms, 43
 - processing steps, 171–172
 - UI, predictable behaviors, 215
 - XForms Basic, 146
 - XPath uses, 26–27
 - XForms accessibility
 - access aids, 212
 - adaptive technologies, 222
 - content, 212
 - accessibility, 218
 - disign, 213
 - encapsulating relevant metadata, 213
 - graceful degradation, 214
 - refactoring and filtering, 214
 - separating from layout and presentation, 213–214
 - CSS, 218–220
 - pseudo-elements, 221
 - events
 - device-specific, 215
 - handlers, centralized handling, 216
 - handlers, declarative *versus* scripts, 217
 - notifications of state changes, 216
 - grouping UI controls, labeling, 93
 - multimodal access
 - adaptation to user environment, 206
 - creating UIs, 206–209
 - graceful degradation, 203
 - predictability, 205–206
 - sharing common states, 204–205
 - synchronization, 202–203
 - UI
 - hooks for attaching special behaviors, 216–217
 - late binding of behaviors, 215–216
 - predictable behaviors, 215
 - universal access, 211–213
 - user agents, 212, 221–222
 - XForms features, 22
 - XForms actions
 - action, 169–170
 - correspondence between actions
 - and events, 172, 184
 - delete, 172–173
 - dispatch, 170–171
 - feature of XForms, 22
 - insert, 172–173
 - load, 166
 - message, 168–169
 - rebuild, 171–172
 - recalculate, 171–172

- refresh, 171–172
- reset, 168
- revalidate, 171–172
- send, 166–168
- setfocus, 165
- setindex, 172–173
- setvalue, 165–166
- triggers
 - basics, 78–79
 - process, 79–81
- XForms attributes
 - accesskey
 - definition, 17
 - grouping UI controls, 94
 - interaction UI controls, 54, 58–59
 - action, 83, 87
 - appearance
 - definition, 17
 - presentation UI controls, 54, 56–58
 - selection controls, 72–73
 - bind
 - binding UI controls, 53–56
 - data submission, 83
 - bubble, 31
 - dispatch action, 170
 - with events (list), 185
 - xforms-setfocus event, 180
 - cancel
 - dispatch action, 170
 - events (list), 185
 - case, 96
 - cdata-section-elements, 85
 - class
 - definition, 17
 - presentation UI controls, 54, 56–58
 - deferred, 171
 - encoding, 84
 - end, 75
 - ev.event
 - action action, 170
 - definition, 17
 - triggering actions, 79
 - ev.handler, 79
 - eventing, 54, 58–59
 - handler, 170
 - implicit, 167
 - incremental, 54, 58–59
 - indent, 85
 - inputmode
 - customizing input controls, 63
 - interaction UI controls, 54, 58–59
 - instance, 123
 - level, 168–169
 - maxOccurs, 146
 - mediatype, 76–77
 - method, 84, 87
 - minOccurs, 146
 - model
 - binding expressions, 159–161
 - definition, 16
 - reset action, 167–168
 - model/nodeset pairs, 104
 - model/ref pairs
 - binding, 53–56
 - binding, grouping UI controls, 94–95
 - data submission, 83
 - UI controls, dynamic selections, 68–70
 - navindex
 - grouping UI controls, 94
 - interaction UI controls, 54, 58–59
 - nodeset
 - <repeat> element, 103
 - binding UI controls, 53–56
 - number, 104
 - observer, 170
 - omit-xml-declaration, 85
 - repeat-bind, 116
 - repeat-id, 116
 - repeat-model, 116
 - repeat-nodeset, 116
 - repeat-number, 116
 - repeat-startindex, 116
 - replace, 84–85, 87
 - send action, 167–168
 - schema, 123
 - selected, 95
 - separator, 84
 - src, 16
 - standalone, 85
 - start, 74–75
 - startindex, 104
 - step, 75
 - submission, 19, 81–82
 - version, 85
- XForms elements
 - <action>, 80, 169–170

- XForms elements, *continued*
- interaction UI controls, 54, 58–59
 - <alert>, 16
 - presentation UI controls, 54, 56–58
 - <bind>, 107–108. *See also* Binding
 - <case>, 95–102
 - <choices>, selection controls, 72, 73
 - <copy>, 71–72
 - <delete>, 111–112, 172–173
 - <dispatch>, 170–171
 - <filename>, 76–77
 - <group>, 92
 - basics, 92
 - binding expressions, 94–95
 - event handlers used with <repeat> element, 112, 114–117
 - labeling, 92–94
 - navigating, 94
 - <help>, 16
 - presentation UI controls, 54, 56–58
 - selections from set of values, 65
 - <hint>, 16
 - presentation UI controls, 54, 56–58
 - selections from set of values, 65
 - <input>, 15–16
 - customizing input controls, 60–63
 - <insert>, 111–112, 172–173
 - <instance>
 - aggregation construct repeats, 107–108
 - binding expressions, 159–160
 - instance function, 159, 160
 - <item>, 18, 106, 146
 - <itemset>, 68–70, 72
 - <label>, 16
 - grouping UI controls, 92–94
 - presentation UI controls, 54, 56–58
 - selection controls, 64, 69–70
 - <load>, 166
 - <mediatype>, 76–77
 - <message>, 168–169
 - <model>, 12, 18
 - binding controls to model, 53–56
 - binding expressions, 159–161
 - data submissions, 82–83
 - shopping cart example, 123–124
 - <model>, properties
 - and CSS, 136–139
 - calculate, for dynamic computation, 147–148
 - constraint, for dynamic validation, 144–145
 - constraint, for limiting entries, 145–147
 - constraints, attaching via binding, 139–140
 - p3ptype, for privacy, 149
 - readonly, for controlling changes, 143–144
 - relevant, for model-based switching, 140–142
 - required, for mandatory fields, 142–143
 - type, for augmenting schemas, 148–149
 - <output>, 16
 - aggregation construct repeats, 109
 - <range>, 74–75
 - <refresh>, 181, 171–172
 - <rebuild>, 171–172
 - <recalculate>, 171–172
 - <repeat>
 - attributes, 104, 114–118
 - basics, 102–103
 - child elements, 104–105
 - index function, 155
 - information encapsulated in repeat construct, 103–104
 - process, 104–105
 - shopping cart model, 105–108
 - shopping cart UI, 108–111
 - shopping cart, adding controls, 111–113
 - shopping cart, user interaction, 113–114
 - within XHTML, 114–118
 - <revalidate>, 171–172
 - <secret>, 60–63
 - <select>, 65–68. *See also* Selection controls
 - <select1>, 64–68. *See also* Selection controls
 - <send>, 166–168
 - <sequence>, 42
 - <setfocus>, 165
 - <setindex>, 111–113, 172–173
 - <setvalue>, 165–166
 - <simpleType>, 38–39
 - <status>, 120
 - <submission>, 18. *See also* Submit component
 - shopping cart example, 133
 - what, how, and where to submit, 82–87
 - <submit>, 18–19
 - basics, 81–86

- process, 88–89
- using, 86–87
- Web services, 199
- <switch>
 - basics, 95
 - creating multi-page dialogs, 98–100
 - creating wizards, 100–102
 - example, 96–97
 - model-driven *versus* interaction-based
 - switching, 97–98
 - process, 95–96
- <textarea>, 60–63
- <todo>, shopping cart example, 120
- <toggle>, 95–97, 99, 102
- <trigger>, 78–81
 - data submission, 81, 88
 - event handlers, 164
 - event handlers used with <repeat> element, 111–112
 - navigation controls, 98–99
- <upload>, 76–77
- <value>, 68–72
- XForms event handlers, 111–112
 - basics, 164–165
 - declarative *versus* scripts, 217
- XForms events
 - accessibility, 215
 - avoiding device-specific events, 215
 - centralized handling, 216
 - correspondence between actions and events, 172, 184
 - definition, 17
 - DOMActivate, 181
 - error, 176
 - help, 180
 - initialization, 176–178
 - interaction, 176, 178–181
 - navigation, 179–180
 - notifications, 176, 181–184
 - of state changes, 183, 184, 216
 - processing, 178–179
 - triggering actions, 79–81
 - xforms-binding-exception, 176
 - xforms-compute-exception, 176
 - xforms-delete, 183
 - xforms-deselect, 181–183
 - xforms-disabled, 184
 - xforms-enabled, 184
 - xforms-focus, 81, 180
 - xforms-help, 180
 - xforms-hint, 180
 - xforms-in-range, 184
 - xforms-insert, 183
 - xforms-invalid, 184
 - xforms-link-error, 176
 - xforms-link-exception, 176
 - xforms-model-construct, 177
 - xforms-model-construct-done, 178
 - xforms-model-destruct, 178
 - xforms-next, 180
 - xforms-options1, 184
 - xforms-out-of-range, 184
 - xforms-previous, 180
 - xforms-readonly, 184
 - xforms-readwrite, 184
 - xforms-ready, 178
 - xforms-rebuild, 172, 178–179
 - xforms-recalculate, 172, 178–179
 - xforms-refresh, 172, 178–179
 - xforms-required, 184
 - xforms-reset, 180
 - xforms-revalidate, 172, 178–179
 - xforms-select, 181–183
 - xforms-setfocus, 179–180
 - xforms-submit, 18, 82, 180
 - xforms-submit-done, 183–184
 - xforms-submit-error, 183–184
 - xforms-valid, 184
 - xforms-value-changed, 181
- XForms functions
 - avg, 154–155
 - boolean, 152–153
 - count-not-empty, 156
 - date-time, 157–159
 - days-from-date, 157
 - if, 153, 154
 - index, 155
 - instance, 159–161
 - max, 155
 - min, 154–155
 - months, 158
 - node-set, 159, 160
 - now, 157, 158–159
 - number, 153–156
 - property, 156–157
 - seconds, 158

- XForms functions, *continued*
 - seconds-from-dateTime, 158
 - string, 156–157
 - XPath binding expressions, 159–161
 - versus* XPath functions, 151–152
- XForms model component, 11–14
 - model-view separation, Web services, 194, 197
 - multimodal access UIs, 206–207
 - Web services, 199
- XForms Processing Model (XPM), 175, 176
- XForms processors, 19
- XForms properties
 - calculate, 147–148
 - cardinality constraints, 146
 - constraint, 139–140, 144–147
 - p3ptype, for privacy, 149
 - properties and CSS, 136–139
 - readonly, 143–144
 - relevant, 98–102
 - for model-based switching, 140–142
 - required, 136, 138
 - mandatory fields, 142–143
 - type, 148–149
- XForms UI component, 11, 14–18. *See also*
 - Aggregation constructs
 - example
 - adding toolbar, 129–130
 - basics, 118–120
 - binding UI controls to task list, 129
 - creating UI via nested repeats, 124–128
 - declaring data model, 123–124
 - inserting inside XHTML page, 130–133
 - submitting task list, 133
 - task list, declaring instances, 122–123
 - task list, defining structure, 120–122
 - model-view separation, Web services, 194, 197
 - multimodal access
 - adaptation to users environment, 206
 - creating UIs, 206–209
 - graceful degradation, 203
 - predictability, 205–206
 - sharing common states, 204–205
 - synchronization, 202–203
- XForms UI controls
 - action triggers
 - basics, 78–79
 - process, 79–81
 - binding attributes, 53–56
 - collection of text input, 59–63
 - content, 51
 - CSS, 51
 - data submissions
 - basics, 81–86
 - process, 88–89
 - using, 86–87
 - data uploads, 76–78
 - date pickers, 207
 - design philosophy, 50–52
 - grouping
 - anonymous, 114–118
 - basics, 92
 - binding expressions, 94–95
 - event handlers, 112, 114–117
 - hiding/showing controls, 95–102
 - labeling, 92–94
 - navigating, 94
 - growing/shrinking during UI interaction, 102–118
 - hiding/showing, 95–102
 - input, 15–16
 - intent-based authoring, 51
 - interaction, 51
 - attributes and child elements, 54, 58–59
 - late binding, 207
 - presentation, 51
 - attributes and child elements, 54, 56–58
 - selections, basics, 17–18
 - selections, range of values, 74–75
 - selections, set of values
 - appearance attribute values, 72–73
 - atomic and list, 65–66
 - basics, 63–65
 - default selections, 66–67
 - dynamic, 68–70
 - grouping available choices, 72, 73
 - open and closed, 66
 - static choices, 67–68
 - XML structures, 70–72
 - structure, 53, 54
 - tightly bound, 16
 - vocabulary, 51
 - HTML Forms *versus* XForms, 52
 - Web services, 199
 - XForms components, 23
 - XML binding, DOM events, 51

- XFrames, X-Smiles, 43
- XHTML
 - elements
 - <body>, 12, 14
 - <head>, 12
 - <table>, 114–118
 - namespaces, 130–132
 - X-Smiles, 42–43
- XHTML+Voice (X+V2), 209
- XML
 - attributes, 33–34
 - basics, 33
 - binding. *See* Binding
 - browsers, X-Smiles, 42–43
 - documents
 - well-formed, 34
 - XPath role in XForms, 26
 - elements, 12, 33–34
 - <cart>, 86–87, 106
 - creating wizards, 100–102
 - <e-store>, 86
 - events, 17, 220–221
 - accessibility, 220–221
 - action handlers, 163–164
 - customizing input controls, 60–63
 - definition, 25–26
 - implementations using W3C standards, 45
 - multimodal access, 209
 - role in XForms, 44
 - instances, 12
 - namespaces, 34–35
 - definition, 26
 - processors, Xerces (Apache), 14
 - properties of elements, 34
 - role in XForms, 44
 - structures, selection controls, 70–72
 - submission, XForms feature, 22
 - type checking, 33
- XML Path Language. *See* XPath
- XML Schema, 13–14, 35
 - augmenting, 22
 - data binding, 36
 - data types, 37
 - built-in, 38–40
 - defining, XML Schema and IDL, 36, 41
 - defining aggregations, 40–42
 - definition, 26
 - definitions and declarations, 40–42
 - implementations using W3C standards, 45
 - reusing, 22
 - role in XForms, 44
 - X-Smiles, 42–43
- XPath
 - basics, 26–27
 - data types, 29
 - definition, 25
 - expressions, 29–30
 - binding, 159–161
 - functions, 29
 - versus* XForms functions, 151–152
 - implementations using W3C standards, 45
 - location paths, 27–28
 - syntax, 28–29
 - role in XForms, 44
 - variables, 29–30
 - X-Smiles, 42–43
- XSL Flow Objects, X-Smiles, 43
- X-Smiles, 42–43
 - example, 105
- X+V2 (XHTML+Voice), 209

