

# INDEX

## Symbols

- (minus) operator, 8, 40
- << (node precedes) operator, 45
- >> (node follows) operator, 45
- \$fs:dot, 289–292
- \$fs:last, 289–292
- \$fs:position, 289–292
- \$fs:sequence, 289–292
- (: :) (begin/end comments), 8
- \* (multiply) operator, 40
- \* (wildcard) operator, 14, 221
- ' ' (apostrophe), delimiting string literals, 8
- . (decimal), 8
- " " (quotation marks), delimiting string literals, 8
- // (double slash), 10, 13
- / (slash), 10, 99, 288
- [] (brackets), 10–11
- { } (curly brackets), 15, 93, 123
- + (plus) operator. *See* plus (+) operator
- = (equals) operator, 43–45

## A

- Abstract syntax, 241, 381, 443
- Access control
  - configuring, 410
  - DBMSs and, 415
- Accessor functions, built-in to XQuery, 49
- Analysis-time. *See* Query-analysis phase
- Annotated XSD Schema language, 331–334, 340
- Anonymous types
  - defined, 443
  - use of, 69
  - XML Schema, 117

- APIs (application programming interfaces), 415
- apostrophe ( ' '), delimiting string literals, 8
- Application programming interfaces (APIs), 415
- Arithmetic operators, 40–41
  - atomization and, 113
  - flexibility of, 297–298
  - kinds of, 40
  - normalizing, 295–296
  - untyped data, 41
  - XPath and, 105
- At (positional variable), 28–30
- Atomic types
  - conversion rules, 48
  - defined, 443
  - referencing, 119
  - XQuery data model, 90
- Atomic values
  - comparison operators and, 41–43
  - defined, 443
  - formal semantics, 267–269
  - items and, 90, 207
  - matching to types, 248–250
  - XQuery data model, 6
- Atomization
  - comparison operators and, 41–43, 298
  - conversion of arguments, 113, 217
  - defined, 443
  - value extraction and, 40, 104
  - as XPath implicit coercion, 294–296
- Attributes
  - defined, 443
  - document order of, 7
  - importing types and, 66
  - node attributes, 208
- Auction use case
  - converting input (XML) to output (XHTML), 196–197

- debugging, 197–199
- input data (in XML), 190–192
- output data (in XHTML), 194–196
- static typing, 201–203
- validation, 199–201
- XML Schema, 192–194

Audit logs, 355

avg(), 56

Axes

- reverse, 290–291
- XPath steps, 150
- XSLT vs. XQuery, 166–168

## B

Basic validation, 368

Basic XQuery

- defined, 444
- static typing and, 129
- type conformance and, 54

Begin/end comments (: :), 8

Bibliography, data sample, 5–6

Binary large objects. *See* BLOB (binary large objects)

Binding languages to databases, 421–422

BLOB (binary large objects)

- data storage and, 356
- defined, 444
- XML physical models and, 361

Boolean expressions

- branches of, 138
- Effective Boolean Value and, 103
- where clause and, 22

Boolean types, 168, 268

Boundary whitespace, 17

Brackets ([ ]), 10–11

Branches

- boolean values, 138
- conditional expressions, 218

Built-in functions, 47–49

- accessor types, 49
- numeric types, 48
- SQL types, 47–48

Built-in types

- constructors and, 70
- function signatures and, 55

- list of, 61
- sequence types, 61–62
- XML Schema, 96

## C

Canonicalized XML, 361, 444

Cartesian cross products, 22, 33, 371

Case-sensitivity, 93, 444

CASE statement, 72

CDATA, 109

Character large objects. *See* CLOBs (character large objects)

Choice types, 284

Clark, James, 156, 175

Client APIs, XQuery, 414–420

CLOBs (character large objects)

- data storage and, 316, 356
- defined, 444
- XML physical models, 360–361

Closure

- defined, 444
- principle of, 87
- property, 127

CLR (Common Language Runtime), 362, 444

Code, internal efficiency, 174–175

Collations, of XML data, 358, 365–366, 444

collection(), 9–10, 92, 386–387

Collections

- configuring, 407
- defined, 444
- native XML databases, 413–414
- overview of, 399

Columns, relational data model, 112

Command execution, DBMS, 415

Comment nodes, 7, 208

Comments, 8–9

Common Language Runtime (CLR), 362, 444

Comparison operators, 41–45

- atomization and, 113, 295
- equals operator, 43–45
- error handling and, 137
- general comparison operators, 42–43
- node comparisons, 45
- transitivity property, 104–105
- value comparison, 41–42

- value comparison operators, 41
  - XPath and, 106
  - Complex types
    - defined, 444
    - defining and naming, 96
    - formal semantics, 271
  - Composed representation
    - application types supported, 319
    - composition techniques and, 318, 320–325
    - LOB representation and, 316–317, 319
    - overview of, 317
    - querying/transforming XML documents, 349
    - shredding and, 318–319
  - Composition techniques
    - annotated XML templates, 331–334
    - concepts, 320–325
    - default mapping, 325–328
    - defined, 444
    - shredding and, 336
    - SQL/XML, 328–331
  - Compositionality
    - defined, 445
    - principle of, 86
  - Computed constructors
    - alternative syntax to XML constructors, 123
    - element construction with, 226–227
    - functionality of, 16–17
  - Conclusions, 242, 445
  - Concrete syntax, 242, 445
  - Conditional expressions
    - branches of, 218
    - overview of, 38–39
    - promotion rules, 218–219
    - static typing, 258
  - Configuration, native XML databases, 406–410
    - access control, 410
    - collections, 407
    - databases, 407
    - indexes, 407–409
    - locking, 410
    - schemas, 410
    - stored functions, 409–410
    - triggers, 409–410
  - Conjunction rules, evaluation order, 263–264
  - Connections, DBMS access, 415
  - Consolidation, 337, 445
  - Constructors
    - casting and typed value, 70–71
    - computed, 16–17, 123, 226–227
    - constructed element type and, 123
    - defined, 445
    - document creation, 15
    - dynamic content, 15
    - implicit validation, 75–77
  - Content management application, native XML database, 432–434
  - Context items
    - defined, 445
    - untyped data and, 109–112
    - XPath, 102–103
  - Conversion rules
    - atomic types, 48
    - function arguments, 69
    - return values, 70
  - Cotton, Paul, 82
  - Curly brackets ({}), 15, 93, 123
- ## D
- Data binding, 421
  - Data definition, 401
  - Data definition interfaces, 401–405
    - database-design phase, 403–404
    - overview of, 401–403
    - query-analysis time, 404
    - query-authoring phase, 404
    - query-evaluation time, 405
  - Data extraction/insertion, DBMS access, 415
  - Data interchange
    - models, 353–357
    - relational systems, 355
    - XML format for, 81
  - Data manipulation, 401
  - Data models
    - defined, 445
    - encoding unknown and inapplicable data, 112
    - relational. *See* Relational data model
    - XML. *See* XML data model

- XQuery. *See* XQuery (XQ-DM) data model
- Data modification language, 379–380
- Data-oriented (or data-centric) XML, 428–429, 445
- Data sources, 315–316
- Data structures, 175
- Database command language, 411–412
- Database configuration, 412–413
  - database objects, 412
  - indexes, 412
  - root objects, 412
  - triggers, 412–413
- Database-design phase, 403, 403–404
- Database languages, 154
- Database objects, 412
- Databases
  - configuring, 403, 407
  - defined, 393
  - managing. *See* DBMSs (database management systems)
  - native XML. *See also* Native XML databases
  - object oriented databases (OODB), 414
  - relational. *See also* Relational databases
- Datatypes. *See* Types
- Date, 70, 268
- DBMSs (database management systems), 393–394
  - access features, 415
  - interoperability, 400–401
  - native XML databases and, 393–394
  - row updates, 405–406
- Debugging. *See also* Error handling
  - auction use case, 197–199
  - static typing and, 201–203
  - validation and, 200–201
- Decimals (.), 8
- Decoupled approach, XQuery processing, 381–382
- Default mapping, 325–328, 445
- The Definition of Standard* (Milner, Tofte, and Harper), 237
- Dependencies, expressions, 178
- Dependent joins, 343–344, 446
- Derivation by extension, inheritance, 96, 446
- Derivation by restriction, inheritance, 96, 446
- Derived types, 96, 446
- derives, (matching judgments), 275–276
- Descendant operator, path expressions, 221
- Design principles, XQuery, 86–88
- distinct-values(), 30–33
- div operator, 40, 99
- Division by zero, 136
- doc(), 9–10, 92
- Document nodes, 7, 208
- Document Object Model. *See* DOM (Document Object Model)
- Document order
  - defined, 446
  - ordered sequences and, 138
  - Query data model and, 90
  - XML documents, 7
  - XPath, 100
- Document-oriented (or document-centric) XML, 428–429, 446
- Document Style Semantics and Specification Language (DSSSL), 155
- Document Type Definitions. *See* DTDs (Document Type Definitions)
- Documents, well-formed, 396
- DOM (Document Object Model)
  - BLOBs, 361
  - building, 421
  - defined, 446
  - updates and, 314
  - XPath and, 150
- Double slash (/), 10, 13
- Doubles (E or e), 8
- DSSSL (Document Style Semantics and Specification Language), 155
- DTDs (Document Type Definitions)
  - absence of schemas, 109
  - data definition interfaces, 401
  - defined, 446
  - schemas, 4
  - XML documents, 128–129
- Dublin Core, 14
- Duration type, XML Schema, 97
- Dynamic errors
  - defined, 446
  - handling in XQuery, 136
  - input functions and, 10
  - kinds of errors, 251–252
- Dynamic rules, 246–248
- Dynamic semantics, 241–254

- abstract syntax, 241
  - defined, 240, 447
  - element constructors, 302–304
  - environments, 245–248
  - errors, 250–254
  - evaluation judgments, 241
  - FLWOR expressions, 281–282
  - inference rules, 242–245
  - matching values and types, 248–250
  - static semantics and, 254
  - Dynamic types
    - associating types with values, 212
    - compared with static types, 126
    - defined, 447
    - general comparison operators and, 43, 111
- E**
- E* or *e* (doubles), 8
  - Edge tables
    - defined, 447
    - table shredding and, 364–365
    - for XML data, 338–339
  - Effective Boolean Value
    - defined, 447
    - error handling and, 137
    - functions of, 103
  - element(), 270
  - Element constructors, 122–125
    - computed, 123
    - data construction with, 4, 226–227
    - defined, 447
    - dynamic semantics, 302–304
    - enclosed expressions, 15–16
    - end tags and start tags, 93
    - formal semantics (XQ-FS), 301–304
    - implicit validation and, 75–77
    - node identity and, 299–300
    - Quilt proposal, 122
    - return clause and, 26–27
    - schema validation and, 124–125
    - static semantics, 304
    - stores and, 301–302
    - XSLT vs. XQuery, 160–163
  - Element nodes
    - kinds of nodes, 7, 208
    - referencing, 119–120
  - Element types, 270
  - Elements
    - declaring in schemas, 95, 447
    - defined, 447
    - global and local declarations, 204–205
    - importing types and, 65–66
    - matching judgments, 273–278
    - node values, 268–269
  - Emit as events, 421
  - empty(), 48
  - empty sequence(), 38
  - Empty sequences, 42, 113–114
  - Enclosed expressions, 15–16
  - Encoding, 358, 365–366, 448
  - End tags, 93, 448
  - Entity references, 9
  - Environments
    - defined, 448
    - dynamic, 245–248
    - inference rules and, 246–248
    - static, 254–255
  - eq operator, 41–42
  - Equals (=) operator, 43–45
  - error(), 136
  - Error handling, 250–254. *See also* Debugging
    - auction use case, 201–203
    - detecting errors, 169
    - division by zero and, 136
    - dynamic errors and, 136
    - formalizing notation of raising errors, 250–254
    - if-then-else expressions, 138
    - kinds of errors, 251–252
    - non-deterministic (special rules), 136–137
    - static type errors, 125–126, 215, 219
    - try/catch mechanisms, 138
    - type errors and, 223
    - watershed issues, XQuery design process, 136–138
  - Error types, 136
  - Error values, 136
  - Evaluation judgments
    - defined, 448
    - notation for, 241
    - stores and, 301–302
  - Evaluation order, static semantics, 262–264
  - Evaluation-time. *See* Query-evaluation phase

except operator, 46  
 Execution order, XQuery/SQL integration, 384  
 Existential quantification  
   defined, 448  
   design of XQuery and, 88  
   general comparison operators and, 114  
   overview of, 36–37  
 exists(), 49  
 Expressions  
   compositionality and, 86  
   delimiting enclosed, 93  
   dependencies of, 178  
   FLWOR. *See* FLWOR expressions  
   matching and ranking, 423  
   optimizing, 179–181  
   path. *See* Path expressions  
   static typing and, 212  
 Extensible Markup Language (XML). *See* XML (Extensible Markup Language)

## F

Facets  
   checking with constructor function, 71  
   defined, 448  
   XML Schema, 95  
 Factored types  
   defined, 449  
   FLWOR expressions, 224, 282–286  
   overview of, 220  
 Factorization theorem, 285–286  
 Fibonacci sequences, 55  
 Flat data structures, 84  
 FLWOR expressions, 4  
   for clause, 19–22  
   clauses, 19  
   combining data sources, 33–34  
   combining with distinct values() to remove duplicates from subtrees, 30–33  
   defined, 449  
   direct translation into XSLT, 164–165  
   dynamic semantics, 281–282  
   factored types and, 224, 282–286  
   grammar for, 279  
   iteration with, 140–141, 225  
   let clauses, 19–22  
   normalizing, 280–281  
   optimizing joins, 180–181  
   order by clause, 23–26, 226  
   overview of, 18–19  
   return clause, 26–28  
   static semantics, 282–286  
   where clause, 22–23, 225  
 fn:boolean, 291  
 for clauses  
   combining data sources, 33–34  
   dynamic semantics, 281–282  
   FLWOR expressions, 19–22  
   FLWOR grammar, 280  
   normalizing, 280–281  
   overview of, 19  
   positional variables and, 28–30  
 Foreign keys, 84, 449  
 Formal semantics (XQ-FS), 237–305  
   benefits of, 238–240  
   combining types, 210  
   defined, 449  
   dynamic semantics. *See* dynamic semantics  
   element constructors, 301–304  
   FLWOR expressions, 279–286  
   function calls, 296–298  
   implicit operations, 293–296  
   irregular data, 293–298  
   matching judgments, 272–278  
   node identity, 299–300  
   normalization, 264–266  
   notation, 204  
   overview of, 240–241  
   path expressions, 287–292  
   sequence types, 209–210  
   static semantics. *See* static semantics  
   subtyping, 278–279  
   types, 204, 269–272  
   values, 268–269  
   XML Schema conversion, 204–206  
 fs namespace, 289  
 Full-text searches, 422–428  
   features, 427–428  
   invoice example, 431  
   overview of, 422–423  
   query-execution plans, 424–426  
   ranking algorithms, 426–427  
   return clause, 424

- techniques, 423
- Function calls, 216–217, 296–298
- Function libraries, 378–379
- Function overloading
  - defined, 449
  - overview of, 132
  - resolving, 296–297
  - XQuery and, 133, 135
- Function resolution, 132–135
  - defined, 449
  - overloading and, 296–297
  - overview of, 132
  - simulating polymorphism, 135
  - XPath 1.0 core function library, 133–134
- Function signatures, 216
  - built-in types and, 55
  - declaring parameters with sequence types, 67–70
  - defined, 449
- Functional languages
  - defined, 449
  - lazy evaluation, 177–178
  - pipelining, 175–176
  - XQuery as, 86
  - XSLT as, 146–147
- Functions, 216–217
  - built-in, 47–49
  - calling, 216–217, 296–298
  - error handling, 137
  - external, 52
  - library modules and, 51–52
  - resolving overloaded, 296–297
  - signature of, 216
  - type definition and, 118–119
  - user-defined, 49–50
  - variable definition and, 50
  - XPath 1.0, 151
  - XSLT vs. XQuery, 163–164

## G

- General comparison operators
  - atomization and, 298
  - defined, 450
  - equals (=) operator, 43–45
  - overview of, 42–43
  - rules for handling data based on type, 111

- transitivity property and, 105
- unknown values and, 114
- value comparison operators and, 41
- Global element declarations, 204–205, 271, 450
- GROUP BY, SQL, 330, 340
- Grouping
  - defined, 450
  - example, 233–234
  - influence of SQL on XQuery, 107
  - XML data generation and, 324–325

## H

- Hierarchical groups, XML data, 324–325
- Hierarchical joins, 323–324, 450
- Hierarchical order, 93
- HTML, 146
- HTTP, 395
- Hypotheses, inference rules, 242

## I

- Identity
  - defined, 450
  - node, 4, 6, 299–300
- idiv operator, 40, 99
- if clause
  - conditional expressions and, 38
  - normalizing, 280–281, 294
- If-then-else expressions, 131, 138
- Impedance mismatch problems, 421–422
- Implicit operations, 293–296
  - examples, 294–296
  - flexibility of, 293
  - XPath, 104–105
- Indexes
  - canonicalized XML and, 361
  - configuring, 407–409, 412
  - data definition and, 403
  - defined, 450
- Inference rules
  - dynamic environments, 246–248
  - hypotheses and conclusions, 242
  - operational semantics and, 241
  - proof tree, 243–244

- static environments, 255–257
  - static typing, 126, 234
  - type soundness theorem and, 260
  - Information items, 89, 450
  - Infoset (Information Set), 89, 395, 451
  - Infoset-level fidelity, XML storage, 360
  - Inheritance
    - defined, 451
    - type inheritance and, 96
    - XML Schema, 96
    - XPath, 99
    - XQuery, 87
  - Inlining, 337, 451
  - Input data
    - auction use case, 190–192
    - Query data model and, 91–92
    - uptyped data, 109
    - validating, 199
  - Input functions, 9–10
  - Instance-of expressions, 131
  - instance of (operator), 72
  - Integers
    - atomic values, 268
    - numeric literals, 8
    - XML and, 168
  - Integrated approach, XQuery processing, 381–383
  - Interfaces, native XML databases, 399–422
    - configuration interfaces, 406–410
    - data definition interfaces, 401–405
    - interoperability, 400–401
  - internal coding efficiency, 174–175
  - International Standards Organization (ISO), 400
  - Internet Explorer, 145
  - Interoperability, 400–401
  - intersect operator, 46–47
  - Inverting hierarchies, 34–35, 37
  - Invoice archive application, 430–431
  - is/is not, node comparisons, 45
  - ISO (International Standards Organization), 400
  - Item type, 270
  - Items
    - atomic values, 7, 268
    - context items, 102–103
    - defined, 451
    - information items, 89
    - node values, 268
    - testing for type, 72
    - values and, 207
    - XQuery data model, 90
  - Iterations
    - FLWOR expressions, 140–141, 225
    - nested (joins), 159
    - pipelining and, 176
- ## J
- Java Virtual Machines (JVMs), 362, 451
  - JDBC (Java Database Connectivity), 400, 416
  - Joins
    - combining data sources, 33–34
    - defined, 451
    - dependent, 343–344
    - optimization, 180–181
    - simple, 342–343
    - Sorted Outer Unions (SOU), 344–347
    - XSLT and XQuery and, 159
  - Judgments. *See* Evaluation judgments
  - JVM (Java Virtual Machines), 362, 451
- ## K
- Keywords
    - defined, 451
    - referencing nodes by, 120
    - as syntax for XQuery, 82
    - XPath, 99
  - KindTest*, step expressions, 12
- ## L
- last(), 176
  - Lax validation mode, 200, 368
    - defined, 452
    - element constructors and, 125
    - uses of, 230–232
    - XML Schema, 75–77
  - Layered processing model, XML applications, 310–311
  - Lazy evaluation, 177–178



let clause  
 dynamic semantics, 281–282  
 FLWOR expressions, 19–22  
 FLWOR grammar for, 279  
 iteration controls, 140–141  
 normalizing, 280–281  
 overview of, 19  
 static semantics, 283  
 variables, 214

Library modules, 51–52

List type, 99, 452

Literal expressions  
 numeric types, 8  
 operators, 213–214  
 string literals, 8–9  
 types associated with, 212–213

LOB representation  
 application types supported, 320  
 coexisting with composed representation, 319  
 compared with composed representation, 316–317  
 querying or transforming XML documents, 348

LOBs (large object)s  
 data storage and, 310, 356  
 defined, 452

Local elements declarations, 204–205, 221–222, 452

Locking, 410, 433

Logical models, XML data, 359–360

Logical operators, 113

## M

Mapping combined XQuery/SQL queries, 380–385

Mapping languages, 334

Mapping XML to relational data, 309–352  
 annotated XML templates, 331–334  
 applications for, 312–315  
 composed representation, concepts, 320–325  
 data sources, 315–316  
 default mapping, 325–328  
 emitting XML documents, 339–347  
 overview of, 309–310

processing models for, 310–312  
 querying and updating XML documents, 347–350  
 representation approaches, 316–320  
 shredding, 335–339  
 SQL/XML, 328–331

Markup data, 353–355, 452

Matching judgments, 272–279  
 defined, 452  
 derives, 275–276  
 matches, 276–278  
 notation for, 249–250  
 overview of, 272–274  
 substitutes, 275  
 subtype, 278–279  
 yields, 274–275

max(), 47–48

Metadata, 84, 452

Minus (-) operator, 8, 40

mod operator, 40

Multiply (\*) operator, 40

Mutators, 379, 452

## N

Namespace  
 attributes, 16  
 defined, 453  
 influences of XML on XQuery, 93  
 schemas, 64  
 target namespace, 117  
 URL for, 211

Namespace prefixes  
 defined, 453  
 library modules and, 52  
 QNames and, 93–94  
 schema imports and, 58

*NameTest*, step expressions, 11–12

Native XML databases, 393–435  
 collections and storage, 413–414  
 command language, 411–412  
 configuration interfaces, 406–410  
 content management application, 432–434  
 data definition interfaces, 401–405  
 full-text searches, 422–428  
 getting the data, 421–422  
 interfaces, 399–400

- interoperability, 400–401
  - invoice archive application, 430–431
  - overview of, 393–395
  - sample applications, 428–430
  - text data, 395
  - update interfaces, 405–406
  - XML data model and, 396–399
  - XQuery client APIs, 414–420
  - Nesting
    - defined, 453
    - iterations, 159
    - sequences, 95
    - XML elements, 83–84
  - Netscape, 145
  - Node comparison operators, 45
  - Node hierarchy, 89–90, 453
  - Node tables, 363–365, 453
  - Node tests, XPath steps, 150
  - Node types, 270
  - Node values, 267–269
  - Nodes
    - combining and restructuring, 18
    - creating, 14–18
    - defined, 453
    - formal semantics, 267–270
    - identity, 299–300
    - of items, 90
    - kinds of, 6–7, 208
    - locating with path expressions, 10–14
    - referencing, 119–120
    - steps, 100
    - XML document structure, 4
  - Nonlinear hierarchy, 324–325, 454
  - Nonrecoverable errors, 98
  - Normalization rules
    - defined, 240, 454
    - FLWOR expressions, 280–281
    - irregular data, 294–298
    - overview of, 264–266
    - XPath, 288–292
  - not(), 48
  - Notation. *See also* Formal semantics (XQ-FS)
    - comments, 8
    - path expressions, 10
    - string literals, 8–9
    - XML and XQuery and, 93
    - XPath, 99–100
  - Null
    - defined, 454
    - relational data and, 85
    - sorting, 25
  - Numeric functions, 48
  - Numeric literals, 8
- ## O
- Object oriented databases (OODB), 414
  - Occurrence indicators
    - defined, 454
    - sequence types, 61, 210
    - type references and, 120–121
  - ODBC (Open Database Connectivity), 400, 416
  - OLTP (Online transaction processing), 454
  - OODB (object oriented databases), 414
  - Open Database Connectivity (ODBC), 400, 416
  - Operational semantics, 241, 454
  - Operators, 39–47
    - arithmetic, 40–41
    - comparison, 41–45
    - existential quantification and, 88
    - literals and, 213–214
    - ordered sequences and, 138–141
    - overview of, 39–40
    - sequence, 46–47
    - uptyped data and, 109, 111
    - XPath 1.0, 151
  - Optimization, 170–183
    - defined, 454
    - expression rewriting, 178–181
    - internal coding efficiency, 174–175
    - overview of, 170–171
    - pipelining and lazy evaluation, 175–178
    - query-analysis phase and, 88
    - query-execution plans, 426
    - query processors and, 169
    - static typing, 125–126
    - time uses and, 171–174
    - type information, 181–183
    - XSLT and, 166
  - OQL, 107–108
  - order by clause
    - FLWOR expressions, 140–141, 226

- FLWOR grammar and, 279
  - function of, 23–26
  - overview of, 19
  - Outer joins, 107, 455
  - Output data
    - auction use case, 194–196
    - Query data model and, 91–92
    - validating, 199
  - Overloaded functions. *See* Function overloading
- P**
- Parse errors, 254
  - Partial updates, 406, 455
  - Path expressions, 4
    - axes, 166
    - defined, 455
    - descendant operator, 221
    - evaluating, 10–12
    - examples, 12–14, 219–222
    - factored type and, 220
    - formal semantics, 287–292
    - locally declared elements in, 221–222
    - notation, 10
    - predicates, 10–11
    - rules for executing, 101–102
    - steps, 150–151
    - type error and, 11
    - wildcards, 221
    - XPath, 100
  - Path extraction, 421
  - PCDATA, 109
  - Physical mapping, XQuery/SQL queries, 380–385
  - Physical models, XML datatype, 360–365
    - BLOB (binary large objects), 361
    - CLOB (character large objects), 360–361
    - relational table mappings, 363–365
    - user-defined, 361–362
  - Pipelining, 175–177
  - Plus (+) operator
    - arithmetic operators and, 40
    - normalizing, 295
    - numeric literals and, 8
  - Polymorphism
    - not supported by XQuery, 134
    - overview of, 132–133
    - simulating, 135
  - Position, of nodes, 100
  - Positional variables, 28–30
  - Post-Schema Validation Infoset. *See* PSVI (Post-Schema Validation Infoset)
  - Predicate expressions, 222–224
    - defined, 455
    - empty sequences and, 114–115
    - as integer-valued expression, 224
    - kinds of, 102–103
    - normalizing, 290–291
    - overview of, 10–11
    - picking elements by position, 223–224
    - steps and, 150
    - what it does, 222
  - PrimaryExpression*, 12
  - prime(), 285
  - Prime types, 283–284
  - Primitive types
    - defined, 455
    - XML Schema and, 96
    - XQuery and, 87
  - Principles, XQuery design, 86–88
  - Processing instruction nodes, 208
  - Processing models, mapping XML to relational data, 310–312
  - Programming languages
    - database languages, 154
    - efficiency vs. determinism, 137–138
    - functional vs. procedural, 4
    - mapping languages, 334
    - pipelining and, 175–176
    - precise description of, 238
    - query languages, 106–108
    - transformation languages, 152–154
    - XQuery-related. *See* XML (Extensible Markup Language); XML Schema; XPath
  - Prolog
    - binding namespace prefix to URI, 94
    - defined, 455
    - external functions, 52
    - variables, 52
  - Proof trees
    - defined, 455
    - environments and, 247–248

- inference rules, 243–245
  - static typing and, 258
- PSVI (Post-Schema Validation Infoset)
  - defined, 455
  - schema validation and, 89
  - typing datatypes, 368

## Q

- Qualified names (QNames), 93, 455
- Quantifiers
  - computing, 283–284
  - error handling and, 137
  - inverting hierarchies and, 37
  - overview of, 36–37
- quart(), 285
- Queries
  - basing on XML format, 82
  - optimizing by rewriting, 178–179
  - phases of, 88, 211–212, 402–404
  - ranking algorithms, 426–427
  - relational compared with XML query,
    - 84–85
    - results, 399
    - testing existence of XML structure,
      - 372–373
  - XML data from relational database, 313
  - XML documents, 347–350
- Query-analysis phase
  - overview of, 402–404
  - query phases and, 88
  - static analysis, 211–212
- Query-authoring phase, 403–404
- Query data model, 89–92
  - as basis of XQuery, 89
  - defined, 456
  - input and output of data, 91–92
  - kinds of data models, 87, 89–92
  - specifications based on, 89
  - type annotation, 118
  - XML documents represented by, 90–91
  - XPath and, 89–90
- Query-evaluation phase
  - answers provided by, 211–212
  - overview of, 402–403, 405
  - query phases and, 88
  - type soundness and, 258–262
- Query-execution plans, 424–426
- Query languages
  - defined, 456
  - influences on XQuery, 106–108
  - need for new language, 152–156
- Query processors, 169, 174
- Quilt language
  - defined, 456
  - element constructors, 122
  - influence on XQuery, 106–107
- Quotation marks (" "), delimiting string
  - literals, 8

## R

- Rank
  - algorithms for, 426–427
  - defined, 456
  - ranking expressions, 423
- Recursive functions, 50, 456
- Relational data, 84
- Relational data model
  - compared with XML data model, 84–86,
    - 353
  - defined, 456
  - mapping XML documents to. *See* Mapping XML to relational data
  - pipelining and, 175–176
  - query optimization and, 178–179
  - rows and columns of data in, 112
- Relational databases
  - data source for XML applications, 309
  - defined, 456
  - emitting XML documents or XML
    - fragments, 312–313, 339–347
  - list of, 357
  - querying or transforming XML
    - documents, 313
  - shredding and, 335–336
  - storing XML data. *See* XML (Extensible Markup Language), relational storage
  - strongly typed nature of, 53
  - XML representation of, 3
- Relational-level fidelity, XML storage, 360
- Relational table mappings
  - data storage and, 356
  - node tables, 363–365

- table shredding, 364–365
- Relational tables, XML views of, 388–390
- RELAX-NG, 129, 401
- Reserved words, 99, 456
- Result trees, XSLT, 160–161
- return clause
  - FLWOR grammar and, 279
  - full-text searches, 424
  - function of, 26–28
  - iteration controls, 140–141
  - overview of, 19
- Return values, 70
- Root nodes, 90, 456
- Root objects, 412
- Rows, relational data model, 112
- Rules
  - dynamic inference rules, 246–248
  - promotion rules for conditional expressions, 218–219
  - static inference rules, 255–257
  - untyped data, 109–110
  - XSLT as rule-based language, 147

## S

- Salton, Gerard, 426–427
- SAX (Standard API for XML), 421
- Saxon, 146, 177
- Schema imports
  - Basic XQuery, 129
  - defined, 457
  - overview of, 210–211
  - typed value extraction and, 40
- Schema validation
  - defined, 457
  - element constructors and, 124–125
  - invoice example, 431
  - modes of, 368
  - PSVI and, 89
  - type annotation and, 118
  - xs:anyType, 62
- Schemas
  - built-in types and, 53, 56–60
  - configuring, 410
  - conformance principle, 87
  - declaring elements, 95
  - defined, 457

- importing types from, 62–67
- information in, 64–65
- W3C XML Schema language, 367–368
- XQuery, 4
- SELECT statement, SQL, 164
- Semantic constraints, 86, 457
- Semi-structured data
  - defined, 457
  - optimizing, 169
  - XML and, 316, 353, 354–355
  - Sequence operators, 46, 46–47
- Sequence types, 60–67
  - built-in, 61–62
  - converting into choice types, 284
  - defined, 457
  - function signatures and, 67–68
  - imported from schemas, 62–67
  - lists of, 209–210
  - Occurrence indicators, 61, 210
  - overview of, 60
- Sequences
  - heterogeneous nature of, 95–96
  - of items, 7
  - operators for ordered sequences, 138–141
- Sets, XPath, 151
- SGML (Standard Generalized Markup Language), 155
- Shanmugasundaram, Jayavel, 344
- Shredding, 335–339
  - adding information to composition, 336
  - composed representation and, 318–319
  - database creation, 335–336
  - defined, 310, 457
  - full XML support, 337–338
  - inlining and consolidation, 336–337
  - overview of, 335
  - schema-independent representation, 338–339
  - table shredding, 364–365
- Signature. *See* Function signatures
- Simple joins, 342–343
- Simple types
  - constructor functions for, 70–71
  - defined, 457
  - formal semantics, 271
  - list of, 6
- Skip validation mode, 77, 200, 368

- defined, 457
  - element constructors and, 125
  - uses of, 230–232
- slash (/), 10, 99, 288
- SOAP messages, 355, 458
- sort(), 139
- SORT BY, SQL, 340
- Sort keys, 139–140, 458
- Sorted outer unions (SOU), 344–347, 458
- Sorting, XPath vs. XSLT, 176–177
- SOU (sorted outer unions), 344–347, 458
- Sources, XML data
  - relational, 315
  - XML sources, 315–316
- Spelling errors, 59
- SQL-2003
  - defined, 458
  - mapping relational tables to XML, 388
  - relational storage and, 357
  - SQL WITH clause, 375
  - XML data storage, 366
  - XML datatype, 359
- SQL Access Group, 400
- SQL multimedia (SQLMULTI), 423
- SQL query language
  - built-in functions (XQuery), 47–48
  - WITH clause, 375
  - as database query language, 154
  - defined, 458
  - development of XQuery and, 83
  - generating XML data, 328–331, 340–341
  - influence on XQuery, 107
  - INSERT clause, 387
  - mapping SQL types to XML Schema types, 377–378
  - SELECT clause, 164, 371
  - three-valued logic, 112, 115–116
  - updates, 314–315
  - XPath sets compared with SQL tuples, 151
  - XQuery designers' background with, 155–156
- SQL query language, integration with
  - accessing SQL data in XQuery, 375–378
  - aspects not related to queries, 370
  - augmenting XQuery static context, 374–375
  - data modification language, 379–380
  - decoupled approach, 381–382
  - integrated approach, 381–384
  - issues with, 385–386
  - logical models for XML data, 359–360
  - physical mapping of combined
    - XQuery/SQL queries, 380–385
  - physical models for XML data, 360–365
  - storing XML data, 357–358, 366
  - typing XML data, 366–369
  - XQuery and, 370–374
  - XQuery function libraries, 378–379
- SQL/XML
  - composition technique, 328–331
  - defined, 458
  - mapping relational tables to XML, 388
  - mapping SQL types to XML Schema types, 377–378
  - SQL-2003 standard, 357
  - W3C XML Schema, 53
  - XML datatype, 359
- Standard API for XML (SAX), 421
- Standard Generalized Markup Language (SGML), 155
- Standards
  - interoperability and, 400–401
  - SQL-2003 standard, 357
- Start tags, 93, 458
- Static analysis, 272
- Static context, 374–375
- Static environment
  - defined, 458
  - validation context of, 228
  - variables in, 214–215
- Static semantics, 254–264
  - defined, 458
  - element constructors, 304
  - evaluation order, 262–264
  - FLWOR expressions, 282–286
  - inference rules, 255–257
  - notation for static environment, 254–255
  - overview of, 254–258
  - rules, 255–257
  - type soundness and, 258–262
  - typing judgments and, 254
- Static type-checking, 128, 459
- Static type error, 219

- Static types
    - checking, 128
    - defined, 459
    - evaluation-time types and analysis-time types, 211–212
    - schema imports and, 210–211
    - sequence types, 209–210
    - tests and, 60
    - values, 207–208
    - XML Schema and XQuery types, 204–207
  - Static typing
    - advantages of, 126, 188–189, 234
    - associating types with values, 212
    - Basic XQuery and, 129
    - conditionals, 218–219
    - debugging cycle and, 201–203
    - defined, 240
    - element constructors, 226–227
    - error checking and optimization, 125–126, 130
    - expressions supporting, 131–132
    - FLWOR expressions, 224–226
    - functions, 216–217
    - grouping, 233–234
    - inference rules, 126–127, 234
    - literals, 212–214
    - path expressions, 219–222
    - predicates, 222–224
    - schema imports and, 210–211
    - sequence types, 209–210
    - spelling error detection, 59
    - static type-checking, 128
    - validated annotations vs. structural comparisons, 127–128
    - validation compared with, 201
    - validation context, 227–230
    - validation modes, 230–232
    - values, 207–208
    - variables, 214–215
    - weaknesses of, 234
  - Static Typing option, 129–130
  - Steps
    - defined, 459
    - forward vs. reverse, 290
    - of path expressions, 10–11, 13, 100
  - Storage
    - native XML databases, 413–414, 431
    - XML datatype, 366
  - Stored functions, 409–410
  - Stores
    - capturing node identity, 299–300
    - defined, 459
    - evaluation judgments and, 301–302
  - Strict validation mode, 77, 200, 368
    - defined, 459
    - element constructors and, 124
    - uses of, 230–232
  - String-level fidelity, XML storage, 360
  - String literals, 8–9
  - String operators, 105–106, 268
  - String values
    - defined, 459
    - operators and, 39
    - Query data model and, 91
  - Strongly typed data, 182. *See also* Structured data
  - Structured data
    - defined, 459
    - relational management of, 353
    - semi-structured data and, 169
    - XML and, 316, 354–355
    - XQuery and, 53, 56
  - Structured types, SQL, 83
  - Subelements, 319, 323–325, 388, 459
  - substitutes, (matching judgments), 275
  - Substitution groups
    - creator element and, 64
    - defined, 459
    - type inheritance and, 96
  - Subtrees, 30–33
    - subtype, (matching judgments), 278–279
  - Subtyping, 272
- ## T
- Table shredding, 364–365
  - Tables
    - edge tables, 338–339, 364–365, 447
    - node tables, 363–365, 453
    - relational, 112, 388–390
    - relational table mappings, 356, 363–365
  - Tags, 93, 459
  - Tamino, 394, 408
  - Target namespace, XML namespaces, 117

- Template rules, 165–166
- Text
  - formal semantics, 270
  - node values, 268–269
  - XML data, 395
- Text nodes, 7, 208
- then clauses, 38
- Three-valued logic, 112, 115–116, 460
- Top-level XQuery
  - collection() and, 386–387
  - overview of, 386
  - XML views of relational data, 388–390
- Transaction controls, DBMSs, 415
- Transformation languages, 152–154
- Transformations
  - inverting hierarchies, 34–35
  - tree-to-tree, 147–148
  - XML data from relational database, 313
  - XML datatype instances, 371
  - XML transformations, 145
  - XSLT and, 152
- Transitivity, 104–105, 460
- Treat expressions, 74, 131–132
- Trees
  - comparing XSLT and XQuery, 160–163
  - design efficiency of, 175
  - operator trees, 380–381
- Triggers
  - configuring, 406, 409–410, 412–413
  - defined, 460
- Try/catch mechanisms, 138
- Tuples
  - for clauses, 19–22
  - FLWOR expressions, 19
  - let clauses, 19–22
  - order by clauses, 23–26
  - where clauses, 22–23
  - XPath sets compared with, 151
- Two-phase commit, 431
- Two-valued logic, 114, 460
- Type annotation, 91, 118, 460
- Type errors
  - defined, 460
  - detecting, 58
  - kinds of, 251–252
  - path expressions and, 11
  - static typing and, 223
- Type promotion, 69, 460
- Type soundness
  - defined, 461
  - relating static and dynamic semantics, 258–262
  - static typing and, 126
- Type soundness theorem, 240, 260, 461
- Type system, 203–211. *See also* Static typing
  - analysis-time types, 211–212
  - defined, 461
  - error detection, 227
  - evaluation-time types, 211–212
  - schema imports and, 210–211
  - sequence types, 209–210
  - type strictness, 168–170
  - values, 207–208
  - XML Schema and XQuery, 204–207
- Typed values
  - defined, 461
  - extracting, 39–40
  - nodes converted to, 217
  - Query data model and, 91
  - XQuery, 70–71
- Typed variables, 71–72
- Types
  - atomic types, 90
  - defined, 461
  - formal semantics, 269–272
  - function definitions and, 118–119
  - mapping SQL to XML Schema, 377–378
  - matching values to, 248–250, 272–274
  - optimizing, 181–183
  - referencing, 119–121
  - simple and complex, 4
  - type strictness, 168–170
- Types, XQuery
  - atomic values, 208
  - built-in, 61–62
  - casting and typed value construction, 70–71
  - formal semantics, 204–207
  - implicit validation, 75–77
  - importing from schemas, 62–67
  - instance of operator and, 72
  - nodes, 208
  - overview of, 54–56
  - schemas and, 56–60
  - sequence types, 60



- treat as expression and, 74
- typed variables, 71–72
- typeswitch expression, 72–74
- wide range of XML documents to process, 53–54

Typeswitch expression, 72–74, 131

Typing judgment, 254, 461

## U

Unicode

- defined, 461
- UTF-8/UTF-16, 365
- XML and, 354

Union operators, 46

Union types, 128, 461

Universal quantification, 36, 461

Universal Resource Identifier (URI), 93–94, 461

Universal Resource Locator (URL), 211

Unknown values, 112–117

- relational representation of, 112
- XML's representation of, 112–113
- XQuery comparison operators, 114

unordered(), 139

Untyped data

- defined, 462
- handling according to context, 109–112
- operators and, 41
- XQuery's accommodation of, 53, 56

Update interface, native XML database, 405–406

Updates

- defined, 462
- invoice example, 431
- partial, 406
- support for, 309
- user-defined types and, 362
- XML data from relational database, 313–315
- XML documents, 331–334, 347–350

URI (Universal Resource Identifier), 93–94, 462

URL (Universal Resource Locator), 211

Use cases, 82, 462. *See also* Auction use case

User-defined

- functions, 49–50, 217

- XML datatype, 381
- XML physical models, 361–362

UTF-8/UTF-16, 365

## V

Validate expressions, 76

Validation. *See also* Schema validation

- auction use case, 199–201
- debugging cycle and, 200–201
- defined, 462
- implicit, 75–77
- input and output data and, 199–200
- XML Schema, 87, 97, 303

Validation context

- defined, 462
- function calls and, 229–230
- static environment and, 125, 228
- validate expression and, 76

Validation modes, 200, 368

- defined, 462
- element constructors and, 124–125
- list of, 230
- skip validation example, 231–232

Value comparison operators

- compared with general comparison operators, 41
- defined, 462
- overview of, 41–42
- transitivity property and, 105
- unknown values and, 114

Value space, 396, 462

Values

- atomic values. *See* atomic values
- defined, 462
- dynamic types and, 212
- formal semantics, 267–269
- matching to types, 272–274
- node values, 268
- query phases and, 211–212
- type system and, 207–208
- unknown and inapplicable data and, 112–117

Variables

- binding multiple, 33–34
- binding with FLWOR expressions, 18
- declaring, 71–72

defining, 51, 159  
 external, 52  
 let clause and, 214  
 overview of, 214–215  
 Virtual XML view, 356, 463

## W

W3C (World Wide Web Consortium)

defined, 463  
 interoperability and, 400–401  
 query language workshop, 82  
 schemas, 4  
 specification consistency and, 156  
 SQL/XML proposal, 53  
 XML Schema language, 367

Wadler, Phil, 157

WebDAV

content management and, 433  
 defined, 463  
 updates and, 314

Well-formed documents, 396

where clauses

combining data sources, 33–34  
 FLWOR expressions, 225  
 FLWOR grammar, 279  
 function of, 22–23  
 iteration controls, 140–141  
 normalizing, 281  
 overview of, 19  
 quantifiers and, 36

Whitespace, 17, 463

Wildcard operators (\*), 14, 221

Working data, 399

World Wide Web Consortium. *See* W3C  
 (World Wide Web Consortium)

## X

xdt:dayTimeDuration, 97, 129, 205, 225, 463

xdt:untypedAtomic

defined, 463  
 rules for handling, 111  
 schema validation, 62

xdt:yearMonthDuration, 97, 129, 205, 463

XHTML, 29

XIndices, 418

XML data model, 396–399. *See also* Infoset  
 (Information Set)

levels of, 395  
 markup data and, 353  
 relational data model compared with,  
 84–86  
 textual representation, 395

XML datatypes

defined, 463  
 generating by extending SQL, 328–331  
 generating by hierarchical groups, 324–325  
 generating by hierarchical joins, 323–324  
 logical models, 359–360  
 mapping, 381  
 physical models, 360–365  
 queries and, 370  
 sources of, 315–316  
 SQL integration. *See* SQL query language,  
 integration with  
 storing, 357–358, 366  
 typing, 366–369  
 user-defined, 381

XML documents

collections, 413–414  
 as data source, 315–316  
 DTDs and, 128–129  
 emitting from relational database, 312–313,  
 339–347  
 intrinsic order of, 85  
 mapping to relational data model. *See*  
 Mapping XML to relational data  
 querying, 313, 347–350  
 range of, 53–54  
 representation by Query data model, 90–91  
 representation by relational data model, 3  
 storing, 413–414  
 transforming, 313  
 updating, 331–334, 347–350

XML (Extensible Markup Language)

comments, 8  
 data-centric vs. document-centric, 428–429  
 data interchange over Web, 81  
 defined, 448  
 element constructors, 122  
 text data, 168  
 transformations, 145, 146

- unknown values, representing, 112–113
- upgrade languages, 3
- versatility of, 3
- XQuery and, 92–94, 159–160
- XSLT and, 159–160
- XML (Extensible Markup Language),
  - relational storage
  - encoding and collations, 365–366
  - logical models, 359–360
  - overview of, 357–358
  - physical models, 360–365
  - storing and exposing XML data, 356
  - typing XML datatype, 366–369
- XML fragments
  - defined, 463
  - edge tables and, 338–339
  - emitting from relational database, 312–313
- XML Infoset. *See* Infoset (Information Set)
- XML Namespace, 93, 117
- XML-QL, 107
- XML Query Working Group (XQ-WG),
  - 82–83
  - design principles for XQuery, 86–88
- XML Schema
  - converting types to XQuery, 204–206
  - data definition interfaces, 401
  - defined, 464
  - duration type, 97
  - importing types, 66–67
  - mapping types to/from, 270, 377–378
  - primitive datatypes, 268
  - schema imports and, 210–211
  - simple types, 6
  - structural descriptions of types, 127
  - types, 4, 96
  - union types, 128
  - validation, 75–77, 200, 303
  - XQuery and, 4, 87, 95–97, 157
  - xsi:nil attribute, 117
- XML storage fidelity, 360, 464
- XMLAGG, SQL, 330–331
- xmldb program, 418–420
- xmlns, 94
- XPath, 97–106
  - axes, 166
  - backward compatibility of version 2.0, 158
  - defined, 464
  - expressions, defining in terms of other
    - expressions, 287
  - implicit operations, 104–105, 293–298
  - influence on design of XQuery, 97–98,
    - 156–157
  - normalizing, 288–292
  - operators and functions, 151
  - predicates, 102–103
  - Query data model and, 89–90
  - steps, 150–151
  - syntax and semantics, 99–102
  - transitivity, 104–105
  - types, 98–99
  - version 1.0, 149–151
  - version 2.0, 156–158
  - XML Schema and, 157
  - XQuery and, 10, 87, 105–106, 121,
    - 156–158
  - XSLT and, 148, 157
- XPointer, 97
- XQ-FS. *See* Formal semantics [XQ-FS]
- XQ-LANG, 237, 403
- XQ-REQ, 82
- XQ-UC, 82, 189
- XQ-WG (XML Query Working Group),
  - 82–83, 86–88
- XQuery
  - design principles, 86–88
  - development culture, 155–156
  - influences on, 83
  - integration with SQL. *See* SQL query
    - language, integration with
  - reserved words and, 99
  - structure of, 3–4
  - technical requirements, 152–155
  - top-level. *See* Top-level XQuery
  - XSLT and. *See* XSLT (eXtensible
    - Stylesheet Language), comparing with
      - XQuery
- XQuery 1.0 Language* (XQ-LANG), 237,
  - 402–403
- XQuery design process, 108–141
  - element constructors, 122–125
  - error handling, 136–138
  - function resolution, 132–135
  - operators, ordering, 138–141
  - overview of, 108–109

- static typing, 125–132
  - types and, 117–121
  - unknown and inapplicable data, 112–117
  - untyped data, 109–112
  - XQuery (XQ-DM) data model, 396–399. *See also* Query data model
    - compared with classical relational model, 4
    - defined, 456
    - illustration of, 397
    - native XML databases and, 398–399
    - overview of, 6–7
    - persistent document storage, 398
    - value space of, 396–398
    - XML data model and, 396
  - xs:anyType, 62, 91
  - XSD language, 331–334, 340
  - xs:decimal, 69
  - xs:double type, 43
  - xsi:nil, 117, 464
  - xsi:type attribute, 77
  - XSLT (eXtensible Stylesheet Language),
    - 146–149
    - defined, 464
    - development culture, 155–156
    - integration with XML Schema and XPath, 157
    - key characteristics of, 146–148
    - processors, 171–174, 181–182
    - strongly typed data and, 182
    - technical requirements, 152–155
    - transforming XML to HTML, 146
    - XPath and, 97, 105
  - XSLT (eXtensible Stylesheet Language),
    - comparing with XQuery
    - axes, 166–168
    - development culture, 155–156
    - element constructors, 160–163
    - FLWOR expressions, 164–165
    - functions, 163–164
    - similarities, 159
    - technical requirements, 152–155
    - templates rules, 165–166
    - type strictness, 168–170
    - XML-based syntax, 160
  - xslt:apply-templates, 165
  - xslt:for-each, 159
  - xs:string type, 43
  - XStreamDB, 416–418, 423
- Y**
- yields, (matching judgments), 274–275