

Index

- 4.2BSD filesystem, 174
- 6bone, 384, 390, 392
- A**
- A records, 227, 237
- .a suffix, 273
- ACID, 422
- ACL, running on /dev and /etc/passwd, 54
- Actions, 55, 281
- activadm command, 345
- ActivCard authentication, 345
- add privilege, 333
- Add-on programs, 61
- Address spoofing protection, 67
- AddType variable, 244
- adduser command, 95–96, 98
- Administrative server, controlling access to, 333–334
- Administrators' files, 46
- advocacy mailing list, 483
- AES (Advanced Encryption Standard)
 - algorithms, 11
- afs, starting, 54
- AFS mirrors, 481
- afterboot(8) manual page, 76
- Agents, 258–259
- AH (Authentication Header), 347, 349
- Alias addresses (Sendmail), 119–120
- Aliases and /etc/sudoers file, 105–106
- aliases file (Sendmail), 219–220
- all privilege, 333
- allow, 310
- Alpha platform, 19
- Alternate authentication methods, 71
- Alternate root device, 20
- ALTQ traffic-shaping framework, 285
- Amanda (Advanced Maryland Automatic Network Disk Archiver), 201–203
 - amanda.conf file, 202–203, 203
- amd, starting, 53
- an driver, 117
- analog tool, 251
- analyze.logfiles command, 255
- Anchors, 297–298, 310
- ancontrol command, 116–117
- Andrew filesystem (AFS), 54
- announce mailing list, 483
- antispoof action, 292
- a.out executables, 432–433
- Apache
 - 2.0.x, 250
 - analyzing logs, 251
 - chroot mode, 245
 - configuration, 244
 - default configuration file, 244
 - default document root, 244
 - documentation, 244
 - enhancing security, 243
 - file icons, 244
 - insecure mode, 247
 - IPv6, 400
 - logging IP addresses of clients, 244
 - modules, 244, 249–250
 - overview, 243–244
 - remote client variables, 243
 - resolving and saving host names, 244
 - servers, 56, 243–250
 - server administrator's address, 244
 - site summaries, 251
 - SSL, 245–247
 - storing files, 243
 - user directories, 244
 - variables, 243
 - /var/www hierarchy, 243–244
- APM (Automatic Power Management), 62–63
- apm tool, 62–63

494 Index

- apmd daemon, 57, 62
 - APOP, 224
 - Applications
 - installing, 13
 - libpcap-based, 306
 - OpenBSD-specific patches needed, 161
 - parameters passed to, 66
 - process IDs as security markers, 10
 - secure and insecure, 12
 - stand-alone environment, 48
 - support applications, 159
 - type of socket, 66
 - arc4random() function, 283
 - Archives, 195–197, 201
 - ARP (Address Resolution Protocol), 120–122, 142
 - ARP addresses, 120
 - arp command, 120
 - ARP tables, 120, 122, 127–128
 - arpwatch tool, 423
 - ASCII sequence of characters, 139
 - at command, 212–214
 - atq command, 214
 - atrm command, 214
 - Auditing actions taken on system, 107
 - auth 4/6 service, 65
 - auth key word, 343
 - Authenticated firewall rules, 309–311
 - Authentication
 - ActivCard, 345
 - additional login classes, 343–346
 - agent, 258
 - backups, 191–195
 - changing passwords, 344
 - CRYPTOCARD, 345
 - Kerberos, 338, 345
 - keychain management, 258–259
 - OpenSSH, 262
 - overview, 339
 - passwd method, 339
 - public key pairs, 257–258
 - radiusd server, 345
 - rejecting login attempts, 346
 - remote systems, 256
 - SecureID login, 345
 - SecureNet, 345
 - sendmail, 220–221
 - S/Key, 339–343
 - token-based methods, 344–345
 - authpf shell, 297, 309–311
 - authpriv events, logging, 69
 - autoconf tool, 282
 - automake, 282
 - Automated backups, 201–203
 - Automatic power daemon, 57
 - Automount daemon, 53
 - awk, 270
- ## B
- Backtrace capture, 476–477
 - Backtrace command, 276
 - Backup media, 187
 - Backups, 187
 - Amanda, 201–203
 - authentication, 191–195
 - automated, 201–203
 - central backup server, 191–195
 - configuration files, 190
 - cpio command, 195
 - within cron job, 191
 - data-specific options, 190–191
 - describing methods, 203
 - differential, 188–189
 - Father-Son strategy, 189
 - files, 197–200
 - full, 188–189
 - GNU tar, 203
 - Grandfather-Father-Son strategy, 189
 - incremental, 188–189
 - labeling, 188
 - listing, 208
 - modified Towers of Hanoi strategy, 190
 - non-full dump levels, 198
 - partitions, 197–200
 - pax command, 195–197
 - planning, 188
 - restoring files from, 198–200
 - root filesystem, 208
 - rsync utility, 204–206
 - strategies, 188–195
 - system software, 190
 - tar command, 200–201
 - testing and retesting, 188
 - tools, 195–206
 - Towers of Hanoi strategy, 189–190
 - verifying, 188
 - volatile data, 190
 - Banner message before login, 71
 - Base language support, 270–273
 - Base software set installation, 35–39
 - Base system source code, 46

- base*.tgz installation set, 36
 - Basic X applications, 90–91
 - batch facility, 214
 - Battery, current state, 63
 - Berkeley Copyright, 12
 - bge Ethernet device, 43
 - bge1 networking device, 111
 - Bidirectional mappings, 293
 - biff, enabling, 137
 - /bin directory, 13, 45–46
 - Binary, full path to, 66
 - Binary boot system, unpacking, 433
 - Binary format changes, 432–434
 - Binary sets, upgrading from, 427
 - binat rule, 293
 - BIND package, 227–228, 396, 399–400
 - BIND8, 233
 - BIND9, 228, 233
 - BIND9 Administrator's Reference Manual Web site, 239
 - bin_ls policy, 408
 - /bin/sh shell, 211, 407
 - /bin/sync command, 62
 - Blackhole router, 291
 - Block action for packets, 291
 - Blowfish algorithms, 11–12, 96
 - boot command, 432
 - Boot configuration, 20
 - Boot files, cleaning up, 51
 - Boot floppies, customized, 42–43
 - boot keyword, 20
 - Boot media selection, 19–20
 - Boot process, 48–58
 - Boot sectors, installing, 180
 - Booting, 20–25
 - bootp protocol, 149
 - bootp servers, 141
 - bootparamd daemon, 56, 141–142
 - bootp(8) manual page, 149
 - Boot-time networking configuration, 115
 - Bottlenecks and disk access, 178
 - BPF device, 146
 - brconfig command, 125, 128
 - Breakpoints, setting, 477–478
 - Bridge virtual device, 114
 - Bridges, 125–128
 - Broadcast address, 147, 383
 - BSD Apps Web site, 482
 - BSD Central Web site, 482
 - bsd file, 23
 - bsd installation set, 36
 - bsd kernel, 20, 35–36, 437
 - bsd.port.mk(5) manual page, 166
 - bsd.prog.mk template, 282
 - bsd.rd kernel, 434
 - BSD-specific software, 481–482
 - Bug fixes, 11
 - Bug reports, 443
 - Bugs, 444–449. *See also* Debugging
 - bugs mailing list, 483
 - bugs@openbsd.org mailing list, 445
 - build target, 165
- ## C
- C directives, 280
 - C libraries, 283
 - C program verifier, 280
 - C programming language, 270, 280–281
 - C++ programming language, 270, 280–281
 - calendar facility, 208
 - cbq (class-based queue), 300
 - cc command, 272–273, 282, 475
 - CCD (Concatenated Disk Driver), 48–49, 170–171, 173
 - CDR, 187
 - Central mail servers, 215
 - .cf files, 217, 219, 221
 - CGI files, 243
 - cgi-bin folder, 243
 - ChallengeResponseAuthentication parameter, 71–72
 - change command, 440
 - change-password privilege, 333
 - chargen service, 139
 - chat(8) manual page, 130
 - CHECKFILESYSTEMS environment variable, 208
 - chpass, 344
 - chroot, 12, 243–249
 - chsh utility, 100, 407
 - clean target, 165–166
 - Clients mounting NFS filesystem, 313–314
 - CNAME records, 227, 237
 - COM1, 130
 - Commercial applications, 15
 - common.m4 file, 360–365, 368–369
 - Communication protocol, 66
 - comp set, 428
 - Compiler package, 35
 - Compilers, 36, 270–273
 - Complex projects, managing, 281–282

496 Index

- comp.protocols.kerberos newsgroup, 338
 - Compressing archives, 195–197
 - comp.security.ssh newsgroup, 484
 - comp*.tgz installation set, 36
 - comp.unix.bsd.openbsd.announce newsgroup, 484
 - comp.unix.bsd.openbsd.misc newsgroup, 445, 484
 - Computers and clear text logins, 69
 - comsat, 137
 - Conditionals, 282
 - conf folder, 244
 - config tool, 439–440
 - Configuration files
 - backups, 190
 - loading by default, 286
 - specifying, 68
 - upgrading, 429–432
 - configure script, 162, 165, 282
 - Connections, 66–67
 - Console mode, 144
 - Consoles, 57, 59, 137
 - Copying files, 70–71
 - Core dump, 274–276, 476
 - courtesan.mc file, 219
 - cpio command, 195
 - CPU, information about, 471
 - Crash dump analysis, 478–480
 - Crashed applications, 475–478
 - CRIMELABS.NET realm, 329–330, 333
 - cron job, 191, 296–297
 - cron service, 60, 65, 210–212
 - crontab command, 211
 - crontab file, 211–212
 - cryptoadm command, 345
 - CRYPTOCARD authentication, 345
 - Cryptography, 11–12
 - CS Scripts Web site, 79
 - Cscope tool, 278
 - csd backup set, 202
 - .cshrc file, 96, 455
 - cu command, 22
 - cua00 device, 22
 - CUPS printing interface, 146
 - current branch, 425
 - Current routing table, 62
 - curses interface, 278
 - Customized installation floppies, 42–43
 - CVS (Concurrent Versions System), 262
 - CVSROOT environment variable, 249, 437, 454
 - CVS.RSH environment variable, 263, 454
 - CVSweb, 247–249
 - choosing mirror, 458
 - command, 454, 458
 - compression, 458
 - .cvsignore files, 459
 - environment variables, 454
 - files in repository, 458
 - ignoring parts of tree, 458–459
 - Info page, 78
 - module check out, 456
 - OpenBSD tags, 457–458
 - operations, 453–454
 - ports tree, 160
 - pserver, 436–437, 455
 - servers, 425–426, 454
 - source tree check out, 456
 - speeding up, 458–459
 - ssh rather than rsh, 263
 - updating src/sys module, 436
 - usage, 455–457
 - CWD environment variable, 409
- D**
- Daemons, 56, 59
 - DAV (distributed authoring and versioning)
 - standard, 249–250
 - daytime service, 66, 139–140
 - .db file, 219
 - db.cache file, 232
 - dd command, 42, 182
 - ddb kernel debugger, 20, 478–479
 - ddb.console variable, 479
 - ddb.panic variable, 479
 - de Raadt, Theo, 1, 9
 - Deadly Web site, 345
 - Debuggers, 274–280
 - Debugging
 - crashed applications, 475–478
 - DDD interface, 278
 - NFS, 317
 - tools from ports, 278
 - tracing system calls, 278–280
 - Default hosts settings, 72
 - Default mail server, 60
 - Default printers, 145
 - Default processes, 60
 - Default services, 68–72
 - DefaultDepth directive, 87–88
 - delete privilege, 333

- Denial-of-service attack, 232
- Dependencies, 167, 281
- /dev databases, 54
- /dev folder, 47–48
- /dev/ccd1 CCD filesystem, 170–171
- Development environment
 - additional languages from ports, 274
 - automake, 282
 - compilers and languages, 270–274
 - debuggers, 274–280
 - documentation, 284
 - editors, 269–270
 - Imakefile facility, 282–283
 - libraries, 283
 - make system, 281–282
 - shared library and object tools, 283–284
 - source code development tools, 280–281
 - xmkmf command, 282
- Device tree, 185–186
- Devices
 - drivers, 18
 - GENERIC kernel, 436
 - handling full, 196–197
 - listing open, 185–186
 - naming, 47–48
 - number available, 438
 - status of, 185
 - used by process number, 186
 - viewing which process or user is using, 185–186
 - where mouse connects, 63–64
- /dev/log socket, 52
- /dev/null device, 263
- /dev/sd*, 169
- /dev/wd*, 169
- /dev/zero device, 182
- df command, 181–182
- dgram socket, 66
- dhclient program, 119, 146
- DHCP, 119, 148–149, 382
 - DHCP clients, 56
 - DHCP daemons, 56, 146–149, 400
 - DHCP servers, 119, 146–150
- dhcrelay program, 150
- Diagnosing problem, 444
- diff command, 432, 461
- Differential backups, 188–189
- dig command, 234–236, 240
- Digital Alpha platform, 18
- discard service, 140
- Disk access, 177–178
- Disk controllers, 18
- Disk devices, 18, 169
- Disk quotas, 175–177
- Disk space usage, 101
- disklabel command, 25, 41, 174, 178–180, 182–183
- Disklabels, 178–180
- Diskless clients
 - boot parameters, 56–57
 - configuring, 149
 - sending kernel information to, 142
- Diskless systems and tftpd servers, 141
- disklist file, 202–203
- DISPLAY variable, 91–92
- distclean target, 165
- distfiles directory, 161, 165–166
- distinfo file, 161
- DISTNAME.suffix file, 161
- DJBDNS system, 233–234
- dmesg command, 52, 114, 169, 445, 449, 466, 469–470
- DNS
 - BIND8, 233
 - BIND9, 233
 - caching-only nameserver, 231–232
 - CNAME records, 227, 237
 - client configuration, 119
 - configuration file, 229–231
 - configuring resolver, 227–228
 - dig command, 234–236
 - DJBDNS system, 233–234
 - firewall rules, 232–233
 - host command, 236–237
 - IPv6, 399–400
 - MX records, 227
 - NS records, 227
 - names, resolving, 260
 - nslint tool, 239
 - nslookup command, 237–239
 - operations for electronic mail, 215
 - PTR records, 227
 - queries, 227
 - reaching hosts with IP addresses, 240
 - A records, 227, 237
 - reverse zones, 231
 - secondary zones, 231
 - security, 232–233
 - servers, 15, 119, 228–236, 239–240
 - service debugging status, 235–236

498 Index

- DNS (*cont.*)
 - tools, 234–239
 - troubleshooting, 240–241
 - upgrading from named server, 233–234
 - zones, 228
- DNSSEC, 233
- Documentation, 81–82, 284
- Documents, 262–263
- domain keyword, 228
- domainname command, 319
- dproffpp utility, 270
- Drivers, 18, 470
- DSA host key, 56
- Dual booting, 18
- dump command, 188–190, 192–195, 197–200, 479
- dup-to action, 291
- Dynamic content, 247–249
- Dynamic memory allocation analysis, 278
- Dynamic multicast routing protocols, 56
- Dynamic routing protocols, 56
- E**
- echo service, 139
- ecn (Explicit Congestion Notification), 300
- Edge servers, 15
- EDITOR environment setting, 99, 179, 211
- Editors, 269–270
- Electric Fence debugging library, 278
- Electronic mail, 69, 215–225
 - delivery, 56
 - maildirs format, 190
 - mbox format, 190
 - popping to remote system, 138
- ELF kernel boot program, 432
- emacs editor, 269–270
- E-mail servers, 15
- enc driver, 114
- Encrypting passwords, 99
- Encryption
 - electronic mail, 225
 - FTP, 133
 - Kerberos, 336–337
 - sendmail, 220–221
 - sshd, 339
- Enlightenment windows manager, 89
- ENV variable, 108
- Environment variables
 - controlling options for package system, 153
 - CVS (Concurrent Versions System), 454
 - systrace, 409
- err-level events, logging, 69
- ESP (Encapsulating Security Payload), 347, 349
- /etc directory, 40, 46, 62, 172, 427, 429–432
- /etc inittab file, 58
- /etc/active.db file, 345
- /etc/adduser.conf file, 96, 99
- /etc/amp/ directory, 62
- /etc/authpf/ directory, 310
- /etc/boot.conf file, 20–21
- /etc/bridgename.bridge0 file, 128, 301
- /etc/ccd.conf file, 171
- /etc/daily script, 207–208
- /etc/daily.local script, 207
- /etc/dhclient.conf file, 119, 413
- /etc/dhcpd.conf file, 147–148
- /etc/disklabel file, 41
- /etc/disktabs file, 179
- /etc/Distfile file, 208
- /etc/domainname file, 50, 320
- /etc/dot.profile, 42
- /etc/dumpdates file, 198
- /etc/ethers file, 142
- /etc/exports file, 314–315
- /etc/fstab file, 49, 54, 175, 181
- /etc/ftpchroot file, 134
- /etc/ftpusers file, 134, 208
- /etc/group file, 208
- /etc/hostname.* files, 51, 115, 119–120, 301, 385
- /etc/hosts file, 142, 228
- /etc/hosts.allow file, 67–68
- /etc/hosts.deny file, 67–68
- /etc/hosts.equiv file, 143
- /etc/inetd.conf file, 66–67, 133, 204, 222, 397–398
- /etc/init.d, 59
- /etc/inittab file, 48
- /etc/isakmpd/isakmpd.conf file, 355
- /etc/kerberosV directory, 328–329, 331
- /etc/localtime file, 39
- /etc/login.conf file, 99, 101–102, 343–346
- /etc/mail directory, 208, 217–218, 219–221, 398–399
- /etc/mailler.conf file, 216
- /etc/man.conf file, 76
- /etc/master.passwd file, 95, 98–100, 208, 320, 322, 339, 343, 431
- /etc/monthly script, 209
- /etc/monthly.local script, 209
- /etc/motd file, 55
- /etc/mygate file, 51, 116, 119, 386
- /etc/mygate6 file, 385–386

- /etc/myname file, 50
- /etc/named.conf file, 229–231
- /etc/netstart script, 50, 61, 114–115, 432
- /etc/news.expire script, 207
- /etc/newsyslog.conf file, 209
- /etc/ntp.conf file, 144
- /etc/passwd file, 40, 47, 54, 95, 99–100, 431
- /etc/passwd.conf file, 97
- /etc/pf.conf file, 51, 286, 298–299, 304
- /etc/pf.os file, 304
- /etc/ppp/ppp.conf file, 129–130
- /etc/printcap file, 145
- /etc/rc script, 47–48, 57, 59, 61, 284, 314, 334
- /etc/rc.conf file, 50, 51, 57, 63, 144, 217, 247, 286, 314, 334, 386–387, 389, 432
- /etc/rc.local file, 57–59, 116, 122, 385–386, 421
- /etc/rc.local.conf file, 58, 88
- /etc/rc.securelevel script, 55
- /etc/resolv.conf file, 119, 227, 238, 240, 410
- /etc/rpc file, 315
- /etc/rsyncd.conf file, 204
- /etc/security script, 208
- /etc/services file, 66–67, 289
- /etc/shells file, 96
- /etc/skel directory, 96
- /etc/snort/rules directory, 420–421
- /etc/snort/snort.conf file, 420
- /etc/ssh directory, 261
- /etc/ssh_config file, 71–72, 335
- /etc/sshd_config file, 71, 343, 399
- /etc/sudoers file, 105–107, 431
- /etc/sysctl.conf file, 50, 55, 84, 123, 286, 349–350, 387–388, 431, 467
- /etc/syslog.conf file, 60, 68–69
- /etc/systrace directory, 407
- etc*.tgz installation set, 36
- /etc/tyms file, 21–22, 58–60, 479
- /etc/weekly script, 209
- /etc/weekly.local script, 209
- /etc/X11 hierarchy, 84, 87–88, 90
- Ethernet address, 147
- Ethernet interfaces, 120–122
- Executable
 - changing name of, 271–272
 - name of, 66
 - symbol name list, 284
 - systrace facility, 406
 - tracing performance, 270
- Exim mail server, 222
- exports file, 317
- ext2 filesystem, 174–175
- extract command, 199
- extract target, 165
- F**
- fastroute action, 291
- Father-Son backup strategy, 189
- fetch target, 165
- FFS (fast filesystem), 174–175
- Fiedl, Markus, 354
- file command, 476
- File creation redirection, 108
- File descriptors, 185
- Files
 - backups, 197–200
 - copying, 70–71
 - listing open, 185–186
 - moving between hosts, 253
 - not part of base installation, 47
 - with predictable filenames, 47
 - preserving modification times, access times, and mode attributes, 256
 - remote synchronization, 204–206
 - remotely copying between computers, 255–257
 - restoring from backup media, 198–200
 - rolling multiple into archive, 195–197
 - status of, 185
 - temporary, 47
 - used by process number, 186
- files directory, 161
- Filesets, deleting, 35–36
- /filesystem, 27
- Filesystem image, 182–184
- Filesystem layout, 13, 45–48
- Filesystems, 169, 173
 - 4.2BSD filesystem, 174
 - asynchronously mounting, 178
 - availability, 181–182
 - backup superblocks, 174
 - creation of, 174
 - disk quotas, 175–177
 - ext2 filesystem, 174–175
 - FFS (fast filesystem), 174
 - fsck process, 177
 - improvements, 468
 - improving disk access performance, 177, 178
 - iso9660 filesystem, 174–175
 - listing open files and devices, 185–186
 - manual recovery, 184
 - memory, 181

500 Index

- Filesystems, (*cont.*)
 - mounting, 174, 177, 180–182
 - msdos filesystem, 174–175
 - from multiple disks, 170–171
 - options, 438
 - partition creation of, 170–171
 - partitioning, 25–33
 - pseudo-disks, 182–184
 - read-only, 27, 181, 315
 - read-write mode, 181
 - recovering deleted partition table, 184–185
 - running quotacheck on, 54
 - sharing, 313, 315
 - showing usage, 176–177
 - sizes, 25
 - soft updates, 177–178
 - space remaining, 181–182
 - status of, 185
 - synchronously mounting, 178
 - union, 181
 - unmounting, 180–181
 - virtual disks, 182–184
 - Filtering routers, 285
 - Filters
 - bridges, 126
 - printers, 146
 - tcpdump, 305
 - finger tool, 136
 - fingerd daemon, 136–137
 - Fingerprints, 303–304
 - firewalld variable, 58
 - Firewalls, 15
 - application-layer devices, 285
 - authenticated rules, 309–311
 - default accept, 308
 - default deny, 308–309
 - determining rules, 308–309
 - DNS rules, 232–233
 - enabling and disabling, 286
 - flushing rules, 287
 - information about, 287
 - killing state entries for host, 287
 - opening ports, 308–309
 - packet filters, 285
 - parsing rules, 287
 - partitioning example, 28–33
 - performance tuning, 311
 - PF, 288–292
 - properly seeing and recording connections, 306
 - rules for, 286
 - ruleset, 311
 - speed of connections passing through, 300–301
 - verbose information, 287
 - fixed-address directive, 149
 - Fixes, 425–426
 - Flavors, 164–166
 - Floppy34.fs installation image, 19
 - FloppyB34.fs installation image, 19
 - FloppyC34.fs installation image, 19
 - Fonts, 36, 84, 90
 - Fortran 77, 270
 - Forwarding servers, 228
 - Frantzen, Mike, 6
 - FreeBSD, 9, 17
 - Freenet6 Web site, 390
 - Freshmeat Web site, 482
 - Friedl, Markus, 350, 351
 - Fries, Todd, 5, 192, 487
 - FSCK (Filesystem Consistency ChecK), 49
 - fsck command, 174–175, 177, 184, 444
 - FSF (Free Software Foundation), 78
 - fstat command, 131, 185–186
 - FTP, 60, 133, 396–397
 - daemon, 208
 - installation, 19
 - installing packages, 153
 - mirrors, 481
 - obtaining passphrase, 342
 - plaintext logins, 339
 - FTP servers, 14, 27, 61, 133
 - ftpd daemon, 56, 67, 133–134
 - FTP-like channel over SSH-2 channel, 264–265
 - Full backups, 188–189
 - fvwm window manager, 87, 89
 - fxp0 interface, 111, 119–120
- G**
- gaim program under systrace, 410–411
 - games*.tgz installation set, 36, 76, 427
 - gated daemon, 56
 - Gateways, 51
 - gcc compiler, 270–274
 - gdb program
 - backtrace capture, 476–477
 - core dump files, 274–276
 - DDD interface, 278
 - disassembly of executable, examination of
 - registers on stack, 276
 - loading debugging symbols, 276
 - loading symbols, 476

- monitoring, 276
 - Motif-based graphical interface, 278
 - output, 277
 - setting breakpoints, 276, 477–478
 - steps preceding crash, 476–477
 - stepwise tracing through executable, 276
 - targeting core dump, 476, 479–480
 - GECOS information, editing, 100
 - GENERIC kernel, 385
 - bridging devices, 125–126
 - CCD support, 170
 - compiling, 437
 - configuration file, 146
 - configuration setup, 169
 - cryptographic and IPsec frameworks, 349
 - devices, 436
 - disk quotas, 175
 - functionality, 435
 - GRE device, 113
 - INET6 option, 385
 - IPv6 support, 382
 - kernel option, 478–479
 - networking device drivers, 111
 - NFS servers, 314
 - options, 438
 - performance, 435
 - pfsync0 device, 306
 - recompiling, 435–437
 - setting configuration files information, 437–439
 - size of, 435
 - USERLDT option, 435
 - variable settings for options, 436
 - VLAN devices support, 112
 - get privilege, 333
 - getty program, 59
 - gif devices, 112–113, 126, 385, 390–391, 402
 - GIF/GRE/bridge interfaces, 51
 - Global system policies, 407
 - GNATS bug tracking system, 446–449
 - Gnome windows manager, 89
 - GNU
 - autoconf tool, 282
 - Info document markup language, 78
 - Makefiles from templates, 282
 - tar, 203
 - Toolchain, 270
 - GNU Info pages, 78–79
 - GnuPG, 225
 - gprof tool, 270
 - Grandfather-Father-Son backup strategy, 189
 - Graphical installation process, 17
 - Graphical login manager, 58
 - Graveland, Brent, 433
 - gre virtual device, 113–114
 - groff macros, 81
 - Groups
 - adding before updates, 426
 - disk quotas, 175–177
 - managing, 99–100
 - gtar command, 203
 - GUI (graphical user interface), 83
 - gunzip, 35
 - gzip program, 40, 458
- ## H
- Hard disks, 169
 - automating partitioning, 41
 - disklabels, 178–180
 - geometry, 179
 - identifying by type, 169
 - location of, 169
 - main drive and PCI IDE chain identification, 472
 - numbering, 169
 - partitions, 173, 179
 - preparations for holding filesystem, 173
 - reporting on space usage, 208
 - Hardware, 17–18
 - i386, 22
 - support for, 14
 - Heimdal Kerberos V implementation, 336–337
 - he.net, 384
 - hier(7) manual page, 159
 - Home directories, 25–26, 47, 96–98, 97, 175, 208
 - \$HOME environment variable, 409
 - HOME_NET variable (Snort), 420
 - \$HOME/.ssh, 261
 - \$HOME/.ssh/config file, 335
 - /home/username/.systrace directory, 407–408, 410
 - Host * file, 72
 - host command, 236–237
 - Host server, 70
 - hostname.if file, 387
 - Hostnames
 - converting to IP addresses, 227
 - host authentication, 135
 - mapping IP address to, 236–237
 - verification, 67
 - Hosts
 - automatic configuration, 146
 - automatic IPv6 configuration, 387–389

502 Index

- Hosts (*cont.*)
 - broadcast address, 147
 - grouping in sudoers file, 106
 - IPv6, 382, 403
 - moving files between, 253
 - naming with static configurations, 147
 - providing address or host name to, 147
 - requesting mapping for, 120–121
 - restriction based on location, 67
 - settings, 72
 - tying configuration to MAC address, 147
 - zone transfer, 233
 - hosts.access manual pages, 68
 - hosts.equiv file, 135
 - Housekeeping
 - logfile rotation, 209–210
 - regular system scripts, 207–209
 - scheduling facilities, 210–214
 - HP300 platform, 20, 84
 - hs247.com Web site, 402
 - htdocs folder, 244
 - HTML, 251
 - HTTP, 153
 - HTTP mirrors, 481
 - httpd daemon, 56, 244
 - httpd.conf file, 244
- I**
- i386 platform
 - architecture, 1
 - booting, 22
 - configuration setup in GENERIC kernel, 169
 - floppy disk choices, 19
 - hardware, 22
 - ICMP rules, 289
 - icons folder, 244
 - IDE devices, 20, 169
 - ident restrictions, 67
 - identd daemon, 56, 65–66, 137
 - Identity file, 254–255, 263
 - ifconfig command, 51–52, 112–114, 117, 306, 385, 394, 420
 - ifmcstat, 385
 - IKE (Internet Key Exchange), 348, 353, 355
 - Imakefile facility, 282–283
 - IMAP server administration, 223
 - include directives, 161, 282
 - Incremental backups, 188–189
 - inetd daemon, 56, 60, 65–66, 68–69, 133
 - /etc/inetd.conf configuration file, 66, 138–139, 140
 - running popa3d daemon, 222–223
 - running sshd process from, 260
 - servers part of, 138
 - TCP socket listening, 205
 - tcp6 keyword, 397
- Info pages, 78–79
 - info2man script, 79
 - info2pod script, 79
 - init process, 48, 60–61
 - In-line bridge with packet filtering, 301–302
 - Insecure (“Unsecure”) mode (for httpd), 68
 - install target, 165
 - Installation
 - backing up OS (operating system) before, 18
 - base software set, 35–39
 - booting, 20–25
 - customizing, 40–43
 - disk layout, 19
 - example, 37–39
 - filesystem partitioning, 25–33
 - forcing, 41
 - FTP installation, 19
 - graphical installation process, 17
 - HP300, 20
 - i386 platform, 18
 - installation CD, 19–20
 - jumpstarting, 41–42
 - Mac68K, 20
 - network configuration, 33–34
 - obtaining files for, 19
 - script, 42
 - selecting boot media, 19–20
 - Sparc, 23
 - supported hardware, 17
 - system preparation, 18–19
 - types of, 35–36
 - upgrading, 43
 - use of computer, 18
 - Installation CD, 19–20
 - Installation sets, 35–36, 40
 - installboot program, 433–434
 - Installed binaries, 46
 - install.sh installation script, 42
 - install.sub installation script, 42
 - Interface address, 289
 - Interfaces
 - assigning IP addresses to, 115

- bridges, 126
- configuration, 62
- current settings, 117–118
- inet address family, 115
- inet6 address family, 115
- IPv6 addresses support, 385–386
- listing supported options, 116–117
- mapping link-layer addresses to, 127–128
- media options, 116–118
- multiple IP addresses for, 119–120
- parsing and configuring, 51
- passing packets between, 286–288
- removing from bridge configuration, 126
- reporting on settings, 208
- Internal services, 138–140
- Internet services, 60
- intro manual page, 76
- Intrusion detection servers, 15
- IP (Internet Protocol), 381
- IP addresses, 115
 - converting hostnames to, 227
 - IPv6, 383
 - mapping MAC addresses to, 120–122
 - mapping to hostname, 236–237
 - redirecting, 293
 - returning to host, 142
- IP forwarding, 438
- ipconfig tool, 61, 385
- IPng (IP Next Generation), 381
- IPsec, 76, 118
 - AH (Authentication Header), 347
 - allow-all policy file, 351
 - automatic configuration, 351–352
 - basics, 347–349
 - endpoint setup, 350
 - ESP (Encapsulating Security Payload), 347
 - example VPN configurations, 354–380
 - IKE (Internet Key Exchange), 348
 - IPv4 addresses, 381
 - IPv6, 400
 - ISAKMP (Internet Security Architecture Key Management Protocol), 348
 - kernel requirements, 349–350
 - kernel routing tables, 354
 - m4 script, 487–491
 - manual configuration, 350–351
 - Oakley, 348
 - observing activity of kernel code, 353
 - setting up, 349–350
 - setting up IP address and policy, 351
 - starting isakmpd, 52
 - testing and debugging configuration, 352–354
 - transport mode, 348
 - tunnel mode, 348
 - x509 keys creation, 348–349
- IPsec gateway and IP forwarding, 350
- ipsecadm command, 350, 353
- IPsec-related variables, 350
- IPv4, 65–67
 - autoconfiguration, 119
 - DHCP, 382
 - /etc/mygate file, 386
 - netmask, 384
 - PF, 289
 - proxies, 394–396
 - security, 347
 - sizes, 381
 - tunnelling, 384–385
- IPv4 addresses, 381
- IPv5, 394
- IPv6
 - “/64” prefixlen, 384
 - A6 format, 399
 - AAAA record, 399–400
 - addressing, 381–382, 385–386, 403
 - all address, 384
 - all nodes addresses, 384
 - all routers addresses, 384
 - anycast addresses, 383h–384
 - Apache, 400
 - autoconfiguration, 119, 387–389
 - backbone network, 384
 - bandwidth usage, 382
 - broadcast address, 383
 - clients, 390–391
 - DHCP daemons, 400
 - DNS, 399–400
 - forwarding, 387
 - gif tunnel, 391
 - header size, 383
 - host configurations, 382, 397, 403
 - ICMP router solicitation messages, 387
 - identity server for, 65
 - internal time servers, 66
 - IP addresses, 383
 - IPsec, 400
 - IPv6-ready applications, 396
 - ISADMP, 400

504 Index

IPv6 (*cont.*)

- Kerberos, 400
- kernel setup, 385
- link local address, 383
- local networks, 403–404
- localhost address, 384
- mailing list, 401
- manual configuration, 385–386
- multicast addresses, 383–384
- neighbors table, 389
- networks, 389–396, 401–402
- operation of, 383–385
- packet types, 383
- PF, 289, 401
- ports, 382
- prefixlen (prefix length), 384
- programming, 401
- proxies, 394–396
- resources, 401–402
- routers, 386–388, 402
- routing daemons, 400
- routing services, 56
- security, 347, 382, 401–402
- sendmail, 398–399
- service support, 396–400
- special addresses, 383–384
- sshd, 399
- subnet identifier, 384
- TCP6 protocol, 67
- topology, 382
- troubleshooting, 402–404
- tunnelling, 384–385
- usage, 385–389

IPv6 *Essentials* (Hagen), 401

ISA bus identification, 473

ISAKMP (Internet Security Architecture Key Management Protocol), 348, 400

isakmpd daemon, 52, 348–349, 351–359, 365–367, 369–373

isakmpd.m4 file, 359–361, 364, 368

iso9660 filesystem, 174–175

issetgid() function, 283

its4, 280

J

- Java, 15, 274
- Jobs, scheduling, 210–214
- Jumpstarting installations, 41–42

K

- kadmin command, 331–332
- kadmind daemon, 334
- KAME project Web site, 382
- kauth command, 329
- kbd daemon, 57
- KDC (Kerberos Key Distribution Center), 325–326, 331
- kdc daemon, 334
- KDE windows manager, 89
- kdestroy command, 330
- kdump utility, 278–280
- keep state modifiers, 307
- Kerberos, 323, 325
 - authentication, 338, 345
 - build support for, 328
 - clock synchronization, 327–328
 - encryption, 336–337
 - expired tickets, 338
 - forgery attacks, 327
 - instances, 326–327
 - passwords, 327
 - principal, 326–327
 - realms, 326–327
 - reasons for using, 325–326
 - resources, 337–338
 - security, 336–337
 - services, 140, 334–336
 - spoofing, 327
 - ssh secure shell, 335
 - sshd daemon, 335
 - terminology, 326
 - ticket theft, 337
 - tickets, 326
 - troubleshooting, 338
 - valid tickets, 338
- Kerberos clients, 328–331
- Kerberos Domain Controller service, 57
- Kerberos IV, 325, 337, 400
- kerberos KDC server daemon, 57
- Kerberos servers, 331–334
- kerberos slave server daemon, 57
- Kerberos V, 325
 - activating services at start-up, 334
 - as authentication mechanism, 334–336
 - cryptographically strong MAC algorithms, 337
 - databases, 331
 - implementations, 326
 - IPv6, 400

- master KDC, 334
 - slave KDC, 334
 - stronger ciphers, 337
 - telnet, 335–336
 - Windows 2000, 336
 - /kern mount point, 353
 - Kernel
 - building, 428
 - compatibility with older versions, 438
 - configuration files, 111, 437–439
 - configuring, 20
 - crash dump analysis, 478–480
 - driver identification, 472
 - editing binary, 439–441
 - enabling forwarding, 123
 - FFS_SOFTUPDATES option, 177
 - files containing preserved, 480
 - identification information, 471
 - identifying device, 114
 - include files, 436
 - IP forwarding, 438
 - messages, 114
 - method of compiling, 436–437
 - modifying configurations, 43
 - modifying without recompiling, 439–441
 - non-kernel executables and files, 441
 - obtaining source code, 436–437
 - parallel and serial IP linkages, 438
 - post-reboot analysis, 479–480
 - ramdisk version, 36
 - rebuilt with debugger installed, 438
 - recompiling, 435–437
 - routing packet, 123–125
 - setting state, 50
 - source files, 48
 - System V shared memory structures, 438
 - testing, 20
 - tuning with sysctl, 465–468
 - Kernel file, 20
 - Kernel messages, 469–473
 - Kernel profiling, 270
 - Kernel routing table, 124
 - kernfs filesystem, 353
 - “kern.securelevel” sysctl variable, 55
 - Keyboard identification, 473
 - Keyboard translation, 57
 - keytab file, 331–332
 - kgmon, 270
 - kinit command, 329–330
 - klist command, 330
 - knecht.mc file, 219, 221
 - Kohl, Florian, 5
 - Konquerer browser, 394
 - Korn shell scripting language, 270
 - kpasswd daemon, 334
 - KPOP (Kerberized POP), 224
 - krb5.conf manual page, 329
 - ksh, 96, 101, 108, 263
 - ktrace utility, 278–280
 - ktutil command, 332
- ## L
- Languages support, 270–273
 - Laptops, 63, 403
 - lastcomm program, 103
 - Layer 2 MAC addresses, 120
 - lchpass, 344
 - lclint tool, 280
 - ldconfig command, 284
 - ldd command, 284
 - LD_LIBRARY_PATH environment variable, 284
 - LD_PRELOAD environment variable, 284
 - Lex, 270
 - lib.m4 library, 360
 - libpcap-based applications, 306
 - Libraries, 273, 283
 - libwrap, 68
 - Line printer daemon, 145
 - lint program, 280
 - Linux
 - hardware, 17
 - naming disks, 169–170
 - LISP programming languages, 274
 - list privilege, 333
 - Listening processes, 130–131
 - lo (loopback) interface, 50
 - Load balancing, 302–303
 - Local caching name server benefit, 412–413
 - LOCAL keyword, 68
 - Local machine, 56, 143
 - Local networks, 313, 403–404
 - Local subnet, 56
 - locate command, 209
 - Lock files, 51
 - Logfiles, 68, 209–210
 - logger command, 306
 - Logging, 68–69, 304–306
 - Login consoles, 60

506 Index

- .login file, 96
- login.conf file, 102, 309, 344
- Logins, 253
 - classes, 343–346
 - scripts, 90
 - secure, 69
 - timeout, 71
- Logs, storing, 46
- logs folder, 244
- logserver.example.net host, 69
- lookup directive, 228
- lpd daemon, 56, 145–146, 407
- lpr command, 145
- lprm command, 146
- LPRng project, 146
- ls command, 75, 409
- Luff, Jolan, 6, 247
- Lynx, 394

- M**
- m4 macros, 359–360, 364–367
- m4 script, 487–491
- MAC addresses, 120–122, 126–127, 142
- Mac68k machines, 20–21
- machdep.allowaperature variable, 84
- MacPPC hardware, 21–22
- mail command, 216
- Mail queue, 208
- Mail servers
 - central, 215
 - default, 60
 - mail matching conditions, 217–218
 - misconfiguration, 224
 - primary, 215
 - relaying mail to, 218
 - /var/spool filesystem, 27
- Mail software, 215–216
- Mailboxes, verifying security, 208
- maildirs format, 190
- mailer.conf system, 222
- Mailing list server, 223
- Mailing lists, 483–484
- mailman package, 223
- mailq command, 216
- MAILTO variable, 212
- mailwrapper command, 216
- majordomo package, 223
- make command, 164, 167, 282, 322
- make install command, 61, 162, 167
- make package command, 164
- make script, 61
- make system, 281–282
- make utility, 165, 456
- Makefile, 43, 105, 160–161, 281–282, 283, 395
- makeinfo command, 78
- makemap dbm /etc/mail/virtusertable “<” command, 220
- Malan, Robert, 298
- man command, 73, 75
- mandoc, 77
- man*.tgz set, 36, 73
- Manual pages, 36, 73–79, 284
- master/ directory, 231
- Master KDC, 334
- Master parent process, 60
- match library, 273
- max directive, 66
- Maximum BSD Web site, 482
- mbox format, 190
- .mc files, 217, 219
- McKusick, Kirk, 177
- MD5 hashes, 12
- MDA (mail delivery agent), 216
- mergemaster command, 429–432
- Messages and security, 225
- mfs (memory filesystem), 181
- mg editor, 269
- Miller, Todd, 6, 283
- minicom, 22
- Mirrored pairs, 170
- Miscellaneous information, 36
- misc mailing list, 445, 483
- misc*.tgz installation set, 36
- MIT Athena Project, 325
- MIT Kerberos V distribution, 337–338
- MIT Web site, 338
- /mnt filesystem, 42
- Modems, 130
- Modified Towers of Hanoi backup strategy, 190
- modify privilege, 333
- modulate state action, 290
- Monkey.org Web site, 483–484
- mopd daemon, 57
- mount command, 174, 180–181
- mountd daemon, 314, 317
- Mounting filesystems, 180–182
- Mouse, 63–64

- console mode, 144
 - console-only mode, 57
 - identification, 473
 - services, 144
 - Mozilla, 382, 394
 - mrouted daemon, 56
 - msdos filesystem, 174–175
 - MTA (mail transfer agent), 215, 224
 - MUA (mail user agent), 215–216
 - Multicast routing and static routes, 51
 - Multiuser system, 26–27
 - MX records, 215, 227
- N**
- NAI version of PGP, 225
 - Name resolution, 228
 - Name servers, 227, 236–237, 412–413
 - named chroot environment, 52
 - named daemon, 52, 227, 232–234, 407
 - named DNS server, 228–232
 - named process, 27
 - named service, 228
 - named.conf file, 233
 - Nameserver, 27
 - nat action, 292
 - NAT (network address translation) device, 292–293
 - nat rule, 293
 - nc (netcat) command, 396
 - NDP (Neighbor Discovery Protocol), 385, 387
 - NetBSD, 9, 14
 - netcat tool, 140
 - net.inet.ip.forwarding variable, 123
 - Netscape S/Key, 134
 - netstart script, 119, 128
 - netstat command, 62, 130, 205, 354, 385, 466
 - Network card interface driver, 119
 - Network daemons, starting, 56–57, 414–415
 - Network devices, 61–62, 114–115
 - Network servers, 414
 - Network socket identification program, 56
 - Networking, 61–62
 - alias addresses, 119–120
 - ARP (Address Resolution Protocol), 120–122
 - basic setup, 114–118
 - boot-time configuration, 115
 - controlling devices and setup information, 115
 - device support, 111–114
 - DHCP, 119
 - dial-up, 129
 - DNS client configuration, 119
 - IP addresses, 115
 - learning names of network devices, 114–115
 - options, 438
 - PPP, 129–130
 - routing, 123–125
 - starting, 50
 - troubleshooting, 131
 - virtual interface drivers, 112–114
 - Networking devices, 111–114
 - Networking systems, 61
 - Networks
 - 802.11B networking standard, 117
 - automatic configuration of hosts, 146
 - bridging, 125–129
 - checking status of configuration, 61–62
 - configuration for installation, 33–34
 - default gateways, 116
 - denying access to, 68
 - information about, 147
 - installing packages, 153
 - interface media options, 116–118
 - listening ports and processes, 130–131
 - modifying system start-up scripts, 116
 - multihomed, 116
 - NAT (network address translation) device, 292
 - status, 130
 - wireless interfaces, 117–118
 - newfs command, 174, 183
 - new-identity file, 255
 - newsaliases command, 219
 - Newsgroups, 484
 - newsyslog command, 103, 209–210, 212
 - NFS (Network File System), 313–317
 - NFS and NIS*, 323
 - clients, 313–314
 - daemon, 53
 - exports, 208
 - partitions, 54
 - servers, 314–317
 - nfsd daemon, 314, 316–317
 - nfs_server variable, 314
 - nfsstat(1) command, 466
 - NFSv3 specification, 317
 - NIDS (network intrusion detection system), 417–423
 - NIS+, 323
 - NIS (Network Information Service), 319–322
 - binding, 52–53
 - clients, 14, 319–320

508 Index

- NIS (Network Information Service), (*cont.*)
 - database, 321
 - domain, 319–320
 - master, 320–322
 - servers, 14, 319–322
 - subsystem, 52
- nm tool, 284
- nmap program, 162–164
- NNTP, 207
- Non-full backups, 198
- Non-GENERIC kernels, 436
- Non-kernel executables and files, 441
- nowait directive, 66
- no-x11 flavor, 165
- Nroff macros, 77
- NS records, 227
- nslint tool, 239
- nslookup command, 237–239
- ntalkd daemon, 138
- NTP (Network Time Protocol), 14, 143–144, 328
- ntpdate, 143

- O**
- Oakley, 348
- objdump tool, 284
- Object file, disassembling, 284
- Objective C, 270
- Objects, 284
- Official mirrors, 481–482
- Open Source Development with CVS*, 459
- OpenBSD, 1
 - export restrictions, 19
 - filesystem layout, 13, 45–48
 - fixes, 425–426
 - free source code, 12–13
 - full code audit, 11
 - hardware support, 14
 - history of, 1, 9
 - ISO images, 19
 - Java support, 15
 - licensing, 12–13
 - open development model, 10
 - releases, 19
 - security, 9–12, 14
 - sets, 35
 - stable releases, 425
 - upgrading, 425
 - usage, 15
 - user friendliness, 14
- OpenBSD Book Web site, 5
- OpenBSD Journal Web site, 481
- OpenBSD through OpenBSD PF NAT firewall, 373–380
- OpenBSD Web site, 481
 - 3.4 tools directory, 18
 - anonymous CVS servers, 458
 - backup media, 187
 - FAQ, 443, 481
 - INSTALL Linux directory, 18
 - installation guide, 17
 - interface to GNATS tool, 446
 - official mirrors listing, 459
 - patches, 464
 - stable packages, 157
 - supported hardware, 17
 - Upgrade Mini-FAQ, 426
 - usergroups, 484
- openbsd-mobile mailing list, 483–484
- OpenFirmware, 21
- OpenGL libraries, 283
- OpenSSH, 9, 11–12, 69
 - alternative key, 263
 - arbitrary port forwarding, 262
 - authentication, 262
 - channel compression, 262
 - client options, 261
 - command-line switches, 263–264
 - command-line use, 254–260
 - configuration, 261–262
 - connecting to remote hosts, 253
 - encrypted channel, 262
 - identity file, 263
 - keys, 40
 - privilege separation, 264
 - scp command, 253, 255–257
 - server configuration options, 261–262
 - sftp, 264–265
 - ssh command, 254–255
 - ssh-add command, 258–259
 - ssh-agent command, 258–259
 - sshd process, 259–260
 - ssh-keygen utility, 257–258
 - tunnel compression on command line, 263
 - use in other packages, 262–263
 - X forwarding disabled, 14
- openssl command, 220, 247, 348
- OpenSSL libraries, 283
- Openwin, 83
- options manual page, 438
- Orange Book features, 10

- os ruleset factor, 304
 - OSs (operating systems), 18
 - packet identifications, 299
 - selective filtering based on, 303–304
 - out-of-date tool, 167
 - Owner sanity checks, 54
- P**
- p0f tool, 423
 - Package database, 153
 - package target, 165
 - Packages, 15, 61
 - building from ports, 161–166
 - checking compilation, 164
 - detailed information about, 156
 - directory, 161–162
 - documentation, 81–82
 - extracting, 152
 - files for, 161
 - finding files in, 156–157
 - flavors concept, 164–165
 - forced installation or removal, 154–155
 - generating without installing, 164
 - information about, 155–157, 160
 - installation options, 153
 - installing, 152–154, 162, 165, 167
 - listing with description, 155–156
 - location as path, 160
 - looking for additional, 153
 - naming, 152
 - network installation sources, 153
 - overview, 151–152
 - platforms, 152
 - removing working source code directory, 165
 - requirements, 152
 - security, 9
 - uninstalling, 154–155, 165, 167
 - upgrading, 155
 - Packet filters, 285
 - Packet scrubbing, 298–299
 - Packets, 286–288, 298
 - Packetstorm Web site, 482
 - Parallel and serial IP linkages, 438
 - Partition table, 182–185
 - Partitioning
 - automating, 41
 - example, 28–33
 - filesystem, 25–33
 - firewalls, 28
 - general-purpose server system, 26
 - multiuser system with untrusted users, 26–27
 - personal system, 25–26
 - servers, 27
 - swap space allocation, 28
 - Partitions, 170–173, 179
 - Passphrases, 341–342
 - passwd program, 97
 - Passwords, 95–97
 - encrypting, 99
 - Kerberos, 327
 - POP servers, 138
 - restrictions, 97
 - users, 340
 - patch command, 432, 462–463
 - patch target, 165
 - Patches, 461–465
 - patches subdirectory, 161
 - PATH variable, 108
 - Paul, Chris, 423
 - pax command, 195–197
 - Paxson, Vern, 298
 - pcap filters, 309
 - pcap libraries, 283
 - PCI BIOS identification, 472
 - pdg.delete command, 154
 - Performance
 - GENERIC kernel, 435
 - tuning firewalls, 311
 - Web servers, 251
 - Perl, 79–81, 248–249, 270, 280–281
 - perldoc system, 80
 - permanent keyword, 121
 - permit as statements (Systrace.), 413–414
 - persist flag, 294
 - Personal system, partitioning, 25–26
 - PF (packet filter), 9, 127, 285–286, 401
 - advanced usage, 294–303
 - affecting TCP sequence numbers for
 - hosts, 290
 - anchors, 297–298
 - antispoof action, 292
 - arbitrary directionality for packets, 290
 - authenticated firewall rules, 309–311
 - binat rule, 293
 - block policy, 291
 - changing ruleset for user during login, 297
 - cleaning don't fragment bit from packets, 299
 - configuration files, 288, 431
 - congestion problem, 300
 - determining firewall rules, 308–309

510 Index

- PF (packet filter), (*cont.*)
 - dropping random packets from queues, 300
 - duplicating fragments, 299
 - dup-to action, 291
 - effective packet filter, 288
 - enforcing minimum TTL value, 299
 - evaluating rules, 288–289
 - examining NAT statistics, 292
 - examining state table, 306–308
 - fastroute action, 291
 - firewalls, 288–292, 311
 - fixing overlapping fragments, 299
 - interface for handling addresses, 289
 - IPv4, 289
 - IPv6, 289
 - keep state modifiers, 307
 - load balancing, 302–303
 - loading ruleset, 51
 - logging, 304–306
 - maximum MSS value for TCP traffic, 299
 - NAT (network address translation) device, 292–293
 - options applied to packets and connections, 290
 - order of rules, 298
 - os ruleset factor, 304
 - packet analysis, 290
 - packet decisions on basis of network process context, 290
 - packet scrubbing, 298–299
 - ports specification mechanism, 289
 - prioritizing queues, 301
 - priority for each rule, 300
 - randomly assigning IPID values, 299
 - rate limiting, 300–301
 - redirection, 293
 - reply-to action, 291
 - route-to action, 291
 - routing decisions on packets, 291
 - selective filtering based on operating system, 303–304
 - selectively dropping overlapping fragments, 299
 - selectively normalizing TCP connections and states, 299
 - setting up queues, 300–301
 - Snort, 422
 - specifying bandwidth rates for each rule, 300
 - stateful analysis of TCP, UDP, and ICMP packets, 290
 - streams for monitoring, 291
 - tables, 294–297
 - TCP flags, 290–291
 - timing settings, 311
 - transparent filtering, 301–302
 - user interface changes, 286
- pf.conf file, 302, 310
- pfctl command, 286–287, 292–295, 298, 436
- pflog interface, 305, 420
- pflogd daemon, 52, 304–306
- pfsync, 306–309
- PGP, 225
- PHP, 249, 274, 280–281
- PID values, 61
- Pilot/OTP program, 342
- ping6 command, 385, 392, 402–403
- pkg subdirectory, 161
- pkg_add command, 152–154, 162, 167, 418
- PKG_DBDIR environment variable, 153
- pkg_delete command, 154–155, 165, 167
- pkg_info command, 155
- PKG_PATH environment variable, 153
- PKG_TMPDIR environment variable, 153
- Platforms and packages, 152
- Platform-specific information, 22–23
- Pod format, 79–81
- pod2man program, 79
- Policies, 409–413
- POP (or IMAP) over SSL, 224
- POP security, 224
- POP servers, 138, 222–223
- POP3 protocol, 222
- POP3 servers, 224
- popa3d daemon, 138, 216, 222–224
- Port-level redirection, 293
- portmap daemon, 52, 66, 140, 313–315, 317
- Ports, 15, 61, 159
 - building package from, 162–166
 - building source code, 161–162
 - category, 160
 - dependencies, 161, 167
 - directory name, 160
 - distribution archives, 161
 - files needed for distribution, 161
 - flavors, 152, 166
 - identification, 167, 473
 - information needed to build, 161
 - installing files outside of /usr/local, 13
 - integration with OpenBSD, 168
 - IPv6, 382

- life cycle of build, 161–166
 - packages build from ports tree, 161
 - patches, 161
 - prebuilt and packaged, 152
 - preparation of source code, 161
 - problems with, 168
 - ranges, 289
 - removing work files, 165
 - retrieving distfile, 165
 - security, 12
 - simultaneously building multiple, 166
 - source archive, 161
 - templates and directions for makefiles, 161
 - updating specific, 166–168
 - ports mailing list, 483
 - Ports specification mechanism, 289
 - Ports tarball, 46, 156–160
 - Ports tree, 13, 15, 61
 - changes and, 159
 - dependency checks, 159
 - directories without ports, 161
 - distfiles directory, 161
 - files directory, 161
 - grouping applications, 160
 - include directives, 282
 - INDEX file, 160
 - modules, 249–250
 - obtaining, 156–160
 - packages directory, 161
 - ports tarball, 156–160
 - searching for application, 160
 - structure of, 160–161
 - support applications, 159
 - troubleshooting, 168
 - version, 168
 - windows manager, 89
 - without compiler, 159
 - Port-scan detection system, 423
 - ports.tar.gz file, 160
 - POSIX.1e capabilities, 10
 - Postfix mail server, 222
 - Postgres database, 419
 - Post-installation, 39–40
 - Power, automatic management, 62–63
 - PPP user dial-up, 129–130
 - Practice of Programming, The* (Kernighan and Pike), 277
 - Primary mail server, 215
 - Primary servers, 144, 228
 - Principals, 326–327, 333
 - printcap files, 145
 - printenv script, 243
 - Printing, 56, 145–146
 - Priority Queue, 300
 - Privilege separation, 12
 - Privileged users, 104–107, 413–414
 - Proactive security, 12
 - Process accounting, 55, 102–104, 207
 - Process IDs, 10
 - Processes
 - child shells, 108
 - default, 60
 - listening, 130–131
 - random process numbers, 61
 - restricting, 109
 - starting, 59
 - .profile file, 96, 263, 454–455
 - Profiling tools, 270
 - “Programmers Supplementary Documentation,” 284
 - Programs
 - add-on, 61
 - checking for available space, 152
 - identifying dependency, 152
 - protecting, 67
 - stand-alone environment, 48
 - user to run, 66
 - user-added, 57
 - for users, 46
 - PROM, 23
 - ProPolice mechanism, 273–274
 - Provos, Niels, 6, 99, 416
 - Proxies for IPv4 and IPv6, 394–396
 - Proxy servers, 251
 - proxy-arp, 121
 - ps command, 480
 - pserver, 436–437, 455
 - pseudo-device directive, 112
 - Pseudo-disks, 182–184
 - PTR records, 227
 - pub keyword, 121
 - pubkeys/ directory, 349
 - Publicly accessible shell servers, 414
 - Python, 274, 280–281
- Q**
- Qmail mail system, 222
 - quick action, 288–289
 - quota command, 176
 - Quota files, creation of, 175

512 Index

Quota management, 54
quotacheck, 54

R

“r” tools, 135
radiusd server, 345
RAID 5 array, 172
raidctl manual page, 171, 172
RAIDFrame, 48–49, 170–173
Ramdisk kernel configurations, 43
Random number generator, 12
Random PID values, 61
Randomized process IDs, 10
RARP (reverse ARP), 142
rarpd daemon, 56, 141–142
Rate limiting, 300–301
rbootd daemon, 57
RC scripts, 59–60
rc.conf script, 144
rc.local script, 144
rc.securelevel script, 144
rc.vpn script, 351
rdate, 53
rd.conf control file, 62
rdist facility, 208
Reactive rulesets (PF), 296–297
Read-only filesystems, 315
Realms, 326–327, 332–333, 337
Reboot, 40
Recompiling kernel, 435–437
red (Random Early Detection), 300
red flag, 300
Regular system scripts, 207–209
Relocatable objects, 272
Reminders, 208
Remote access, 135
Remote applications, 137
Remote files, 135, 204–206
Remote hosts
 connecting to, 253
 logging onto, 69
 rshd process, 143
 spawning shell on, 142–143
 usernames, 70
Remote login, 135
Remote printers, 145
Remote servers
 connecting users to, 254–255
 verifying fingerprint, 263–264
 viewing logged on users, 136

Remote shell, 142–143
Remote users, 136
Reporting bugs, 447–449
repquota tool, 176–177
resolv.conf file, 412
Resolver, 227–228
Resources, 101–104
restore tool, 197–200
Restoring files from backup media, 198–200
Restricted shells, 108
Restricting processes and users, 109
Resume script, 62
Reverse ARP requests, 56
Reversing text, 90
.rhosts file, 135, 143, 208
rksh command, 108
rlogin program, 135
rmuser: program, 97–98
Roesch, Marty, 417
Rogue, 150
Root
 connecting with ssh, 71
 electronic mail, 218–219
Root device, 20, 471
Root filesystem, 27, 208
/root/XF86Config.new file, 87
round-robin action, 302–303
route command, 123–124, 385, 394
route6d daemon, 56, 386–387, 400
routed daemon, 56
Router advertisements, 388, 403
Router solicitation messages, 56, 387–388
Routing, 123–125, 215
Routing daemons, 400
Routing server, 14
Routing tables, 123–124
RPC, 270
 daemons, 52
 NFS, 314
 program numbers, 315
 services, 140
rpcgen tool, 270
rpcinfo command, 315, 317
rpc.lockd daemon, 314
rpc.yppasswdd daemon, 322
RSA host key, 56
rsh utility, 135, 142–143, 204, 454
rshd daemon, 143
rstatd daemon, 66
rsync command, 204–206, 263, 396

- rsync mirrors, 481
 - rsync servers, 205–206
 - rsyncd.conf file, 205
 - RSYNC_RSH environment variable, 263
 - rtadvd daemon, 56, 387
 - rtsol program, 119, 382, 388–389
 - rtsold daemon, 56, 389, 402–403
 - RULE_PATH variable, 420
 - Runtime link editor directory cache, 55–56
 - rusersd service, 66
 - rwwho tools, 208
 - rwhod daemon, 56
- S**
- S flag, 63
 - sa command, 104
 - savecore command, 479
 - scan_ffs tool, 184–185
 - scanlogd tool, 423
 - Scheduling facilities, 210–214
 - Scheme, 274
 - Schiedar, Stephan, 422
 - scp command, 69–71, 255–257, 403
 - Screen, blanking after period of inactivity, 57
 - Scripts reacting to events in logfiles, 296–297
 - scrub action, 298–299
 - SCSI disks, 169–170
 - sdm program, 58, 88–89
 - search keyword, 228
 - Secondary servers, 144, 228
 - Secure by default, 14
 - Secure file transfer, 69
 - secure keyword, 22
 - Secure logins, 60, 69
 - SecureID login, 345
 - SecureNet authentication, 345
 - Security, 9
 - AES (Advanced Encryption Standard)
 - algorithms, 11
 - Blowfish algorithms, 11
 - bug fixes, 11
 - cryptology, 11–12
 - development model, 9–10
 - DHCP, 150
 - DNS, 232–233
 - electronic mail, 220–221, 223–225
 - enabling services, 14
 - ensuring code correctness, 10
 - firewalls, 15
 - FTP server, 133
 - full code audit, 11
 - gcc compiler, 273–274
 - general-purpose server system, 26
 - handling error conditions, 10
 - IPv4, 347
 - IPv6, 347, 382, 401–402
 - Kerberos, 336–337
 - messages, 225
 - MTA, 224
 - NFS, 317
 - NIS, 322–323
 - OpenBSD security model, 10–11
 - OpenSSH, 11–12
 - OS code, 9
 - packages, 9
 - POP, 224
 - ports, 12
 - proactive, 12
 - randomized process IDs, 10
 - restricted shells, 108
 - sudo command, 107
 - tftpd servers, 141
 - third-party software, 157
 - X Window system, 92
 - zone transfers, 232
 - security-announce mailing list, 464
 - Selective filtering, 303–304
 - sendbug utility, 447–449
 - sendmail, 56, 60, 65, 69, 216–222, 396, 398–399
 - Serial consoles, 20–22
 - Server program arguments field, 66
 - Server Program field, 66
 - Servers
 - nonstandard ports, 254
 - part of inetd, 138
 - partitioning, 27
 - polling for time, 144
 - primary (DNS), 144
 - recognizing, 72
 - secondary (DNS), 144
 - sharing filesystems, 313
 - Stratum 1 and 2 (NTP), 144
 - Service name field, 66
 - Services
 - bootparamd, 141–142
 - build support for Kerberos, 328
 - chargen service, 139
 - comsat, 137
 - daytime service, 139–140
 - dhcpcd, 146

514 Index

- Services (*cont.*)
 - disabled, 133
 - discard service, 140
 - echo service, 139
 - enabling, 14, 58
 - fingerd, 136–137
 - ftpd, 133–134
 - identd, 137
 - internal, 138–140
 - Internet, 60
 - IPv6, 397–400
 - Kerberos, 140, 334–336
 - mouse, 144
 - ntalkd, 138
 - popa3d, 138
 - port redirection, 52
 - portmap service, 140
 - printing, 145–146
 - rarpd, 141–142
 - remote shell, 142–143
 - RPC, 140
 - sftp, 134
 - shell, 135–136
 - starting, 133
 - telnetd, 134–135
 - tftpd, 141
 - time, 143–144
 - time service, 139–140
- set device root_device command, 20
- setgid file, 208
- Sets, adding, 35
- setuid file, 208
- sftp, 134, 264–265
- Shared libraries, 55–56, 273, 283–284
- Sharing filesystems, 313, 315
- SHELL variable, 108
- Shells, 135–136
 - aware of agent, 258
 - changing default, 99
 - default, 96
 - listing, 96
 - PATH variable, 85
 - restricted, 108
 - spawning on remote host, 142–143
- .shosts file, 208
- showmount tool, 317
- Shutdown, 48–58
- Simpson, Cameron, 79
- Single sign-on technology, 325
- Single user mode, 20
- Sinkhole router, 291
- Site-specific files, 40–41
- site*.tgz file, 40–41
- sk* interfaces, 420
- S/Key program
 - authentication, 339–343
 - challenge and response, 339–340
 - ftpd tool, 134
 - hosts, 72
 - Netscape, 134
 - obtaining passphrases, 341–342
 - passwords, 12, 340
 - setup, 340
 - sshd setup and usage, 343
 - telnetd, 134
- skeyinit tool, 340
- slave/ directory, 231
- Slave KDC, 57, 334
- Smalltalk, 274
- S/MIME, 225
- SMTP forwarding daemon, 56
- SMTP servers, 65
- SMTP transactions, 221
- smtplwdd daemon, 56
- Snapshots, 432
- snk command, 345
- SNMP queries, 66
- SNMP servers, 66
- Snort, 417–423
- snort2pf tool, 422
- Socket type field, 66
- Soft updates, 177–178
- Software
 - installed into fake root directory, 162
 - installing custom manual pages, 76
 - mirrors, 481
 - README files, 81
- Software RAID filesystems, 170–173
- Solaris
 - /etc/inittab file, 48
 - naming disks, 170
 - Openwin, 83
- Song, Dug, 6
- Sound hardware, 18
- Source code
 - analysis, 280
 - applying patches, 165
 - assembling, 271

- base system, 46
- build process, 428–429
- building with debugging symbols enabled, 475–476
- compiling, 165, 271
- configuring, 165
- development tools, 280–281
- kernel, 48, 436–437
- linking, 271–272
- patches, 461–464
- upgrading from, 427–429
- Source directory, 48
- Source port-destination port pair, 65
- source-changes mailing list, 483
- source-hash keyword, 302
- SPARC, 21–23
- Spoofing, 317, 327, 381
- Squid, 251
- src CVS module, 456
- srvtab file, 332
- ssh (secure shell), 69, 136, 204, 253, 396, 454
 - combined with key-based authentication, 255
 - configuring, 71
 - default escape character, 72
 - ease of use, 70
 - forwarding X session information, 91–92
 - identity file to authenticate to system, 254–255
 - incoming connections, 57
 - Kerberos, 335
 - port option, 254
 - public key authentication, 191–195
 - rsync program, 263
 - versions, 254
- SSH, the Secure Shell, the Definitive Guide* (Barret and Silverman), 72
- ssh clients, 259–260
- SSH host key, 56
- ssh servers, 14
- ssh-add command, 258–259
- ssh-agent program, 186, 254, 258–259
- .ssh/config file, 72, 261
- sshd daemon, 57, 60, 65, 69–72, 259–261, 335, 339, 343, 399
- ssh-keygen -c command, 257
- ssh-keygen command, 257–258
- SSL, 76, 245–247
- SSL Library, 76
- SSL-enabled Apache Web server, 14
- stable branch, 425–426
- stable packages, 157
- /stand directory, 48
- Standby script, 62
- STARTTLS facility, 220–221
- Start-up, 48–60
- State table, 306–308
- stateless autoconfiguration, 387–389
- Static hosts, 149
- Static libraries, 273
- Static routing tables, 123
- Stream socket, 66
- stsh shell, 476
- stty command, 20
- stunnel tool, 224
- su command, 100
- sudo command, 104–107
- sudoers file, 106
- Super-server for daemons, 56
- Superuser, 100, 176
- Support applications, 159
- Supported hardware, 17
- Suspend script, 62
- Swap space allocation, 28
- swapctl, 49
- /sys symlink, 48
- sysctl command, 123, 286, 349–350, 388, 465–467, 478–479
- syslog command, 46, 52, 60, 68–69, 107, 133, 306, 409
- syslog port, 60
- syslog server, 65, 68
- syslogd daemon, 68–69, 71
- SyslogFacility AUTH and LogLevel INFO paramter, 71
- System
 - adding users and groups, 426
 - adjusting time, 144
 - auditing actions, 107
 - BIOS identification, 472
 - changing state, 63
 - daemons, 46
 - development, 278
 - information leaks about, 66
 - mtree check, 208
 - preparation for installation, 18–19
 - preparation for upgrading, 426
 - serial console, 21–22
 - setting domain name, 50
 - setting hostname, 42, 50

516 Index

- System (*cont.*)
 - setting IP address, 42
 - setting security level, 55
 - stand-by, 63
 - start-up configuration, 438
 - suspending, 63
 - tracking health of, 470
- System binaries, 13, 46
- System calls, 405, 416
- System disks, 49, 208
- System dumps, 208
- System files, 46, 208
- System image, 479
- System logging service, 60
- System scripts, 207–209
- System sets, 434
- System software backups, 190
- System V shared memory structures, 438
- systrace, 109, 405, 406, 416
 - arbitrary external policies, 405–406
 - device, 405
 - environment variables, 409
 - example usage, 408–410
 - executables, 406
 - intrusion detection logging system, 415
 - limitations, 416
 - local caching name server benefit, 412–413
 - network servers, 414
 - permit as action, 413
 - policy creation, 410–413
 - privilege elevation, 413–414
 - protecting users from processes, 407
 - setting user ID, 413–414
 - software testing, 415
 - storing generated policies, 408
 - system calls, 416
 - system coverage, 414–415
 - target uses, 407
 - untrusted data paths, 407
 - untrusted users operating shells, 407
 - where to use, 414
 - wrapping child processes, 415
- T**
- Tables, 294–297
- talk program, 138
- tar command, 35, 40, 200–201
- Targets, 281
- Tasks, 60, 210–212
- Tcl/Tk, 76, 274
- TCP
 - initial sequence numbers, 10–11
 - IPv4, 67
 - SYN operating system, 303–304
- tcp keyword, 397
- TCP wrappers, 67–68
- tcp6 keyword, 397
- TCP6 protocol, 67
- tcpc configuration file, 390
- tcpd daemon, 67–68
- tcpdump command, 304–307, 309, 352–353, 385, 402
- tcpreplay, 304–306
- tech mailing list, 483
- tech@openbsd.org mailing list, 445
- telnet, 60, 396
 - daemon, 134–135
 - denying all connections to, 68
 - Kerberos V, 335–336
 - obtaining passphrase, 341
 - plaintext logins, 339
- Templates and sendmail, 217
- Temporary files, 47
- Terminals, adding and removing, 58–59
- test-cgi script, 243
- Texinfo, 78
- Text, reversing, 90
- Text editors, 269–270
- tftpd daemon, 141
 - .tgz extension, 35
- Third-party software and security, 157
- thttpd daemon, 250
- tickadj program, 143–144
- ticket forwarding, 326
- ticket-granting tickets, 326, 330
- Tickets, 326, 329–331, 337–338
- time 4/6 service, 66
- Time of day, 139
- time service, 139–140, 143–144
- Time zone information and example, 39
- tkman tool, 75
- TLS library, 76
 - /tmp directory, 26, 47, 54, 207, 330
 - /tmp/comp34.tgz file, 35
 - tmpnam() function, 276–277
 - /tmp/pkg directory, 153
- Token-based authentication methods, 344–345

top tool, 436
 Towers of Hanoi backup strategy, 189–190
 traceroute, 393
 traceroute6, 385, 402
 Tracing system calls, 278–280
 Transparent firewall, 127, 301–302
 Trusted third-party SSL, 246–247
 tty00 modem port, 21
 tty01 printer serial port, 21
 TUCOWS Web site, 482
 tunnel keyword, 112
 Tunnelling, 384–385
 twm window manager, 89

U

UDP, 140–141
 udp6 keyword, 398
 ulimit command, 101
 UltraSPARC serial consoles, 21
 unconfig command, 182–184
 uninstall target, 165
 Uninstalling packages, 154–155
 Union filesystems, 181
 UNIX, 9, 45, 76, 83
 unmount command, 180–181
 Unmounting filesystems, 180–181
 Untarring ports tarball, 46
 Upgrade Mini-FAQ, 426
 Upgrading, 425

- binary format changes, 432–434
- from binary sets, 427
- branches, 425–426
- configuration files, 429–432
- CVS servers, 425–426
- fixes, 425–426
- installation, 43
- installboot program, 433–434
- mergemaster command, 429–432
- packages, 155
- snapshots, 432
- from source code, 427–429
- system preparation, 426

 USB identification, 472–473
 User accounts, self administration, 100
 User administration, 95
 USER environment variable, 409
 useradd command, 98–99
 User-created manual pages, 77–78
 Usergroups, 484

user_ip macro, 310
 Userland binaries, 13
 Usernames, 70, 137
 Users

- ability to connect without password, 135
- adding before updates, 426
- altering default options, 99
- audit trail, 97
- batch mode addition, 98
- centralized management, 319
- checking status of disk quota consumption, 176
- chroot locked into home directory, 134
- connecting to remote servers, 254–255
- creation and deletion, 95–99
- default settings for adding, 96
- default shell, 96
- disk quotas, 175–177
- displaying tasks, 211
- home directories, 47, 96–97
- information about, 66, 95
- informing about net mail, 137
- IPv6, 385
- limiting access to resources, 101–102
- listing, 208
- login class, 99
- maximum name length, 97
- passwords, 96–97, 340
- privileged, 104–107
- process accounting, 102–104
- restricted shells, 108–109
- self account administration, 100
- setting default options, 95–96
- S/Key password, 340

 users folder, 244
 users group, 100
 User-specific policies, 407
 User-supplied binaries, 108
 /usr directory, 25–28, 45, 160, 456
 /usr/bin directory, 46
 /usr/lib directory, 273, 284, 412
 /usr/libexec filesystem, 46
 /usr/local directory, 5, 25, 47, 159, 314, 316
 /usr/local/bin directory, 47, 159
 /usr/local/include directory, 47
 /usr/local/lib directory, 47, 273, 284
 .usr/local/man directory, 76
 /usr/local/sbin directory, 47
 /usr/local/share/doc directory, 81

518 Index

- /usr/ports directory, 5, 46
- /usr/ports/mypackages file, 166
- /usr/ports/x11 subtree, 89
- /usr/sbin directory, 46
- /usr/share/man directory, 76
- /usr/share/mk directory, 282
- /usr/share/mk/bsd.own.mk file, 328
- /usr/share/sendmail/cf directory, 219
- /usr/share/zoneinfo directory, 39
- /usr/src directory, 5, 46, 428
- /usr/src/distrib, 41–43
- /usr/src/sys directory, 48
- /usr/src/sys/arch/i386/conf file, 43
- /usr/src/sys/conf directory, 438
- /usr/X11R6 hierarchy, 76, 84–85, 284
- /usr/XF4, 5
- utmp, 133

V

- Valchev, Peter, 6
- /var filesystem, 26–28
- /var partition, 46
- /var/adm directory, 46
- /var/amanda/DailySet1 directory, 203
- /var/cron directory, 211–214
- /var/db directory, 51, 119, 148–149, 153
- /var/heimdal directory, 331–333
- /var/heimdal.kdc.conf file, 331
- Variables, 46, 286, 465–467
- /var/log directory, 46, 87, 97, 133, 259–260, 409
- /var/messages file, 207
- /var/named directory, 27, 52, 228–g229
- /var/preserve file, 207
- /var/run directory, 52, 63, 148, 351, 353–354, 373
- /var/rwho file, 207
- /var/spool filesystem, 26027
- /var/tmp directory, 26, 153, 207, 429–430, 432
- /var/www directory, 27, 243–245, 249, 431
- /var/yp/DOMAINNAME/ directory, 321–322
- Verifying input, 444
- Verisign, 246–247
- vi editor, 55, 99, 269
- Video hardware, 18, 83
- vipw tool, 99–100
- Virtual devices, 112
- Virtual disks, 182–184
- Virtual hosting, 219–220
- Virtual interface drivers, 112–114
- Virtual memory swap space, 49

- Virtual private networking, 76
- virtusertable.txt, 220
- visitors class, 343–344
- VISUAL variable, 211
- visudo command, 105
- VLAN (Virtual LAN) devices, 112–113
- vmstat tool, 466
- vmunix file, 23
- Volatile data, 190
- VPNs (virtual private networks), 76, 350
 - example configuration, 354–380
 - laptop configuration, 374–377
 - Non + Tunnel: Net-Net, 360–364
 - OpenBSD through OpenBSD PF NAT firewall, 373–380
 - OpenBSD-OPENBSD + Tunnel: Net-Net, 355–360
 - OpenBSD-OpenBSD + Tunnel: None, 364–367
 - remote configuration, 377–380
 - wireless laptop to a secure gateway, 368–373

W

- w3m, 394, 396
- wd0a root device, 20
- Web servers, 15, 27, 243, 250–251
- Web-based filesystem, 250
- weblint tool, 251
- WEP (Wired Equivalent Privacy), 118
- whatis command, 75–76
- whatis database, rebuilding, 209
- wheel group, 100
- whois command, 240–241
- wi driver, 111, 117
- wicontrol command, 117–118
- Window managers, 88–90
- Windows 2000, 336
- Windows managers, 83
- winkey.exe program, 342
- Wireless devices, 118
- Wireless interfaces, 117–118, 131
- Wireless laptop to secure gateway, 368–373
- wm2 window manager, 89
- Working directory, 108
- WRKOBJDIR directory, 165
- wsconsctl daemon, 57
- wsmouse devices, 144, 473
- wsmoused daemon, 57, 63–64, 144
- wsmoused(8) manual page, 63
- www6to4 tool, 394–396

X

X Window System, 83

3.3.6 servers, 84

4.x series servers, 84

alternate window managers, 88

applications, 71–72, 83, 90–91

basic X applications, 90–91

components shared across architectures, 84

DefaultDepth directive, 87–88

displaying graphics, 83

distribution, 282–283

editing XF86Config file, 87

environment, 213, 409

forwarding, 262

graphical login, 88–89

installing, 84

processing login scripts, 90

quick setup, 85–88

remote display, 91–92

resizing fonts, 90

reversing text, 90

security, 92

server, 36, 83, 87, 92

source tree, 429

starting -configure flag, 87

switching resolution, 88

system, 36

terminal window, 90

troubleshooting configuration, 87

UNIX sockets creation, 54

video hardware, 83

window managers, 83, 89

wrong color bit depth set, 87–88

wrong resolution, 87–88

xbase33.tgz set, 84

XDM (X Display Manager), 88–89

xinerama, 83

xman, 75

x509 keys creation, 348–349

Xaccess file, 88–89

xbase*.tgz installation set, 36

Xdefaults file, 90

XDM (X Display Manager), 88–89

xemacs editor, 269–270

XF86Config file, 87

xfont*.tgz installation set, 36

XFree86 4.x series userland and libraries,

83–85

XFree86 servers, 85–87

xfs X font server, 92

xhost command, 92

XHP server, 84

.xinitrc file, 89

xman, 75

xmkmf command, 282

Xresources file, 88–89

xserv*.tgz installation set, 36

Xsession file, 88

.xsession file, 88

xshare33.tgz set, 84

xshare*.tgz installation set, 36

xsysrtrace application, 409

xterm, 90–91

Y

Yacc, 270

Ylonen, Tatu, 69

yp daemon, 52

yp manual page, 323

ypbind command, 320

ypinit command, 320

Z

Zalewski, Michal, 303

zzz command, 63

