



Numerics

0xFEFE protocol, 33

A

access layer, 158

 devices, 164

addressing, 61

 duplicate system IDs, 133

 node-based

 Area ID, 40

 NET, 41

 N-selector, 40

 SysID, 40

 structure, 165–167

adjacencies

 DIS election process, 58–59

 error logging, 340

 ES-IS, forming, 48

 establishing fast convergence, 190–192

 formation, troubleshooting, 322

 IS-IS

 forming, 49–50

 over multiaccess media, forming, 54–56

 Level 1, forming, 57

 Level 2, forming, 57

 logging changes in, 295

 maintenance, IS-IS versus OSPF, 205

 point-to-point, forming, 51–54

 problems, debugging, 315

 reachability information, displaying, 333–334

 statistics, displaying, 305, 306

 subnetwork-dependent functions (routing layer), 48

 two-way communication, 57

 virtual adjacencies, 100

Adjacency database, 23

administrative distances, 61, 305

 default, 234

advertising

 external routes, 335–337

 interarea routes, 286

 subnets, 333–334

AFI (Authority and Format Identifier), 70

aggregation, CIDR, 12

ANSI (American National Standards Institute),

 NSAP address registration, 75

arc, 140

Area Addresses TLV (LAN hellos), 45, 52, 56, 104

Area ID field

 NSAP addresses, 69, 72

 simplified NSAP addresses, 73

Area ID, 40

area-level authentication, 285

area-password command, 285

areas, 40, 162–164

 addressing scheme, 41

 adjacencies, two-way communication, 57

 duplicate system IDs, troubleshooting, 326

 IS-IS as an IGP, 168

 IP prefix advertisement restrictions, 170

 metric limitations, 169

 IS-IS versus OSPF, 215

 L1 to L2 route leaking, 286–288

 Level 1 adjacencies

 forming, 57

 routers, 41

 routing table, displaying, 311

 Level 1-2 routers, 41

 Level 2

 adjacencies, 53, 57

 routers, 41

 merging, 80

 multi-area configuration, 289

 nonhierarchical design, 174–175

 splitting, 80

AS (autonomous system), 39, 73. *See also* areas

AS Path attribute (BGP), 16

ASICs (application-specific integrated circuits), 22

assigning

 metrics, 172

 passwords to interfaces, 284

ATM, point-to-point configuration, 268

ATT bit, verifying configuration, 310
 Attached field (LSP), 101
 authentication, 53, 62

- comparing IS-IS and OSPF, 215
- configuring, 284–285
- troubleshooting, 340

 Authentication Information TLV, 45–46
 Authentication Information TLV (Level 1 LSP), 105
 Authentication TLV (LAN hellos), 53, 56
 Authority and Format Identifier. *See* AFI
 autonomous system. *See* AS
 availability, downtime, 236

B

backbone, 161

- Level 2, 41
- routers, 41
- selection criteria, 247

 background method, migrating from EIGRP to IS-IS, 233
 background timers, 181
 BCD (binary coded decimal) format, NSAP address fields, 75
 Bellman-Ford algorithm, 140
 best effort, 124
 best path determination, longest match routing, 21
 BGP (Border Gateway Protocol)

- AS Path attribute, 16
- coexistence with IS-IS, 176–178
- synchronization, 177–178

 black-holing, 176

- overload bit, configuring, 178–179

 broadcast interfaces, show clns interface command output, 308–309
 broadcast links, flooding LSPs, 124–126
 broadcast multicast link configuration, 266
 broadcast subnetworks, 47
 BSI (British Standards Institute), IOTA-based NSAP addresses, 74–75
 building shortest path tree, 147–148

C

calculating

- best path determination, example, 144–146
- IS-IS routes, 147–148
- SPF algorithm
 - computational complexity, 143
 - memory requirements, 144

 CEF (Cisco Express Forwarding), 23–24
 centralized router architecture, 8
 checksum, 132
 Checksum field (LSP), 99–100, 132
 CIDR (Classless Inter-Domain Routing), 12
 Circuit Type field (LAN hello), 55
 Cisco 7500 routers, SPF process, 148–150
 Cisco IOS Software

- command options. enabling, 291
- exponential backoff, 188
- example, 190
- parameters, 189

 classful addressing, 9–10
 classful IGPs. migrating to IS-IS, 246–247
 classful routing protocols, 14
 classification of routing protocols, 14

- classful versus classless, 14
- distance-vector versus link-state, 16
- interdomain versus intradomain, 15–16

 classless IGPs, EIGRP migration, 232
 classless IP addressing, 10
 classless routing protocols, 14
 clear command, 314
 clear-text authentication, configuring, 284–285
 clear-text password authentication, 62

- troubleshooting, 340

 CLNP (Connectionless Network Protocol), 33, 299

- OSI network addresses, 69

 CLNS (Connectionless Network Service), 31–33

- CLNP, 33
- ES-IS, 33, 34
- Integrated IS-IS, design goals, 35
- IS-IS, design goals, 34–35

 clns host command, 84
 clns router command, 260
 clns routing command, 260

- combining
 - areas, 80
 - old and new-style TLVs, 172
- commands
 - area-password, 285
 - clear, 314
 - clns host, 84
 - clns router, 260
 - clns routing, 260
 - debug isis adj-packets, 285, 315, 330
 - debug isis spf-events, 316–317
 - debug isis update-packets, 317–318
 - debugging, 300
 - default-information originate, 272
 - display-route-detail, 335, 338
 - distance, 244
 - domain-password, 285
 - ignore-lsp-errors, 295–296, 339
 - ip router isis, 260, 333
 - isis circuit-type, 323
 - isis hello-interval, 292
 - isis hello-multipplier, 292
 - isis lsp-interval, 181–182
 - isis metric, 292
 - isis retransmit-interval, 130, 232
 - isis retransmit-throttle-interval, 232
 - isis-type, 293
 - knobs, 299
 - log-adjacency-changes, 295–296
 - lsp-max-lifetime, 96
 - lsp-refresh-interval, 96, 181
 - metric-style, 293
 - metric-style narrow, 115
 - metric-style transition, 115
 - metric-style wide, 115
 - no hello padding, 295–296
 - options, enabling, 291
 - passive-interface, 295, 334
 - ping clns, 318–321
 - prc-interval, 190
 - redistribute, 273
 - router isis, 179, 260
 - set-overload-bit, 102
 - sh clns neighbor, 227
 - show as isis database, 95
 - show clns, 240, 303–304
 - output, interpreting, 303–304
 - show clns interface, 300, 306–309, 325
 - output, interpreting, 306–309
 - show clns neighbor, 285, 300
 - show clns neighbors, 283, 305, 324
 - output, interpreting, 305–306
 - show clns neighbors detail, output, 263–264
 - show clns protocol, 262, 304–305
 - output, 263, 304–305
 - show ip interface brief, 334
 - show isis database, 262, 266, 300, 309–310, 338
 - output, 265
 - output, interpreting, 309–310
 - show isis database output, 338
 - show isis database private, 122
 - show isis spf-log, 294, 300
 - output, interpreting, 312
 - show isis topology, 311
 - output, 265
 - output, interpreting, 311
 - show isis-spf-log, 148–149, 312
 - spf-interval, 188–189, 293–294
 - transition, 174
- comparing
 - distance-vector and link-state routing protocols, 16–18
 - IP routing and IP forwarding, 7
 - IS-IS and OSPF, 192
 - adjacency establishment, 205
 - area size, 215
 - commonalities, 197
 - convergence, 213
 - differences, 197–199
 - encapsulation, 200
 - flooding, 206–207
 - hierarchy, 210–212
 - LSA aging, 207
 - metrics, 208–209
 - neighbor discovery, 203–205
 - packet types, 200–203
 - reliability, 209
 - route calculation, 213
 - security, 215
 - terminology, 194–196
 - topology, 209
 - unicast and multicast routing, 18–19

configuring

- authentication, 284–285
 - broadcast multiaccess links, 266
 - exponential backoff, 188
 - example, 190
 - parameters, 189
 - IS-IS over IP tunnels, 283
 - multihomed routers, 78, 80
 - merging areas, 80
 - splitting areas, 80
 - multiple areas, 289
 - NBMA media, 267–268
 - optimized performance, 290–292
 - point-to-point links, 261–266
 - redistribution, 274–278
 - retransmission interval, 130
 - summarization, 278–280
 - unnumbered interfaces, 282–283
- conjectured addresses, 73
- connection models
- multipoint, 225–227
 - point-to-point, 225
 - NBMA networks, 228
- connectionless networks, 6
- connectionless protocols, packets, 42
- control plane, 6
- convergence
- at adjacency setup, 190–192
 - improving, 183
 - IS-IS versus OSPF, 213
 - link failure detection, improving, 184–185
 - LSP generation, improving, 185–186
 - PRCs (partial route computations), 190
 - SPF computation, effect on, 187
- core layer, 158
- corruption storms, troubleshooting, 339
- cost, 111, 143
- CPU process, improving convergence, 183
 - link failure detection, 184–185
 - LSP generation, 185–186
 - SPF computation delay, 187
- CSNPs (complete sequence number packets), 115–118, 130. *See also* PSNPs
 - fields, 116
 - flooding over point-to-point links, 122–123

D

- data communications services
- CLNS, 31–32
 - CLNP, 33
 - ES-IS, 33–34
 - Integrated IS-IS, 35
 - IS-IS, 35
 - IS-IS routing protocol, 34
- data plane, 6
- databases
- LDB, 119–121
 - link-state, update process, 60
 - LSB, stability, 131
 - purging, 132
 - synchronization, 206
 - effect on convergence, 187
- datagrams, 6
- Datalink addresses, 68
- debug isis adj-packets command, 285, 315, 330
- debug isis spf-events command, 316–317
- debug isis update-packets command, 317–318
- debugging commands, 300
- decision process
- Cisco router operation, 148–150
 - RIBs, 60
- default administrative distances, 234
- default gateways, 14
- default metric, 110
- default mode of IIHs, 52
- default-information originate command, 272
- defining unique system IDs, 76–78
- delay metric, 110
- depletion of IP addresses, IPv6, 24–26
- design goals of IS-IS routing protocol, 34–35
- design principles
- access layer, 158
 - core layer, 158
 - distribution layer, 158
 - IP addressing layout, 165–167
 - scalability, 181
 - stability, 182
- destination-based forwarding, 6
- devices
- access layer, 158, 164
 - end systems, 47

host names, mapping to NSAP addresses, 84–85
 loopback addresses, defining as system IDs, 77
 routers, 6

- maintenance problems, troubleshooting, 332–333
- multihoming, 78
- RSPs, 8

 digraphs (directed graphs), 140

- shortest path determination, 143

 Dijkstra’s algorithm, 139–140
 directly connected IP prefixes, advertising, 185
 DIS (designated intermediate system), 266

- election process, 58–59

 disabling

- Level 1 routing capability, 41
- Level 2 routing capability, 41

 displaying

- enabled interfaces on router, 305
- Level 1 routing table, 311
- LSPs, 95
- neighbor statistics, 305–306
- reachability information, 333–334
- SPF process triggers, 148–149

 display-route-detail command, 335, 338
 distance command, 244
 distance-vector routing protocols, 16
 distributed router architecture, 7
 distribution layer, 158

- summarization, 167

 dividing areas, 80
 DNS (Domain Name Service), 6
 domain-password command, 285
 domain-wide authentication, 285
 dotted-decimal notation, 10, 73

- subnet masks, 11–12

 downtime, 236
 DSP (domain specific part), 70
 dual domains, 40
 dual environments, 250–252
 duplicate system IDs, 133
 dynamic host name mapping, 85
 dynamic routing protocols, 14

E

EIGRP (Enhanced Interior Gateway Routing Protocol), 17, 39

election, DISs, 58–59
 enabling

- CLNP forwarding on interfaces, 318
- command options, 291

 encapsulation, IS-IS versus OSPF, 200
 End System Neighbors TLV (Level 1 LSP), 104
 end systems, 47
 Enhanced Interior Gateway Routing Protocol.

- See* EIGRP

 error metric, 110
 errors, logging, 340
 ESHs (end system hellos), 48
 ES-IS (End-System-to-Intermediate System), 33–34
 ES-IS protocol, forming adjacencies, 48
 establishing adjacencies, fast convergence, 190–192
 events, SPF process-related

- logging, 312
- triggers, 313

 examples

- of exponential backoff, 190
- of SPF calculation, 144–146
- of topologies, 301–302

 expense metric, 110
 exponential backoff, 188

- example, 190
- parameters, 189

 Extended IP Reachability TLV, 113–115
 Extended IS Reachability TLV, 113
 external metrics, 111, 273
 external routes, advertising, 335–337

F

fast switching, 22–23
 FIB (forwarding information base), 23
 fields, 347

- LAN hellos, 55
- LSP
 - Attached, 101
 - Checksum, 99, 100, 132
 - IS Type, 102, 103
 - LSP ID, 96, 98
 - Overload, 102
 - Partition, 100
 - Remaining Lifetime, 95

- Sequence Number, 98–99, 132–133
- NSAP addresses, identifying system ID, 76–78
- point-to-point hellos, 52
- TLV
 - RFC 10589, 45
 - RFC 1195, 46
- values, 43
- flag day, 173
 - migrating from old-style metrics to new-style, 222–225
- flat networks versus hierarchical, 160–161
- flooding, 90, 115, 121–122
 - best effort, 124
 - comparing IS-IS and OSPF, 207
 - IS-IS versus OSPF, 206–207
 - on broadcast links, 124–126
 - over NBMA media, 127–128
 - over point-to-point links, 122–123
 - timers, 181–182
- format
 - of IS-IS packets, 43
 - of NSAP addresses, 70–72
 - of point-to-point hello packets, 51
- forming adjacencies
 - ES-IS, 48
 - IS-IS, 49–50
 - IS-IS point-to-point, 51–54
 - Level 1 adjacencies, 57
 - Level 2 adjacencies, 57
 - over multiaccess media, 54–56
 - troubleshooting, 322
- forwarding
 - centralized router architecture, 8
 - CLNP forwarding, enabling on interfaces, 318
 - destination-based, 6
 - distributed router architecture, 7
- Forwarding database, routing table, 61
- Frame Relay
 - multipoint configuration, 269–270
 - multipoint connection model, 226
- FTP (File Transport Protocol), 6
- functional planes, routers, 6

G

- general topology subnetworks, 47
- globally unique NSAP addresses, 73
- GOSIP (Government Open System Interconnection Profile), 71
- graph theory, 140
 - path determination, 141–143

H

- header fields (LSP)
 - Attached, 101
 - Checksum, 99–100, 132
 - IS Type, 102–103
 - LSP ID, 96–98
 - LSPs, 93–95
 - Overload, 102
 - Partition, 100
 - Remaining Lifetime, 95
 - Sequence Number, 98–99, 132–133
- headers, 43
- hello interval, 50
- hello multipliers, 50
- hello packets, 43, 348
 - end system hellos, 48
 - holdtime, 292
 - point-to-point, format, 51
- hellos
 - ES-IS, 34
 - LAN hellos
 - comparing Level 1 and Level 2, 56
 - fields, 55
 - point-to-point, fields, 52
- hierarchical topologies, 160–161
 - areas, 162–164
 - backbone, 161
 - IS-IS versus OSPF, 210–212
- history of IS-IS, 193
- HMAC-MD5 authentication algorithm, 284
- hold-down mechanisms, 140
- Holding Time field (LAN hello), 55
- holdtime, 292
- hop count, reducing, 172

host names, mapping to NSAP addresses
 dynamic mapping, 85
 static mapping, 84

ID Length field, 44
 Identifiers for Organization, 74
 identifying NSAP address system ID, 76–78
 IDI (Initial Domain Identifier), 70
 IDP (initial domain part), 70
 ignore-lsp-errors command, 295–296, 339
 IGP (Interior Gateway Protocols), 16, 39
 classful, migrating to IS-IS, 247–249
 IS-IS, 168
 area limitations, 169
 IP prefix advertisement restrictions, 170
 metric limitations, 169
 migrating to IS-IS, 232
 from EIGRP, 232, 235–245
 troubleshooting, 241
 IGRP (Interior Gateway Routing Protocol), 17
 IIHs, default mode, 52
 implementation requirements (Integrated IS-IS), 40
 Integrated IS-IS, 35
 integrating ISO CLNP and IP, 252
 interaction with BGP, 176
 overload bit, configuring, 178–179
 Interarea Route Leaking, 163
 interarea routes, advertising, 286
 Interdomain Routing Protocol Information TLV, 46
 Level 2, 109
 interdomain routing protocols, 15–16, 39
 interface argument (show clns command), 303
 interfaces
 CLNP forwarding, enabling, 318
 mismatched routing levels, troubleshooting,
 322–323
 MTU size mismatches, troubleshooting,
 327–330
 passwords, assigning, 284
 protocol activity, suppressing, 295
 unnumbered, configuring, 282–283
 Interior Gateway Protocols. *See* IGPs
 Intermediate System Neighbors TLV, 45

intermediate systems, 39
 internal metrics, 111, 273
 international code designator (ICD) addresses, RA
 (Registration Authority), 74
 interpreting
 show clns command output, 303–304
 show clns interface command output, 306–307,
 308–309
 show clns neighbors command output, 305–306
 show clns protocol command output, 304–305
 show command output, 300–302
 show isis database command output, 309–310
 show isis spf-log command output, 312
 show isis topology command output, 311
 Intradomain Routing Protocol Discriminator
 field, 44
 intradomain routing protocols, 15–16
 IOTA (Identifiers for Organizations for
 Telecommunications Addressing), 74
 NSAP addresses, 75
 IP (Internet Protocol)
 dual environment operation, 250–252
 integrating with ISO CLNP, 252
 IP addressing, 9
 classful, 9–10
 classless, 10
 dotted-decimal notation, 10, 73
 link-based, 67
 misconfiguration, troubleshooting, 331–332
 private address space, 11
 structure, 165–166
 subnetting, 11–12
 summarization, 166–167
 VLSM, 12
 IP External Reachability Information TLV, 46
 IP forwarding, 6
 IP Interface Address TLV, 46
 Level 1 LSP, 106–107
 Level 2 LSP, 109
 IP Internal Reachability Information TLV, 46
 Level 1 LSP, 105
 ip router isis command, 260, 333
 IP routing, 5–7
 IPv6, 9, 24–26
 IS Neighbors TLV (LAN hellos), 56
 IS Type field (LSP), 102–103

ISDN (Integrated Services Digital Network),
 multipoint configuration, 270
 IS-IS mesh groups, 127–128
 IS-IS routing engine, subnetwork-independent
 functions, 59
 IS-IS Working Group, 35
 isis circuit-type command, 323
 isis hello-interval command, 292
 isis hello-multiplier command, 292
 isis lsp-interval command, 181–182
 isis metric command, 292
 isis retransmit-interval command, 130, 232
 isis retransmit-throttle-interval command, 232
 isis-type command, 293
 is-neighbors argument (show clns command), 303
 ISO (International Organization for
 Standardization), CLNS, 31–33
 CLNP, 33, 47
 integrating with IP, 252
 DCC addressing, 71
 dual environments, 250–252
 ES-IS, 33–34
 Integrated IS-IS, 35
 network addresses, 67
 ISO 10589, 39
 ISO 8348/AD2, 68
 isolating route installation problems, 337

K–L

knobs, 299

L1 areas, route leaking to L2 areas, 286–288
 LAN hellos
 comparing Level 1 and Level 2, 56
 fields, 55
 LAN ID field (LAN hello), 56
 LAN pseudonodes, 57–59
 Layer 2 addresses, 68
 Layer 2 rewrite string, 19
 layered network design
 core layer, 158
 distribution layer, summarization, 167
 least cost path determination, SPF algorithm, 143
 Length field, 45
 Length Indicator field, 44

Level 1 adjacencies, forming, 57
 Level 1 LSPs
 ATT bit setting, verifying, 310
 TLVs, 103–104
 Area Address, 104
 Authentication Information, 105
 End System Neighbors, 104
 IP Interface Address, 106–107
 IP Internal Reachability Information, 105
 Protocols Supported, 105

Level 1 routers, 41
 Level 1 routing table, displaying, 311
 level-1 option (isis-type command), 293
 level-1-2 option (isis-type command), 293
 level-2-only option (isis-type command), 293
 Level 1-2 routers, 41, 90
 Level 2 adjacencies, forming, 57
 Level 2 backbone, 41
 Level 2 LSPs
 TLVs
 Interdomain Routing Protocol
 Information, 109
 IP Interface Address, 109
 Partition-Designated Level 2 Intermediate
 System, 108
 Prefix Neighbors, 108

Level 2 routers, 41
 limitations
 of IPv4, 24–25
 of IS-IS as IGP
 area limitations, 169
 IP prefix advertisement restrictions, 170
 metric limitations, 169

link-based IP addressing, 67
 link-state database, 140
 listing known LSPs, 309, 310
 lookup, troubleshooting, 332–339
 LSPs, 95
 synchronization, 116, 119–120
 SRM flag, 121
 SSN flag, 121
 update process, 60
 link-state packets, 43, 353
 link-state routing protocols, 16
 migrating to IS-IS, 245
 OSPF, 140
 comparing to IS-IS, 192–215

- SPF process, debugging, 316–317
- troubleshooting, 299
- log-adjacency-changes command, 295–296
- logging
 - errors, 340
 - SPF process events, 312
- longest match routing, 21
- lookup mechanism
 - discontiguous Level 2 subdomains, troubleshooting, 339
 - LSP corruption storms, troubleshooting, 339
 - route advertisement, troubleshooting, 333–337
 - route installation, troubleshooting, 337–338
 - troubleshooting, 332
- loop prevention, hold-down mechanisms, 140
- loopback addresses, defining as system IDs, 77
- LSA aging
 - comparing IS-IS and OSPF, 208
 - IS-IS versus OSPF, 207
- LSB
 - purging, 132
 - stability, 131
- LSP corruption storms, 132
 - troubleshooting, 339
- LSP Entries TLV, 45
- LSP ID field (LSP), 96–98
- lsp-max-lifetime command, 96
- lsp-refresh-interval command, 96, 181
- LSPs
 - Attached field, 101
 - checksum, 132
 - checksum errors, 241
 - Checksum field, 99–100, 132
 - Extended IP Reachability TLV, 113–115
 - Extended IS Reachability TLV, 113
 - flooding, 115, 121–122
 - over NBMA media, 127–128
 - on broadcast links, 124–126
 - over point-to-point links, 122–123
 - pseudonodes, 57–59
 - generation interval, 130
 - header fields, 93–95
 - holdtime, maxage timer, 129
 - IS Type field, 102–103

Level 1

- Area Address TLV, 104
- Authentication Information TLV, 105
- End System Neighbors TLV, 104
- IP Interface Address TLV, 106–107
- Protocols Supported TLV, 105
- TLVs, 103, 104

Level 2

- Interdomain Routing Protocol Information TLV, 109
- IP Interface Address TLV, 109
- IP Internal Reachability Information TLV, 105
- Partition-Designated Level 2 Intermediate System TLV, 108
- Prefix Neighbors TLV, 108

LSP ID field, 96–98

Overload field, 102

packet corruption storms, 295

Partition field, 100

purging, 295

Remaining Lifetime field, 95

Sequence Number field, 98–99, 132–133

timers

- modifying, 231

- refresh interval timer, 181

TLVs, 95

verifying in Link-State database, 309–310

viewing, 95

LSPs (link-state packets), 140

M

MAC addresses, identifying as NSAP address System ID, 76–78

mapping NSAP addresses to host names, 84

- dynamic mapping, 85

- static mapping, 84

matching routes, longest match routing, 21

maxage timer, 129

Maximum Area Addresses field, 44

memory requirements, SPF algorithm, 144

merging areas, 80

mesh groups, 127–128, 228–229, 267

- metrics, 111–112, 143
 - assigning, 172
 - cost, 111
 - Extended IP Reachability TLV, 113–115
 - Extended IS Reachability TLV, 113
 - external, 273
 - internal, 273
 - IS-IS versus OSPF, 208–209
 - narrow, 171
 - migrating to wide, 173–174, 222–225
 - scalar link costs, 143
 - wide, 171
- metric-style command, 293
- metric-style narrow command, 115
- metric-style transition command, 115
- metric-style wide command, 115
- migration strategies, 232
 - classful IGP to IS-IS, 246–247
 - from classful IGPs, 247
 - RIP, 247–249
 - from EIGRP, 232
 - phases of migration, 237–245
 - timer configuration, 235
 - verifying operation, 236
 - narrow metrics to wide, 173–174, 222–225
 - OSPF to IS-IS, 245–246
- minimum LSP transmission interval, 130
- misconfiguration
 - of IP addresses, troubleshooting, 331–332
 - of NSAPs, troubleshooting, 324–325
- mismatched interface MTUs, troubleshooting, 327–330
- mismatched routing levels, troubleshooting, 322–323
- modifying LSP timers, 231
- MPLS (Multiprotocol Label Switching), 170
- MTU size. troubleshooting mismatches across interfaces, 327–330
- multiaccess media, forming adjacencies, 54–56
- multi-area configuration, 289
- multicast routing, 18
 - OIF, 19
 - RPF, 19
- multihoming, router configuration, 78–80
 - merging areas, 80
 - splitting areas, 80

- multipoint configuration
 - Frame Relay, 269
 - ISDN, 270
- multipoint connection model, 225–227
- multipoint mode over NBMA networks, 47

N

- narrow metrics, 171
 - migrating to wide, 173–174, 222–225
- narrow option (metric-style command), 293
- NAT (Network Address Translation), 9
- NBMA (nonbroadcast multiaccess)
 - ATM configuration, 267–268
 - IS-IS implementation, multipoint mode, 47
 - LSPs
 - flooding, 127–128
 - timers, 231
 - mesh groups, 228–229
 - multipoint connection model, 225–228
 - point-to-point connection model, 228
 - point-to-point links, 267
- neighbors
 - discovery, IS-IS versus OSPF, 203–205
 - statistics, displaying, 305–306
- neighbors argument (show clns command), 303
- NETs (network entity titles), 41, 62, 69, 82
 - multihomed router configuration, 78–80
 - merging areas, 80
 - splitting areas, 80
- NetWare Link Services Protocol (NLSP), 39
- network addresses, ISO, 67
 - IP addressing structure, 165–166
 - summarization, 166–167
- network models
 - multipoint, 225–227
 - point-to-point, 225–228
- new-style TLVs, 171
- NIST (United States National Institute of Standards), 74
- NLSP (NetWare Link Services Protocol), 39
- no hello padding command, 295
- node-based addressing, 61, 67
 - Area ID, 40
 - NET (network entity title), 41
 - NSAPs, 67

- n-selector, 40
- SysID, 40
- nodes
 - adjacencies
 - forming, 49, 50
 - over multiaccess media, forming, 54–56
 - point-to-point adjacencies, forming, 51–54
 - subnetwork dependent functions, 47
- no-hello padding command, 295–296
- nonhierarchical network design, 174–175
- Not Specified TLV, 45
- NSAP addresses, 67
 - Area ID, 69
 - Area ID field, 72
 - fields, 72
 - format, 70
 - globally unique, 73
 - IOTA-based, 75
 - mapping to host names
 - dynamic mapping, 85
 - static mapping, 84
 - misconfiguration, troubleshooting, 324–325
 - NET (Network Entity Title), 69
 - NSEL values, 82
 - OSI network addresses, 69
 - OSI NSAP addressing, 68
 - registration authorities, 74, 75
 - renumbering, 80
 - simplified format, 72
 - Area ID field, 73
 - statistics, displaying, 303
 - system ID, identifying, 69, 76, 78
 - System ID field, 72
 - top-level domains, 71
- NSEL (NSAP selector), 69, 82
- N-selector, 40
- NSFNet, history of IS-IS, 193

O

- OIF (outgoing interface list), 19
- old-style TLVs, 171
 - combining with new-style TLVs, 172
 - migrating to, 173–174
 - migrating to new-style, 222–225
- one-way communication between adjacencies, 57

- Open Shortest Path First. *See* OSPF
- optimizing performance, 290–292
- options
 - enabling for Cisco IOS commands, 291
 - metric-style command, 293
- OSI network addresses, 69
- OSI NSAP addressing scheme, 68
- OSPF (Open Shortest Path First), 18, 39, 140, 194
 - comparing to IS-IS, 192
 - adjacency establishment, 205
 - area size, 215
 - commonalities, 197
 - convergence, 213
 - differences, 197–199
 - encapsulation, 200
 - flooding, 206–207
 - hierarchy, 210–212
 - LSA aging, 207
 - metrics, 208–209
 - neighbor discovery, 203–205
 - packet types, 200–203
 - reliability, 209
 - route calculation, 213
 - security, 215
 - terminology, 194–196
 - topology, 209
 - migrating to IS-IS, 245–246
 - SPF process. debugging, 316–317
- output of commands, interpreting
 - show clns command, 303–304
 - show clns interface command, 306–309
 - show clns neighbors command, 305–306
 - show clns protocol command, 304–305
 - show commands, 300–302
 - show isis database command, 309–310
 - show isis spf-log command, 312
 - show isis topology command, 311
- overload bit, configuring, 178–179
- Overload field (LSP), 102

P

- packet processors, 8
- packets, 6, 42
 - authentication, 62
 - black-holing, 176–179

- configuration information (ES-IS), 34
- CSNPs (complete sequence number packets), 116–118
- fields, 347
 - TLV, 45–46
 - values, 43
- format, 43
- headers, 43
- hello packets, 43, 348
 - end system hellos, 48
 - hello interval, 50
 - holdtime, 292
- IS-IS versus OSPF, 20–203
- LAN hello packets, fields, 55
- link-state, 43, 353
- LSPs, 140
 - Area Address TLV, 104
 - Attached field, 101
 - Authentication Information TLV, 105
 - Checksum field, 99–100, 132
 - End System Neighbors TLV, 104
 - flooding, 115, 121–128
 - header fields, 93–95
 - Interdomain Routing Protocol Information TLV, 109
 - IP Interface Address TLV, 106–109
 - IP Internal Reachability Information TLV, 105
 - IS Type field, 102–103
 - LSP ID field, 96–98
 - Overload field, 102
 - packet corruption storms, 295
 - Partition field, 100
 - Partition-Designated Level 2 Intermediate System TLV, 108
 - Prefix Neighbors TLV, 108
 - Protocols Supported TLV, 105
 - Remaining Lifetime field, 95
 - Sequence Number field, 98–99, 132–133
 - TLVs, 95, 103–104
 - viewing, 95
- PSNPs (partial sequence number packets), 118
- RD (route redirection), 34
- sequence number, 43, 358
 - debugging, 317–318
 - SNPs (sequence number packets), 115
 - TLV fields, 45
- Padding TLV, 45, 52, 56
- parameters for exponential backoff, 189
- Partition Designated Level 2 Intermediate System TLV, 45
- Partition field (LSP), 100
- Partition-Designated Level 2 TLV, 108
- passive-interface command, 295, 334
- passwords
 - assigning to interfaces, 284
 - authentication, 62, 340
 - configuring, 284–285
- path determination
 - longest match routing, 21
 - SPF algorithm, 139
 - computational complexity, calculating, 143
 - example calculation, 144–146
 - graph theory, 140–143
 - IS-IS routes, calculating, 147–148
 - memory requirements, 144
 - operation on Cisco routers, 148–150
 - shortest path tree, building, 147–148
 - versus Bellman-Ford algorithm, 140
- PDU (protocol data units), 42
 - Length field (LAN hello), 56
 - PDU Type field, 44
- performance, optimizing, 290–292
- phased migration, EIGRP to IS-IS, 237–245
- ping clns command, 318–321
- point-to-point adjacencies, forming, 51–54
- point-to-point connection model, 225
 - ATM configuration, 268
 - LSPs, flooding, 121–123
 - NBMA networks, 228
 - serial link configuration, 261–266
- point-to-point hellos, fields, 52
- point-to-point interfaces, show clns interface command output, 308–309
- POS (Packet Over Sonet), 225
- PRC (partial route calculation), 147, 190
- pre-interval command, 190
- Prefix Neighbors TLV, 45
 - Level 2, 108

- principles of network design
 - access layer, 158
 - core layer, 158
 - distribution layer, 158
 - IP addressing layout, 165
 - scalability, 181
 - stability, 182
- Priority field (LAN hello), 56
- private address space, 11
- process switching, 22
- propagation of LSPs, improving convergence, 185–186
- protocol activity, suppressing over specific interfaces, 295
- protocol argument (show clns command), 303
- Protocols Supported TLV (Level 1 LSP), 46, 105
- PRT (public routing topology), 25
- pseudonode
- pseudonode LSPs, 54–59, 97
- PSNPs (partial sequence number packets), 115, 118
- purging
 - LSB, 132
 - LSPs, 295

R

- RA (Registration Authority), ICD addresses, 74
- RD (route redirection) packets, 34
- reachability information, displaying, 333–334
- redistribute command, 273–276
- redistribution, 273
 - configuring, 274–278
 - migration from EIGRP to IS-IS, 233
 - static routes, 273
- reducing hop count, 172
- refresh interval, 96
- registration authorities, NSAP addresses, 74–75
- reliability, IS-IS versus OSPF, 209
- Remaining Lifetime field (LSP), 95
- remaining lifetime timer, 181
- renumbering NSAP addresses, 80
- representation of IPv6 addresses, 26
- Reserved field, 44
- restrictions on multi-area router support, 289
- retransmission interval, 123
 - configuring, 130
- RFC 10589 TLVs, 45
- RFC 1195 TLVs, 46
- RFC 941, NSAP addresses, 68
- RIB (routing information base), 7
 - decision process, 60
 - Forwarding database, routing table, 61
 - Link-State database, update process, 60
- RIP (Routing Information Protocol), 39
 - RIPv1, 17
 - RIPv2, 17
- route argument (show clns command), 303
- route calculation, IS-IS versus OSPF, 213
- route flaps, troubleshooting, 338
- route leaking, 271, 286
 - L1 areas to L2, 286–288
- route processors, 7
- route redistribution, 273
- route summarization, configuring, 278–280
- router isis command, 179, 260
- routers, 6
 - adjacencies
 - formation of, troubleshooting, 322
 - problems, debugging, 315
 - centralized architecture, 8
 - debugging command, 300
 - distributed architecture, 7
 - Level 1, 41
 - Level 1-2, 41
 - Level 2, 41
 - LSPs, purging, 295
 - maintenance, troubleshooting, 332–333
 - multi-area support, configuring, 289
 - multihoming, 78
 - configuring, 78–80
 - RSPs, 8
- routes, PRC (partial route calculation), 147
- routing domains, 40. *See also* areas
 - areas, 40
 - addressing scheme, 41
 - Level 1 routers, 41
 - Level 2 adjacencies, 53
 - dual domains, 40
- routing engine, 7
- Routing Information Protocol. *See* RIP

- routing layer functions, 46
 - subnetwork-dependent, 47
 - adjacencies, maintaining, 48
 - broadcast subnetworks, 47
 - general topology subnetworks, 47
 - routing between nodes, 47
 - subnetwork-independent, 46, 59
- routing protocols, 5
 - administrative distance, 61
 - classful versus classless, 14
 - classification, 14
 - default administrative distance, 234
 - distance-vector versus link-state, 16
 - EIGRP, 39
 - intradomain versus interdomain, 15, 16
 - link-state, troubleshooting, 299
 - metrics, 111–112
 - cost, 111
 - migrating, 222–225
 - narrow, 171
 - scalar link costs, 143
 - wide, 171
 - OSPF, 39
 - comparing to IS-IS, 192–215
 - RIP, 39
 - ships in the night, 39
 - SPF algorithm
 - computational complexity,
 - calculating, 143
 - example calculation, 144–146
 - graph theory, 140–143
 - IS-IS routes, calculating, 147–148
 - memory requirements, 144
 - operation on Cisco routers, 148–150
 - shortest path tree, building, 147–148
 - versus Bellman-Ford algorithm, 140
- routing tables, 7
- RPF (reverse path forwarding), 19
- RRR (Routing with Resource Reservation), 305
- RSPs (route switch processors), 8
- scalar link costs, 143
- security
 - authentication, 53, 62
 - comparing IS-IS and OSPF, 215
 - configuring, 284–285
 - troubleshooting, 340
 - HMAC-MD5 authentication algorithm, 284
 - IS-IS versus OSPF, 215
 - selecting backbone, 247
 - selective interface blocking, 231
 - Sequence Number field (LSP), 98–99, 132–133
 - sequence number packets, 43, 358
 - debugging, 317–318
 - SequenceModulus, 98
 - set-overload-bit command, 102
 - sh clns neighbor command, 227
 - ships in the night, 39
 - shortage of IP addresses, IPv6, 24–26
 - shortest path tree, building, 147–148
 - show as isis database command, 95
 - show clns command, 303–304
 - show clns interface command, 300, 306–309, 325
 - output, interpreting, 306–309
 - show clns neighbor command, 285, 300
 - show clns neighbors command, 283, 305, 324
 - output, interpreting, 305–306
 - show clns neighbors detail command, output, 263–264
 - show clns protocol command, 240, 262–263, 304–305
 - show commands, 300–302
 - show ip interface brief command, 334
 - show isis database command, 262, 266, 272, 300, 309–310, 338
 - output, interpreting, 265, 309–310
 - show isis database output command, 338
 - show isis database private command, 122
 - show isis spf-log command, 294, 300, 312
 - output, interpreting, 312
 - show isis topology command, 311
 - output, 265
 - output, interpreting, 311
 - show isis-spf-log command, 148–149
 - simplified NSAP format, 72
 - Area ID field, 73

S

- scalability, 181
 - NBMA networks, mesh groups, 228–229

SNPAs (subnetwork points of attachment), 48, 68

SNPs (sequence number packets), 115

- CSNPs, 116–118
- PSNPs, 118

Source ID field (LAN hello), 55

specifying interval between SPF calculation events, 293–294

SPF (shortest path first) algorithm, 139

SPF algorithm, 139

- computational complexity, calculating, 143
- debugging, 316–317
- events, logging, 312
- example calculation, 144–146
- graph theory, 140–143
- IS-IS routes, calculating, 147–148
- memory requirements, 144
- operation on Cisco routers, 148–150
- shortest path tree, building, 147–148
- triggers, 313
 - viewing, 148–149
- versus Bellman-Ford algorithm, 140

spf-interval command, 188–189, 293–294

splitting areas, 80

SRM (Send Routing Message) flag, 121

SSN (Send Sequence Number) flag, 121

stability, 182

- of LSB, 131

standardization, IS-IS Working Group, 35

static host name mapping, 84

static routes, 14

- redistribution, 273

subcategories of IS-IS packets, 43

subinterfaces, mesh groups, 228–229

subnet masks, 11–12

subnets, 11–12

- advertising, 333–334
- broadcast, 47
- general topology, 47
- misconfiguration, troubleshooting, 331–332

subnetwork points of attachment (SNPAs), 68

subnetwork-dependent functions, 46–47

- adjacencies, maintaining, 48
- broadcast subnetworks, 47
- general topology subnetworks, 47
- routing between nodes, 47

subnetwork-independent functions, 46, 59

summarization, configuring, 278–280

suppressing protocol activity over specific interfaces, 295

switching mechanisms

- CEF, 23–24
- fast switching, 23
- process switching, 22

synchronization, 177–178

- effect on convergence, 187
- LDB, 119, 120
 - SRM flag, 121
 - SSN flag, 121

SysID (system identifier), 40, 69

- NSAP addresses, identifying, 76–78

System ID field (NSAP addresses), 72

T

TAC (Technical Assistance Center), expediting troubleshooting issues, 299

TCP/IP (Transmission Control Protocol/Internet Protocol), IP suite, 5–6

Telnet, 6

terminology, comparing OSPF and IS-IS, 194–196

TFTP (Trivial File Transport Protocol), 6

three-layer model

- access layer, 158
- core layer, 158
- distribution layer, summarization, 167

timers

- CSNP interval, 130
- LSP generation interval, 130
- maxage, 129

TLVs (type, length, and value), 43–45, 95, 103–104

- Area Address, 104
- combining old- and new -style, 172
- Extended IP Reachability TLV, 113–115
- Extended IS Reachability TLV, 113
- Interdomain Routing Protocol Information, 109
- IP Interface Address (Level 1 LSP), 106–109
- Level 1 LSPs
 - Authentication Information, 105
 - End System Neighbors, 104
 - IP Internal Reachability Information, 105
 - Protocols Supported, 105

- new-style, 171
- old-style, 171
 - migrating to new, 222–225
- Partition-Designated Level 2 Intermediate System, 108
- Prefix Neighbors, 108
- RFC 10589, 45
- RFC 1195, 46
 - Type 1-2, Traffic Engineering Router ID, 112
- top-level domains, NSAP addresses, 71
- topologies
 - convergence, 190–192
 - hierarchical, 160–161
 - areas, 162, 163–164
 - backbone, 161
- topology
 - convergence, improving, 183–187
 - IS-IS versus OSPF, 209
 - least cost, 146
- traffic, assigning metrics, 172
- traffic argument (show clns command), 303
- Traffic Engineering ID TLV, 112
- transition command, 174
- transition option (metric-style command), 293
- transition schemes, 232
 - from classful IGPs, 247
 - IGRP, 249
 - RIP, 247–249
 - from EIGRP, 232
 - phases, 237–245
 - timers, 235
 - verifying, 236
 - from narrow to wide metrics, 224–225
- triggers for SPF process events, 313
- troubleshooting, 340
 - adjacency formation, 322
 - areas, duplicate system IDs, 326
 - authentication problems, 340
 - IGPs, 241
 - IP addresses, misconfiguration, 331–332
 - lookup mechanism, 332
 - discontiguous Level 2 subdomains, 339
 - LSP corruption storms, 339
 - route advertisement problems, 333–337
 - route installation problems, 337–338
 - LSP corruption storms, 339
 - NSAP misconfiguration, 324–325

- route flaps, 338
- router maintenance problems, 332–333
- unstable routes, 338
- tunnel configuration, 283
- Type field, 45

U

- unicast routing, 18–19
- unique system IDs, defining, 76–78
- unnumbered interfaces, configuring, 282–283
- unstable links, effect on convergence, 184–185
- unstable routes, troubleshooting, 338
- update process (Link-State database), 60
 - operation on Cisco routers, 148–150
- updates, debugging, 317–318

V

- Value field, 45
- verifying ATT bit setting, 310
- Version field, 44
- Version/Protocol ID Extension field, 44
- viewing
 - enabled interfaces on router, 305
 - LSPs, 95
 - neighbor statistics, 305–306
 - SPF process triggers, 148–149
- VIPs (versatile interface processors), 8, 23
- virtual adjacencies, 100
- virtual nodes, pseudonodes, 57–59
- VLSM (Variable-Length Subnet Masking), 12

W-Z

- WANs, multipoint connection model, 226
- wide metrics, 171
- wide option (metric-style command), 293

- ZeroAgeLifetime, 96