



Symbols

μ-law, 59

Numerics

10-high-day (10HD) busy period, 416
 1750 series routers, 91
 2600 series routers, 92–94
 configuring, 147–148
 digital T1/E1 packet voice trunk, 103–104
 PVDM, 103
 VICs, 102
 voice/fax network module, 101–102
 3600 series routers, 95
 Cisco 3620 modular access routers, 95
 Cisco 3640 modular access routers, 95
 Cisco 3660 modular access routers, 95
 configuring, 148, 150–151
 digital T1/E1 packet voice trunk, 103–104
 hardware, verifying installation, 156
 PVDM, 103
 VICs, 102
 port addressing, 155
 selecting, 154–155
 VNMs
 assembly, 155
 selecting, 152
 voice/fax network module, 101–102
 7200 series routers, 112–114
 7500 series routers, 114, 117

A

A bit, 73
 ABBH (average bounding busy hour), 416
 ABCD bit pattern, 74
 robbed bit format, 76
 trunk configuration, 237–239
 ABR (available bit rate), 308
 access codes, 124
 access gateways, 375

access layer, 9
 in new-world networks, 18
 access numbers, pilot number, 374
 access servers, AS5300, 107
 DSP module, 170
 DSP module, selecting, 172
 feature card module, 170
 feature cards, selecting, 171–172
 MICA (modem ISDN channel aggregation), 170
 setting up, 168
 ACD, 421–422
 adaptive differential pulse code modulation (ADPCM), 431
 adding string description to voice ports, 185
 address signaling, 36, 417
 Ad-Hoc conferences, 391
 adjunct control PBXs, 406
 adjusting
 voice port timing parameters, 212–213
 voice quality, 203
 admission control, 349
 CCM, 381–383
 ADPCM (adaptive differential pulse code modulation), 431
 advanced router systems (ARSs), Cisco 7500 series, 114, 117
 A-law, 59
 alert signaling, 418
 alerting indicators, 38
 allocation of bandwidth in voice networks, 381–383
 analog signaling
 coding, 61
 delay-start, 35
 digitization
 compression, 61–64
 encoding process, 60–61
 quantization process, 58–60
 sampling, 56–57
 immediate-start, 36
 supervisory, 28
 wink-start, 34–35
 analog technologies
 access gateways, 375
 E&M signaling

- Type I lines, 42–43
- Type II lines, 43
- Type III lines, 44
- Type IV lines, 44
- Type V lines, 46
- hybrid 2-to 4-wire conversion, balanced, 49
- telephones
 - dialer, 27
 - glare, 30
 - handset, 26
 - hybrid 2- to 4-wire converter, 27
 - placing a call, 23–26
 - power supply, 40
 - ringer, 27
 - sidetone, 27
 - switch hook, 27
- trunks, 46–47
 - CO trunks, 47
 - DID/DOD trunks, 48
 - FXO trunks, 47–48
 - FXS, 48
 - private trunk lines, 47
 - telco trunks, 48
- voice-grade channels, bandwidth, 56
- voice networks, 6
 - cable connections, configuring on
 - MC3810, 166–167
 - echo, 49–50
 - voice ports, configuring, 182–183
- applications
 - FXS, 129
 - gatekeepers, 133–134
 - IP Phone, 130
 - MCM (Multimedia Conference Manager), 133–134, 139
- applying QoS policies to VoFR, 264–265
- architecture
 - ATM, requirements of, 308
 - DVMs (digital voice modules), 160–161
 - ISDN, 81
 - PBXs, 408, 410–414
 - line interfaces, 412
 - main system controller, 410
 - trunk interfaces, 413
 - wiring, 413–414
- Architecture for Voice, Video and Integrated Data.
See AVVID
- ARS (advanced router systems), Cisco 7500 series, 114, 117
- AS5300s
 - DSP module, selecting, 172
 - feature cards, selecting, 170–172
 - MICA (modem ISDN channel aggregation), 170
 - setting up, 168
- assembling VNM/VIC for 3600 routers, 155
- assigning DLCIs to Frame Relay subinterfaces, 270–271
- ATM (Asynchronous Transfer Mode)
 - architectural requirements, 308
 - bandwidth, calculating, 312
 - configuration commands
 - dial-peer voice voatm, 324
 - encapsulation, 320
 - inarp parameter, 325
 - interface atm, 319
 - mode, 316, 318–319
 - pvc name, 319
 - session target, 324
 - vbr-rt, 322
 - MC3810 fixed prioritization, 314–316
 - MFT (Multiflex Trunk), 311
 - PVCs, virtual template parameters, 321
 - SAR, 309
 - service classes, 308–309
 - minimizing delay, 310
 - non-real time, 314, 316
 - real time, 314–315
 - traffic shaping, 312
 - for data/video, 314
- atm pvc command, 326
- auditing network inventory, 428–429
 - global firms, 440
 - multinational firms, 463
 - pan-European firms, 449
- auto-cut-through command, 191–192
- automated attendant, 421
- available bit rate (ABR), 308
- availability on old-world telephony systems, 390
- average bounding busy hour (ABBH), 416
- average options for voice traffic, calculating, 323–324

AVVID (Architecture for Voice, Video and Integrated Data), 14–16

- access gateways, 375
- components of, 372
 - access gateways, 375
 - CallManager, 373
 - Cisco IP Phones, 375
 - uOne, 374
- hardware
 - Cisco conference bridges, 391–392
 - Cisco WebAttendant, 392
 - gateways, 386–387, 389
 - IP Phone, 384–385
 - media convergence servers, 389–390
- IP protocols
 - DHCP, 376
 - H.323, 377
 - MGCP, 378–379
 - SCCP, 379
 - TFTP, 376
- signaling, 380

B

B8ZS (Bipolar with Eight-Zero Substitution Return-to-Zero), 77

backplane (PBXs), 411

balanced hybrid 2- to 4-wire conversion, 49

bandwidth

- allocating, 309, 381–383
- ATM, calculating, 312
- calculating for voice calls, 359–360
- conservation techniques, digital speech interpolation, 65
- managing, 349
- reserving, 344
 - on DLCIs, 275
- voice-grade analog channels, 56

baselining input/output power levels, 205

BC (Basic Call) sublayer, QSIG, 419

Bc (committed burst size), configuring, 281

Be (excess burst), configuring, 281

BECN (backward explicit congestion notification), 260

BHCA (busy hour call attempts), 416

Bipolar Alternate Mark Inversion Return-to-Zero, 77

bipolar violation (BPV), 77

Bipolar with Eight-Zero Substitution Return-to-zero (B8ZS), 77

BPV (bipolar violation), 77

break segment, 36

building blocks of IP voice installations

- backbone speed and scale, 349
- bandwidth management/admission control, 349
- congestion management, 350
- packet classification, 349
- queue management, 350

burst options for voice traffic, calculating, 323–324

business level telephone voice quality, 66

busy hour call attempts (BHCA), 416

busy hour call handling, PBXs, 415–416

busy signal, 38

BVM (BRI voice module)

- configuring on MC3810, 163–164
- specifying as clock source, 164

C

cabinet carriers, PBX systems, 411–412

cabinet/shelf controller, PBX systems, 409

cablelength long command, 216

cablelength short command, 216

cabling

- analog voice connections (MC3810), 166–167
- PBX systems, 413–414

calculating

- average options for voice traffic, 323–324
- bandwidth
 - ATM, 312
 - for voice calls, 359–360
- burst options for voice traffic, 323–324
- busy-hour call handling, 416
- centum call seconds, 416
- decibel levels, 205
- delay budget, 435, 437–438
- erlangs, 416
- fragmentation size, 268–269
- payback period of capital investments, 460–461
- peak options for voice traffic, 323–324

call detail recording (CDR), 421

call legs, 181

- call progress indicators, 38
 - call progress tone, voice port configuration, 185
 - call setup (VoFR), displaying information, 301–302
 - CallManager, 373
 - admission control, 381–383
 - callout, PBX systems, 416–417
 - calls
 - analog, placing, 23–26
 - VoIP, 345
 - capacitors, 27
 - capacity planning
 - for voice traffic, 416–417
 - integrated voice/data networks, 438–439
 - global firms, 445
 - multinational firms, 468–470
 - pan-European firms, 453, 456–458
 - capital investments, calculating payback period, 460–461
 - carriers (PBX systems), 411–412
 - CAS (channel-associated signaling), 79, 317, 417
 - case studies, network design, 440
 - global firms, 440–448
 - multinational firms, 462–471
 - pan-European firms, 449–461
 - Catalyst 6000 Voice T1 module, 388
 - CBR (constant bit rate), 308
 - CBWFQ (class-based weighed fair queuing), 354–355
 - ccfrf11 function calls, displaying, 297, 299
 - CCM (Cisco CallManager), admission control, 381–383
 - CCS (common channel signaling), 80, 317, 418–419
 - ccs connect command, 217
 - ccsvoice function calls, displaying, 299–300
 - CDR (call detail recording), 421
 - cells (ATM), SAR, 309
 - CELP (code excited linear predictive) coding, 63
 - centralized control PBXs, 403
 - centum call seconds, 416
 - channel banks, drop-and-insert, 12
 - characteristics
 - of access layer, 9
 - of distribution layer, 10
 - Chord, 60
 - CIPT (Cisco IP Telephony Solutions), 373
 - CIR (committed information rate), 260
 - configuring on PVC/SVC, 280
 - circuits, local loop, 28–32, 39
 - circuit-switching, 13, 414
 - Cisco 1750 series routers, 91
 - Cisco 2600 series routers, 92–94
 - configuring, 147–148
 - digital T1/E1 packet voice trunk, 103–104
 - PVDM (Packet Voice DSP Module), 103
 - VICs, 102
 - voice/fax network module, 101–102
 - Cisco 3600 series routers, 95
 - Cisco 3620 modular access routers, 95
 - Cisco 3640 modular access routers, 95
 - Cisco 3660 modular access routers, 95
 - configuring, 148, 150–151
 - digital T1/E1 packet voice trunk, 103–104
 - hardware, verifying installation, 156
 - PVDM (Packet Voice DSP Module), 103
 - VICs, 102
 - assembly, 155
 - port addressing, 155
 - selecting, 154–155
 - VNMs
 - assembly, 155
 - selecting, 152
 - voice/fax network module, 101–102
- Cisco 7200 series routers, 112–114
- Cisco 7500 series routers, 114, 117
- Cisco AS5300 routers, 107
 - feature cards, selecting, 171–172
- Cisco AS5800 routers, 110–112
- Cisco conference bridges, AVVID, 391–392
- Cisco IP Phones, 375. *See also* IP Phones
 - model 7910, 384
 - model 7960, 385
- Cisco MC3810 router, 105–107
- Cisco MCM (Multimedia Conference Manager), , 107, 133–134, 139
- Cisco MCS-7822, 389
- Cisco MCS-7835, 390
- Cisco VG200 VoIP gateway, 387–388

- Cisco voice-over routers
 - connection types
 - local, 123
 - off-net, 124
 - on-net, 123
 - on-to off-net, 126
 - PLAR, 124
 - tie-line, 125
 - trunk calls, configuring, 286–287
- Cisco WebAttendant for AVVID, 392
- Cisco Works Voice Manager, 134
- Cisco's VoFR implementation, 262–264
- Cisco's VoIP implementation, 347
- class command, 271
- classes of service (ATM), 308–309
 - minimizing delay, 310
- classification schemes (packets), 349
- CLECs (competitive local exchange carriers), 7
- client/server-based PBXs, 407–408
- clock source command, 215
- clocking, T1 connections, 76–77
- clustering technology, Cisco CallManager, 390
- CO (central office), 6
 - local loop, 28–32
 - switches, 40–41
 - trunks, 47
- codec command, 192
- codec complexity command, 240
- codecs (coder-decoders), 56
 - compression types, 193–194
- coding, 61, 431
- coloring, 265
- combining voice and data traffic, 16–18, 131
- comfort noise, 65
- commands
 - atm pvc, 326
 - auto-cut-through, 191–192
 - cablelength long, 216
 - ccs connect, 217
 - class, 271
 - clock source, 215
 - codec, 192
 - codec complexity, 240
 - compand-type, 195
 - connection, 197
 - connection tie-line, 201
 - connection trunk, 202–203
 - controller, 215
 - cptone, 185
 - debug, 248, 331, 363
 - debug cccrf11 session, 297, 299
 - debug ccswwvoice vofr-debug, 299
 - debug ccswwvoice vofr-session, 299
 - debug frame-relay fragment, 300–301
 - debug voice vofr, 301–302
 - description, 185, 216
 - destination-pattern, 224, 230
 - dial-peer voice, 224, 229–230
 - dial-peer voice voatm, 324
 - dial-type, 187
 - ds0-group timeslots type, 218–220
 - echo cancel coverage, 209
 - echo-cancel enable, 208
 - encapsulation, 320
 - encapsulation frame-relay, 270
 - forward digits, 228
 - frame-relay adaptive-shaping, 281
 - frame-relay bc, 281
 - frame-relay be, 281
 - frame-relay cir, 280
 - frame-relay fair-queue, 278–279
 - frame-relay fragment, 279–280
 - frame-relay interface dlci, 270–271
 - frame-relay mincir, 280
 - frame-relay traffic-shaping, 274
 - frame-relay voice bandwidth, 275
 - framing, 216
 - impedance, 208, 211
 - input gain, 206, 215
 - interface atm, 319
 - linecode, 216–217
 - loopback, 234
 - loop-timed, 216
 - loss plan, 206
 - loss-plan, 210
 - map-class frame-relay, 275
 - mode, 316, 318–319
 - mode cas, 317
 - mode ccs, 218
 - network-clock-select, 164
 - non-linear, 209
 - num-exp, 226
 - operation, 189
 - output attenuation, 206, 215

- port, 225–226
- prefix, 228
- pvc name, 319
- ring frequency, 187
- ring number, 186
- session target, 231–234, 324
- show, 246–247, 329, 363
- show atm pvc, 329
- show dial-peer voice, 243
- show frame-relay fragment, 294–295, 297
- show frame-relay vofr, 292–293
- show interface, 330
- show running-config, 245
- show voice port, 245
- shutdown, 185
- signal, 185, 189
- signal pattern, 237
- signal-type, 235
- test, 248–249
- timeout interdigit, 212
- timeouts initial, 212
- timing, 212–213
- type, 190–191
- vad, 227
- vbr-rt, 322
- vofr, 271–274
- voice bandwidth, 276–278
- voice class permanent, 236
- voice confirmation-tone, 198
- voice local-bypass, 214
- voice vad-time, 213
- voice-card, 239
- voice-port, 182–183
- companding, 59
- compand-type command, 195
- comparing
 - E1 and T1 lines, 80
 - key systems and PBXs, 398
 - voice compression techniques, 64
 - voice-capable and standards-based routers, 121
- components
 - of AVVID, 372–373
 - access gateways, 375
 - CallManger, 373
 - Cisco IP Phones, 375
 - uOne, 374
 - of basic PBX architecture, 410
- compression, 61, 431. *See also* companding
 - degradation of voice quality, 70
 - HCMs (high-performance voice-compression modules), 159–160
 - hybrid, 63–64
 - techniques
 - codecs, 193–194
 - comparing, 64
 - vocoder, 62–63
 - wave form, 62
- concentrators, MC3810
 - analog voice cable connections, configuring, 166–167
 - BRI voice module, configuring, 163–164
 - digital chassis, configuring, 160–161
 - hardware installation, verifying, 167–168
 - interface ports, configuring, 156, 158, 160
 - MFT options, configuring, 162–163
 - trunk options, configuring, 161
- configuration commands, ATM
 - dial-peer voice voatm, 324
 - encapsulation, 320
 - inarp parameter, 325
 - interface atm, 319
 - mode, 316, 318–319
 - pvc name, 319
 - session target, 324
 - vbr-rt, 322
- configuring
 - ABCD bit pattern for trunks, 237, 239
 - analog voice ports, 182–183
 - Cisco 2600 routers, 147–148
 - Cisco 3600 routers, 148, 150–151
 - port addressing, 155
 - VIC selection, 154–155
 - VNM selection, 152
 - controllers, 215–216
 - dial peers, 223–224, 229–230, 244, 328–329
 - voice-over, 229–242
 - digital voice ports, 183
 - E1 controller settings, 217, 219
 - fragmentation, 358
 - end-to-end FRF.12, 283
 - Frame Relay, Cisco proprietary, 284
 - FRF.11 Annex C fragmentation for data traffic, 283
 - Frame Relay map classes, 275

- FRF.11 trunk calls, 287–288
- local dial peers, 224–227, 229
- MC3810
 - BRI voice module, 163–164
 - digital chassis, 160–161
 - interface ports, 156, 158
 - MFT options, 162–163
 - WAN trunk options, 161
- MC3810 for voice-over, 165
- MLPPP, 361
- packet classification schemes, 349
- PQ-WFQ, 282, 356
- private-line calls, 286–287
- RTP header compression, 351
- VoATM, 322
- VoFR
 - CIR, 284
 - PVCs, 284–285
 - tandeming, 289, 291
- voice cards, 239
- voice ports
 - E&M, 189–195
 - ISDN PRI, 221, 223
 - tie-line connections, 201–202
- voice-over dial peers, session targets, 233–234
- WFQ, 282
- confirmation tone, 38
- congestion
 - BECN, 260
 - management, 350
 - telephone networks, 38
- connection command, 197
- connection sequence, H.323, 340–341
- connection tie-line command, 201
- connection trunk command, 202–203
- connections
 - E1, 78
 - framing, 78
 - line coding, 79
 - FXO, 128
 - local, 123
 - off-net, 124
 - on-net, 123
 - on-to off-net, 126
 - PLAR, 124
 - T1, 71–72
 - clocking, 76–77
 - D4 framing pattern, 73
 - ESF, 74–76
 - line coding, 76–77
 - management channel, 74–76
 - Ones Density rule, 76–77
 - robbed bit signaling, 73–74
 - tie-line, 125
- conserving bandwidth, 381–383
 - digital speech interpolation, 65
- constant bit rate (CBR), 308
- control complex, 400
- control signaling, 418
- controller command, 215
- controllers, configuring, 215–216
- conversational quality speech (ITU-T), 68
- converting analog signals to digital
 - compression, 61
 - hybrid compression, 63–64
 - vocoder, 62–63
 - wave form compression, 62
 - encoding process, 60–61
 - quantization process, 58–60
 - sampling, 56–57
- core layer, 11
 - in new-world networks, 19
- correcting input levels on voice ports, 210
- cost/benefit analysis, integrated voice/data networks, 439
 - global firms, 446, 448
 - multinational firms, 470–471
 - pan-European firms, 460–461
- cptone command, 185
- CPUs, PBX processing network design, 407
- CQ (Custom Queuing), 353
- creating peer configuration table, 328
- CS-ACELP (conjugate structure-algebraic code excited linear predictive), 64, 432
- CTIs (computer telephony interfaces), 401, 422–423

D

- D4 framing pattern, 73
- data link layer, VoIP protocol stack, 337
- data networks, 6
 - Frame Relay, 15–16
 - leased-line, 7
 - traffic shaping, 314
 - voice/data integration, 132
 - voice-data integration, 131
- data queuing methods
 - CBWFQ, 354–355
 - CQ, 353
 - FIFO, 352
 - LLQ, 356–358
 - PQ, 352
 - WFQ, 353
- data traffic, FRF.11 Annex C fragmentation,
 - example configuration, 283
- databases, SS7, 83
- DE (Discard Eligible) bit, 265
- debug cccrfl1 session command, 297, 299
- debug ccsvoice vofr-debug command, 299
- debug ccsvoice vofr-session command, 299
- debug command, 331
- debug commands, 248, 362–363
- debug frame-relay fragment command, 300–301
- debug voice vofr command, 301–302
- decibel levels, calculating, 205
- degradation of voice quality in compression
 - schemes, 70
- de-jitter buffers, 17, 259, 435
- delay, 17
 - ATM, minimizing, 310
 - dejitter buffers, 435
 - integrated voice/data networks, 427
 - jitter, 431
 - packetization delay, 436
 - processing delay, 434
 - propagation delay, 434
 - queuing delay, 435
 - serialization delay, 434
- delay budget, 336
 - calculating, 435, 437–438
- delay-start signaling, 35
- deregulated telecommunications markets, network
 - cloud terminology, 7
- description command, 185, 216
- designing networks
 - auditing current network, 428–429
 - global firms, 440
 - multi-national firms, 463
 - pan-European firms, 449
 - capacity planning, 438–439
 - global firms, 445
 - multinational firms, 468–470
 - pan-European firms, 453, 456–458
 - case studies, 440
 - global firm, 440, 443, 446, 448
 - multinational firm, 462–471
 - pan-European firm, 449–461
 - establishing technologies guidelines, 430–434
 - delay budgets, 436–438
 - global firms, 444
 - multinational firms, 464–468
 - pan-European firms, 452–453
 - financial analysis, 439
 - global firms, 446–448
 - multinational firms, 470–471
 - pan-European firms, 460–461
 - reviewing technologies and services, 430
 - global firms, 441–443
 - multinational firms, 464
 - pan-European firms, 450
 - setting objectives, 429
 - global firms, 441
 - multi-national firms, 463
 - pan-European firms, 450
- destination pattern, 123
- destination-pattern command, 224, 230
- devices
 - analog access gateways, 375
 - AVVID
 - Cisco conference bridges, 391–392
 - Cisco WebAttendant, 392
 - gateways, 386–387, 389
 - IP Phones, 384–385
 - media convergence servers, 389–390
 - codecs, 56
 - destination patterns, 123
 - drop-and-insert, 12
 - switches, 39
 - CO, 40–41
 - intermediate, 41

- PBXs, 41
 - voice, 40
- DHCP (dynamic host configuration protocol)
 - in AVVID, 376
- dial peers, 179
 - call legs, 181
 - configuring, 223–224, 244, 328–329
 - E.164 telephone numbers, configuring, 225
 - example configuration, 242
 - local, configuring, 224–227, 229
 - POTS, 181
 - verifying configuration, 243
 - voice-over, 181
 - configuring, 229–242
 - session targets, 233–234
- dial tone, 38
- dialers, 27
- dial-peer voice command, 224
- dial-peer voice voatm command, 324
- dial-type command, 187
- DID (direct inward dial), 420
 - trunks, 48
 - wink start signaling, 418
- DiffServ, 349
- digital chassis (MC3810), configuring, 160–161
- digital signals, conversion from analog
 - compression, 61–64
 - encoding process, 60–61
 - Nyquist theorem, 57
 - quantization process, 58–60
 - sampling, 56–57
- digital trunks
 - gateways, 386
 - T1/E1 packet voice trunk, Cisco 2600/3600 series routers, 103–104
- digital voice networks, 6
- digital voice ports
 - configuring, 183–184
 - disabling, 185
- dispersed control PBXs, 405
- displaying
 - function calls
 - ccfrf11, 297–299
 - ccswvoice, 299–300
 - VoFR call setup information, 301–302
- distributed control PBXs, 404

- distribution layer, 10
 - in new-world networks, 19
- DLCIs (data-link connection identifiers)
 - assigning to Frame Relay subinterface, 270–271
 - bandwidth, reserving, 275
 - VoFR, enabling, 271–274
- DPNSS (Digital Private Network Signaling System), 18
- drop-and-insert, 12
- ds0-group timeslots type command, 218–220
- DS1, 71. *See also* T1
 - digital signal Superframe format, 72
- DSCP (DiffServ Code Point), 265
- DSP (digital signal processor) modules
 - digital speech interpolation, 65
 - on AS5300s, 170
 - selecting, 172
- DTMF (dual-tone multi-frequency), 37
- DVM (digital voice module)
 - architecture, 160–161
 - mode cas command, 317

E

- E&M signaling
 - Type I lines, 42–43
 - Type II lines, 43
 - Type III lines, 44
 - Type IV lines, 44
 - Type V lines, 46
- E&M trunk seizure, 32–36
 - delay-start signaling, 35
 - disconnect, 36
 - immediate-start signaling, 36
 - wink-start signaling, 34–35
- E&M voice ports, 33–34
 - call completion, enabling, 191–193
 - Cisco 2600/3600 series routers, 102
 - configuring, 189–195
 - signaling type, specifying, 189
 - VICs, 127–129
- E.164 telephone numbers, dial peer configuration, 225

E1

- Catalyst 6000 Voice E1 module, 388
- channel signaling, 78
- comparing to T1, 80
- controller settings, configuring, 217–219
- framing, 78
- line coding, 79

echo, 49–50

echo cancel coverage command, 209

echo-cancel enable command, 208

ECMA (European Computer Manufacturer's Association), 18

enabling

- call completion on E&M voice ports, 191–193
- Frame Relay on interfaces, 270

encapsulation, MLPPP, 132

encapsulation command, 320

encapsulation frame-relay command, 270

encoding, 60–61

end-to-end FRF.12 fragmentation, example configuration, 283

enterprise networks

- FXO, 128
- H.323, 139
- hoot-and-holler applications, 138–139
- OPX connections, 138
- PBX implementations, 400–401
- toll bypass, 137

enterprise telephony, 20

erlangs, 416

ESF (Extended Superframe Format), 74–76

establishing voice quality guidelines, 431

- coding/compression, 431
- fixed delay components, 434
- MOS, 432–433
- variable delay components, 435

Ethernet Phone, 130

example configurations

- Cisco-trunk calls, 286–287
- dial peers, 242
- PQ-WFQ, 282
- VoATM, 322, 326–328
- VoFR
 - CIR, 284
 - Cisco proprietary fragmentation, 284
 - end-to-end FRF.12 fragmentation, 283

- FRF.11 trunk calls, 287–288
- PVCs, 284–285
- tandeming, 289–291
- WFQ, 282

Extended Superframes, 72–74

external networks, 401

F

fast busy signal, 38

fast packet switching, PBXs, 415

fax-to-fax connections, 130

FDM (frequency division multiplexing), 6

feature cards

- circuit cards, PBX systems, 412
- Cisco AS5300, 170
- Cisco AS5800 Voice Feature card, 111
- MICA (modem ISDN channel aggregation), 170
- VOIP, selecting, 171–172

features of PBXs, 420–421

FECN (forward explicit congestion notification), 260

FIFO (First In First Out) queuing, 352

first-generation private telephony systems, 400

fixed delay

- processing delay, 258
- propagation delay, 257
- serialization delay, 258

fixed prioritization, 314–316

formulas for calculating bandwidth, ATM, 312–314

forward-digits command, 228

fragmentation, 266, 358, 280

- Cisco proprietary (Frame Relay), example configuration, 284
- FRF.11 Annex C, example configuration, 283
- MLPPP, configuring, 361
- PDU size, calculating, 268–269

Frame Relay, 15–16. *See also* VoFR

- fragmentation, 280
- map classes, configuring, 275

frame synchronization, D4 framing pattern, 73

frame-relay adaptive-shaping command, 281

frame-relay bc command, 281

frame-relay be command, 281

frame-relay cir command, 280

frame-relay fair-queue command, 278–279
 frame-relay fragment command, 279–280
 frame-relay interface dlci command, 270–271
 frame-relay mincir command, 280
 frame-relay traffic-shaping command, 274
 frame-relay voice bandwidth command, 275
 frames, prioritizing, 260
 framing command, 216
 framing patterns

- DS1, 71
- E1, 78
- ESF, 74, 76

 FRF.11 Annex C fragmentation, 260

- configuring for data traffic, 283
- subchannels, displaying information, 292–293
- trunk calls, configuring, 287–288

 FRF.12 fragmentation, 260

- example configuration, 283

 fricatives, 63
 FRTS (Frame Relay traffic shaping), 260–261
 FXO (foreign exchange office)

- Cisco 2600/3600 series routers, 102
- trunks, 47–48, 128
- voice ports
 - dial type, specifying, 187
 - terminating impedance, specifying, 208

 FXS (foreign exchange station)

- applications, 129
- Cisco 2600/3600 series routers, 102
- trunks, 48
- voice ports
 - impedance, adjusting, 211
 - ring frequency, specifying, 187

G

G.711 standard (ITU-T), 66
 gain, adjusting, 206
 gatekeepers, 133–134, 338
 gateways, 338–340, 386–389

- Catalyst 6000 Voice T1 module, 388
- Cisco AS5300, 107
- Cisco AS5800, 110–112
- digital trunk gateways, 386
- H.323, 141
- VG 200 VoIP gateway, 387–388

GF (Generic Feature), Q.SIG, 83
 GF (generic functional) sublayer (QSIG), 419
 glare, 30
 goals of uOne, 374
 ground start signaling, 30–32, 418

- specifying for voice ports, 186

 GSTN (global system telephone network), 373
 guaranteed traffic rates, FRTS, 261

H

H.225 protocol, 341
 H.245, 341
 H.323, 139, 338–342

- connection sequence, 340–341
- gateways, 340
- H.225, 341
- H.243, 341
- in AVVID, 377
- IP Phone, 130
- media formats, 379
- signaling, 340
- terminals, 339

 handsets, 26
 hardware

- AVVID
 - Cisco conference bridges, 391–392
 - Cisco WebAttendant, 392
 - gateways, 386–387, 389
 - IP Phones, 384–385
 - media convergence servers, 389–390
- VoATM, 310–311
- MC3810
 - analog voice cable connections, 166–167
 - installation, verifying, 167–168

 Hawking, Stephen, 63
 HCMs (high-performance voice-compression modules), 159–160

- Cisco MC3810, 107

 HDB3 (high density bit 3), 78
 HDV (High Density Voice) NM, 103
 high availability on MCS-7822 media convergence server, 389
 high density bit 3 (HDB3), 78
 high-utilization trunks (HUTs), 49
 holding time per call, calculating, 417

hoot-and-holler, 138–139
 hunt groups, 392
 HUTs (high-utilization trunks), 49
 hybrid compression, 63–64
 2- to 4-wire, balanced, 27, 49

I

IDF (intermediate distribution frame), 402
 IMA cards, 311
 immediate-start signaling, 36
 impedance command, 208, 211
 implementing
 IP voice installations, building blocks, 349–350
 VoIP with MGCP, 342
 improving voice quality, 205–214
 inarp parameter, 325
 information signaling, 38, 417
 alerting indicators, 38
 call progress indicators, 38
 input gain command, 206, 215
 input power levels
 correcting on voice ports, 210
 baselining, 205
 installation, verifying for Cisco 3600 series
 routers, 156
 integrated voice/data networks
 delay, 427
 propagation delay, 427
 delay budget, calculating, 435, 437–438
 design process
 auditing network inventory, 428–429
 capacity planning, 438–439
 case studies, 440–471
 establishing technologies guidelines,
 430–434
 delay budgets, 436–438
 financial analysis, 439
 reviewing technologies and services, 430
 setting network objectives, 429
 interexchangenetworks, 401
 interface atm command, 319
 interface cards. *See* VICs

interfaces
 E&M, 33–34
 in PBXs, 413
 MC3810, configuring, 156–160
 intermediate switches, 41
 inter-office trunks (IOTs), 49
 interpolation, 65
 intertandem trunks (ITTs), 49
 IOTs (inter-office trunks), 49
 IP Phones, 375, 384–385
 Cisco IP Phone 7910, 384
 Cisco IP Phone 7960, 385
 IP Precedence, 265, 337
 IP protocols in AVVID
 DHCP, 376
 H.323, 377
 MGCP, 378–379
 SCCP, 379
 TFTP, 376
 ISDN (Integrated Services Digital Network), 6
 BRI VoIP, 104
 network architecture, 81
 network protocols, 82
 PRI, voice port configuration, 221–223
 ISO 3166 country name standards, 185
 ITTs (inter-tandem trunks), 49
 ITU-T Recommendation I.451, 419–420
 IVR (interactive voice response), 20, 422

J-K-L

J1, 80
 jitter, 17, 431
 dejitter buffers, 435
 key systems, 397–399
 large-scale voice/data routers
 Cisco 7200 series, 112–114
 Cisco 7500 series, 114, 117
 Cisco AS5800, 110–111
 latency. *See* delay
 layers of VoIP protocol stack, 337–338
 LCR (least-cost routing), 420
 LD-CELP (low-delay CELP), 63

- LD-CELP (low-delay code-excited linear-predictive) algorithms, 432
 - leased line networks, 7
 - point-to-point, 8
 - multi-drop, 9
 - least-cost routing (LCR), 420
 - LECs (local exchange carriers), 6
 - legacy PBX systems, 397
 - legacy telephony systems
 - PBXs, 399–401
 - private key systems, 398–399
 - limitations of bandwidth, voice-grade telephony channels, 57
 - line circuit cards in PBX systems, 412
 - line coding
 - E1, 79
 - T1, 76–77
 - line interface circuitry, PBX systems, 411–412
 - line provisioning, 438–439
 - linecode command, 216–217
 - listener echo, 49–50
 - LLQ (Low Latency Queuing), 337, 356–358
 - local calls, 123
 - local connections, 123
 - local dial peers, configuring, 224–229
 - local loop, 39
 - ground start signaling, 30–32
 - loop start signaling, 28–30
 - local networks, 401
 - logical voice ports, 219
 - long data frames, 260
 - loop start circuits, 28
 - loop start signaling, 28–30, 418
 - specifying for voice ports, 186
 - loopback command, 234
 - loop-timed command, 216
 - loss-plan command 206, 210
 - low-delay CELP (code excited linear predictive) coding, 63
- M**
-
- main system controller (PBXs), 410
 - maintaining synchronization over digital interfaces, 81
 - make/break cycle, 36
 - management channel, T1 line coding, 74, 76
 - map classes, configuring, 275
 - map-class frame-relay command, 275
 - marking, 265
 - MC3810 routers
 - analog voice cable connections, 166–167
 - BRI voice module, configuring, 163–164
 - digital chassis, configuring, 160–161
 - fixed prioritization, 314–316
 - hardware installation, verifying, 167–168
 - interface ports, configuring, 156, 158, 160
 - MFT (multiflex trunk module) options, configuring, 162–163
 - synchronous serial connections, 167
 - voice-over configuration, 165
 - WAN trunk options, configuring, 161
 - MCM (Multimedia Conference Manager), 133–134, 139
 - MCS-7822, 389
 - MCS-7835, 390
 - MCU (multipoint control unit), 339
 - MDF (main distribution frame), 402
 - measuring
 - PBX traffic handling, 416–417
 - speech quality, 68, 70–71
 - PSQM, 69
 - subjective, MOS, 432–433
 - telephone voice quality, 65
 - media convergence servers
 - for AVVID, 389–390
 - MCS-7822, 389
 - MCS-7835, 390
 - media formats, H.323, 379
 - Meet-Me conferences, 391
 - Megaco, 342
 - MELCAS (Mercury Exchange Limited), 317
 - messaging
 - Q.931 signaling, 419–420
 - unified messaging, 141
 - uOne, 374
 - voice-mail systems, 422
 - MFT (Multiflex Trunk), 311
 - configuring on MC3810, 162–163
 - VWIC, 103

MGCP (Media Gateway Control Protocol), 18, 338, 342
 configuring on MC3810, 162–163
 MICA (modem ISDN channel aggregation), 170
 minCIR (minimum committed information rate), 260
 minimizing delay in VoATM, 309–310
 MLPPP (Multilink Point-to-Point Protocol), 360
 configuring, 361
 encapsulation, 132
 mode cas command, 317
 mode ccs command, 218
 mode command, 316, 318–319
 modular wiring, PBX systems, 411
 modulation, B8ZS, 77
 monitoring commands, 329–331
 MOS (mean opinion score), 68, 432–433
 MTP (media termination point), 382
 multicast conference bridges, 391
 multi-drop networks, 8–9
 multiflex trunking, 457
 Multiframe, 79
 multipoint controller, 339
 multiservice networks
 voice/data integration, 131
 voice-over technology, selecting, 132
 multiservice routers
 Cisco AS5300, 107
 Cisco MC3810, 105–107

N

network design
 access layer requirements, 9
 new-world networks, 18
 auditing current network, 428–429
 global firms, 440
 multi-national firms, 463
 pan-European firms, 449
 capacity planning, 438–439
 global firms, 445
 multinational firms, 468–470
 pan-European firms, 453, 456–458

case studies, 440
 global firm, 440–448
 multinational firm, 462–471
 pan-European firm, 449–461
 circuit-switched, 13
 core layer requirements, 11, 19
 distribution layer requirements, 10, 19
 establish technologies guidelines, 430–434
 delay budgets, 436–438
 global firms, 444
 multinational firms, 464–468
 pan-European firms, 452–453
 financial analysis, 439
 global firms, 446–448
 multinational firms, 470–471
 pan-European firms, 460–461
 reviewing technologies and services, 430
 global firms, 441–443
 multinational firms, 464
 pan-European firms, 450
 setting objectives, 429
 global firms, 441
 multi-national firms, 463
 pan-European firms, 450
 shared, 12
 traditional, 5
 data, 6–7
 voice, 5–6
 network layer (VoIP protocol stack), 337
 Network Module-Inverse Multiplex ATM (NM-IMA), 311
 network protocols, ISDN, 82
 network-clock-select command, 164
 new-world telephony models, AVVID, 373
 access gateways, 375
 CallManager, 373
 Cisco conference bridges, 391
 Cisco IP Phones, 375
 Cisco WebAttendant, 392
 Cisco's role in, 18–20
 DHCP, 376
 gateways, 386–387, 389
 H.323, 377
 IP Phones, 384–385
 media convergence servers, 389–390
 MGCP, 378–379
 SCCP, 379

- signaling, 380
- TFTP, 376
- uOne, 374
- NM-IMA (Network Module-Inverse Multiplex ATM), 311
- NMs (network modules), HDV (High Density Voice), 103
- non-linear command, 209
- non-real time service classes, 314, 316
- num-exp command, 226
- Nyquist theorem, 56–57

O

- off-hook state, 28
- off-net calls, 124
- off-net connections, 124
- old-world telephony models, 371. *See also* new-world telephony models
- PBXs, 397, 402
 - ACD, 421–422
 - adjunct control, 406
 - architecture, 408–414
 - automated attendant, 421
 - busy hour call handling, 415–416
 - callout, 416–417
 - centralized control, 403
 - circuit switching, 414
 - client/server-based, 407–408
 - CTI, 422–423
 - dispersed control, 405
 - distributed control, 404
 - fast packet switching, 415
 - features, 420–421
 - IVR, 422
 - line interfaces, 412
 - packet switching, 415
 - processing network design, 407
 - switching network design, 403
 - trunk interfaces, 413
 - Windows/Unix server-based, 407
 - wiring, 413–414
- private systems
 - key systems, 398–399
 - PBXs, 399, 401

- Ones Density rules, 76–77, 80
- on-hook state, 28
- on-net connections, 123
- on-to off-net connections, 126
- oos (out-of-service) receive pattern, 237
- operation command, 189
- options
 - dial-peer voice voatm command, 324
 - encapsulation command, 321
 - interface atm command, 319
 - mode command, 317
 - pvc command, 320
 - session target command, 325
 - vbr-rt command, 322, 324
- OPX connections, 138
- output attenuation command, 206, 215
- output power levels, baselining, 205

P

- packet switching, PBXs, 415
- packetization delay, 436
- packets
 - classification schemes, 349
 - fragmentation, 266, 358
 - SAR, 309
 - scheduling, 264
 - sequencing, 343–344
 - time-stamping, 343–344
- payback period, calculating for capital investments, 460–461
- PBXs (private branch exchanges), 6, 41, 397–399, 401–402
 - ACD, 421–422
 - architecture, 408, 410–414
 - cabinet/shelf controller, 409
 - main system controller, 410
 - wiring, 413–414
 - automated attendant, 421
 - busying out, 237
 - circuit switching, 414
 - CTI, 422–423
 - fast packet switching, 415
 - features, 420–421
 - grounding, 42
 - in enterprise networks, 401

- IVR (interactive voice response), 422
- legacy systems, 397
- line interfaces, 412
- local loop, 39
- old-world telephony model, 371
- packet switching, 415
- processing methods
 - busy hour call handling, 415–416
 - callout, 416–417
 - circuit/packet switching, 414–415
- processing network design, 407
 - client/server-based, 407–408
 - Windows/Unix server-based, 407
- switching network design, 403
 - adjunct control, 406
 - centralized control, 403
 - dispersed control, 405
 - distributed control, 404
- tandem switching, disadvantages in voice networks, 137
- terminal interfaces, 400
- tie-lines, 32
- trunk interfaces, 413
- trunks, 46–47
 - CO trunks, 47
 - DID/DOD trunks, 48
 - FXO trunks, 47–48
 - private trunk lines, 47
 - telco trunks, 48
- voice-mail systems, 422
- PBX-to-PBX calls, 125
- peak options for voice traffic, calculating, 323–324
- peer configuration table, VoATM, 328
- Perceptual Speech Quality Measurement (PSQM), 69
- permanent calls. PLAR connections, 199
- per-VC queuing, enabling on PVCs, 274
- physical connectivity, MC3810, 166–167
- physical layer, VoIP protocol stack, 337
- pilot number, 374
- PINX (private integrated network exchange), 163–164
 - QSIG, 419
- placing a call, 23–26
- PLAR (private line automatic ring-down), 124, 198
 - off-premises extension, 200
- point-to-point connections, enterprise networks, 138–139
- point-to-point networks, 8
- policing, 264
- port addressing, Cisco 3600 routers, 155
- port circuit cards, PBX systems, 412
 - controller, 410
- port command, 225–226
- POTS, dial peers, 181, 328
- power failure transfer, 421
- power supply, telephones, 40
- PQ (priority queuing), 352
- PQ-WFQ (priority queuing-weighted fair queuing), 355–356
 - example configuration, 282
- prefix command, 228
- presentation layer, VoIP protocol stack, 338
- prioritizing voice frames, 260
- private networks, 401
- private phone systems, 397
- private telephony systems
 - first-generation, 400
 - key systems, 398–399
 - PBXs, 399, 402
 - ACD, 421–422
 - adjunct control, 406
 - architecture, 408, 410–414
 - automated attendant, 421
 - busy hour call handling, 415–416
 - callout, 416–417
 - centralized control, 403
 - circuit switching, 414
 - client/server-based, 407–408
 - CTI, 422–423
 - dispersed control, 405
 - distributed control, 404
 - fast packet switching, 415
 - features, 420–421
 - IVR, 422
 - line interfaces, 412
 - packet switching, 415
 - processing network design, 407
 - switching network design, 403
 - terminal interfaces, 400
 - trunk interfaces, 413
 - Windows/Unix server-based, 407
 - wiring, 413–414

- second-generation, 400
- third-generation, 400
- private trunk lines, 47
- private-line calls, example configuration, 286–287
- processing delay, 258, 434
- processing methods, PBXs
 - busy hour call handling, 415–416
 - callout, 416–417
 - switching, 414–415
- processing network designs (PBXs)
 - client/server-based, 407–408
 - Windows/Unix server-based, 407
- propagation delay, 257, 434
 - integrated voice/data networks, 427
- protocol stack, VoIP, 337–338
- PSQM (Perceptual Speech Quality Measurement), 69
- PSTNs (private switched telephone networks).
 - See also* old-world telephony
 - access code, 124
 - access numbers, pilot number, 374
 - FXO interfaces, 128
- PTT (Post, Telephone, and Telegraph) agency, 7
- pulsed digits, 36
- pvc name command, 319
- PVCs (permanent virtual circuits), 13
 - fragmentation, displaying information, 300–301
 - per-VC queuing, enabling, 274
 - traffic shaping, 260–261
 - virtual template parameters, 321
 - WFQ, enabling, 278–279
- PVDM (Packet Voice DSP Module), 103

Q

- Q.931 signaling, 419–420
- Q.SIG, 83, 419
- Q.SIG GF (Generic Features), 83
- QoS (quality of service)
 - applying to VoFR, 264–265
 - fragmentation size, calculating, 268–269
- quantization, 58–60

- queue management, 350
 - CBWFQ, 354–355
 - data transmission
 - CQ, 353
 - FIFO, 352
 - PQ, 352
 - LLQ, 356, 358
 - PQ-WFQ, 355–356
 - RTP header compression, 350–351
 - WAN edge queuing techniques, 351
 - WFQ, 353
- queuing, 264
 - delay, 259, 435
 - PQ-WFQ, example configuration, 282
 - WFQ, example configuration, 282

R

- rate queues, 326
- real time service classes, 314–315
- RED (Random Early Detection), 350
- regional offices, redesigning for voice traffic, 454
- regulated telecommunications markets, network
 - cloud terminology, 7
- reorder, 38
- reserving bandwidth on DLCIs, 275
- residual echo suppression, 210
- ring frequency command, 187
- ring number command, 186
- ring-back, 38
- ringer, 27
- robbed bit signaling, 73–74, 417
 - ABCD format, 74–76
- rotary telephones
 - pulsed digits, 36
- routers
 - Cisco 1750 series, 91
 - Cisco 2600 series, 92, 94
 - configuring, 147–148
 - digital T1/E1 packet voice trunk, 103–104
 - PVDM, 103
 - VICs, 102
 - voice/fax network module, 101–102

- Cisco 3600 series, 95
 - Cisco 3620 modular access routers, 95
 - Cisco 3640 modular access routers, 95
 - Cisco 3660 modular access routers, 95
 - configuring, 148–151
 - digital T1/E1 packet voice trunk, 103–104
 - PVDM, 103
 - VICs, 102, 154–155
 - VNM, selecting, 152
 - voice/fax network module, 101–102
 - Cisco 7200 series, 112–114
 - Cisco 7500 series, 114, 117
 - Cisco AS5300, 107
 - Cisco AS5800, 110–112
 - Cisco MC3810, 105–107
 - signaling
 - between routers, 346
 - to PBX, 347
 - voice-over connection types, 123–126
 - RSVP (Resource Reservation Protocol), 344
 - RTP header compression, 343–344, 350
 - configuring, 351
- ## S
-
- sampling, Nyquist theorem, 56–57
 - SAP (Session Announcement Protocol), 342
 - SAR (segmentation and reassembly), 309
 - SCCP (signaling connection control part),
 - AVVID, 379
 - scheduling, 264
 - second-generation private telephony systems, 400
 - selecting
 - DSP modules, 172
 - network technology, 430
 - global firms, 441, 443
 - multinational firms, 464
 - pan-European firms, 450
 - VICs, Cisco 3600 routers, 154–155
 - VNMs, Cisco 3600 routers, 152
 - voice-over technologies, 132
 - VoATM, 135–136
 - VoFR, 134
 - VOIP feature cards, 171–172
 - sequencing packets, 343–344
 - serialization delay, 258, 358, 434
 - server farms, 408
 - service circuit cards, PBX systems, 412
 - service classes (ATM), 308–309
 - minimizing delay, 310
 - non-real time, 314–316
 - real time, 314–315
 - service provider telephony, 20
 - VPNs, 402
 - session layer, VoIP protocol stack, 338
 - session target command, 231–234, 324
 - session targets, configuring on voice-over dial peers,
 - 233–234
 - setting network objectives, 429
 - global firms, 441
 - multi-national firms, 463
 - pan-European firms, 450
 - shaping traffic, 264
 - shared networks, drop-and-insert devices, 12
 - show atm pvc command, 329
 - show commands, 246–247, 329, 362–363
 - show dial-peer voice command, 243
 - show frame-relay fragment command, 294–295, 297
 - show frame-relay vofr command, 292–293
 - show interface command, 330
 - show running-config command, 245
 - show voice port command, 245
 - shutdown command, 185
 - sidetone, 27
 - signal command, 185, 189
 - signal pattern command, 237
 - signaling, 27, 417
 - AVVID, 380
 - between routers, 346
 - CAS, 79, 317
 - CCS, 317, 418–419
 - delay-start, 35
 - DID wink start, 418
 - E&M
 - disconnect, 36
 - seizure, 32, 34–35
 - Type I lines, 42–43
 - Type II lines, 43
 - Type III lines, 44
 - Type IV lines, 44
 - Type V lines, 46
 - E1 channel, 78
 - from router to PBX, 347

- glare, 30
- ground start, 418
- H.323, 338, 340–342
 - H.225, 341
 - H.245, 341
- immediate-start, 36
- information, 38
- local loop
 - ground start signaling, 30, 32
 - loop start signaling, 28, 30
- loop start, 418
- Q.931, 419–420
- Q.SIG, 83, 419
- specifying type for voice ports, 185, 189
- supervisory, 28
 - local-loop seizure, 28, 30, 32
- VoIP, 345
- wink-start, 34–35
- signal-type command, 235
- silence suppression, VAD, 227
- SIP (Session Initiation Protocol), 18, 342
- smoother circuits, 60
- SOT (service order threshold), 353
- specifying
 - BVMs as clock source, 164
 - confirmation tones for voice ports, 198
 - signaling type for voice ports, 185
- speech quality
 - establishing guidelines, 431
 - coding/compression, 431
 - fixed delay components, 434
 - MOS, 432–433
 - variable delay components, 435
 - measuring, 65, 67
 - MOS (mean opinion score), 68, 70–71
 - toll-quality, 67
 - transparent quality (ITU-T), 67
- SS7 (Signaling System 7), 82
- SSCP (Skinny Station Control Protocol), 379
- subjective speech measurement, MOS, 68–71, 432–433
- sublayers of QSIG, 419
- Superframes, 72
- supervisory signaling, 28, 417
 - local-loop seizure, 28–32
- SVCs (switched virtual circuits), 13
- switch hook, 27

- switched calls
 - PLAR connections, 199
 - tandeming, configuration, 289, 291
- switching, 39, 400
 - circuit switching, 414
 - CO, 40–41
 - fast packet switching, 415
 - intermediate switches, 41
 - packet switching, 415
 - PBXs, 41–42
 - adjunct control, 406
 - centralized control, 403
 - dispersed control, 405
 - distributed control, 404
 - voice switches, 40
- symptoms of poor QoS, 266
- synchronization
 - D4 framing pattern, 73
 - time-slot, 80
- synchronous serial connections, for MC3810, 167
- synthetic quality speech (ITU-T standard), 68
- system circuit cards, PBX systems, 412
- system processor bus, PBX design, 409
- system-wide PBX features, 420–421

T

- T1 line coding, 71–72, 76–77
 - Catalyst 6000 Voice T1 module, 388
 - clocking, 76–77
 - comparing to E1, 80
 - controller settings, 216–217
 - D4 framing pattern, 73
 - ESF (Extended Superframe Format), 74, 76
 - management channel, 74, 76
 - Ones Density rules, 76–77
 - robbed bit signaling, 73–74
- tagging, 265
- talk slots, 417
- talk spurts, 259
- talker echo, 49–50
- tandeming, 289–291
 - disadvantages in voice networks, 137
- TCD (telephony call dispatcher), 392
- TDM cross connect. *See* drop-and-insert
- telco trunks, 48

- telephony systems
 - confirmation tone, 38
 - devices, 26–27
 - glare, 30
 - GSTN (global system telephone network), 373
 - off-hook state, 28
 - old-world
 - key systems, 398–399
 - PBXs, 399, 401
 - on-hook state, 28
 - power supply, 40
 - private
 - first-generation, 400
 - PBXs, 402
 - second-generation, 400
 - third-generation, 400
 - switches, 39
 - CO switches, 40–41
 - intermediate switches, 41
 - PBXs, 41
 - voice switches, 40
 - third-generation, 400
- terminal interfaces, 400
- terminals, 339
- test commands, 248–249
- TFTP (trivial file transport protocol), AVVID, 376
- third-generation private telephony systems, 400
- tie-line connections, 32, 125, 129
 - voice port configuration, 201–202
- time slots, 417
- timeouts initial command, 212
- timeouts interdigit command, 212
- time-slot synchronization, 80
- time-stamping, UDP packets, 343–344
- timing command, 212–213
- toll bypass, 137
- toll quality speech
 - G.711 standard, 66
 - ITU-T standard, 67
- ToS (type of service) bits, 349
- traditional networks, 5
 - data networks, 6–7
 - delay, 17
 - jitter, 17
 - shared, 12
 - voice, 5–6
- traffic
 - classes, 308–309
 - minimizing delay, 310
 - non-real time, 314–316
 - real time, 314–315
 - congestion management, 350
 - packet classification schemes, 349
 - policing, 264
 - queuing, 264
 - scheduling, 264
 - voice/data integration, 132
- traffic shaping, 260–261, 264
 - ATM, 312
 - for data/video, 314
 - voice traffic
 - calculating average options, 323–324
 - calculating burst options, 323–324
 - calculating peak options, 323–324
- transcoding, 389
- transparent quality speech, 67
- transport layer, VoIP protocol stack, 338
- troubleshooting commands, 329–331, 362
 - debug commands, 363
 - show commands, 363
- troubleshooting QoS, 269
- trunks, 46–47
 - ABCD bit pattern, configuring, 237, 239
 - CO trunks, 47
 - DID/DOD trunks, 48
 - digital trunk gateways, 386
 - FXO trunks, 47–48
 - FXS trunks, 48
 - interfaces, 411–413
 - line provisioning, 438–439
 - MC3810, setting options for, 161
 - MFT (Multiflex Trunk), 311
 - private trunk lines, 47
 - service cards, 412
 - telco trunks, 48
 - voice classes, configuring, 236

tuning voice port quality, 205–207, 209–214
 two-way communication, VoATM, 328
 type command, 190–191
 Type I E&M lines, 42–43
 Type II E&M lines, 43
 Type III E&M lines, 44
 Type IV E&M lines, 44
 Type V E&M lines, 46

U

UBR (unspecified bit rate), 308
 UDP (user datagram protocol), time-stamping packets, 343–344
 unacceptable telephone voice quality, 66
 unicast conference bridges, 391
 unified messaging, 141
 Unix server-based PBXs, 407
 unsatisfactory speech quality (ITU-T standard), 68
 unspecified bit rate (UBR), 308
 uOne, 374
 upgrading networks, pan-European firms, 455–458
 user features for PBX, 420–421

V

VAD (voice activity detection), 65
 vad command, 227
 variable bit rate (VBR), 308
 variable delay
 de-jitter buffers, 259
 queuing delay, 259
 WAN/service provider delay, 259
 variation. *See also* delay
 VBR (variable bit rate), 308
 VBR-nrt (non-real time), 308
 VBR-rt (real time), 308
 vbr-rt command, 322
 VC (virtual circuit) queues, VoATM networks, 135
 verifying
 dial peer configuration, 243
 hardware installation
 Cisco 3600 routers, 156
 MC3810, 167–168
 VFCs (voice feature cards), Cisco AS5800, 111.
 See also feature cards
 VG 200 VoIP gateway, 387–388
 VICs (voice interface cards)
 assembly, 155
 Cisco 2600/3600 series routers, 102
 E&M, 127
 port addressin, Cisco 3600 routers, 155
 selecting, 154–155
 virtual circuits (VCs), 13
 VNMs
 assembly, 155
 selecting, 152
 VoATM, 135–136
 bandwidth allocation, 309
 dial peers, configuring, 328–329
 example, 326, 328
 example configuration, 322
 hardware, 310–311
 peer configuration table, 328
 VC queues, 135
 vocoder compression, 62–63
 VoFR, 134
 CIR, example configuration, 284
 Cisco implementation, 262
 benefits of, 263
 restrictions, 264
 enablingn on specified DLCI, 271–274
 PVCs, example configuration, 284–285
 QoS, applying, 264–265
 tandeming, 289, 291
 vofr command, 271–274
 voice bandwidth command, 276–278
 voice calls, calculating bandwidth, 359–360
 voice cards, configuring, 239
 voice class permanent command, 236
 voice compression
 codec complexity, 240
 comparing techniques, 64
 Voice Feature cards, Cisco AS5800, 111
 voice gateways
 Cisco AS5300, 107
 Cisco AS5800, 110–112
 voice local-bypass command, 214

- voice networks, 5. *See also* integrated voice/data networks
 - analog, 6
 - capacity planning, 438–439
 - global firms, 445
 - multinational firms, 468–470
 - pan-European firms, 453, 456–458
 - delay, 427
 - delay budget, calculating, 435, 437–438
 - digital, 6
 - echo, 49–50
 - echo cancellation, 50
 - echo suppression, 50
 - financial analysis, 439
 - global firms, 446–448
 - multinational firms, 470–471
 - pan-European firms, 460–461
- voice ports, 179
 - analog, configuring, 182
 - call progress tone, setting, 185
 - confirmation tones, specifying, 198
 - connection mode, specifying, 197
 - decibel levels, calculating, 205
 - digital, configuring, 183
 - disabling, 185
 - E&M
 - call completion, enabling, 191–193
 - configuring, 189–195
 - FXO
 - dial type, specifying, 187
 - impedence, adjusting, 211
 - terminating impedence, specifying, 208
 - FXS, specifying ring frequency, 187
 - input/output power levels
 - baselining, 205
 - correcting, 210
 - ISDN PRI, configuring, 221, 223
 - logical, 219
 - PLAR
 - off-premises extension, 200
 - specifying, 198
 - residual echo suppression, 210
 - signaling type, specifying, 185
 - string description, adding, 185
 - tie-line connections, configuring, 201–202
 - timing parameters, adjusting, 212–213
 - trunk connections, specifying, 202–203
 - tuning, 205–214
- voice quality
 - establishing guidelines, 431
 - coding/compression, 431
 - fixed delay components, 434
 - MOS, 432–433
 - variable delay components, 435
 - measuring, 65
- voice switches, 40
- Voice T1 and Services Module, 389
- voice vad-time command, 213
- voice/data integration, *See* integrated voice/data networks
- voice/fax network module, Cisco 2600/3600 series
 - routers, 101–102
- voice-card command, 239
- voice-confirmation-tone command, 198
- voice-grade analog channels, bandwidth, 56
- voice-mail systems, 422
 - AVVID, 16
 - uOne messaging, 374
- voice-over technologies
 - connection types
 - local, 123
 - off-net, 124
 - on-net, 123
 - on-to off-net, 126
 - PLAR, 124
 - tie-line, 125
 - dial peers, 181, 229–242
 - MC3810, configuring, 165
 - selecting, 132
 - VoATM, 135–136
 - VoFR, 134
- voice-port command, 182–183
- voice-port tuning commands, 204
- VoIP
 - Cisco implementation, 347
 - H.323, 338, 340–342
 - ISDN BRI, 104
 - signaling, 345
- VPNs (virtual private networks), 402
- VWICs, MFT (MultiFlex Trunk), 103

W-Z

WANs

- bandwidth, conserving over links, 381–383
 - edge queuing techniques, 351
 - fast packet switching, 415
 - service provider delay, 259
- wave form compression, 62
- WFQ (weighted fair queuing), 353
- enabling for PVCs, 278–279
 - example configuration, 282
- WICs (WAN interface cards), MFT (MultiFlex Trunk) VWIC, 103
- Windows server-based PBXs, 407
- wink signals, 418
- wink-start signaling, 34–35
- wiring, PBX systems, 413–414
- WRED (Weighted Random Early Detection), 350

X.25, 15–16