



Symbols

%OSPF-4-BADLSATYPE error messages, 529

Numerics

128-bit addressing scheme, IPv6, 5
 2-way state, OSPF neighbors, 336
 getting stuck, 398–400
 32-bit addressing scheme, IPv4, 5
 classes, 5–7
 private address space, 7–8
 subnetting, 8

A

ABRs (area border routers), generating default
 summary routes, 326–327

access lists

 distribute lists

 IGRP uninstalled routes, 149–150
 unadvertised IGRP routes, 173–174

 filtering BGP traffic

 unfiltered masked routes, 831–835
 unfiltered subnets, 828–830

 inbound interfaces, blocked RIP broadcast,
 63–65

 source address. blocked RIP route installation,
 60–63

 unintentional TCP packet blockages, 741–742

Acknowledgment field (EIGRP packets), 216

active routes (EIGRP), 213

Active state (BGP-4), 663

AD (administrative distance), 24, 661

Address Resolution Protocol (ARP), 5

addresses

 CLNP, 548

 NSAPs, 536

 defining, 551

 format, 549–551

addressing, 4

 classless, 7

 CLNP NSAPs, 536, 548

 defining, 551

 format, 549–551

 hop-by-hop destination-based forwarding, 4

 IPv4

 CIDR, 10

 classes, 5–7

 private address space, 7–8

 subnet, 8

 media independence, 5

adjacencies, 334–335

 2-way state, 336

 Attempt state, 336

 Down state, 335

 ES-IS, 538, 589

 formation in IS-IS network, 605

 Exchange state, 337

 Exstart state, 336

 Full state, 338

 Init state, 336

 IS-IS, 537–540, 587–589

 absence of, 590–596

 INIT state, 596–605

 Loading state, 338

 OSPF

 optional capability mismatches, 370–372

 Stuck in 2-WAY state, 398–400

 Stuck in ATTEMPT, 383–386

 Stuck in EXSTART/EXCHANGE state,
 401–417

 Stuck in INIT, 387–398

 Stuck in LOADING state, 417–422

administrative distance, 24, 661

advanced distance vector routing protocols

 EIGRP

 dial backup, 286–290

 error messages, 291

 mismatched AS numbers, 239

 mismatched K values, 237

 mismatched masks, 235–237

 neighbor relationships, 227–232

 redistribution, 280–286

 route advertisement, 250–256

 route flapping, 271–275

- route installation, 264–270
- route summarization, 276–280
- SIA errors, 240–250
- uncommon subnets, 233–235
- unexpected metrics, 259–263
- unexpected route advertisement, 257–259
- advertising
 - BGP-4 routes, 668–670
 - synchronization rule, 671–672
 - IGRP routes
 - broadcast capability, 178–180
 - distribute lists, 173–174
 - misconfigured neighbor statement, 180–181
 - misconfigured network statement, 169–171
 - network interface, 175–176
 - outgoing interface, 171–172
 - passive outgoing interface, 176–178
 - split horizon, 184, 187–188
 - troubleshooting, 169
 - VLSM, 182–184
 - RIP routes, 86
 - blocked routes, 91–93
 - broken multicast capability, 96–98
 - down network interface, 93–94
 - down outgoing interface, 89–91
 - misconfigured neighbor statement, 99–100
 - missing network statement, 87–89
 - passive outgoing interface, 95–96
 - split horizon, troubleshooting, 102, 105–106
 - VLSM routes, troubleshooting, 100–102
- Advertising Router field
 - OSPF link-state request packets, 300
 - LSAs, 303
- AFI (address family identifier), 42
- aggregate-address command, configuring BGP route origination, 747–749
- Area 0, 315
- Area ID field (OSPF packets), 297
- areas, 315–318
 - IS-IS, 536–537
 - hierarchical routing, 541
 - normal, 319
- NSSAs, 321–324
 - configuring, 322–324
 - default routes, 326–327
 - filtering Type 7 LSAs, 326
 - injecting external routes, 325–326
 - totally NSSAs, 324–326
- stub, 319–320
- totally stubby, 321
- ARP (Address Resolution Protocol), 5
- AS (autonomous system), 659
 - confederations, designing, 758–761
 - inbound traffic flows, 812
 - underutilized links, 813–818
 - outbound IP traffic flows, 790
 - asymmetrical routing, 802–806
 - dual-homed connections, 798–802
 - reachability, 795–798
 - single exit point, 791–795
- AS confederations, 711–712
- AS_PATH attribute
 - filtering, 835
 - policy control, 682, 684–685
- AS_SEQUENCE attribute, 685
- AS_SET attribute, 685
- ASBR (autonomous system boundary router), 660
 - assert mechanism, 640
 - PIM dense mode, 631–632
- assigning default IGRP metric for redistribution, 191–194
- asymmetrical routing, 802–806
- Attached Bit field (LSPs), 554
- Attached Router field (Network LSAs), 307
- ATTEMPT state, OSPF neighbors, 336
 - getting stuck, 383–386
- attributes (BGP)
 - AS_PATH
 - filtering, 835
 - policy control, 682–685
 - COMMUNITIES, policy control, 697–699
 - interpreting from command output, 688–690
 - LOCAL_PREF policy control, 675–676
 - MED
 - infinite setting, 777
 - policy control, 677–682
 - NEXT_HOP, policy control, 685
 - ORIGIN, policy control, 685

- authentication
 - IS-IS, 548
 - keys, 69
 - null authentication, 364
 - RIP, 42
- Authentication field (OSPF packets), 297
- auto-cost reference-bandwidth command, 305
- Autonomous System Number field, EIGRP packets, 216
- autosummarization
 - EIGRP, 219–220
 - IP routes into Level 1/Level2, 573–574
 - missing RIP subnetted routes, 106–109
 - RIP, 43
- AuType field (OSPF packets), 297
- avoiding routing loops, split horizon, 130

B

- backbone
 - indication LSAs, 332–333
 - IS-IS networks, 537
 - virtual links, 316–318
- Backup Designated Router field, OSPF Hello packets, 299
- backup interface command, 194
- backup links, dialup, 194–198
- Bad LSA type error messages, 529
- bandwidth, calculating IGRP metric, 128–129
- behavior, IGRP, 131
- best-path calculation, 661, 668
 - BGP, 820–827
 - BGP-4, 713–716
 - IS-IS SPF algorithm, 558
- BGP-4 (Border Gateway Protocol), 659
 - AD, 661
 - advertising routes, 668–670
 - AS confederations, 711–712
 - AS-PATH, filtering, 835
 - attributes, interpreting from command output, 688–690
 - best-path calculation, 661, 713–716, 820
 - selection of lowest MED value, 824–827
 - selection of wrong path, 821–823
 - cold potato, 661
 - confederations, designing, 758–761
 - EBGP multihop, misconfiguration, 736–740
 - Established state, 663
 - extended access lists, unfiltered masked routes, 831–835
 - external neighbor relationships
 - incorrect IP address assignment, 731–732
 - IP connectivity, 728
 - Layer 2 problems, 729–731
 - nondirectly connected, 732–733
 - hot potato, 661
 - inbound traffic flows, 812
 - underutilized links, 813–818
 - internal neighbor relationships, route propagation, 754–762
 - load balancing, dual-homed outbound traffic, 806–812
 - neighbor relationships, 663–664, 659
 - advertised routes, 726
 - external, 665–667
 - internal, 667
 - statistics, displaying, 726
 - nondirectly connected external neighbor relationships, missing routing table addresses, 733–736
 - peers, 659–660
 - policies, 661
 - policy control, 672–674
 - AS_PATH attribute, 682–685
 - communities, 697–699
 - distribute lists, 695–696
 - filter lists, 695
 - LOCAL_PREF attribute, 675–676
 - MED attribute, 677–682
 - NEXT_HOP attribute, 685
 - ORF, 700–702
 - ORIGIN attribute, 685
 - prefix lists, 696
 - route maps, 690–694
 - WEIGHT knob, 686–688
 - policy routing, outbound IP traffic flows, 790–806
 - private peering, 660
 - protocol specifications, 662
 - public peering, 660
 - RFC 1771, 662
 - route dampening, 702–706

- route origination
 - classful network advertisements, 749–751
 - misconfiguration, 746–749
 - misconfigured distribute lists, 752–754
 - missing routing table entries, 743–746
- route reflection, 707–711, 778
 - client-to-client reflection, 780–782
 - identical cluster IDs, 785, 788–790
 - misconfiguration, 779–780
 - peer groups, 783–785
- routing table
 - uninstalled EBGp-learned routes, 771–777
 - uninstalled IBGP-learned routes, 763–771
- standard access lists, unfiltered subnets, 828–830
- synchronization rule, 671–672
- synchronization, disabling, 766
- BGP feed, 659
- Bit B field (router LSAs), 305
- Bit E field (external LSAs), 313
- Bit E field (router LSAs), 304
- Bit V field (router LSAs), 304
- black holes, 671–672
- boundaries, EIGRP queries, 220
- broadcast addresses, 12
- broadcast capability, unadvertised IGRP routes, 178–180
- broadcast links, IS-IS, 536
- broadcast mode (NBMA), 329–330

C

- calculating
 - best paths
 - BGP-4, 713–716
 - IS-IS SPF algorithm, 558
 - EIGRP metrics, 208–209
 - IGRP metric, 127
 - bandwidth variable, 128–129
 - delay variable, 128–129
- case study, IS-IS configuration, 619–622

- causes of uninstalled RIP routes
 - access lists blocking RIP broadcast, 63–65
 - access lists blocking source address, 60–63
 - discontiguous networks, 71–74
 - distribute list incoming routes, 58–60
 - equal cost paths, 83–86
 - hop count exceeded, 81–83
 - incompatible RIP version, 65–68
 - incorrect network statement, 53–56
 - invalid source, 74–76
 - Layer 1/2 down, 56–58
 - Layer 2 problems, 76–78
 - mismatched authentication key, 68–71
 - offset value too high, 79–81
- characteristics
 - normal areas, 319
 - NSSAs, 322
 - stub areas, 320
 - totally stubby areas, 321
- Checksum field
 - EIGRP packets, 216
 - IGMP packets, 636
 - LSPs, 554
 - OSPF packets, 297
- checksum operation, LSAs, 303
- CIDR (Classless Interdomain Routing), 7, 10
- classes of IP addresses, 5–7
- classful networks
 - masks, 8
 - redistribution into BGP, 749–751
 - subnetting, 8
- classful routing protocols, 29
 - versus classless, 15
- classless addressing, 7
 - CIDR, 10
- classless routing protocols versus classful, 15
- clear isis command, 587
- clients, route reflection, 757
- client-to-client reflection, 780–782
- CLNP (Connectionless Network Protocol), 534, 586
 - addressing, 548
 - IS-IS, 586
 - NSAPs, format, 549–551
 - NSAPs, defining, 551
- CLNS (connectionless network services), 533

- clusters
 - identical cluster IDs between RR, 785, 788–790
 - route reflector client/servers, designing, 757–758
- cold potato routing, 661, 682
- commands
 - aggregate-address, configuring BGP route origination, 747–749
 - auto-cost reference-bandwidth, 305
 - backup interface, 194
 - clear isis, 587
 - debug ip bgp update, 727
 - debug ip bgp updates, 727
 - debug ip rip, 35, 55
 - ip default-network, 132, 221
 - ip summary-address eigrp, 219
 - match as_path, implementing in route maps, 692–693
 - match community, implementing in route maps, 692
 - match ip address, implementing in route maps, 691
 - output, interpreting BGP attributes, 688, 690
 - ping clns, 617–619
 - set as-path prepend, implementing in route maps, 693
 - set community, implementing in route maps, 693
 - set local preference, implementing in route maps, 694
 - set metric command, implementing in route maps, 694
 - show clns interface, 564, 586
 - show clns neighbors, 586
 - show clns neighbors detail, 563
 - field definitions, 588
 - show clns protocol, 562–563
 - show ip bgp, 726
 - show ip bgp neighbor, 726
 - show ip bgp neighbors, 726–727
 - show ip bgp summary, 726
 - show ip eigrp neighbor, 210
 - show ip eigrp topology active, 242–245
 - show ip protocols, 56
 - show ip route, 12, 56, 134, 142
 - show isis database, 586
 - show isis topology, 565, 586
 - timers basic, 130
 - traceroute, 617–619
 - variance, 133–134, 221–223
- communities, BGP-4 policy control, 697–699
- comparing
 - classless and classful routing protocols, 15
 - interior and exterior gateway protocols, 15, 17–18
 - IPv4 and IPv6, 5
 - link-state and distance vector protocols, 18
 - TCP/IP and OSI reference model, 3
 - Type 7 and Type 5 LSAs, 322
- confederations (BGP), designing, 758–761
- configuring
 - EIGRP manual summarization, 219
 - IS-IS
 - ATM connectivity, 566–568
 - autosummarization, 573–574
 - case study, 619–622
 - default route advertisement, 569
 - IP routing, 560, 566–573
 - redistribution, 570–573
 - routing on point-to-point links, 559–566
 - NSSA areas, 322–324
 - virtual links, 316–318
- Connect state (BGP-4), 663
- connectivity
 - external BGP neighbor relationships, 728
 - IS-IS
 - adjacencies, 587–605
 - ping clns command, 617–619
 - traceroute command, 617–619
- constant SPF calculations in OSPF networks, troubleshooting, 518–528
- convergence, 129
 - BGP networks, peer groups, 783–785
 - diffused computation, 213
 - distance vector protocols, 19–20
 - EIGRP, 207
 - query process, 220
 - local computation, 213
- cost
 - IS-IS default metric, 546
 - OSPF metric calculation, overriding, 305
 - “could not allocate route id” error messages, 529

count to infinity, 29
 distance vector protocols, 21
 CPU utilization, displaying IS-IS statistics, 613–615
 CPUHOG messages, OSPF, 499–503
 CSNP Interval timer, IS-IS link-state database, 557
 CSNPs (complete sequence number packets), 556

D

dampening routes, modifying parameters, 771–774
 data-forward process, addressing, 4
 datagram delivery service model, 3
 DBD (Database Description) packets, OSPF, 299
 Sequence Number field, 300
 DC bit, 332
 DDR (dial-on-demand routing)
 IGRP, 194
 dial backup, 194–198
 OSPF, 503–516
 RIP, 116–122
 debug ip bgp update command, 727
 debug ip bgp updates command, 727
 debug ip rip command, 35, 55
 debugging SPF problems (IS-IS), 615–616
 decision process, IS-IS SPF algorithm, 558
 default routes
 EIGRP, 221
 IGRP, 132–133
 unadvertised candidates, 188–191
 OSPF
 unadvertised, 450–462
 NSSAs, 326–327
 RIP, 39–40
 unadvertised, 450–462
 defining
 metric for IGRP redistribution, 191–194
 NSAPs, 551
 delay, calculating IGRP metric, 128–129
 delay metric, IS-IS, 546
 demand circuits (OSPF), 331–334
 dense mode (PIM), 625, 630–631
 assert mechanism, 631–632
 prune mechanism, 631
 troubleshooting, 646–651
 Designated Router field (OSPF Hello packets), 299
 designing
 BGP confederations, 758–761
 route reflector model, 757–758
 devices
 interfaces, link-based addressing, 5
 Layer 2 media, troubleshooting uninstalled
 IGRP routes, 161–163
 dial backup
 EIGRP, 286–290
 IGRP, 194–198
 diffused computation, 213
 Dijkstra algorithm, 295
 direct inspection of LSPs, 606–607
 directed broadcasts, 12
 directly connected external BGP neighbors, IP
 connectivity, 728–729
 DIS (designated intermediate system), 539
 disabling BGP synchronization, 766
 discontinuous networks
 EIGRP, 252–253
 routing behavior, 218–219
 RIP, 36–37
 troubleshooting route installation, 71–74
 uninstalled IGRP routes, 155–158
 displaying
 BGP neighbor statistics, 726
 IS-IS CPU utilization statistics, 613–615
 IS-IS link-state database, 565
 IS-IS topology, 565
 prefixes, assigned attributes, 726
 distance vector protocols
 convergence, 19–20
 counting to infinity, 21
 holddown, 21
 IGRP, 133–134
 behavior, 131
 default routes, 132–133
 defining metric for redistribution,
 191–194
 dial backup links, 194–198
 flapping routes, 198–201
 metrics, 127–129
 packets, 131
 split horizon, 130
 split horizon with poison reverse, 130

- timers, 129–130
 - unadvertised default route candidates,
 - troubleshooting, 188–191
 - uninstalled equal-cost paths,
 - troubleshooting, 166–168
 - uninstalled routes, troubleshooting,
 - 142–188
 - variance, 201–204
 - loop avoidance, 20–21
 - metrics, 19
 - periodic updates, 22
 - poison reverse, 22
 - RIP
 - authentication, 42
 - compatibility issues, 43
 - DDR, 116, 118–122
 - default routes, 39–40
 - discontiguous networks, 36–37
 - flapping routes, 122–124
 - multicast, 42
 - Next Hop fields, 41
 - packet behavior, 31
 - receiving updates, 33–35
 - redistribution, 113–116
 - route advertisements, 86–106
 - passive outgoing interface, 96
 - route tag field, 40–41
 - route installation, 52–85
 - sending updates, 31–33
 - split horizon, 30
 - with poison reverse, 31
 - subnet masks, 41
 - summarization, 109–113
 - timers, 30
 - uninstalled routes, 52
 - version field, 43
 - VLSM, 37–39
 - split horizon, 22
 - triggered updates, 22
 - versus link-state, 18
 - distribute lists, 58
 - BGP-4
 - misconfiguration, 752–754
 - policy control, 695–696
 - blocked routes, troubleshooting, 91–93
 - IGRP uninstalled routes, 149–150
 - incoming routes, blocked RIP route installation,
 - 58–60
 - misconfiguration, 251–252
 - unadvertised IGRP routes, troubleshooting,
 - 173–174
 - dotted-decimal notation, IP address representation, 7
 - Down state, OSPF neighbors, 335
 - Doyle, Jeff, 214
 - dropped packets, IGRP, 199–201
 - DRs (designated routers), network LSAs, 307–308
 - DUAL (Diffusing Update Algorithm), 207, 211,
 - 240–241
 - active routes, 213
 - FC, 211
 - FD, 211
 - FSM, 213–214
 - feasible successors, 212
 - passive routes, 213
 - RD, 211
 - successors, 211
 - dual addressing scheme, IS-IS, 586
 - dual homing
 - load balancing, 806–812
 - outbound BGP traffic flows, 798–802
 - duplicate router IDs, EIGRP, 268–270
 - dynamic routing, 4, 11
 - classless versus classful, 15
 - interior versus exterior gateway, 15–18
 - link-state versus distance vector protocols, 18
 - multicast versus unicast, 12–14
 - versus static routing, 11
- ## E
-
- EBGP (External BGP), 660
 - multihop
 - misconfiguration, 736–740
 - resolving nondirectly connected neighbor relationships, 732
 - unreachable next hop, 774–777
 - underutilized links between two ASes, 813–818
 - uninstalled routes, 771
 - dampened BGP routes, 771–774
 - infinite MED value, 777

- EGP (exterior gateway protocol), 659
- EIGRP (Enhanced Interior Gateway Routing Protocol), 17, 207
 - convergence, 207
 - diffused computation, 213
 - local computation, 213
 - default routes, 221
 - dial backup, 286–290
 - DUAL, 207, 211, 240–241
 - active routes, 213
 - FC, 211
 - FD, 211
 - feasible successors, 212
 - passive routes, 213
 - RD, 211
 - successors, 211
 - error messages, 291
 - hold time, 209
 - metrics, 208–209
 - neighbor relationships, 209–210, 227
 - log, reviewing, 228–229
 - mismatched AS numbers, 239
 - mismatched k values, 237
 - mismatched masks, 235–237
 - one-way, 230–232
 - SIA errors, 240–250
 - uncommon subnets, 233–235
 - packets, TLV, 216–217
 - redistribution, 280–286
 - reliable packets, 214
 - route advertisement, 250
 - discontiguous networks, 252–253
 - misconfigured distribute lists, 251–252
 - split-horizon, 253–256
 - unexpected advertisements, 257–259
 - unexpected metrics, 259–263
 - route flapping, 271–275
 - route installation, 264–270
 - route summarization, 276–280
 - routing behavior, 218–219
 - RTP, 214
 - summarization, 219–220
 - unequal-cost load balancing, 221–223
- empty neighbor lists, OSPF, 351–383
- empty routing tables (IGRP), troubleshooting, 142–166
- Enhanced Interior Gateway Routing Protocol.
See EIGRP
- equal-cost paths, route installation
 - IGRP, 166–168
 - RIP, 83–86
- error messages, EIGRP, 291
- error metric, IS-IS, 546
- ES-IS (End System-to-Intermediate System), 589
 - adjacencies, 538
 - misidentification in IS-IS networks, 605
- Established state (BGP-4), 663–664
 - route advertisements, 668–670
 - synchronization rule, 671–672
- establishing IGRP dial backup, 194–198
- Exchange state, OSPF neighbors, 337
 - getting stuck, 401–417
- expense metric, IS-IS, 546
- Exstart state, OSPF neighbors, 336
 - getting stuck, 401–417
- extended access lists
 - BGP filtering, unfiltered masked routes, 831–835
 - debug ip bgp update command output, 727
 - uninstalled IGRP routes, troubleshooting, 151–155
- exterior gateway protocols, versus interior, 15–18
- external LSAs (Type 5), 302, 313–315
- external metrics, IS-IS, 547
- external neighbor relationships, BGP-4, 665–667
 - incorrect IP address assignment, 731–732
 - IP connectivity, 728
 - Layer 2 problems, 729–731
 - nondirectly connected, 732–733
 - misconfiguration, 736–740
 - missing routing table addresses, 733–736
- external routes
 - injecting into NSSAs, 325–326
 - OSPF, unadvertised, 441–449
 - redistribution into IS-IS, 570–573
 - summarization, 497–499
 - uninstalled, 479–487

F

- FC (feasible condition), 211
- FD (feasible distance), 211
- feasible successor routes, 17, 212
- field definitions
 - EIGRP packets, 216–217
 - external LSAs, 313
 - IGMP packets, 635
 - IS-IS packets, TLVs, 543–545
 - LSP headers, 553–555
 - show clns neighbors command output, 588
 - OSPF
 - Hello packets, 298–299
 - LSA headers, 303–304
 - packets, 296
 - summary LSAs, 310
- filter lists, BGP-4 policy control, 695
- filtering traffic
 - BGP traffic
 - AS_PATH, 835
 - unfiltered masked routes, 831–835
 - unfiltered subnets, 828–830
 - extended access lists, troubleshooting
 - uninstalled IGRP routes, 151–155
 - Type 7 LSAs, 326
- Flags field (EIGRP packets), 216
- flapping routes
 - dampening, 702–706
 - EIGRP, 271–275
 - IGRP, 198–201
 - IS-IS, 612–616
 - RIP, 122–124
- flooding, 552
 - IS-IS, 555–557
- flush timers
 - IGRP, 130
 - RIP, 30
- format of NSAPs, 549–551
- Forwarding Address field (External LSAs), 313
- forwarding packets
 - high-speed, 25
 - multicast, 12–14
- full feed, 659
- Full state, OSPF neighbors, 338

G

- gateway of last resort, IGRP, 188
- generating default summary routes, 326–327
- generic format, IS-IS packets, 543–545
- Group Address field, IGMP packets, 636

H

- headers
 - LSAs, 303–304
 - LSPs, 553–555
 - OSPF packets, 296
- Hello Interval field, OSPF Hello packets, 298
- hellos
 - IIHs, 538–539
 - OSPF, 297–299
- hierarchical Route-Reflection, 709
- hierarchical routing, IS-IS, 541
- hold time
 - BGP-4, 663
 - EIGRP, 209
- holddown, distance vector protocols, 21
- hold-down timers
 - IGRP, 130
 - RIP, 30
- hop count, 29
 - troubleshooting RIP route installation, 81–83
- hop-by-hop destination-based forwarding
 - mechanism, 4
- hot potato, 661
- hybrid routing protocols, EIGRP, 207
 - convergence, 207
 - default routes, 221
 - DUAL, 207, 211–213
 - IP Internal Route TLV (EIGRP), 216–217
 - metrics, 208–209
 - neighbor relationships, 209–210
 - packet fields, 216–217
 - query process, 220
 - routing behavior, 218–219
 - RTP, 214
 - summarization, 219–220
 - unequal-cost load balancing, 221–223

- I Bit field (OSPF DBD packets), 299
- IBGP (Internal BGP), 660
 - AS confederations, 711–712
 - black holes, 671–672
 - neighbor relationships
 - client-to-client reflection, 780–782
 - misconfiguration, 779–780
 - route reflection, 707–711
 - uninstalled routes, 763–766
 - unreachable next-hops, 766–771
- identical cluster IDs in RR session, troubleshooting, 785, 788–790
- identifying routers attached to transit links, 308
- Idle state (BGP-4), 663
- IETF standardization of IS-IS, 535
- IGMP (Internet Group Management Protocol)
 - version 1, 626
 - version 2, 627
 - joins, 643–645
 - leave mechanism, 627–628
 - packets, 635
 - querier election mechanism, 627
- IGRP (Interior Gateway Routing Protocol)
 - behavior, 131
 - DDR, 194
 - dial backup links, 194–198
 - default routes, 132–133
 - intermediate media problems, 142
 - load balancing, 168
 - metrics, 127–129
 - packets, 131
 - redistribution
 - into NSSA area, 321
 - metric, defining, 191–194
 - route flapping, 198–201
 - route installation, 142–166
 - split horizon, 130
 - split horizon with poison reverse, 130
 - timers, 129–130
 - unadvertised default route candidates, 188–191
 - unequal-cost load balancing, 133–134
 - uninstalled equal-cost paths, 166–168
 - uninstalled routes, sender problems, 142, 168–188
 - variance, 201–204
- IIHs (intermediate system-to-intermediate system hellos), 538–539
- improving BGP network convergence, 783–785
- inbound BGP traffic flows, 812
 - underutilized links, 813–818
- incompatible RIP versions, troubleshooting RIP route installation, 65–68
- incorrect network statements, RIP route installation, 53–56
- indication LSAs, 332–333
- INIT state, 336
 - getting stuck, 382, 387–398
 - IS-IS adjacencies, 596–605
- injecting external routes into NSSAs, 325–326
- installing RIP routes, 52
 - access lists
 - blocked RIP broadcast, 63–65
 - blocked source addresses, 60–63
 - discontiguous networks, 71–74
 - distribute lists, blocked RIP routes, 58–60
 - equal-cost paths, 83–86
 - hop count exceeded, 81–83
 - incompatible RIP version, 65–68
 - incorrect network statements, 53–56
 - invalid sources, 74–76
 - Layer 2 problems, 76–78
 - line protocols, down state, 56–58
 - mismatched authentication key, 68–71
 - offset list value too high, 79–81
- Integrated IS-IS. *See* IS-IS
- interarea routes, summarization, 495–496
- interesting traffic, 117
- Interface MTU field, OSPF DBD packets, 299
- interfaces
 - link-based addressing, 5
 - oilist, 630–631
- Interior Gateway Protocols
 - EIGRP, 17
 - versus exterior, 15–18
- intermediate media problems, 142
- internal metrics, IS-IS, 547
- internal neighbor relationships
 - BGP-4, 667
 - route propagation, 754–761
 - synchronization, 761–762
 - unintentional TCP packet blockages, 741–742

- interpreting BGP attributes from command output, 688–690
- Invalid lsa error messages, 529
- invalid sources, troubleshooting uninstalled routes
 - IGRP, 159–161
 - RIP, 74–76
- invalid timers
 - IGRP, 129
 - RIP, 30
- IP addressing
 - broadcast addresses, 12
 - CIDR, 10
 - dynamic routing, 11
 - classless versus classful routing protocols, 15
 - interior versus exterior gateway, 15–18
 - link-state versus distance vector protocols, 18–24
 - unicast versus multicast routing, 12–14
 - subnets, 12
- ip default-network command, 132, 221
- IP Internal Route TLV (EIGRP), 216–217
- IP network numbers, 6
- IP prefix, 659
- IP routing, IS-IS configuration, 560, 566–573
 - ATM connectivity, 566–568
 - autosummarization, 573–574
 - default route advertisement, 569
 - point-to-point links, 559–566
 - redistribution, 570–573
- ip summary-address eigrp command, 219
- IPv4
 - address classes, 5–7
 - private address space, 7–8
 - subnetting, 8
 - versus IPv6, 5
- IS Type field (LSPs), 555
- IS-IS (Intermediate System-to-Intermediate System), 533–535
 - adjacencies, 538–540, 587–589
 - absence of, 590–596
 - INIT state, 596–605
 - misidentified ES-IS adjacencies, 605
 - three-way reliable, 540
 - areas, 536–537
 - authentication, 548
 - backbone, 537
 - broadcast links, 536
 - CLNP addressing, 548, 586
 - NSAP format, 549–551
 - NSAPs, defining, 551
 - DIS, 539
 - errors, 616–617
 - external routes, redistribution to Level 1, 611
 - flapping routes, 612–616
 - flooding, 552
 - hierarchical routing, 541
 - IETF standardization, 535
 - IP routing
 - ATM configuration, 566–568
 - autosummarization, 573–574
 - configuring, 560, 566–573
 - default route advertisement, 569
 - point-to-point links, 559–566
 - redistribution, 570–573
 - level 1, 535
 - links, 536–537
 - link-state database, 552–555
 - displaying, 565
 - flooding, 555–557
 - synchronization, 555–557
 - update timers, 556–557
 - LSPs, header fields, 553–555
 - metrics, 545–548
 - external, 547
 - internal, 547
 - nodes, 536–537
 - NSAPs, 536
 - packets, 542
 - generic format, 543–545
 - PDU, 542
 - ping clns command, 617–619
 - point-to-point links, 536
 - PSN, 539
 - route advertisements, misconfiguration, 607–611
 - routing domains, 536
 - routing updates, 606–607
 - SNPs, 556
 - SPF algorithm, 558
 - triggers, 614–615
 - traceroute command, 617–619
 - update process, 555

ISO CLNS (International Organization for Standardization Connectionless Networking Services)

- CLNP, 534
- IS-IS, 533–535
 - adjacencies, 537
 - areas, 536–537
 - ATM configuration, 566–568
 - autosummarization, 573–574
 - backbone, 537
 - broadcast links, 536
 - CLNP addressing, 548–551
 - default route advertisement, 569
 - DIS, 539
 - ES-IS adjacencies, 538
 - flooding, 552
 - header fields, 553–555
 - hierarchical routing, 541
 - IETF standardization, 535
 - IP routing configuration, 559–573
 - IS-IS adjacencies, 538–540
 - Level 1, 535
 - links, 536–537
 - link-state database, 552–557
 - metrics, 545–548
 - nodes, 536–537
 - NSAPs, 536
 - packets, 542–545
 - point-to-point links, 536
 - PSN, 539
 - redistribution, 570–573
 - routing domains, 536
 - SPF algorithm, 558
 - three-way reliable adjacencies, 540
 - update process, 555
- SNPs, 556
- ISPs, BGP-4 659
 - advertising routes, 668–672
 - best path calculation, 713–716
 - external neighbor relationships, 665–667
 - internal neighbor relationships, 667
 - neighbor relationships, 663–664
 - policy control, 672–688
 - protocol specifications, 662
 - route dampening, 702–706
- IXP (Internet Exchange Point), 660

J-K-L

- join mechanism
 - IGMP version2, 627–628, 643–645
 - PIM sparse mode, 633
- knobs, policy control, 686–688
- Layer 1 (OSI), IGRP uninstalled routes, 147–149
- Layer 2 (OSI)
 - connectivity between external BGP neighbors, 729–731
 - IGRP uninstalled routes, 161–163
 - RIP route installation, 76–78
- layered protocol suites, TCP/IP, 3
- leave mechanism, IGMP version 2, 627–628
- Length field (LSAs), 304
- Level 1 LAN ITHs, 539
- Level 2 LAN ITHs, 539
- line protocols
 - RIP route installation, 56–58
 - uninstalled IGRP routes, troubleshooting, 147–149
- Link Data field (router LSAs), 305
- link flaps, 506
- Link ID field (router LSAs), 305
- link-based addressing, 5
- links
 - IS-IS, 536–537
 - OSPF, 305
- link-state acknowledgment packets (OSPF), 301
- link-state database (IS-IS), 552–555
 - displaying, 565
 - flooding, 555–557
 - synchronization, 555–557
 - update timers, 556–557
- Link-State ID field
 - LSAs, 303
 - OSPF link-state request packets, 300
- link-state protocols, 23
 - IS-IS, 533, 535
 - adjacencies, 537, 587–605
 - areas, 536–537
 - ATM configuration, 566–568
 - authentication, 548
 - autosummarization, 573–574
 - backbone, 537

- broadcast links, 536
- CLNP addressing, 548–551, 586
- configuring, case study, 619–622
- confusion with ES-IS adjacencies, 605
- default route advertisement, 569
- DIS, 539
- displaying CPU utilization statistics, 613–615
- errors, 616–617
- ES-IS adjacencies, 538
- external routes, redistribution into Level 1, 611
- flapping routes, 612–616
- flooding, 552
- header fields, 553–555
- hierarchical routing, 541
- IETF standardization, 535
- IP routing configuration, 559–573
- IS-IS adjacencies, 538–540
- Level 1, 535
- links, 536–537
- link-state database, 552–557
- metrics, 545–548
- nodes, 536–537
- NSAPs, 536
- packets, 542–545
- ping clns command, 617–619
- point-to-point links, 536
- PSN, 539
- redistribution, 570–573
- route advertisements, 607–611
- routing domains, 536
- routing updates, 606–607
- SNPs, 556
- SPF algorithm, 558
- SPF process triggers, 614–615
- three-way reliable adjacencies, 540
- traceroute command, 617–619
- update process, 555
- metrics, 24
- OSPF, 295
 - “%OSPF-4-BADLSATYPE error messages, 529
 - adjacencies, 334–338
 - areas, 315–320
 - constant SPF calculations, troubleshooting, 518–528
 - “could not allocate route id” error messages, 529
 - CPUHOG messages, 499–503
 - DDR, 503–516
 - debugs, CPU utilization, 341
 - demand circuits, 331–334
 - Dijkstra algorithm, 295
 - empty neighbor lists, 351–383
 - external LSAs, 313–315
 - LSAs, 302–304
 - multiaccess media, 327–328
 - NBMA media, 329–331
 - network LSAs, 307–308
 - NSSAs, 321–326
 - null authentication, 364
 - “OSPF-4-ERRRCV” error messages, 529–531
 - packets, 295–301
 - point-to-point media, 328
 - redistribution, 488–494
 - router LSAs, 304–306
 - Stuck in 2-WAY state, 398–400
 - Stuck in ATTEMPT state, 383–386
 - Stuck in EXSTART/EXCHANGE state, 401–417
 - Stuck in INIT, state, 387–398
 - Stuck in LOADING state, 417–422
 - summarization, 494–499
 - summary LSAs, 309–312
 - totally stubby areas, 321
 - unadvertised default routes, 450–462
 - unadvertised external routes, 441–449
 - unadvertised routes, troubleshooting, 422–429, 431
 - unadvertised summary routes, 432–440
 - uninstalled external routes, 479–487
 - uninstalled routes, 463–478
 - “unknown routing protocol” error messages, 528
 - virtual links, 316–317
 - versus distance vector, 18
 - link-state request packets (OSPF), 300
 - link-state update packets (OSPF), 301

- load balancing
 - dual-homed outbound BGP traffic, 806–812
 - IGRP, 168
 - uninstalled equal-cost paths, 166–168
 - variance, 201–204
- Loading state, OSPF neighbors, 338
 - getting stuck, 417–422
- local computation, 213
- LOCAL_PREF attribute, policy control, 675–676
- loop avoidance, distance vector protocols, 20–21
- loopback interfaces, BGP peering, 732–733
- LS Age field (LSAs), 303
- LS Checksum field (LSAs), 303
- LS Sequence Number field (LSAs), 303
- LS Type field (OSPF link-state request packets), 300
- LS Type field (LSAs), 303
- LSA Header field (OSPF DBD packets), 300
- LSAs, 295, 302–303
 - external LSAs (Type 5), 313–315
 - header fields, 303–304
 - indication LSAs, 332–333
 - network LSAs (Type 2), 307–308
 - NSSA, P bit, 324
 - periodic, 332
 - router LSAs (Type 1), 304–306
 - summary LSAs (Type 3/4), 309–312
 - fields, 310
 - Type 7, filtering, 326
- LSP Database Overload Bit field (LSPs), 555
- LSP Identifier field (LSPs), 553
- LSP number field (LSPs), 554
- LSP Refresh Interval timer, IS-IS link-state database, 557
- LSP Retransmit Interval timer, IS-IS link-state database, 557
- LSPs (link-state packets), 553
 - direct inspection, 606–607
 - flooding, 552, 555–557
 - header fields, 553–555
 - TLVs, 547
 - Transmission Interval timer, 557

M

- M Bit field, OSPF DBD packets, 299
- manual summarization, EIGRP, 219–220
- masks, 8
- match as_path command, implementing in route maps, 692–693
- match community command, implementing in route maps, 692
- match ip address command, implementing in route maps, 691
- Maxage timer, IS-IS link-state database, 556
- Maximum Response Time field, IGMP packets, 636
- MED (multi-exit discriminator) attribute
 - best-path selection, 824–827
 - infinite value, 777
 - policy control, 677–682
- media independence of IP addressing, 5
- media types
 - Layer 2, uninstalled IGRP routes, troubleshooting, 161–163
 - OSPF
 - demand circuits, 331–334
 - multiaccess media, 327–328
 - NBMA media, 329–331
 - point-to-point media, 328
- messages
 - “%OSPF-4-BADLSATYPE
Invalid lsa Bad LSA type”, 529
 - “could not allocate route id”, 529
 - CPUHOG (OSPF), 499–503
 - “OSPF-4-ERRRCV”, 529–531
 - “unknown routing protocol”, 528
 - PIM, 638–640
- Metric field (router LSAs), 305
- metric field (summary LSAs), 310
- metrics, 29–30
 - cost (OSPF), overriding, 305
 - distance vector protocols, 19
 - EIGRP, 208–209
 - IGRP, 127–129
 - defining for redistribution, 191–194
 - IS-IS, 545–548
 - link-state protocols, 24

misconfiguration

- access lists, troubleshooting uninstalled IGRP routes, 149–155
- BGP
 - distribute lists, 752–754
 - neighbor addresses, 731–732
 - route origination, 746–749
- IS-IS
 - adjacencies, 589–605
 - case study, 619–622
 - redistribution, 611
 - route advertisements, 607–611
- neighbor statements, 99–100
 - unadvertised IGRP routes, 180–181
- network statements, unadvertised IGRP routes, 169–171
- route reflection
 - IBGP neighbors, 779–780
 - identical cluster IDs, 785–790
- routers, troubleshooting uninstalled IGRP routes, 143–146
- mismatched AS numbers (EIGRP), 239
- mismatched authentication key, troubleshooting RIP
 - route installation, 68–71
- mismatched K values, EIGRP, 237
- mismatched masks, EIGRP, 235–237
- mismatched sender AS number, troubleshooting
 - uninstalled IGRP routes, 163–166
- modifying BGP dampening parameters, 771–772, 774
- MS Bit field, OSPF DBD packets, 300
- multiaccess media, OSPF networks, 327–328
- multicast, 625
 - IGMP
 - joins, 643–645
 - leave mechanism, 627–628
 - packet format, 635
 - querier election mechanism, 627
 - version 1, 626
 - version 2, 627
 - PIM
 - dense mode, 625, 630–632, 646–651
 - messages, 638–640
 - packets, 636–638
 - sparse mode, 625, 632–634, 651–656
 - RIP addresses, 42
 - RPF, 628–630

multicast routing, versus unicast, 12–14

multihoming, 552, 660

N

NBMA media, OSPF networks, 329

- broadcast mode, 329–330
- point-to-multipoint mode, 331
- point-to-point mode, 330

Neighbor field (OSPF Hello packets), 299

neighbor relationships

- BGP-4, 663–664
 - external, 665–667
 - external, incorrect IP address assignment, 731–732
 - internal, 667
- route advertisements, 668–672

EIGRP, 209–210, 227

- mismatched AS numbers, 239
- mismatched K values, 237
- mismatched masks, 235–237
- one-way, 230, 232
- reviewing documented changes, 228–229
- SIA error, 240–250
- uncommon subnets, 233–235

external (BGP)

- IP connectivity, 728
- Layer 2 problems, 729–731

IBGP, client-to-client reflection, 780–782

internal

- misconfiguration, 779–780
- route propagation, 754–762
- unintentional TCP packet blockages, 741–742

OSPF

- 2-way state, 336
- Attempt state, 336
- Down state, 335
- empty neighbor lists, 351–383
- ES-IS, 538
- Exchange state, 337
- Exstart state, 336
- Full state, 338
- Init state, 336
- IS-IS, 538–540

- Loading state, 338
- Stuck in 2-WAY state, 398–400
- Stuck in ATTEMPT, 383–386
- Stuck in EXSTART/EXCHANGE state, 401–417
- Stuck in INIT, 387–398
- Stuck in LOADING state, 417–422
- unadvertised default routes, 450–462
- unadvertised external routes, 441–449
- unadvertised summary routes, 432–440
- network convergence time, 129
- network interfaces, unadvertised IGRP routes, troubleshooting, 175–176
- network LSAs (Type 2), 302, 307–308
- Network Mask field
 - External LSAs, 313
 - Network LSAs, 307
 - OSPF hello packets, 298
 - summary LSAs, 310
- Next Hop field (RIP packets), 41
- NEXT_HOP attribute, policy control, 685
- nodes, IS-IS, 536–537
- nondirectly connected external BGP neighbor relationships, 732–733
 - misconfiguration, 736–740
 - missing routing table addresses, 733–736
- normal areas, 319
- NSAPs (network service access points), 536
 - defining, 551
 - format, 549–551
- NSSAs, 321–324
 - configuring, 322–324
 - default routes, 326–327
 - injecting external routes, 325–326
 - totally NSSAs, 324–326
 - Type 7 LSAs, 302
 - filtering, 326
 - P bit, 324
- null authentication, 364
- Null0 route, advertising, 670
- Number of Links field (router LSAs), 305

O

- octets, IP address representation, 7
- offset list values
 - troubleshooting RIP route installation, 79–81
- oolist, 630–631
- one-way neighbor relationships, EIGRP, 230–232
- Opcode field, EIGRP packets, 216
- OpenConfirm state (BGP-4), 664
- OpenSent state (BGP-4), 664
- optional capability mismatch, 370–372
- Options field
 - OSPF DBD packets, 299
 - OSPF Hello packets, 298–299
- Options field (LSAs), 303
- ORF, BGP-4 policy control, 700–702
- ORIGIN attribute, policy control, 685
- originating BGP routes
 - classful network advertisements, 749–751
 - misconfiguration, 746–749
 - misconfigured distribute lists, 752–754
 - missing routing table entries, 743–746
- OSI reference model versus TCP/IP model, 3
- OSPF, 295
 - %OSPF-4-BADLSATYPE error messages, 529
 - adjacencies, 334–335
 - 2-way state, 336
 - Attempt state, 336
 - Down state, 335
 - Exchange state, 337
 - Exstart state, 336
 - Full state, 338
 - Init state, 336
 - Loading state, 338
 - optional capability mismatches, 370–372
 - areas, 315–316, 318
 - normal, 319
 - NSSAs, 321–326
 - stub, 319–320
 - totally stubby, 321
 - backbone
 - indication LSAs, 332–333
 - virtual links, 316–317
 - “could not allocate route id” error messages, 529
 - DDR, 503–516
 - debugs, CPU utilization, 341

demand circuits, 331–334
 Dijkstra algorithm, 295
 external routes, summarization, 497–499
 link types, 305
 LSAs, 295, 302–303

- external LSAs (Type 5), 313–315
- header fields, 303–304
- network LSAs (Type 2), 307–308
- router LSAs (Type 1), 304–306
- summary LSAs (Type 3/4), 309–312

 multiaccess media, 327–328
 NBMA media, 329

- broadcast mode, 329–330
- point-to-multipoint mode, 331
- point-to-point mode, 330

 neighbor relationships

- empty neighbor lists, 351–383
- unadvertised default routes, 450–462
- unadvertised external routes, 441–449
- unadvertised summary routes, 432–440

 null authentication, 364
 “OSPF-4-ERRRCV” error messages, 529–531
 packets, 295–297

- DBD, 299
- fields, 296
- Hello, 297–299
- link-state acknowledgment, 301
- link-state request, 300
- link-state update, 301

 point-to-point media, 328
 redistribution, 488–494
 SPF calculations, 518–528
 Stuck in 2-WAY state, 398–400
 Stuck in ATEMPT, 383–386
 Stuck in EXSTART/EXCHANGE state, 401–417
 Stuck in INIT state, 387–398
 Stuck in LOADING state, 417–422
 summarization, 494–496
 unadvertised routes, 422–431
 uninstalled external routes, 479–487
 uninstalled routes, 463–478
 “unknown routing protocol” error messages, 528

outbound dual-homed BGP traffic, outbound traffic flows (BGP)

- asymmetrical routing, 802–806
- dual-homed, 798–802
 - load balancing, 806–812
- reachability, 795–798
- single exit point from AS, 791–795

 outgoing interface, unadvertised IGRP routes, troubleshooting, 171–172
 overriding OSPF metric calculation, 305

P

P bit, 324
 packet drops, IGRP, 199–201
 Packet Length field (OSPF packets), 297
 packets, 3, 533

- data-forwarding process, addressing, 4
- EIGRP
 - IP Internal Route TLV, 216–217
 - Q count, 232
 - query process, 220
 - reliable, 214
 - TLV, 216–217
- forwarding, high-speed, 25
- hop-by-hop destination-based forwarding, 4
- IGMP Type field, 635
- IGRP, 131
- IIHs, 538–539
- IS-IS, 542
 - generic format, 543–545
 - TLV fields, 543–545
- LSPs
 - direct inspection, 606–607
 - flooding, 552
 - header fields, 553–555
- multicast, 625
- multicast routing, 12–14
- OSPF, 295–297
 - DBD, 299
 - Hello, 297–299
 - link-state acknowledgment, 301
 - Link-State Request, 300
 - link-state update, 301
- PIM, 636–638

- RIP
 - AFI, 42
 - Next Hop field, 41
 - SNPs, 556
 - TCP, unintentional blockages, 741–742
- parameters for BGP dampening, modifying, 771–774
- partial feed, 659
- Partition Bit field (LSPs), 554
- passive outgoing interfaces
 - RIP route advertisement, 95–96
 - unadvertised IGRP routes, 176–178
- passive routes (EIGRP), 213
- payload, 4
- PDU (protocol data units), 542
- peer groups, improving BGP convergence, 783–785
- peering
 - between nondirectly connected external neighbors, missing routing table addresses, 733–736
 - BGP-4
 - external neighbor relationships, 665–667
 - internal neighbor relationships, 667
 - route advertisements, 668–672
- periodic LSAs, 332
- periodic updates, distance vector protocols, 22
- PIM (Protocol Independent Multicast)
 - dense mode, 625, 630–631
 - assert mechanism, 631–632
 - troubleshooting, 646–651
 - IGMP joins, 643–645
 - messages, 638–640
 - packets, 636–638
 - sparse mode, 625, 632, 651, 654–656
 - discovery process, 632–633
 - join mechanism, 633
 - register process, 634
 - RPs, 632
- ping clns command, 617–619
- point-to-multipoint mode (NBMA), 331
- point-to-point IIHs, 539
- point-to-point links, IS-IS, 536
- point-to-point media, OSPF networks, 328
- point-to-point mode (NBMA), 330
- point-to-point serial links, IS-IS configuration, 559–565
- poison reverse, distance vector protocols, 22
- poison updates, 130
- policies, BGP, 661
- policy control, 672–674
 - AS_PATH attribute, 682–685
 - communities, 697–699
 - distribute lists, 695–696
 - filter lists, 695
 - LOCAL_PREF attribute, 675–676
 - MED attribute, 677–682
 - NEXT_HOP attribute, 685
 - ORF, 700–702
 - ORIGIN attribute, 685
 - prefix lists, 696
 - route maps, 690–694
 - match as_path command, 692–693
 - match community command, 692
 - match ip address command, 691
 - set as-path prepend command, 693
 - set community command, 693
 - set local preference command, 694
 - set metric command, 694
 - WEIGHT knob, 686–688
- policy routing (BGP), outbound IP traffic flows, 790
 - asymmetrical routing, 802–806
 - dual-homed connections, 798–802
 - reachability, 795–798
 - single exit point, 791–795
- prefix lists, BGP-4 policy control, 696
- prefixes
 - advertising, 668–670
 - synchronization rule, 671–672
 - assigned attributes, displaying, 726
 - origination
 - classful network advertisements, 749–752
 - distribute lists, 752–754
 - misconfiguration, 746–749
- prepending AS_PATH, 682–685
- preventing routing loops
 - DUAL, 207, 211
 - active routes, 213
 - FC, 211
 - FD, 211
 - feasible successors, 212
 - passive routes, 213
 - RD, 211
 - successors, 211
- private IPv4 address space, 7–8

- private peering, 660
- protocol header format, OSPF packets, 296
- protocol specifications, BGP-4, 662
 - external neighbor relationships, 665–667
 - internal neighbor relationships, 667
 - neighbor relationships, 663–664
- protocol-independent commands, 24
- prune mechanism, PIM dense-mode, 631
- Pseudonode identifier field (LSPs), 554
- PSN (pseudonodes), 539
- PSNPs (partial sequence number packets), 556
- public peering, 660

Q-R

- Q count, 232
- querier election mechanism, IGMP version 2, 627
- queries
 - EIGRP, 214, 220
 - RIPs, 43
- RD (reported distance), 211
- reachability
 - EBGP multihop next hops, 774–777
 - IBGP next-hops, 766–771
 - IS-IS
 - ping clns command, 617–619
 - traceroute command, 617–619
 - IS-IS TLVs, 547
 - outbound BGP traffic flows, 795–798
 - RIP route installation, 52
- receiver problems, IGRP uninstalled routes, 142
- receiving updates, RIP, 33–35
- redistribution
 - EIGRP, 280–286
 - external routes into IS-IS, 570–573
 - IGRP metric, defining, 191–194
 - into NSSAs, filtering Type 7 LSAs, 326
 - IS-IS, misconfiguration, 611
 - OSPF, 488–494
 - RIP, 113–116

- redundancy
 - dial backup links
 - EIGRP, 286–290
 - IGRP, 194–198
 - virtual links, 316
- register message (PIM), 638
- register process, PIM sparse mode, 634
- reliable EIGRP packets, 214
- Remaining Lifetime field (LSPs), 553
- replies (EIGRP), 214
- resolving EIGRP SIA errors, 240–250
- reviewing EIGRP neighbor changes, 228–229
- RFC 1771, synchronization rule, 671–672
- RIDs (router IDs), 659
 - best-path selection, 821–823
- RIP (Routing Information Protocol)
 - authentication, 42
 - compatibility issues, 43
 - DDR, 116–122
 - default routes, 39–40
 - discontiguous networks, 36–37
 - flapping routes, 122–124
 - hop count, 29
 - metrics, 29–30
 - missing subnetted routes, 106–109
 - Next Hop field, 41
 - packet behavior, 31
 - packets, AFI, 42
 - redistribution, 113–116
 - route advertisements, 86
 - blocked routes, 91–93
 - broken multicast capability, 96–98
 - down network interface, 93–94
 - down outgoing interface, 89–91
 - misconfigured neighbor statement, 99–100
 - passive outgoing interface, 95–96
 - sending RIP routes, 86
 - split horizon, 102, 105–106
 - VLSM routes, 100–102
 - route installation, 52
 - split horizon, 30–31
 - subnet masks, 41
 - summarization, 109–113
 - timers, 30

- uninstalled routes, causes of, 52
 - blocked RIP broadcast, 63–65
 - blocked source address, 60–63
 - discontiguous networks, 71–74
 - distribute list incoming routes, 58–60
 - equal-cost paths, 83–86
 - hop count exceeded, 81–83
 - incompatible RIP version, 65–68
 - incorrect network statements, 53–56
 - invalid sources, 74–76
 - Layer 2 problems, 76–78
 - line protocol in down state, 56–58
 - mismatched authentication key, 68–71
 - offset list value too high, 79–81
- updates
 - receiving, 33–35
 - sending, 31–33
- version field, 43
- VLSM, 37–39
- RIP-2
 - multicast, 42
 - Route Tag field, 40–41
- route advertisements
 - EIGRP, 250
 - discontiguous networks, 252–253
 - misconfigured distribute lists, 251–252
 - split-horizon, 253–256
 - unexpected advertisements, 257–259
 - unexpected metrics, 259–263
 - IGRP, 168–188
 - OSPF, troubleshooting unadvertised routes, 422–431
- route dampening, 702–706
- route flapping, EIGRP, 271–275
- route installation
 - EIGRP, 264
 - summarization, 265–270
 - OSPF
 - uninstalled external routes, 479–487
 - uninstalled routes, 463–478
- route maps, BGP-4 policy control, 690–694
 - communities, 697–699
 - distribute lists, 695–696
 - filter lists, 695
 - match as_path command, 692–693
 - match community command, 692
 - match ip address command, 691
- ORF, 700–702
 - prefix lists, 696
 - set as-path prepend command, 693
 - set community command, 693
 - set local-preference command, 694
 - set metric command, 694
- route origination (BGP)
 - classful network advertisements, 749–751
 - misconfiguration, 746–749
 - misconfigured distribute lists, 752–754
 - missing routing table entries, 743–746
- route redistribution, OSPF, 488–494
- route reflection, 707–711, 778
 - client-to-client, 780–782
 - cluster design, 757–758
 - identical cluster IDs, 785, 788–790
 - misconfigured IBGP neighbor, 779–780
 - peer groups, 783–785
- route summarization
 - EIGRP, 276–280
 - OSPF
 - external routes, 497–499
 - troubleshooting, 494–496
- route tag field (RIP-2), 40–41
- route-flapping, IS-IS, 612–616
- Router Dead Interval field (OSPF Hello packets), 299
- Router ID field (OSPF packets), 297
- router LSAs (Type 1), 302–306
- routers
 - convergence, 129
 - high-speed packet forwarding, 25
 - OSPF
 - adjacencies, 334–338
 - link types, 305
- routes, poisoned, 22
- routing domains, IS-IS, 536
- routing loops, 30
 - DUAL, 207, 211
 - active routes, 213
 - FC, 211
 - FD, 211
 - feasible successors, 212
 - passive routes, 213
 - RD, 211
 - successors, 211

- IGRP
 - split horizon, 130
 - split horizon with poison reverse, 130
- routing policies, BGP-4, 672–674
 - AS_PATH attribute, 682–685
 - LOCAL_PREF attribute, 675–676
 - MED attribute, 677–682
 - NEXT_HOP attribute, 685
 - ORIGIN attribute, 685
 - WEIGHT knob, 686–688
- routing protocols
 - administrative distance, 24
 - classful, 29
 - distance vector
 - convergence, 19–20
 - counting to infinity, 21
 - holddown, 21
 - loop avoidance, 20–21
 - metrics, 19
 - periodic updates, 22
 - poison reverse, 22
 - split horizon, 22
 - triggered updates, 22
- EIGRP, 207
 - behavior, 218–219
 - convergence, 207
 - default routes, 221
 - DUAL, 207, 211–213
 - IP Internal Route TLV, 216–217
 - metrics, 208–209
 - neighbor relationships, 209–210
 - packet fields, 216–217
 - query process, 220
 - RTP, 214
 - summarization, 219–220
 - unequal-cost load balancing, 221–223
- IGRP
 - behavior, 131
 - default routes, 132–133
 - metrics, 127–129
 - packets, 131
 - split horizon, 130
 - split horizon with poison reverse, 130
 - timers, 129–130
 - unequal-cost load balancing, 133–134
- link-state, 23–24
- OSPF, 295
 - adjacencies, 334–338
 - areas, 315–326
 - demand circuits, 331–334
 - external LSAs, 313–315
 - LSAs, 302–304
 - multaccess media, 327–328
 - NBMA media, 329–331
 - network LSAs, 307–308
 - packets, 295–301
 - router LSAs, 304–306
 - summary LSAs, 309–312
 - virtual links, 316–317
 - unicast versus multicast, 13–14
- routing tables
 - BGP
 - uninstalled EBGP-learned routes, 771–777
 - uninstalled IBGP-learned routes, 763–771
 - EIGRP, nonexistent summarized routes, 276–278
 - IGRP
 - flapping routes, 198–201
 - uninstalled routes, troubleshooting, 142–166
 - OSPF
 - uninstalled external routes, 479–487
 - uninstalled routes, 463–478
- routing updates, 606–607
 - IS-IS
 - redistribution into Level 1, 611
 - route advertisements, 607–611
 - RPF (reverse path forwarding), 628–630
 - RPF check failure, 650
 - RPs (rendezvous points), 632
 - RTO (retransmission timeout), 232
 - RTP (Reliable Transfer Protocol), 214
- Rtr Pri field (OSPF Hello packets), 299

S

- scalability, IBGP
 - AS confederations, 711–712
 - route reflectors, 707–711
- security
 - authentication, null authentication, 364
 - IS-IS, authentication, 548
- selecting BGP best-path, 821–827
- sender problems
 - IGRP uninstalled routes, troubleshooting, 142, 168–188
 - uninstalled IGRP routes, 163–166
- sending RIP routes, 31–33, 86
 - blocked routes, 91–93
 - broken multicast capability, 96–98
 - down network interface, 93–94
 - down outgoing interface, 89–91
 - misconfigured neighbor statement, 99–100
 - missing network statement, 87–89
 - passive outgoing interface, 95–96
 - split horizon, 102, 105–106
 - VLSM routes, 100–102
- Sequence field (EIGRP packets), 216
- Sequence Number field (LSPs), 554
- serial links (point-to-point), IS-IS configuration, 559–565
- servers, route reflectors, 757
- set as-path prepend command, implementing in route maps, 693
- set community command, implementing in route maps, 693
- set local preference command, implementing in route maps, 694
- set metric command, implementing in route maps, 694
- show clns interface command, 564, 586
- show clns neighbors command, 586
- show clns neighbors detail command, 563
 - field definitions, 588
- show clns protocol command, 562–563
- show ip bgp command, 726
- show ip bgp neighbor command, 726
- show ip bgp neighbors command, 726–727
- show ip bgp summary command, 726
- show ip eigrp neighbor command, 210
- show ip eigrp topology active command, 242– 245
- show ip protocols command, 56
- show ip route command, 12, 56, 134, 142
- show isis database command, 586
- show isis topology command, 565, 586
- SIA (stuck in active) route errors, 220
 - EIGRP, 240–250
- SNPs (sequence number packets), 556
- source validity checks, failure on IGRP networks, 159–161
- sparse mode (PIM), 625, 632
 - discovery process, 632–633
 - join mechanism, 633
 - register process, 634
 - RPs, 632
 - troubleshooting, 651, 654–656
- SPF algorithm, 17
 - IS-IS decision process, 558
 - OSPF, 518–528
 - triggers, 614–615
- split horizon, 130–131
 - distance vector protocols, 22
 - EIGRP, 253–256
 - RIP, 30
 - poison reverse. 31
 - route advertisement, 102, 105–106
 - unadvertised IGRP routes, troubleshooting, 184, 187–188
- SRTT (smooth round-trip time), 232
- standard access lists
 - BGP filtering, unfiltered subnets, 828–830
 - debug ip bgp update command output, 727
- static routing, 4, 11
- stub areas, 319–320
- Stuck in 2-WAY state, 398– 400
- Stuck in ATTEMPT, 383–386
- Stuck in EXSTART/EXCHANGE state, 401–417
- Stuck in INIT state, 382, 387–398
- Stuck in LOADING state, 417–422
- subnet masks, RIP, 41
- subnets, 12
 - autosummarization, 106–109
 - discontiguous, uninstalled IGRP routes, 155–158
 - masks, 8

successors (EIGRP), 211
 summarization
 EIGRP, 276–280
 OSPF
 external routes, 497–499
 troubleshooting, 494–496
 RIP, 109
 excessively large routing table, 110–113
 summary ASBR LSAs (Type 4), 302
 summary LSAs (Type 3), 309–312
 summary network LSAs (Type 3), 302
 summary routes, unadvertised, 432–440
 supernets, 10
 synchronization
 BGP routes, disabling, 766
 IS-IS, 555–557
 synchronization rule (BGP-4), 671–672
 synchronized BGP routes, propagating to neighbor,
 761–762
 System identifier field (LSPs), 554

T

TCP (Transmission Control Protocol), unintentional
 packet blockages, 741–742
 TCP/IP (Transmission Control Protocol/Internet
 Protocol)
 IP addressing
 CIDR, 10
 classes, 5–7
 media independence, 5
 private address space, 7–8
 subnets, 12
 subnetting, 8
 IP protocol, 3
 versus OSI reference model, 3
 three-way reliable adjacencies, 540
 timers, RIP, 30
 timers basic command, 130

TLV (Type/Length/Value), 216–217
 IP Internal Route, 216–217
 IS-IS packets, 543–545
 LSP TLVs, 547
 metric information, 545–548

 topologies, IS-IS, displaying, 565
 topology table (EIGRP)
 convergence, 19–20
 diffused computation, 213
 local computation, 213
 ToS field (router LSAs), 305
 ToS field (summary LSAs), 310
 ToS Metric field (router LSAs), 305
 ToS metric field (summary LSAs), 310
 totally NSSAs, 324–326
 totally stubby areas, 321
 traceroute command, 617–619
 traffic
 EIGRP, unequal-cost load balancing, 221–223
 IGRP
 load balancing, 168
 unequal-cost load balancing, 133–134
 transit links, identifying attached routers, 308
 transit peering, 660
 triggered updates, distance vector protocols, 22
 Type 1 LSAs, 304–306
 Type 2 LSAs, 307–308
 Type 3 LSAs, 309–312
 Type 4 LSAs, 309–312
 Type 5 LSAs, 313–315
 comparing to Type 7, 322
 Type 7 LSAs
 filtering, 326
 NSSAs, 321–324
 Type field
 IGMP packets, 635
 OSPF packets, 296
 router LSAs, 305

U

- unadvertised IGRP routes
 - broadcast capability, 178–180
 - default route candidates, 188–191
 - distribute lists, 173–174
 - misconfigured neighbor statement, 180–181
 - misconfigured network statement, 169–171
 - network interface, 175–176
 - outgoing interface, 171–172
 - passive outgoing interface, 176–178
 - split horizon, 184, 187–188
 - troubleshooting, 169
 - VLSM, 182–184
- uncommon subnets, EIGRP, 233–235
- unequal-cost load balancing, 133–134
 - EIGRP, 221–223
 - IGRP, 133–134
 - variance, 201–204
- unexpected metrics, EIGRP, 259–263
- unexpected route advertisements, EIGRP, 257–259
- unicast routing versus multicast, 12–14
- unicasts, 625
- unidirectional links, EIGRP, 230, 232
- uninstalled routes
 - EBGP
 - dampening, 771–774
 - infinite MED value, 777
 - unreachale multihop EBGP next hop, 774–777
 - EIGRP, 265–270
 - external (OSPF), 479, 481–487
 - IBGP
 - synchronization, 763–766
 - unreachable next-hops, 766–771
 - IGRP
 - receiver problems, 142
 - sender problems, 168–188
 - troubleshooting, 142–166
 - OSPF, 463–478
 - RIP, 52
- “unknown routing protocol” error messages, 528
- unreachable IBGP next hops, 766–771
- unreliable EIGRP packets, 214
- update packets (EIGRP), 214
- update process (IS-IS), 555

- update timers
 - IGRP, 129
 - IS-IS, 556–557
 - RIP, 30
- updates
 - IGRP, poison updates, 130
 - RIP
 - receiving, 33–35
 - sending, 31–33
- utilization (CPU), OSPF, 499–503

V

- variable-length subnet mask. *See* VLSM
- variance, 201–204
- variance command, 133–134, 221–223
- Version field
 - EIGRP packets, 216
 - RIP, 43
- Version Number field (OSPF packets), 296
- virtual links, 316–318
- VLSM (variable-length subnet mask), 9
 - RIP, 37–39
 - route advertisement, 100–102
 - unadvertised IGRP routes, troubleshooting, 182–184

W

- WEIGHT knob, policy control, 686–688