



## Numerics

---

- 12000 series routers, dCEF, 387
- 23B+D format (ISDN), 140
- 30B+D format (ISDN), 140

## A

---

- AAA (Accounting, Authentication, and Authorization), 448, 453–461
- AARP (AppleTalk Address Resolution Protocol), 118, 332
- abbreviating commands, 7
- ABR (Area Border Router), 268
- ABR (Available Bit Rate), 115
- accept-lifetime parameters, 257
- access
  - CAR, 372–373
  - CBAC, 475–480
  - configuring, 15–18
  - Lock and Key, 466–469
  - NBMA, 264
  - NSAP, 124, 275
  - reflective access lists, filtering IP sessions, 470–471
  - remote, 42
  - router lines, controlling, 449
  - SNAP, 119
  - SNMP, configuring, 41
- access expressions, 189
- access lists
  - AppleTalk, 523–525
    - example configuration, 525
  - bit ordering, 517
  - DLsw+ filters, 199
  - DSCP, matching, 514–515
  - expressions, 189
  - extended
    - applying during specified time range, 515
    - configuring, 513–515
    - matching summary addresses, 312
  - implicit deny statements, 187
  - IP precedence, defining, 514
  - IPX, 519–522
    - applying permit/deny statements during specified time range, 520
  - Lock and Key, 514
  - MAC address filters, 517–518
  - NebBIOS filters
    - applying to RSRB peers, 193–194
    - SRB configuration, 186–187
  - port numbers, matching, 515
  - regular expressions, 512
    - examples of, 527
    - creating, 52–527
  - SAP filters
    - applying to RSRB peers, 193
    - configuring, 521–522
  - standard, configuring, 512–513
  - Token Ring filters, SRB configuration, 188–189
  - ToS bit, matching, 515
  - type code, configuring, 518
- access-class command, 16
- access-enable timeout 30 command, 469
- accounting (IP), 70–71
- ACE (Access Control Entry), 462
- ACK (acknowledgment), 472
- action parameters, 349
- active ring monitors, 80
- address command, 239
- addresses, 450–451
  - BIA, 226
  - care-of, 231
  - fields, 235
  - inside destination, 241
  - MBGP, 297–299
  - NAT, configuring, 237–241, 243
  - peer IP, 289
  - protocols, 105
- administrative distance
  - assigning to static routes, 306
  - routing information sources, 319
- aggregate addresses, filtering with extended access lists, 312
- AH (Authentication Header), 499
- alias commands, 29
- analog voice ports, 402

ANI (Automatic Number Identification), 417, 422

any keyword (ip access list command), 513

AppleTalk

access lists, 523–525

cable ranges

filtering, 524

static route configuration, 334

configuring, 331–333

discovery mode, 333

example configuration, 334–335

NBP packets, filtering, 524

split horizon, disabling, 333

zones, filtering, 523

appletalk bandwidth-percent eigrp command, 334

appletalk cable-range command, 332–333

appletalk discovery command, 333

appletalk eigrp-timers command, 334

appletalk protocol eigrp command, 333

appletalk route-redistribution command, 333

appletalk routing command, 331

appletalk routing eigrp command, 333

appletalk static cable-range command, 334

appletalk zone command, 332

applets, blocking, 479

applications, NBAR, 350–357

applying

access lists to

DLSw+ traffic, 199

during specified time range, 515

IPX traffic, 519–522

Token Ring traffic, 188

NetBIOS filters to interfaces, SRB

configuration, 187

APS (Automatic Protection Switching), 96

POS interface configuration, 98–99

ARE (All-Routes Explorer) frames, 183–185

area-address command, 325

arguments

as-path-lits-number, 285

community-list-number, 284

multiplier, 260

ARP (Address Resolution Protocol), 218–220

AS (autonomous-system), 262

ASBR (Autonomous System Boundary Router), 273

ASN.1 (Abstract Syntax Notation 1), 40

as-path-list-number argument, 285

assigning

administrative distance to static routes, 306

multiple interfaces to rotary groups, 152

asynchronous serial router line connections, 11–13

ATM (Asynchronous Transfer Mode)

interfaces, configuring, 115–123

LANE, 123–130

components, viewing, 128

attacks, 482

DoS, preventing, 472–474

IDS, 481–491

signatures, 482

attributes of BGP route maps

community, 315

local preference, 315

origin, 315

route dampening, 315

metric, 314

route tag value, 314

setting, 314–316

audits, 480, 491

AURP (AppleTalk Update Routing Protocol), 85

authentication, 448

AAA, 448

proxy, 462–465

authorization, authentication proxies, 462–465

autocommand command, 468

automatic modem recovery process, defining, 136

automatic tag computation, 315

autonomous system paths, 279

average rates, 349

---

## B

B channels (ISDN), 140

backup peers (DLSw+), configuring, 198

backup ring monitors, 80

bandwidth

OSPF, 266–273

voice, 401

bandwidth command, 260

bandwidth interface configuration command, 263

banner login command, 449

banners  
 AAA, 458  
 configuring, 18  
 warning, configuring, 449–450

basic-3des transform, 507

Bc (committed burst rate), 100

BDR (Backup Designated Router), 269

Be (excess burst rate), 100

BECN (backward explicit congestion notification), 100, 103

BGP (Border Gateway Protocol), 279–290  
 community attribute, setting, 315  
 local preference attribute, setting, 315  
 MBGP, 297–299  
 origin attribute, setting, 315  
 redistributing into, 317  
 route dampening, 315

bgp dampening command, 287

bgp neighbor commands, 288

bgp network command, 287

BIA (burned-in address), 226

bit ordering in access lists, 517

blocking Java, 479

b-node (broadcast), 229

Boolean operators, expressions, 189

boot config parameter, 28

boot system flash command, 28

BRI (Basic Rate Interface), 141  
 configuring, 143–144  
 example, 145  
 load threshold, configuring, 150  
 TE1 negotiation, 144

bridging  
 RSRB  
 example configuration, 194–195  
 FST, 191  
 FST encapsulation, 192  
 TCP encapsulation, 192–193  
 virtual rings, configuring, 191

SRB, 183  
 configuring, 184–185  
 example configuration, 189  
 filtering NetBIOS names, 186  
 Token Ring packet filters, applying, 188

broadcasts, configuring, 221–223

browsers, 21

BSR (bootstrap router), 293

buckets-of-history-kept command, 56

buffers  
 jitter, 425  
 management, 59–63

BUS (Broadcast and Unknown Server), 124

busyouts, 415

byte patterns (wildcards), 187

bytes, comparing in extended MAC address access lists, 518

## C

CA (Certification Authority), 492–494

cable ranges, filtering, 524

cable-range 0-0 command, 332

Call Tracker, viewing history, 135

calls, dial plans, 416–426

CAMA (Centralized Automatic Message Accounting), 438

CAR (Committed Access Rate), 372–373

care-of addresses, 231

CAS (Channel Associated Signaling), 89, 403, 426

cayman (Cayman TunnelTalk Appletalk), 85

CBAC (context-based access control), 475–480

CCS (common-channel signaling), 402

cd command, 23

CDP (Cisco Discovery Protocol), 29–31

CEF (Cisco Express Forwarding), 351  
 configuring, 386–387  
 example configuration, 387

CEP (Simple Certificate Enrollment Protocol), 495

CGMP (Cisco Group Management Protocol), 291

channelized E1, 402  
 serial interfaces, configuring, 88–89

channelized T1, 402

channelized T3 serial interfaces, configuring, 87–88

characteristics of codecs, 420

characters, operators, 9

chat scripts, 139  
 escape sequences, 139–140  
 regular expressions, creating, 525, 527

CIR (Committed Information Rate), 100

- circuits
  - DLCI, 99
  - fields, 98
  - numbers, 98
  - PVCs, 99
  - SVCs, 99
  - VCs, 99
- circuit-weights, DLSw+ remote peers, 198
- Cisco Express Forwarding. *See* CEF
- Cisco IOS switching services
  - CEF (Cisco Express Forwarding)
    - configuring, 386–387
    - example, 387
  - fast switching, 385
    - configuring, 385
    - example, 386
  - MLS
    - configuring, 389–391
    - example, 391
  - NetFlow switching
    - configuring, 388–389
    - example, 389
- citrix protocol, 356
- classes, NBAR, 350–357
- classification
  - CAR, 372–373
  - IP packet, 360–361
  - QoS packets, 359
- clear ip route command, 307
- clear line line-number command, 12
- clearing routes from routing table, 307
- CLI (command-line interface), 5
  - access, configuring, 15–18
  - banners, configuring, 18
  - commands, entering, 7–11
  - configuration, 6
  - menus, configuring, 19–20
  - reverse Telnet connections, 11–14
  - SSH connections, 14–15
  - Web browsers, 21
- client-identifier command, 230
- clients (SLB), configuring, 244–250
- CIIP (Classical IP), 115
- closing reverse Telnet connections, 12
- CLP (cell loss priority), 346
- clusters, 289
- CM (CallManager), SRS, 438–442
- codecs, 420
- command-line interfaces, MQC, 342–349
- commands, 230
  - abbreviating, 7
  - access-class, 16
  - access-enable timeout 30, 469
  - address, 239
  - appletalk bandwidth-percent eigrp, 334
  - appletalk cable-range, 332–333
  - appletalk discovery, 333
  - appletalk eigrp-timers, 334
  - appletalk protocol eigrp, 333
  - appletalk route-redistribution, 333
  - appletalk routing, 331
  - appletalk routing eigrp, 333
  - appletalk static cable-range, 334
  - appletalk zone, 332
  - area address, 325
  - autocommand, 468
  - bandwidth, 260
  - bandwidth interface configuration, 263
  - banner login, 449
  - bgp dampening, 287
  - BGP neighbor, 288
  - BGP network, 287
  - boot system flash, 28
  - buckets-of-history-kept, 56
  - cable-range 0-0, 332
  - cd, 23
  - clear ip route, 307
  - clear line line-number, 12
  - client-identifier, 230
  - copy, 27
  - crypto ca authenticate, 499
  - crypto ca authenticate mydomain, 508
  - crypto ca enroll mydomain, 499
  - crypto key generate rsa, 498
  - crypto key generate rsa, 508
  - crypto key zeroize, 14
  - data-pattern, 54
  - debug, 7, 68–69
  - delay interface configuration, 260
  - delete, 25
  - dhcp-server ip-address, 51
  - dir, 23
  - dir/all, 25
  - disable, 6
  - disconnect, 11

distance eigrp, 320  
 distributions-of-statistics-kept, 56  
 enable, 6  
 enable password, 17, 448  
 enable secret, 17, 448  
 exit, 6, 346  
 file management, 28–29  
 filter-for-history, 57  
 format, 26  
 frame-relay map, 107  
 hops-of-statistics-kept, 56  
 hours-of-statistics-kept, 56  
 http-raw-request, 52  
 interface dialer, 152  
 interface ethernet 0, 7  
 interface serial, 142  
 interfaces, 5  
 ip access-class, 449  
 ip address negotiated, 163  
 ip cef, 386  
 ip cef distributed, 387  
 ip default network, 307  
 ip dhcp ping packet, 230  
 ip dhcp pool, 228  
 ip forward-protocol, 221  
 ip forward-protocol ?, 223  
 ip forward-protocol udp, 222  
 ip igmp join-group, 294  
 ip load-sharing, 387  
 ip mobile secure, 233  
 ip name-server, 220  
 ip nat inside source, 238  
 ip ospfcost, 271  
 ip policy route-map, 309  
 ip route-cache, 386  
 ip rtp priority, 347  
 ip telnetsource-interface interface, 67  
 ipx bandwidth-percent eigrp, 328  
 ipx hello-interval-eigrp, 328  
 ipx hold-time eigrp, 328  
 ipx internal-network, 325  
 ipx maximum-paths, 324  
 ipx network, 324  
 ipx nlsr priority, 327  
 ipx router eigrp, 327  
 ipx router nlsr, 325  
 ipx router rip, 328  
 ipx routing, 323  
 lives-of-history-kept, 56  
 logging, 37  
 logging buffered, 68  
 logging monitor, 37  
 logging monitor debugging, 68  
 logging synchronous, 35, 38  
 login, 449  
 login authentication, 468  
 lsr-path, 51  
 match, 344  
 match as-path, 314  
 match community list, 314  
 match metric, 313  
 matchinterface, 313  
 match-ip address, 308  
 matchip route-source, 313  
 match-length, 308  
 matchroute-type, 313  
 matchtag, 313  
 menu name clear-screen, 19  
 menu-exit, 20  
 mls rp ip, 390  
 mls rp management-interface, 391  
 mls rp nde-address, 391  
 mls rp vlan-id, 390  
 mls rp vtp-domain, 390  
 more, 8  
 nat, 241  
 neighbor activate, 298  
 network, 254, 307  
 no appletalk protocol rtmp, 333  
 no cdp enable, 451  
 no cdp run, 30  
 no crypto isakmp enable, 500  
 no digit-strip, 423  
 no ip http-server, 21  
 no ip route-cache cef, 387  
 no ip split-horizon, 256  
 no ipx eigrp-split-horizon, 328  
 no logging on, 36  
 no login, 12  
 no ntp enable, 452  
 no password, 449  
 no service finger, 452  
 no snmp trap link-status, 48  
 passive-interface, 258  
 paths-of-statistics-kept, 56  
 physical-layer sync, 90  
 ping, 64–65  
 preempt, 225

- priority list, 362
- pwd, 25
- redistribute subnets, 272
- remark, 513
- request-data-size, 51, 53
- RIP-2-specific, 256–258
- router bgp, 280
- router isis, 275
- service compress-config, 28
- service password-encryption, 448
- set interface, 309
- set ip next-hop, 309
- set ip precedence, 308
- show, 8
- show buffers, 63
- show call calltracker active, 135
- show call calltracker history, 135
- show cdp, 31
- show cdp interface, 31
- show cdp neighbors, 18
- show crypto ca certificates, 496
- show history, 8
- show ip bgp regexp regular-expression, 285
- show ip nbar port-map, 356
- show ip nbar protocol-discovery, 356
- show ip route, 307
- show line line, 12
- show logging, 68
- show modemcap, 138
- show OSPF, 272
- show running-config, 7
- show sessions, 10, 13
- show users all, 12, 16
- show version, 59
- source-bridge, 184
- standby, 224
- standby preempt, 225
- standby priority, 225
- statistics-distribution-interval, 56
- telnet, 67
- terminal logging, 37
- threshold, 57
- timeout, 57
- traceroute, 66–67
- transport input none, 449
- transport input telnet, 449
- transport input telnet ssh, 449
- username username password password, 448
- version, 254
- virtual-link, 269
- where, 10, 13
- zone local, 431
- zone remote, 431
- zone submit, 430
- common regular expressions, 285
- community attribute (BGP), configuring as route map attribute, 315
- community attribute (BGP), setting, 315
- community lists, 314
- community-list-number argument, 284
- comparing
  - bytes, extended MAC address access lists, 518
  - routing protocol metrics, 311–312
- components of ATM LANE, viewing, 128
- compressing files, 28
- configuring, 244–248, 250
  - AAA, 453–461
  - access, 15–18
  - access lists, example, 516–517
  - AppleTalk, 331–333
    - example, 334–335
    - zones, 332
  - ATM LANE, 125–130
  - banners, 18
  - BGP, 279–290
  - BRI (ISDN), 143–144
  - buffers, 60–63
  - CDP, 30–31
  - CEF, 386–387
  - DDR
    - dialer interface parameters, 149–152
    - example, 152–153
    - via dialer profiles, 145–148
  - DHCP, 227–230
  - dial backup, 153–154
  - dial watch, 155–156
  - enable-delay-period, 154
  - example, 155
  - dial plans, 416–426
  - DLSw+, 196
    - backup peers, 198
    - dynamic peers, 198
    - encapsulation, 198–199
    - example, 205
    - load balancing, 203–204
    - local peers, 196
    - mapping to DLC source, 200–203

- on-demand peers, 203
- peer groups, 196
- remote peers, 197–198
- traffic filtering, 199
- EIGRP, 262–266
- extended IP access lists, 513–515
- extended MAC address access lists, 518
- fast switching, 385
- Frame Relay switching, 110–114
- FRTS, 375–377
- GTS, 374–375
- H.323
  - gatekeepers, 429–435
  - gateways, 426–428
- HSRP, 224–226
- IDS, 481–491
- IGRP, 259–260
- IKE, 493–499
- interfaces, 6
  - ATM, 115–123
  - channelized T1/E1 serial, 88–89
  - channelized T3 serial, 87–88
  - DPT OC-12c POS, 97
  - Ethernet, 78–79
  - FDDI, 79–80
  - Frame Relay, 99–109
  - loopback, 81–82
  - null, 81–82
  - OC-3 POS, 96
  - Packet-Over-SONET, 96–99
  - synchronous serial, 86–95
  - Token Ring, 80–81
  - tunnels, 84–86
  - VLANs, 82–83
- integrated IS-IS, 275–278
- internal modems, 134–139
- IP addressing, 218–220
- IP broadcast handling, 221–223
- IP multicast routing, 291–297
- IPSec, 499–508
- IPX, 323–325
- IVR, 436–438
- LFI, 381–383
- MAC address access lists, example, 518
- MBGP, 297–299
- menus, 19–20
- message logging, 35–38
- MLS, 389–391
- mobile IP, 231–237
- modems. idle time, 149
- MQC, 342–349
- multiple encapsulations on single interface, 324
- NAT, 237–243
- NBAR, 350–357
- NetFlow switching, 388–389
- NLSP, 325–326
- Novell IPX
  - EIGRP routing, 327–329
  - NLSP routing, 325–326
- ODR, 159–160
- OSPF, 266–273
- PBR, 357–358
- policy routing, 308–310
- PPP
  - callback, 161
  - LQM, 162
  - MLP, 163
- PPP encapsulation, 161–163
  - example, 164
- prefix lists, 516
- PRI (ISDN), 141
  - optional parameters, 143
  - PRI group, 142
  - T1/E1 controller, 142
- QoS
  - CQ, 364–367
  - policy propagation, 360–361
  - PQ, 362–363
  - RSVP, 377–380
  - voice, 398–401
  - VPNs, 359
  - WFQ, 367–369
- regular expressions, 525–527
- RIP, 253–256
  - commands, 256–258
  - route filtration, 318–321
  - route maps, 312–313
    - attributes, 314–316
  - route redistribution, 310, 316
- RSRB
  - FST encapsulation, 192
  - NetBIOS filters, 193–194
  - SAP filters, 193
  - TCP encapsulation, 192–193
  - virtual rings, 191
- SAA, 50–58



- SAP filters, 521–522
- SLB, 244–248, 250
- snapshot routing, 157–158
- SRB, 184
  - applying Token Ring packet filters, 188
  - bridging routed protocols, 185
  - example, 189
  - explorer frame processing, 189
  - filtering MAC addresses, 188
  - ring numbers, 184
  - spanning-tree, 184–185
  - virtual rings, 184
- SRS, 438–442
- standard IP access lists, 512–513
- static routes, 305–307
  - example, 307
- STUN, 207–211
  - encapsulation types, 208–209
  - example, 211
  - local acknowledgment, 209
  - priority queuing, 209–210
- system monitoring, 41–49
- system time, 31–35
- timeout values, 13
- type code access lists, 518
- voice ports, 402–415
- warning banners, 449–450
- Web browsers, 21
- WRED, 370–371
- congestion
  - QoS, managing, 362–369
  - WRED, 370–371
- connections, 12–13
  - dial backup, configuring, 153–154
  - reverse Telnet, 11–13
  - SSH, 14–15
  - testing
    - debug command, 68–69
    - ping command, 64–65
    - telnet command, 67
    - traceroute command, 66–67
  - trunks, 411
- contention, dialer contention, 150
- controlling
  - access, Lock and Key, 466–469
  - CBAC, 475–480
  - RIP updates on NLSP networks, 326
  - router line access, 449

- COPS (Common Open Policy Service), 378
- copy command, 27
- copying files, 26–27
- CoS (class of service), 344
- cost option, 271
- CQ (custom queuing), QoS, 364–367
- crashes, troubleshooting, 71
- creating
  - regular expressions, 525, 527
  - route maps, 312–313
    - attributes, setting, 314–316
- CRL (Certificate Revocation List), 495
- crypto ca authenticate mydomain command, 499, 508
- crypto ca enroll mydomain, 508
- crypto ca enroll mydomain command, 499, 508
- crypto key generate rsa command, 498, 508
- crypto key zeroize command, 14
- crypto maps, 506

---

## D

- D channels (ISDN), 140
- DASs (Dual-Attach Stations), 80
- data-pattern command, 54
- dCEF (distributed CEF), 386–387
- DDR (Dial-on-Demand Routing)
  - configuring, example, 152–153
  - dialer profiles, 145–148
  - interface parameters, defining, 149–152
  - PPP encapsulation, 160
    - configuring, 161–163
    - example, 164
  - watchdog spoofing, 148
- DE (discard-eligible), 100
- debug command, 68–69
- dedicated mode (PPP), 161
- default administrative distances, 306
- default static routes, 307
- defining
  - idle timeouts, 13
  - modem initialization string, 137
  - modem recovery method, 136
- delay interface configuration command, 260
- delay option, 225

- delay-dial signaling, 402
- delete command, 25
- deleting files from Flash, 24–26
- dense mode, 292
- denug command, 7
- DES (Data Encryption Standard), 499
- destination pattern wildcards, 418
- detecting
  - faulty modems, 136
  - IDS, 481, 483–484, 486–491
  - VAD, 421
  - WRED, 348
- devices
  - H.323 gatekeepers, 429–435
  - H.323 gateways, 426–428
  - internal modems, 134–139
  - MAC addresses, applying access lists, 517–518
  - modems
    - chat scripts, 139
    - defining recovery method, 136
    - recovery pending state, 137
- DFP (Dynamic Feedback Protocol), 244
- DHCP (Dynamic Host Configuration Protocol),
  - configuring, 227–230
- dhcp-server ip-address command, 51
- dial backup
  - configuring, 153–155
  - dialer watch, 155–156
  - enable-delay-period, 154
- dial plans, 416–426
- dial watch
  - configuring, 155
  - example, 156
- dialer contention, 150
- dialer profiles
  - DDR configuration, 145–148
  - defining dialer interface parameters, 149–152
- dialup networks
  - ODR configuration, 159–160
  - routing, 156
  - snapshot routing
    - configuring, 157–158
    - example, 158–159
- digital voice, 403
- dir command, 23
- dir/all command, 25
- Direct Encapsulation RSRB, configuring, 191–192
- directed broadcasts
  - configuring, 221–223
  - disabling, 452
- disable command, 6
- disabling
  - directed broadcasts, 452
  - finger services, 452
  - faulty modems, 137
  - split horizon on AppleTalk networks, 333
  - TCP, 452
  - UDP, 452
- disconnect command, 11
- discovery mode (AppleTalk), 333
- displaying
  - Call Tracker history, 135
  - gateway of last resort, 307
  - lines, 7
  - preconfigured modem attributes, 138
  - preconfigured modem types, 138
- distance eigrp command, 320
- distance vector routing protocols
  - IGRP, redistributing into, 316
  - RIP, redistributing into, 316
  - route filtering, 318–320
- distributions-of-statistics-kept command, 56
- DLCI (Data Link Circuit Identifier), 99
- DLSw+ (Data-Link Switching Plus)
  - configuring, 196
  - dynamic peers, 198
  - encapsulation, 198–199
  - example configuration, 205
  - load balancing, 203–204
  - local peers, 196
  - mapping to DLC source, 200–203
  - on-demand peers, 203
  - peer groups, 196
  - remote peers, 197–198
  - traffic
    - load balancing, 198
    - prioritizing, 199
    - traffic filtering, 199
- DNIS (Dial Number Information Service), 417, 422
- DNS (Domain Name System), 218
- DoS (denial-of-service) attacks, preventing,
  - 472–474

DPT (Dynamic Packet transport), 96–97  
 DR (designated router), 269  
 DSCP (Differentiated Services Code Point), 399  
   matching in IP access lists, 514–515  
 DTE (Data Terminal Equipment), 111  
 DVMRP (Distance-Vector Multicast Routing Protocol), 85  
 DWFQ (Distributed WFQ), 368  
 dynamic peers, DLSw+, 198

## E

E&M (receive and transmit) ports, 402, 406  
 early token release, 80  
 echoes, 51  
 ECN (Explicit Congestion Notification), 113  
 editing preconfigured modem initialization string, 138  
 EIGRP (Enhanced Interior Gateway Routing Protocol), 262–266  
   configuring for Novell IPX, 327–329  
   redistributing into, 316  
 ELAN (Emulated LANs), 123–130  
   ATM LANE, 123–130  
 enable command, 6  
 enable password command, 17, 448  
 enable secret command, 17, 448  
 enable-delay-period (dial backup), 154  
 enabling, 70–71  
   IP accounting, 70–71  
   NetBIOS name caching, 186  
   NLSP routing process, 326  
   RMON support, 48  
   session warnings, 13  
 enabling, 493. *See also* configuration  
 encapsulation  
   DLSw+, configuring, 198–199  
   Ethernet, selecting, 78  
   FST (Fast-Sequenced Transport), 191–192  
   GRE, 231  
   selecting for IPX, 324  
   PPP, 160  
     configuring, 161–163  
     example, 164  
   RSRB, configuring, 191–193  
   STUN, configuring, 208–209  
   synchronous serial interfaces, 90  
   TCP, RSRB configuration, 192–193  
   tunnels, 84–86  
   VLAN, 83  
 encryption  
   IP packets, 359  
   passwords, 18  
 end-to-end QoS, 377–380  
 escape sequences on modem chat scripts, 139–140  
 ESI (End-System Identifier), 124  
 ESP (Encapsulating Security Payload), 499  
 establishing rotary group member priority, 152  
 Ethernet  
   interfaces, 77–79  
   type codes, 625  
 exact keyword, match community-list command, 314  
 example configuration  
   AppleTalk, 334–335  
   IP access lists, 516–517  
 example configurations  
   MAC address access lists, 518  
   MLS, 391  
   NetFlow switching, 389  
   Novell IPX, 329–330  
   policy routing, 310  
 examples  
   AppleTalk access lists, 525  
   DLSw+ configuration, 205  
   ISDN BRI, 145  
   of CEF, 387  
   of DDR configuration, 152–153  
   of dial backup, 155  
   of dialer watch, 156  
   of fast switching, 386  
   of ISDN PRI, 143  
   of regular expressions, 527  
   of route filtering, 321  
   of route redistribution, 317–318  
   of snapshot routing, 158–159  
   of SRB configuration, 189  
   of static routes, 307  
   RSRB, 194–195  
   STUN configuration, 211  
 exit command, 6, 346  
 expect-send-strings, 139–140

explorers, processing (SRB), 189

expressions
 

- combining filters, 189
- regular, 285
- searching, 9

extended IP access lists
 

- bit ordering, 517
- configuring, 513–515
- matching summary addresses, 312
- permit/deny statements, applying during
  - specified time range, 515
- port numbers, matching, 515

extended MAC address access lists, configuring, 518

extended ping, 65

external modems, 134
 

- chat scripts, escape sequences, 139–140
- parameters, setting, 137–139

## F

failure recovery (modems), defining, 136

fair-queues, 348

fallback
 

- SRS, 438–442
- thresholds, 414

fast switching, 385
 

- configuring, 385
- example, 386

faulty modems, detecting, 136

FDDI interfaces, configuring, 79–80

FECN (forward explicit congestion notification), 100

fields
 

- addresses, 235
- circuits, 98
- protect-ip-address, 98

FIFO (first in, first out), 103

files
 

- compressing, 28
- management, 22
  - alias commands, 29
  - commands, 28
  - deleting from Flash, 24–26
  - moving, 26–27
  - navigating, 22–23

filter-for-history command, 57

filtering
 

- access expressions, 189
- AppleTalk zones, 523
- cable ranges, 524
- CBAC, 475–480
- DLSw+ traffic, 199
- ICMP, 452
- implicit deny statements, 187
- IP sessions, 470–471
- MAC addresses, SRB configuration, 188
- NBP packets, 524
- NetBIOS names (SRB), 186
- summary addresses with extended
  - access lists, 312
  - Token Ring packets, 188

finger services, disabling, 452

Flash memory, deleting files from, 24–26

flush parameter, 255
 

- ODR, 159

forced-switch option, 97

foreign agents, 231

Foresight, 103

format command, 26

fragments
 

- Frame Relay, 106
- LFI, 381–383
- LFI sizes, 401

Frame Relay
 

- interfaces, configuring, 99–109
- switching, configuring, 110–114

frame-relay map command, 107

FRTS (Frame Relay Traffic Shaping), 374–377

FST (Fast-Sequenced Transport), 191–192

FXO (Foreign Exchange Office), 402

FXS (Foreign Exchange Station), 402

## G

gatekeepers, H.323, 429–435

gateway of last resort, displaying, 307

gateways, H.323, 426–428

Gigabit Ethernet, 77. *See also* Ethernet

GRE (generic routing encapsulation), 231

ground-start signaling, 402

group-list option, 293  
 group-number, 224  
 group-number option, 224  
 GTS (Generic Traffic Shaping), 374–375

## H

H.323  
   gatekeepers, 429–435  
   gateways, 426–428  
 handling IP broadcasts, 221–223  
 hardware, MAC address filtering, 517–518  
 hardware-address, 230  
 hardware-address command, 230  
 hash-mask-lengths, 293  
 histories  
   messages, 37  
   parameters, 56  
 h-node (hybrid), 229  
 holddown parameter (ODR), 159, 255  
 home addresses, 231  
 home agents, 231  
 hops-of-statistics-kept, 56  
 host keyword (ip access list command), 513  
 hours-of-statistics-kept command, 56  
 HSRP (Hot Standby Router Protocol), 223–224  
   configuring, 224–226  
 HSSI (High-Speed Serial Interface), 86  
 HTTP management interfaces, 450  
 http-raw-request command, 52  
 hunt groups, 139

IANA, Ethernet type codes, 625  
 IBGP (Interior BGP), 279  
 IBM networks  
   DLSw+  
     configuring, 196–199  
     dynamic peers, 198  
     example, 205  
     load balancing, 203–204

RSRB  
   FST encapsulation, 192  
   TCP encapsulation, 192–193  
   virtual rings, configuring, 191  
 SRB, 183–185  
 STUN, 206  
   encapsulation type, configuring, 208–209  
   traffic, prioritizing, 210–211  
 ICMP (Internet Control Message Protocol)  
   access lists, defining, 514  
   filtering, 452  
 ICMPF (Impairment/Calculated Planning Impairment Factor), 415  
 idle timeouts  
   defining, 13  
   modem configuration, 149  
 IDS (Intrusion Detection System), 481–484, 486–491  
 IGMP (Internet Group Management Protocol),  
   defining access lists, 514  
 IGP (Interior Gateway Protocols), 279  
 IGRP (Interior Gateway Routing Protocol), 259–260  
   redistributing into, 316  
 IKE (Internet Key Exchange), 499  
   VPNs, 492–497  
 IMA (inverse Multiplexing over ATM), 115  
 immediate-start signaling, 402  
 implementing system logging, 450  
 implicit deny, 187  
 inactive modems, shutting down, 136  
 inbound route filtering, 320  
 indexes, SPI, 234  
 infinite option, 229  
 inform requests, 40  
 inside destination addresses, 241  
 integrated IS-IS, 275–278  
 interactive mode (PPP), 161  
 intercept mode (TCP), 473  
   preventing DoS attacks, 472–474  
 interface dialer command, 152  
 interface ethernet 0 command, 7  
 interface serial command, 142  
 interfaces, 5  
   access, configuring, 15–18  
   AppleTalk, dynamic configuration, 332  
   assigning to rotary groups, 152  
   ATM, configuring, 115–123

- banners, configuring, 18
- buffers, troubleshooting, 60
- channelized T1/E1 serial, configuring, 88–89
- channelized T3 serial, configuring, 87–88
- configuring, 82–83
- crypto maps, 506
- dial backup, configuring, 153–154
- dialer contention, 150
- DPT OC-12c POS, configuring, 97
- E&M, 406
- Ethernet, 77–79
- FDDI, configuring, 79–80
- Frame Relay, configuring, 99–109
- HSSI, 86
- LFI, 381–383
- LMI, 99
- loopback, configuring, 81–82
- menus, configuring, 19–20
- MQC, 342–349
- multiple encapsulation types, configuring, 324
- NASI, 456
- null, configuring, 81–82
- OC-3 POS, configuring, 96
- Packet-Over-SONET, configuring, 96–99
- reverse telnet connections, 11–14
- SSH connections, 14–15
- synchronous serial, configuring, 86–95
- Token Ring, configuring, 80–81
- tunnels, configuring, 84–86
- VLANs, configuring, 82–83
- Web browsers, 21
- internal modems, 134
  - chat scripts, escape sequences, 139–140
  - configuring, 134–139
- intialization string (modems), defining, 137
- IP
  - accounting, enabling, 70–71
  - addresses, spoofing, 450–451
  - addressing, 218–220
  - BGP, 279–290
  - broadcast handling, configuring, 221–223
  - debug command, 68–69
  - DHCP, 227–230
  - EIGRP, 262–266
  - IGRP, 259–260
  - integrated IS-IS, 275–278
  - MBGP, 297–299
  - MMoIP, 416
  - mobile, configuring, 231–237
  - multicast routing, 291–297
  - NAT, configuring, 237–243
  - OSPF, 266–273
  - packets
    - CAR, 372–373
    - encrypting, 359
    - monitoring, 72–74
  - peer addresses, 289
  - phones, 439
  - ping command, 64–65
  - precedence, 344
  - RIP, 253–258
  - sessions, filtering, 470–471
  - SLB, 244–248, 250
  - Telnet command, 67
  - traceroute command, 66–67
  - VoIP, 416
- IP access lists
  - bit ordering, 517
  - DSCP, matching, 514–515
  - example configuration, 516–517
  - extended, configuring, 513–515
  - port numbers, matching, 515
  - ToS bit, matching, 515
- ip access-class command, 449
- ip address negotiated command, 163
- ip cef command, 386
- ip cef distributed command, 387
- ip default network command, 307
- ip dhcp ping packet command, 230
- ip dhcp pool command, 228
- ip forward-protocol command, 221
- ip forward-protocol udp ? command, 223
- ip forward-protocol udp command, 222
- ip igmp join-group command, 294
- ip load-sharing command, 387
- ip mobile secure command, 233
- ip name-server command, 220
- ip nat inside source command, 238
- ip ospfcost command, 271
- ip policy route-map command, 309
- IP precedence, defining for IP access lists, 514
- ip route-cache command, 386
- ip rtp priority command, 347
- ip telnetsource-interface interface command, 67
- IPS (Intelligent Protection Switching), 97

- IPsec (IP Security), VPN tunnels, 499–508
- IPX (Internetwork Packet Exchange), 323–325
  - access lists, 519–522
  - EIGRP routing, 327–329
  - encapsulation type, selecting, 324
  - example configuration, 329–330
  - load balancing, 324
  - SAP filters, defining, 521–522
- ipx bandwidth-percent eigrp command, 328
- ipx hello-interval eigrp command, 328
- ipx hold-time eigrp command, 328
- ipx internal-network command, 325
- ipx maximum-paths command, 324
- ipx network command, 324
- ipx nlsr priority command, 327
- ipx router eigrp command, 327
- ipx router nlsr command, 325
- ipx router rip command, 328
- ipx routing command, 323
- IRDP (ICMP Router Discovery protocol), 220, 232
- ISAKMP (Internet Security Association and Key Management Protocol), 492
- ISDN (Integrated Services Digital Network)
  - 23B+D, 140
  - BRI, 143–145
  - PRI, 402
  - user EXEC mode, 6
- IS-IS, 275–278, redistributing into, 317
- IVR (Interactive Voice Response), 428, 436–438

## J-K

---

- Java, blocking, 479
  - permanent (ip route command), 306
  - tag (ip route command), 306
- jitter buffers, 425
- KDC (Key Distribution Center), 455
- keepalive requests, 106
- keywords
  - host (ip access list command), 513
  - log (ip access list command), 513

## L

---

- LAN segmentation, SRB bridging, 183–185
- LANE (LAN Emulation), 123–130
- LEC (LAN Emulation Client), 124
- LECS (LAN Emulation Configuration Server), 124
- link-state routing protocols
  - integrated IS-IS, 275–278
    - redistributing into, 317
  - NLSP, 325–326
  - OSPF, 266–273
    - redistributing into, 317
    - route filtering, 321
- lists, CRL, 495
- lives-of-history-kept command, 56
- LLC (Logical Link Control), 119
- LLQ (low latency queuing), 378
- LMI (Local Management Interface), 99
- load balancing, 198
  - DLSw+, configuring, 203–204
  - IPX, 324
  - SLB, configuring, 244–248, 250
- load sharing, per-packet, 387
- load threshold, ISDN BRI configuration, 150
- local acknowledgment, STUN configuration, 209
- local peers (DLSw+), configuring, 196
- Lock and Key access lists, 466–469, 514
- log keyword (ip access list command), 513
- logging
  - implementing, 450
  - messages
    - configuring, 35–38
    - verifying, 39
- logging buffered command, 68
- logging history command, 37
- logging monitor command, 37
- logging monitor debugging command, 68
- logging synchronous command, 7, 35, 38
- login authentication command, 468
- login command, 449
- loopback interfaces, configuring, 81–82
- loop-start signaling, 402
- LRQs (location requests), 431
- LSPs (Link State Packets), 276
- lsp-path command, 51

## M

- MAC addresses
  - access lists, 517–518
  - filtering, 188
- maintenance windows (modems), creating, 137
- management, 22
  - buffers, 59
    - configuring, 60–63
  - files, 22
    - alias commands, 29
    - commands, 28
    - deleting from Flash, 24–26
    - moving, 26–27
    - navigating, 22–23
  - QoS congestion, 362–369
  - routers, 450
- manual route configuration, 305–307
- manual-switch option, 97
- mapping DLSw+ to DLC source, 200–203
- map classes, 105
  - crypto, 506
- match as-path command, 314
- match command, 344
- match community-list command, 314
- match metric command, 313
- match statements, 286
- matching strings, 98
- matchinterface command, 313
- match-ip address command, 308
- match-ip route-source command, 313
- match-length command, 308
- matchroute-type command, 313
- matchtag command, 313
- MBGP (Multiprotocol BGP), 297–299
- MCUs (multimedia control units), 429
- MD5 (Message Digest 5), 232, 499
- MED (Multi-Exit Discriminator), 279
- membership, rotary groups, 152
- menu name clear-screen command, 19
- menu-exit command, 20
- menus, configuring, 19–20
- message-digest option, 271
- messages
  - logging, 35–39
    - SAP, filtering, 521–522
    - terminal sessions, sending, 13
  - metric attribute (route maps), setting, 314
  - metrics, comparison chart, 311–312
  - MIB (Management Information Base), 40
  - mii (Media-Independent Interface), 78
  - milliseconds, 276
  - milliseconds option, 276
  - MLP (Multilink PPP), configuring, 163
  - mls command, 390
  - MLS (Multilayer Switching)
    - configuring, 389–390
    - example, 391
  - mls rp ip command, 390
  - mls rp management-interface command, 391
  - mls rp nde-address command, 391
  - mls rp vlan-id command, 390
  - mls rp vtp-domain command, 390
  - MLSP (Multilayer Switching Protocol), 390
  - MMoIP (Multimedia Mail over IP), 416
  - mobile IP, configuring, 231–237
  - mobile nodes, 231
- modems
  - chat scripts, 139
    - escape sequences, 139–140
  - expect-send process, monitoring, 140
  - external, 134
  - failure, defining recovery method, 136
  - hunt groups, 139
  - idle time, configuring, 149
  - internal, 134–139
    - preconfigured attributes, viewing, 138
    - recovery pending state, 137
    - removing from service, 136
    - rotary groups, load threshold, 150
- monitoring
  - active ring monitors, 80
  - activity, 72–74
  - backup ring monitors, 80
  - buffers, 60
  - modems, expect-send process, 140
  - RTTMON, 49
  - systems, 40–49
- more commands, 8
- moving files, 26–27



MQC (modular QoS command-line interface),  
 342–349  
 multicast routing, 291–297  
 Multilayer Switching. *See* MLS  
 Multilayer Switching Protocol, 390  
 multiple encapsulations, configuring on a single  
 interface, 324  
 multiplexing IMA, 115  
 multiplier arguments, 260

## N

named access lists, configuring, 512–513  
 NASI (Netware Asynchronous Services Interface),  
 456  
 NAT (Network Address Translation), configuring,  
 237–243  
 nat command, 241  
 navigating file systems, 22–23  
 NBAR (Network-Based Application Recognition),  
 344, 350–357  
 NBMA (nonbroadcast multiaccess), 264  
 NBP (Name Binding Protocol) packets,  
 filtering, 524  
 nd (Network Disk), 223  
 neighbor activate command, 298  
 NetBIOS  
   access lists, configuring, 522  
   applying to RSRB peers, 193–194  
   name caching, enabling, 186  
 NetFlow switching  
   configuring, 388–389  
   example, 389  
 network command, 254, 307  
 networks  
   Ethernet, configuring interfaces, 77–79  
   FDDI, configuring interfaces, 79–80  
   NBAR, 350–357  
   numbers, 228  
   SDH, 96  
   telephony, 416–426  
   Token Ring, configuring interfaces, 80–81  
   VLANs, configuring interfaces, 82–83  
 NLSP  
   configuring, 325–326  
   RIP updates, controlling, 326  
   route aggregation, 522  
 no appletalk protocol rtmp command, 333  
 no cdp enable command, 451  
 no cdp run command, 30  
 no crypto isakmp enable command, 500  
 no digit-strip command, 423  
 no ip http-server command, 21  
 no ip route-cache cef command, 387  
 no ip split-horizon command, 256  
 no ipx eigrp-split-horizon command, 328  
 no logging on command, 36  
 no login command, 12  
 no ntp enable command, 452  
 no password command, 449  
 no service finger command, 452  
 no snmp trap link-status command, 48  
 nodes, 231  
 no-llc timer (DLSw+), 198  
 non-IP routing protocols  
   AppleTalk  
     access lists, configuring, 523–525  
     configuring, 331–333  
     discovery mode, 333  
     example, 334–335  
   Novell IPX, 323  
     access lists, configuring, 519–523  
     configuring, 323–325  
     encapsulation type, selecting, 324  
     example configuration, 329–330  
     NLSP routing configuration, 325–326  
 no-summary option, 268  
 notification  
   BECN, 100  
   ECF, 113  
   FECN, 100  
 notifications (SNMP), configuring, 44  
 Novell IPX, 323  
   access lists  
     applying permit/deny statements during  
       specified time range, 520  
     defining, 519–522  
   configuring, 323–325

- EIGRP routing, configuring, 327–329
- example configuration, 329–330
- NLSP routing, configuring, 325–326
- SAP filters, defining, 521–522
- NSAP (Network Service Access Point), 124, 275
- NTP (Network Time Protocol), H.323 gateways, 428
- null interfaces, configuring, 81–82
- numbered access lists, configuring, 512–513
- numbers, 99
  - ANI, 417
  - circuits, 98
  - DNIS, 417
  - group-number option, 224
  - networks, 228

## O

- OAM (operation, administration, and maintenance), 115
- OC-3 POS interfaces, configuring, 96
- ODR
  - configuring, 159–160
  - flush parameter, 159
  - holddown parameter, 159
  - sleeptime parameter, 159
  - update parameter, 159
- on-demand peers (DLSw+), configuring, 203
- opening reverse Telnet connections, 12
- operators, characters, 9
- optimization
  - buffers, 63
  - SAA, 49–58
- optional parameters. ISDN PRI configuration, 143
- options, 224, 254, 276
  - cost, 271
  - delay, 225
  - forced-switch, 97
  - group-list, 293
  - infinite, 229
  - level-1-2, 276
  - level-2-only, 276
  - manual-switch, 97
  - message-digest, 271
  - no-summary, 268
  - override, 292
  - priority, 271
  - RIP commands, 256–258

- rp-list, 293
- secondary, 224
- seconds, 276
- sparse-dense-mode, 292
- origin (BGP), configuring as route map
  - attribute, 315
- OSPF (Open Shortest Path First), 266–273
  - redistributing into, 317
- outbound route filtering, 320
- output
  - debugging, 68–69
  - searching, 9
- override option, 292

## P

- packet filtering
  - NetBIOS filters, applying to RSRB
    - configuration, 193–194
  - SAP filters, applying to RSRB
    - configuration, 193
- Packet-Over-SONET interfaces, configuring, 96–99
- packets
  - CAR, 372–373
  - IDS, 481–491
  - LFI, 381–383
  - monitoring, 72–74
  - NBP, filtering, 524
  - QoS
    - policy propagation, 360–361
    - VPNs, 359
  - spoofing, 450–451
  - WRED, 370–371
- parameters
  - accept-lifetime, 257
  - action, 349
  - boot config, 28
  - dialer interface, defining, 149–152
  - flush, 159, 255
  - history, 56
  - holddown, 159, 255
  - modems, setting, 137–139
  - SAA, configuring, 50–58
  - send-lifetime, 257
  - sleeptime, 159, 255
  - update, 159, 255
  - VoIP, 425

- passive remote peers, 199
- passive-interface command, 258
- passwords
  - encrypting, 18
  - user-level, 6
- PAT (Port Address Translation), 237
- paths-of-statistics-kept command, 56
- PBR (policy-based routing), 357–358
- PDL (Packet Description Language), 351
- PDLMs (PDL Modules), 351
- PDPs (Policy Decision Points), 378
- peak rates, 349
- peer groups (DLsw+), configuring, 196
- peer ip-addresses, 289
- peers
  - BGP, 279–290
  - dial, 418
- PEPs (Policy Enforcement Points), 378
- performance
  - buffers, 63
  - SAA, 49–58
- permanent keyword (ip route command), 306
- permit statements, 470
- permit/deny statements, applying to IPX access lists
  - during specified time range, 520
- per-packet load sharing, 387
- Per-VLAN Spanning Tree (PVST), 83
- PFS (Perfect Forward Secrecy), 505
- physical-layer sync command, 90
- PIM (Protocol Independent Multicasting), 291–297
- ping command, 64–65
- p-node (peer-to-peer), 229
- policies
  - COPS, 378
  - FRTS, 375–377
  - GTS, 374–375
  - QoS, 360–361
- policy routing. configuring, 308–310
- ports, voice, 402–415
- PPP (Point-to-Point Protocol), 160
  - callback, configuring, 161
  - configuring, 161–163
  - dedicated mode, 161
  - example, 164
  - interactive mode, 161
  - LQM, configuring, 162
  - MLP, configuring, 163
- PQ (priority queuing), QoS, 362–363
- precedence, 344
- preconfigured modem types. 138
- preempt command, 225
- prefix lists, configuring, 516
- prefixes, dialing, 441
- preventing DoS attacks, 472–474
- PRI (ISDN)
  - configuring, 141
  - example, 143
  - PRI group, configuring, 142–143
  - referencing corresponding serial interfaces, 142
  - T1/E1 controller, configuring, 142
- prioritizing
  - DLsw+ traffic, 199
  - rotary group members, 152
  - STUN traffic, 210–211
- priority list commands, 362
- priority option, 271
- priority queuing, STUN configuration, 209–210
- privileged EXEC mode, 6
- prompts, AAA, 458
- protect-ip-address field, 98
- protocol type-code access lists, configuring, 518
- protocols
  - AARP (AppleTalk ARP), 118
  - addresses, 105
  - AURP (AppleTalk Update Routing Protocol), 85
  - BGP (Border Gateway Protocol), 279–290
  - CDP, 29–30
    - configuring, 30–31
    - disabling, 451–452
  - CEP (Simple Certificate Enrollment Protocol), 495
  - CGMP (Cisco Group Management Protocol), 291
  - citrix, 356
  - DFP (Dynamic Feedabck Protocol), 244
  - DHCP (Dynamic Host Configuration Protocol), configuring, 227–230
  - DVMRP (Distance-Vector Multicast Routing Protocol), 85
  - EIGRP (Enhanced Interior Gateway Routing Protocol), 262–266
  - HSRP (Hot Standby Router Protocol), 223–224
    - configuring, 224–226
  - IGPs (Interior Gateway Protocols), 279

IGRP (Interior Gateway Routing Protocol), 259–260  
 IRDP (ICMP Router Discovery Protocol), 220, 232  
 ISAKMP (Internet Security Association and Key Management Protocol), 492  
 IS-IS, 275–278  
 MBGP (Multiprotocol BGP), 297–299  
 NTP, 257  
   disabling, 452  
   H.323, 428  
 OSPF (Open Shortest Path First), 266–273  
 RARP (Reverse Address Resolution Protocol), 218  
 RIP (Routing Information Protocol), 253–258  
 RTP (Real-Time Protocol), 345  
 SNAP (Subnetwork Access Protocol), 119  
 SSRP (Simple Server Redundancy Protocol), 124  
 STP (Spanning-Tree Protocol), 83  
 proxies, authentication, 462–465  
 PVCs (Permanent Virtual Circuits), 99  
 PVST (Per-VLAN Spanning Tree), 83  
 pwd command, 25

## Q

QoS (quality of service), 103  
 CAR, 372–373  
 CQ, 364–367  
 FRTS, 375–377  
 GTS, 374–375  
 LFI, 381–383  
 MQC (modular QoS command-line interface), 342–349  
 NBAR, 350–357  
 PBR, 357–358  
 policy propagation, 360–361  
 PQ, 362–363  
 RSVP, 377–380  
 voice, 398–401  
 VPNs, 359  
 WFQ, 367–369  
 WRED, 370–371

queuing  
 CQ, 364–367  
 FIFO, 103  
 LLQ, 378  
 PQ, 362–363  
 WFQ, 367–369

## R

RA (Registration Authority), 494  
 RARP (Reverse Address Resolution Protocol), 218  
 RAS (Registration, Admission, and Status), 427  
 RealAudio, 349  
 realms, 455  
 recognition, NBAR, 350–357  
 “recovery pending” state (modems), 137  
 redisplaying lines, 7  
 redistribute subnets command, 272  
 redistributing routing information, 310, 316  
   between RTMP and EIGRP, 333  
   into BGP, 317  
   into IS-IS, 317  
   into OSPF, 317  
   route maps, community lists, 314  
   route maps, creating, 312–316  
 reflective access lists, filtering IP sessions, 470–471  
 refreshing routers, 7  
 regular expressions, 285, 512  
   creating, 525–527  
   examples, 527  
   matches in chat scripts, 140  
   searching, 9  
   wildcards, 526  
 remark command, 513  
 remote peers  
   backup peer configuration, 198  
   BGP, 279–290  
   DLSw+, configuring, 197–198  
 remote sites, SRS, 438–442  
 removing modems from service, 136  
 request-data-size command, 51, 53  
 requests  
   inform, 40  
   keepalive, 106  
 resetting routing table, 307  
 resolving dialer contention, 150

- reverse Telnet connections, 11
- RIF (Routing Information Field), 183
- RIF strings, 185
- ring numbers (SRB), 184
- RIP (Routing Information Protocol), 253–256
  - commands, 256–258
  - redistributing into, 316
  - updates, controlling on NLSP networks, 326
- RMON (Remote Monitoring), 40
  - support, 48
- rotary groups
  - assigning multiple interfaces to, 152
  - load threshold, 150
- route dampening attribute (BGP), configuring as route map attribute, 315
- route filtering, 318, 320
  - access lists, implicit deny statements, 187
  - example, 321
- route maps
  - attributes
    - BGP community, 315
    - BGP local preference, 315
    - BGP origin, 315
    - BGP route dampening, 315
    - community attribute, 315
    - metric, 314
    - route tag value, 314
  - community lists, 314
  - creating, 312–313
  - policy routing configuration, 308–310
- route redistribution
  - configuring, 310, 316
  - example, 317–318
  - route maps, community lists, 314
  - route maps, creating, 312–316
- route tag value (route maps), setting, 314
- routed protocols, SRB configuration, 185
- route-map statement, 286
- route-map statements, 358
- router bgp command, 280
- router isis command, 275
- routers
  - ABR, 268
  - address spoofing, 450–451
  - ASBR, 273
  - BDR, 269
  - BSR, 293
  - DR, 269
  - HSRP, 223–226
  - logging synchronous, 7
  - management, 450
  - refreshing, 7
  - security, 448
    - AAA, 453–461
    - authentication, 448
    - CBAC, 475–480
    - configuring warning banners, 449–450
    - controlling line access, 449
    - Lock and Key, 466–469
  - services, controlling, 451–452
  - Telnet, 10
- routing
  - multicast, 291–295, 297
  - over dialup networks, 156
    - ODR, 159–160
    - snapshot routing, 157–159
  - PBR, 357–358
  - snapshot, 118
- Routing Control Field (RCF), 185
- routing protocols
  - AppleTalk
    - access lists, configuring, 523–525
    - configuring, 331–333
  - BGP, redistributing into, 317
  - distance vector, route filtering, 318–320
  - EIGRP, redistributing into, 316
  - IGRP, redistributing into, 316
  - IS-IS, redistributing into, 317
  - link-state, NLSP, 325–326
  - metrics, comparison chart, 311–312
  - Novell IPX, 323
    - access lists, configuring, 519–523
    - configuring, 323–325
    - example configuration, 329–330
  - OSPF, redistributing into, 317
  - redistribution, 317–318
  - RIP, redistributing into, 316
- rp-list option, 293
- RPs (rendezvous points), 291
- RSRB (Remote Source-Route Bridging), 191
  - example configuration, 194–195
  - FST, 191
  - NetBIOS filters, applying, 193–194

- SAP filters, applying, 193
- virtual rings, configuring, 191
- well-known ports, 191
- RST (reset), 473
- RSVP (Resource Reservation Protocol), QoS, 377–380
- RTP (Real-Time Protocol), 345
- RTTMON (round-trip time monitoring), 49

## S

- 
- SAA (Service Assurance Agent), 49–50, 413
    - configuring, 50–58
  - SAP (Service Advertising Protocol) filters, 521
    - applying to RSRB peers, 193
    - defining, 521–522
  - SAs (security associations), 500
  - SASs (Single-Attach Stations), 80
  - scaling-factors, 371
  - SDH (Synchronous Digital Hierarchy) networks, 96
  - SDNS (Secure Data Network Service), 223
  - searching
    - output, 9
    - regular expressions, 9
  - security
    - AAA, 453–461
    - CBAC, 475–480
    - IDE, 481, 483–484, 486–491
    - IKE for VPNs, 492–497, 499
    - IP sessions, filtering, 470–471
    - IPSec, VPN tunnels, 499–508
    - routers, 448
      - authentication, 448
      - configuring warning banners, 449–450
      - controllign services, 451–452
      - controlling lone access, 449
      - implementing logging, 450
      - Lock and Key, 466–469
      - management, 450
  - selecting encapsulation type
    - for IPX, 324
    - for Ethernet, 78
  - send process, monitoring, 140
  - send strings (modems), 139
  - sending messages, terminal sessions, 13
  - send-lifetime parameter, 257
  - serial interfaces
    - enabling STUN, 208
    - LFI, 381–383
    - referencing corresponding PRI interfaces, 142
  - servers
    - AAA, configuring, 453–461
    - ATM LANE, 124
  - Service Advertising Protocol. *See* SAP
  - service compress-config command, 28
  - service password-encryption command, 448
  - services
    - AAA, 462
    - routers, controlling, 451–452
  - sessions
    - IP, filtering, 470–471
    - Telnet, 10
    - timeout values, configuring, 13
    - warning, enabling, 13
  - set interface command, 309
  - set ip next-hop command, 309
  - set ip precedence command, 308
  - setting modem parameters, 137–139
  - SHA (Secure Hash Algorithm), 499
  - shaping traffic, 349, 374–377
  - show buffers command, 63
  - show call calltracker active command, 135
  - show call calltracker history command, 135
  - show cdp command, 31
  - show cdp interface command, 31
  - show cdp neighbors command, 18
  - show commands, 8
  - show crypto ca certificates command, 496
  - show history command, 8
  - show ip bgp regexp regular-expression command, 285
  - show ip nbar port-map command, 356
  - show ip nbar protocol-discovery command, 356
  - show ip route command, 307
  - show line line command, 12
  - show logging command, 68
  - show modemcap command, 138
  - show OSPF command, 272
  - show running config command, 7
  - show sessions command, 10, 13
  - show users all command, 12, 16
  - show version command, 59

- shutting down inactive modems, 136
- signatures, 482
- signaling, 402
  - CAS, 403, 426
  - CCS, 402
  - delay-start, 402
  - ground-start, 402
  - immediate-start, 402
  - QoS, RSVP, 377–380
  - wink-start, 402
- sizes of LFI fragments, 401
- sizing RMON queues, 48
- SLB (server load balancing), 244–248, 250
- SLDC (Synchronous Data Link Control), STUN, 206–211
- sleeptime parameter (ODR), 159, 255
- SNAP (Subnetwork Access Protocol), 119
- snapshot routing, 118
  - configuring, 157–158
  - example, 158–159
- sniffers, 70–71
- SNMP (Simple Network Management Protocol), 40
  - configuring, 41–49
  - router management, 450
- Software Bug Toolkit, 75. *See also* troubleshooting
- source-bridge command, 184
- spanning-tree, SRB configuration, 184–185
- sparse-dense-mode option, 292
- SPI (security parameter index), 234
- SPIDs (service profile identifiers), 141
  - BRI, 144
- split horizon, disabling on AppleTalk networks, 333
- spoofing
  - addresses, 450–451
  - SPX, 149
- SRB (Source-Route Bridging), 183
  - configuring, 184, 189
  - explorer frame processing, configuring, 189
  - NetBIOS names, filtering, 186
  - ring numbers, configuring, 184
  - routed protocols, bridging, 185
  - spanning-tree, 184–185
  - Token Ring packet filters, applying, 188
  - virtual rings, 184
- SRS (survivable remote site), 438–442
- SSH (Secure Shell), 14–15
- SSRP (Simple Server Redundancy Protocol), 124
- stacks, collecting traces, 71
- standard access lists
  - configuring, 512–513
  - IPX, 519–522
- standard IP access lists, example, 516–517
- standby command, 224
- standby preempt command, 225
- standby priority command, 225
- statements
  - route-map, 286
    - match, 286
    - permit, 470
    - route-map, 358
- static routes
  - assigning administrative distance, 306
  - configuring, 305–307
  - default static routes, 307
- statistics-distribution-interval command, 56
- status of ATM LANE, viewing, 128
- STP (Spanning-Tree Protocol), 83
- streaming, 349–350
- StreamWorks, 349
- strings, matching, 98
- STUN (Serial Tunnel), 206
  - configuring, 207–211
  - enabling on serial interfaces, 208
  - encapsulation, configuring, 208–209
  - local acknowledgment, configuring, 209
  - priority queuing, configuring, 209–210
  - traffic, prioritizing, 210–211
- summary addresses, filtering with extended access lists, 312
- SVCs (Switched Virtual Circuits), 99
- switching
  - APS, 96
  - CEF
    - configuring, 386–387
    - example configuration, 387
  - fast switching, 385
    - configuring, 385
    - example, 386
  - Frame Relay, configuring, 110–114
  - IPS, 97
  - MLS, configuring, 389–391

- NetFlow switching
  - configuring, 388–389
  - example configuration, 389
- synchronous serial interfaces, configuring, 86–95
- SYSLOG, 479

## T

- T1/E1 controller, ISDN PRI configuration, 142
- TAC (Technical Assistance Center), 74–75
- tag keyword (ip route command), 306
- Tc (committed rate measurement interval), 100
- TCL (Tool Command Language), 436
- TCP (Transmission Control Protocol)
  - access lists, defining, 515
  - disabling, 452
  - encapsulation, RSRB configuration, 192–193
  - intercept, preventing DoS attacks, 472–474
- TED (Tunnel Endpoint Discovery), 505
- TEI negotiation, 144
- Telnet
  - reverse connections, 11
  - sessions, 10
- telnet command, 67
- terminal logging command, 37
- terminal sessions, sending messages, 13
- text strings, creating regular expressions, 525–527
- threshold command, 57
- thresholds
  - fallback, 414
  - IOS IDS, 488
- time, router configuration, 31–35
- timeout command, 57
- timeouts, defining, 13
- timers
  - DLSw+, 198
  - ODR, tuning, 159
- Token Ring networks
  - DLSw+
    - mapping to DLC source, 200–203
    - on-demand peers, configuring, 203
    - traffic, prioritizing, 199
  - interfaces, configuring, 80–81
  - packet filtering, 188
  - RSRB, example configuration, 194–195
- tools, 63
  - debug, 68–69
  - ping, 64–65
  - sniffers, 70–71
  - Telnet, 67
  - traceroute, 66–67
- TOS (type of service), 55
  - matching in access lists, 515
- traceroute command, 66–67
- traffic
  - CBAC, 475–480
  - DLSw+
    - load balancing, 198–199, 203–204
    - prioritizing, 199
  - FRTS, 375–377
  - GTS, 374–375
  - IPX, load balancing, 324
  - limiting, 373
  - NBAR, 350–352, 354–357
  - RSRB, configuring access lists, 193–194
  - shaping, 349
  - SRB, configuring access lists, 187–189
  - STUN, prioritizing, 210–211
  - voice, 398–401
  - WRED, 370–371
- transport input none command, 449
- transport input telnet command, 449
- transport input telnet ssh command, 449
- traps, 40
  - SNMP, 48
- troubleshooting
  - buffers, 60
  - crashes, 71
  - tools, 63
    - debug, 68–69
    - ping, 64–65
    - sniffers, 70–71
    - Telnet, 67
    - traceroute, 66–67
- trunk connections, 411
- TTL (Time-to-Live), 222
- tuning ODR timers, 159
- tunneling
  - interfaces, configuring, 84–86
  - PPP encapsulation, 160
    - configuring, 161–163
    - example, 164



STUN, 206  
  configuring, 207–211

VPN  
  IPSec, 499–508  
  QoS, 359

type code access lists, configuring, 518  
types of file systems, 24

## U

---

UDP (User Datagram Protocol)  
  access lists, defining, 515  
  disabling, 452  
undelete command, 25  
update parameter, 255  
update parameter (ODR), 159  
user authentication, 448  
user interfaces, 5  
  access, configuring, 15–18  
  banners, configuring, 18  
  commands, entering, 7–11  
  configuration, 6  
  menus, configuring, 19–20  
  reverse Telnet connections, 11–14  
  SSH connections, 14–15  
  Web browsers, 21  
user-level passwords, 6  
utilities, 63  
  debug, 68–69  
  ping, 64–65  
  sniffers, 70–71  
  Telnet, 67  
  traceroute, 66–67

## V

---

VAD (Voice Activity Detection), 421  
values  
  precedence, 344  
  timeout, configuring, 13  
VCs (virtual circuits), 99, 115  
VCIs (Virtual Circuit Identifiers), 115  
verification messages, logging, 39  
version command, 254

viewing  
  Call Tracker history, 135  
  gateway of last resort, 307  
  lines, 7  
  messages, 37  
  preconfigured modem attributes, 138  
virtual rings  
  configuring, 184  
  RSRB, 191  
virtual-link command, 269  
VLAN (virtual LANs), 82–83  
VLSM (variable-length subnet masking), 262  
VoFR (Voice over Frame Relay), 416  
voice  
  bandwidth, 401  
  IVR, 436–438  
  ports, 402–415  
  QoS, 398–401  
VoIP (Voice over IP), 416  
  parameters, 425  
VPNs (Virtual Private Networks)  
  IKE, 492–497, 499  
  IPSec, 499–508  
  QoS, 359  
VRF (virtual routing and forwarding), 298

## W

---

warning sessions, enabling, 13  
warning banners, configuring, 449–450  
watchdog spoofing, 148–149  
Web browsers, configuring, 21  
weighted least connection, 244  
weighted round robin, 244  
WFQ (weighted fair queuing), 367–369  
where command, 10, 13  
wildcards  
  destination pattern, 418  
  for byte patterns, 187  
  matching against pattern multiples, 526  
wink-start signaling, 402  
WINS (Windows Internet Naming Service), 229  
WRED (Weighted Random Early Detection),  
  370–371, 348

## Z

---

- zone local command, 431
- zone remote command, 431
- zone subnet commands, 430
- zones (AppleTalk)
  - configuring, 332
  - filtering, 523