



INDEX

A

- absolute tunnel metric, 231–233
- abstract nodes (ERO), 177
- active LDP session establishment, 57–61
- adjusting
 - bandwidth, auto bandwidth, 246–251
 - RSVP input queue size, 180
 - TE tunnel metric, 229–231, 236–242
 - absolute tunnel metric, 231–233
 - relative tunnel metric, 233–236
- administrative weight
 - CSPF, 124–125
 - information distribution, 96–97
- administratively shut down tunnels, troubleshooting, 506–508
- admission control, 141
- advanced FRR features
 - bandwidth protection, 333
 - limited bandwidth, 334
 - unlimited backup, 334–335
 - configuring multiple backup tunnels to multiple NNHops, 338, 340
 - multiple tunnels to same MP, 329–332
 - promotion, 337
- advertising
 - delay in voice networks, 125–127
 - LDP labels, 62
 - address messages, 62–64
 - Address Withdraw messages, 64
 - Label Abort Request messages, 67
 - Label Mapping messages, 66
 - Label Release messages, 67
 - Label Request messages, 65
 - Label Withdraw messages, 66
 - Notification messages, 68
- AF (Assured Forwarding) values, 266
- affinities, 94–96
- allocating reservable bandwidth, 85–87
- append-after command, 551
- applying
 - MPLS TE, 17
 - negative offsets to tunnel costs, 234
 - tactical TE to real-world situations, 479–484
- APS (automatic protection switching), 292
- areas, 187

- assigning tunnel numbers, 469–471
- associating backup tunnels with protected links, 306–308
- ATM (Asynchronous Transfer Mode)
 - cell mode MPLS, 26–28
 - frame-mode MPLS, 27
 - IP integration, 11–12
 - resource contention, 6
 - traffic engineering, 8–10
 - fish problem, 9–10, 13
 - versus MPLS TE, 15
- AToM (Any Transport over MPLS), 14
- attribute flags, information distribution, 93–96
- auto bandwidth
 - configuring, 248–251
 - operation, 246–248
- autoroute, 12
 - forwarding traffic down tunnels, 209–216
 - DS-TE traffic, 284–286
 - multicast RPF, 467–469
- available bandwidth information distribution, 85–87

B

- backup LSPs, 294
- backup resources versus protection schemes, 293
- backup tunnels, 293
 - associating with protected links, 306–308
 - multiple tunnels to same MP, 329–332
 - NHop versus NNHop, 332
 - parallel, 332
 - promotion, 337
- backward compatibility, LDP support for TDP commands, 54
- bandwidth
 - admission control, 141
 - auto bandwidth
 - configuring, 248–251
 - operation, 246–248
 - consumable resources, 12
 - CSPF, 124
 - measuring with TE tunnels, 453–454
 - oversubscription ratio, 5

- protection, 333
 - limited backup bandwidth, 334
 - unlimited backup bandwidth, 334–335
- reference bandwidth (OSPF), 125
- reserving, 85–87
- subpools, 278
- thresholds, 99–102
- best path calculation, reoptimization, 135
- event-driven, 136
- lockdown, 137
- manual, 136
- periodic, 136
- buffering, statmux, 5
- building
 - services, 14
 - traffic matrices
 - with NetFlow, 444
 - with TMS, 444–453

C

- calculating latency
 - ping method, 127
 - route-mile estimation, 128
 - SAA, 128
- call admission control, 277
- case studies, sample networks, 392–395
- CEF (Cisco Express Forwarding), configuring, 70–71
- cell mode MPLS, 26–28
 - interface configuration, 74
 - restrictions, 46–47
- cells, 4
- CIA World Factbook, 128
- Cisco IOS, SAA
 - measuring delay, 455
 - measuring one-way delay, 459–461
 - measuring two-way delay, 457–459
- class maps, configuring, 258–260
- classification of packets, 28
 - DiffServ, 255–256
 - FEC, 28–29
 - label operations, 29
- commands
 - append-after, 551
 - debug, 550
 - debug mpls traffic-eng, 550
 - debug mpls traffic-eng path, 550
 - debug mpls traffic-eng topology, 550
 - debug mpls traffic-eng tunnels, 550
 - exclude address, 551
 - exec, 544
 - global configuration, 544
 - IGP configuration, 548–549
 - index, 551
 - ip rsvp bandwidth, 550
 - ip rsvp msg-pacing, 549
 - ip rsvp signalling hello, 549
 - list, 551
 - mpls accounting experimental, 546
 - mpls netflow egress, 546
 - mpls traffic-eng administrative-weight, 546
 - mpls traffic-eng area, 548
 - mpls traffic-eng attribute-flags, 546
 - mpls traffic-eng auto-bw timers, 544
 - mpls traffic-eng backup-path, 546
 - mpls traffic-eng flooding thresholds, 546
 - mpls traffic-eng interface, 549
 - mpls traffic-eng level-1, 549
 - mpls traffic-eng level-2, 549
 - mpls traffic-eng link-management timers
 - bandwidth-hold, 464, 544
 - mpls traffic-eng link-management timers
 - periodic-flooding, 464–465, 544
 - mpls traffic-eng logging lsp, 544
 - mpls traffic-eng logging tunnel
 - lsp-selection, 545
 - mpls traffic-eng multicast-intact, 549
 - mpls traffic-eng path-selection metric, 545
 - mpls traffic-eng path-selection overload
 - allow, 545
 - mpls traffic-eng reoptimize, 544
 - mpls traffic-eng reoptimize events link-up, 463, 545
 - mpls traffic-eng reoptimize timers frequency, 462, 545
 - mpls traffic-eng router-id, 549
 - mpls traffic-eng scanner interval, 549
 - mpls traffic-eng scanner max-flash, 549

- mpls traffic-eng signalling advertise
 - implicit-null, 545
- mpls traffic-eng signalling interpret
 - explicit-null verbatim, 545
- mpls traffic-eng topology holddown sigerr, 463, 545
- mpls traffic-eng tunnels, 545–546
- next-address, 551
- path-option, CSPF configuration, 128–134
- physical interface configuration, 546
- RSVP, 549–550
- show, 542–543
- show ip rsvp counters, 182–183
- show ip rsvp interface, 183
- show ip rsvp neighbor, 184
- show ip rsvp reservation, 184, 186
- show mpls traffic-eng link-management
 - admission-control, 198
- show mpls traffic-eng link-management advertisements, 199–200
- show mpls traffic-eng link-management bandwidth-allocation, 201–202
- show mpls traffic-eng link-management igp-neighbors, 202
- show mpls traffic-eng link-management interfaces, 202–203
- show mpls traffic-eng link-management statistics, 203–204
- show mpls traffic-eng link-management summary, 204
- show mpls traffic-eng tunnel, 508–510
- snmp-server enable traps mpls traffic-eng, 544
- tunnel interface configuration, 547–548
- tunnel mpls traffic-eng affinity, 547
- tunnel mpls traffic-eng auto-bw, 547
- tunnel mpls traffic-eng autoroute announce, 547
- tunnel mpls traffic-eng autoroute metric, 547
- tunnel mpls traffic-eng bandwidth, 547
- tunnel mpls traffic-eng fast-reroute, 548
- tunnel mpls traffic-eng forwarding-adjacency, 548
- tunnel mpls traffic-eng load-share, 548
- tunnel mpls traffic-eng path-option, 548
- tunnel mpls traffic-eng path-selection metric, 548
- tunnel mpls traffic-eng priority, 548
- tunnel mpls traffic-eng record-route, 548
- common header format (RSVP packets), 143
- Common Hello Parameters TLV format (LDP hello messages), 55–57
- Common Session Parameters TLV format (LDP initialization messages), 60
- comparing
 - flooding in IS-IS and OSPF, 100–101
 - IP and MPLS forwarding, 31–40
 - LDP hello messages and keepalives, 62
 - MPLS TE and ATM, 15
 - MPLS TE and QoS, 15
 - node and link protection, 326–329
 - SPF and CSPF, 119
- components of DiffServ, 255
- configuring
 - administrative weight, 96–97
 - attribute flags, 93–96
 - auto bandwidth, 248–251
 - class maps, 258–260
 - CSPF, path-option command, 128–134
 - DS-TE, 278
 - headend subpool bandwidth requirements, 279
 - headend tunnel admission control, 280
 - per-link scheduling, 279
 - per-link subpool bandwidth availability, 279
 - tunnel preemption, 280–283
- forwarding adjacency
 - holdtime, 242–244
 - restrictions, 246
- headend, 502–503
- LDP, 69
 - CEF, 70–71
 - Cell-Mode interface, 74
 - Frame-Mode interface, 72–73
 - global MPLS forwarding, 72
 - session attributes, 78
- link protection, 302–309
 - downstream signalling, 323
 - failure detection, 309–312
 - IGP notification, 322
 - restoring connectivity, 312–317
 - upstream signalling, 317–322
- MPLS TE, prerequisites, 81–84
- policy maps, 260–262
- primary tunnels, 494–495

- QoS, MQC, 257–263
 - reservable bandwidth, 85–87
 - SAA probes, DSCP, 461–462
 - service policies, 263
 - TE tunnels with multiple paths options, 134
 - TMS, 447
 - tunnel priority, 88–93
 - holding priority, 92
 - setup priority, 92–93
- congestion, handling with MPLS TE, 17
- connectivity, restoring, 312–317
- conservative retention mode, 45
- constraints, 510–519
- consumable resources, 12
- control plane, 28
 - in MPLS network, 30–31
- convergence, limitations of IGP, 291
- cost metric, advertising delay, 126–128
- creating explicit paths, 130–134
- cross-connect table (MPLS MIB), 359–361
- CSCP (Class Selector Code Points), 265
- CSPF (Constrained SPF) algorithm
 - administrative weight, 124–125
 - bandwidth, 124
 - examples, 120
 - explicit paths, 130
 - link attributes, 124
 - operation, 119–122
 - path-option configuration, 128
 - tiebreakers, 122–124

D

- data files (TMS), 450–453
- databases, verifying TE-DB information, 519–524
- debug commands, 550
 - troubleshooting headend, 506
- debug mpls traffic-eng forwarding-adjacency
 - command, 550
- debug mpls traffic-eng link-management
 - command, 550
- debug mpls traffic-eng load-balancing
 - command, 550
- debug mpls traffic-eng path, 550
- debug mpls traffic-eng topology command, 550
- debug mpls traffic-eng tunnels command, 550
- decision-making process (CSPF), tiebreakers, 123
- decoupling routing and forwarding processes, 11

- defining FRR scalability variables, 431–436
 - link protection, 432
 - node protection, 433
 - path protection, 433
- delay
 - advertising in voice networks, 125–127
 - measuring
 - one-way, 459–461
 - two-way, 457–459
 - with SAA, 455
- deploying MPLS TE, related URLs, 565
- descriptions, assigning to tunnels, 470–471
- design models
 - offline strategic, packing problem, 427–430
 - strategic, 408
 - event-driven reoptimization, 422–423
 - LSP scalability, 409–419
 - manual reoptimization, 424
 - multiple parallel tunnels, 426
 - periodic reoptimization, 421–422
 - tunnel reoptimization, 420–421
 - tunnel resizing, 425
 - tactical, 396
 - building LSPs, 396–398
 - placement of LSPs, 398–403
 - recommended features, 406–407
 - removing tunnels, 403–406
- detecting failed links, 309–310
 - RSVP hellos, 310–317
 - SONET alarms, 310
- DiffServ, 253–254
 - components of, 255
 - dropping packets, 257
 - DSCP, conversion from IP Precedence, 265
 - EXP bit, interaction with IP Precedence, 270–271
 - IP
 - DSCP byte, 265
 - MPLS packets, 267
 - ToS byte, 264
 - marking, 256
 - MQC, 255
 - packet classification, 255–256
 - policing, 256
 - queuing, 256–257
 - tunnel modes
 - Pipe mode, 275–276
 - Short-Pipe mode, 274–275
 - Uniform mode, 273–274

Dijkstra Shortest Path First algorithm, 114
 directly connected neighbors (LDP), discovery process, 53–57
 discovery interval, LDP Hello messages, 58
 displaying
 RSVP input queue size, 179
 TMS data, 447–450
 distribution of label bindings, 42
 label space, 45
 liberal versus conservative label retention mode, 45
 ordered versus independent control, 42–43
 unsolicited downstream versus DoD, 43–44
 DoD (Downstream-on-Demand)
 label distribution, 43–45
 loop detection, 69
 downstream routers, 140–141
 dropping packets, 257
 DSCP (DiffServ Code Point) bits, 265
 DS-TE (DiffServ-Aware Traffic Engineering), 254, 277–278
 call admission control, 277
 configuring, 278–280
 forwarding traffic down tunnels, 284–288
 subpools, 278
 tunnel-preemption, configuring, 280–283

E

ECMP (Equal-Cost MultiPath), 122–124
 ECN (Explicit Congestion Notification), 265
 EF (Expedited Forwarding) values, 266
 end-to-end latency, methods of calculation
 pinging, 127
 route-mile estimation, 128
 SAA, 128
 equal-cost load sharing, 216
 behind tunnel tail, 219–221
 between TE tunnel and IGP path, 217
 to tunnel tail, 217–219
 equal-cost paths, ATM traffic engineering, 10
 ERO (Explicit Route Object), 155
 subobjects, 177
 ERROR_SPEC class format (RSVP packets), 148–149
 establishing LDP sessions, 57–61
 estimating route-miles, latency calculation, 128

ethertype, 37
 event-driven reoptimization, 136
 exclude-address command, 551
 EXEC commands, 544
 EXP bits (frame mode MPLS), 26
 interaction with IP Precedence, 270–271
 ip2mpls, 267
 PHBs, 271
 mpls2ip, 269
 PHBs, 271
 mpls2mpls, 268
 explicit null labels, 178–179
 explicit paths, 130–134
 EXPLICIT_ROUTE class format (RSVP packets), 155
 expressions, $O(N^2)$, 8

F

FEC (Forwarding Equivalence Class), 28–29
 FIB table, role in MPLS forwarding, 40–41
 field definitions, RSVP common header, 144
 files, TMS data files, 450–453
 FILTERSPEC class format (RSVP packets), 151
 flooding
 distribution information, bandwidth thresholds, 99–102
 MPLS TE in IS-IS, 107–110
 MPLS TE in OSPF, 103–105
 periodic, 102
 FLOWSPEC class format (RSVP packets), 150
 format
 Hello messages (RSVP), 168
 Path messages (RSVP), 160–162
 PathErr messages (RSVP), 166
 PathTear messages (RSVP), 164
 Resv messages (RSVP), 162–163
 ResvConf messages (RSVP), 167
 ResvErr messages (RSVP), 166
 ResvTear messages (RSVP), 164–165
 ResvTearConf messages (RSVP), 167–168
 Forward (F) bit, LDP messages, 52
 forwarding
 control plane, 28
 decoupling, 11
 DS-TE traffic down a tunnel, 284–288
 label space, 45

MPLS

- cell mode, 26–28, 46–47
- control plane, 30–31
- FIB table, 40–41
- frame mode, 25–26
- IP versus MPLS, 31–40
- label distribution, 42–43, 45
- Layer 2 encapsulation, 27
- LFIB table, 40–41
- LIB table, 40–41
- loop detection (DoD mode), 69
- packet classification, 28
 - FEC, 28–29
 - label operations, 29
- related URLs, 555–556

forwarding adjacency, 242–244

- restrictions, 246
- scalability, 437

forwarding traffic down tunnels

- with autoroute, 209–216
- with PBR, 208–209
- with static routes, 207–208

Frame Relay, statmux, 5

Frame-Mode MPLS, 25–26

- interface configuration, 72–73

frames, 4

FRR (Fast Reroute), 291–292

- backup bandwidth reservation, 333–335
- configuring multiple backup tunnels to multiple NNHops, 338–340
- link protection
 - connectivity restoration, 312–317
 - downstream signalling, 323
 - failure detection, 309–312
 - IGP notification, 322
 - prefailure configuration, 302–309
 - scalability, 432–433
 - upstream signalling, 317–322
- multiple backup tunnels, 329–332
- promotion, 337
- scalability, defining variables, 431–436

functions of LDP

- label advertisement, 62
 - address messages, 62–64
 - Address Withdraw messages, 64
 - Label Abort Request messages, 67
 - Label Mapping messages, 66
 - Label Release messages, 67
 - Label Request messages, 65
 - Label Withdraw messages, 66
 - Notification messages, 68
 - neighbor discovery, 53–57
 - session establishment/maintenance, 57–61

G

- global configuration commands, 544–545
 - LSR configuration requirements, 496–498
 - ip cef command, 496
 - mpls traffic-eng command, 498
- global MPLS forwarding, configuring, 72

H

handling

- congestion, 17
- link/node failures, 17

hard-state protocols, 139

headend

- affinities, 94–96
- configuring, 502–503
 - knobs, 462–463
- constraints, 510–519
- link protection, configuring, 303
- reroute, 292
- troubleshooting
 - debug commands, 506
 - show commands, 504

HELLO class format, RSVP packets, 157

hello interval (LDP), modifying, 58

hello messages

- LDP, 53
 - Common Hello Parameters TLV format, 55–57
 - Hold Time, 55
 - RSVP, 140

Hold Time, LDP hello messages, 55

holding priority, tunnel configuration, 92–93

hop count TLV, 46

I

- identification schemes, 469–471
- IGP configuration commands, 548–549

-
- IGPs (Interior Gateway Protocols), limitations of convergence, 291
 - implicit null labels, 178–179
 - independent LSP control mode, 43
 - index command, 551
 - information distribution, 84
 - administrative weight, 96–97
 - attribute flags, 93–96
 - available bandwidth information, 85–87
 - bandwidth thresholds, 99–102
 - IS-IS, 107–110
 - OSPF, 103–105
 - periodic flooding, 102
 - related URLs, 557
 - timers, 98–99
 - tunnel priority, 88–93
 - holding priority, 92
 - setup priority, 92–93
 - validating, 519–525
 - initialization messages, LDP, 60–61
 - input queues (RSVP), adjusting size of, 180
 - InSegment Performance table (MPLS MIB), 354–355
 - InSegment table (MPLS MIB), 350–353
 - integrating
 - MPLS TE and MPLS VPNs, 471–475
 - IP and ATM, 11–12
 - intended receivers of RSVP messages, 175–177
 - interarea tunnels, 187–188
 - features, 188
 - operation, 189–195
 - restrictions, 195–197
 - interface configuration table (MPLS MIB), 344–349
 - interface-level commands, configuration requirements, 499–501
 - interface performance table (MPLS MIB), 349–350
 - IntServ, 253
 - invalid tunnel paths, troubleshooting, 508–510
 - IP
 - ATM integration, 11–12
 - QoS
 - DSCP byte, 265
 - ToS byte, 264
 - IP forwarding versus MPLS forwarding, 31–40
 - IP Precedence
 - bit values, 270
 - converting to DSCP, 265
 - interaction with EXP bit, 270–271
 - ip rsvp bandwidth command, 550
 - ip rsvp msg-pacing command, 549
 - ip rsvp signalling hello command, 549
 - IP switching, 10
 - ip2mpls push, 267
 - PHBs, 271
 - IP-Extended TLVs, 107
 - IS-IS (Intermediate System-to-Intermediate System)
 - configuration, troubleshooting, 502
 - flooding, comparing to OSPF, 100–101
 - information distribution, 107–110
 - narrow metrics, migration to wide metrics, 466
- ## K
-
- keepalive messages, LDP, 62
 - knobs
 - mpls traffic-eng reoptimize events link-up, 463
 - mpls traffic-eng reoptimize timers frequency command, 462
 - mpls traffic-eng topology holddown sigerr, 463
- ## L
-
- label disposition, 29
 - label distribution, 42
 - label space, 45
 - liberal versus conservative label retention mode, 45
 - ordered versus independent control, 42–43
 - unsolicited downstream versus DoD, 43–44
 - label space, 45
 - LABEL_REQUEST class format
 - RSVP packets, 155
 - Label-Controlled ATM, 16
 - labels
 - advertisements (LDP), 62
 - address messages, 62–64
 - Address Withdraw messages, 64
 - Label Abort Request messages, 64
 - Label Mapping messages, 66
 - Label Release messages, 67
 - Label Request messages, 65
 - Label Withdraw messages, 66
 - Notification messages, 68
 - popping, 29
 - pushing, 29

- stack entries, 25–26
- swapping, 29
- latency, methods of calculation
 - pinging, 127
 - route-mile estimation, 128
 - SAA, 128
- Layer 2 encapsulation (MPLS), 27
- LDP (Label Distribution Protocol), 50
 - address messages, 62–64
 - Address Withdraw messages, 64
 - CEF, configuring, 70–71
 - Cell-Mode interface, configuring, 74
 - configuring, 69
 - Frame-Mode interface, configuring, 72–73
 - global MPLS forwarding, configuring, 72
 - hello interval, modifying, 58
 - hello messages, 53
 - Common Hello Parameters TLV format, 55–57
 - Hold Time, 55
 - initialization messages, 60–61
 - interface configuration, 476–478
 - keepalive messages, 62
 - Label Abort Request messages, 67
 - label advertisement, 62
 - address messages, 62–64
 - Address Withdraw messages, 64
 - Label Abort Request messages, 67
 - Label Mapping messages, 66
 - Label Release messages, 67
 - Label Request messages, 65
 - Label Withdraw messages, 66
 - Notification messages, 68
 - message format, 51–52
 - neighbor discovery, 53–57
 - Notification messages, 68
 - PDU header, 50
 - session attributes, configuring, 78
 - session establishment/maintenance, 57–61
 - support for TDP commands, 54
 - verifying configuration, 74–77
- Length field (LDP messages), 52
- LFIB table, role in MPLS forwarding, 40–41
- LIB table, role in MPLS forwarding, 40–41
- liberal retention mode, 45
- limitations
 - of forwarding adjacency, 246
 - of interarea tunnels, 195–197
- limited backup bandwidth, 334
- link attributes, CSPF, 124
- link failures. *See also* node failures
 - APS, 292
 - detection, 309–310
 - RSVP hellos, 310–312
 - SONET alarms, 310
 - downstream signalling, 323
 - FRR (Fast Reroute), 292
 - handling with MPLS TE, 17
 - headend reroute, 292
 - IGP notification, 322
 - protection, 293, 302–309
 - local protection, 295–301
 - node protection, 300–301, 326–329
 - path protection, 294
 - resiliency, 292
 - restoring connectivity, 312–317
 - upstream signalling, 317–322
 - versus node failures, 326–329
- link manager, 197–204
- link protection, 299
 - downstream signalling, 323
 - failure detection, 309–310
 - RSVP hellos, 310–317
 - SONET alarms, 310
 - over one-hop tunnels, SONET APS, 485–486, 489
 - prefailure configuration, 302–309
 - restoring connectivity, 312
 - upstream signalling, 317–322
 - versus node protection, 301, 326
- link-state database, 114
- link-state protocols
 - IS-IS, information distribution, 107–110
 - OSPF
 - information distribution, 103–105
 - reference bandwidth, 125
 - SPF algorithm
 - ECMP, 122–124
 - link-state database, 114
 - operation, 114–118
 - PATHs list, 115
 - root node, 115
 - TENT list, 115
 - versus CSPF, 119
- list command, 551
- L-LSPs (Label-Only Inferred PSC LSPs), 267
- load balancing (unequal-cost), applying to one-hop tunnels, 489–490

- load sharing, 216
 - equal-cost
 - behind tunnel tail, 219–221
 - between TE tunnel and IGP path, 217
 - to tunnel tail, 217–219
 - unequal-cost, 221–223
 - operation, 224–229
- local protection, 295–299
 - advanced FRR features, 329–332
 - bandwidth protection, 333–335
 - configuring multiple backup tunnels to multiple NNHops, 338–340
 - promotion, 337
 - link protection, 299
 - connectivity restoration, 312
 - downstream signalling, 323
 - failure detection, 309–317
 - prefailure configuration, 302–309
 - upstream signalling, 317–322
 - versus node protection, 301
 - node protection, 300–301
 - versus link protection, 326–329
- lockdown, 137
- logical entities, protection schemes, 293. *See also*
 - link protection; node protection
 - local protection, 295–323, 326–329
 - path protection, 294
- loop detection, MPLS DoD, 69
- LSPs. *See also* TE tunnels
 - headend reroute, 292
 - local protection, 295, 299
 - link protection, 299–310, 312–323
 - node protection, 300–301, 326–329
 - path protection, 294
 - placement
 - with offline tools, 430–431
 - with tactical design model, 398–403
 - setup, RSVP, 141
 - standby, 294
- LSRs, configuring
 - global configuration commands, 496–498
 - headend, 502–503
- Mandatory parameters, LDP messages, 52
- manual reoptimization, 136
- marking packets, DiffServ, 256
- max-fill LSP placement, 427
- measurement tools, building traffic matrices
 - with NetFlow, 444
 - with TMS, 444–453
- measuring
 - delay
 - one-way, 459–461
 - two-way, 457–459
 - with SAA, 455
 - TE tunnel traffic, 453–454
- messages
 - LDP
 - Address messages, 62–64
 - Address Withdraw messages, 64
 - Common Hello Parameters TLV format, 55–57
 - format, 51–52
 - hello, 53
 - Hold Time, 55
 - initialization messages, 60–61
 - keepalive, 62
 - Label Abort Request messages, 67
 - Label Mapping messages, 66
 - Label Release messages, 67
 - Label Request messages, 65
 - Label Withdraw messages, 66
 - Notification messages, 68
 - RSVP, 140, 179–181
 - Hello, 168
 - Path, 160–162
 - PathErr, 166
 - PathTear, 164
 - receivers, 175–177
 - Resv, 162–163
 - ResvConf, 167
 - ResvErr, 166
 - ResvTear, 164–165
 - ResvTearConf, 167–168
- metrics
 - administrative weight, information distribution, 96–97
 - delay, integrating with bandwidth metric, 126–128
 - narrow (IS-IS), migration to wide metrics, 466
 - reference bandwidth, 125

M

- maintenance of LDP sessions, 57–61
- make-before-break (RSV-TE), 136, 169
 - link protection, 319

- TE tunnels, adjusting, 229–242
- wide, 108
- MIBs (Management Information Bases)
 - MPLS LSR MIB, 343
 - cross-connect table, 359–361
 - InSegment Performance table, 354–355
 - InSegment table, 350–353
 - interface configuration table, 344–349
 - interface performance table, 349–350
 - OutSegment Performance table, 358
 - OutSegment table, 355–357
 - MPLS TE MIB
 - mpls TunnelHop Table, 383–387
 - mpls TunnelResource Table, 387–389
 - mpls TunnelTable, 362–382
- midpoint
 - configuration knobs, 464–465
 - troubleshooting
 - debug commands, 506
 - show commands, 504–505
- migrating from narrow to wide metrics, 466
- misconfiguration, troubleshooting
 - global configuration, 496–498
 - interface-level configuration, 499–501
 - routing protocol configuration, 502
 - tunnels, 532–538
- models of TE design
 - offline strategic, packing problem, 427–430
 - strategic, 408
 - event-driven reoptimization, 422–423
 - LSP scalability, 409–419
 - manual reoptimization, 424
 - multiple parallel tunnels, 426
 - periodic reoptimization, 421–422
 - tunnel reoptimization, 420–421
 - tunnel resizing, 425
 - tactical, 396
 - building LSPs, 396–398
 - placement of LSPs, 398–403
 - recommended features, 406–407
 - removing tunnels, 403, 405–406
- modifying LDP hello interval, 58
- MPLS (Multiprotocol Label Switching)
 - cell mode, 26–28
 - restrictions, 46–47
 - control plane mechanism, 30–31
 - decoupling routing and forwarding processes, 11
 - DoD, loop detection, 69
 - EXP bits
 - ip2mpls, 267
 - mpls2ip, 269–271
 - mpls2mpls, 268
 - PHBs, 271
 - forwarding mechanism, 31–40
 - frame mode, 25–26
 - IP/ATM integration, 11–12
 - label distribution, 42
 - label space, 45
 - liberal versus conservative label retention mode, 45
 - ordered versus independent control, 42–43
 - unsolicited downstream versus DoD, 43–44
 - Layer 2 encapsulation, 27
 - VPNs, combining with TE, 471–475
- mpls accounting experimental command, 546
- MPLS forwarding, 40–41
- MPLS LSR MIB, 343
 - cross-connect table, 359–361
 - InSegment Performance table, 354–355
 - InSegment table, 350–353
 - interface configuration table, 344–349
 - interface performance table, 349–350
 - OutSegment Performance table, 358
 - OutSegment table, 355–357
- mpls netflow egress command, 546
- MPLS TE applications, 17
- MPLS TE MIB
 - mpls TunnelHop Table, 383–387
 - mpls TunnelResource Table, 387–389
 - mpls TunnelTable, 362–382
- mpls traffic-eng administrative-weight command, 546
- mpls traffic-eng area command, 548
- mpls traffic-eng attribute-flags command, 546
- mpls traffic-eng auto-bw timers command, 544
- mpls traffic-eng backup-path command, 546
- mpls traffic-eng flooding thresholds command, 546
- mpls traffic-eng interface command, 549
- mpls traffic-eng level-1 command, 549
- mpls traffic-eng level-2 command, 549
- mpls traffic-eng link-management timers
 - bandwidth-hold command, 464, 544
- mpls traffic-eng link-management timers periodic-flooding command, 464–465, 544
- mpls traffic-eng logging lsp command, 544

- mpls traffic-eng logging tunnel lsp-selection command, 545
- mpls traffic-eng multicast-intact command, 549
- mpls traffic-eng path-selection metric command, 545
- mpls traffic-eng path-selection overload allow command, 545
- mpls traffic-eng reoptimize command, 544
- mpls traffic-eng reoptimize events link-up command, 463, 545
- mpls traffic-eng reoptimize timers frequency command, 462, 545
- mpls traffic-eng router-id command, 549
- mpls traffic-eng scanner interval command, 549
- mpls traffic-eng scanner max-flash command, 549
- mpls traffic-eng signalling advertise implicit-null command, 545
- mpls traffic-eng signalling interpret explicit-null verbatim command, 545
- mpls traffic-eng topology holddown sigerr command, 463, 545
- mpls traffic-eng tunnels command, 545–546
- MPLS TunnelHop Table (MPLS TE MIB), 383–387
- MPLS TunnelResource Table (MPLS TE MIB), 387–389
- MPLS TunnelTable (MPLS TE MIB), 362–363, 365–366, 368–374, 376, 378–382
- mpls2ip, 269
 - PHBs, 271
- mpls2mpls, 268
- mplsOutSegmentNextHopIpAddr (mplsOutSegmentTable), 357
- mplsOutSegmentNextHopIpAddrType (mplsOutSegmentTable), 357
- mplsOutSegmentPushTopLabel variable (mplsOutSegmentTable), 356
- mplsOutSegmentTopLabel (mplsOutSegmentTable), 357
- mplsTunnelARHopTableIndex variable (mplsTunnelTable), 373
- mplsTunnelCHopTableIndex variable (mplsTunnelTable), 374
- mplsTunnelCreationTime variable (mplsTunnelTable), 376
- mplsTunnelDescr variable (mplsTunnelTable), 368
- mplsTunnelExcludeAllAffinity variable (mplsTunnelTable), 379
- mplsTunnelHoldingPrio variable (mplsTunnelTable), 371
- mplsTunnelHopAddrType variable (mplsTunnelHopTable), 385
- mplsTunnelHopIncludeExclude variable (mplsTunnelHopTable), 386
- mplsTunnelHopIpv4Addr variable (mplsTunnelHopTable), 385
- mplsTunnelHopIpv4PrefixLen variable (mplsTunnelHopTable), 385
- mplsTunnelHopPathOptionName variable (mplsTunnelHopTable), 387
- mplsTunnelHopTableIndex variable (mplsTunnelTable), 373
- mplsTunnelHopType variable (mplsTunnelHopTable), 386
- mplsTunnelIfIndex variable (mplsTunnelTable), 369
- mplsTunnelIncludeAllAffinity variable (mplsTunnelTable), 379
- mplsTunnelIncludeAnyAffinity variable (mplsTunnelTable), 379
- mplsTunnelInstancePriority variable (mplsTunnelTable), 373
- mplsTunnelIsIf variable (mplsTunnelTable), 368
- mplsTunnelLastPathChange variable (mplsTunnelTable), 376
- mplsTunnelLocalProtectInUse variable (mplsTunnelTable), 372
- mplsTunnelName variable (mplsTunnelTable), 367
- mplsTunnelOperStatus variable (mplsTunnelTable), 382
- mplsTunnelOwner variable (mplsTunnelTable), 372
- mplsTunnelPathChanges variable (mplsTunnelTable), 375
- mplsTunnelPathInUse variable (mplsTunnelTable), 380
- mplsTunnelPrimaryTime variable (mplsTunnelTable), 374
- mplsTunnelResourcePointer variable (mplsTunnelTable), 373
- mplsTunnelRole variable (mplsTunnelTable), 380
- mplsTunnelSessionAttributes variable (mplsTunnelTable), 371
- mplsTunnelSetupPrio variable (mplsTunnelTable), 370
- mplsTunnelSignallingProto variable (mplsTunnelTable), 370
- mplsTunnelStateTransitions variable (mplsTunnelTable), 378
- mplsTunnelTotalUpTime variable (mplsTunnelTable), 381

- mplsTunnelXCPointer variable (mplsTunnelTable), 369
- MQC (Modular QoS CLI), 255–258
 - class maps, configuring, 258–260
 - policy maps, configuring, 260–262
 - service policies, configuring, 263
- multicast, RPF lookup, 467–469
- multiple paths options for TE tunnels, 134
- multiplexing
 - statmux, 4
 - over statmux, 6
 - resource contention, 5
 - TDM, 3–4

N

- narrow metrics (IS-IS), migration to wide metrics, 466
- neighbor discovery, LDP, 53–55, 57
- NetFlow, building traffic matrices, 444
- network design
 - offline strategic model, packing problem, 427–430
 - related URLs, 564
 - strategic model, 408
 - event-driven reoptimization, 422–423
 - LSP scalability, 409–419
 - manual reoptimization, 424
 - multiple parallel tunnels, 426
 - periodic reoptimization, 421–422
 - tunnel reoptimization, 420–421
 - tunnel resizing, 425
 - tactical model, 396
 - building LSPs, 396–398
 - placement of LSPs, 398–403
 - recommended features, 406–407
 - removing tunnels, 403–406
- network engineering versus traffic engineering, 7
- next-address command, 551
- NHOp backup tunnels, 332
- NNHop backup tunnels, 332
- node failures, handling with MPLS TE, 17
- node protection, 300–301
 - versus link protection, 301, 326–329
- non-directly connected neighbors (LDP), discovery process, 53–57
- numbering tunnels, 469–471

O

- O(N²), 8
- object class format, RSVP packets, 144–147
- objects (RSVP)
 - ERROR_SPEC, 148–149
 - EXPLICIT_ROUTE, 155
 - abstract nodes, 177
 - FILTERSPEC, 151
 - FLOWSPEC, 150
 - HELLO, 157
 - LABEL_REQUEST, 155
 - RECORD_ROUTE, 156
 - RESV_CONFIRM, 154
 - RSVP_LABEL, 154
 - SCOPE, 149
 - SENDER_ADSPPEC, 153
 - SENDER_TEMPLATE, 152
 - SENDER_TSPEC, 152
 - SESSION, 147
 - SESSION_ATTRIBUTE, 158
 - STYLE, 150
 - TIME_VALUES, 148
- offline strategic design model, packing problem, 427–430
- offline tools, placing LSPs, 430–431
- one-hop tunnels
 - link protection, 485–486, 489
 - unequal-cost load balancing, 489–490
- one-way delay, measuring, 459, 461
- one-way probes, 459, 461
- optimality, 401
- optimizing network utilization, 17
- Optional Parameters (LDP messages), 52
- ordered LSP control mode, 43
- OSPF (Open Shortest Path First)
 - configuration, troubleshooting, 502
 - flooding, comparing to IS-IS, 100–101
 - information distribution, 103–105
 - reference bandwidth, 125

OutSegment Performance table (MPLS MIB), 358
 OutSegment table (MPLS MIB), 355–357
 overlay model, 12
 oversubscription ratio, 5

P

packets

- classification, 255–256
- classification during forwarding, 28
 - FEC, 28–29
 - label operations, 29
- dropping, 257
- loss as goal of FRR, 293
- marking, 256
- policing, 256
- queuing, 256–257
- RSVP
 - common header format, 143
 - ERROR_SPEC class format, 148–149
 - EXPLICIT_ROUTE class format, 155
 - FILTERSPEC class format, 151
 - FLOWSPEC class format, 150
 - HELLO class format, 157
 - LABEL_REQUEST class format, 155
 - object class format, 144–147
 - RECORD_ROUTE class format, 156
 - RESV_CONFIRM class format, 154
 - RSVP_LABEL class format, 154
 - SCOPE class format, 149
 - SENDER_ADSPEC class format, 153
 - SENDER_TEMPLATE class format, 152
 - SENDER_TSPEC class format, 152
 - SESSION class format, 147
 - SESSION_ATTRIBUTE class format, 158
 - STYLE class format, 150
 - TIME_VALUES class format, 148
- packing problem, 427–430
- parallel backup tunnels, 332
- passive LDP establishment, 57–61
- path calculation
 - CSPF
 - administrative weight, 124
 - bandwidth, 124
 - examples, 120–122
 - link attributes, 124
 - operation, 119
 - path-option configuration, 128–134
 - tiebreakers, 122
 - related URLs, 558
 - reoptimization, 135
 - event-driven, 136
 - lockdown, 137
 - manual, 136
 - periodic, 136
- path maintenance, RSVP, 142
- Path message (RSVP), 140
- path protection, 294–295
- path setup, RSVP, 140–142
- path signalling, RSVP, 143
- path teardown, RSVP, 143
- path vector TLV, 46
- PathErr message (RSVP), 140
- PATHS list, 115
- PathTear message (RSVP), 140
- PBR (policy-based routing), 11
 - forwarding traffic down tunnels, 208–209
- PDU header (LDP), 50
- per-flow load sharing, 216–221
- per-interface label space, 45
- periodic flooding, 102
- periodic reoptimization, 136
- per-link scheduling, DS-TE, 279
- PHBs (per-hop behaviors), 257
 - DiffServ, 255
 - dropping packets, 257
 - forwarding DS-TE traffic through tunnels, 287–288
 - ip2mpls, 271
 - mpls2ip, 271
 - tunnel mode
 - Pipe mode, 275–276
 - Short-Pipe mode, 274–275
 - Uniform mode, 273–274
- phop (previous hop), 140
- physical interface configuration commands, 546
- pinging, latency calculation, 127
- Pipe tunnel mode, 275–276
- placement of LSPs using offline tools, 430–431
- policing DiffServ, 256
- policy maps, configuring, 260–262
- post-failure signalling, upstream signalling, 317–322
- preempting non-subpool tunnels, 280–283
- prefailure configuration, links, 302–309
- pre-MPLS traffic engineering, 7–8

prerequisites for MPLS TE configuration, 81–84
 previous hop (phop), 140
 primary tunnels, configuring, 494–495
 prioritizing tunnels, 88–93
 holding priority, 92
 setup priority, 92–93
 probes, 455
 one-way, 459–461
 SAA, DSCP configuration, 461–462
 two-way, 457–459
 promotion, 337
 protection schemes, 293
 local protection, 295–299
 downstream signalling, 323
 IGP notification, 322
 link protection, 299–322
 node protection, 300–301, 326–329
 path protection, 294
 protocol type field, 37

Q

QoS (quality of service), 14
 DiffServ, 253–254
 components of, 255
 dropping packets, 257
 DSCP byte, 265
 DS-TE, 277–283
 EXP bit, 270–271
 marking, 256
 MPLS packets, 267
 packet classification, 255–256
 policing, 256
 queuing, 256–257
 ToS byte, 264
 tunnel modes, 273–276
 IntServ, 253
 MQC, 255–258
 class map configuration, 258–260
 policy map configuration, 260–262
 service policy configuration, 263
 related URLs, 560
 versus ATM, 15
 versus MPLS TE, 15
 queuing
 DiffServ, 256–257
 statmux, 5

R

real-world applications
 of MPLS TE, 17
 of RSVP, 181–186
 recommended features, tactical TE design, 406–407
 RECORD_ROUTE class format
 (RSVP packets), 156
 recovering from link failures, 292
 recursive static routes, 208
 reference bandwidth (OSPF), 125
 Refresh mechanism (RSVP), 172, 175
 regular expressions, 471
 relative tunnel metric, 233–236
 remote bindings, 41
 removing
 tactical TE tunnels, 403–406
 tunnel constraints, 510–519
 reoptimization, 135
 event-driven, 136
 lockdown, 137
 manual, 136
 periodic, 136
 promotion, 337
 requirements of MPLS TE configuration, 81–84
 reservations, Shared Explicit, 170–172
 reserved label values, 42
 reserving bandwidth, 85–87
 auto bandwidth
 configuring, 248–251
 operation, 246–248
 resiliency, recovering from link failures, 292
 resizing tunnels, 425
 resolving fish problem, 13
 resource contention, 5
 ATM, 6
 consumable resources, 12
 Frame Relay, 5
 resource information, validating distribution,
 519–525
 Resource Reservation Protocol. *See* RSVP
 resources available, URLs, 554–556
 responders, 455
 restoring connectivity, 312
 restrictions
 of cell mode MPLS, 46–47
 of interarea tunnels, 195–197

- RESV_CONFIRM class format, 154
- Resv message (RSVP), 140
- ResvConf message (RSVP), 140
- ResvErr message (RSVP), 140
- ResvTear message (RSVP), 140
- ResvTearConf message (RSVP), 140
- RFCs (Requests for Comments), DiffServ, 265
- root node, 115
- route-miles, latency calculation, 128
- Router Alert (RA) option, RSVP messages, 177
- routers
 - link failures
 - APS, 292
 - configuring protection against, 302–309
 - detection, 309–312
 - downstream signalling, 323
 - FRR, 292
 - IGP notification, 322
 - local protection, 295–301
 - path protection, 294
 - protection, 293
 - resiliency, 292
 - restoration, 312–317
 - upstream signalling, 317–322
 - node failures, 326
 - node protection, 326–329
- routing, decoupling procedure, 11
- routing protocols
 - configuration requirements, 502
 - link-state, SPF algorithm, 114–118
- RSVP (Resource Reservation Protocol), 138–139
 - commands, 549–550
 - downstream routers, admission control, 141
 - EXPLICIT_ROUTE class format, abstract nodes, 177
 - Hello messages
 - format, 168
 - link failure detection, 310–312
 - input queue, adjusting size, 180
 - link manager, 197–204
 - make-before-break, 169
 - message pacing, 179–181
 - messages, 140
 - intended receivers, 175–177
 - RA option, 177
 - packets
 - common header format, 143
 - ERROR_SPEC class format, 148–149
 - EXPLICIT_ROUTE class format, 155
 - FILTERSPEC class format, 151
 - FLOWSPEC class format, 150
 - HELLO class format, 157
 - LABEL_REQUEST class format, 155
 - object class format, 144–147
 - RECORD_ROUTE class format, 156
 - RESV_CONFIRM class format, 154
 - RSVP_LABEL class format, 154
 - SCOPE class format, 149
 - SENDER_ADSPEC class format, 153
 - SENDER_TEMPLATE class format, 152
 - SENDER_TSPEC class format, 152
 - SESSION_ATTRIBUTE class format, 158
 - SESSION class format, 147
 - STYLE class format, 150
 - TIME_VALUES class format, 148
 - path maintenance, 142
 - Path messages, format, 160–162
 - path setup, 140–142
 - path signalling, 143
 - path teardown, 143
 - PathErr messages, format, 166
 - PathTear messages, format, 164
 - real-world applications, 181–186
 - Refresh mechanism, 172, 175
 - Resv messages, format, 162–163
 - ResvConf messages, format, 167
 - ResvErr messages, format, 166
 - ResvTear messages, format, 164–165
 - ResvTearConf messages, format, 167–168
 - Shared Explicit reservations, 170–172
 - signalling, troubleshooting, 525–528, 530–531
 - tunnel tail node, explicit versus implicit labels, 178–179
- RSVP_LABEL class format (RSVP packets), 154
- RSV-TE
 - make-before-break, 136
 - reoptimization, 135
 - event-driven, 136
 - lockdown, 137
 - manual, 136
 - periodic, 136

S

- S bit, frame mode MPLS, 26
- SAA (Service Assurance Agent)
 - delay, measuring, 455
 - latency, calculating, 128
 - probes, DSCP configuration, 461–462
- sample networks, 392–395
- scalability, O(N²), 8
- scope, 45
- SCOPE class format (RSVP packets), 149
- SENDER_ADSPEC class format (RSVP packets), 153
- SENDER_TEMPLATE class format (RSVP packets), 152
- SENDER_TSPEC class format (RSVP packets), 152
- service policies, configuring, 263
- services, 14
- SESSION_ATTRIBUTE class format (RSVP packets), 158
- SESSION class format (RSVP packets), 147
- sessions, LDP
 - attributes, configuring, 78
 - establishment, 57–61
- setup priority, tunnel configuration, 92–93
- Shared Explicit reservations, 170–172
- shim headers, 27
- Short-Pipe tunnel mode, 274–275
- show commands, 542–543
 - troubleshooting headend, 504
- show ip rsvp counters command, 182–183
- show ip rsvp interface command, 183
- show ip rsvp neighbor command, 184
- show ip rsvp reservation command, 184–186
- show mpls traffic-eng link-management admission-control command, 198
- show mpls traffic-eng link-management advertisements command, 199–200
- show mpls traffic-eng link-management bandwidth-allocation command, 201–202
- show mpls traffic-eng link-management igp-neighbors command, 202
- show mpls traffic-eng link-management interfaces command, 202–203
- show mpls traffic-eng link-management statistics command, 203–204
- show mpls traffic-eng link-management summary command, 204
- show mpls traffic-eng tunnel command, 508–510
- signalling
 - downstream, 323
 - upstream, 317–322
- signalling protocols, RSVP, 138–139
 - common header format, 143
 - ERROR_SPEC class format, 148–149
 - EXPLICIT_ROUTE class format, 155
 - FILTERSPEC class format, 151
 - FLOWSPEC class format, 150
 - HELLO class format, 157
 - Hello message format, 168
 - LABEL_REQUEST class format, 155
 - link manager, 197–204
 - make-before-break, 169
 - message pacing, 179–181
 - messages, 140, 175–177
 - object class format, 144, 146–147
 - path maintenance, 142
 - Path message format, 160–162
 - path setup, 140–142
 - path signalling, 143
 - path teardown, 143
 - PathErr message format, 166
 - PathTear message format, 164
 - real-world applications, 181–186
 - RECORD_ROUTE class format, 156
 - Refresh mechanism, 172, 175
 - RESV_CONFIRM class format, 154
 - Resv message format, 162–163
 - ResvConf message format, 167
 - ResvErr message format, 166
 - ResvTear message format, 164–165
 - ResvTearConf message format, 167–168
 - RSVP_LABEL class format, 154
 - SCOPE class format, 149
 - SENDER_ADSPEC class format, 153
 - SENDER_TEMPLATE class format, 152
 - SENDER_TSPEC class format, 152
 - SESSION_ATTRIBUTE class format, 158
 - SESSION class format, 147
 - Shared Explicit reservations, 170, 172
 - STYLE class format, 150
 - TIME_VALUES class format, 148
 - troubleshooting, 525–531

- SNMP (Simple Network Management Protocol)
 - MPLS LSR MIB, 343
 - cross-connect table, 359–361
 - InSegment Performance table, 354–355
 - InSegment table, 350–353
 - interface configuration table, 344–349
 - interface performance table, 349–350
 - OutSegment Performance table, 358
 - OutSegment table, 355–357
 - MPLS TE MIB
 - MPLS TunnelHop Table, 383–387
 - MPLS TunnelResource Table, 387–389
 - MPLS TunnelTable, 362–382
 - snmp-server enable traps mpls traffic-eng
 - command, 544
 - soft-state protocols, RSVP, 139
 - SONET (Synchronous Optical Network), 4
 - alarms, 310
 - APS, 292
 - link protection, 485–486, 489
 - SPF (Shortest Path First) algorithm
 - ECMP, 122–124
 - examples, 120
 - link-state database, 114
 - operation, 114–118
 - PATHS list, 115
 - root node, 115
 - TENT list, 115
 - versus CSPF, 119
 - standby LSPs, 294
 - static routes
 - forwarding traffic down tunnels, 207–208, 286
 - recursive, 208
 - statmux (statistical multiplexing), 4
 - over statmux, 6
 - resource contention, 5
 - strategic design model, 408
 - event-driven reoptimization, 422–423
 - LSP scalability, 409–419
 - manual reoptimization, 424
 - multiple parallel tunnels, 426
 - periodic reoptimization, 421–422
 - tunnel reoptimization, 420–421
 - tunnel resizing, 425
 - STYLE class format (RSVP packets), 150
 - subobjects of ERO, 177
 - subpools, 278
 - headend bandwidth requirements, 279
 - per-link bandwidth availability, 279
 - preempting non-subpool tunnels, 280–283
-
- ## T
-
- tactical design model, 396
 - building LSPs, 396–398
 - placement of LSPs, 398–403
 - recommended features, 406–407
 - removing tunnels, 403–406
 - tactical TE applications, 479–484
 - tag switching, 10
 - tag VCs, 47
 - tailend, troubleshooting
 - debug commands, 506
 - show commands, 504–505
 - targeted LDP sessions, 53
 - TDM (time-division multiplexing), 3–4
 - TE (Traffic Engineering), 6
 - ATM, 8
 - combining with MPLS VPNs, 471–475
 - fish problem, 9–10
 - resolving, 13
 - prior to MPLS, 7–8
 - tunnels, 12, 187–188
 - features, 188
 - interarea, restrictions, 195–197
 - multiple path options, 134
 - operation, 189–195
 - per VRF, 476
 - versus network engineering, 7
 - TE-DB, verifying information, 519–524
 - TENT list, 115
 - thresholds, bandwidth, 99–102
 - tiebreakers (CSPF), 122–124
 - TIME_VALUES class format (RSVP packets), 148
 - TLVs, 107
 - hop count, 46
 - path vector, 46
 - TMS (Traffic Matrix Statistics)
 - building traffic matrices, 444–453
 - configuring, 447
 - data files, 450–453
 - displaying data, 447–450

- topology convergence, limitations of IGPs, 291
- ToS (type of service) byte, 264
- traffic
 - equal-cost load sharing
 - behind tunnel tail, 219–221
 - between TE tunnel and IGP path, 217
 - to tunnel tail, 217–219
 - forwarding down tunnels
 - unconstrained paths, 510
 - with autoroute, 209–216
 - with PBR, 208–209
 - with static routes, 207–208
 - load sharing, 216
 - unequal-cost load balancing, applying to one-hop tunnels, 489–490
 - unequal-cost load sharing, 221–223
 - operation, 224–229
- traffic matrices, 442–443
 - building
 - with NetFlow, 444
 - with TMS, 444–453
- transit LSPs, 416
- triggering reoptimization, 318
- troubleshooting
 - administratively shut down tunnels, 506–508
 - common configuration of MPLS TE routers, 496–498
 - headend
 - debug commands, 506
 - show commands, 504
 - interface-level configuration, 499–501
 - related URLs, 566
 - routing protocol configuration, 502
 - RSVP signalling problems, 525–531
 - tunnels
 - invalid paths, 508–510
 - misconfiguration, 532–538
 - removing constraints, 510–519
- TTL (Time To Live), 26
- tunnel interface configuration command, 547–548
- tunnel modes
 - Pipe, 275–276
 - Short-Pipe, 274–275
 - Uniform, 273–274
- tunnel mpls traffic-eng affinity command, 547
- tunnel mpls traffic-eng auto-bw command, 547
- tunnel mpls traffic-eng autoroute announce command, 547
- tunnel mpls traffic-eng autoroute metric command, 547
- tunnel mpls traffic-eng bandwidth command, 547
- tunnel mpls traffic-eng fast-reroute command, 548
- tunnel mpls traffic-eng forwarding-adjacency command, 548
- tunnel mpls traffic-eng load-share command, 548
- tunnel mpls traffic-eng path-option command, 548
- tunnel mpls traffic-eng path-selection metric command, 548
- tunnel mpls traffic-eng priority command, 548
- tunnel mpls traffic-eng record-route command, 548
- tunnel preemption, 88
- tunnel priority information
 - distribution, 88–93
 - holding priority, 92
 - setup priority, 92–93
- tunnel tail node1, 78–179
- tunnels
 - administratively shut down, troubleshooting, 506–508
 - affinities, 94–96
 - applying negative offsets to costs, 234
 - backup, promotion, 337
 - equal-cost load sharing
 - behind tunnel tail, 219–221
 - between TE tunnels and IGP path, 217
 - to tunnel tail, 217–219
 - failure resistance, 292
 - forwarding adjacency, 242–246
 - forwarding traffic
 - DS-TE traffic, 284–288
 - related URLs, 559
 - headend
 - configuring, 502–503
 - constraints, 510–519
 - identification schemes, 469–471
 - interarea, 187–188
 - features of, 188
 - operation, 189–195
 - restrictions, 195–197
 - interfaces, LDP, 476–478
 - invalid paths, troubleshooting, 508–510
 - link protection, configuring, 303
 - load sharing, 216

- metrics
 - absolute value, 231–233
 - adjusting, 229–231, 236–242
 - relative value, 233–236
- misconfiguration, troubleshooting, 532–538
- per VRF, 476
- preempting non-subpool tunnels, 280–283
- reoptimization, 135
 - event-driven, 136
 - lockdown, 137
 - manual, 136
 - periodic, 136
- resizing, 425
- routing traffic
 - with autoroute, 209–216
 - with PBR, 208–209
 - with static routes, 207–208
- traffic, measuring, 453–454
- unequal-cost load sharing, 221–223
 - operation, 224–229
- two-way delay, measuring, 457–459
- two-way probes, 457–459
- Type field, LDP messages, 52

U

- unconstrained paths, 510
- unequal-cost load sharing, 221–223
 - operation, 224–229
- Uniform tunnel mode, 273–274
- Unknown (U) bit, LDP messages, 52
- unlimited backup bandwidth, 334–335
- upstream routers, 140
- upstream signalling, 317–322
- URLS
 - available resources, 554–556
 - related to deploying MPLS TE, 565
 - related to forwarding traffic down tunnels, 559
 - related to information distribution, 557
 - related to MPLS TE management, 562–563
 - related to network design, 564
 - related to path calculation, 558
 - related to protection and restoration, 561
 - related to QoS, 560
 - related to troubleshooting MPLS, 566

V-Z

- validating information distribution, 519–525
- variables, defining for FRR scalability formulae, 431–436
 - link protection, 432
 - node protection, 433
 - path protection, 433
- VC Merge, 44, 48
- verifying LDP configuration, 74–77
- voice networks, advertising delay, 125–127
- VPNs, 14
- wide metrics, 107
- WRED (Weighted Random Early Detection), 257