



Symbols & Numerics

μ -Law, 88–91

1s density, 112

2B1Q line coding, 244

48-octet ATM payload, 300

4B3T line coding, 245

64-kbps loop rate (DSS), 115

A

AAL (ATM adaptation layer), B-ISDN model, 319, 350

AAL0, 351

AAL1, 351–353

AAL2, 353–355

AAL3/4, 355–360

AAL5, 361–363

CS, 319

SAR, 320

AAL-indicate bit, 310

ABR (available bit rate), 337–341

closed-loop flow control, 338

service category, 366

AC (access control) field

DQDB slots, 380

SIP Layer 2 PDUs, 394

access classes, SMDS, 376

access signaling specifications, Frame Relay, 273

AD (Adjunct), 64

adaptation layer, 317

adaptive QAM (quadrature amplitude modulation), CAP, 416

Address Complete messages (TUP), 58

address field (DXI), 404

Address messages (DUP), 55

address octets (Q.921), 221

address screening, 390

addressing (SMDS), 376

subscriptions, 388–390

admission control, 479

ADMs (add/drop multiplexers), 498

ADPCM (adaptive differential pulse code modulation), 95–96

SB-ADPCM, 99

ADSL (asymmetric digital subscriber line), 432

components of, 419–420

AERM (alignment error rate monitor), 43

AF (ATM Forum), 300

Traffic Management Specification, service categories, 365–366

UNI 3.x/4.0 specification, 304

UNI IAs, 303

alarm conditions (T1), troubleshooting, 146–147

A-Law, 89–91

alias point codes, 38

alignment process, Q.921, 224–227

A-links (access links), 36

AMI (alternate mark inversion) encoding, 42

1s density, 112

DSS implementation, 110–111

pulse stuffing, 134

amplifier cascades, 448

amplitude, 4

analog communication, 3

amplitude, 4

attenuation, 6–9

DACs, 10

distortion, 5–6

E&M signaling, 13

EMI, 9

frequency, 5

GR-303-CORE standard, 17–18

ground start signaling, 13

IDLCs (Integrated Digital Loop Carriers), 14–16

interference, 81

loop start signaling, 13

noise, 7–9

- R2, 169
 - reverse battery signaling, 13
 - sampling, 85
 - sinusoidal waves, 82
 - tip and ring circuits, 11–14
 - versus digital, 3, 81–82
 - wavelength, 5
- ANSI (American National Standards Institute)
- signaling links versus ITU signaling links, 35
- ANSI T1.410-1992. *See* DDS
- AO-DI (Always On Dynamic ISDN), 250
- APCs (Adjacent Point Codes), 38
- applications, SDH/SONET, 522–523
- architectures
- ISDN, 212
 - circuit switching, 213–215
 - local loop, 213–216
 - reference points, 218–219
 - DQDB AU, 378
 - DSL
 - CPE, 437
 - NAP, 437
 - NSP, 437–440
 - SMDS, 374
- AS (address screening), 376
- AS bearer channels (ADSL), 427
- associated signaling, 29
- asynchronous circuits, T3, 182
- asynchronous technologies versus synchronous, 105
- AT (access tandem) switches, 25
- ATM (Asynchronous Transfer Mode)
- AAL, 350
 - AAL0, 351
 - AAL1, 351–353
 - AAL2, 353, 355
 - AAL3/4, 355–360
 - AAL5, 361–363
 - B-ISDN model, 316
 - AAL, 319–320
 - ATM layer, 319
 - C-plane, 317
 - M-plane, 317
 - physical layer, 318–319
 - U-plane, 317
 - development of
 - B-ISDN origins, 301
 - consensus on 48-octet payload, 300
 - standards bodies, 301–302
 - error control modes, 314
 - header fields, 305
 - CLP, 313
 - GFC, 306
 - HEC, 313, 316
 - PT, 309–313
 - VCI, 306–308
 - VPI, 306
 - interfaces, 304
 - QoS
 - CAC, 320
 - CER, 325
 - CLR, 323
 - maxCTD, 323–325
 - peak-to-peak CDV, 325
 - SECBR, 326
 - reference points, 304
 - service classes, 331
 - ABR, 337–341
 - CBR, 333–334
 - GFR, 343
 - rt-VBR, 334–336
 - UBR, 341–342
 - traffic management, 344
 - continuous-state leaky bucket
 - algorithm, 347
 - GCRA, 345–346
 - PCR algorithm, 349
 - policing, 345
 - SCR algorithm, 350
 - traffic parameters, 327
 - BT, 329
 - CDVT, 329–331
 - connection-traffic descriptors, 328
 - MBS, 329
 - MCR, 329
 - MFS, 329
 - PCR, 328
 - SCR, 328
 - versus STM, 303

ATM layer (B-ISDN model), 319
 attenuation, 6–9, 448
 in DSL circuits, 421
 ATU-R (ATU-Remote), 419
 AUs (access units), 377–379

B

B (Bearer) channels, 213
 B8ZS (bipolar 8-zero substitution), 133
 BACP (bandwidth allocation control protocol), 243
 bandwidth reservation, CAC, 320–321
 BAP (bandwidth allocation protocol), 243
 baseline privacy, 479
 BASize field (SIP Layer 3 PDUs), 387
 Bc (committed burst size), 282
 BE (Beginning-End) Tag fields, SIP Layer 3
 PDUs, 386
 Be (excess burst size), 282
 bearer capability IE (Q.931 messages), 234–236
 bearer channels, DSL, 427
 bearer traffic, 22
 Bellcore, role in SMDS development, 373–374
 BERT (bit error rate test), 143–144
 B-ICI (Broadband Inter-Carrier Interface), 304
 billing methods, ISDN BRI, 254–255
 bipolar line coding schemes, 83
 bipolar signals versus unipolar, 108
 B-ISDN model, 300, 316
 AAL, 319, 350
 AAL0, 351
 AAL1, 351–353
 AAL2, 353–355
 AAL3/4, 355–360
 AAL5, 361–363
 CS, 319
 SAR, 320
 ATM layer, 319
 C-plane, 317
 M-plane, 317
 physical layer, 318
 PMD sublayer, 318
 TC sublayer, 318–319
 U-plane, 317
 bit meanings of DLCIs, 280–282
 bit stuffing, 43, 185
 DS3 PLCP frames, 400
 BITS (Building Integrated Timing Supply), 494–495
 B-links (bridge links), 36
 BLSR (bidirectional line-switched ring), 523
 blue alarms (T1), 147
 BNRZ (bipolar non-return to zero), 133
 BOD (bandwidth on demand), 243
 boosting DSL power levels, 429
 boundary detection, ATM cells, 318
 BPVs (bipolar violations), 112, 134
 BRI (Basic Rate Interface)
 AO-DI, 250
 billing methods, 254–255
 circuit provisioning, 248–249
 configuring, 250–252
 echo cancellation, 216–217
 features, 243–244
 FX, 249
 Japanese implementations, 244
 line coding
 2B1Q, 244
 4B3T, 245
 NIDs, 217
 operation, 242–243
 reference points, 218–219
 SPIDs, 248
 troubleshooting, 252–254
 bridge taps, 131, 434
 broadcast television
 frequency allocation, 451–453
 standards, 451
 BRZ (bipolar return to zero), 84
 BT (burst tolerance), 329
 bursty traffic
 AAL3/4, 355–356
 errors, 424
 buses (DQDB), HoB, 379
 byte-interleaved multiplexing, 492, 504

C

- cable IP network networks, 484
 - DPT/RPR architectures, 486
 - Ethernet aggregation architectures, 486
 - future of, 487
 - high-speed optical core, 487
 - OCx architectures, 486
- cabling
 - home run, 254
 - length, effect on DSL performance, 435
- cable modem initialization process
 - DHCP request/response, 471–472
 - frequency scanning, 468
 - online state, 473
 - power ranging, 470–471
 - registration request, 472–473
 - TOD, 472
 - UCD receipt, 470
- cable plant, 447
 - frequency allocation, 451–453
 - headend, 450–451
 - hubs, 451
 - quality requirements, 453–454
 - RF signals, 455
 - upstream noise, 455–456
- cable throws, 253
- CAC (connection admission control), 320–321
- calculating
 - cell arrival times, 346
 - CMR, 327
 - noise margin in DSL circuits, 421
- Call Accept Message (DUP), 55
- call control
 - Frame Relay, 292
 - R2 signaling, 167
- call flow, ISDN, 232–233
- call reference length indication octet (Q.931 messages), 230
- Call Rejected Message (DUP), 55
- called/calling number IE (Q.931 messages), 238–240
- Calling Line Identity message (DUP), 55
- CAP (carrierless amplitude and phase modulation), 416
- capabilities of ISDN BRI, 243–244
- capability point code, 38
- capacitance, 111
- CAS (channel associated signaling), 22, 28, 229
- CATV, 446
 - cable plant, 447
 - frequency allocation, 451–453
 - headend, 450–451
 - hubs, 451
 - quality requirements, 453–454
 - RF signals, 455
 - upstream noise, 455–456
 - DOCSIS specification, 456
 - baseline privacy, 479
 - binary configuration files, 473–478
 - downstream signaling, 465
 - FEC, 459–460
 - fiber node combining, 482–484
 - interleaving, 460
 - MAC domains, 463–464
 - modulation, 458–459
 - MPEG framing, 461
 - security features, 480–482
 - throughput, 461–463
 - upstream admission control, 479
 - upstream signaling, 466–467
 - versus Euro-DOCSIS, 457
 - headend, 447, 450
 - HFC networks, 449–450
 - signal attenuation, 448
- C-bits, 114, 195–197
- CBR (constant bit rate), 333
 - conformance definition, 334
 - service category, 365
- CCAF (Call Control Agent Function), 62
- CCS (common channel signaling), 22, 29, 229.
 - See also* SS7
- CDVT (cell delay variation tolerance), 327–331
- CE (carrier equipment), SMDS, 374–375
- cell-rate decoupling, 319

- cells, 303
 - arrival times, calculating, 346
 - boundary detection, 318
 - clumping, 330
 - discarding
 - EPD, 342
 - SD, 342
 - entry/exit events, 323
 - header fields, 305
 - CLP, 313
 - GFC, 306
 - HEC, 313, 316
 - PT, 309–313
 - VCI, 306–308
 - VPI, 306
- CER (cell error ratio), 325
- CFAs (carrier failure alarms), 146
- channel associated signaling (CAS), 22, 28, 229
- channel banks, 136
 - D1, 137–139
 - D1D, 140
 - D3, 140
 - D4, 140
 - D5, 140–142
- channel ID IE (Q.931 messages), 237–238
- channelized T3, 182–184
 - Cisco 1000 ESR configuration, 198–199
- Charging Message (TUP), 58
- check bytes, 422
- CICS (Customer Information Control Systems), 35, 57
- CIR (committed information rate), 282
- circuit provisioning, 248–249
- Circuit State Message (DUP), 55
- circuit switching, ISDN, 213–215
 - reference points, 218–219
- circuit testing patterns, 117–118
- circuits (DSL)
 - attenuation, 421
 - bridge taps, 434
 - bursty errors, 424
 - cable length, 435
 - coding gain, 425
 - crosstalk, 435
 - dribbling errors, 425
 - Fastpath, 425
 - FEC, 422–424
 - interfering signals, 434
 - loading coils, 434
 - noise margin, 421–422
 - resistance, 436
 - RFI, 434
- Cisco routers, DSS/SW56 configuration, 118–119
- Class 5 SSPs, 25
- Clear messages (DUP), 55
- CLI (Cumulative Leakage Index), 455
- C-links (cross links), 36
- cloned MAC addresses, detecting, 481
- closed-loop flow control model (ABR), 338
- closed topology (DQDB), 379
- CLP (cell loss priority) field, 313
- CLR (cell loss ratio), 323
- clusters, 39
- CMI (coded mark inversion), 175
- CMTS (cable modem termination system), CPE
 - database, 482
- coaxial cable networks
 - HFC, 449–450
 - signal attenuation, 448
- coding gain, 425
- co-directional interfaces, 156
- combining, 482–484
- common channel signaling (CCS), 22, 29, 229
- Common Part (AAL3/4), 356
- common path distortion, 456
- companding algorithms, 88–91
- concatenation, 467
 - SDH versus SONET, 504
- configuring
 - DSS/SW56, 118–119
 - E1 controllers, 163–166, 173–174
 - E3 interfaces, 205–206
 - Frame Relay on Cisco devices, 292–295
 - ISDN BRI, 250–252
 - ISDN PRI, T1/E1, 258–259
 - SMDS, 405–406

- T1 controllers, 147
- T1 hairpin connections, 148
- T3 on Cisco 1000 ESR, 198–199
- conformance definitions
 - CBR, 334
 - nrt-VBR, 337
 - rt-VBR, 336
- congestion avoidance mechanisms, Frame Relay, 286–289
- congestion control
 - closed-loop flow control, 338
 - dual leaky bucket model, 336
 - EPRCA, 339
 - GCRA, virtual scheduling algorithm, 346–347
- connection status, Frame Relay, 289–291
- connection-traffic descriptors, components of, 328
- connectors, RJ-48X, 129
- constellations, 415
 - Trellis coding, 429–430
- control field (DXI), 404
- control octets, 222–223
- controlled frame slip, 126
- controllers (T1), configuring, 147
- conversion process
 - encoding, 92–93
 - sampling, 85–87
- converters, D/A, 9–10
- core access specifications, Frame Relay, 272
- corrupted frames, 323
- COs (central offices), 14
- cost benefits of SW56, 115
- COTs (Continuity Tests), 56
- CPCS (common part convergence sublayer), 320
 - functions, 359–361
- CPE (customer premises equipment)
 - addressing, 376
 - database, 482
 - SMDS, 374
- C-plane (B-ISDN model), 317
- CRC-4 framing, E1 circuits, 160
- CRC-32 field (SIP Layer 3 PDUs), 391
- crosstalk, 8, 435
- CS (convergence sublayer), 319

- CS-1 (Capability Set-1), 65–66
- CS-2 (Capability Set-2), 66–68
- CSES (consecutive severely errored seconds), 146
- CSU (customer service unit), 107, 117–118
- CSU/DSU (channel service unit/data service unit), 128
- CTD (cell transfer delay), 323–324
- customer premises
 - ISDN installation, 254
 - NIDs, 217
- CVSD (Continuously Variable Slope DM), 98–99

D

- D (Data channels), 213
- D1 channel banks, 137–139
- D1D channel banks, 140
- D3 channel banks, 140
- D4 channel banks, 140
- D5 channel banks, 140–142
- DA (Destination Address) field (SIP Layer 3 PDUs), 387
- DACs (digital-to-analog converters), 10
- DACS (Digital Access and Crossconnect System), 497
- data-link layer functionality, Q.921 specification, 220–224
 - alignment process, 224–227
 - timers, 227–228
- DB-15 connectors, 157
- DBR (deterministic bit rate), 333
- dBs (decibels), 7
 - logarithmic signal gain/loss, 131
 - mid-span repeaters, 216
- DDS (digital dataphone service). *See also* SW56
 - circuit deployment, 105
 - circuit testing patterns, 117–118
 - Cisco router configuration, 118–119
 - CSU, 107
 - DSU, 108
 - line coding
 - 64-kbps loop rate, 115

- AMI, 110–111
 - naming conventions, 112
 - secondary channels, 113
- local loop, 106
- loop rates, secondary channel, 106
- nailed architecture, 109
- OCU-DP, 108–109
- point-to-multipoint connections, 109
- timing sources, 112
- transmission rates, 106
- transmit filter, 106
- default Q.921 timer values, 227
- deferred blocking, GR-303-CORE standard, 17
- delay parameters (QoS)
 - CER, 325
 - maxCTD, 323, 325
 - peak-to-peak CDV, 325
 - SECBR, 326
- dense combining, 482
- dependability parameters (QoS), CLR, 323
- deploying
 - DDS circuits, 105
 - T3, options, 193
- detection state, 314
- development
 - of ATM
 - B-ISDN origins, 301
 - consensus on 48-octet payload, 300
 - standards bodies, 301–302
 - of Frame Relay, 266–270
 - of SMDS
 - DQDB, 377
 - time-to-market delay, 385
- devices
 - ATM, error control modes, 314
 - cable modems, initialization sequence, 468–473
 - Cisco routers, configuring for DSS/SW56, 118–119
 - cloning, 480
 - CSU/DSU, circuit testing patterns, 117–118
 - digital repeaters, 215
 - DSL modems, trainup, 426
 - DSS
 - CSU, 107
 - DSU, 108
 - OCU-DP, 108–109
 - echo cancellers, ISDN BRI deployment, 216–217
 - IMTs, 27
 - ISDN BRI hardware, 242
 - mid-span repeaters, 215–216
 - network nodes, clusters, 39
 - NIDs, 11, 217
 - NT12s, 218
 - optical networking components, 495
 - LTE, 498–499
 - optical routers, 500
 - PTE, 496
 - STE, 500
 - POTS splitters, 419
 - required for SMDS CE, 375
 - SLT (Signaling Link Terminal), 43
 - SS7
 - SCPs, 27
 - SSPs, 23–25
 - STPs, 27
 - sub-band codecs, 99
 - TE1, 219
- digital communication
 - black and white analogy, 81
 - conversion process
 - encoding, 92–93
 - quantizing process, 87–91
 - sampling, 85–87
 - evolution of, 81
 - impetus for, 80
 - pulse streams, 85
 - quantizing process, noise reduction, 88–91
 - sampling, 87
 - signal conversion process, 83–84
 - versus analog, 81–82
- digital repeaters, 215
- digital signaling
 - R2, 169
 - versus analog, 3

- discarding cells, SD, 342
- discards (Frame Relay), 284–286
- discrete pulses, 83–84
- discrete values, 91
- distance-insensitive transport technologies, 372
- distributed architecture, INs, 62
- divide and conquer, 456
- DLCIs, (data-link connection identifiers), 276–278
 - bit meanings, 280–282
 - Inverse ARP, 279–280
- D-links (diagonal links), 36
- DM (Delta Modulation), 97
- DMT (discrete multi-tone modulation), 417–418
- DOCSIS cable specification, 456–457
 - baseline privacy, 479
 - binary configuration files, 473–474
 - DOCSIS 1.0, 474–475
 - DOCSIS 1.1, 475–478
 - cable modem initialization process
 - DHCP request/response, 471–472
 - frequency scanning, 468
 - online state, 473
 - power ranging, 470–471
 - registration request, 472–473
 - TOD, 472
 - UCD receipt, 470
 - cable plant quality requirements, 453–454
 - CMTS, CPE database, 482
 - FEC, 459–460
 - fiber node combining, 482, 484
 - interleaving, 460
 - MAC domains, 463
 - downstream signaling, 465
 - SID, 464
 - upstream signaling, 466–467
 - modulation, 458–459
 - MPEG framing, 461
 - security features, 480, 482
 - throughput, 461–463
 - upstream admission control, 479
- DPC (Destination Point Code), 38
- DPCM (differential pulse code modulation), 94–95
- DQDB (Distributed Queue Dial Bus), 377
 - AU, 377–379
 - DMPDUs, format, 384
 - IMPDUs, SAR, 382, 385
 - MAC layer functionality, 380–382
 - topologies, 379
- dribbling errors, 425
- drop and insert, 164
- DS0 (digital signal level zero), 88, 109, 127
- DS1 (digital signal level one) media, PLCP frames, 397–399
- DS2 (digital signal level two) media
 - E12 multiplexing, 200
 - frame structure, 187
 - M-Frame, bit stuffing, 188
- DS3 (digital signal level three) media
 - bit stuffing, 400
 - circuits, 185
 - M12 multiplexing, 185
 - PLCP frames, 399–400
- DS4 (digital signal level four), 206
- DSL (digital subscriber line)
 - architectures
 - CPE, 437
 - NAP, 437
 - NSP, 437–440
 - bridge taps, 434
 - cable length, effect on performance, 435
 - CAP, 416
 - circuit attributes
 - attenuation, 421
 - bursty errors, 424
 - coding gain, 425
 - dribbling errors, 425
 - Fastpath, 425
 - FEC, 422–424
 - noise margin, 421–422
 - crosstalk, 435
 - DMT, 417–418
 - flavors
 - ADSL, 432
 - EtherLoop, 432
 - G.Lite, 432

- HDSL, 432
- HDSL2, 433
- IDSL, 433
- RADSL, 433
- SDSL, 433
- VDSL, 433
- framing modes, 427–428
- higher-layer protocol transport mechanisms, 439–440
- history of, 414
- interfering signals, 434
- loading coils, 434
- modem trainup, 426
- power levels, 428
 - reducing/boosting, 429
 - Trellis coding, 429–430
- QAM, 415–416
- resistance, effect on performance, 436
- RFI, 434
- wholesale services, 441
- DSLAM (DSL access multiplexer), 419
- DSU (data service unit), 108
 - circuit testing patterns, 117–118
- DTMF (dual tone multifrequency), 12, 170
 - SW56 implementation, 116
- DTP/RPR architectures, 486
- dual leaky bucket congestion control, 336, 348
- dual-latency modem, DSL data transmission, 427
- DUP (Data User Part), 54–55
- DWDM (dense wavelength division multiplexing), 521
- DXI (Data Exchange Interface) protocol, 375, 403
 - framing, 404–405
 - heartbeat polling, 405–406
 - troubleshooting, 407
- configuring, 163–166
 - R2 signaling, 173–174
- CRC-4 framing, 160
- line coding, 161
- NO-CRC-4 framing, 158
- physical characteristics, 155–157
- PLCP frames, 401
- PRI configuration, 258–259
- subrate offerings, 157
- E3 circuits, 199–200
 - E12 multiplexing, 200
 - E23 multiplexing, 202
 - G.804 framing, 205
 - G.823 framing, 202–204
 - interface configuraiton, 205–206
- E12 multiplexing, 200
- E23 multiplexing, 202
- echo cancellation, 216–217
- Elastic Networks, EtherLoop, 432
- E-links (extended links), 36
- EMI (electromagnetic interference), 8
 - in ISDN deployments, 215
- en bloc signaling, 59
- encapsulation, SMDS, 374
- encoding schemes, 92–93. *See also* line coding
 - DSL
 - CAP, 416
 - DMT, 417–418
 - QAM, 415–416
- encryption, 479
- end-to-end signaling, 59
- entry events, 323
- EPD (early packet discard), 342
- EPRCA (enhanced proportional rate control algorithm), 339
- ERM (explicit rate marking), 340
- error detection, Frame Relay FCS field, 285
- error detection code field (OAM), 311
- error mitigation
 - FEC, 459–460
 - interleaving, 460
- errors, T1, 145–146
- ES (errored second), 146

E

- E&M signaling, 13
- E.164 numbers, 213
- E1 circuits, 154. *See also* T1 circuits
 - controllers

ESF (Extended Superframe), 136
 D5 channel banks, 140–142
 estimating DSL power levels, 428
 EtherLoop, 432
 Euro-DOCSIS, 457
 modulation, 458–459
 throughput, 461–463
 exit events, 323
 expected cell arrival times, calculating, 346
 extreme-dense combining, 482

F

fast byte, 427
 Fastpath, 425
 FCC First Report & Order, 69
 FCS (frame-check sequence) field
 DXI, 404
 Frame Relay packets, 285
 FDM (frequency-division multiplexing), 127, 450
 FEBEs (far-end block errors), 161,
 FEC (forward error correction), 422–423, 459–460
 interleaving, 423–424
 FEs (functional entities), 62
 FEXT (far-end crosstalk), 9, 435
 F-GCRA (Frame-GCRA), 349
 fiber-node combining, 482–484
 fiber-optic cabling, 501, 504, 522
 fields
 of ATM headers, 305
 CLP, 313
 GFC, 306
 HEC, 313, 316
 PT, 309–313
 VCI, 306–308
 VPI, 306
 of DXI frames, 404–405
 of Q.931 messages, 230
 of SIP Layer 1 PDUs, 396
 of SIP Layer 2 PDUs, 393
 Access Control field, 394
 MID field, 395
 NCI field, 394

Payload CRC field, 396
 Payload Length field, 395
 Segment Type field, 394
 Segmentation Unit field, 395
 Sequence Number field, 395
 of SIP Layer 3 PDUs, 386
 BAsize field, 387
 BE Tag fields, 386
 CRC-32 field, 391
 DA field, 387
 HE field, 391–392
 HLPID field, 390
 Information field, 392
 Length field, 387
 PAD field, 390
 QoS field, 391
 Reserved field, 386
 SA field, 387–388

filtering, 84
 FISU (Fill-In Signal Unit), 43–45
 fixed-length slots (DQDB), 380–382
 flag field (DXI), 404
 flavors of DSL
 ADSL, 432
 DSLVDSL, 433
 EtherLoop, 432
 G.Lite, 432
 HDSL, 432
 HDSL2, 433
 IDSL, 433
 RADSL, 433
 SDSL, 433
 F-links (fully associated links), 36
 FLR (frame loss ratio), 323
 format
 of DMPDUs, 384
 of Q.931 messages, 230
 format errors, T1, 145–146
 fragmentation, 467
 Frame Relay
 access signaling specifications, 273
 ATM interworking, 302
 configuring on Cisco devices, 292–295

congestion avoidance mechanisms, 286–289
 core access description specifications, 272
 DLCI bit meanings, 280, 282
 development of, 266–270
 discards, 284–286
 DLCI, 276–280
 framework specifications, 271
 LMI specification, 289–291
 service description specifications, 271–272
 signaling, 286–292
 SLAs, contractual values, 282
 VCs, 275–276
 framework specifications, Frame Relay, 271
 framing
 DSL, 427–428
 DSS, bit values, 114
 DXI, 404–405
 Q.921, octets, 221–222
 SDH, 519–520
 T1, 135
 D1 channel banks, 137–139
 D1D channel banks, 140
 D3 channel banks, 140
 D4 channel banks, 140
 D5 channel banks, 140–142
 T3, 195–197
 unchannelized E3
 G.804, 205
 G.832, 202–204
 unmarked frames, 343
 frequency, 5, 84
 FRF (Frame Relay Forum), 268–270
 ATM/Frame Relay interworking, 302
 IAs, 273–274
 full async framing (DSL), 427
 full booking, 321
 full overhead framing (DSL), 427
 full sync framing (DSL), 427
 function-specific field (OAM), 311
 future of cable IP networks, 487
 FX (foreign exchange), 249

G

G.804 framing, 205
 G.832 framing, 202–204
 G.Lite, 432
 GCRA (generic cell rate algorithm), 345
 F-GCRA, 349
 PCR algorithm, 349
 SCR algorithm, 350
 General Forward Setup Information
 message (TUP), 58
 GFC (generic flow control) field, 306
 GFR (guaranteed frame rate), 343
 GPS (global positioning system) timing
 distribution, 493
 GR-303-CORE standard, 17–18
 ground start signaling, 13

H

hairpin connections, configuring
 E1, 164
 T1, 148
 hardware
 optical network components, 495
 LTE, 498–499
 optical routers, 500
 PTE, 496
 STE, 500
 ISDN, 242
 HDB3 line coding, 258
 HDSL (high data-rate DSL), 432
 HDSL2, 433
 HE (Header Extension) field (SIP Layer 3 PDUs),
 391–392
 headend, 450–451
 heartbeat polling (DXI), 405
 HEC (header error correction) field, 313, 316
 hertz, 84
 HFC (hybrid-fiber coaxial) networks, 449–450
 hierarchy of national SSPs, 25
 higher-layer transport mechanisms, 439–440

- high-order address octets (Q.921), 221
 - high-speed optical core networks, 487
 - history
 - of DSL, 414
 - of Frame Relay, 266–270
 - of NADH, 181
 - of SMDS, 372
 - alignment with 802.6, 373, 385
 - SIG, 374
 - HLPID (Higher Layer Protocol Identifier) field (SIP Layer 3 PDUs), 390
 - HoB (head of bus), 379
 - home run, 254
 - hubs, 451
 - hunt state, 315
 - hybrid SSPs, 23
-
- IACR (initial allowed cell rate), 338
 - IAs (Implementation Agreements), 268, 273–274, 300
 - B-ICI 2.0, 304
 - UNI-related, 303
 - IDSL (ISDN-based DSL), 433
 - IETF (Internet Engineering Task Force)
 - RFC 1209, 374
 - IMPDU (Initial Meeting Access Control PDUs), SAR, 382, 385
 - impulse noise, 455
 - IMTs (Inter-Machine Trunks), 27
 - INs (intelligent networks)
 - CS-1, 65–66
 - CS-2, 66–68
 - FEs, 62
 - PEs, 63–64
 - information elements, Q.931 messages, 233–240
 - information field
 - DXI, 404
 - SIP Layer 3 PDUs, 392
 - ingress noise, 455
 - interfaces, ATM, 304
 - interference
 - analog communication, 81
 - EMI
 - ISDN carriers, 215
 - effect on DSL performance, 434
 - interleaving, error mitigation, 460
 - international digital hierarchies, JDH, 174–176
 - international split plans, 452
 - international SSPs, 23, 25
 - international television standards, 451
 - interregister signaling, R2 signaling, 170–173
 - interworking
 - ATM/Frame Relay, 302
 - SMDS and Layer 3 protocols, 377
 - Inverse ARP, 279–280
 - IP (Intelligent Peripheral), 64
 - ISDN
 - architecture, 212
 - BRI
 - 2B1Q line coding, 244
 - 4B3T line coding, 245
 - AO-DI, 250
 - billing methods, 254–255
 - circuit provisioning, 248–249
 - configuring, 250, 252
 - features, 243–244
 - FX, 249
 - Japanese implementations, 244
 - operation, 242–243
 - SPIDs, 248
 - troubleshooting, 252–254
 - circuit switching, 213–215
 - E.164 numbers, 213
 - echo cancellation, 216–217
 - local loop, 213–215
 - mid-span repeaters, 216
 - NID, 217
 - NT12s, 218
 - PRI, 255–256
 - NFAS, 257
 - Q.Sig, 260
 - T1/E1 configuration, 258–259
 - troubleshooting, 259–260

- Q.921 specification, SAPs, 221
- reference points, 218–219
- specifications
 - ITU Q.921, 220–228
 - ITU Q.931, 229–233
 - physical layer, 219
- S/T bus, 218–219
- TE1 devices, 219
- ISUP (ISDN user part), 58
 - messages, 59–60
 - signaling methods, 59
- ITU (International Telecommunications Union)
 - digital hierarchy
 - E3, 199–200
 - E12 multiplexing, 200
 - E23 multiplexing, 202
 - G.804 framing, 205
 - G.832 framing, 202–204
 - interface configuration, 205–206
 - point code format, 40
 - signaling links, 35
 - ITU-T (International Telecommunications Union Telecommunications Standardization Sector)
 - ATM recommendations, 302
 - recommendation I.121, B-ISDN model, 316–320

J

- Japanese BRI services, 244
- JDH (Japanese Digital Hierarchy), 174–176
- jitter, 146, 330, 467

K

- KEK (key encryption key), 480
- Kentrox, development of SMDS access solution, 386

L

- LAPD (Link Access Procedure on the D channel), 220–224
 - Q.921 alignment, 224–227
 - Q.921 timers, 227–228
- laser clipping, 456
- latency
 - interleaving delay, 424
 - real-time polling, 467
- Layer 3 protocols, interworking with SMDS, 377
- layer management (M-plane), 317
- layers of AAL
 - AAL0, 351
 - AAL1, 351–353
 - AAL2, 353–355
 - AAL3/4, 355–360
 - AAL5, 361–363
- layers of MTP protocol
 - DUP, 54–55
 - ISUP, 58–59
 - MTP1, 42–43
 - MTP2, 43
 - FISU, 43–45
 - link alignment, 48–52
 - LSSU, 45–47
 - MTP3, 52–54
 - TUP, 56–58
- LBO (long-haul line build-out), 130
- LEDs (light emitting diodes), multimode fiber, 502
- legislation, Telecommunication Act of 1996, 68
- Length field (SIP Layer 3 PDUs), 387
- line coding, 258
 - AMI
 - 1s density, 112
 - DSS implementation, 110–111
 - CMI, 175
 - DSS
 - 64-kbps loop rate, 115
 - naming conventions, 112
 - secondary channels, 113
 - E1, 161
 - ISDN BRI, 244

- 2B1Q, 244
- 4B3T, 245
- T1, 132–135
- T3, 194
- line equalization, 130
- line noise, 8
- line overhead, STS-1 frames, 510–513
- line protection switched topologies, 523
- line signaling, R2, 167
- link alignment, 48–52
- link-by-link signaling, 59
- link sets, 34
- LMI (Local Management Interface) specification, 289–291
- LMU (line-monitoring unit), 142
- LNP (local number portability), 69–70
 - call flow, 71–72
- LNPAs (local number portability administrators), 69
- load sharing, MTP3, 53
- loading coils, 131, 434
- local loop technologies
 - DDS, 106
 - ISDN, 213–216
- local number portability, 69–72
- location portability, 72
- logic errors, T1, 145–146
- loop rates, DDS
 - secondary channel, 106
 - 64-kbps, 115
- loop start signaling, 13
- lost frames, 323
- low-order address octets (Q.921), 221
- LS bearer channels, 427
- LSSU (Link Status Signal Unit), 45–47
- LTE (line termination equipment), 498–499

M

- MAC domains (DOCSIS), 463
 - downstream signaling, 465
 - SID, 464
 - upstream signaling, 466–467
- MAC layer functionality, DQDB, 380–382
- magnetic coils, 254
- management cells, 312
- MANs (metropolitan-area networks), 501
- MAP messages, 470
- marked frames, 343
- mated pairs, 27
- maxCTD (cell transfer delay), 323–325
- MBR (maximum burst rate), 282
- MBS (maximum burst size), 329
- MCNS (Multimedia Cable Network System Partners Ltd.), 447
- MCR (minimum cell rate), 329
- message mode (common part), 356
- messages
 - DUP, 55
 - ISUP, 59–60
 - Q.931, 230, 233
 - information elements, 233–240
 - TUP, 56–58
- metasignaling, 307
- M-Frame (DS2), bit stuffing, 188
- MFS (maximum frame size), 329
- microfilters, 419
- MID field (SIP Layer 2 PDUs), 395
- MIDs (message identification pages), 379
- mid-span repeaters, 215–216
- MNs (matched nodes), 499
- modems, DSL
 - framing modes, 427–428
 - trainup, 426
- modulation schemes
 - ADPCM, 95–96
 - CVSD, 98–99
 - DM, 97
 - DOCSIS, 458–459
 - DPCM, 94–95
- MPEG framing, 461
- M-plane (B-ISDN model), 317

- M12 multiplexing, DS3, 185
- M13 multiplexing, 193
- M23 framing (T3), 195–197
- M23 multiplexing, 189, 192

- MSB (most significant bit), cell payload values, 310
 - MSOs (multiple service operators), 446
 - MSU (Message Signal Unit), Service Information Field, 50–52
 - MT (multi-tone) signaling, interregister signaling, 170–173
 - MTP (Message Transfer Part), 41
 - MTP1, 42–43
 - MTP2, 43
 - FISU, 43–45
 - link alignment, 48–52
 - LSSU, 45–47
 - timers, 49
 - MTP3, 37, 52–54
 - multimode distortion, 502
 - multimode fiber, 502
 - multiplexing, 109
 - M13, 193
 - M23, 189, 192
 - SRDM, 108
 - STDM, 267
 - TDM, 109
- ## N
-
- NADH (North American Digital Hierarchy)
 - DS2 frame structure, 187
 - DS3
 - M13 multiplexing, 193
 - M23 multiplexing, 189, 192
 - DS4, 206
 - evolution of, 181
 - signal levels, 184–185
 - T3 framing, 195–197
 - nailed architecture, 109
 - naming conventions, DSS line coding schemes, 112
 - NANP (North American Numbering Plan), 59
 - NAPs (Network Access Points), 63
 - national SSPs, 23–25
 - NCI (Network Control Information) field, SIP Layer 2 PDUs, 394
 - network indicators, 24
 - network layer functionality, Q.931 specification, 229–233
 - network layer protocols, interworking with SMDS, 377
 - network nodes, clusters, 39
 - NEXT (near-end crosstalk), 9, 435
 - NFAS (non-facility associated signaling), 155, 257
 - NIDs (network interface devices), 11, 217, 419
 - home run, 254
 - NNI (Network-to-Network Interface), 304
 - header fields, 305
 - CLP, 313
 - HEC, 313, 316
 - PT, 309–313
 - VCI, 306–308
 - VPI, 306
 - NO-CRC-4 framing, E1 circuits, 158
 - noise, 7–9
 - noise funneling, 455
 - noise margin, 421–422
 - non-associated signaling, 31
 - non-compelled R2 signaling, 167
 - non-deferred blocking, GR-303-CORE, 17
 - nonreal-time service classes, 331
 - ABR, 337–341
 - GFR, 343
 - nrt-VBR, conformance definition, 336
 - UBR, 341–342
 - North American Digital Hierarchy (NADH), 125
 - North American point code format, 39
 - nrt-VBR (real-time variable bit rate), 336
 - nrt-VBR service category, 365
 - NT12s, 218
 - NTSC (National Television Systems Committee), 451
 - number portability, 69–70
 - call flow, 71–72
 - location portability, 72
 - Nyquist Theorem, 85

O

OAM (Operations, Administrations, and Maintenance) cells, 309–313
 network management levels, 312

OAM&P (operations, administration, maintenance and provisioning), 521

obsolescence of SMDS, 409

OC designation, SONET, 505–506

OCU-DP (office channel unit-data port), 108–109

OCx architectures, 486

OOF (out-of-frame), 137

OPC (Originating Point Code), 38

open topology, DQDB, 379

optical networks
 DWDM, 521
 fiber-optic cabling, 501, 504
 hardware, 495
 LTE, 498–499
 optical routers, 500
 PTE, 496
 STE, 500

rings, 522
 line protection switched topologies, 523
 path protection switched topologies, 524

SDH
 applications, 522–523
 frame structure, 519–520
 VCs, 517, 519

SONET, 505
 applications, 522–523
 STS-1 frame overhead, 508–516
 STS-1 frame structure, 506–507

WDM, 521

optical routers, 500

OSI reference model, equivalent SS7 layers, 41

overbooking, 321

overlap signaling, 59

overlapped PAM (pulse amplitude modulation), 430

P

packets, fragmentation, 467

packet-switching technologies, Frame Relay, 266–268
 access signaling specifications, 273
 congestion avoidance mechanisms, 286–289
 contractual SLA values, 282
 core access specifications, 272
 discards, 284–286
 DLCI, 276–282
 framework specifications, 271
 LMI specification, connection status, 289–291
 service description specifications, 271–272
 signaling, 286–292
 standards bodies, 268–270
 VCs, 275–276

PAD field (SIP Layer 3 PDUs), 390

pair gain, 14

PAL (Phase Alternating Line) standard, 451

PAM (pulse amplitude modulation), 85–91

path overhead, STS-1 frames, 513

path protection switched topologies, 524

Payload CRC field (SIP Layer 2 PDUs), 396

Payload Length field (SIP Layer 2 PDUs), 395

PCM (pulse code modulation), 84
 AMI line coding, 110–111

PCR (peak cell rate), 328

PDH (Plesiochronous Digital Hierarchy), 125–126, 181

peak-to-peak CDV, 325

PEs (physical entities), 63–64

physical characteristics
 E1 circuits, 155–157
 T1, 128–131

physical layer (B-ISDN model), 318
 PMD sublayer, 318
 TC sublayer, 318–319

physical layer specifications, ISDN, 219

plane management (M-plane), 317

PLAR (private line, automatic ringdown), 167

PLCP (physical layer convergence procedure)
 functions, SIP Layer 1, 396
 DS1 media, 397–399
 DS3 media, 399–400
 E1 media, 401
 Plesiochronous Digital Hierarchy (PDH), 125–126, 181
 plesiochronous timing versus hierarchical synchronous timing, 492
 PLL (Phase Lock Loop), 112
 PMD (physical medium dependent) sublayer
 functions, SIP Layer 1 318, 396
 PNNIs (Private Network-Network Interfaces), 304
 point codes, 37–38
 ANSI format, 39
 network indicators, 24
 UTI format, 40–41
 point-to-multipoint connections, DDS, 109
 polarity states, 108
 BPVs, 112
 capacitance, 111
 policing, 344–345. *See also* UPC
 portability, 69–72
 POTS splitters, 419
 power cross, 107
 power levels of DSL services, 428
 reducing/boosting, 429
 Trellis coding, 429–430
 power ranging, 470–471
 prediction mechanism, DPCM, 94
 presync state, 315
 PRI (Primary Rate Interface), 255–256
 NFAS, 257
 Q.Sig, 260
 T1/E1 configuration, 258–259
 troubleshooting, 259–260
 probability density model (CTD), 324
 protected fibers, 522
 protocol discriminator (Q.931 messages), 230
 proving period, link alignment process, 49
 PSD (power spectral density), 428
 pseudo-LAN conflict (SMDS), troubleshooting, 409
 PT (payload type) field, 309–313

PTE (path termination equipment), 496
 pulse signaling, R2, 169
 pulse streams, 85
 pulse stuffing, 134
 PVCs (permanent virtual circuits), 275

Q

Q.921 specification, 220–224
 alignment process, 224–227
 control octets, 222–223
 SAPs, 221
 timers, 227–228
 Q.931 specification, 229–230
 call flow, 232–233
 messages, 230, 233
 information elements, 233–240
 Q.Sig, 260
 QAM (quadrature amplitude modulation), 415–416, 458
 Trellis coding, 429–430

 QoS (quality of service)
 CAC, 320
 CER, 325
 CLR, 323
 maxCTD, 323–325
 peak-to-peak CDV, 325
 SECBR, 326
 QoS field (SIP Layer 3 PDUs), 391
 QPSK (quadrature phase shift keying), 458
 quantiles, 325
 quantizing process, 87–91
 quasi-associated signaling, 30
 queue-arbitration algorithm (DQDB), 380–382
 quick train, 426

R

R reference points, 219

R2 signaling

- call control, 167
- characteristics, 166–167
- interregister signaling, 170–173
- line signaling, 167

RADSL (rate adaptive DSL), 421, 433

RARP (Reverse ARP), 279

RBE (routing bridge encapsulation), RFC 1483, 438

RBS (robbed-bit signaling), 17, 28, 138

real-time polling, 467

real-time service classes, 331

- CBR, 333–334
- rt-VBR, 334–336

recovering discarded Frame Relay packets, 284–286

red alarms (T1), 146

reduced merged framing (DSL), 428

reduced overhead framing (DSL), 427

reduced separate framing (DSL), 427

reducing

- DSL power levels, 429
- noise during quantizing phase, 88–91

redundancy bytes, 422

reference points, 218–219

- ATM, 304
- CTD, 323

reflections, 455

regenerators, 517

repeaters, mid-span, 215–216

requirements of signaling data link setup, 42

Reserved field (SIP Layer 3 PDUs), 386

resistance, effect on DSL performance, 436

reverse battery signaling, 13

RF (radio frequency) signals, noise funneling, 455

RFC 1209, 374

RFC 1483 bridging, 438

RFI (radio frequency interference), effect on DSL performance, 434

rings (optical), self-healing, 522

- line protection switched topologies, 523
- path protection switched topologies, 524

- RJ-48X connectors, 129
- routers, optical, 500
- rt-VBR (real-time variable bit rate), 334
 - conformance definition, 336
 - service category, 365
- RZ (return-to-zero) encoding, DDS AMI implementation, 110–111

S

S reference point, 218

S/T bus, 218–219

SA (Source Address) field, SIP Layer 3 PDUs, 387–388

sampling, 85–87

SANC (signaling area network code), 40

SAPs (service access points), 221

SAR (segmentation and reassembly), IMPDUs, 382, 385

SAR (segmentation and reassembly) sublayer, 320

SAV (source address verification), 376

SB-ADPCM (Sub-Band ADPCM), 99

SCEF (Service Creation Environment Function), 63

SCF (Service Control Function), 63

SCPs (Service Control Points), 27

SCR (sustained cell rate), 328

screening SMDS addresses, 390

SD (selective discard), 342

SDF (Service Data Function), 63

SDH (Synchronous Digital Hierarchy)

- applications, 522–523
- frame structure, 519–520
- OAM&P, 521
- VCs, 517–519
- versus SONET, 504

SDP (Service Data Point), 64

SDSL, 433

SECAM (Système Electronique Couleur Avec Memoire), 451

SECBR (severely errored cell block ratio), 326

secondary channels, DDS, 106, 113

- security
 - cloned devices, 480
 - DOCSIS, 480–482
 - Segment Type field (SIP Layer 2 PDUs), 394
 - Segmentation Unit field (SIP Layer 2 PDUs), 395
- self-healing rings, 523
 - line protection switched topologies, 523
 - path protection switched topologies, 524
- semi-compelled R2 signaling, 167
- Sequence Number field (SIP Layer 2 PDUs), 395
- serial-link layer protocols, DXI, 403–405
- service classes (ATM), 331
 - nonreal-time
 - ABR, 337–341
 - GFR, 343
 - nrt-VBR, 336
 - UBR, 341–342
 - real-time
 - CBR, 333–334
 - rt-VBR, 334–336
- service description specifications, Frame Relay, 271–272
- service providers
 - portability, 69–70
 - local number portability call flow, 71–72
 - location portability, 72
 - wholesale, DSL, 441
- services
 - CS-2, 66–68
 - Type A, 65
 - Type B, 65
- SEUM (signal unit error rate monitor), 43
- SF (D4 Superframe), 136
- SFID (service flow identifier), 464
- shades of gray analogy, analog communication, 81
- SIB (Status Indicator Busy), 46–47
- SIE (Status Indicator Emergency), 46–48
- SIF (Service Information Field), MSU, 50–52
- SIG (SMDS Interest Group), 374
- signal levels of NADH, 184–185
- signal unit identification (FISU), 44
- signaling, 22
 - analog, 3
 - amplitude, 4
 - attenuation, 6–9
 - DACs, 10
 - distortion, 5–6
 - frequency, 5
 - GR-303-CORE standard, 17–18
 - IDLCs, 14, 16
 - noise, 7, 9
 - tip and ring circuits, 11–14
 - versus digital, 3
 - wavelength, 5
 - associated, 29
 - CAS, 28
 - CCS, 29
 - conversion process, 83–84
 - Frame Relay, 286–289
 - call control, 292
 - connection status, 289–292
 - non-associated signaling, 31
 - polarity states, 108
 - quasi-associated signaling, 30
 - SS7
 - DUP, 54–55
 - ISUP, 58–59
 - link sets, 34
 - links, 36
 - MTP, 41–54
 - need for, 32–33
 - point codes, 37–41
 - SCPs, 27
 - signaling links, 33–34
 - SSPs, 23, 25
 - STPs, 27
 - TUP, 56–58
 - traffic management, 53
- signaling links, 33–34
- Simple Unsuccessful Backward Setup Information Message (TUP), 58
- SIN (Status Indicator Normal), 46–48
- single leaky bucket method, congestion control, 334
- single mode fiber, 502
- single-ended services, 65

- single-latency mode, DSL data transmission, 427
- sinusoidal waves, 82
- SIO (Status Indicator Out of Alignment), 47
- SIOS (Status Indicator Out of Service), 46
- SIP (SMDS Interface Protocol), 375–377
 - Layer 1
 - PLCP functions, 396–401
 - PDU fields, 396
 - Layer 2 PDU fields, 393–396
 - Layer 3 PDU fields, 386–392
- SIP (SMDS Interface Protocol), 375
- SIPO (Status Indicator Processor Outage), 46–47
- SLAs (service-level agreements), contractual values, 282
- SLCs (Signaling Link Code), 15, 34
- slots, DQDB, 380
 - IMPDU's, SAR, 382, 385
- SLS (Signaling Link Selection), 34
- SLT (Signaling Link Terminal), 43
- SMAF (Service Management Access Function), 63
- smart-jacks, 128
- SMC (SONET Minimum Clock), 493
- SMDS (Switched Multimegabit Data Service), 355–356
 - access-classes, 376
 - access speeds, 376
 - addressing, 376
 - screening, 390
 - subscription, 388–390
 - alignment with 802.6, 373, 385
 - architecture, 374
 - Bellcore's role in development, 373–374
 - configuring, 405–406
 - DQDB, 377
 - DXI protocol, 375
 - troubleshooting, 407
 - features, 372
 - history, 372–374
 - Layer 3 protocol interworking, 377
 - obsolescence of, 409
 - pseudo-LAN conflict, troubleshooting, 409
 - SIP, 375–377
 - Layer 1 PDU, PLCP functions, 396–401
 - Layer 2 PDU fields, 393–396
 - Layer 3 PDU fields, 386–392
 - SNI, troubleshooting, 408
 - source address validation, 390
 - time-to-market delay, 385
 - troubleshooting, 407
- SMF (Service Management Function), 63
- SN (Service Node), 64
- SNI (Subscriber Network Interface), troubleshooting, 408
- SONET (Synchronous Optical Network), 505
 - applications, 522–523
 - fiber-optical cabling, 501, 504
 - OAM&P, 521
 - OC designation, 505–506
 - STS-1 frame overhead, 508–516
 - STS-1 frame structure, 506–507
 - versus SDH, 504
- source address validation, SMDS, 390
- source devices (ATM), traffic parameters, 327
 - BT, 329
 - CDVT, 329, 331
 - MBS, 329
 - MCR, 329
 - MFS, 329
 - PCR, 328
 - SCR, 328
- source-traffic descriptors, 327
- sparse combining, 482
- specifications
 - Frame Relay
 - access signaling, 273
 - core access, 272
 - framework, 271
 - service description, 271–272
 - ISDN
 - physical layer, 219
 - Q.921, 220–228
 - Q.931, 229–233
- SPIDs (service profile identifiers), 40, 248
- split plan, 452
- SPVCs (soft PVCs), 275
- SRDM (Subrate Data Multiplexer), 108

- SRF (Special Resource Function), 63
- SS7 (Signaling System 7). *See also* INs
- DUP, 54–55
 - equivalent OSI layers, 41
 - ISUP, 58–59
 - links, 36
 - MTP, 41
 - MTP1, 42–43
 - MTP2, 43–52
 - MTP3, 52–54
 - need for, 32–33
 - point codes, 37–38
 - ANSI format, 39
 - UT format, 40–41
 - SCPs, 27
 - signaling links, 33–34
 - SSPs, 23–25
 - STPs, 27
 - TUP, 56–58
- SSCF (service specific coordination function), 320
- SSCS (service specific convergence sublayer), 320
- SSF/CCF (Service Switching Function/Call Control Function), 62
- SSPs (Service Switching Points), 23–25
 - national SSPs, Class 5, 25
 - SLS, 34
- SSU (Synchronization Supply Unit), 494–495
- standard train, 426
- standards bodies
 - Frame Relay, FRF IAs, 273–274
 - governing ATM development, 301–302
- STDM (statistical TDM), 267
- STE, 500
- steaming mode (common part), 356
- STM (Synchronous Transport Module) versus ATM, 303
- STPs (Signal Transfer Points), 27
- Stratum clocks, 493
- STS (Synchronous Transport Signal), 505
- STS-1 frame structure
 - overhead, 508–516
 - SONET, 506–507
- sub-band codecs, 99
- sublayers of AAL, 319–320
- subrate offerings, E1, 157
- Subsequent Address Message (TUP), 57
- super headends, 451
- SVCs (switched virtual circuits), 275
- SW56, 115
 - Cisco router configuration, 118–119
 - DTMF, 116
- sync byte, 427
- sync state, 315
- synchronous technologies versus asynchronous, 105
- synchronous timing
 - BITS, 494–495
 - Stratum clocks, 493
- SYNTRAN (synchronous transmission), 182, 505

T

T reference point, 218

T1 circuits

- alarm conditions, troubleshooting, 146–147
- controller configuration, 147
- ESF frame format, D5 channel banks, 140–142
- framing formats, 135
 - D1 channel banks, 137–139
 - D1D channel banks, 140
 - D3 channel banks, 140
 - D4 channel banks, 140
 - D5 channel banks, 140–142
- hairpin connections, configuring, 148
- line-coding schemes, 132–135
- physical characteristics, 128–131
- PRI configuration, 258–259
- troubleshooting, 142
 - BERT, 143–144
 - format errors, 145–146
 - logic errors, 145–146

- T3 circuits, 180
 - channelized, 183, 198–199
 - deployment options, 193
 - framing, 195–197
 - line coding, 194
 - synchronous circuits, 182
 - unchannelized, 183
- T3Plus, development of HSSI, 402
- tandem switches, 25
- Tc (committed rate measurement interval), 282
- TC sublayer, 318–319
- TDM (time-division multiplexing), 14, 22, 109, 126
- TE1 (terminal equipment type 1) devices, 219
- TE2 (terminal equipment type 2) devices, 219
- TEI checks, 225
- TEK (traffic encryption key), 480
- Telecommunication Act of 1996, 68
- television, international standards, 451
- test patterns, DDS, 117–118
- tilt effect of signal strength, 448
- timers
 - for link alignment, 49
 - Q.921, 227–228
- timing sources of DDS, 112
- tip and ring circuits, 11–14
- TMs (terminal multiplexers), 496
- toll free number lookup, 67
- tone-on-idle signaling, 168
- topologies, DQDB, 379
- traffic, congestion control
 - closed-loop flow control, 338
 - continuous-state leaky bucket model, 347
 - dual leaky bucket model, 336
 - EPRCA, 339
 - single leaky bucket model, 334
- traffic management, 344
 - ABR service category, 366
 - CBR service category, 365
 - CER, 325
 - CLR, 323
 - GCRA, 345–346
 - maxCTD, 323, 325
 - nrt-VBR service category, 365
 - PCR algorithm, 349
 - peak-to-peak CDV, 325
 - policing, 345
 - rt-VBR service category, 365
 - SCR algorithm, 350
 - SECBR, 326
 - UBR service category, 365
- traffic parameters (ATM), 327. *See also* service classes
 - BT, 329
 - CDVT, 329–331
 - MBS, 329
 - MCR, 329
 - MFS, 329
 - PCR, 328
 - SCR, 328
- traffic shaping, 330
- trainup, 426
- transmission frame adaptation, 319
- transmission rates, DDS, 106
- transmit filter, DDS, 106
- transport mechanisms, DSL, 439–440
- Trellis coding, 429–430
- tributaries, 516
- troubleshooting
 - ISDN BRI, 252–254
 - ISDN PRI, 259–260
 - SMDS, 407
 - DXI, 407
 - pseudo-LAN conflict, 409
 - SNI, 408
- T1, 142
 - alarm conditions, 146–147
 - BERT, 143–144
 - format errors, 145–146
 - logic errors, 145–146
- trunk cable, 447
- trunks, IMTs, 27
- TUP (Telephone User Part) messages, 56–58
- Type A frames (Q.921), 221
- Type A services, 65
- Type B frames (Q.921), 221
- Type B services, 65

U

U interface (ISDN), 218
 UBR (unspecified bit rate), 341–342, 365
 UCDs (upstream channel descriptors), 469
 UGS (Unsolicited Grant Service), 466
 unassigned cells, 319
 unchannelized T3, 182–184
 UNI (User-Network Interface), 304
 header fields, 305
 CLP, 313
 GFC, 306
 HEC, 313, 316
 PT, 309–313
 VCI, 306–308
 VPI, 306
 PNNIs, 304
 related IAs, 303
 UNI 3.x/4.0 specification, 304
 unipolar signals versus bipolar, 108
 unmarked frames, 343
 unprotected fiber, 522
 UPC (usage parameter control)
 continuous-state leaky bucket algorithm, 347
 GCRA (generic cell rate algorithm), 345–346
 PCR algorithm, 349
 SCR algorithm, 350
 U-plane (B-ISDN model), 317
 upper-layer protocols (SS7)
 DUP, 54–55
 ISUP, 58–59
 TUP, 56–58
 UPSR (unidirectional path switched ring), 524
 upstream admission control, 479
 upstream noise, 455–456

V

VCCs (virtual channel connections), 306
 VCI (virtual channel identifier) field, 306–308
 effect on PT, 312–313
 VCs (virtual circuits), 275–276

VCs (virtual containers), 517–519
 VDSL (very high-rate DSL), 433
 virtual channel switching, 308
 virtual path switching, 308
 virtual scheduling algorithm, 346
 voltage
 1s density, 112
 capacitance, 111
 VPCs (virtual path connections), 306
 VPI (virtual path identifier) field, 306
 effect on PT, 312–313

W

wavelength, 5
 WDM (wavelength-division multiplexing), 127, 521
 wholesale services, DSL, 441
 wink mode (E&M signaling), 13

X-Y-Z

XOR (exclusive OR) function, 92–93

yellow alarms, T1, 146

zero substitution, DSS line coding schemes, 113
 zone ID (ITU point codes), 40