



# INDEX

## A

---

- AAC
  - Cube/Office Locator service, 16–17
- AAC Associates, Inc., 5, 24
- Accept Header (HTTP), 132–133
- accessing device information
  - Cisco IP Phones, 107
- accounts billing
  - CRM, 10–11, 13
  - phone services, 4
- adding
  - soft keys to XML objects, 70
  - to directories list (Cisco IP Phones), 150
- adding phone services, 159–160
- advertising on Cisco IP phones, 18
- angle brackets
  - escape sequences (XML), 121–122
- appending
  - device name to services, 165
- application primitives
  - building directories, 147, 149
- applications
  - generating graphics with arrays, 169–170, 173
  - generating graphics with numeric strings, 173–175
  - SDK
    - Graphics Conversion Control, 195–200
    - LDAP Search Control, 205–212
    - Photoshop Graphics Filter, 212
    - URL Proxy Control, 201–204
    - Validator, 214–215
- applying
  - phone usage to corporate accounts, 4
- architecture
  - of services, 35–36
- architecture of CallManager, 27
  - components of, 27–28
  - high-level protocols, 29
  - low-level networking, 28

- arrays
  - data concatenation, 172–173
  - generating graphics, 169–170, 173
- ASP (Active Server Pages)
  - Content-type header
    - displaying, 101
  - Refresh header
    - displaying, 101
- ASP pages
  - SonOfMagicCube.asp, 48–49
  - VAT-Goodbye, 136, 141
  - VAT-Track, 136
  - VAT-Welcome, 134
- aspect ratio
  - maintaining for resized images, 176, 178
- assigning
  - CM-SIM IP address to Cisco IP Phones, 226–227
  - IP address to CIM-SIM system, 224–225
- attributes (XML), 45, 114–115
- authentication, 65
  - Cisco IP Phones, 107
  - URL Proxy Control properties, 203

## B

---

- behavioral differences of directories and services, 146–147
- Berbee, 4, 24
  - CRM, 10–11, 13
- billing
  - phone services to accounts, 4
- bitwise operations, 173
- browser
  - HTTP client sessions, 103
    - authentication, 104–105
    - Proxy, 105
    - session life, 104
    - State management, 104
    - URL history, 104

- browser (Cisco IP Phone), 99
  - GET requests, 99
  - HTTP headers
    - Content-type, 100
    - Expiration, 102
    - Location, 101–102
    - Refresh, 101
    - Set-Cookie, 103
- browsers
  - XML-capable, 117
- buffering content, 139
- building
  - directories
    - LDAP Search COM objectd, 151–154
    - primitives, 147, 149
- business goals
  - gaining competitive edge, 13
    - hospitality services, 14, 17
  - generating revenue, 17
    - advertising on Cisco IP Phones, 18
  - increasing productivity, 3–7, 9–10, 12–13
- buttons
  - Services, 34

## C

- 
- Calence, 24
    - menu-driven business listings, 18
  - call routing
    - CM-SIM, 222
  - CallManager
    - architecture, 27
      - components, 27–28
      - high-level protocols, 29
      - low-level networking, 28
    - CM-SIM functionality, 221
    - phone services
      - adding, 159–160
      - deleting, 161
      - updating, 161
  - CallManager Administration
    - adding phone services, 159–160
    - deleting phone services, 161
    - Enterprise Parameters Configuration, 57–58
    - updating phone services, 161
  - CallManager URL Directories enterprise parameter, 80
  - Cancel soft key, 71
  - capturing
    - CIP display, 189–191
  - character sets
    - support, 64
  - chat rooms
    - Discussion Forum (HotDispatch), 24
  - choosing
    - soft key positions, 70
    - Web programming language, 39–40
    - Web servers, 37–38
  - CIP
    - data manipulation, 172
    - image navigation, 178, 181–188
    - images
      - manipulating, 169–170, 173
      - screen captures, performing, 189–191
  - Cisco 7940 IP Phones, 30
  - Cisco 7960 IP Phones, 30
  - Cisco CallManager Simulator
    - See* CM Sim
  - Cisco CTE 1400, 57
  - Cisco IP Phones
    - communicating with CM-SIM, 225, 227
    - directories
      - building, 147, 149, 151–154
      - displaying, 150
      - versus services, 146
    - Exit, 71
    - HTTP, 97
      - requests, 97
      - responses, 98
    - HTTP Client, 99
      - Content-type header, 100
      - Expiration header, 102
      - GET requests, 99
      - Location header, 101–102
      - Refresh header, 101
      - sessions, 103–105
      - Set-Cookie header, 103
    - HTTP servers, 106
      - accessing device information, 107
      - push, 106–107

- Next soft key, 147
- Search soft key, 147
- service integration, 157–158
- services
  - subscriptions, 157–158, 162
- Services button, 34
- soft keys, 70
  - Cancel, 71
  - Submit soft key, 146
  - versus PBX phones, 31–32
- CiscoIPPhoneDirectory object, 78–80
- CiscoIPPhoneError object, 88
- CiscoIPPhoneExecute object, 87–88
- CiscoIPPhoneGraphicMenu object, 83–85
- CiscoIPPhoneIconMenu object, 85–87
- CiscoIPPhoneImage object, 80–81, 83
  - creating from numeric strings, 174–175
  - runtime image conversion, 176, 178
- CiscoIPPhoneInput object, 76–78
- CiscoIPPhoneMenu object, 73–74
- CiscoIPPhoneResponse object, 88
- CiscoIPPhoneText object, 74–76
- client functionality
  - authentication, 65
  - Cisco IP Phones services, 59
- client/server
  - Cisco IP Phones, 99
    - Content-type header, 100
    - Expiration header, 102
    - GET requests, 99
    - Location header, 101–102
    - Refresh header, 101
    - Set-Cookie header, 103
  - HTTP, 97
    - requests, 97
    - responses, 98
    - sessions, 103–105
- CM-SIM
  - call routing, 222
  - configuring, 224–225
  - debugging, 232
  - default settings, 228
    - overriding, 229–230
  - functionality, 219
    - CallManager service, 221
    - TFTP server, 220–221
    - handling external/internal calls, 225
    - installing, 223
    - Keep-alive count, 230
    - limitations, 222
    - network configuration, 226–227
    - phone setup, 225, 227
    - running, 230
    - running from CD, 223
    - system requirements, 224
  - ColorBitDepth property, 198
  - ColorImage property, 199
  - comments (XML), 123
  - companion CD-ROM
    - contents, 21
  - compiled languages, 39
  - concatenating
    - data with arrays, 172–173
  - configuration files
    - XML, 220
    - loadinformation element, 221
  - configuring
    - CM-SIM, 224–225
    - overriding default settings, 229–230
    - phone setup, 225, 227
  - content
    - pushing, 191–192
  - content buffering, 139
  - content translation engine
    - Cisco CTE 1400, 57
  - contents of companion CD-ROM, 21
  - Content-type header (HTTP), 100
  - cookies, 103
  - creating
    - directories
      - with LDAP Search COM object, 151–154
      - single object directories, 147, 149
    - criteria
      - for selecting Web servers, 37–38
      - for Web programming language selection, 39–40
  - CRM (customer relationship management), 10–11, 13
  - Cube/Office Locator service, 16–17
  - custom directories, 80

- custom soft keys
  - defining, 131
- customizing
  - user subscriptions, 164

## D

---

- data
  - concatenating with arrays, 172–173
- debugging
  - CM-SIM, 232
  - XML, 127
- default services, 164
- default settings
  - CM-SIM, 228
  - overriding, 229–230
- defining
  - custom soft keys, 131
- deleting phone services, 161
- designing
  - VAT services, 134, 136
  - example source code, 137, 139–141
- Developer Support Program, 51
- device names
  - appending to services, 165
- devices
  - HTTP clients
    - identifying, 61
- directories
  - building
    - LDAP Search COM object, 151–154
    - primitives, 147, 149
  - characters set support, 64
  - custom, 80
  - displaying on Cisco IP Phones, 150
  - indirection, 58
  - soft key support, 64
  - versus services, 146–147
- displaying
  - directories on Cisco IP Phones, 150
  - XML schema supported version, 132–133
- DNs (Directory Numbers), 224–225
- documentation
  - XML comments, 123
- DTD, 125
- DTD (Document Type Definition), 45
- DuCharme, Bob, 128

## E

---

- elements
  - behavior in objects, 72
- elements (XML), 115
- enterprise parameters
  - CallManager URL Directory, 80
- Enterprise Parameters Configuration, 57–58
- entrepreneurial opportunities, 19
  - developing successful services, 20
- error messages
  - plain text, 132
- error reporting
  - URL Proxy Control properties, 203
- escape sequences (XML), 121–122
  - mandatory, 89
- examples
  - Graphics Conversion Control (SDK), 199–200
  - of stock quote services, 36
  - of URL Proxy Control, 204
  - of Web application, 45–47
  - of XML configuration files, 220
  - of XML Schema, 125–126
  - phone applications for increased productivity
    - AAC Associates, 5, 12–13
    - Berbee, 4, 10, 12
    - Frederick County school district, 5–6, 9–10
- executable files
  - CM-SIM
    - running from CD, 223
- Exit soft key, 71
- Expiration header (HTTP), 102
- external calls
  - handling with CM-SIM, 225
- exXclusive OR (XOR), 173

## F

---

- fail back, 66
- fail over, 66
- FAQs
  - XML, 128
- files
  - CM-SIM executable
    - running from CD, 223

- loading
  - methods, 197
  - valid (XML), 125
  - well-formed, 124
  - XML, 220
    - loadinformation element, 221
- FileSystemObject
  - ForAppending value, 137
- flow control
  - of service architecture, 36
- ForAppending value (FileSystemObject), 137
- formatting
  - of structured documents, 112–113
- formatting output
  - LDAP Search Control, 210–212
- FTP
  - versus TFTP, 219
- functionality
  - of CM-SIM, 219
    - CallManager service, 221
    - TFTP server, 220–221
  - of directories and services, 146–147
- functions
  - formatImage, 184
  - getBaseURL, 181
  - JavaScript
    - getBaseURL(), 137
    - logStats, 138
  - setXLoc, 182
  - setYLoc, 182
  - setZoom, 182

## G

---

- gaining competitive edge
  - as business goal, 13
    - hospitality services, 14, 17
- generating revenue
  - as business goal, 17–18
- GET requests (HTTP), 98–99
  - phone-initiated services, 32–33
- getBaseURL function, 181
- getBaseURL() function (JavaScript), 137

- graphics
  - generating with Arrays, 169–170, 173
  - generating with numeric strings, 173–175
  - image navigation, 178, 181–188
  - pixel packed format, 171
  - resizing images, 176, 178
  - runtime conversion, 176, 178
- Graphics Conversion Control, 195
  - example, 199–200
  - installation, 196–197
  - methods, 197–199
  - properties, 197–199
  - server-side conversion, 196
- guidelines
  - for enabling soft keys, 131

## H

---

- headers
  - HTTP, 97
- Height property, 197
- Help soft key, 59
- high-level protocols
  - Cisco IP Phone services, 29
- history
  - of XML, 41–42
- hospitality services
  - gaining competitive edge, 14, 17
- HotDispatch, 22
- HTTP (Hypertext Transfer Protocol), 29, 97
  - Accept Header, 132–133
  - Client sessions, 103
    - authentication, 104–105
    - proxy servers, 105
    - session life, 104
    - state management, 104
    - URL history, 104
  - GET requests
    - phone-initiated services, 32–33
  - requests
    - GET, 97–98
  - servers, 106
    - accessing device information, 107
    - push, 106–107
    - suitability for IP Phone services, 43

HTTP Client (Cisco IP Phones), 59, 99

- Content-type header, 100
- Expiration header, 102
- GET requests, 99
- Location header, 101–102
- Refresh header, 101
- Set-Cookie header, 103

HTTP headers

- designing VAT services, 134, 136
- example source code, 137–141

HTTP servers

- client authentication, 65
- creating screen captures, 60
- gathering device information, 60
- HTTP Post, 60
- identifying client devices, 61
- Push/Pull operations, 61
- server authentication, 65
- stream control, 62–63
- URIs, 62

hybrid languages, 40

## I

i button

- redirecting, 59

identifying

- client devices, 61

IIS

- Web server error messages
- plain text, 132

images

- creating, 170
- generating from numeric strings, 173–175
- manipulating, 169–170, 173
- navigating, 178, 181–188
- pixel packet format, 171
- resizing, 176, 178
- runtime conversion, 176, 178

increasing productivity

- as business goal, 3–7, 9–10, 12–13

indirection, 58

installing

- CM-SIM, 223
- Graphics Conversion Control (SDK), 196–197
- Photoshop Graphics Filter, 212
- URL Proxy Control, 202
- Validator, 214

integrating

- services with Cisco IP Phones, 157–158

internal calls

- handling with CM-SIM, 225

Internet Explorer (Microsoft)

- Microsoft Internet Explorer, 117

invoking

- services, 34

IP address

- assigning to CM-SIM system, 224–225

IP Phones

- service integration, 157–158
- services

  - subscriptions, 157–158
  - subscriptions, 162

- soft keys, 70
- versus PBX phones, 31–32

## J

JavaScript

- getBaseURL() function, 137
- logStats function, 138
- SonOfMagicCube.asp, 48–49

JSP (Java Server Pages)

- Content-type header

  - displaying, 101

- Date header

  - displaying, 103

- Location header

  - identifying, 102

- Refresh header

  - displaying, 101

## K

---

Keep-alive count (CM-SIM), 230  
Key tag (XML), 71–72

## L

---

languages (Web programming), 38–39  
  compiled, 39  
  hybrid, 40  
  scripting, 40  
Latin-1 character set, 64  
LDAP Search COM objects  
  creating directories, 151–154  
LDAP Search Control, 205  
  configuring, 207  
  formatting output, 210–212  
  installing, 206  
  methods, 209  
  output options, 207  
  search options, 208–209  
limitations  
  of CM-SIM, 222  
lines  
  DNs, 224–225  
loadInformation element  
  XML configuration files, 221  
loading files  
  methods, 197  
Location header (HTTP), 101–102  
logStats function (JavaScript), 138  
low-level networking  
  Cisco IP Phones, 28

## M

---

maintaining aspect ratio of resized images, 176, 178  
mandatory escape sequences (XML), 89  
manipulating  
  CIP data, 172  
  CIP images, 169–170, 173–175  
  images, 178, 181–188

manual configuration  
  CM-SIM IP address, 226–227  
markup languages, 43  
  SGML, 113  
  XML. *See also* XML  
    adding soft keys to objects, 70  
    attributes, 114–115  
    CiscoIPPhoneDirectory, 78–80  
    CiscoIPPhoneError, 88  
    CiscoIPPhoneExecute, 87–88  
    CiscoIPPhoneGraphicMenu, 83–85  
    CiscoIPPhoneIconMenu, 85–87  
    CiscoIPPhoneImage, 80–81, 83  
    CiscoIPPhoneInput, 76–78  
    CiscoIPPhoneMenu, 73–74  
    CiscoIPPhoneResponse, 88  
    CiscoIPPhoneText, 74–76  
    comments, 123  
    debugging, 127  
    DTD, 45, 125  
    elements, 115  
    escape sequences, 121–122  
    importance of, 111  
    mandatory escape sequences, 89  
    objects, 48, 72, 116  
    objects, quick reference guide, 89, 91, 93–94  
    prolog statement, 120  
    schema, 124  
    SKD training and support, 50–51  
    structured documents, 112–113  
    tags, 44, 114  
    valid files, 125  
    validating schema, 127  
    Web sites, 128  
    well-formed files, 124  
menu-driven business listings, 18  
  type-head menu selection, 20  
messages  
  Web server errors  
    plain text, 132  
methods  
  Graphics Conversion Control (SDK), 197–199  
  LDAP Search Control, 209  
  URL Proxy Control, 202–203



- micro-browser (Cisco IP Phone), 99
  - Get requests, 99
  - HTTP client sessions, 103
    - authentication, 104–105
    - Proxy, 105
    - session life, 104
    - state management, 104
    - URL history, 104
  - HTTP headers
    - Content-type, 100
    - Expiration, 102
    - Location, 101–102
    - Refresh, 101
    - Set-Cookie, 103
- Microsoft Jscript scripting engine
  - updating, 138
- MIME (multipurpose Internet mail extensions), 69
- MIME type
  - identifying, 100

## N

---

- navigating images, 178, 181–188
- network architecture
  - CallManager, 27
    - components of, 27–28
    - high-level protocols, 29
    - low-level networking, 28
- network configuration
  - CM-SIM, 226–227
- Next soft key, 147
- numeric strings
  - generating graphics, 173–175

## O

---

- objects
  - CiscoIPPhoneDirectory, 78–80
  - CiscoIPPhoneError, 88
  - CiscoIPPhoneExecute, 87–88
  - CiscoIPPhoneGraphicMenu, 83–85
  - CiscoIPPhoneIconMenu, 85–87

- CiscoIPPhoneImage, 80–81, 83
  - creating from numeric strings, 174–175
  - runtime image conversion, 176, 178
- CiscoIPPhoneInput, 76–78
- CiscoIPPhoneMenu, 73–74
- CiscoIPPhoneResponse, 88
- CiscoIPPhoneText, 74–76
- quick reference guide, 89, 91, 93–94
- XML, 44
- objects (XML), 48, 72, 116
  - adding soft keys, 70
- orMatImage function, 184
- output options
  - LDAP Search Control, 207
- overlapping tag definitions (XML), 116
- overriding
  - CM-SIM default settings, 229–230

## P

---

- parameters (service), 157
- PBX phones
  - versus IP Phones, 31–32
- per-device user subscriptions, 164
- performing
  - screen captures on display, 189–191
- phone setup
  - CM-SIM, 225, 227
- phone usage
  - applying to corporate accounts, 4
- phone-initiated services, 32–33
- Photoshop Graphics Filter, 212
  - installing, 212
- pixel packet image format, 171
- plain text error messages, 132
- positioning soft keys
  - selecting, 70
- primitives
  - building directories, 147, 149
  - designing VAT services, 134, 136
    - example source code, 137–141
- product support
  - HotDispatch, 22

- productivity
  - as business goal, 3–4, 6
    - AAC Associates, 5, 10
    - Berbee, 10, 12–13
    - Frederick County public schools, 6–7, 9–10
- profitability
  - as business goal, 17–18
- profit-making opportunities, 19
  - developing successful services, 20
- prolog statement (XML), 120
- properties
  - Graphics Conversion Control (SDK), 197–199
  - URL Proxy Control, 202, 204
- proprietary protocols
  - suitability for phone services, 42
- proxy use
  - URL Proxy Control properties, 203
- Pull operations, 61
- push, 106
  - authentication, 107
- Push operations, 61
- pushing
  - content, 191–192
- requests
  - GET, 99
  - HTTP, 97
- requirements
  - for CM-SIM operation, 224
- Resize method, 198
- resizing
  - images, 176, 178
- responses
  - HTTP, 98
- restrictions
  - of CM-SIM operation, 222
- returning plain text error messages, 132
- revenue generation
  - advertising on Cisco IP Phones, 18
  - developing successful services, 20
  - entrepreneurial opportunities, 19
- routing calls
  - CM-SIM, 222
- RTP (Real-Time Transport Protocol), 29
  - stream control, 62–63
- running CM-SIM from CD, 220, 223
- runtime conversion
  - of CiscoIPPhoneImage object, 176, 178

## Q

---

- query strings, 99

## R

---

- redirecting the i button, 59
- ReducePaletteColors() method, 199
- redundancy
  - fail over, 66
- Refresh header (HTTP), 101
- registry (Windows)
  - CM-SIM configuration information, 231
- removing
  - phone services from CallManager, 161
- requesting
  - HTTP client devices, 61

## S

---

- sample Web application, 45–47
- SaveCIP() method, 199
- SCCP (Skinny Client Control Protocol), 29
- schema
  - DTD, 125
- schema (XML), 45, 124
  - supported version, displaying, 132–133
- scraping, 202
- screen captures
  - creating, 60
  - performing on display, 189–191
- scripting engine
  - Microsoft Jscript
    - updating, 138
- scripting languages, 40
  - JavaScript
    - SonOfMagicCube.asp, 48–49

## SDK

- Graphics Conversion Control, 195
  - example, 199–200
  - installation, 196–197
  - methods, 197–199
  - properties, 197–199
  - server-side conversion, 196
- LDAP Search Control, 205
  - configuring, 207
  - formatting output, 210–212
  - installing, 206
  - methods, 209
  - output options, 207
  - search options, 208–209
- Photoshop Graphics Filter, 212
  - installing, 212
- URL Proxy Control, 201–202
  - example, 204
  - installing, 202
  - methods, 202–203
  - properties, 202, 204
- Validator, 215
  - installing, 214
- XML, 50–51
- search options
  - LDAP Search Control, 208–209
- Search soft key, 147
- security
  - client authentication, 65
  - HTTP Basic Authentication, 104–105
  - server authentication, 65
- selecting
  - soft key positions, 70
  - Web programming language, 39–40
  - Web servers, 37–38
- server functionality (HTTP servers)
  - authentication, 65
  - Cisco IP Phones services, 59
  - creating screen captures, 60
  - gathering device information, 60
  - HTTP Post, 60
- servers
  - HTTP, 106
    - accessing device information, 107
    - push, 106–107
- services, 33
  - adding to CallManager, 159–160
  - architecture, 35–36
  - CallManager
    - CM-SIM functionality, 221
  - character set support, 64
  - client functionality, 59
  - default, 164
  - deleting from CallManager, 161
  - device name, appending, 165
  - Enterprise Parameters Configuration (CallManager Administration), 57–58
  - Help soft key, 59
  - indirection, 58
  - integrating with Cisco IP Phones, 157–158
  - invoking, 34
  - parameters, 157
  - phone-initiated, 32–33
  - Push/Pull operations, 61
  - redundancy, 66
  - server functionality, 59
    - creating screen captures, 60
    - gathering device information, 60
    - HTTP Post, 60
  - soft key support, 64
  - stock quotes, 36
  - subscriptions, 157–158, 162
  - updating on CallManager, 161
  - VAT (Voice Anomaly Tracking), 134
    - designing, 134, 136
    - source code, example, 137, 139–141
  - versus directories, 146–147
- Services button, 34
- Set-Cookie header (HTTP), 103
- setXLoc function, 182
- setYLoc function, 182
- setZoom function, 182
- SGML (Standard Generalized Markup Language), 113
- simulating
  - CallManager service with CM-SIM, 221
- skills relevant to IP Phone service developers, 38
- Skiny Client Control Protocol
  - See SCCP
- soft keys, 70
  - adding to XML objects, 70
  - Cancel, 71

- custom
  - defining, 131
- directory support, 64
- Exit, 71
- Help, 59
- Next, 147
- Search, 147
- service support, 64
- Submit, 146
- SoftKeyItem tag, 71
- SonOfMagicCube.asp, 48
- state management
  - Web servers, 104
- stock quote services, 36
- stream control, 62–63
- structure
  - of CiscoIPPhoneDirectory object, 79
  - of CiscoIPPhoneExecute object, 88
  - of CiscoIPPhoneGraphicMenu object, 84–85
  - of CiscoIPPhoneIconMenu object, 86–87
  - of CiscoIPPhoneImage object, 81–82
  - of CiscoIPPhoneInput object, 77–78
  - of CiscoIPPhoneMenu object, 74
  - of CiscoIPPhoneResponse object, 88
  - of CiscoIPPhoneText object, 75
- structured documents, 112–113
- Submit soft key, 146
- subscriptions, 162
  - per-device, 164
- subscriptions to services, 157–158
- system requirements
  - CM-SIM, 224

## T

- tags (XML), 44, 114
  - Key, 71–72
  - overlapping definitions, 116
  - SoftKeyItem tag, 71
  - URL, 71
- TFTP (Trivial File Transfer Protocol) versus FTP, 219
  - CM-SIM functionality, 220
    - servicing XML configuration files, 221
  - command-line version, 232

- versus FTP, 219
- Timed Pull operations, 62
- tools (SDK)
  - Graphics Conversion Control, 195
    - example, 199–200
    - installation, 196–197
    - methods, 197–199
    - properties, 197–199
    - server-side conversion, 196
  - LDAP Search Control, 205
    - configuring, 207
    - formatting output, 210–212
    - installing, 206
    - methods, 209
    - output options, 207
    - search options, 208–209
  - Photoshop Graphics Filter, 212
    - installing, 212
  - URL Proxy Control, 201–202
    - example, 204
    - installation, 202
    - methods, 202–203
    - properties, 202, 204
  - Validator, 215
    - installing, 214
- type-head menu selection, 20

## U

- UDP
  - RTP, 29
- updating
  - Microsoft Jscript scripting engine, 138
  - updating phone services, 161
- URI (Uniform Resource Identifier), 62, 99
  - pushing content, 191–192
- URL
  - cookies, 103
  - indirection, 58
  - pushing content, 191–192
- URL Proxy Control, 201–202
  - example, 204
  - installation, 202
  - methods, 202–203
  - properties, 202, 204

URL tag (XML), 71  
user interface  
  soft keys  
    defining, 131  
user subscriptions, 162  
  per-device, 164

## V

---

valid files (XML), 125  
validating  
  XML schema, 127  
Validator, 215  
  installing, 214  
VAT (Voice Anomaly Tracking) service, 134  
  designing, 134, 136  
  source code, example, 137, 139–141  
VAT-Goodbye.asp page, 136, 141  
VAT-Track.asp page, 136  
VAT-Welcome.asp page, 134  
viewing  
  XML schema, supported version, 132–133  
Voice Anomaly Tracking  
  See VAT

## W

---

W3C (World Wide Web Consortium)  
  description of XML, 111  
  Web site, 128  
Web browsers  
  XML-capable, 117  
Web client/server (Cisco IP Phone)  
  HTTP, 97  
    requests, 97  
    responses, 98  
Web developers  
  transitioning to IP Phone services developer, 38  
Web programming  
  languages, 38–39  
    compiled, 39  
    hybrid, 40  
    scripting, 40

  sample application, 45–47  
Web servers  
  client devices  
    identifying, 61  
  client functionality  
    authentication, 65  
  HTTP, 106  
    accessing device information, 107  
    push, 106–107  
  HTTP client, 59  
  Push/Pull operations, 61  
  server functionality, 59  
    authentication, 65  
    creating screen captures, 60  
    gathering device information, 60  
    HTTP Post, 60  
  state management, 104  
  stream control, 62–63  
  types of, 37–38  
  URIs, 62  
web servers  
  plain text error messages, 132  
Web sites  
  cookiers, 103  
  HotDispatch, 22  
  XML, 128  
well-formed files, 124  
Width property, 197  
Windows  
  registry  
    CM-SIM configuration information, 231  
Windows 2000  
  TFTP  
    command-line version, 232

## X

---

XML, 43, 125  
  attributes, 45, 114–115  
  browsers, 117  
  capabilities, 33  
  comments, 123  
  configuration files, 220  
  content translation engine, 57

- content translation engine (Cisco CTE 1400),
  - 57
- debugging, 127
- DTD, 45
- elements, 115
- escape sequences, 121–122
  - mandatory, 89
- history of, 41–42
- importance of, 111
- objects, 44, 48, 72, 116
  - adding soft keys, 70
  - CiscoIPPhoneDirectory, 78–80
  - CiscoIPPhoneError, 88
  - CiscoIPPhoneExecute, 87–88
  - CiscoIPPhoneGraphicMenu, 83–85
  - CiscoIPPhoneIconMenu, 85–87
  - CiscoIPPhoneImage, 80–81, 83
  - CiscoIPPhoneInput, 76–78
  - CiscoIPPhoneMenu, 73–74
  - CiscoIPPhoneResponse, 88
  - CiscoIPPhoneText, 74–76
  - quick reference guide, 89, 91, 93–94
- prolog statement, 120
- schema, 124
  - DTD, 125
  - validating, 127
- SDK training and support, 50–51
- structured documents, 112–113
- suitability for IP Phone services, 43
- tags, 44, 114
  - Key, 71–72
  - SoftKeyItem tag, 71
  - URL, 71
- tools, 45
- valid files, 125
- Web sites, 128
- well-formed files, 124
- XML configuration files
  - loadinformation element, 221
- XML schema, 125
  - supported version, displaying, 132–133
- XMLSpy
  - Web site, 129
- XOR (exXclusive OR), 173

## Z

---

- zoom in/out image capability, 178, 181–188