



Symbols & Numerics

? (question mark), Catalyst 3550 help system, 82
 10BASE-T Ethernet, NLP, 26
 802.1Q trunking, 18

A

AAL (ATM Adoption Layer) types, 293
 access-list rate-limit command, 449–451
 active flows, 399
 Active state (FSM), 559–560
 as symptom of error condition, 639, 642–645
 addressing, IP multicast, 228
 administratively scoped addresses, 230–231
 globally scoped addresses, 229
 GLOP addresses, 230
 Layer 2 multicast addresses, 231–233
 local-link addresses, 229
 source-specific addresses, 230
 Adj-RIB-In table, 516
 Adj-RIB-Out table (BGP), 516
 administrative distance
 BGP backdoors, 815–818
 effect on BGP routing, 815
 administratively scoped addresses, 230–231
 Admission Control Module (RSVP), 337
 advanced features on Catalyst 3550 switches, 86
 BackboneFast, 91
 MST, configuring, 101, 104–111
 PortFast Spanning Tree, configuring, 87–88
 Root guard, configuring, 92–94
 RSTP, configuring, 95–99
 UplinkFast, configuring, 89–90
 VLAN maps, configuring, 111–114
 VLAN protected ports, configuring, 114–115
 advertising local networks to BGP peers, 680
 connected networks, 682–684
 IGP routes, 687–689
 static routes, 685–687
 aggregate-port learners, 25
 aggregating BGP routes, 732–737
 conditional route advertisements, 742–745
 route suppression, 738–741
 AGGREGATOR attribute (BGP), 581
 alias command, customizing Cisco IOS
 Software, 601
 anycast RP, 244–246
 applications, minimum requirements for operation,
 276–279
 applying
 IP RTP priority to interfaces, 452–453
 policies
 to CBWFQ class maps, 460–462
 to interfaces, 463
 policy-based routing to incoming traffic,
 182–192
 PQ to interfaces, 416–424
 route maps during redistribution, 149
 traffic shaping to Layer 2 technologies, 441
 arguments
 of fair-queue command, 403
 of priority-list command, 409–413
 of queue-list command, 427–431
 AS_PATH attribute (BGP), 567, 570
 affecting route selection, 760–763
 route filtering, 764–771
 AS numbers, 514
 assessing router capacity for BGP, 598
 CPU, 598
 memory, 599–601
 ATM (Asynchronous Transfer Mode)
 AAL types, 293
 CIR, 292
 DLCIs, 292

multiservice traffic support, 291
 QoS

- CoS, 304
- versus Frame Relay, 303–305

 subinterfaces, configuring, 294
 UBR circuits, configuring, 307–308
 VBR-nrt circuits, configuring, 305–307

- versus Frame Relay, 290–308

 ATOMIC_AGGREGATE attribute (BGP), 579
 attributes (BGP), 515

- AGGREGATOR, 581
- AS_PATH, 567, 570
 - affecting route selection, 760–763
 - route filtering, 764–771
- ATOMIC_AGGREGATE, 579
- CLUSTER_LIST, 586
- COMMUNITY, 167, 170, 581–583
 - community lists, 789–794
 - removing, 170
 - route filtering, 787–789
 - well-known values, 785–787

 configuring, 174–175
 LOCAL_PREF, 577–578

- setting, 173
- specifying network exit points, 780–783

 MED, 576

- best path selection, 776–780

 NEXT_HOP, 572–573

- modifying on I-BGP peers, 664–671
- path manipulation, 772–776

 ORIGIN, 566

- affecting route selection, 755–760
- setting, 174

 ORIGINATOR_ID, 586
 WEIGHT, 578

- manipulating path selection, 783–785

 authentication, BGP peers, 707–708
 autonegotiation, 26–28
 autonomous system path

autonomous systems, 515. *See also* confederations
 BGP interaction with IGP, 677–679
 Auto-RP, 244

B

BackboneFast, configuring on Catalyst 3550
 switches, 91
 backdoors (BGP), 815–818
 bandwidth allocation of CQ queues, 435–440
 BAs (behavior aggregates), 371
 Bc (committed burst rate), 440
 Bc (sustained burst rate), 441
 Be (excess burst rate), 441
 BECN (Backward Explicit Congestion
 Notification), 293
 benefits of policy-based routing, 181
 best effort versus guaranteed QoS, 273
 best path selection with MED attribute, 776–780
 BGP (Border Gateway Protocol)

- administrative distance
 - backdoors, 815–818
 - effect on routing, 815
- advertising local networks to peers, 680
 - connected networks, 682–684
 - IGP routes, 687–689
 - static routes, 685–687
- AS_PATH attribute
 - affecting route selection, 760–763
 - route filtering, 764–771
- AS numbers, 514
- attributes, 515
 - AGGREGATOR, 581
 - AS_PATH, 567, 570
 - ATOMIC_AGGREGATE, 579
 - CLUSTER_LIST, 586
 - COMMUNITY, 581–583
 - configuring, 174–175

- LOCAL_PREF, 577–578
- MED, 576
- NEXT_HOP, 572–573
- ORIGIN, 566
- ORIGINATOR_ID, 586
- WEIGHT, 578
- autonomous system path, 515
- capabilities advertisement, 538
- confederations, 588–590, 593
- configuring, 646
- dampening, 170
- E-BGP multihop
 - configuring, 673–677
 - peer relationships, 671–672
- filtering routes, 745
 - with distribute lists, 746–748
 - with prefix lists, 748–750
 - with route maps, 750–754
- FSM, 553–555, 639
 - Active state, 559–560
 - as diagnostic tool, 639, 642–645
 - Connect state, 558–559
 - Established state, 563
 - Idle state, 555–558
 - OpenConfirm state, 562–563
 - OpenSent state, 561–562
- I-BGP synchronization, configuring, 646–662
- interaction with IGP, 677–679
- lab exercises, 689–705
- LOCAL_PREF attribute, specifying network exit points, 780–783
- MED attribute, best path selection, 776–780
- messages
 - KEEPALIVE, 550
 - NOTIFICATION, 546–549
 - OPEN, 534–538
 - ROUTE-REFRESH, 551–553
 - UPDATE, 539–545
- multihomed network configuration, 795–814
 - lab exercises, 826–866
 - neighbor relationships, 519
 - authentication, 707–708
 - configuring, 604–621
 - E-BGP, 520–526
 - I-BGP, 526, 530–533
 - troubleshooting, 604, 621–634
 - NEXT_HOP attribute
 - modifying on I-BGP peers, 664–671
 - path manipulation, 772–776
 - ORIGIN attribute, affecting route selection, 755–760
 - peer capabilities, 538
 - peer groups, 593
 - performance tuning, 821–822
 - memory conservation, 823–826
 - route refresh, 821–823
 - prerequisites for configuring, 597–598
 - assessing router capacity, 598–601
 - CPU, 598
 - memory, 599–601
 - reducing design complexity
 - with confederations, 712, 715–726
 - with peer groups, 730–732
 - with private autonomous systems, 727–729
 - with route reflectors, 709–712
 - route aggregation, 732–737
 - conditional route advertisements, 742–745
 - route suppression, 738–741
 - route dampening, 818–821
 - route reflectors, 584–586
 - route selection process, 593–594
 - routing tables, 515–516
 - session types, 513
 - route exchange process, 516, 519
 - set commands, 164–175
 - set as-path, 164–167
 - set comm-list delete, 170
 - set community, 167, 170
 - set dampening command, 171–173

- set local-preference command, 173
 - set origin command, 174
 - set weight command, 174
- speakers, 514
- storing routes, 680
- troubleshooting with messages, 634–636, 638–639
- WEIGHT attribute, manipulating path selection, 783–785
- BGP Open process, 598
- BGP-4. *See* BGP
- bidirectional PIM, 239
- Big Show commands
 - show ip cache policy, 194
 - show ip policy, 194
 - show route-map, 193
- BPDU (bridge protocol data units), 29
- bridge IDs, 29
- broadcast domains, VLANs, 8
 - default settings, 9–10
 - design rules, 8
- broken state (SPT), 32

C

- calculating
 - sequence numbers for WFQ routers, 401–403
 - TC for GTS, 441
- capabilities advertisement (BGP), 538
- CAR (committed access rate)
 - configuring, 446–451
 - marking traffic, 445–446
- Catalyst 3550 switches
 - advanced features, 86–115
 - command modes, 36
 - configuring, 35
 - default VTP settings, 15
 - EtherChannel port groups, 37
 - Ethernet switching, configuring, 38–86
 - help system, 82
 - Layer 3 switching, 10
 - routed ports, 38
 - SVI, 38
 - switch ports, 37
- CBWFQ (Class-Based Weighted Fair Queuing), 454
 - class maps, 455
 - applying policies, 460–462
 - default classes, 463
 - match command values, 456–457, 460
 - class-based shaping, 468–472
 - configuring, 464–466
 - displaying configuration information, 467–468
 - NBAR, 455
 - lab exercises, 500–508
 - queuing voice traffic with LLC, 483–486
 - traffic policing, 472
 - configuring, 473–479
 - two-bucket policies, 472, 480–482
- CCIE exam
 - practice labs, 879–880
 - !!! Boom, 890–900
 - Broken Arrow, 880–890
 - Enchilada II, 912–924
 - Kobayashi Maru, 925–935
 - The Intimidator, 901–912
 - preparing for, 871–879
- CEF (Cisco Express Forwarding), 311–312
 - load balancing, 312
 - verifying configuration, 313–315
- characteristics of route maps, 149
- CIR (committed information rate), 292, 440–441
- Cisco Catalyst 3550 Intelligent Ethernet Switch, 5
 - base models, 7
 - features, 6–7

- Cisco Catalyst 3550 switches
 - advanced features, 86–115
 - command modes, 36
 - configuring, 35
 - default VLAN settings, 9–10
 - default VTP settings, 15
 - EtherChannel port groups, 37
 - Ethernet switching, configuring, 38–86
 - Layer 3 switching, 10
 - routed ports, 38
- SVI, 38
 - switch ports, 37
- Cisco IOS Software
 - customizing with alias command, 601
 - verifying configuration, 274–276
- Cisco WFQ algorithm. *See* WFQ
- class maps, 455
 - applying policies, 460–462
 - default classes, 463
 - match command values, 456–457, 460
- class-based shaping (CBWFQ), 468–472
- client mode (VTP), 12
- clns keyword (match command), 162
- CLUSTER_LIST attribute (BGP), 586
- codepoints, 371
- command modes on Catalyst 3550, 36
- commands, 445
 - access-list rate-limit, 449–451
 - alias, customizing Cisco IOS Software, 601
 - fair-queue, arguments, 403
 - ip rtp priority, 451–452
 - match, 152–153
 - clns keyword, 162
 - example, 153–158
 - matching tags, 159–161
 - metric keyword, 161–162
 - next-hop keyword, 162
 - tag keyword, 157
 - mrinfo, 263
 - mstat, 264
 - output, editing shortcuts, 601–603
 - priority-list, arguments, 409–413
 - queue-list, arguments, 427–431
 - queue-list byte-count, 439
 - rate-limit, 446–449
 - route-map, 151
 - set, 163
 - BGP-specific, 164–175
 - redistribution-specific, 176–180
 - set as-path, 164–167
 - set comm-list delete, 170
 - set community, 167, 170
 - set dampening, 171–173
 - set local-preference, 173
 - set origin, 174
 - set weight, 174
 - show interface, 403
 - show interface serial, displaying interface performance statistics, 279–290
 - show ip bgp, 166, 519, 622–624
 - show ip bgp neighbors, 625–632
 - show ip bgp summary, 632–634
 - show ip cache policy, 194
 - show ip policy, 194
 - show memory dead, 278–279
 - show memory failures alloc, 278
 - show processes cpu, 598
 - show processes memory, 599
 - show processor cpu, 276
 - show queueing priority, 414–416
 - show route-map, 193
 - traceroute, 185–186
 - traffic-shaping group, 442
- communities (BGP), 581

- COMMUNITY attribute (BGP), 581–583
 - community lists, 789–794
 - removing, 170
 - route filtering, 787–789
 - setting, 167, 170
 - well-known values, 785, 787
- community lists, 789–794
- comparing
 - ATM and Frame Relay, 290–308
 - QoS implementation, 303–305
 - switching modes, 315
- compression, 316
 - effect on utilization, 316
 - Predictor algorithm, 318–320
 - stacker algorithm, 316–317
- conditional route advertisements (BGP), 742–745
- confederations (BGP), 588–593
 - reducing BGP network complexity, 712, 715–726
- configuring
 - ATM
 - traffic shaping, 305–307
 - UBR circuits, 307–308
 - VBR-nrt circuits, 305–307
 - BGP, 646
 - as IGP, 678–679
 - attributes, 174–175
 - E-BGP multihop, 673–677
 - I-BGP synchronization, 646–662
 - multihomed networks, 795–814
 - neighbor relationships, 604–621
 - prerequisites, 597–601
 - route dampening, 818–821
 - routing policies with COMMUNITY attribute, 787–794
 - CAR, 446–451
 - Catalyst 3550 switches, 35–36
 - advanced features, 86–115
 - Ethernet switching, 38–86
 - CBWFQ, 464–468
 - CEF, load balancing, 312
 - CQ, 432–434
 - queue bandwidth allocation, 435–440
 - E-BGP connections, 671–672
 - GTS, 442–445
 - policy-based routing, 186–191
 - lab exercises, 207–220
 - ToS bit, 191–192
 - PQ, 409–416
 - route maps, 150
 - lab exercises, 195–205
 - match command, 152–162
 - route-map command, 151
 - set command, 163–180
 - RSVP, 341–342
 - for voice traffic, 349–353
 - traffic policing, 473–479
 - two-bucket policies, 480–482
 - WRED, 376–381
- congestion avoidance
 - WRED, 375–381
 - FRED, 381–383
- congestion notification, Frame Relay, 293
- Connect state (FSM), 558–559
- connected networks, advertising to BGP peers, 682–684
- conserving memory on BGP networks, 823–826
- controlled load services (RSVP), 341
- controlling
 - multicast
 - with fast switching, 253
 - with tunneling, 254
 - traffic with policy-based routing, 182–192
- CoS (class of service) types, 304
- cost to root bridge, 34
- CPU allocation, verifying, 276

- CQ (Custom Queuing), 424–431
 - configuring, 432–434
 - lab exercises, 486–500
 - queue bandwidth allocation, 435–440
- CRC (cyclic redundancy check) computation, 309
- creating static RSVP reservations, 346–348
- customizing Cisco IOS Software with alias command, 601

D

- dampening, 170
 - applying to unstable routes, 171–173
 - BGP routes, 818–821
- DE (discard eligibility) bit, 292
- debug commands, monitoring multicast routing, 262
- default classes (class maps), defining, 463
- default VLAN settings on Catalyst switches, 9–10
- default VTP settings on Catalyst 3550 switches, 15
- defining class map default classes, 463
- dense mode (PIM), 237
- deriving weight values from
 - IP precedence values, 399
- design rules of VLANs, 8
- designated ports, 34
- devices, PAgP, 25
- diagnosing BGP problems
 - with FSM, 639–645
 - with messages, 634–639
- DiffServ (Differentiated Services), 366
 - classes of service, 367–368
 - DSCP, marking traffic, 371–375
 - lab exercises, 383–393
 - ToS, IP Precedence, 368–370
 - WRED, 375–376
 - configuring, 376–381
 - FRED, 381–383
- DISL (Dynamic ISL), 19
- displaying
 - BGP processes, 598
 - CBWFQ configuration information, 467–468
 - interface statistics, show interface serial command, 279–290
 - Layer 2/3 mapping information on VC, 299
 - queuing configurations on interfaces, 403–406
 - router memory statistics, 278–279
- distinct reservations, 336
- distribute lists, filtering BGP routes, 746–748
- distributed switching, 310
- distribution trees, 233
 - multicast forwarding, 236
 - reverse path forwarding, 236
 - shared trees, 234–235
 - source trees, 233
- DLCIs (data-link connection identifiers), 292
- DSCP (Differentiated Service Code Point)
 - codepoints, 371
 - marking traffic, 371–375
- DTP (Dynamic Trunk Protocol), 19
 - CatOS configurations, 19–21
- DVMRP (Distance Vector Multicast Routing Protocol), 257–258

E

- E-BGP, 514
 - administrative distance
 - backdoors, 815–818
 - effect on routing, 815
 - multihop, configuring, 673–677
 - neighbor relationships, 520–526
 - peer relationships, 671–672
- editing command output, shortcuts, 601–603
- EF (expedited forwarding) PHB, 372
- enabling WFQ, 403

enforcing

- traffic policies with traffic shaping, 440–441
 - GTS, 441–445
- traffic rates with traffic policing, 472–482
 - two-bucket policies, 472

Established state (FSM), 563

EtherChannel, 22

Layer 3, 26

PAGP, 23–25

port groups on Catalyst 3550 switches, 37

Ethernet

- advanced features, configuring on Catalyst 3550 switches, 86–115
- autonegotiation, 26–28
- configuring on Catalyst 3550 switches, 38–86
- full-duplex, 26
- half-duplex, 26

evaluating router performance, 274

interfaces, 279–290

network application requirements, 276–279

verifying Cisco IOS Software configuration, 274–276

evolutionary protocols, 5

exam, preparing for, 871–879

examples of route map logic, 147–148

explicit sender selection lists (RSVP), 337

F

fair-queue command, arguments, 403

fast switching, 309

controlling multicast, 253

FECN (Forward Explicit Congestion Notification), 293

FIFO Queuing, 397

filtering BGP routes, 745

- with AS_PATH attribute, 764–771
- with COMMUNITY attribute, 787–789
 - community lists, 789–794
- with distribute lists, 746–748
- with prefix lists, 748–750
- with route maps, 750–754

flapping routes, dampening, 818–821

flow descriptor, 336

flows, 399–400

Floyd, Sally, 375

FLP (fast link pulse), 26

Forward delay timer (STP), 35

forwarding state (STP), 34

Frame Relay

BECN, 293

DE bit, 292

FECN, 293

multicast over Frame Relay, 242

versus ATM, 290–308

QoS implementations, 303–305

Zero CIR service, 292

frames, compression, 316

effect on utilization, 316

Predictor algorithm, 318–320

stacker algorithm, 316–317

FRED (Flow-Based RED), 381–383

FSM (finite-state machine), 553–555, 639

Active state, 559–560

as diagnostic tool, 639, 642–645

Connect state, 558–559

Established state, 563

Idle state, 555–558

OpenConfirm state, 562–563

OpenSent state, 561–562

full-duplex Ethernet, 26

G

- global synchronization, 375
- globally scoped addresses, 229
- GLOP addresses, 230
- GTS (generic traffic shaping), 441
 - configuring, 442–445
 - Tc, calculating, 441
- guaranteed bit rate services (RSVP), 341

H

- half-duplex Ethernet, 26
- Hello timer (STP), 35
- High priority queue (PQ), 407

I

- I-BGP, 514
 - modifying NEXT_HOP attribute, 664–671
 - neighbor relationships, 526, 530–533
 - route reflectors, 584–586
 - synchronizing with BGP routes, 646–662
- Idle state (FSM), 555–556, 558
- IEEE 802.1d. *See* STP (Spanning Tree Protocol)
- IEEE 802.1Q trunking, 18
- IEEE 802.1S (Multiple Spanning Tree), 101–107
- IGPs (interior gateway protocols)
 - advertising routes to BGP peers, 687–689
 - BGP interaction, 677–679
 - set commands, 176–180
- ill-behaved routes, 170
 - dampening, 171–173
- inactive flows, 399

- incoming traffic, policy-based routing, 182–192
- interfaces
 - CIR, 440
 - performance, verifying, 279–290
 - PQ, applying, 416–424
 - queuing configurations, displaying, 403–406
 - service policies, applying, 463
- IntServ (Integrated Services), 335
 - lab exercises, 383–393
 - RSVP, 336
 - Admission Control Module, 337
 - configuring, 341–342
 - configuring RSVP paths, 337–338
 - controlled load services, 341
 - distinct reservations, 336
 - explicit sender selection lists, 337
 - flow descriptor, 336
 - guaranteed bit rate services, 341
 - lab exercises, 355–366
 - messages, 338–341
 - Policy Control Module, 337
 - shared reservations, 336
 - simulating messages, 343–346
 - static reservations, creating, 346–348
 - troubleshooting, 354–355
 - voice traffic configuration, 349–353
 - wildcard lists, 337
- IP Precedence values
 - setting, 368–370
 - weight values, 399
- IP RTP priority, 451–452
 - applying to interfaces, 452–453
- ip rtp priority command, 451–452
- ISL (Inter-Switch Link), 17

J-K

joining multicast groups, 249–250

KEEPALIVE message (BGP), 550

keywords for match command, 152

 clns, 162

 metric, 161–162

 next-hop, 162

L

lab exercises

 applying PQ, 416–424

 ATM and QoS, 320–333

 BGP multihoming, 826–866

 BGP routing, 689–705

 CBWFQ with NBAR, 500–508

 configuring policy-based routing, 207–220

 configuring route maps, 195–205

 CQ, 486–500

 DiffServ, 383–393

 IntServ, 383–393

 multicast, 239–241

 RSVP, 355–366

Layer 2 multicast addresses, 231–233

Layer 2 technologies, traffic shaping, 441

Layer 2/3 mapping information, displaying, 299

Layer 3 EtherChannel, 26

Layer 3 switching, 10

learning state (SPT), 34

Lemple-Ziv standard algorithm, 316

limitations of QoS, 273

listening state (SPT), 32

LLC (Low Latency Queuing)

 priority classes, 482

 with CBWFQ for voice traffic, 483–486

load balancing with CEF, 312

local networks, advertising to BGP peers, 680

 connected networks, 682–684

 IGP routes, 687–689

 static routes, 685–687

LOCAL_PREF attribute (BGP), 577–578

 setting, 173

 specifying network exit points, 780–783

local-link addresses, 229

Loc-RIB table (BGP), 516

loop avoidance with STP, 28

 BPDUs, 29

 broken state, 32

 forwarding state, 34

 learning state, 34

 listening state, 32

 path cost, 30–31

 states, 32

 timers, 35

Low priority queue (PQ), 407

M

manipulating BGP routes

 with NEXT_HOP attribute, 772–776

 with WEIGHT attribute (BGP), 783–785

map tags, 151

marking traffic

 with CAR, 445–451

 DSCP, 371–375

match command, 152–153

 clns keyword, 162

 example, 153–158

 keywords, 152

 matching tags, 159–161

 metric keyword, 161–162

 next-hop keyword, 162

 tag keyword, 157

- match statements (route maps), 148
- Max age timer (STP), 35
- MBS (maximum burst size), ATM traffic shaping, 305–307
- MED attribute (BGP), 576
 - best path selection, 776–780
- Medium priority queue (PQ), 407
- member autonomous systems, reducing BGP network complexity, 712–726
- memory
 - conserving on BGP networks, 823–826
 - router statistics, displaying, 278–279
 - verifying router configuration, 274–276
- messages
 - BGP
 - as diagnostic tool, 634–639
 - KEEPALIVE, 550
 - NOTIFICATION, 546–549
 - OPEN, 534–538
 - ROUTE-REFRESH, 551–553
 - UPDATE, 539–545
 - RSVP, 338–341
 - simulating, 343–346
 - VTP, 13–14
- metric keyword (match command), 161–162
- min-max fair-share algorithm, 398
- monitoring multicast routing, commands, 262
- mrinfo command, 263
- MRM (Multicast Routing Manager), 267–268
- MSDP (Multicast Source Discovery Protocol), 245
- MST (Multiple Spanning Tree), 101–107
 - configuring on Catalyst 3550 switches, 101, 104–111
- mstat command, 264
- multicast, 225–226
 - addressing, 228
 - administratively scoped addresses, 230–231
 - globally scoped addresses, 229
 - GLOP addresses, 230
 - Layer 2 multicast addresses, 231–233
 - local-link addresses, 229
 - source-specific addresses, 230
 - anycast RP, 244–246
 - controlling
 - with fast switching, 253
 - with tunneling, 254
 - distribution trees, 233
 - multicast forwarding, 236
 - reverse path forwarding, 236
 - shared trees, 234–235
 - source trees, 233
 - DVMRP, 257–258
 - monitoring, show commands, 262
 - MRM, 267–268
 - over Frame Relay, 242
 - PIM, 237
 - Auto-RP, 244
 - bidirectional PIM, 239
 - dense mode, 237
 - sparse mode, 237–239
 - PIMv2, 258–259
 - stub networks, 254
 - versus unicast, 226
- multicast forwarding, 236
- multicast groups, joining, 249–250
- multicast TTL, 243
- multihoming BGP networks, 795–814
 - lab exercises, 826–866
- multiservice traffic, 291

N

- naming route maps, 151
- NBAR (Network-Based Application Recognition), 454
 - with CBWFQ, 455
 - lab exercises, 500–508
- neighbor relationships (BGP), 519
 - configuring, 604–621
 - E-BGP, 520–526
 - FSM, 553–555
 - Active state, 559–560
 - Connect state, 558–559
 - Established state, 563
 - Idle state, 555–558
 - OpenConfirm state, 562–563
 - OpenSent state, 561–562
 - I-BGP, 526, 530–533
 - peer authentication, 707–708
 - troubleshooting, 604, 621
 - with show ip bgp command, 622–634
- NetFlow switching, 310–311
- network applications, verifying minimum requirements, 276–279
- network design (BGP), reducing complexity of, 709–741
- NEXT_HOP attribute (BGP), 572–573
 - modifying on I-BGP peers, 664–671
 - path manipulation, 772–776
- next-hop keyword (match command), 162
- NLP (normal link pulse), 26
- NLRI (network layer reachability information), 539
- nondesignated ports, 34
- Normal priority queue (PQ), 407
- NOTIFICATION message (BGP), 546–549

O

- OPEN message (BGP), 534–538
- OpenConfirm state (FSM), 562–563
- OpenSent state (FSM), 561–562
- optimum switching, 310
- ORIGIN attribute (BGP), 566
 - affecting route selection, 755–760
 - setting, 174
- ORIGINATOR_ID attribute (BGP), 586

P

- packet marking, 371–375
- packets, multicast, 226
- PAgP (Port Aggregation Protocol), 23–25
 - physical learners, 25
 - verifying status, 62
- path cost (STP), 30–31
- path selection, manipulating
 - with AS_PATH attribute, 760–763
 - with ORIGIN attribute, 755–760
- path-vector protocols, BGP. *See* BGP
- PCR (peak cell rate), ATM traffic shaping, 305–307
- peer capabilities, 538
- peer groups, 593
 - reducing BGP network complexity, 730–732
- peers, 566
- performance
 - evaluating, 274–276
 - network application requirements, evaluating, 276–279
 - of router interfaces, evaluating, 279–290
 - tuning BGP networks, 821–822
 - memory conservation, 823–826
 - route refresh, 821–823

Perlman, Radia, 28
 PHB (per-hop behavior), 371–372
 PIM (Protocol Independent Multicast), 237

- Auto-RP, 244
- bidirectional PIM, 239
- dense mode, 237
- sparse mode, 237–239

 PIMv2, 258–259
 Policy Control Module (RSVP), 337
 policy-based routing, 182–186

- benefits of, 181
- configuring, 186–191
 - lab exercises, 207–220
- ToS bit, setting, 191–192

 ports, changing duplex settings, 52
 PortFast Spanning Tree, configuring on Catalyst 3550 switches, 87–88
 PQ (Priority Queuing), 406

- applying to interfaces, 416–424
- configuring, 409–416

 practice labs, 879–880

- !!! Boom, 890–900
- Broken Arrow, 880–890
- Enchilada II, 912–924
- Kobayashi Maru, 925–935
- The Intimidator, 901–912

 Predictor compression algorithm, 318–320
 prefix lists, filtering BGP routes, 748–750
 preparing for CCIE exam, 871–879
 prerequisites for BGP configuration, 597–598

- assessing router capacity, 598–601

 prioritizing RTP traffic, 451–453
 priority classes, 482
 Priority-Based Weighted Fair Queuing. *See* LLC (Low Latency Queuing)
 priority-list command, arguments, 409–416
 private autonomous systems, reducing BGP network complexity, 727–729

process CPU allocation, verifying, 276
 process switching, 309
 processes (BGP), displaying, 598
 protected ports, configuring on Catalyst 3550 switches, 114–115
 PVCs (permanent virtual circuits), creating on Cisco routers, 294–298

Q

QoS (quality of service)

- comparing ATM and Frame Relay implementations, 303–305
- DiffServ, 366
 - classes of service, 367–368
 - DSCP, 371–375
 - ToS values, 368–370
 - WRED, 375–383
- IntServ, 335
 - Admission Control Module, 337
 - configuring RSVP paths, 337–338
 - controlled load services, 341
 - guaranteed bit rate services, 341
 - Policy Control Module, 337
 - RSVP, 336–355
- limitations of, 273
- traffic shaping, 440
 - applying, 441
 - GTS, 441–445

 queue-list byte-count command, 439
 queue-list command, arguments, 427–428, 431
 queuing

- CBWFQ, 454
 - class-based shaping, 468–472
 - class maps, 455–457, 460–463
 - configuring, 464–466
 - displaying configuration information, 467–468

- lab exercises, 500–508
- NBAR, 455
- traffic policing, 472–482
- CQ, 424–431
 - configuring, 432–434
 - lab exercises, 486–500
 - queue bandwidth allocation, 435–440
- FIFO, 397
- LLC
 - priority classes, 482
 - with CBWFQ for voice traffic, 483–486
- PQ, 406
 - applying to interfaces, 416–424
 - configuring, 409–416
- token-bucket scheme, 445
- WFQ, 398–399, 406
 - enabling, 403
 - flows, 399–400
 - sequence numbers, 399–400
 - sequence numbers, calculating, 401–403

R

- Radix Trie, 598
- rate-limit command, 446–449
- redistribution, set commands, 176–180
- reducing complexity of BGP networks
 - with confederations, 712–726
 - with peer groups, 730–732
 - with private autonomous systems, 727–729
 - with route aggregation, 732–741
 - with route reflectors, 709–712
- removing community attribute (BGP), 170
- reverse path forwarding, 236
- revolutionary protocols, 5
- RIBs (Routing Information Bases), 516
- Root guard, configuring on Catalyst 3550 switches, 92–94
- route aggregation
 - conditional route advertisements, 742–745
 - reducing BGP network complexity, 732–741
- route dampening, 818–821
- route maps. *See also* policy-based routing
 - characteristics of, 149
 - configuring, 150
 - lab exercises, 195–205
 - match command, 152–162
 - route-map command, 151
 - set command, 163–180
 - filtering BGP routes, 750–754
 - logic, 147
 - match statements, 148
 - naming, 151
- route reflectors, 584–586
 - reducing BGP network complexity, 709–712
- route refresh capability (BGP), 821–823
- route selection process (BGP), 593–594
 - manipulating with AS_PATH attribute, 760–763
 - manipulating with ORIGIN attribute, 755–760
- route tape, 147
- routed ports, 80
 - on Catalyst 3550 switches, 38
- route-map command, 151
- ROUTE-REFRESH message (BGP), 551–553
- routers
 - memory, verifying configuration, 274–276
 - performance, evaluating, 274–290
- routing tables, BGP, 515–516
- RP (rendezvous point), 234
 - anycast RP, 244–246
- RSTP (Rapid Spanning Tree Protocol), 95
 - configuring on Catalyst 3550 switches, 95–99

RSVP (Resource Reservation Protocol), 336

- Admission Control Module, 337
- configuring, 341–342
- controlled load services, 341
- distinct reservations, 336
- explicit sender selection lists, 337
- flow descriptor, 336
- guaranteed bit rate services, 341
- lab exercises, 355–366
- messages, 338–341
 - simulating, 343–346
- Policy Control Module, 337
- RSVP paths, 337–338
- shared reservations, 336
- static reservations, creating, 346–348
- troubleshooting, 354–355
- voice traffic configuration, 349–353
- wildcard lists, 337

RTP traffic, prioritizing, 451–453

S

SCR (sustained cell rate), ATM traffic shaping, 305–307

security, BGP peer authentication, 707–708

sequence numbers, applying to route maps, 152

sequence numbers (WFQ), 399–400

- calculating, 401–403

server mode (VTP), 12

service policies, applying to interfaces, 463

sessions, BGP, 513

- route exchange process, 516, 519

set as-path command, 164–167

set command, 163

- BGP-specific, 164–175
- redistribution-specific, 176–180

- set comm-list delete command, 170
- set community command, 167, 170
- set dampening command, 171–173
- set local-preference command, 173
- set origin command, 174
- set weight command, 174
- shared reservations, 336
- shared trees, 234–235
- shortcuts for editing Cisco IOS Software command
 - output, 601–603
- show commands, monitoring multicast routing, 262
- show interface command, 403
- show interface serial command, displaying interface statistics, 279–290
- show ip bgp command, 166, 519, 622–624
- show ip bgp neighbors command, 625–632
- show ip bgp summary command, 632–634
- show ip cache policy command, 194
- show ip policy command, 194
- show memory dead command, 278–279
- show memory failures alloc command, 278
- show processes cpu command, 598
- show processes memory command, 599
- show processor cpu command, verifying CPU allocation, 276
- show queueing priority command, 414–416
- show route-map command, 193
- show traffic-shaping, 445
- show traffic-shaping command, 445
- simulating RSVP messages, 343–346
- software compression techniques, 316
 - affect on utilization, 316
 - Predictor algorithm, 318–320
 - stacker algorithm, 316–317
- source trees, 233
- source-specific addresses, 230
- sparse mode (PIM), 237–239

- speakers, 514
 - neighbor relationships, 519
 - E-BGP, 520–526
 - I-BGP, 526, 530–533
 - route reflectors, 584–586
- specifying
 - best path with MED attribute (BGP), 776–780
 - network exit points with LOCAL_PREF attribute (BGP), 780–783
- stacker compression algorithm, 316–317
- states of STP, 32
 - broken state, 32
 - forwarding state, 34
 - learning state, 34
 - listening state, 32
- static routes, advertising to BGP peers, 685–687
- static RSVP reservations, creating, 346–348
- storage of BGP routes, 680
- STP (Spanning Tree Protocol), 28
 - BPDU, 29
 - broken state, 32
 - forwarding state, 34
 - learning state, 34
 - listening state, 32
 - path cost, 30–31
 - port states versus RSTP port states, 99
 - states, 32
 - timers, 35
- stub networks (multicast), 254
- study labs, ATM and QoS, 320–333
- subinterfaces (ATM), configuring, 294
- summary, 739
- suppressing BGP advertisements, 738–741
- SVI (Switch Virtual Interface), 38
- switch ports on Catalyst 3550 switches, 37

- switching, 308
 - CEF, 311–312
 - load balancing, 312
 - verifying configuration, 313–315
 - distributed switching, 310
 - fast switching, 309
 - NetFlow switching, 310–311
 - optimum switching, 310
 - process switching, 309
- synchronizing BGP routes with I-BGP routing table, 646–662
- syntax for route maps, 150
 - match command, 152–162
 - route-map command, 151
 - set command, 163–180

T

- tag keyword (match command), 157–161
- Tc (time interval), 441
- timers (STP), 35
- Token Ring, VTP version II, 14
- token-bucket scheme, 440, 445
- ToS bit values, 367–368
 - IP Precedence, configuring, 368–370
 - setting on policy routes, 191–192
- traceroute command, 185–186
- traffic
 - ATM, CoS, 304
 - congestion avoidance, WRED, 375–383
 - incoming, policy-based routing, 182–192
 - load balancing with CEF, 312
 - marking, 445
 - policy classification, 445–446

- queuing
 - CBWFQ, 454–482
 - CQ, 424–440
 - FIFO, 397
 - LLC, 482–486
 - PQ, 406–424
 - WFQ, 398–406
- voice, prioritizing, 451–453
- traffic policing, 472
 - configuring, 473–479
 - two-bucket policies, 472, 480–482
- traffic shaping, 440
 - applying, 441
 - class-based shaping, 468–472
 - configuring on ATM, 305–307
 - GTS, 441
 - configuring, 442–445
 - Tc, calculating, 441
- traffic-shaping group command, 442
- transparent mode (VTP), 12
- troubleshooting
 - BGP
 - Idle/Active state scenario, 639–645
 - neighbor relationships, 604, 621–634
 - with messages, 634–639
 - multicast routing, 263–266
 - RSVP, 354–355
- trunking
 - 802.1Q, 18
 - DTP, CatOS configurations, 19–21
 - EtherChannel, 22
 - Layer 3, 26
 - PAgP, 23–25
 - ISL, 17
 - VTP, 12
 - messages, 13–14
 - modes of operation, 12–13
 - pruning, 15

- tuning BGP performance, 821–822
 - memory conservation, 823–826
 - route refresh, 821–823
- two-bucket traffic policies, 472
 - example, 479

U

- UBR circuits, configuring, 307–308
- unstable routes, dampening, 171–173, 818–821
- UPDATE message (BGP), 539–545
- UplinkFast, configuring on Catalyst 3550 switches, 89–90
- utilization of processors, verifying, 277

V

- VCs (virtual circuits)
 - displaying Layer 2/Layer 3 mapping information, 299
 - VBR-nrt, ATM configuration, 305–307
- verifying
 - CEF configuration, 313–315
 - Cisco IOS Software configuration, 274–276
 - PAgP status, 62
 - policy-based routing with traceroute command, 185
 - process CPU allocation, 276
 - router interface performance, 279–290
- VLAN maps, configuring on Catalyst 3550 switches, 111–114
- VLANs, 8
 - default Catalyst switch settings, 9–10
 - design rules, 8
 - Layer 3 switching, 10

- protected ports, configuring on Catalyst 3550 switches, 114–115
- trunking
 - 802.1Q, 18
 - EtherChannel, 22–26
 - ISL, 17
- VTP, 12
 - messages, 13–14
 - modes of operation, 12–13
 - pruning, 15
- voice traffic
 - prioritizing, 451–453
 - queuing with LLC, 483–486
 - RSVP configuration, 349–353
- VTP (VLAN Trunking Protocol), 12
 - default settings on Catalyst switches, 15
 - messages, 13–14
 - modes of operation, 12–13
 - pruning, 15
- weight values, deriving from IP precedence values, 399
- well-behaved routes, 170
- well-known COMMUNITY attribute values, 785–787
- WFQ (Weighted Fair Queuing), 398–399, 406
 - enabling, 403
 - fair-queue command, arguments, 403
 - flows, 399–400
 - sequence numbers, 399–403
- wildcard lists (RSVP), 337
- WRED (Weighed Random Early Detection), 375–376
 - configuring, 376–381
 - FRED, 381–383
- Zero CIR service, 292

W-Z

WANs

ATM

- AAL types, 293
 - CIR, 292
 - CoS types, 304
 - DLCIs, 292
 - multiservice traffic support, 291
 - subinterface, configuring, 294
 - versus Frame Relay, 290–308
- Frame Relay, DE bit, 292
- WEIGHT attribute (BGP), 578
 - manipulating path selection, 783–785
 - setting, 174