



## Numerics

---

- 1 GE. *See* GE
- 1+1 protection, 164
- 10 GE (10 Gigabit Ethernet), 211, 215
  - physical layer, 215
  - XAUI, 217
  - XGMII, 215
- 2R (reshape and reamplify) regeneration, 111
- 300 km OC-192 metro core ring,
  - VPItransmissionMakerWDM demo, 319
- 300 km OC-48 metro core ring,
  - VPItransmissionMakerWDM demo, 319
- 3R (reshape, retime, and reamplify) regeneration, 265
- 40 Gbps systems
  - data communication, 245
  - FEC, 253
  - RZ modulation, 254–255

## A

---

- absolute quality of optical signals, 66
- absorption, 21
- acceptance angle, 9–11
- access methods, HORNET implementation of
  - CSMA/CD, 258
- access network topologies, 149
  - access rings, designing, 168
  - hubbed topology, 150
  - node architecture, 168–170
  - protection algorithms, 151
  - thin film filter-based architecture, 150
- access points, HORNET, 257
- active devices, 4
  - FOTP, 272
- add/drop architecture, SONET/SDH, 228
- ADNs (add/drop nodes), 228
- Ampere's Law, 16–17
- amplifiers. *See also* repeaters
  - bandwidth, 89
  - Brillouin gain, 29
  - calculating maximum transmission distance, 110
  - characteristics, testing, 272
  - EDFAs, 91–94, 313
    - testing, 290–292
  - effect on WDM network design, 181
  - fiber, 111

- millisecond power transient analysis, 313
- OSNR, 112
- Raman, 94–95
  - DRAs, 97
  - hybrid, 98
  - improving OSNR, 123
- spacing and launch power,
  - VPItransmissionMakerWDM demo, 321
- testing, ISS method, 290
- angle of incidence
  - effect on polarization, 13
  - effect on refraction, 7–8
- AOTFs (acousto-optical tunable filters), 72–73
- APDs (Avalanche photodiodes), 55–57
- architectures
  - long-haul system design, 177
  - metro core design, 170–176
    - BER, 175–176
    - gain-tilt, 176
    - power budget, 175
    - TFF, 174
    - wavelength conversion, 171
- arrayed waveguides, 3
- ASE (amplified spontaneous emission), 90, 111
- assessing power penalty for excess dispersion, 114
- attenuation, 21
  - calculating maximum transmission distance, 110
  - estimating system losses, 124–126
  - from bending losses, 23
  - necessity for signal propagation, 109–110
- attenuation coefficient, 23
- attenuators, 274
- autocovariance function, 262
- avalanche breakdown, 56
- Avalanche effect, 55
- Avalanche multiplication, 55
- AWG devices, 73

## B

---

- back-to-back receiver sensitivity,
  - VPItransmissionMakerWDM demo, 318
- backward reservation protocols, RSVP, 256
- bandgap energy, 44
- bandwidth
  - amplifier bandwidth, 89
  - SRP-fa, 236–237
  - techniques for increasing, 36–37
- beat length, 25

bending losses, 23  
 BER (bit error rate), 58–67  
   dispersion, effect on, 24  
   error function, 63–67  
   Gaussian distribution, 61–63  
   metro core networks, 175–176  
   relationship to Q-factor, 117  
   requirements for optical network design, 113  
 BERTs (bit error rate testers), 297  
 Bessel's Function, 20  
 birefringence, 11–12, 25, 131  
 blocking probability, 188  
   calculating, 202–204  
   minimizing, 198  
 BPSK (binary phase shift keying) modulation, 5  
 Bragg's condition, 45  
 Bragg's diffraction, 15  
 Bragg's wavelength, 72  
 branches, 144  
 breakthroughs in fiber-optic network layer  
   technology, 187  
 bridges, PSR, 252  
 Brillouin gain, 29  
 broadband light sources, 276  
 brown-field network design, 168  
 bubble switches, 82  
 burst switching, 244–245  
   attributes, 246  
   delayed reservation, 247  
   JET, 247–248  
   LOBS, 249  
   TAG, 246–247  
 burst-mode receivers, 259–260  
 bursts, Self-Similarity, 260–262  
   heavy-tailed distribution, 264–265  
   long-range dependence, 263  
   second-order, 262–263

## C

C (conventional) band, 30, 153  
 calculating  
   blocking probability of optical networks,  
     202–204  
   chirp-induced power penalties, 129  
   group velocity, 13  
   magnetic field strength, 16–17  
   maximum transmission distance, 110  
   OSNR, 120–122  
   Q-factor, 119–120

capacity planning  
   calculating maximum throughput, 189  
   wavelength assignment, mathematical formula,  
     190–192  
 carrier sense multiple access with collision  
   avoidance, 210  
 case studies, 318  
 cavities, 70  
   Fabry Perot cavity filters, 70–71  
 CDM (code division multiplexing), 36  
 channels, 5  
   add-drop capabilities, 34  
   dropping, 34  
   lightpaths, 35  
   subcarrier multiplexing, 37  
   tilt-limited systems, 132  
   uneven spacing in long-haul networks, 177  
 characteristics of fiber, tests and measurements  
   requirements, 269  
 chirped pulses, 49, 129  
   extinction ratio, 179  
   prechirping, 101  
 chromatic dispersion, 14, 24, 112  
   effect on maximum transmission distance, 116  
 circular polarization, 12  
 circulators, 69  
 cladding, 9  
 coherent interference, 312  
 collector networks, 153  
 collision detection at optical layer, 211  
 commercial simulation tools, 303–304  
 compensation techniques for dispersion, 104  
   GVD compensation with FGBs, 102–103  
   high dispersion fibers, 101–102  
   postcompensation, 100–101  
   precompensation, 101  
 composite WDM signals, 32, 36  
 conduction state, 44  
 constraints  
   on lightpath-link matrix formula, 191–192  
   on throughput, 189  
 contention resolution schemes, 244  
   deflection routing, 244  
   SDLs, 252  
 control packets, SRP, 234  
 CORD (contention resolution using delay), 244  
 core section, 9  
   birefringence, 12  
   modes, 15  
   pulse propagation, cutoff condition, 19–20  
 couplers, 68  
   directional, 81

critical angle, 8  
 cross phase modulation, 115  
 cross-connects, 256  
 CSMA/CA (carrier sense multiple access with collision avoidance), 210  
   HORNET implementation, 258  
 CSMA/CD (carrier sense multiple access with collision detection), 210  
 cutoff condition, 19–20  
 cylindrical geometry, PMD, 25

## D

data packets, SRP, 234  
 data rates of SONET/SDH, 221–223  
 dB (decibel), 32  
 DBR (distributed Bragg reflector) lasers, 46–47  
 DC-biased lasers, 179  
 DCUs (dispersion compensation units), optimal placement of, 126–128  
 dedicated protection, 164  
 deflection routing, 244  
 degree of connectivity, 144  
 degree of conversion, 203  
 delay lines  
   contention resolution, 252  
   CORD, 244  
 delayed reservation, 247  
 demos (VPItransmissionMakerWDM)  
   300 km OC-192 metro core ring, 319  
   300 km OC-48 metro core ring, 319  
   amplifier spacing and launch power, 321  
   back-to-back receiver sensitivity, 318  
   importing, 305  
   long-haul WDM system, 320  
 density, effect on refraction, 7  
 depletion region, 53  
 designing WDM networks, 113, 178  
   access network topologies, 168  
   access rings, 168  
   node architecture, 168–170  
   attenuation, necessity of for signal propagation, 109–110  
   based on fiber types, 180  
   BER, 113  
   case studies, 134–140  
   chromatic dispersion, 116  
   DCUs, optimal placement, 126–128  
   degree of connectivity, 144  
   fully connected mesh, 143  
   green-field networks, 145  
   laser modulation, 179  
   logical topology, 145–147  
   long-haul architectures, 177  
     FWM, effect on, 130  
     PMD, effect on, 132  
   metro core architecture, 170–176  
   nodes, effect on design, 159  
   nonlinearity, 114–116  
   OADMs, 181  
   optical amplifiers, 181  
   optical receivers, 180  
   OSC, 158  
   physical layer, 308  
   power budget, 113  
   PPMN, 166  
   protection, 162  
     1+1, 164  
     from fiber failure, 163  
     from path failure, 163  
     from subsystem failure, 163  
   simulation, signal-to-noise, 310  
   simulations, 303, 306–307  
   standalone photonic computer-aided design tools, 305  
   topology selection, 143  
   trees, 144  
   virtual topologies, 200–201  
 destination address field (Ethernet), 212  
 destination-based slot assembly, PSR, 250–251  
 development of fiber optic technology, 3  
 devices  
   amplifiers, 88  
     calculating maximum transmission distance, 110  
     EDFA, 91–94  
     heuristics, 88–89  
     millisecond power transient analysis, 313  
     noise, 90–91  
     SOAs, 98–99  
     testing, 272, 290–292  
   burst-mode receivers, 259–260  
   cavities, 70  
   circulators, 69  
   couplers, 68  
   filters, 70  
     AOTFs, 72–73  
     AWG devices, 73  
     Fabry Perot cavity filters, 70–71  
     FBGs, 72  
     MZI, 74  
     thin film, 74–75

- FOTP (fiber-optic test procedures), 270
- lasers, 43–44
  - chirp, 49
  - DBR, 46–47
  - distributed feedback, 45
  - Fabry Perot (FP) cavity lasers, 47
  - line width, 49
  - modulation, 50–51
  - spontaneous emission, 44
  - VCSEL, 47
- passive, performance measurement parameters, 287–288
- photodetectors, 52
  - APDs, 55–57
  - PIN, 53–54
  - receiver noise, 57–58
  - receiver performance, 58
  - receiver sensitivity, 67–68
- photonic component design, 316
- Raman amplifiers, 94–95
  - DRAs, 97
  - hybrid, 98
- repeaters, 111
- switches
  - bubble, 82
  - electro-optical, 81
  - mechanical, 78–79
  - thermo-optic, 82
- test equipment, 270
  - attenuators, 274
  - BERTs, 297
  - broadband light sources, 276
  - laser sources, 275
  - optical spectrum analyzers, 276–278
  - OTDRs, 279
  - power meters, 273
- transponders, 75–77
  - cost of, 266
  - full/limited wavelength conversion, 203
- DFCs (dispersion compensation fibers), 101–102
- DGD (differential group-delay), 12, 132
- diffraction, 15
- direct modulation, 50
- directional couplers, 81
- directly modulated lasers, 179
- dispersion, 13, 24
  - assessing power penalty, 114
  - chromatic, 112
    - DCUs, 126–128
    - effect on maximum transmission distance, 116
    - effect on pulse spreading, 112
    - high dispersion fibers, 101–103
    - material, 26
    - optical velocity parameters, 14
    - PMD, 25
      - compensation techniques, 104
      - mitigating effects of through simulation, 314
    - postcompensation, 100–101
    - precompensation, 101
    - waveguide dispersion, 28
- dispersion maps, optimizing DCU placement, 126–128
- dispersion-shifted fibers, 28, 31
- displaying eye patterns, 296
- distance limitations of optical fiber
  - attenuation coefficient, 23
  - calculating maximum transmission distance, 110
- distributed amplification, 97
- distributed Bragg reflector lasers, 46–47
- distributed feedback lasers, 45
- distributions, Self-Similarity, 245, 260–262
  - heavy-tailed distribution, 264–265
  - long-range dependence, 263
  - second-order, 262–263
- DLE (dynamic lightpath establishment), 197
- doping, 43, 290–292
  - EDFAs, 91–94
    - ISS testing method, 290
    - noise, 93–94
    - time domain extinction testing method, 291–292
    - versus Raman amplifiers, 98
- downstream transmission, EPON, 220
- DPT (Dynamic Packet Transport), 231
  - SRP architectures, 232, 237
    - control/data packets, 234
    - generic frame header, 233–234
    - IPS, 233
    - ring selection, 235
    - topology discovery, 235
    - traffic flow, 235
- DRAs (Distributed Raman amplifiers), 97. *See also* Raman amplifiers
- dropping channels, 34
- DSFs (dispersion shifted fibers), 112
- dual-hubbed architectures, 151
- dynamic lightpath establishment, 197
  - optimization parameter, 198–199
- Dynamic Packet Transport. *See* DPT

## E

- E field
  - effect on polarization, 12
  - Maxwell's equations, 15
  - relationship to H field, 16
- EDFAs (Erbium doped fiber amplifiers), 91–92, 313
  - noise, 93–94
  - testing, 290–292
    - ISS method, 290
    - time domain extinction method, 291–292
    - versus Raman amplifiers, 98
- edge-emitting LEDs (ELEDs), 276
- EFM (Ethernet in the First Mile) task force, 218
- electrical repeaters, 111
- electromagnetics
  - Maxwell's equations, 16
  - wave-propagation theory, 16
- electrons, 43
  - population inversion, 43
- electro-optical switches, 81
- ellipticity of signal, 284
- encoding schemes, Gigabit Ethernet, 212
- EPONs (Ethernet passive optical networks), 219
  - downstream transmission, 220
  - upstream transmission, 220–221
- equations
  - lightpath-link matrix, 190–192
  - Schrödinger's nonlinear propagation, 116
- Erbium doped fiber amplifiers. *See* EDFAs
- error function of BER, 63–67
- estimating node-induced system loss, 124–126
- Ethernet
  - 10 GE, 215
    - physical layer, 215
    - XAUI, 217
    - XGMII, 215
  - EFM task force, 218
  - EPON, 219
    - downstream transmission, 220
    - upstream transmission, 220–221
  - evolution of, 210
  - Fast Ethernet, 210
  - frames, 212
  - GE, 211–212
    - encoding scheme, 212
    - GBIC applications, 213–214
    - physical layer, 213–214
    - protocol stack, 212
  - over WDM, 209
- Eurasian optical network standards, SDH, 221
- external modulation, 51

- lasers, 179
- extinction ratio, 179, 294–296
- extraordinary rays, 11–12
- extrinsic bending loss, 21
- eye mask testing, 296
- eye patterns
  - extinction ratio, 296
  - waveform analysis, 293–294

## F

- Fabry Perot (FP) cavity lasers, 47
- Fabry Perot cavity-based SOAs, 99
- fairness algorithm (SRP-fa), 236–237
- Faraday rotators, 69
- Faraday's Law of Induction, 16
- Fast Ethernet, 210
- fault tolerance
  - lightpath protection, 162
    - 1+1, 164
    - dedicated, 164
    - mesh protection, 166
    - of fiber failure, 163
    - of path failure, 163
    - of subsystem failure, 163
    - PCA, 165
  - restoration, 153
- FBGs (fiber Bragg gratings), 72
  - dispersion compensation, 112
  - GVD compensation, 102–103
- FCS (frame check sequence) field (Ethernet), 212
- FDLs (fiber delay lines), 243
- FEC (forward error correction), 178
  - in 40 Gbps systems, 253
- feedback, 45
- Fermi-Dirac distribution equations, 44
- fiber amplifiers, 111
- fiber cut, 163
- fiber delay lines (FDLs), 243
- fiber lasers, 43
- fiber optics, 15. *See also* optical communications
  - active devices, 4
  - attenuation, 21, 23
    - necessity of for signal propagation, 109–110
  - bending losses, 23
  - birefringence, 11–12
  - degradation in performance, 269
  - DGD, 12
  - dispersion-shifted, 28
    - DSFs, 112
    - GVD, 102–103

- high dispersion fibers, 101–102
  - postcompensation, 100–101
  - precompensation, 101
- effect on WDM network design, 180
- increasing capacity, 36–37
- initial use of, 3
- longitudinal cross section of fiber, 9
- loss versus dispersion, 180
- material absorption, 21
- Maxwell's equations, 16
- modes, cutoff condition, 19–20
- NA, 9–11
- network layer technology breakthroughs, 187
- passive devices, 4
- pulse propagation, broadening of induced pulses, 25–26
- SMF, types of, 31
- TIR, 4
- fields
  - of Ethernet frames, 212
  - of SRP frames, 234
- filters
  - AOTFs, 72–73
  - AWG devices, 73
  - Fabry Perot cavity filters, 70–71
  - FBGs, 72
  - MZI, 74
  - TFFs, 74–75
    - reducing nodal loss in MANs, 162
- fixed transponders, 76
- formulating integer linear programs to solve RWA problems, 193
- forward pumping, 92
- FOTP (fiber-optic test procedures), 270
- Fourier analysis of time domain representation, 254
- FP-based analyzers, 276
- framing
  - Ethernet, 212
  - IP over WDM, 210
  - optical technologies, 238
  - SRP, 233–234
- Fresnel's effect, 15
- full wavelength conversion, 203
- fully connected mesh, 143
- future of optical switching technologies, 244
- FWM (four-wave mixing), 29

## G–I

- gain
  - dBs, 32
  - enhancing, 92
  - Raman gain spectra, 95–97
  - saturation, 89
- gain-tilt in metro core networks, 176
- Gauss's Law of Electricity, 16
- Gaussian distributions
  - mean, 61
  - variance, 61–63
- GBIC (Gigabit Interface Converter) types, 213–214
- GE (Gigabit Ethernet), 211–212. *See also* 10 GE
  - encoding scheme, 212
  - GBIC applications, 213–214
  - physical layer, 213–214
  - protocol stack, 212
- geometric optics, limitations of, 18–19
- GMPLS (Generalized Multi-protocol Label Switching), 260
- graded index of fiber media, 9
- graph coloring
  - sequential approach, 195–196
  - solving wavelength assignment problem, 194–197
- gratings, 15
  - AOTFs, 73
  - FBGs, 72
    - dispersion compensation, 112
    - GVD compensation, 102–103
- green-field networks, 145
- group delay, 12
- group index, material dispersion, 26
- group velocity, 13, 24
- GVD (group velocity dispersion), 24, 100, 112
  - compensation with FBGs, 102–103
- H (magnetic) field
  - effect on polarization, 12
  - Maxwell's equations, 15
  - relationship to E field, 16
- hamming distance, 178
- heavy-tailed distribution, 264–265
- high dispersion fibers, 101–103
- higher-order VCs, 227
- HORNET (Hybrid Opto-Electronic Ring Network), 257–259
- hubbed topology, 150
- hybrid amplifiers, 98

- 
- Hybrid Opto-Electronic Ring Network (HORNET), 257–259
  - IEEE 802.3 standard
    - evolution of Ethernet, 210
    - Fast Ethernet, 210
    - frame format, 212
    - GE, 211
  - IEEE 802.3ah (EFM) standard, 218
  - IEEE 802.3z (Gigabit Ethernet) standard, 212
    - encoding scheme, 212
    - GBIC applications, 213–214
    - physical layer, 213–214
    - protocol stack, 212
  - IEEE 802.ae (10 GE) standard, 215
    - physical layer, 215
    - XAUI, 217
    - XGMII, 215
  - IM (intensity modulated) schemes, 6
  - importing VPItransmissionMakerWDM demos, 305
  - incident rays, polarization, 13
  - increasing fiber capacity, 36–37
  - index profiles of fiber media, 9
  - input section of nodes, 158
  - installing VPItransmissionMakerWDM, 304
  - integer linear formulations to solve
    - RWA problem, 193
  - interferometer-based analyzers, 276
  - Internet, future of, 260
  - intrinsic fiber loss, 21
  - IP (Internet Protocol)
    - over DWDM, 238
    - framing issues, 210
    - POS, 229–231
  - IPS (intelligent protection switching), 233
  - irregular multihop topologies, 188
  - ISI (intersymbol interference), 13
  - ISS (interpolated source subtraction), 290
  - ITU standards
    - G.654, 31
    - metro core network-related, 153
    - optical network component testing, 270
  - ITU-grid wavelengths, 76
  - L (long) band, 30
  - LAN PHY (10 GE), 215
  - lasers, 43–44
    - chirp, 49
    - DBR, 46–47
    - directly modulated, 179
    - distributed feedback, 45
    - externally modulated, 179
    - Fabry Perot (FP) cavity lasers, 47
    - line width, 49
    - mechanically tuned, 47
    - modulation, 50–51, 179
      - NRZ, 51
      - RZ, 51
    - sources, 275
    - spontaneous emission, 44
    - VCSEL, 47
  - lasing effect, 47
  - lasing threshold, 44
  - latency, 188
    - CORD, 244
  - layered protocols, SONET, 224–226
  - length field (Ethernet), 212
  - light quanta, 24
  - lightpath switches, 78
    - bubble, 82
    - electro-optical, 81
    - mechanical, 78–79
    - thermo-optic, 82
  - lightpath-link matrix, 190–192
  - lightpaths, 4, 35
    - blocking probability
      - calculating, 202–204
      - minimizing, 198
    - dynamic establishment, 197
      - optimization parameter, 198–199
    - load, 201
    - propagation, 3
    - protection, 146, 162
      - 1+1 protection, 164
      - mesh protection, 166
      - of fiber failure, 163
      - of path failure, 163
      - of subsystem failure, 163
      - PCA, 165
    - Raleigh scattering, 22
    - reflection, 7
    - refraction, 7
      - critical angle, 8
      - refractive index of the media, 6–7
      - Snell's law, 7–8
- 
- ## J–L
- 
- JET (Just Enough Time) protocol, 247–248
  - Jones vector measuring polarization, 281

- restoration, 153
- shortest path routing, 35
- spatial diversity, 189
- spontaneous emission, 44
- static establishment, 197–199
- stimulated emission, 44
- virtual topology of optical networks, 187
- limitations
  - of applying geometric optical principles to pulse propagation, 18–19
  - of network design, 129
- limited wavelength conversion, 203
- line layer (SONET/SDH), 225
- line rate of STM-1, 223
- line width of lasers, 49
- linear add/drop architecture, SONET/SDH, 228
- linear polarization, 12
- Lithium Niobate waveguide, 81
- LOBS (label optical burst switching), 249
- logical topologies, designing, 145–147
- long-haul networks, 155–156
  - design considerations, 177
    - FWM, 130
    - nonlinearity, 114–116
    - PMD, 132
    - XPM, 131
  - nodal architectures, 159–161
  - VPItransmissionMakerWDM demo, 320
  - wavelength routing, 161
- loopless deflection, 244
- lower-order VCs, 227

## M

- macrobending, 23
- magnetism
  - Ampere's Law, 16–17
  - Gauss's Law, 16
- MANs (metropolitan area networks)
  - BER, 175–176
  - designing, 170–176
  - gain-tilt, 176
  - nodal architectures, 161–162
  - power budget, 175
  - TFF, 174
  - wavelength conversion, 171
- material absorption loss, 21
- material dispersion, 24–26
- maximum transmission distance
  - calculating, 110
  - extending through simulation, 315–316
  - chromatic dispersion, effect on, 116
- Maxwell's equations, 3, 16
  - limitations of geometric optical principles, 18–19
  - modes, 15
- mean of Gaussian distributions, 61
- measuring
  - eye pattern, 295
  - polarization, 281
    - Jones vector, 281
    - PMD, 287
    - Poincare's sphere, 285–286
    - SOP, 284–285
    - Stokes vector, 282–284
- mechanical switches, 78–79
- mechanically tuned lasers, 47
- MEMS technology, 79
  - optical cross-connect, 257
- mesh protection, 166
- metro access networks, 149
  - hubbed topology, 150
  - protection algorithms, 151
  - thin film filter-based architecture, 150
- metro core networks, 152
  - BER, designing, 175–176
  - collector networks, 153
  - designing, 170–176
  - gain-tilt, 176
  - ITU standards, 153
  - power budget, 175
  - ring topology, 154–155
  - TFF, 174
  - wavelength conversion, 171
- metro rings, Gigabit Ethernet over DWDM, 214
- Michelson interferometer-based analyzers, 276
- micro bubbles, 82
- microbending, 23
- millisecond power transient analysis, 313
- minimizing optical crosstalk, 312
- minimum-weight spanning tree, 144
- mitigating effects of PMD, 26
- Mode field (SRP frames), 234
- modeling Internet traffic, Self-Similarity, 260–262
  - heavy-tailed distribution, 264–265
  - long-range dependence, 263
  - second-order, 262–263
- modes, 15
  - cutoff condition, 19–20
  - of pulse propagation, 18
  - SMF, types of, 31

- modulation schemes, 5, 50–51
  - cross phase, 115
  - NRZ, 51
  - of lasers, 179
  - RZ, 51, 254
  - SPM, 115
- monochromators, 277
- MPLS (multiprotocol label switching), label optical burst switching, 249
- MSOH (multiplexing section overhead), 224
- Muller matrix method of measuring polarization, 281
- multihop networks, 188
- multihubbed networks. *See* metro core networks
- multiplexing techniques in optical networks, 36–37
  - SONET/SDH, 226
- multiplicative factor, 56
- multipoint PON topologies, 218–219
- multistage amplification, 111
- muxponding, 146
- MZI (Mach Zehnder Interferometer), 74
  - FBGs, 72
  - MZI, 74
  - thin film, 74–75
- lasers, 43–44
  - chirp, 49
  - DBR, 47
  - DBR feedback, 46
  - distributed feedback, 45
  - line width, 49
  - spontaneous emission, 44
  - VCSEL, 47
- photodetectors, 52
  - APDs, 55–57
  - PIN diode, 53–54
  - receiver noise, 57–58
  - receiver performance, 58
  - receiver sensitivity, 67–68
- switches
  - bubble, 82
  - electro-optical, 81
  - mechanical, 78–79
  - thermo-optic, 82
- transponders, 75–77

## N

- N protection, 164
- NA (numerical aperture), 9–11
- NEs (network elements)
  - degree of connectivity, 144
  - estimating losses, 124–126
  - input section, 158
  - nodal architectures
    - of long-haul networks, 159–161
    - of MANs, 161–162
  - switching section, 159
- net fiber nonlinearity as network design consideration, 114–116
- NMSs (network management systems), 156
- nodes (WDM), 41
  - architectures
    - access network, 169–170
    - long-haul network, 159–161
    - MANs, 161–162
  - cavities, 70
  - circulators, 69
  - couplers, 68
  - filters, 70
    - AOTFs, 72–73
    - AWG devices, 73
    - Fabry Perot cavity filters, 70–71
- noise
  - accumulation from multistage amplification, 111
  - ASE, 111
  - EDFA, 93–94
  - OSNR, 111
  - receiver, 57–58
- nonblocking cross-connects, 256
- nondeterministic polynomial time hard solutions to RWA problems, 190
- nondispersion-shifted fiber, 31
- nonlinearity
  - FWM, 29
  - Soliton, 254
  - third-order susceptibility, 28
- normal, 7–8
- normalized frequency  $V$ , 20
- NRZ (non-return to zero) modulation, 5, 51
  - in 40 Gbps systems, 254–255
- NZDSFs (nonzero dispersion-shifted fibers), 31

## O

- OADM s (optical add/drop multiplexers)
  - architectures, 171
  - effect on WDM network design, 181
  - reconfigurable, 266

- OBS (optical burst switching), 244
  - OC-768, 40 Gbps data communication, 245
  - OEO (opto-electro-opto) repeaters, 34, 111
  - offline RWA, 194
  - OH molecule, 21
  - OLT (optical line terminal), 218
  - online RWA, 194
  - ONUs (optical network units), 218
    - upstream transmission, 221
  - OOK (on/off keying), 51
  - O-O-O switches, 34
  - optical amplifiers, 88
    - doped fiber, EDFAs, 91–94
    - heuristics, 88–89
    - noise, 90–91
    - Raman amplifiers, 94–95
      - DRAs, 97
      - hybrid, 98
    - SOAs, 98–99
  - optical communication. *See also* optical networks
    - attenuation, 21
    - birefringence, 11–12
    - contention resolution, 244
    - DGD, 12
    - diffraction, 15
    - dispersion, 13, 24–25
    - fiber
      - increasing capacity of, 36–37
      - longitudinal cross section, 9
    - load, 201
    - material dispersion, 26
    - multihopping, 188
    - NA, 9–11
    - nonlinearity of optical fiber, 28
    - PMD, 12
    - reflection, 7
    - refraction, 7
      - normal, 7
      - refractive index of the media, 6–7
      - Snell's law, 7–8
    - research in, 243–245
    - units of power measurements, 32
    - unusable wavelengths, 22
    - waveguide dispersion, 28
    - WDM nodes
      - cavities, 70
      - circulators, 69
      - couplers, 68
      - filters, 70–75
      - lasers, 43–49
      - photodetectors, 52–58, 67–68
      - switches, 78–82
      - transponders, 75–77
      - windows of operation, 30
  - optical cross-connects, 256–257
  - optical fiber, nonlinearity, 28
    - four-wave mixing, 29
    - third-order susceptibility, 28
  - optical framing, 238
  - optical label swapping, 245
  - optical networks
    - design considerations, 113
      - BER, 113
      - chromatic dispersion, 116
      - nonlinearity, 114–116
      - power budget, 113
    - SONET
      - drawbacks, 209
      - linear add/drop architecture, 228
      - multiplexing scheme, 226
      - POS, 209, 229–231
      - ring architecture, 229
      - VTs, 226
    - switching technologies, 243
      - burst switching, 244–249
    - traffic engineering, 256
    - virtual topology, 187
  - optical service channel(OSC), 156–158
  - optical signals, absolute quality, 66
  - optical spectrum analyzers, 276–278
  - optical spread. *See* dispersion, 13
  - optical waveform analysis, 293–294
  - optimizing WDM networks with simulations, 303
    - VPItransmissionMaker software, 306–307
  - ordinary rays, 11–12
  - OSC (optical service channel), 156–158
  - OSNR (optical signal-to-noise ratio), 111
    - calculating, 120–122
    - improving with Raman amplification, 123
    - tilt-limited systems, 132
  - OTDRs (Optical Time Domain Reflectometers), 279
  - outage probability, 104
  - output saturation power, 89
  - OXCs (optical cross-connects), 159
- ## P
- 
- packet bursts, 244
  - parameters of group velocity, 14
  - Pareto distributions, 264

- parity bit field (SRP frames), 234
- passive devices, 4
  - performance measurement parameters, 287–288
  - testing, 289
- path layer (SONET/SDH), 225
- PCA (protection channel access), 165
- PDF (probability density function), 60
- PDL, measuring, 281
- performance
  - FOTP, 270
  - of passive devices
    - measurement parameters, 287–288
    - testing, 289
  - optical network component testing, 270
  - performing full end-to-end WDM tests, 299
- performing full WDM end-to-end test, 299
- perturbations, 44
  - FBGs, 72
- phase shifts
  - chirped pulses, 129
  - in nonlinear signals, 114–116
  - walkover effect-induced, 115
- photodetectors, 52
  - PIN, 53–57
  - receiver noise, 57–58
  - receiver performance, 58
    - BER, 59–67
  - receiver sensitivity, 67
    - SNR, 67–68
- photoelastic effect, 73
- photonic component design, 316
- photonic layer (SONET/SDH), 225
- photonic simulation, 307
  - maximizing transmission lengths, 315–316
  - minimizing optical crosstalk, 312
  - mitigating effects of PMD, 314
  - signal-to-noise simulation, 310
- photonic slot routing (PSR), 244
- photons, 44
  - phonon interaction, 73
  - spontaneous emission, 44
- physical layer network design, 308
  - 10 GE, 215
- PIN photodetectors, 53–54
- PMD (polarization mode dispersion), 12, 24–25, 112
  - measuring polarization, 287
  - mitigation techniques, 26, 314
- p-n junction, 43
  - depletion region, 53
  - feedback, 45
- Poincare's sphere, measuring polarization, 285–286
- point-to-point WDM networks, 32–34
  - Q-factor, 117
  - wavelength assignment, 35
- polarization, 11–12, 69
  - circular, 12
  - linear, 12
  - measuring, 281
    - Jones vector, 281
    - PMD, 287
    - Stokes vector, 282–284
  - Poincare's sphere, 285–286
  - SOP representation, 284–285
- PONs (passive optical networks)
  - EPONs, 218
    - downstream transmission, 220
    - upstream transmission, 220–221
  - OLT, 218
  - ONU, 218
  - topologies, 218–219
- population inversion, 43–44
- POS (packet over SONET), 209, 229–231
- postcompensation, 100–101
- power budget, 175
- power measurements, 32
- power meters, 273
- power penalties
  - chirp-induced, 129
  - Q-factor induced, 117
- power requirements
  - OSNR, 111
  - receiver sensitivity, 110
- PPMN (path protected mesh networks), 166
- preamble, 212
- prechirping, 101
- precompensation, 101, 127
- PRI field (SRP frames), 234
- probabilities
  - BER, 59
    - error function, 63–67
    - Gaussian distribution, 61–63
  - outage probability, 104
- protection, 146
  - 1+1, 164
    - dedicated, 164
    - in metro access networks, 151
    - mesh protection, 166
    - PCA, 165
    - shared, 164
- PSR (photonic slot routing), 244, 250
  - bridges, 252
  - slot copying, 251
  - subslot merging, 251

- pulse propagation
  - broadening of induced pulses, 25–26
  - cutoff condition, 19–20
  - frequency chirp, 129
  - modes, 18
  - nonlinear phase shift, 114–116
  - Schrödinger's nonlinear propagation, 116
- pumps, 92

## Q–R

- Q-factor
  - calculating, 119–120
  - effect on point-to-point link design, 117
  - relationship to BER, 117
- quanta, 24
- quantum efficiency, 55
- queueing SRP traffic, 235
- Raleigh scattering, 21–22
- Raman amplifiers, 94–95
  - DRAs, 97
  - hybrid, 98
  - improving OSNR, 123
  - versus EDFAs, 98
- Raman gain spectra, 29, 95, 97
- Raman threshold, 96
- rarity of media, effect on refraction, 7
- rays of light, 7
  - extraordinary rays, 11–12
  - ordinary rays, 11–12
- receivers, 58
  - BER, 59–67
    - error function, 63–67
    - Gaussian distribution, 61–63
  - burst-mode, 259–260
  - noise, 57–58
  - sensitivity, 110
    - SNR, 67–68
- reconfigurable OADMs, 266
- redundancy, lightpath protection, 162
  - 1+1, 164
  - dedicated, 164
  - mesh protection, 166
  - of fiber failure, 163
  - of path failure, 163
  - of subsystem failure, 163
  - PCA, 165
- reflection, 7
- reflective stack (thin film filters), 75
- refraction, 7. *See also* polarization
  - birefringence, 11–12
  - critical angle, 8
  - density, effect on, 7
  - group index, material dispersion, 26
  - index profiles, 9
  - NA, 9–11
  - normal, 7
  - Snell's law, 7–8
- relationship of E and H fields, 16
- repeaters, 111
- requirements for VPItransmissionMakerWDM
  - installation, 304
- researching new technologies, 243–245
  - 40 Gbps systems
    - FEC, 253
    - RZ modulation, 254–255
  - burst switching, 245
    - attributes, 246
    - delayed reservation, 247
    - JET, 247–248
    - LOBS, 249
    - TAG, 246–247
  - burst-mode receivers, 259–260
  - HORNET, 257–259
  - optical cross-connect, 256–257
  - PSR, 250–251
  - SDLs, 252
  - transparent optical networks, 265–266
- responsivity, 55
- restoration, 153
- reverse pumping, 92
- ring topology, 144
  - in metro core networks, 154–155
  - SONET/SDH, 229
- routing assignment, 189
  - constraints on maximizing throughput, 189–190
- RPRs (resilient packet rings), 210
- RSOH (regeneration section overhead), 224
- RSVP (Resource Reservation Protocol), 255–256
- RWA (routing and wavelength assignment)
  - blocking probability, calculating, 202–204
  - constraints, 193
  - corollaries, 201
  - degree of conversion, 203
  - dynamic lightpath establishment, 197–199
  - NP-hard solutions, 190
  - offline, 194
  - online RWA, 194
- RZ (return to zero) modulation, 5, 51, 254–255

# S

- S (short) band, 30
- semiconductors, conduction state, 44
- saturation power, 89
- SBS (stimulated Brillouin scattering), 29
- scattering, SRS, 29
- Schrödinger's nonlinear propagation, 116
- SCM (subcarrier channel multiplexing), 37
- SDH (Synchronous Digital Hierarchy)
  - linear add/drop architecture, 228
  - multiplexing scheme, 226
  - protocol stack layers, 224–226
  - ring architecture, 229
- SDLs (switched optical delay lines), 252
- second-order Self-Similarity, 262
- section layer (SONET/SDH), 225
- selecting network topologies, 143
- Self-Similarity, 245
  - heavy-tailed distribution, 264–265
  - long-range dependence, 263
  - properties of, 260, 262
  - second-order, 262–263
- Sellmeier's equation, 26
- semiconductors
  - doping, 43
  - lasers, 43
  - p-n junction
    - depletion region, 53
    - feedback, 45
  - SOAs, 98–99
- semi-lightpaths, 35
- sequential approach to graph coloring, 195–196
- serial interfaces, 10 GE physical layer, 215
- shared protection, 164
- Shot noise, 57
- signals
  - measuring, 296
  - propagation
    - 2R regeneration, 111
    - attenuation, 109–110
    - attenuation coefficient, 23
    - fiber attenuation, 21
    - Raleigh scattering, 22
    - repeaters, 111
  - representations (VPItransmissionMaker), 307
  - SOP, 284–285
- signal-to-noise simulation, 310
- simulations
  - commercial tools, 303–304
  - maximizing transmission lengths, 315–316
  - minimizing optical crosstalk, 312
  - mitigating effects of PMD, 314
  - signal-to-noise, 310
  - VPItransmissionMaker software, 306–307
- sine waves, 254
- single-hop networks, 188
- sized-based network classification, 147–149
  - long-haul networks, 155–156
    - nodal architectures, 159–161
  - MANs, nodal architectures, 161–162
  - metro access networks, 149
    - hubbed topology, 150
    - protection algorithms, 151
    - thin film filter-based architecture, 150
  - metro core networks, 152
    - collector networks, 153
    - ITU standards, 153
    - ring topology, 154–155
- SLE (static lightpath establishment), 197
- slot copying, 251
- SMF (single-mode fiber)
  - cutoff condition, 19–20
  - types of, 31
- Snell's law, 7–8
- SNR (signal-to-noise ratio), 58
  - of optical receivers, 67–68
  - OSNR, 111
    - calculating, 120–122
    - improving with Raman amplification, 123
- SOAs (semiconductor optical amplifiers), 23, 98–99
- SOF (start of frame) field, Ethernet, 212
- Soliton, 254
- solving RWA problems with integer linear
  - formulations, 193
- solving wavelength assignment problem with graph
  - coloring, 194–197
- SONET/SDH
  - drawbacks, 209
  - linear add/drop architecture, 228–229
  - multiplexing scheme, 226
  - POS, 209, 229
    - interfaces, 231
  - protection, 146
  - protocol stack layers, 224–226
  - SDH, 221
  - STM-1, 223
    - line rate, 223
    - MSOH, 224
    - RSOH, 224
    - transmission capacity, 224
  - STS-1, 222
  - VTs, 226

transport overhead, 222  
 40 Gbps systems  
     FEC, 253  
     RZ modulation, 254–255  
     data rates, 221–223  
 SOP (state of polarization), 284–285  
 source address field (Ethernet), 212  
 spacer (thin film filters), 75  
 spacing of channels, 5  
 spatial diversity, 189  
 speed of light, refractive index of the media, 6–7  
 SPM (Self Phase Modulation), 115  
 spontaneous emission, 44  
 SRP (Spatial Reuse Protocol), 232  
     architectures, 237  
     control packet, 234  
     data packet, 234  
     generic frame header, 233–234  
     IPS, 233  
     ring selection, 235  
     topology discovery, 235  
     traffic flow, 235  
 SRP-fa (SRP fairness algorithm), 236–237  
 SRS (stimulated Raman scattering), 29  
 standalone photonic computer-aided design  
     tools, 305  
 static lightpath establishment, 197–199  
 stimulated emission, 44  
 STM-1 (Synchronous Transport Module  
     Level-1), 223  
     line rate, 223  
     MSOH, 224  
     RSOH, 224  
     transmission capacity, 224  
 Stokes vector, 95  
     measuring polarization, 282–284  
 strength of magnetic fields. Ampere's Law, 16–17  
 STS-1 (Synchronous Transport Signal Level-1), 222  
     VTs, 226  
 submarine networks, 156  
 subslot merging, 251  
 subsystem modules  
     optical amplifiers, 88  
         EDFA, 91–94  
         heuristics, 88–89  
         noise, 90–91  
         Raman amplifiers, 94–98  
         SOAs, 98–99  
 susceptibility of nonlinear effects, 28  
 switch fabric (WDM networks), 34

switches  
     bubble, 82  
     electro-optical, 81  
     mechanical, 78–79  
         MEMS technology, 79  
     thermo-optic, 82  
 switching section of nodes, 159  
 switching technologies, 244  
 system loss, estimating, 124–126

## T

TAG (Tell and Go) protocol, 247  
 TDM (time-division multiplexing), 36  
 Tell and Go protocol, 247  
 test equipment  
     attenuators, 274  
     broadband light sources, 276  
     laser sources, 275  
     optical spectrum analyzers, 276–278  
     OTDRs, 279  
     passive devices, 289  
     power meters, 273  
 testing  
     amplifiers  
         ISS method, 290  
     EDFAs, 290  
         ISS method, 290  
         time domain extinction method, 291–292  
     equipment  
         attenuators, 274  
         broadband light sources, 276  
         laser sources, 275  
         optical spectrum analyzers, 276–278  
         OTDRs, 279  
         passive devices, 289  
         power meters, 273  
     FOTP, 270  
     full WDM end-to-end tests, performing, 299  
     performance of optical network components,  
         270  
 TFFs (thin film filters), 74–75  
     metro access network architecture, 150  
     reducing nodal loss in MANs, 162  
     transition layer, 75  
 thermal noise, 58  
 thermo-optic switches, 82

thin film filters. *See* TFFs

third-order susceptibility, 28

throughput, 188–189

tilt limited systems, 132

time domain extinction method of EDFA testing, 291–292

TIR (total internal reflection), 4

tools

- commercial simulation tools, 303–304
- test equipment
  - attenuators, 274
  - BERTs, 297
  - broadband light sources, 276
  - laser sources, 275
  - optical spectrum analyzers, 276–278
  - OTDRs, 279
  - power meters, 273

topologies

- access networks, 168
  - access rings, 168
  - node architecture, 168–170
- hub, 150
- multihop, 188
- PON, 218–219
- ring, 154–155
- selecting, 143
- SRP, discovery process, 235
- virtual, 200–201

traffic

- burstiness, 245
- self-similarity, 245

traffic engineering, 256

traffic grooming, 265

transition layer (thin film filters), 75

transmission capacity of STM-1, 224

transmission distance-based network classification, 147–149

- long-haul networks, 155–156
  - designing, 177
  - nodal architectures, 159–161
- MANs, nodal architectures, 161–162
- metro access networks, 149
  - hubbed topology, 150
  - protection algorithms, 151
  - thin film filter-based architecture, 150
- metro core networks, 152
  - collector networks, 153
  - ITU standards, 153
  - ring topology, 154–155

transparent optical networks, 265–266

transponders, 34, 75–77

- cost of, 266
- full/limited wavelength conversion, 203

transport overhead (SONET), 222

traveling wave SOAs, 99

trees, 144

TTL field (SRP frames), 233

tunable lasers, 3, 47

tunable transponders, 76

## U–V

uneven channel spacing in long-haul networks, 177

units of power measurement, 32

upstream transmission (EPONs), 220–221

V parameter of cutoff condition, 20–21

variable attenuators, 274

variance of Gaussian distributions, 61–63

VCSELs (vertical cavity surface-emitting lasers), 47

velocity of lightwaves, dispersion, 24–25

vendor-conducted fiber tests, 269

virtual topology of optical networks, 187, 200–201

VPItransmissionMakerWDM

- installation requirements, 304
- maximizing transmission lengths, 315–316
- physical layer network design, 308
- signal representations, 307
- simulation technology, 306
- demos
  - 300 km OC-192 metro core ring, 319
  - 300 km OC-48 metro core ring, 319
  - amplifier spacing and launch power, 321
  - back-to-back receiver sensitivity, 318
  - long-haul WDM system, 320

VSR (very short reach) applications, VCSEL lasers, 47

VTs (virtual tributaries), 226

## W

"walkover" effect, 115

WAN PHY (10 GE), 215

waveform analysis, 293–294

- BERTs, 297

waveguide dispersion, 24, 28

wavelength assignment, 189

- constraints on maximizing throughput, 189–190
- integer linear formulations, 193

ITU-grid, 76  
 lightpath-link matrix, 190–192  
 reuse
 

- in metro rings, 154
- topologies, effect on, 201–202

 solving with graph coloring approach, 194–197  
 zero dispersion, 26  
 wavelength routing, 159  
 WDM (wavelength division multiplexing), 4  
 WDM network design, 178  
 WDM networks
 

- cavities, 70
- channels
  - add-drop capabilities, 34
  - spacing, 5
- circulators, 69
- composite signals, 32
- couplers, 68
- design considerations
  - access network topologies, 168–170
  - based on fiber types, 180
  - case studies, 134–140
  - degree of connectivity, 144
  - dispersion-based, 129
  - fully connected mesh, 143
  - green-field networks, 145
  - laser modulation, 179
  - logical topologies, 145–147
  - long-haul, 131
  - NEs, estimating system loss, 124–126
  - nodes, effect on, 159
  - nonlinearities, 115
  - OADMs, 181
  - optical amplifiers, 181
  - optical receivers, 180
  - OSC, 158
  - OSNR-based, 129
  - physical layer, 308
  - PPMN, 166
  - protection, 162–163
  - simulations, 303, 306–310
  - standalone photonic computer-aided
    - design tools, 305
  - topology selection, 143
  - trees, 144
- filters, 70
  - AOTFs, 72
  - AWG devices, 73
  - Fabry Perot cavity filters, 70–71

FBGs, 72  
 MZI, 74  
 thin film, 74–75  
 lasers, 43–44
 

- chirp, 49
- DBR, 46–47
- distributed feedback, 45
- line width, 49
- spontaneous emission, 44
- VCSEL, 47

 modulation schemes, 5, 50–51  
 photodetectors, 52
 

- APDs, 55–57
- PIN, 53–54
- receiver noise, 57–58
- receiver performance, 58
- receiver sensitivity, 67–68

 point-to-point, 32–34
 

- wavelength assignment, 35

 signals, 36  
 switch fabric, 34  
 switches
 

- bubble, 82
- electro-optical, 81
- mechanical, 78–79
- thermo-optic, 82

 transponders, 75–77  
 windows of operation, 30  
 windows of operation, 30

---

## X

XAUI
 

- 10 GE, 217

 XAUI (10 Gigabit attachment unit interface), 217  
 XGMII (10 Gigabit Media Independent Interface), 215  
 XPM
 

- effect on long-haul design, 131

---

## Z

zero dispersion wavelength, 26