



## Numerics

---

- 108 Bert Test, 132
- 11-bit chipping, 50
- 22 second issue (ISDN), resolving, 387–396
- 2B+D, 238
- 2B1Q (two binary one quaternary) signaling, 55, 58–59
- 3G wireless, 91–92
- 56-kbps flex modems, 14
- 5ess switch types (ISDN), 259–260
- 5-GHz UNII band, 51–52
- 77x routers, accessing IOS routers, 366–367, 369
- 800 toll-free numbers, dialup, 13
- 802.11a specification, 51–52
- 802.11e specification, 53
- 802.11g specification, 52
- 804 routers, calling from 77x routers, 366–369

## A

---

- access servers, 13
- activating Layer 2 in ISDN routers, 320–321
- active periods (snapshot routing), 291
- adaptive shaping, 487–488
- ADCs (analog-to-digital converters), 39
- Address field
  - Frame Relay frames, 421–423
  - LAPD frames, 244
  - PPP frames, 134
- addressing, Frame Relay
  - ARP, 453
  - Inverse ARP, 454
  - RARP, 454
- adjustable CIRs, 437
- administratively down interfaces on Frame Relay
  - new installs, troubleshooting, 548–549
- ADSL (asymmetric DSL) , 24, 732
  - PPoE, 733
    - discovery stage, 735
    - negotiations, 736–739
    - session stage, 736
- advanced Frame Relay configurations
  - bridging, 474–476
  - compression, 476–477
    - payload compression, 480–481
    - Van Jacobson header compression, 477–480
  - frame switching, 469–470
  - generic traffic shaping, 484–486
  - IP multicast, 482–483
  - IP unnumbered, 469
  - ISDN backup, 471–473
  - traffic shaping, 483–484
    - ELMI, 487–488
    - map classes, 486–487
- AES (Advanced Encryption Standard), 618
- aggregate CIR, 436–437
- agile time division multiple access (A-TDMA), 742
- AH (Authentication Header) format, 614
  - ICV calculation, 615
- alarms states of T1 circuits, 184, 186
- alternate mark inversion. *See* AMI
- AMI (alternate mark inversion), 61, 130
  - ones density, 131
- amplitude, 40
- amplitude-shift keying (ASK), 40
- analog dialup services, 12
  - limitations of, 14
  - VPNs, 13
- analog modems, 126
  - signal loss, 127
- analog pads, echo removal, 129–130
- analog-to-digital converters (ADCs), 39
- Annex A LMI type, 453
- Annex D LMI, 516–520
- Annex D LMI type, 451
- ANSI (American National Standards Institute)
  - standards, Frame Relay, 415

ANSI T1.617 Annex D LMI, 516–520  
 application layer (OSI model), 99  
 Application Service Providers (ASPs), 85–86  
 applications, accessing remotely, 8  
 applying timestamps, 313–314  
 approaches to troubleshooting, models, 101–102  
 AR (access rate), Frame Relay, 434  
 architecture  
   ISDN  
     C-plane, 236  
     Layer 1, 237–241  
     Layer 2, 242–247  
     Layer 3, 248–252  
 ARP (Address Resolution Protocol), 453  
 AS5x00 routers, 205–207  
   AS5200 router commands, 207, 209  
   AS5300 router commands, 209–214  
   AS5400 router commands, 215  
 ASK (amplitude-shift keying), 40  
 ASPs (Application Service Providers), 85–86  
 asymmetrical CIR, 437  
 A-TDMA (agile time division multiple access), 742  
 authentication  
   OTPs, 228  
   PAP, 133  
   PPP, 340, 396–398  
   remote access VPN users, 637  
   servers, 133  
   timeouts (dialup), 219–221  
   VPNs  
     client authentication, 619  
     DH algorithm, 624–627  
     HMAC, 627–628  
     key management, 624–627  
     RADIUS, 621–623  
     user/identity authentication, 620  
 Authentication phase (PPP), 136, 197  
 authenticator GINAs, 705  
 Auto-RP, 483  
 availability  
   of remote access services, 7  
   of phone services for ISDN, 309–310

## B

B (Bearer) channels (ISDN), 234  
   Layer 1, 237–241  
     devices, 238  
     interfaces, 239–241  
   Layer 2, 242  
     LAPD frame format, 242–247  
     logical link establishment (LAPD),  
       246–247  
   Layer 3, 248  
     Q.931, 248–252  
     NFAS, out-of-order detection, 227  
 B8ZS (bipolar 8-zero substitution), 131–132  
   backup interfaces, DDR configuration, 147  
 BACP (Bandwidth Allocation Control Protocol), 16  
 bandwidth  
   of modems, 126  
   on demand, ISDN BRI configuration, 376  
 Bandwidth Allocation Control Protocol (BACP), 16  
 bandwidth interval, Frame Relay, 434  
 Barker sequence, 50  
 baseline behavior  
   network topology, discovering, 103–105  
   performance, establishing, 105–109  
 basic-5ess switch types (ISDN), 259–260  
   SPIDs, configuring, 260–262  
 BBFW (Broadband Fixed Wireless) P2MP  
   solutions, 53  
 Bc (committed burst rate), 434  
 Be (excess burst rate), 434  
 bearer services, Frame Relay, 438  
 BECNs (backward explicit congestion  
   notifications), 441–443, 536  
   Frame Relay Address field bit, 421  
 BERTs (bit error rate testers), testing T1 circuits,  
   183–184  
 bidirectional procedures, 439  
 billing expenses, 7  
 binary phase-shift keying (BPSK), 50  
 BISDN (Broadband ISDN), 235  
 bit errors, checking on T1 circuits, 183–184  
 bit-robbing signaling, 65

- blue alarms, 185
  - Boosted Session Transport, 29, 750
  - BPSK (binary phase-shift keying), 50
  - BRI (Basic Rate Interface), 57, 237–241
    - D channel, testing, 327
    - developing troubleshooting process in remote services environments, 359
      - accessing remote user's router, 365–369
      - preconfiguring routers on both ends, 364–365
    - end-to-end communications, 386
      - routing issues, resolving, 399
      - troubleshooting LEC switch settings, 387
    - initializing, 241
    - keepalive mechanism, 323
    - performance issues
      - LEC switch problems, 382–386
      - line problems, 377–382
      - routing, 377
      - settings, 382
    - service layers, viewing, 360–363
    - SPIDs, 253
  - bridging Frame Relay, 474, 476
  - broadband wireless services, 25
    - limitations of, 27
    - LMDS, 26–27
    - MMDS, 25–26
    - unlicensed frequencies, 27
  - broadcast queues, Frame Relay configuration, 468
  - BST (Boosted Session Transport), 29, 750
  - budgeting remote access costs, 6
  - bursty traffic, 414
- C**
- 
- C/R (Command/Response) bit, Frame Relay
    - Address field, 421
  - cable modems, 740
    - services, 20
      - limitations of, 22
      - standards, 21
  - cabling
    - long versus short lengths, 183
    - shorts, detecting, 223
  - calculating
    - CIR, 435
    - ISDN BRI load at full utilization, 376
    - maximum DLCIs per interface, 467
    - RER, 444
  - call clearing messages, 251
  - Call Reference field (Q.931 messages), 249
  - callback function, PPP, 344–347
    - ISDN configuration, 303–305
  - called-party number verification, 306
  - caller ID screening, 306
  - calling IOS routers from IOS 77x routers, 366–369
  - CAP (carrierless amplitude/phase modulation), 44
  - Capacity Theorem, 38
  - captured Log Viewer results, viewing, 688–699
  - carrierless amplitude/phase modulation (CAP), 44
  - carriers, 69
    - CO, 81
    - first-tier exchange carriers, 80
    - IXCs, 81
    - switching systems, 70–71
    - tandem office, 83
    - T-carriers, 75
      - E1, 77
      - T1, 76–77
  - categories of ISDN network designs, 258–259
  - CATV (cable TV)
    - cable modems, 20–22, 740
    - data transmission, 740
      - standards, 741–744
    - heartbeats, 745
    - two-way Internet connections, 744
  - Cause messages (ISDN BRI), 331–334
  - CCITT (Comité Consultatif International Téléphonique et Télégraphique), 12
  - CCP (Compression Control Protocol), 352
  - CCS (common channel signaling), 78
  - CDMA2000 1xEV, 91
  - CDP (Cisco Discovery Protocol), discovering network topology, 103

- CDSL (consumer DSL), 24
- cell switching, 70
- CERT (Computer Emergency Response Team), 77
- Challenge Handshake Authentication Protocol (CHAP), 340
- change management of remote access VPNs, 636
- channel banks, 73
- channels, ISDN, 234
- CHAP (Challenge Handshake Authentication Protocol), 340
- charge backs, 7
- Chinese Remainder Theorem, 625
- CIR (committed information rate), 435
  - adjustable CIRs, 437
  - aggregate CIR, 436–437
  - asymmetrical CIR, 437
  - flexible CIR, 437
  - zero CIR, 436
- circuit switching, 70
- Cisco Discovery Protocol, 103
- Cisco Easy VPN client, 713
  - client status, displaying, 716
  - debugging IPSec key events, 717–719
  - initial troubleshooting checklist, 714, 716
  - monitoring, 720–721
  - resetting connection, 717
  - restrictions, 713–714
- Cisco IOS
  - 77x routers, accessing ISDN routers, 366–369
  - commands, 102
  - ISDN
    - available phone services, 309–310
    - voice privacy, configuring, 308–309
  - NFAS groups, 393
- Cisco Mobile Office initiative, 8–9
- Cisco PIX VPN clients
  - 501 VPN Client, configuring, 669–670
  - 506 VPN Client, configuring, 669–671
  - connectivity, verifying, 722–732
  - restrictions, 722
- Cisco UBR7200 Series routers, 21
- Cisco UBR7246 Universal Broadband Router, 26
- Cisco VPN 3000 Concentrator, IPSec over UDP, 639
- Cisco VPN 3002 router
  - connection establishment, 795–796
    - verifying group name/password, 800
    - verifying interface status, 797–799
  - HW Client, 706
    - configuring, 665–666
    - Event Log, 708–712
    - initial troubleshooting checklist, 707
- Cisco VPN IOS Client, configuring, 666–668
- Cisco VPN Unity client, 663–664
  - Concentrator Event Log, 699–701
    - event classes, 702–704
    - event security levels, 704–705
  - Event Log Viewer, 685
    - Client Log Viewer, starting, 686
    - ISAKMP, 688
    - reviewing captured data, 688–699
  - incompatible GINAs, 705–706
  - restrictions, 676–679
  - troubleshooting checklist, 682–685
- classifying
  - enterprise VPNs, 593–595
    - data link layer VPNs, 599–603
    - firewall-based VPNs, 597–598
    - network VPNs, 604–607
    - remote access VPNs, 595
    - site-to-site VPNs, 596
  - troubleshooting tools, 110
- clear interface bri0 command, 318
- CLECs (competitive LECs), 80, 732
- client authentication, 619
- Client mode configuration, Cisco VPN 3002 routers, 706
- CLLM (consolidated link-layer management), 442–443
- clocking issues, 55
  - Frame Relay
    - isolating, 499–500
    - troubleshooting, 493–498
  - SCTE, 499
- CO (central office), 81
- code values for LMIs, 520–521
- codexs, 73

- coded orthogonal FDM (COFDM), 52
- coding schemes
  - 2B1Q, 55–59
  - AMI, 61, 130
  - B8ZS, 131–132
  - COFDM, 52
  - DSL, 41–42
  - HDB3, 132
  - pseudo-ternary signaling, 55–57
  - WLANs, 48
  - zero-suppression, 61–62
- COFDM (coded orthogonal FDM), 52
- Comité Consultatif International Téléphonique et Télégraphique (CCITT), 12
- commands
  - AS5200 series routers, 207–209
  - AS5300 series routers, 209–214
  - AS5400 series routers, 215
  - clear interface bri0, 318
  - debug bri, 316–317
  - debug interface serial, 523–524
  - debug isdn q931, 325, 328
  - debug ppp negotiation, 220–221
  - debug ppp authentication, 340
  - extended ping, 111
  - isdn autodetect, 262
  - isdn timeout signaling, 318
  - logging console, 548
  - loopback, troubleshooting T1 circuits, 183
  - mtrace, 578
  - ping, 110–114
    - replies, 112
    - syntax, 110
  - service timestamps, 313
  - short format, 102
  - show cdp neighbors, 103
  - show controllers bri0, 316
  - show dialer, 373–374
  - show interface serial 0, 502–505
  - show isdn active, 372
  - show isdn status, 315, 320, 360–363
  - show modem operational status, 224
  - tracert, 114–115
  - committed burst rate (Bc), 434
  - committed interval (Tc), 434
  - comparing
    - remote access and site-to-site VPNs, 633–634
    - X.25 and Frame Relay features, 414–415
  - components of Frame Relay networks, 419
  - compression, Frame Relay, 476–477, 538, 540–543
    - hardware compression, 537
    - payload compression, 480–481
    - software compression, 542–543
    - Van Jacobson header compression, 477–480
  - Concentrator Event Log, 699–701
    - event classes, 702–704
    - event security levels, 704–705
  - configuration management of remote access
    - VPNs, 635
  - configuration negotiation phase (LCP), 335–336
  - configuring
    - DDR
      - backup, 173–176
        - with backup interfaces, 147
        - with dialer watch, 148
        - with floating static routes, 148
    - dialer profiles, 297, 299–303
    - dial-in
      - large-scale, 160–164
      - PPP dial-in, 151–159
      - text dial-in, 150–151
    - dial-out
      - large-scale, 171–173
      - PPP dial-out, 168–171
      - text dial-out, 164–168
    - Frame Relay
      - bridging, 474–476
      - broadcast queues, 468
      - compression, 476–477
      - frame switching, 469–470
      - generic traffic shaping, 484–486
      - IP multicast, 482–483
      - IP unnumbered, 469
      - ISDN backup, 471–473
      - payload compression, 480–481
      - point-to-multipoint connections, 458–461

- point-to-point connections, 461–466
- routing protocol overhead estimates, 467–468
- traffic shaping, 483–488
- Van Jacobson header compression, 477–480
- ISDN
  - BRI, bandwidth on demand, 376
  - DDR, 294–303
  - IP pools, 262–265
  - MMP, 278–284
  - NAT, 267–271
  - PAT, 266–267
  - per-user configuration, 272–273
  - POTS interfaces, 306–308
  - PPP callback, 303–305
  - snapshot routing, 290–292
  - SPIDs, 260–262
  - spoofing, 290
  - switch type, 259–260
  - voice privacy, 308–309
- PPP callback, 304–305
- remote access VPNs
  - Cisco PIX 501 VPN Client, 669–670
  - Cisco PIX 506 VPN Client, 669, 671
  - Cisco VPN 3002 HW Client, 665–666
  - Cisco VPN IOSClient, 666–668
  - Cisco VPN Unity Client, 663–664
- VPN 3000 Concentrator, 648–649
  - filters and rules, 650–651
  - Group Lock, 662
  - IKE peer identity validation, 662
  - IKE proposals, 656, 658–659
  - IPSec SAs, 661
  - load balancing, 654–655
  - redundancy, 653
  - reverse route injection, 655
  - SAs, 659–660
- congestion control mechanisms, Frame Relay, 441
  - BECNs, 536
  - CLLM, 443
  - FECNs, 535
  - rate adoption algorithm, 442
  - windowing, 443
- connection speeds
  - increasing, 226
  - limitations of, 128
  - of modems, 126–127
- connection termination phase (PPP), 352–353
- connectionless data integrity, 608, 614
- connectivity
  - of Cisco PIX VPN client, verifying, 722–732
  - testing, 110–117
- console logging, 548
- Consortium LMI, 513–515
  - Status Enquiry message format, 514–515
  - Status message format, 515
- constellations, 40
- contention resolution, 57
- Control field
  - LAPD frames, 244–245
  - LAPF control protocol, 424–425
  - PPP frames, 135
- control LAPF, 419
- Control plane. *See* C-plane
- core aspects of Frame Relay, 413
- core LAPF, 419
- core routers, 257
  - DLCI settings, verifying, 560–562
  - Frame Relay point-to-multipoint configuration, 458–460
  - IP pool assignment, 262, 264–265
  - NFAS groups, 393
  - point-to-point Frame Relay configuration, 462–465
- corporate managed services, 8
- cost-effective ISDN solutions
  - DDR, 294–295
    - dialer profiles, 296–303
  - PPP callback, 303–305
  - snapshot routing, 290–292
  - spoofing, 290
- costs of remote access, budgeting, 6
- counter parameters for LMIs, 521, 523
- CPE (customer premises equipment), 5
- C-plane, 236, 417–418

creating  
   dial peers, 307–308  
   VPN client profiles, 772  
 CSU/DSU (channel service unit/data service unit)  
   pinouts, 499  
 custom design ISDN switches, 260  
 customer premises equipment (CPE), 5

## D

D (Delta) channel, 234  
   Layer 1, 237–241  
     devices, 238  
     interfaces, 239–241  
   Layer 2, 242  
     LAPD frame format, 242–247  
     logical link establishment, 246–247  
   Layer 3, 248  
     Q.931 message format, 248–252  
     TDM, 393  
     testing, 327  
 D/C (data/control) bit (Frame Relay Address field), 421  
 DACs (digital-to-analog converters), 39  
 DARPA (Defense Advanced Research Projects Agency), 97  
 data centers, 87–89  
 Data Encryption Standard, 617  
 Data field (LAPD frames), 246  
 Data field (PPP frames), 135  
 data link connection identifiers. *See* DLCIs  
 data link layer (OSI model), 98  
   Frame Relay, 506  
     LMI issues, 513–526  
     misconfigured PVCs, 507–513  
   ISDN BRI, 319–324  
 data link layer protocols, 599–601  
   L2TP, 602–603  
   PPTP, 600–601  
   PPP, 134  
     Authentication phase, 136, 396–398  
     frame fields, 134–135  
     LCP, troubleshooting, 387–396  
     Link Dead phase, 135  
     Link Establishment phase, 135–136  
     Link Termination phase, 137  
     Network Layer Protocol phase, 137  
     troubleshooting, 138  
 data transmission over CATV, standards, 740–744  
 dB (decibel), 128  
 DBS (Direct Broadband Satellite) systems, 28  
   BST, 29, 750  
   FITFEEL protocol, 751  
   IPA, 28  
   IPSec, 752–753  
   LEO satellites, 30  
   manipulating TCP stack, 749–750  
   performance, 749  
   VPNs, 745–746  
     bandwidth, 747–748  
     error control coding, 746  
 DDR (dial-on-demand routing), 294–295  
   configuring, 173–176  
     with backup interfaces, 147  
     with dialer watch, 148  
     with floating static routes, 148  
   dialer profiles, 296  
     configuring, 297–303  
     Windows 2000, 399–408  
 DDS (Dataphone Digital Service), 495  
 DE (discard eligible) bit, Frame Relay Address field, 421, 434  
 debug bri command, 316–317  
 debug information, timestamping, 313–314  
 debug interface serial command, 523–524  
 debug isdn q931 command, 325, 328  
 debug ppp authentication command, 340  
 debug ppp negotiation command, 220–221  
 debugging  
   Cisco Easy VPN client connection, IPSec key events, 717–719  
   Frame Relay LMI, 552  
 Defense Advanced Research Projects Agency (DARPA), 97  
 defining service levels, 9  
 delivered erroneous frames, 445  
 demand circuits (OSPF), 293



- demodulation, 39
- dense mode (PIM), Frame Relay multicast
  - configuration, 482–483
- design objectives of remote access VPNs, 634–635
- designing
  - enterprise services, 30–34
  - Frame Relay network parameters, 434
    - CIR, 435–437
  - ISDN networks
    - hub and spoke, 257
    - IP pools, 262–265
    - MLP, 273–277
    - MMP, 278–285
    - NAT, 267–271
    - PAT, 266–267
    - per-user configuration, 272–273
- Destination Unreachable messages (ICMP), 113–114
- detecting
  - dirty phone lines, 223–224
  - shorts in modem cables, 223
  - source of frequent disconnections, 226
- devices
  - AS5200 routers, commands, 207, 209
  - AS5300 routers, commands, 209–214
  - AS5400 routers, commands, 215
  - AS5x00 routers, 205–207
  - cable modems, 740
  - codecs, 73
  - Frame Relay, 419
  - ISDN, 238
    - switch types, 252–253
  - modems, 125
    - 56-k flex modems, 14
    - analog, 126
    - analog dialup services, 12–13
    - bandwidth, 126
    - cable modem services, 20
    - connection speeds, 126–127
    - digital, 126
    - malfunctioning, 225
    - PCM, 13
    - Shannon's Capacity Theorem, 12
    - repeaters, 126
  - DH (Diffie-Hellman) algorithm, 624–627
  - DHCP (Dynamic Host Configuration Protocol)
    - servers, verifying reachability, 227
  - dial peers, creating, 307–308
  - dial-back authentication, 134
  - dialer maps, 294
  - dialer profiles, 294–296
    - configuring, 297–303
  - dialer watch, DDR configuration, 148
  - dial-in
    - large-scale dial-in, configuring, 160–164
    - PPP dial-in
      - configuring, 151–159
      - network design, 143–144
    - text dial-in
      - configuring, 150–151
      - network design, 143
  - troubleshooting procedure
    - verifying incoming connection type, 192–194
    - verifying modem operability, 191–192
    - verifying PPP negotiation, 194–200
- dial-on demand backup routing, configuring
  - with backup interfaces, 147
  - with dialer watch, 148
  - with floating static routes, 148
- dial-out
  - ISDN, 372–374, 376
  - large-scale, 146
    - configuring, 171–173
  - PPP dial-out
    - configuring, 168–171
    - network design, 145
  - text dial-out
    - configuring, 164–168
    - network design, 144
  - troubleshooting procedure, 200–205
- dial up
  - 800 toll-free numbers, 13
  - analog, 12–14
  - authentication
    - PAP, 133

- servers, 133
  - time outs, 219–221
- disconnections, isolating source of, 221–223
- Frame Relay, 17
  - benefits of, 18
  - limitations of, 18
  - standards, 17–18
- ISDN, 14
  - benefits of, 15–16
  - limitations of, 16
- PPP, 134
  - Authentication phase, 136
  - frame fields, 134–135
  - Link Dead phase, 135
  - Link Establishment phase, 135–136
  - Link Termination phase, 137
  - Network Layer Protocol phase, 137
  - troubleshooting, 138
- retrains, 221–223
- diffused-beam WLANs, 45
- digital modems, 126
- digital pads, echo cancellation, 129–130
- digital sampling, Nyquist’s sampling theorem, 39
- digital transmissions, clocking, 55
- digitalization of voice, 73
- digital-to-analog converters (DACs), 39
- Direct Broadband Satellite. *See* DBS systems
- direct-beam WLANs, 45
- direct sequence spread spectrum (DSSS), 49
- dirty phone lines, as source of slow line speeds, 223–224
- discard eligible (DE), 434
- disconnections, troubleshooting, 221–223
- Discrete Multi-Tone. *See* DMT
- displaying
  - Cisco Easy VPN client status, 716
  - ISDN BRI service layers, 360–363
- distance vector routing protocols,
  - size estimation, 467
- DLCIs (data link connection identifiers), 421
  - channel assignments, 422–423
- CIR, 435
  - aggregate CIR, 436–437
  - asymmetrical CIR, 437
  - flexible CIR, 437
  - zero CIR, 436
- mismatched settings, troubleshooting, 556–562
- per interface limitations, 466–467
- DMT (Discrete Multi-Tone), 42–44
  - CAP, 44
  - SF structure, 43
- DOCSIS (Data-Over-Cable Service Interface Specifications), 741–744
  - satellite communications, 54
- DoD (Department of Defense) interconnection model, 97
- down interfaces, troubleshooting Frame Relay new installs, 548–552
- DPD (Dead Peer Detection), 803–804
- dropped calls (ISDN), resolving 22 second issue, 387–396
- DS0, 77
- DSL (digital subscriber line)
  - coding schemes, 41–42
  - PPoE, 733
    - discovery stage, 735
    - negotiations, 736–737, 739
    - session stage, 736
- xDSL services, 22
  - ADSL, 24
  - CDSL, 24
  - FDIs, 22–23
  - HDSL, 24
  - IDSL, 24
  - RADSL, 24
  - SDSL, 24
  - TDRs, 23
  - VDSL, 25
- DSLAMs (digital subscriber line access multiplexers), 733
- DSSS (direct sequence spread spectrum), 49

## E

---

- E1, 77
- EA (extended address) bit (Frame Relay Address field), 421
- echo, removing, 129–130
- Effective Isotropic Radiated Power (EIRP), 50
- EFM (Ethernet to the First Mile), 596
- ELMI (Enhanced Local Management Interface), 567
  - Foresight adaptive shaping, 487–488
- enabling ForceKeepAlive, 787
- encapsulation
  - DDR backup solutions, 148
  - over Frame Relay, 447
- encoding schemes
  - 2B1Q, 55, 58–59
  - AMI, 61
  - COFDM, 52
  - zero-suppression, 61–62
- encryption
  - AES, 618
  - DES, 617
  - remote access VPNs, 638
- endpoint migration, Frame Relay, 584–585
- end-to-end communications
  - Frame Relay, 528–533
  - ISDN BRI, 386
    - 22 second issue, 387–396
    - LEC switch settings, 387
    - PPP authentication, 396–398
    - routing issues, 399
- end-user routers (ISDN), 257
  - configuring, 262
- enterprise ISDN networks, 258–259
- enterprise remote access services, provisioning, 30–34
  - Frame Relay, 31–33
  - ISDN, 31, 33
  - xDSL, 33–34
- enterprise VPNs, 593–594
  - categories of, 595
  - data link layer, 599–601

- L2TP, 602–603
- PPTP, 600–601
- firewall-based, 597–598
- network layer layer, 604
  - Layer 3 tunneling, 605
  - SAs, 605–607
- remote access, 595
- site-to-site, 596

errors on T1 circuits, 187

- E-Series protocols, 14, 233
- ESF (Extended Super Frame) signal format, 63
- ESP header format, 616–618
- establishing baseline behavior
  - network topology, 103–105
  - performance characteristics, 105–109
- estimating transit delay, 444
- ET (Exchange Termination), 238
- Ethernet to the First Mile (EFM), 596
- Event Log, Cisco VPN 3002 HW client, 708–712
- excess burst rate (Be), 434
- expenses, billing, 7
- extended bus architecture (ISDN), 237
- extended ping command, 111

## F

---

- far end, 96
- far-end crosstalk (FEXT), 23
- fast busy signals, debugging, 226
- fast-dial, 15
- Fast Information Transfer For Extremely Errored Links (FITFEEL) protocol, 751
- FCS (frame check sequence) field
  - Frame Relay frames, 420
  - LAPD frames, 246
  - PPP frames, 135
- FDIs (Feeder Distribution Interfaces), 22
- FDM (frequency-division multiplexing), 71–72, 414
  - DMT, 42
- FECNs (forward explicit congestion notifications), 421, 441–443, 535

- Feeder Distribution Interfaces (FDIs), 22
- Fermat/Euler Theorem, 625
- FEXT (far-end crosstalk), 23
- FHSS (frequency hopping spread spectrum), 48
- fiber-optic networks, SONET, 80
- fields
  - of ICV, 608–610
  - of LAPD frames
    - Address field, 244
    - Control field, 244–245
    - Data field, 246
    - FCS field, 246
    - Flag field, 243
  - of PPP frames, 134–135
- filter GINAs, 705
- firewall-based VPNs, 597–598
- firewalls, implementing in remote access VPNs, 640–641
- first-tier exchange carriers, 80
- FITFEEL (Fast Information Transfer For Extremely Errored Links) protocol, 751
- Flag field
  - Frame Relay frames, 420
  - LAPD frames, 243
  - PPP frames, 134
- flapping lines, 562–566
- flapping links, 526–528
- flapping routes, 572
- floating static routes, DDR configuration, 148
- ForceKeepAlive, enabling, 787
- Foresight adaptive shaping ELMI, 487–488
- fragmentation process, 610
  - Frame Relay, 448
- Frame Relay, 17
  - addressing
    - ARP, 453
    - Inverse ARP, 454
    - RARP, 454
  - ANSI standards, 415
  - benefits of, 18
  - bidirectional procedures, 439
  - bridging, 474, 476
  - broadcast queues, 468
  - CIR, 435
    - aggregate CIR, 436–437
    - asymmetrical CIR, 437
    - flexible CIR, 437
    - zero CIR, 436
  - compression, 538, 540–543
    - configuring, 476–477
    - hardware compression, 537
    - software compression, 542–543
  - congestion control mechanisms, 441
    - CLLM, 443
    - rate adoption algorithm, 442
    - windowing, 443
  - core aspects, 413
  - C-plane, 417–418
  - CSU/DSU pinouts, 499
  - data link layer troubleshooting, 506
    - LMI issues, 513–526
    - misconfigured PVCs, 507–513
  - design parameters, 434
  - DLCIs
    - mismatched settings, troubleshooting, 556–562
    - per interface limitations, 466–467
  - ELMI, 487–488
  - end-to-end connectivity, 528–533
  - flapping lines, 563–566
  - flapping links, 526–528
  - frame switching configuration, 469–470
  - full-mesh topology, 441
  - generic traffic shaping, 484–486
  - host migration, 580–585
  - IAs, 415–416
  - initial troubleshooting steps, 492–493
  - IP multicast, 440
    - checking IGMP group members, 576–577
    - checking upstream neighbor availability, 574–576
    - configuring, 471–473
    - group flags, 573
    - multicast trace reporting, 577–580
    - testing remote user's router, 577

- IP unnumbered configuration, 469
  - ISDN backup configuration, 471–473
  - LAPF
    - control protocol, 424
      - Control field, 424–425
      - Information field, 426–429
    - logical frame processing, 422
    - T1.618 frame format, 419–423
  - limitations of, 18
  - LMIs, 449
    - Annex D, 451
    - Cisco-Consortium, 451
    - code values, 520–521
    - counter parameters, 521, 523
    - ITU-T Q.933 Annex A, 453
    - timers, 522
  - multiplexing, 414
  - network components, 419
  - new install issues, 548–556
  - NNI, 439
  - partial-mesh topology, 441
  - payload compression, configuring, 480–481
  - performance parameters, 562
    - RER, 444
    - throughput, 444
    - transit delay, 444
  - physical layer
    - clocking problems, 493–498
    - DSU/CSU, testing, 501
    - loopback testing, 500
    - performance issues, 501–505
  - point-to-point connections
    - configuring, 461
    - hub configuration, 462, 464
    - spoke configuration, 465–466
  - provisioning enterprise remote access services, 31–33
  - pseudo-ternary signaling, 55–57
  - QoS parameters, 445
  - remote user router, verifying status, 553
  - serial interface configuration, verifying, 551
  - service architecture, VCs, 418
  - service functioning, checking, 553–555
  - standards, 17–18
  - traffic shaping, 483–484, 534
    - BECNs, 536
    - FECNs, 535
    - flapping routes, investigating, 572
    - high RTT numbers, investigating, 567–569
    - map classes, 486–487
    - slow performance, investigating, 569–572
    - verifying settings, 566
  - UNI, 438
  - upper-layer protocol interoperability, 445
    - encapsulation, 447
    - fragmentation, 448
    - multiprotocol support, 445–447
  - Van Jacobson header compression. configuring, 477–480
  - variable length framing, 415
  - VCs, 415
  - versus X.25, 414–415
  - VoFR, 440
- framing techniques
- ESF, 63
  - T1, 62
    - ESF signal format, 63
    - SF signal format, 62–63
  - T3, M23 signal format, 63–64
- frequency, 40
- frequency-division multiplexing. *See* FDM
- frequency-shift keying (FSK), 40
- frequent disconnections, detecting source of, 226
- FRF (Frame Relay Forum) IAs, 415–416
- FSK (frequency shift-keying), 40
- full-mesh topology, Frame Relay, 441
- funding remote access, 6
- 
- ## G
- Gang of Four, 449
  - generic traffic shaping, 484–486

- geographic requirements for remote access deployment, 7
- GINA, 705
- global dialer software, 13
- group flags, 573
- Group Lock parameter, configuring on VPN 3000 Concentrators, 662
- group members, 573
- GSM/GPRS (Global System of Mobility/General Packet Radio Service), 91

## H

- H (Hybrid) channel, ISDN, 234
- hardware compression, 537
- hardware simulators, 110
- Hash-based Message Authentication Code (HMAC), 627–628
- HDB3 (high density binary 3), 132
- HDSL (high-data rate DSL), 24
- heartbeats, 745
- helpdesks, supporting remote access users, 7
- HFC (hybrid fiber-coaxial) networks, 20
- HMAC (Hash-based Message Authentication Code), 627–628
- host migration, Frame Relay, 580–585
- Host Page Accelerator (HPA), 28
- hosting services, 87–89
- HPA (Host Page Accelerator), 28
- hub and spoke network design, 142
  - ISDN, 257
- hub configuration
  - Frame Relay point-to-multipoint configuration, 458–460
  - point-to-point Frame Relay connections, 462, 464–465
- hybrid systems, 20
  - line-coding techniques, 53–54
  - modulation, 53–54

- IAs (Implementation Agreements), 415–416
- ICMP (Internet Control Message Protocol), message types, 112–113
  - Destination Unreachable, 113–114
- IDBs (interface descriptor blocks), 273
- IDSL, 24
- IE (information element) fields, LAPF control protocol, 426–429
- IEEE 802.11a specification, 51–52
- IEEE 802.11e specification, 53
- IEEE 802.11g specification, 52
- IGMP (Internet Group Message Protocol)
  - group members, verifying on Frame Relay networks, 576–577
- IKE (Internet Key Exchange)
  - key management, 624–627
  - peer identity validation, configuring on VPN 3000 Concentrators, 662
  - proposals, configuring on VPN 3000 Concentrators, 656–659
  - remote access VPN authentication, 638
- ILECs (incumbent LECs), 80, 732
- illegal serial line type xx messages, 524
- immutable ICV fields, 608–610
- incompatible GINAs, 705–706
- increasing slow connection speeds, 226
- Information Elements field (Q.931 messages), 251–252
- Information field
  - Frame Relay frames, 420
  - LAPF control frames, 426–429
- information transfer messages, 245
- initial troubleshooting steps, Frame Relay, 492–493
- in-sourcing remote access support, 7
- installation issues, Frame Relay, 548–556
- interconnection models
  - DoD, 97
  - OSI, 98–100
- interfaces, 469
  - Frame Relay, broadcast queues, 468
  - ISDN, 239–241

- internal standard PCI modems, 21
- International Telecommunication Union
  - Telecommunication Standardization Sector.
    - See* ITU-T
- Internet hosting services, 87–89
- Internet Page Accelerator (IPA), 28
- interoperability of Frame Relay and upper-layer protocols, 445
  - encapsulation, 447
  - fragmentation, 448
  - multiprotocol support, 445–447
- Inverse ARP (Address Resolution Protocol), 454
- IOS-based troubleshooting methods, 102
- IP addressing, ISDN configuration
  - NAT, 267–271
  - PAT, 266–267
- IP datagrams, fragmentation, 610
- IP multicast
  - Frame Relay networks, 482–483
    - multicast trace reporting, 577–580
    - remote user's router, testing, 577
    - verifying IGMP group members, 576–577
    - verifying upstream PIM neighbor availability, 574–576
  - group flags, 573
- IP pools, defining, 262, 264–265
- IP unnumbered Frame Relay configuration, 469
- IPA (Internet Page Accelerator), 28
- ipconfig command (Windows NT/2000), verifying
  - IP addressing configuration, 769–770
- IPSec
  - AH, 614–615
  - authenticating remote access VPNs, 638
  - connectionless data integrity, 608
  - ESP header, 616–618
  - ICMP processing, 611–612
  - ICV calculation, 615
  - ICV fields, 608–610
  - IP fragmentation, 610
  - modes, 612
  - over satellite systems, 752–753
  - over TCP, 640
  - PMTU discovery, 610–611
  - SAs, configuring on VPN 3000 Concentrators, 661
    - selecting mode for remote access VPNs, 637
- IR (infrared) radio-channel, 45
- ISAKMP (Internet Security Association and Key Management Protocol), 688
- ISDN (Integrated Services Digital Network), 14
  - accessing routers from IOS 77x routers, 366–369
  - B channel, 234
  - benefits of, 15–16
  - channels, 234
  - C-plane, 236
  - custom design switches, 260
  - D channel, 234
    - TDM, 393
  - data link layer, activation procedure, 320–321
  - DDR, 294–295
    - dialer profiles, 296–303
  - design solutions
    - NAT, 267–271
    - PAT, 266–267
  - dial-out, 372–374, 376
  - H channel, 234
  - hub and spoke design, 257
  - IP pools, configuring, 262, 264–265
  - Layer 1, 237–238, 241
    - devices, 238
    - interfaces, 239–241
  - Layer 2, 242
    - LAPD frame format, 242–247
    - logical link establishment, 246–247
  - Layer 3, 248
    - Q.931 messages, 248–252
  - limitations of, 16
  - load interval, 376
  - local loop, 234
  - MLP, 273–277
  - MMP, 278, 280
    - configuring, 281–282
    - sample implementation, 282–284
    - verifying, 284–285

- network design, categories of, 258–259
- new install issues, 369, 371
- NISDN, 235
- per-user configuration, 272
  - virtual interface templates, 272
  - virtual profiles, 273
- POTS interfaces, configuring, 306–308
- PPP
  - callback, 303–305
  - LCP, 387–396
- PRI
  - 1.544-Mbps interface, 64–65
  - 2.048-Mbps interface, 65
- PRI circuits, 188
  - Layer 1 status, verifying, 188
  - Layer 2 status, verifying, 188–190
- provisioning enterprise remote access services, 31–33
- pseudo-ternary signaling, 55–57
- security, 305
- snapshot routing, 290–292
- SPIDs, 253
- spoofing, 290
- supplementary phone services, 309–310
- switch types, 252–253, 259–260
- voice privacy, configuring, 308–309

isdn autodetect command, 262

ISDN BRI

- bandwidth on demand, configuring, 376
- developing troubleshooting process in remote services environment, 359
  - accessing remote user's router, 365–369
  - preconfiguring routers on both ends, 364–365
  - viewing service layers, 360–363
- end-to-end communications, 386
  - resolving routing issues, 399
  - troubleshooting LEC switch settings, 387
- keepalive mechanism, 323
- performance issues
  - LEC switch problems, 382–386
  - lines, 377–382
  - routing, 377
  - settings, 382

- isdn timeout-signaling command, 318
- I-series protocols, 234
- isolating Frame Relay clocking problems, 499–500
- ISPs, 85–86
  - ISDN networks, 258–259
- ITFS (Instructional Television Fixed Service), 25
- ITU-T (International Telecommunication Union Telecommunication Standardization Sector), 12
  - E-series protocols, 233
  - I-series protocols, 234
  - Frame Relay standards, 415
  - Q.933 Annex A, 453
  - Q-series protocols, 234
- IXCs, 81

## J-L

- keepalive mechanism
  - ISDN BRI, 323
  - spoofing, 290
- key management, 624–627
- L2TP (Layer 2 Tunneling Protocol), 602–603
- LAN-specific VPN issues
  - inability to log in, 760
  - MTU settings, 754–756, 758
  - NAT, multiple client handling, 753
  - packet size, 758, 760
- LAN-to-LAN VPNs, 596
- LAPD (Link Access Procedure on the D channel), 242, 248
  - Address field, 244
  - Control field, 244–245
  - Data field, 246
  - FCS field, 246
  - Flag field, 243
  - frame format, 242–247
  - logical link establishment, 246–247
- LAPF
  - control protocol, 424
    - Control field, 424–425
    - Information field, 426–429



- T1.618 frame format, 419
  - Address field, 421–423
  - fields, 420
  - Flag field, 420
  - logical frame processing, 422
- large-scale dial-in, configuring, 160–164
- large-scale dial-out
  - configuring, 171–173
  - network design, 146
- last mile, 90–91
- LATAs (local access and transport areas), 80
- layer 1/2 status of PRI circuits, verifying, 188–190
- Layer 3 tunneling, 605
- layered architecture
  - DoD model, 97
  - ISDN
    - BRI, 237–241
    - C-plane, 236
    - LAPD, 242–244, 246–248
    - Q.931, 248–249, 251–252
  - OSI Reference Model, 98–100
- layered approach to troubleshooting, 96
- LCP (link control protocol) phase of PPP, 194–196
  - configuration negotiation phase, 335–336
  - magic numbers, 339
  - troubleshooting, 335–339
- LDN (local directory number), 308
- LDNs (Local Directory Numbers), 252
- LE (Local Exchange), 238
- LEC (local exchange carrier) switch problems,
  - ISDN
    - end-to-end communications, 387
    - performance issues, 382–386
- legacy DDR, 294–295
- limitations
  - of analog dialup services, 14
  - of analog modem connection speeds, 128
  - of cable modems services, 22
  - of Cisco Easy VPN client, 713–714
  - of Cisco PIX VPN client, 722
  - of Cisco Unity client, 676–679
  - of ISDN services, 16
  - of wireless broadband services, 27
- line coding techniques
  - B8ZS, 131–132
  - errors, 130
  - HDB3, 132
  - in hybrid networks, 53–54
  - in wireless LANs, 44–45
- line problems
  - Frame Relay, investigating, 493–498
  - ISDN performance issues, 377–382
- line provision, verifying, 354
- linecode violations of T1 circuits, 186
- link compression, 477
- Link Dead phase (PPP), 135
- Link Establishment phase (PPP), 135–136, 335–339
- link speeds, 434
- Link Termination phase (PPP), 137
- link-state protocols
  - OSPF, demand circuits, 293
  - size estimation, 467–468
- listen option (Netcat utility), 117
- LMDS (Local Multipoint Distribution Service), 25–27
- LMIs (Local Management Interfaces), 449
  - ANSI T1.617 Annex D, 516, 518–520
  - Annex D, 451
  - Cisco-Consortium, 451
  - code values, 520–521
  - Consortium LMI, 513–515
    - Status Enquiry message format, 514–515
    - Status message format, 515
  - counter parameters, 521, 523
  - debugging, 552
  - ITU-T Q.933 Annex A, 453
  - timers, 522
- load balancing, configuring on VPN 3000
  - Concentrators, 654–655
- load interval, 376
- local loop, 234
- Local Multipoint Distribution Service, 25–27
- log files, timestamping, 313–314
- logging console command, 548
- logical frame processing, LAPF, 422
- logical link establishment (LAPD), 246–247

- long cable lengths, 183
- loopback command, troubleshooting T1 circuits, 183
- loopback testing, Frame Relay, 500
  - magic numbers, 339
- lost frames, 445
- LT (Local Termination), 238
- LTI (linear time-invariant) systems, 47

## M

---

- magic numbers, 339
- malfunctioning modems, detecting, 225
- managing Frame Relay host migration, 580–585
  - endpoint migration, 583–585
  - host preparation, 581–583
  - routing options, 583
- mandatory user participation, troubleshooting ring options, 354–355
- map classes, defining, 486–487
- marking malfunctioning modems, 225
- MDF (main distribution frame), 81
- message switching, 70
- Message Type field (Q.931 messages), 249–250
- messages
  - CLLM, 442
  - ICMP, 112–113
    - Destination Unreachable, 113–114
  - illegal serial line type xxx, 524
  - ISDN BRI Cause Messages, 331–332, 334
  - SABME, 322
- M-frames, 63
- Microsoft Windows 2000, DDR troubleshooting procedures, 399–408
- migration strategies, Frame Relay, 580–585
  - endpoint migration, 583–585
  - host preparation, 581–583
  - routing options, 583
- minimum acceptable throughput, 435
- misconfigured PVCs, troubleshooting, 507–513
- misdelayed frames, 445
- mismatched DLCI settings, investigating, 556–562
- MLP (multilink PPP), 273–277, 343–344
- MMDS (Multichannel Multipoint Distribution System), 25–26, 53
- MMP (Multichassis Multilink PPP), 278–280, 347–351
  - configuring, 281–282
  - sample implementation, 282–284
  - verifying configuration, 284–285
- mobile solutions, 8–9
- modems, 125
  - 56-kbps flex, 14
  - analog, 126
    - signal loss, 127
  - analog dialup services, 12–13
    - limitations of, 14
    - VPNs, 13
  - authentication timeouts, 219–221
  - bandwidth, 126
  - cable modem services, 20
    - limitations of, 22
    - standards, 21
  - cables
    - dirty phone lines as source of slow connection speeds, 223–224
    - shorts, detecting, 223
  - connection speeds, 126–127
    - increasing, 226
    - limitations of, 128
  - digital, 126
  - disconnections, 221–223
  - fast busy signals, debugging, 226
  - internal standard PCI modems, 21
  - malfunctioning, 225
  - PCM, 13
  - Shannon’s Capacity Theorem, 12, 38
  - slow busy signals, debugging, 227
- modes of IPsec operation, 612
- modulation, 39
  - in hybrid networks, 53–54
  - in wireless LANs, 44–45
  - WLANs
    - DSSS, 49
    - FHSS, 48

modulator-demodulators. *See* modems

monitoring

    Cisco Easy VPN client environment, 720–721

    network performance, SAA, 117–119

M-plane (ISDN), 236

MPLS VPN, 90

MPOE (minimum point of entry), 129

mtrace command, 578

multicast

    Frame Relay, 440, 482–483

    group flags, 573

Multichannel Multipoint Distribution System.

*See* MMDS

multiple frequency operation (UHF), 47

multiplexing, 414

    FDM, 71–72, 414

    statistical multiplexing, 414

    TDM, 74, 414

mutable ICV fields, 608–610

## N

---

nailed-up, 81

NAPs (network access points), 86

narrowband, 46

narrowband ISDN (NISDN), 235

NASs (Network Access Servers)

    dial-in, 191–200

    dial-out, 200–205

    T1 circuits, 181–187

NAT (Network Address Translation)

    implementing in remote access VPNs, 639–640

    ISDN configuration, 267–271

    multiple client handling, 753

NBMA (nonbroadcast multi-access) model

    point-to-point Frame Relay, 461

NCPs (network control protocols), 197–200,  
341–352

    CCP, 352

    MLP, 343–344

    MMP, 347–351

near end, 96

near-end crosstalk (NEXT), 23

negotiating upper-layer protocols, NCPs, 341–352

    CCP, 352

    MLP, 344

    MMP, 347–351

Netcat utility, 115–117

network design

    DDR, configuring

        with backup interfaces, 147

        with dialer watch, 148

        with floating static routes, 148

    dial-in

        PPP dial-in, 143–144

        text dial-in, 143

    dial-out

        large-scale, 146

        PPP dial-out, 145

        text dial-out, 144

    hub and spoke, 142

    ISDN

        categories of, 258–259

        configuring switch type, 259–260

        hub and spoke, 257

        MLP, 273–277

        MMP, 278, 280–285

        per-user configuration, 272–273

        SPIDs, configuring, 260–262

Network Extension mode, Cisco 3002 HW  
client, 706

network layer (OSI model), 98

    troubleshooting ISDN BRI, 324–334

    VPNs, 604

        Layer 3 tunneling, 605

        SAs, 605–607

Network Layer Protocol phase (PPP), 137

network monitoring tools, 109

new install issues

    ISDN, 369–371

    Frame Relay, 548–556

NEXT (near-end crosstalk), 23

NFAS (Non-Facility-Associated Signaling), 16

D channel, verifying correct circuit locations, 227

groups, 393

NI (National ISDN) standards, 233

NNI (network node interface), 439

Non-Facility-Associated Signaling. *See* NFAS

NT1 (network termination type 1), 58, 238

NT2 (network termination type 2) devices, 238

N-way multicast service, Frame Relay, 440

Nyquist sampling theorem, 72

Nyquist's Theorem, 39

## O

off net dial-out, 146

ones density, 131, 499

one-way service, Frame Relay multicast, 440

on-net dial-out, 145

operating systems, Windows 2000

DDR issues, resolving, 399–408

well-known ports, 403–405

operations management of remote access VPNs, 636

optical networks, SONET, 80

OSI model, 98–100

data link layer

correlated Frame Relay protocol

functions, 419–420

troubleshooting ISDN BRI, 319–324

network layer, 324–334

physical layer, 314–319

OSPF (Open Shortest Path First) demand circuits, 293

OTPs (one-time passwords), 228

outgoing calls, ISDN, 372–376

out-of-band signaling, 78

outsourcing remote access support, 7

overload. *See* PAT

oversubscription, 436

## P

packet switching, 70

PAP (Password Authentication Protocol), 133

partial-mesh topologies, Frame Relay, 441

passive bus point-to-multipoint architecture (ISDN), 237

passwords

authentication, PPP, 340

OTPs, 228

PAT (Port Address Translation)

in remote access environments, 639–640

ISDN configuration, 266–267

PathChar utility. *See* Pchar

pathcode violations of T1 circuits, 186

payload compression, 477

configuring, 480–481

Pchar

establishing baseline performance, 105–109

options, 105–106

PCM (pulse code modulation), 13, 39, 73

PdUs (protocol data units), 99

per interface limitations of DLCIs, 466–467

perfect scheduling, 57

performance

discovering baseline behavior, 105–109

Frame Relay, physical layer, 501–505, 562

compression, 537–543

end-to-end connectivity, 528–533

flapping lines, 563–566

flapping links, 526–528

RER, 444

throughput, 444

traffic shaping, 534–536, 566–572

transit delay, 444

monitoring with SAA, 117–119

selection criteria for VPN termination

equipment, 646–648

per-interface compression, 477

periodic retransmissions, packets sent from W2K systems, 401

permanent virtual circuits. *See* PVCs

- per-virtual circuit compression, 477
- PFS (perfect forward secrecy), 627
- phase modulations, 40
- phase-shift keying, 40
- photonic WLANs, 45
- physical layer
  - Frame Relay
    - clocking problems, 493–498
    - CSU/DSU, testing, 501
    - loopback testing, 500
    - performance issues, 501–505
  - ISDN BRI, 314–319
  - T1 circuits
    - alarm states, 184, 186
    - checking bit errors, 183–184
    - errors, 187
    - identifying loopback features, 183
    - linecode violations, 186
    - pathcode violations, 186
    - slip seconds, 186
    - verifying controller status, 181–183
- PIM SM (Protocol Independent Multicast Sparse Mode), Frame Relay multicast configuration, 482–483
- ping command, 110–114
- PMTU (Path MTU) discovery, 610–612
- point-to-multipoint Frame Relay
  - hub side configuration, 458, 460
  - spoke side configuration, 460–461
- point-to-point Frame Relay configuration
  - hub configuration, 462, 464
  - NBMA model, 461
  - spoke configuration, 465–466
- ports, 403
- POTS (plain old telephone service) interfaces, ISDN configuration, 306–308
- PPPoE, 733
  - discovery stage, 735
  - negotiations, 736–739
  - session stage, 736
- PPP (Point-to-Point Protocol), 134. *See also* MLP
  - authentication
    - servers, 133
    - timeouts, troubleshooting, 220–221
    - troubleshooting, 340
  - Authentication phase, 136, 396–398
  - callback, 303–305, 344–347
  - connection termination, 352–353
  - dial-in network design, 143–144, 151–159
  - dial-out
    - configuring, 168–171
    - network design, 145
  - frame fields, 134–135
  - LCP, 335–339
    - 22 second issue, 387–396
  - Link Dead phase, 135
  - Link Establishment phase, 135–136
  - Link Termination phase, 137
  - NCPs, 341–352
  - negotiation
    - authentication phase, 197
    - LCP phase, 194–196
    - NCP phase, 197–200
  - Network Layer Protocol phase, 137
  - protocol field, 335
  - troubleshooting, 138
- PPTP (Point-to-Point Tunneling Protocol), 600–601
- Predictor data compression, 477
- premature disconnect, 445
- presentation layer (OSI model), 99
- PRI (Primary Rate Interface) circuits, 188
  - 1.544-Mbps interface, 64–65
  - 2.048-Mbps interface, 65
  - Layer 1 status, verifying, 188
  - Layer 2 status, verifying, 188–190
- profiles (VPN client), creating, 772
- projecting PPP link to call master, 278
- protected band (RF), 46
- Protocol Discriminator field (Q.931 messages), 248
- Protocol field (PPP frames), 135, 335
- protocol layer (Frame Relay), 506
  - LMI issues, 513–526
  - misconfigured PVCs, 507–513
  - new installs, 549–552
- provisioning process, enterprise remote access services, 30–31, 33–34

- Frame Relay, 31–33
- ISDN, 31, 33, 369
- xDSL, 33–34
- pseudo-ternary signaling, 55, 57
- PSK (phase-shift keying), 40
- PSTN (Public Switched Telephone Network), 37
- pulse code modulation. *See* PCM
- pulse density, 131
- PVCs (permanent virtual circuits), 17, 418
  - DLCIs, per interface limitations, 466–467
  - end-to-end connectivity, 528–533
  - flapping lines, 563–566
  - misconfiguration issues, 507–513
  - premature disconnect, 445

## Q

- Q.921, 242. *See also* LAPD
  - LAPD frame format, 242–247
    - Address field, 244
    - Control field, 244–245
    - Data field, 246
    - FCS field, 246
    - Flag field, 243
  - logical link establishment, 246–247
- Q.922 protocol, 424
  - Control field, 424–425
  - Information field, 426–429
- Q.931 message format, 248, 331–332, 334
  - Call Reference field, 249
  - Information Elements field, 251–252
  - Message Type field, 249–250
  - Protocol Discriminator field, 248
- QoS (quality of service) parameters, Frame Relay, 445
- QPSK (quaternary phase-shift keying), 44
- Q-series protocols, 234
- quiet periods (snapshot routing), 291

## R

- RA to MPLS VPN (Remote Access to Multiprotocol Label Switching Virtual Private Network), 90, 592–593
- RADIUS, 621–623
- RARP (Reverse Address Resolution Protocol), 454
- rate adoption algorithm, 442
- RBS (robbed bit signaling), 78
- red alarms, 185
- redundancy
  - configuring on VPN 3000 Concentrators, 653
  - ISDN backup for Frame Relay, configuring, 471–473
- reimbursements, 7
- remote access VPNs, 595
  - change management, 636
  - Cisco PIX 501 VPN Client, configuring, 669–670
  - Cisco PIX 506 VPN Client, configuring, 669–671
  - Cisco VPN 3002 HW Client, configuring, 665–666
  - Cisco VPN IOS Client, configuring, 666–668
  - Cisco VPN Unity Client, configuring, 663–664
  - configuration management, 635
  - design objectives, 634–635
  - operations management, 636
  - security issues, 636
    - firewalls, 640–641
    - IPSec, 637–638
    - NAT/PAT, 639–640
    - split tunneling, 640
    - user authentication infrastructure, 637
  - termination equipment, 641–642
    - performance criteria, 646–648
    - selecting core devices, 643–646
  - versus site-to-site, 633–634
- remote control software, 109
- Remote Page Accelerator, 28
- remote users of Frame Relay, troubleshooting nonpassing traffic in up, up state, 555–556

- removing echo with digital pads, 129–130
- repeaters, 126
- RER (residual error rate), 444
- resetting Cisco Easy VPN client connections, 717
- restrictions
  - of Cisco Easy VPN client, 713–714
  - of Cisco PIX VPN client, 722
  - of Cisco Unity client, 676–679
- retrains, 221–223
- reverse route injection, configuring on VPN 3000 Concentrators, 655
- RF (radio frequency), 44
  - narrowband, 46
  - SS RF transmissions, 48
    - DHSS, 49
    - FHSS, 48
- Rijndael algorithm, 618
- ring options, troubleshooting mandatory user participation, 354–355
- router commands
  - AS5200, 207, 209
  - AS5300, 209–214
  - AS5400, 215
- routing ISDN BRI, 399
  - performance issues, 377
- routing protocols, discovering network topology information, 104–105
- RPA (Remote Page Accelerator), 28
- RPC (remote procedure call), 402–403
- RTT (round-trip time), 745
  - verifying Frame Relay service, 567–569

## S

- SAA (Service Assurance Agent), 117–119
- SABME (Set Asynchronous Balanced Mode Extended) messages, 190, 322
- sampling, Nyquist's sampling theorem, 39
- SAPI (service access point identifier) data types, 189
- SAs (security associations), 605–607
  - configuring on VPN 3000 Concentrators, 659–660
- satellite systems, 28
  - BST protocol, 29, 750
  - DOCSIS 1.1 standard, 54
  - FITFEEL protocol, 751
  - IPA, 28
  - IPSec, 752–753
  - LEO satellites, 30
  - manipulating TCP stack, 749–750
  - performance, 749
  - VPNs, 745–746
    - bandwidth, 747
    - error control coding, 746
    - TCP efficiency, 747–748
- S-CDMA (synchronous code division multiple access), 742
- SCTE (serial clock transmit external) timing, 499
- SDSL (single-line DSL), 24
- security
  - authentication
    - DH algorithm, 624–627
    - HMAC, 627–628
    - key management, 624–627
    - OTPs, 228
    - PAP, 133
    - RADIUS, 621–623
    - resolving issues, 396–398
    - servers, 133
    - timeouts, 219–221
    - VPN client authentication, 619
    - VPN user/identity authentication, 620
  - IPSec
    - AH header format, 614–615
    - connectionless data integrity, 608
    - ESP header format, 616–618
    - ICMP processing, 611–612
    - ICV calculation, 615
    - ICV fields, 608–610
    - IP fragmentation, 610
    - modes, 612
    - PMTU discovery, 610–611

- ISDN, 305
- policies, 8
- remote access VPNs, 636
  - encryption, 638
  - firewalls, 640–641
  - IPSec authentication, 638
  - IPSec mode, selecting, 637
  - NAT/PAT, 639–640
  - split tunneling, 640
  - user authentication infrastructure, 637
- selecting
  - CIR
    - aggregate CIR, 436–437
    - asymmetrical CIR, 437
    - flexible CIR, 437
    - zero CIR, 436
  - compression type for Frame Relay, 538
  - core devices in remote access VPNs, 643–646
  - IPSec mode for remote access VPNs, 637
  - VPN model, 19
- serial interfaces
  - debugging, 552
  - SCTE timing, 499
- service architecture (Frame Relay), C-plane, 417–418
- Service Assurance Agent, 117–119
- service levels, defining, 7–9
- service providers
  - future of, 89
  - last mile, 90–91
  - options, 9
  - service offering, 90
- service timestamps command, 313
- service-provider dependant VPNs, 19
- service-provider independent VPNs, 19
- services
  - Frame Relay, 17
    - benefits of, 18
    - limitations of, 18
    - standards, 17–18
  - ISDN, 14
    - benefits of, 15–16
    - limitations of, 16
  - technology offerings, 10–11
  - user- versus corporate-managed, 8
  - VPNs, 18–19
    - cable modem services, 22
    - cable modems, 20
    - limitations of, 19
    - satellite services, 28–30
    - standards, 21
    - wireless broadband services, 25–27
    - xDSL services, 22–25
    - Windows 2000, RPC, 402–403
- session layer (OSI model), 99
- SF (Super Frame), 43
- SGBP (Stack Group Bidding Protocol), 278
  - queries, debugging, 351
- Shannon, Claude, 12
- Shannon's Capacity Theorem, 38
- shared secrets, PFS, 627
- short cable lengths, 183
- short command format (Cisco IOS), 102
- show cdp neighbors command, 103
- show controllers bri0 command, 316
- show dialer command, 373–374
- show interface serial 0 command, 502–505
- show isdn active command, 372
- show isdn status command, 315, 320, 360–363
- show modem operational status command, 224
- signaling (ISDN), D channel, 234
- signals
  - amplitude, 40
  - analog, 37
  - frequency, 40
- site-to-site VPNs, 596
  - versus remote access VPNs, 633–634
- size estimates
  - of distance vector routing protocols, 467
  - of link-state routing protocols, 467–468
- sliding windows, 443
- slip seconds on T1 circuits, 186
- slow busy signals, debugging, 227
- slow connection speeds
  - increasing, 226
  - sources of, 223–224



- snapshot routing, 290, 292
- sniffing W2K traffic, 402–403
- SNR (signal-to-noise ratio), affecting factors, 128–129
- soft skills versus technical skills, 95
- software
  - global dialer, 13
  - compression, 542–543
- SONET (Synchronous Optical Network), 80
- sparse mode (PIM), Frame Relay multicast configuration, 482–483
- specifying loopback format of T1 circuits, 183
- SPID (service profile identifier), 253, 308
  - configuring, 260–262
- split tunneling, implementing in remote access VPNs, 640
- spoke configuration
  - Frame Relay point-to-multipoint connection, 460–461
  - point-to-point Frame Relay connections, 465–466
- spoofing, 290
- SS (spread spectrum) RF transmissions
  - DSSS, 49
  - FHSS, 48
- SS7 (Signaling System 7), 78–79
- STAC data compression, 477
- Stack Group Bidding Protocol. *See* SGBP
- standards
  - CATV data transmission, 741–744
  - Frame Relay, 415
    - IAs, 415–416
    - service architecture planes, 417–418
- starting Cisco VPN Client Log Viewer, 686
- Static RP, 483
- statistical multiplexing, 414, 437
- Status Enquiry message format, Consortium LMIs, 514–515
- Status message format, Consortium LMIs, 515
- STS (Station-to-Station protocol), 626
- STS-1, 80
- subchannels, 42
- supervisory messages, 245

- supporting remote access services, 7
  - defining service levels, 9
  - in-sourcing versus outsourcing, 7
- SVCs (switched virtual circuits), 17, 418
- switched virtual circuits. *See* SVCs
- switches, 82
  - ISDN, 252–253, 259–260
- symbols, 50
- synchronization, clocking, 55
- synchronous data transmission, 71
- syntax, IOS-based ping command, 110
- synthesized radio technology, 46

---

## T

- T1 circuits, 76–77
  - bit errors, checking, 183–184
  - controller status, verifying, 181–183
  - errors, 187
  - framing
    - ESF signal format, 63
    - SF signal format, 62–63
  - linecode violations, 186
  - loopback features, identifying, 183
  - ones density, 131
  - pathcode violations, 186
  - physical layer alarms, 184, 186
  - slip seconds, 186
- T3 framing, M23 signal format, 63–64
- tandems, 82–83
- TAs (terminal adapters), 238
- Tc (committed interval), 434
- T-carriers, 75
  - E1, 77
  - T1, 76–77
- TCP boomerangs, 751
- TDM (time-division multiplexing), 74, 414
  - D channels, 393
- TDRs (time domain reflectometers), 23
- TE1 devices, 238
- TE2 devices, 238

- technology offerings, 10–11
    - Frame Relay, 17
      - benefits of, 18
      - limitations of, 18
      - standards, 17–18
    - ISDN, 14
      - benefits of, 15–16
      - limitations of, 16
    - VPNs, 18–19
      - cable modem services, 20–22
      - limitations of, 19
      - satellite services, 28–30
      - wireless broadband services, 25–27
      - xDSL services, 22–25
  - TEIs (terminal endpoint identifiers), 190
  - Telnet sessions, logging to console, 548
  - terminal servers, 86
  - termination equipment, remote access VPNs, 641–642
    - performance criteria, 646–648
    - selecting core devices, 643, 645–646
  - termination sequence (PPP), 352–353
  - testing
    - D channel, 327
    - remote user’s router on Frame Relay multicast network, 577
  - testing network connectivity
    - extended ping command, 111
    - Netcat utility, 115–117
    - ping command, 110–114
    - tracert command, 114–115
  - text dial-in
    - configuring, 150–151
    - network design, 143
  - text dial-out
    - configuring, 164–168
    - network design, 144
  - throughput, Frame Relay, 444
  - time domain reflectometers, 23
  - time-division multiplexing. *See* TDM
  - timeouts, modem authentication, 219–221
  - timeslots, line code errors, 130
  - timestamps, applying, 313–314
  - timing, SCTE, 499
  - token bucket filters, 483
  - topologies
    - discovering baseline behavior, 103–105
    - Frame Relay, 441
  - T-plane (ISDN), 236
  - tracert command, 114–115
  - tracing Frame Relay multicast networks, 577–580
  - traffic shaping, 483–484
    - ELMI, 487–488
    - Frame Relay, 441–443, 534
      - BECNs, 536
      - FECNs, 535
    - flapping routes, investigating, 572
    - high RTT numbers, investigating, 567–569
    - slow performance, investigating, 569–572
    - verifying settings, 566
  - generic, 484–486
  - map classes, 486–487
- transit delay, Frame Relay, 444
- transmission rates, Shannon’s Capacity Theorem, 38
- transport layer (OSI model), 98
- Transport mode (IPSec), implementing in remote access VPNs, 637
- transport mode (IPSec), 612
- troubleshooting methodologies, 101–102
  - ISDN BRI recommendations, 359
    - accessing remote user’s router, 365–369
    - preconfiguring routers on both ends, 364–365
    - viewing service layers, 360–363
  - layered approach, 96
- troubleshooting tools
  - classifying, 110
  - extended ping command, 111
  - Netcat utility, 115–117
  - ping command, 110–114
    - replies, 112
  - SAA, 117–119
  - tracert command, 114–115
- Tunnel mode (IPSec), 613
  - implementing in remote access VPNs, 637

tunneling, DPD, 803–804  
two-way Internet connections, 744  
two-way multicast service, Frame Relay, 440  
type codes (ICMP messages), 112–113

## U

---

UHF (ultra-high frequency)  
multiple frequency operation, 47  
narrowband, 46  
synthesized radio technology, 46

UNI (user node interface)  
bearer services, 438  
LMI, 449  
Annex D, 451  
Cisco-Consortium, 451  
ITU-T Q.933 Annex A, 453

Unity client  
Concentrator Event Log, 699–701  
event classes, 702–704  
event security levels, 704–705  
data not passing, causes of, 784  
bad ISP connections, 786–787  
default MTU size, 786  
dropped connections, 786  
inaccessible internal domain, 787–790  
NAT, 785  
Event Log Viewer, 685  
Client Log Viewer, starting, 686  
ISAKMP, 688  
reviewing captured data, 688–699  
extranet issues, 801  
dead peer detection, 803–804  
ESP 50, 801  
tunnel keepalives, 802  
UDP 500 ISAKMP, 801  
failed authentication, causes of  
bad group name, 774–775  
DNE Miniport, 776–777  
misconfigured firewalls, 777–778  
MTU setting too high, 779–784

MTU setting too low, 784  
RADIUS, 775–776  
inaccessible internal domain, WINS, 788  
incompatible GINAs, 705–706  
PPPoE problems, causes of  
IOS configuration, 793–795  
software, 791–793  
preliminary troubleshooting steps  
creating profiles, 772  
verifying client installation, 771  
verifying Internet connection, 767–770  
restrictions, 676–679  
troubleshooting checklist, 682–685  
unnumbered messages, 245  
unprotected band (RF), 46

U-plane  
Frame Relay service architecture, 417  
ISDN, 236

upper-layer protocols  
Frame Relay interoperability, 445  
encapsulation, 447  
fragmentation, 448  
multiprotocol support, 445–447  
NCPs, 341–352

upstream PIM neighbor availability, verifying on  
Frame Relay networks, 574–576  
user authentication, remote access VPNs, 637  
user participation, troubleshooting ring options,  
354–355  
user/identity authentication, 620  
user-managed services, 8  
UWB (ultra wideband) technology, 47

## V

---

V.21 standard, 12  
V.32 standard, 12  
V.32b standard, 12  
V.90 calls, limitations of, 129  
Van Jacobson header compression, 477–480  
path characterization model, 105

- variable length framing, Frame Relay, 415
- VCs (virtual circuits), 415
- VDSL (Very-high rate DSL), 25
- verifying
  - Cisco PIX VPN connectivity, 722–732
  - DHCP server reachability, 227
  - Frame Relay configuration
    - DLCI settings, 556–562
    - remote user router status, 553
    - serial interface, 551
    - service operation, 553–555
    - traffic shaping, 566
  - incoming connection type, dial-in
    - troubleshooting procedure, 192–194
  - ISDN configuration
    - D channel functionality, 327
    - Layer 1 status of PRI circuits, 188
    - Layer 2 status of PRI circuits, 188–190
  - IP address configuration on Windows operating systems, 769–770
  - line provision, 354
  - MMP configuration, 284–285
  - modem operability, dial-in troubleshooting
    - procedure, 191–192
  - out of order B channels (NFAS), 227
  - PPP negotiation, dial-in troubleshooting
    - procedure, 194–200
  - VPN client installation, 771
- viewing
  - captured Log Viewer results, 688–699
  - ISDN BRI service layers, 360–363
- virtual circuits, compression, 477
- virtual connections, MLP, 343–344
- virtual interface templates, 272
- virtual ports, 474
- virtual profiles, 273
- VoFR (Voice over Frame Relay), 440
- voice
  - digitalization, 73
  - priority over data, 353–354
- voice privacy, ISDN configuration, 308–309
- VPN 3000 Concentrator, configuring, 648–649
  - filters and rules, 650–651
  - Group Lock, 662
- IKE
  - peer identity validation, 662
  - proposals, 656, 658–659
- IPSec SAs, 661
  - load balancing, 654–655
  - redundancy, 653
  - reverse route injection, 655
  - SAs, 659–660
- VPNs (Virtual Private Networks), 10, 13, 18–19
  - ADSL, 732
    - PPoE, 733–739
  - authentication
    - client authentication, 619
    - DH algorithm, 624–627
    - HMAC, 627–628
    - key management, 624–627
    - RADIUS, 621–623
    - user/identity authentication, 620
  - cable modem services, 20
    - limitations of, 22
    - standards, 21
  - CATV infrastructure
    - data transmission, 740–744
    - heartbeats, 745
    - two-way Internet connections, 744
  - Cisco 3002 HW client, 706
    - Event Log, 708–710, 712
    - initial troubleshooting checklist, 707
  - Cisco Easy VPN Client, 713
    - client status, displaying, 716
    - debugging IPSec key events, 717–719
    - initial troubleshooting checklist, 714–716
    - monitoring, 720–721
    - resetting connection, 717
    - restrictions, 713–714
  - Cisco PIX VPN
    - connectivity, verifying, 722–732
    - restrictions, 722
  - Cisco Unity client
    - Concentrator Event Log, 699–705
    - Event Log Viewer, 685–699
    - incompatible GINAs, 705–706
    - restrictions, 676–679
    - troubleshooting checklist, 682–685

- Cisco VPN 3002, connection establishment, 795–800
- data not passing, causes of, 784
  - bad ISP connections, 786–787
  - default MTU size, 786
  - dropped connections, 786
  - inaccessible internal domain, 787–790
  - NAT, 785
- enterprise VPNs, 593–594
  - categories of, 595
  - data link layer, 599–603
  - firewall-based VPNs, 597–598
  - network layer, 604–607
  - remote access VPNs, 595
  - site-to-site VPNs, 596
- extranet issues, 801
  - dead peer detection, 803–804
  - ESP 50, 801
  - tunnel keepalives, 802
  - UDP 500 ISAKMP, 801
- failed authentication, causes of
  - bad group name, 774–775
  - DNE Miniport, 776–777
  - misconfigured firewalls, 777–778
  - MTU setting too high, 779, 781–784
  - MTU setting too low, 784
  - RADIUS, 775–776
- inaccessible internal domain, causes of, 788
- LAN-specific issues
  - inability to log in, 760
  - MTU settings, 754–758
  - NAT, multiple client handling, 753
  - packet size, 758–760
- latency, 228
- limitations of, 19
- PPPoE problems, causes of
  - IOS configuration, 793–795
  - software, 791–793
- preliminary troubleshooting steps
  - creating profiles, 772
  - verifying client installation, 771
  - verifying Internet connection, 767–770
- remote access
  - change management, 636
  - configuration management, 635
  - design objectives, 634–635
  - operations management, 636
  - security issues, 636–641
  - termination equipment, 641–648
- satellite services, 28
  - BST, 29
  - IPA, 28
  - LEO satellites, 30
- satellite systems, 745–746
  - bandwidth, 747
  - BST protocol, 750
  - error control coding, 746
  - FITFEEL protocol, 751
  - IPSec, 752–753
  - manipulating TCP stack, 749–750
  - performance, 749
  - TCP efficiency, 747–748
- site-to-site versus remote access VPNs, 633–634
- wireless systems, 25, 745–746
  - bandwidth, 747
  - error control coding, 746
  - limitations of, 27
  - LMDS, 26–27
  - MMDS, 25–26
  - TCP efficiency, 747–748
  - unlicensed frequencies, 27
- xDSL services, 22
  - ADSL, 24
  - CDSL, 24
  - FDIs, 22–23
  - HDSL, 24
  - IDSL, 24
  - RADSL, 24
  - SDSL, 24
  - TDRs, 23
  - VDSL, 25

## W

---

- WAN links
  - PRI circuits
    - Layer 1 status, verifying, 188
    - Layer 2 status, verifying, 188–190
    - troubleshooting, 188
  - T1 circuits
    - alarm states, 184, 186
    - BERT testing, 183–184
    - line code violations, 186
    - loopback features, 183
    - pathcode violations, 186
    - slip seconds, 186
    - T1 errors, 187
    - troubleshooting, 181–86
    - verifying controller status, 182
- well-known ports, 403–405
- Whitecamp network protocol, 53
- WIC T1 pinouts, 499
- wi-fi, 44
- windowing, 443
- Windows operating systems
  - verifying IP address configuration, 769–770
- Windows 2000
  - DDR, 399–408
  - ports, 403
  - RPC, 402–403
  - well-known ports, 403–405
- wireless broadband services, 25
  - 3G, 91–92
  - limitations of, 27
  - LMDS, 26–27
  - MMDS, 25–26
  - unlicensed frequencies, 27
- wireless cable, 26
- wireless VPNs, 745–746
  - bandwidth, 747
  - error control coding, 746
  - TCP efficiency, 747–748
- WISP (wireless ISP), 54

## WLANs

- 802.11a, 51–52
- 802.11e, 53
- 802.11g, 52
- barker sequence, 50
- IR radio-channel, 45
- line-coding techniques, 44–48
- LTI systems, 47
- modulation, 44–45, 48
- narrowband technologies, 46
- photonic, 45
- SS RF transmissions
  - DSSS, 49
  - FHSS, 48
- UHF, multiple frequency operation, 46
- UWB technology, 47

## X

---

- X.25 protocol, 17
  - versus Frame Relay, 414–415
- XAUTH, 623
- xDSL services, 22
  - 2B1Q coding, 55, 58–59
  - ADSL, 24
  - CDSL, 24
  - coding schemes, 41–42
  - FDIs, 22–23
  - HDSL, 24
  - IDSL, 24
  - provisioning enterprise remote access services, 33–34
  - RADSL, 24
  - SDSL, 24
  - TDRs, 23
  - VDSL, 25

## Y-Z

---

yellow alarms, 185

zero CIR, 436

zero-suppression schemes, 61–62