



INDEX

A

- AC routers
 - interdomain multicast configuration, 256–259
 - example, 142–149
- address scoping, 9
- addresses, IP multicast, 7
 - Class D, 7
 - globally scoped addresses, 8
 - GLOP addresses, 8
 - Layer 2, 9
 - limited scope addresses, 8
 - reserved link local addresses, 7
 - source specific addresses, 8
- address-family ipv4 command, 273
- administratively scoped addresses, 8
- Anycast RP, 29–31
- application-level multicast, 5
- AS (autonomous system)
 - address scoping, 9
 - GLOP addressing, 8
- ASICs (application-specific integrated circuits), 18
- assignment of IP multicast addresses, 7
 - globally scoped addresses, 8
 - GLOP addresses, 8
 - limited scope addresses, 8
 - reserved link local addresses, 7
 - source specific multicast addresses, 8

B

- backbone routers
 - interdomain multicast configuration, 197–233, 260–271
 - characteristics, 153–154, 160–161, 168, 175, 180, 185, 189
 - configuration file, 154–193
 - example configuration, 93–127
- BGP peering address, setting for Anycast RP, 31
- bidirectional shared trees, 26
- Bidir-PIM (Bidirectional PIM), 26–27

C

- caching SA messages, 86
- CGMP (Cisco Group Management Protocol), 16–17

- characteristics of backbone routers, interdomain
 - multicast deployment, 153–154, 160–161, 168, 175, 180, 185, 189
- Class D IP multicast addresses, 7
 - mapping to MAC addresses, 10
- commands
 - address-family ipv4, 273
 - debug ip igmp, 274
 - debug ip mrouting, 274
 - debug ip urd, 274
 - ip cgmp, 275
 - ip igmp v3lite, 275
 - ip igmp version, 275
 - ip mrm, 276
 - ip mrm manager, 276
 - ip mroute-cache, 276
 - ip msdp cache-sa-state, 277
 - ip msdp originator-id, 277
 - ip msdp peer, 277–278
 - ip msdp redistribute, 278
 - ip msdp sa-filter in, 278
 - ip msdp sa-filter out, 279
 - ip multicast boundary, 280
 - ip multicast multipath, 280
 - ip multicast-routing, 280
 - ip pim, 281
 - ip pim accept-register, 281
 - ip pim accept-rp, 282
 - ip pim bsr-border, 282
 - ip pim rp-address, 282–283
 - ip pim send-rp-announce, 283
 - ip pim send-rp-discovery, 284
 - ip pim spt-threshold, 284
 - ip pim ssm, 284
 - ip urd, 285
 - manager, 285
 - match nlri, 285
 - neighbor activate, 286
 - neighbor default-originate, 286–287
 - neighbor peer-group, 287
 - neighbor remote-as, 287–288
 - neighbor route-map, 288
 - network, 288
 - receivers, 289
 - redistribute, 290, 292
 - senders, 293
 - set nlri, 293
 - show ip bgp ipv4 multicast summary, 294
 - show ip bgp neighbors, 294
 - show ip igmp groups, 295
 - show ip mbgp summary, 295

- show ip mroute, 295
- show ip msdp peer, 296
- show ip msdp sa-cache, 296
- comparing
 - shared and source trees, 21–22
 - SSM and ISM, 239
- configuration files, interdomain multicast backbone
 - router deployment, 154–193
- configuring
 - MBGP
 - peering sessions, 42–44, 76–84
 - verifying multicast routing, 45
 - MSDP peering sessions, 79–81, 85
 - multicast borders, 46–47, 81–82, 87
 - SA caching, 46, 74, 86
 - SA filters, 45–46, 85
 - SSM operation mode, 240

D

- DA routers, interdomain multicast implementation, 128–142
- datagram delivery with SSM, 239
- debug ip igmp command, 274
- debug ip mrouting command, 274
- debug ip urd command, 274
- denial-of-service attacks, preventing with SSM, 244
- dense mode (PIM), 24
- deploying
 - interdomain multicast, 38, 42–47
 - AC routers, example configuration, 142–149
 - backbone routers, characteristics, 153–154, 160–161, 168, 175, 180, 185, 189
 - backbone routers, configuration files, 154–193
 - backbone routers, example configuration, 93–127
 - connecting customers to infrastructure, 48
 - DA routers, example configuration, 129–141
 - MBGP configuration, 76–79, 82–84
 - medium-scale ISPs, 59–75
 - MSDP configuration, 79–81, 85
 - multicast border configuration, 81–82, 87
 - prerequisites, 38–39
 - SA caching configuration, 86
 - SA filter configuration, 85
 - small-scale ISPs, 52–58
 - intradomain multicast, 40
 - global multicast configuration, 40
 - in small-scale ISPs, 49–52

- interface configuration, 41
- RP configuration, 42
- RP selection, 42
- small-scale ISPs, 49–52
- SSM
 - ramifications, 245–247
 - requirements, 240
- devices
 - AC routers, interdomain multicast configuration, 142–149, 256–259
 - backbone routers
 - characteristics, 153–154, 160–161, 168, 175, 180, 185, 189
 - configuration file, 154–193
 - interdomain multicast configuration, 93–127, 197–233, 260–271
 - DA routers, interdomain multicast implementation, 129–141
 - icons, xix
 - distribution trees, shared trees
 - bidirectional, 26
 - unidirectional (PIM-SM), 25

E

- efficiency of IP multicast, 5
- establishing
 - interdomain multicast strategy, 42–47
 - connecting customers to infrastructure, 48
 - intradomain multicast strategy, 40
 - global multicast configuration, 40
 - interface configuration, 41
 - RP configuration, 42
 - RP selection, 42
- Ethernet
 - mapping Class D multicast addresses to MAC addresses, 10
 - switched backbone segments, 18
- example configurations
 - interdomain multicast
 - AC routers 142–149, 256–259
 - backbone routers, 93–127, 260–271
 - DA routers, 128–142
 - medium-scale ISP implementation, 59–75
 - small-scale ISP implementation, 52–58
 - intradomain multicast, small-scale ISP implementation, 49–52
- examples
 - of Anycast RP, 31
 - of IP multicast, 6
- EXCLUDE mode (IGMPv3), 15

F-G-H-I

- fast switching, interface configuration, 41
- field definitions
 - IGMPv3 query messages, 14
 - IGMPv3 report messages, 8–9, 15
- filtering SA messages, 45–46, 85
- forcing Router ID on Anycast RP, 31
- globally scoped addresses, 8
- GLOP addresses, 8
 - IP address management, 244
- IANA (Internet Assigned Numbers Authority), 7–8
 - globally scoped addresses, 8
 - GLOP addresses, 8
 - limited scope addresses, 8
 - reserved link local addresses, 7
 - source specific multicast addresses, 8
- icons
 - network connections, xx
 - peripheral devices, xix
- IGMP (Internet Group Management Protocol), 11
 - snooping, 17
 - version 1, 11
 - version 2, 12
 - version 3
 - EXCLUDE mode, 15
 - host signaling, implementing SSM with
 - Cisco IOS software, 241
 - INCLUDE mode, 15
 - source filtering, 13
- IGMP v3lite host signaling, implementing SSM with
 - Cisco IOS software, 241–242
- implementing
 - interdomain multicast, 38, 42–47
 - AC router configuration, 142–149
 - backbone router characteristics, 153–154, 160–161, 168, 175, 180, 185, 189
 - backbone router configuration, 93–127, 154–193
 - DA router configuration, 128–142
 - multicast border configuration, 81–82, 87
 - SA caching configuration, 86
 - SA filter configuration, 85
 - connecting customers to infrastructure, 48
 - MBGP peering sessions, 76–84
 - medium-scale ISPs, 59–75
 - MSDP peering sessions, 79–81, 85
 - prerequisites, 38–39
 - small-scale ISPs, 52–58
 - with SSM, 237–238
 - intradomain multicast, 40
 - global multicast configuration, 40
 - in small-scale ISPs, 49–52
 - interface configuration, 41
 - RP configuration, 42
 - RP selection, 42
- SSM
 - IGMP v3lite host signaling, 241–242
 - IGMPv3 host signaling, 241
 - URD host signaling, 242–252
- INCLUDE mode (IGMPv3), 15
- installing SSM, 245
- interdomain multicast
 - connecting customers to infrastructure, 48
 - implementing, 42–47
 - prerequisites, 38–39
- MBGP, 27
- MSDP, 28
 - AC routers, example configuration, 142–149
 - Anycast RP, 29–31
 - backbone router characteristics, 197–233
 - backbone routers, example configuration, 93–127
 - DA routers, example configuration, 128–142
- SSM, 32, 237
 - benefits of, 244
 - device characteristics, 256–271
 - ramifications of using, 245
 - topology, 238
- intradomain multicast
 - Bidir-PIM, 26–27
 - global multicast configuration, 40
 - IGMP, 11
 - version 1, 11
 - version 2, 12
 - version 3, 13–15
 - implementing, 40
 - interface configuration, 41
 - multicast distribution trees, 19
 - shared trees, 20
 - source trees, 19–20
 - multicast forwarding, 22
 - RPF, 22–23
 - PGM, 27
 - PIM, 24
 - dense mode, 24
 - sparse mode, 24–25
 - RP configuration, 42
 - RP selection, 42

- IP addresses
 - managing with SSM, 244
 - reserved SSM range, 239
- ip cgmp command, 275
- ip igmp v3lite command, 275
- ip igmp version command, 275
- ip mrm command, 276
- ip mrm manager command, 276
- ip mroute-cache command, 276
- ip msdp cache-sa-state command, 277
- ip msdp originator-id command, 277
- ip msdp peer command, 45, 277–278
- ip msdp redistribute command, 278
- ip msdp sa-filter in command, 278
- ip msdp sa-filter out command, 279
- IP multicast
 - addresses, 7
 - Class D, 7
 - globally scoped addresses, 8
 - GLOP addresses, 8
 - Layer 2, 9
 - limited scope addresses, 8
 - reserved link local addresses, 7
 - source specific multicast addresses, 8
 - Class D addresses, mapping to MAC addresses, 10
 - efficiency of, 5
 - example, 6
 - forwarding, 22
 - RPF, 22–23
 - groups, 6
 - interdomain multicast
 - MBGP, 27
 - MSDP, 28–31
 - SSM, 32
 - intradomain multicast
 - Bidir-PIM, 26–27
 - PGM, 27
 - PIM, 24–25
 - Layer 2 switching environments, 16
 - CGMP, 16–17
 - IGMP snooping, 17
 - RGMP, 18
- ip multicast boundary command, 280
- ip multicast multipath command, 280
- ip multicast-routing command, 280
- ip pim accept-register command, 281
- ip pim accept-rp command, 282
- ip pim bsr-border command, 282
- ip pim command, 281
- ip pim rp-address command, 282–283
- ip pim send-rp-announce command, 283
- ip pim send-rp-discovery command, 284

- ip pim spt-threshold command, 284
- ip pim ssm command, 284
- ip urd command, 285
- ISM (Internet Standard Multicast), comparing with SSM, 239
- ISPs
 - interdomain multicast
 - connecting customers to infrastructure, 48
 - implementing, 38–39, 42–47
 - medium scale ISPs, 59–75
 - small-scale ISPs, 52–58
 - intradomain multicast
 - global multicast configuration, 40
 - implementing, 40
 - interface configuration, 41
 - RP configuration, 42
 - RP selection, 42
 - small-scale ISPs, 49–52

J-K-L

- LANs
 - Ethernet
 - mapping Class D multicast addresses to MAC addresses, 10
 - switched backbone segments, 18
 - IP multicast, broadcast bit, 9
 - Layer 2 switching, multicast, 16
 - addresses, 9
 - CGMP, 16–17
 - IGMP snooping, 17
 - RGMP, 18
 - leave group messages (IGMPv2), 12
 - limited scope addresses, 8

M

- manager command, 285
- managing IP addresses with SSM, 244
- mapping Class D addresses to MAC addresses, 10
- match nlri command, 285
- MBGP (Multiprotocol Border Gateway Protocol), 27
 - multicast routing, verifying, 45
 - peering sessions, configuring, 42–44, 76, 82–84
- medium-scale ISPs, interdomain multicast example configuration, 59–75
- membership, IGMPv3 multicast groups, 15

memory requirements, shared tree-only environments, 22

messages

- IGMPv2, leave group, 12
- IGMPv3 query messages, field definitions, 14
- IGMPv3 report messages, field definitions, 8–9, 15

SA

- caching, 86
- filtering, 45–46, 85

MSDP (Multicast Source Discovery Protocol), 28

- AC routers, example configuration, 142–149
- Anycast RP, 29–30
 - forcing Router ID, 31
- backbone routers, example configuration, 93–127
- DA routers, example configuration, 128–142
- implementing interdomain multicast, backbone router characteristics, 197–233
- peering sessions, 28
 - configuring, 79–81, 85
 - verifying, 46

multicast

- application-level, 5
- borders
 - configuring, 46–47
 - interdomain multicast configuration, 81–82, 87
- distribution trees, 19
 - shared trees, 20
 - source trees, 19–20
- forwarding, 22
 - RPF, 22–23
- groups, 6
- host groups, 239
- interdomain
 - backbone router characteristics, 153–154, 160–161, 168, 175, 180, 185, 189
 - backbone router configuration file, 154–193
 - Bidir-PIM, 26–27
 - connecting customers to infrastructure, 48
 - implementing, 38–39, 42–47
 - implementing with SSM, 237–238
- intradomain
 - global multicast configuration, 40
 - IGMP, 11–15
 - implementing, 40
 - interface configuration, 41
 - PGM, 27
 - PIM, 24–25
 - RP configuration, 42
 - RP selection, 42

Layer 2 switching environments, 16

- CGMP, 16–17
- IGMP snooping, 17
- RGMP, 18

N–O

neighbor activate command, 286

neighbor default-originate command, 286–287

neighbor peer-group command, 287

neighbor remote-as command, 287–288

neighbor route-map command, 288

network command, 288

network connections, icons for, xx

operation of URD host signaling, 247–249

P–Q

packets, IGMPv3 queries, 13

peering sessions

- MBGP, configuring, 42–44, 76–84
- MSDP, 28
 - configuring, 79–81, 85
 - verifying, 46, 86–87

PGM (Pragmatic General Multicast), 27

PIM (Protocol Independent Multicast), 24

- See also* Bidir-PIM
- dense mode, 24
- sparse mode, 24–25

prerequisites for implementing URD host signaling, 249

preventing denial-of-service attacks with SSM, 244

query messages (IGMPv3), 13

- field definitions, 14

R

ramifications of deploying SSM, 245–247

receivers command, 289

redistribute command, 290–292

report messages (IGMPv3), field definitions, 8–9, 15

requirements for SSM operation, 240

reserved address range (SSM), 239

reserved link local addresses, 7

- RFCs
 - online reference, 40
 - RFC 1112 “*Host Extensions for IP Multicasting*”, 7
- RGMP (Router-Port Group Management Protocol), 18
- RPs (rendezvous points), 20
 - Anycast RP, 30–31
 - configuring, 42
- RPF (Reverse Path Forwarding), 22
 - RPF check, 23

S-T

- SA caching
 - configuring, 46, 86
 - enabling, 74
- SA messages, filtering, 45–46, 85
- senders command, 293
- set nlri command, 293
- shared trees, 20
 - bidirectional, 26
 - unidirectional (PIM-SM), 25
 - versus source trees, 21–22
- show ip bgp ipv4 multicast summary command, 294
- show ip bgp neighbors command, 294
- show ip igmp groups command, 295
- show ip mbgp summary command, 295
- show ip mroute command, 295
- show ip msdp peer command, 296
- show ip msdp sa-cache command, 296
- small-scale ISPs
 - interdomain multicast, example configuration, 52–58
 - intradomain multicast, example configuration, 49–52
- source filtering, 13
- source specific multicast addresses, 8
- source trees, 19–20
 - unidirectional (PIM-SM), 25
 - versus shared trees, 21–22
- sparse mode (PIM), 24–25
- SSM (Source Specific Multicast), 32
 - address management, 246
 - broadcast applications, 245
 - comparing with ISM, 239
 - datagram delivery, 239
 - description, 238
 - IGMP v3lite host signaling, 241–242
 - IGMPv3 host signaling, 241
 - implementing interdomain multicast, 237
 - device characteristics, 256–260, 263–271
 - topology, 238
 - installation, 245
 - IP address management, 244
 - IP address range, 239
 - legacy application support, 246
 - operational requirements, 240
 - prevention of denial-of-service attacks, 244
 - ramification of deploying, 245–247
 - state maintenance limitations, 247
 - URD host signaling, 242
 - deployment strategy, 243
 - implementing, 249–252
 - network topology, 243–245
 - operation, 247–249
 - state maintenance limitations with SSM, 247
- STP (shortest path tree), 19
- switching, IP multicast handling, 16
 - CGMP, 16–17
 - IGMP snooping, 17
 - RGMP, 18
- syntax, URD intercept URLs, 247

U

- unidirectional shared trees, PIM-SM, 25
- URD host signaling, implementing SSM with Cisco
 - IOS software, 242, 249–252
 - deployment strategy, 243
 - network topology, 243–245
 - operation, 247–249
 - prerequisites, 249
 - URD intercept URL, 247–249
- URLs
 - RFC online reference, 40
 - URD intercept URLs, 247–249

V-W-X-Y-Z

- verifying
 - MBGP multicast routing, 45
 - MDSP peering sessions, 46
 - MSDP peering sessions, 86–87
- wildcard notation, shared trees, 21