

Symbols

`%zoneid` argument, 298

Numerics

3G, 379

6bone (IPv6 backbone), 12, 355–356

addresses, 360–361

architecture, 359

BGP4+, 163

qualifying as pTLAs, 362–363

route registry, 366

routing policies, 363–365

topology, 357–358

6NET, 376

6to4 mechanisms

deploying, 245–248

enabling, 248–251

relays, 251

tunnels

FreeBSD, 319–321

Linux, 332

Microsoft Windows, 301–305

A

a/127 IPv6 prefixes, assigning to point-to-point links, 239

A6 resource records, 129

access

NAPs, 371–372

NSAP, 11, 78

ACLs (access control lists), 129

applying, 130

creating, 130

defining, 130–133

extended ACLs

defining, 133–140

managing, 140

activation of IPv6, 79

adding static neighbor entries, 110

Address Resolution Protocol (ARP), 24

addresses, 41, 53, 77–78

6bone, 360–361

AAAA records, 127–129

aggregatable global unicast, 173

allocation, 369

policies, 367–369

providers, 374

anycast, 72, 73

autoconfiguration, 21–22

DAD, 121–123, 239

DHCP, 144

IPv4

exhaustion of, 9–11

growth, 8–9

IANA allocation, 8

space, 6–8

IPv4-compatible IPv6, 74

ISATAP, 256

link-layer, 21–23

link-local, 160, 173

loopback, 74

MAC, 22

Microsoft Windows, 296

NAT, 13–15, 236

NAT-PT, 264–273

NET, 198

next-hop, 160, 192

NSAP, 11

private, 247

querying, 230

representation of, 54–61

required IPv6, 76

space, 16

aggregatable global unicast, 67

automatic IPv4-compatible tunnels, 261

reassignment of, 368

static

configuration, 83

FreeBSD, 315–316

Linux, 326–328

Solaris, 308–309

Tru64 UNIX, 336

- types of, 61
 - aggregatable global unicast, 65–67
 - link-local, 62–63
 - multicast, 67–76
 - site-local, 63–65
- unspecified, 74
- address-family ipv6
 - configuration submode, 168
 - subcommand mode of the IS-IS router, 198
- adjacency entries, viewing, 109
- adjacency routers, 163, 194
- administration
 - ACLs, 140
 - BGP4, 183–184
 - FreeBSD, 316–317
 - IS-IS, 204
 - Linux, 328–329
 - Microsoft Windows, 297–298
 - NAT-PT, 270
 - OSPFv3, 211
 - RIPng, 192
 - Solaris, 309–310
 - Tru64 UNIX, 336–338
- administrative distances, routing protocols, 159
- advertisements
 - 6bone, 364
 - aggregatable global unicast addresses, 173
 - debugging, 124
 - default routes, 189
 - disabling, 117
 - ISATAP prefixes, 258
 - modifying, 119
 - neighbors, 107
 - prefixes, 19, 181–183
 - autoconfiguration, 21–22
 - NDP, 112
 - overriding, 115
 - viewing, 114
 - prohibited announcements, 365
 - requesting, 120
 - RIPng, 188
 - stateless autoconfiguration, 294
 - FreeBSD, 314
 - Solaris, 307
- aggregatable global unicast addresses, 65–67, 173
- aggregation, 19
 - IPv6 providers, 374
 - pTLAs, 357, 360
- AH (authentication header), 14, 30, 51, 145
- algorithms
 - Bellman-Ford, 186
 - SIIT, 264
- ALGs (application-level gateways), 262–264
- allocation
 - addresses, 369
 - by providers, 374
 - policies, 367–369
 - aggregation, 19
 - IANA IP address space, 8
 - NSAP, 78
- American Registry for Internet Numbers (ARIN), 7
- announcements
 - 6bone, 365
 - filtering, 168
 - permitted, 364
- anycast addresses, 72, 73
- anycast prefixes, 254
- APNIC (Asia Pacific Network Information Center), 7
- application-level gateways. *See* ALGs
- applications
 - dual stacks, 228–229
 - Flow Label fields, 26
 - NAT, 14
 - Telnet, 142
- applying
 - ACLs, 130
 - dynamic NAT-PT configuration, 270
 - prefix lists, 168
 - route maps, 171
 - static NAT-PT configuration, 268
- architecture, 77–78
 - 6bone, 359
 - addresses, 77–78
 - ALGs, 262–264
 - CATNIP, 11
 - DHCP, 144
 - IS-IS adjacency routers, 195
 - types of IPv6 addresses, 61
- arguments
 - %zoneid, 298
 - names, 168
 - prefix-list-name, 168
- ARIN (American Registry for Internet Numbers), 7

ARP (Address Resolution Protocol), 24, 107–111
 AS (autonomous system), 21

- IGP, 184–186
 - IS-IS, 193–205
 - RIP, 186–192
- multiple paths, 162

 Asia Pacific Network Information Center (APNIC), 7
 ASN (Autonomous System Number), 72

- assignment
 - a/127 IPv6 prefixes to point-to-point links, 239
 - addresses, 256
 - automatic prefixes, 245
 - BGP neighbors, 164
 - default routes
 - FreeBSD, 315–316
 - Linux, 326–328
 - multicast addresses, 70
 - static addresses
 - Microsoft Windows, 296
 - Solaris, 308–309
- attributes
 - BGP-4, 162–177
 - local preference
 - modifying, 172
 - NEXT_HOP
 - modifying, 173
- authentication, 180. *See also* security
- authentication header. *See* AH
- autoconfiguration, 21–22
 - DAD. *See* DAD
 - FreeBSD, 314–315
 - Linux, 324–326
 - NDP, 112–121
 - Solaris, 306–308
 - stateless (Microsoft Windows), 293–296
 - Tru64 UNIX, 334–336
- automatic IPv4-compatible tunnels, 260–261
- automatic prefix assignment, 245
- automatic tunneling, 245, 256
- Autonomous System Number (ASN), 72
- autonomous systems. *See* AS

B

Bellman-Ford algorithm, 186

Berkeley Internet Name Domain (BIND), 128
 BGP (Border Gateway Protocol), 72

- link-local addresses, 173
- managing, 183–184
- MD5 authentication, 180
- neighbors
 - applying prefix lists, 168
 - assignment, 164
- peering, 165, 177–179
- routes
 - maps, 171
 - redistribution, 181–183
 - security, 180
- bgp router-id ipv4-address command, 164
- BGP-4 (Border Gateway Protocol 4), 161–177
- BGP4+, IS-IS redistribution, 202–203
- BIND (Berkeley Internet Name Domain), 128
- BIS (Bump in the Stack), 273
- bits, netmasks, 6
- BITSLABEL resource records, 129
- black holes, 196
- blocking 6to4 traffic, 248
- Border Gateway Protocol. *See* BGP
- Border Gateway Protocol 4 (BGP-4). *See* BGP-4
- border routers, 245
- boundaries, 6bone, 369
- Bump in the Stack (BIS), 273

C

caches, 108

- adding static entries, 110
- deleting, 111
- viewing adjacency entries, 109

 CATNIP (Common Architecture for the Internet), 11
 ccTLDs (country code Top-Level Domains), 128
 CEF (Cisco Express Forwarding), 79, 211–213
 change-policies, route maps, 171
 Checksum

- fields, 26
- headers, 43

 CIDR (classless interdomain routing), 5, 60
 Cisco Express Forwarding (CEF). *See* CEF
 Class A addresses, 6
 Class B addresses, 6

- classes (IPv4), 6–8
 - exhaustion of space, 9–11
 - growth, 8–9
 - IANA allocation, 8
- classless interdomain routing (CIDR), 5, 60
- clear bgp ipv6 command, 184
- clear commands, NAT-PT, 270
- clear ipv6 ospf command, 211
- clear ipv6 rip command, 192
- clear isis command, 205
- clients
 - SSH, 143
 - Teredo, 261
- CLNP (Connectionless Network Protocol), 11, 193, 200
- CLNS (Connectionless Network Service), 193
- coexistence
 - dual stacks, 228
 - applications, 228–229
 - enabling, 233–234
 - selection, 230–233
 - strategies, 227, 372
- collisions, NAT, 15
- combination of IPv6 address compression methods, 56
- commands
 - 6to4 routers, 248–251
 - bgp router-id ipv4-address, 164
 - clear bgp ipv6, 184
 - clear ipv6 ospf, 211
 - clear ipv6 rip, 192
 - clear isis, 205
 - clear NAT-PT, 270
 - debug
 - ICMPv6, 103
 - NAT-PT, 270
 - debug bgp, 184
 - debug ipv6 cef, 213
 - debug ipv6 packet, 141
 - debug ipv6 rip, 192
 - debug isis, 205
 - dynamic NAT-PT, 271
 - FreeBSD, 316–317
 - ifconfig interface, 315
 - ip name-server, 128
 - ip route ipv4-prefix mask null 0, 182
 - ipv6 access-list, 130
 - ipv6 adu, 296
 - ipv6 host, 128
 - ipv6 icmp error-interval, 126
 - ipv6 nd dad, 122
 - ipv6 nd ns-interval, 111
 - ipv6 nd reachable-time, 111
 - ipv6 redirects, 126
 - ipv6 route rip, 187
 - ipv6 router ospf, 207
 - ipv6 suppress-ra, 118
 - ipv6 unicast-routing, 79
 - ISATAP tunnels, 259
 - isis circuit-type level-2-only, 200
 - Linux, 326
 - NAT-PT, 267
 - neighbor ipv6-address prefix-list, 169
 - netsh interface ipv6 install, 289
 - netsh interface ipv6 interface number, 293
 - netsh interface ipv6 set privacy state=disabled, 295
 - netsh interface ipv6 show interface 4, 295
 - no adjacency-check, 195
 - no bgp default ip4-unicast, 167
 - ping, 141, 250
 - ping6, 297
 - redistribute isis, 204
 - RIPng router, 189–190
 - route add-inet6 default, 315
 - route-map, 170–171
 - route-map PreferAS65100 permit 10, 172
 - router bgp, 165
 - set ipv6, 171
 - set ipv6 next-hop, 171
 - show
 - CEFv6, 212–213
 - NAT-PT, 270
 - show bgp ipv6, 183
 - show ip prefix-list, 184
 - show ipv6 nat translations, 270
 - show ipv6 neighbors, 110
 - show ipv6 rip, 192
 - show ipv6 route, 158, 161
 - show isis, 204
 - ssh, 143
 - static route configuration, 159–161
 - telnet, 142
 - traceroute, 142

- tracert6, 297
 - Tru64 UNIX, 336–338
 - Common Architecture for the Internet (CATNIP), 11
 - compressed IPv6 address representation, 55
 - configuration, 79
 - 6to4 routers, 248–251
 - autoconfiguration, 21–22, 112–121
 - BGP4+, 163, 167
 - DHCP, 144
 - dynamic NAT-PT, 270
 - enabling IPv6, 79
 - GRE tunnels, 256
 - intervals between neighbor solicitation, 111
 - IS-IS, 197–198, 200–201
 - link-local addresses, 160, 173
 - loopback interfaces, 84
 - MD5 authentication, 180
 - NAT-PT, 268
 - network interfaces, 83–88
 - OSPFv3, 207–210
 - over data-link technologies, 80–82
 - prefix renumbering, 124
 - RIPng, 187–189
 - route maps, 172
 - stateless autoconfiguration
 - FreeBSD, 314–315
 - Linux, 324–326
 - Microsoft Windows, 293–296
 - Solaris, 306–308
 - Tru64 UNIX, 334–336
 - static addresses, 83
 - static routes, 159–161
 - tunnels, 239
 - FreeBSD, 317–319
 - Linux, 330, 332
 - Microsoft Windows, 298–301
 - Solaris, 310–312
 - Tru64 UNIX, 338–340
 - viewing interfaces, 242
 - unnumbered interfaces, 85
 - Connectionless Network Protocol (CLNP), 11, 193, 200
 - Connectionless Network Service (CLNS), 193
 - connections
 - 6bone, 355–356
 - addresses, 360–361
 - architecture, 359
 - qualifying pTLAs, 362–363
 - route registry, 366
 - routing policies, 363–365
 - topology, 357–358
 - BGP-4, 161
 - Mobile IP protocol, 146
 - mobility, 28–29
 - production IPv6 Internet, 370–371
 - address allocation, 374
 - aggregation, 374
 - customer networks, 372–373
 - hosts, 375
 - NAPs, 371–372
 - state of (NAT), 14
 - controlling tunnel establishment, 248
 - country code Top-Level Domains (ccTLDs), 128
 - CPE (Customer Premises Equipment), 144
 - Customer Premises Equipment (CPE), 144
- ## D
-
- DAD (Duplicate Address Detection), 68, 71, 121–123, 239
 - databases
 - FIB, 211
 - RIPng, 192
 - data-link technologies, IPv6 over, 80–82
 - debug bgp command, 184
 - debug commands
 - ICMPv6, 103
 - NAT-PT, 270
 - debug ipv6 cef command, 213
 - debug ipv6 packet command, 141
 - debug ipv6 rip command, 192
 - debug isis command, 205
 - debugging
 - ACLs, 141
 - prefixes, 124
 - DECnet (Digital Equipment Corporation network protocol), 228
 - Deering, Steve, 11
 - default parameters, overriding, 115
 - default routes
 - advertising, 189
 - Linux, 326–328
 - Microsoft Windows, 296–297

- Solaris, 308–309
- Tru64 UNIX, 336
- default-free zones, 357
- defining
 - ACLs, 130–140
 - prefix lists, 168
 - route maps, 170, 174
- deleting neighbors, 111
- deployment
 - 6to4 mechanisms, 245–248
 - tunnels, 238–254
 - automatic IPv4, 260–261
 - GRE, 254–256
 - ISATAP, 256–259
 - selecting, 261
 - Teredo, 261
- design. *See also* configuration
 - IS-IS networks, 194–197
 - overview of, 5
 - tunnels, 238–254
 - automatic IPv4, 260–261
 - GRE, 254–256
 - ISATAP, 256–259
 - selecting, 261
 - Teredo, 261
- Destination Options header, 49
- destinations, 163
- detection, DAD, 121–123, 239
- development
 - design upgrades to, 5
 - of IPv6, 11–12
- DHCP (Dynamic Handshake Challenge Protocol), 144
- Differentiated Services Code Point (DSCP), 42, 135
- Digital Equipment Corporation network protocol (DECnet), 228
- disabling advertisements, 117
- Distance Vector Multicast Routing Protocol (DVMRP), 234
- distribution, Linux, 323–324
- DNAME resource records, 129
- DNS (Domain Name System), 127, 230
 - AAAA records, 127–129
 - PTR, 129
- domains
 - BIND, 128
 - ccTLDs, 128

- gTLDs, 128
- IGP, 184–186
 - IS-IS, 193–205
 - RIP, 186–192
- downstream provider prefix allocation, 360
- DSCP (Differentiated Services Code Point), 42, 135
- DSTM (Dual-Stack Transition Mechanism), 274
- dual stacks, 227–228
 - ALGs, 262–264
 - applications, 228–229
 - automatic IPv4-compatible tunnels, 260
 - enabling, 233–234
 - hosts, 243
 - nodes, 32
 - selection, 230–233
- Dual-Stack Transition Mechanism (DSTM), 274
- Duplicate Address Detection (DAD), 68, 71, 239
- DVMRP (Distance Vector Multicast Routing Protocol), 234
- Dynamic Handshake Challenge Protocol (DHCP), 144
- dynamic NAT-PT, 265, 270

E

- edge routers, 247
- efficient headers, 25–26
- EGP (Exterior Gateway Protocol), 161–177
- EIGRP (Enhanced Interior Gateway Routing Protocol), 211
- embedded IPv4 addresses, IPv6 addresses with, 57
- enabling
 - 6to4 mechanisms, 248–251
 - 6to4 tunnels, 302
 - BGP-4+, 163
 - CEFv6, 212
 - configured tunnels, 241
 - DAD, 122
 - dual stacks, 233–234
 - dynamic NAT-PT, 271–272
 - GRE tunnels, 255
 - IPv6, 79
 - ISATAP tunnels, 258
 - IS-IS, 197–205
 - Microsoft Windows, 289–291
 - NAT-PT, 267

- network interfaces, 83–88
 - plug and play, 22
 - RIPng, 187
 - Solaris, 306
 - stateless autoconfiguration, 294, 314
 - Encapsulating Security Payload (ESP), 30, 51, 145
 - encapsulation, GRE, 236
 - end-to-end IPv6 sessions, 246
 - end-to-end network security, inhibition of, 14
 - errors. *See also* troubleshooting
 - ICMPv4, 236
 - ICMPv6, 102–104
 - ESP (Encapsulating Security Payload), 30, 51, 145
 - Ethernet
 - IPv6 over, 80
 - multicast addresses, 81
 - EUI-64 (Extended Unique Identifier), 62
 - IPv6 addresses, 82
 - static address configuration, 85
 - European IPv6 Task Force, 377
 - exchanging
 - IPX, 228
 - routes between BGP peers, 177–179
 - exhaustion of IPv4 address space, 9–11
 - existing networks, 234–237
 - automatic IPv4, 260–261
 - deploying, 238–254
 - GRE, 254–256
 - ISATAP, 256–259
 - selecting, 261
 - Teredo, 261
 - extended ACLs, defining, 133–140
 - Extended Unique Identifier 64 (EUI-64), 62
 - extensions
 - headers, 27, 47–52
 - privacy, 295
- ## F
-
- fast forwarding, CEF, 211–213
 - features of
 - IPSec, 29–30
 - IPv6, 16
 - aggregation, 19
 - autoconfiguration, 21–22
 - efficient headers, 25–26
 - Flow Label fields, 26
 - global reachability, 18
 - hierarchy levels, 18
 - larger address spaces, 16–17
 - multicast use, 24–25
 - multiple addresses, 20–21
 - renumbering, 22–24
 - mobility, 28–29
 - Options field, 27
 - transition, 31–32
 - FIB (Forwarding Information Database), 211
 - fields
 - Checksum, 26
 - Flow Label, 26
 - ICMPv6 packets, 102
 - IP headers, 41
 - extension, 47–52
 - formats, 41–44
 - IPv6, 44–47
 - MTU, 52–53
 - TCP, 52
 - UDP, 52
 - multicast addresses, 69
 - Next Header, 28
 - Options, 27, 43
 - successive 16-bit, 55
 - filtering, 236
 - 6to4 traffic, 248
 - packets, 137
 - prefixes, 167
 - firewalls, 236. *See also* security
 - flags, multicast addresses, 69
 - Flow Label fields, 26
 - Forgie, Jim, 13
 - formats
 - EUI-64, 82, 85
 - IP addresses, 59
 - IP headers, 41–44
 - extension, 47–52
 - IPv6, 44–47
 - MTU, 52–53
 - TCP, 52
 - UDP, 52
 - multicast addresses, 69
 - formatting
 - 6to4 routers, 248–251
 - ACLs, 130

- autoconfiguration, 21–22, 112–121
- BGP4+, 163, 167
- DHCP, 144
- dynamic NAT-PT, 270
- enabling IPv6, 79
- GRE tunnels, 256
- intervals between neighbor solicitation, 111
- IS-IS, 197–198, 200–201
- link-local addresses, 160, 173
- loopback interfaces, 84
- MD5 authentication, 180
- NAT-PT, 268
- network interfaces, 83–88
- OSPFv3, 207–210
- over data-link technologies, 80–82
- prefix renumbering, 124
- RIPng, 187–189
- route maps, 172
- stateless autoconfiguration
 - FreeBSD, 314–315
 - Linux, 324–326
 - Microsoft Windows, 293–296
 - Solaris, 306–308
 - Tru64 UNIX, 334–336
- static addresses, 83
- static routes, 159–161
- tunnels, 239
 - FreeBSD, 317–319
 - Linux, 330, 332
 - Microsoft Windows, 298–301
 - Solaris, 310–312
 - Tru64 UNIX, 338–340
 - viewing interfaces, 242
- unnumbered interfaces, 85
- forwarding CEF, 211–213
- Forwarding Information Database (FIB), 211
- FQDN (fully qualified domain name), 60, 230
- Fragment Offset, 43
- FreeBSD, 312–313
 - managing, 316–317
 - stateless autoconfiguration, 314–315
 - static addresses, 315–316
 - tunnels, 317–319
 - verifying, 313
- fully qualified domain name (FQDN), 60, 230
- functionalities of ICMPv6, 103
- functions, 230. *See also* commands

G

- gateways
 - addresses (Microsoft Windows), 296
 - ALGs, 262–264
 - SOCKS-based IPv6/IPv4, 274
- generic routing encapsulation. *See* GRE
- generic Top-Level Domains (gTLDs), 128
- gethostbyname function, 230
- global BGP router configuration mode, 169
- Global Internet Routing Table, 10
- global reachability, 18
- government support of IPv6, 380
- GRE (generic routing encapsulation), 236
 - IS-IS, 200–201
 - tunnels, 254–256
- growth
 - development of IPv6, 11–12
 - hierarchical classes, 7
 - future growth of Internet, 8–9
- gTLDs (generic Top-Level Domains), 128

H

- HD ratio, 8
- HDLC (High-level Data Link Control), 81
- headers
 - AH, 30, 145
 - AU, 14
 - Checksum, 43
 - Destination Options, 49
 - efficiency of, 25–26
 - ESP, 51
 - extension, 27
 - Hop-by-Hop Options, 48
 - IP, 41
 - extension, 47–52
 - formats, 41–44
 - IPv6 formats, 44–47
 - MTU, 52–53
 - TCP, 52
 - UDP, 52
 - Multiple extension, 51
 - Routing, 49

- hierarchies
 - 6bone, 357–358
 - classes, 6–8
 - exhaustion of, 9–11
 - growth, 8–9
 - IANA allocation, 8
 - levels of, 18
 - High-Level Data Link Control (HDLC), 81
 - history of IPv6, 11–12
 - Homogeneous Communications, 260
 - Hop-by-Hop Options header, 48
 - hops
 - multihop eBGP peering, 166
 - NEXT_HOP attribute, 173
 - next-hop
 - addresses, 160
 - RIPng, 192
 - hosts
 - autoconfiguration, 21–22
 - DHCP, 144
 - dual stacks, 243
 - implementations, 340. *See also* operating systems
 - ipv6 host command, 128
 - IPv6 Internet connections, 375
 - ISATAP, 256
 - tunneling, 237
 - HTTP (Hypertext Transfer Protocol), 144
-
- IANA (Internet Assigned Numbers Authority), 6
 - allocation, 8
 - assignment of aggregatable global unicast prefixes, 66
 - ICMPv4 (Internet Control Message Protocol), 236
 - ICMPv6 (Internet Control Message Protocol for IPv6), 102–104, 160
 - Identification Flags, 43
 - IETF (Internet Engineering Task Force), 5
 - IETF Internet Experiment Note 199, 13
 - ifconfig interface command, 315
 - IGP (Interior Gateway Protocol), 184–186
 - EIGRP, 211
 - IS-IS, 193–205
 - OSPFv3, 205–211
 - redistribution, 182
 - RIP, 186–192
 - illegal IPv6 compressed address representations, 56
 - implementations, hosts, 340. *See also* operating systems
 - inhibition of end-to-end network security, 14
 - input route announcements, filtering, 168
 - installation
 - FreeBSD, 313
 - Linux, 323–324
 - netsh interface ipv6 install command, 289
 - Solaris, 306
 - integrated IS-IS, 193–205
 - integration
 - dual stacks, 228
 - applications, 228–229
 - enabling, 233–234
 - selection, 230–233
 - strategies, 227
 - interaction of ALGs, 262–264
 - interconnections, IS-IS, 199
 - interfaces, 160
 - advertisements, 117
 - ALGs, 263
 - configuration, 86
 - FreeBSD, 314–315
 - ISATAP, 257
 - IS-IS, 199
 - Linux, 326
 - loopback configuration, 84
 - MTU configuration, 86
 - networks, 83–88
 - RIPng, 187–189
 - routers, 173
 - Solaris, 306–308
 - stateless autoconfiguration, 294
 - tunnels, 242
 - types of IPv6 addresses, 61
 - aggregatable global unicast, 65–67
 - link-local, 62–63
 - multicast, 67–76
 - site-local, 63–65
 - unnumbered configuration, 85
 - Windows XP, 291
 - intermediary routers, 158. *See also* routers
 - Internet
 - 6to4 relays, 253

- CATNIP, 11
- future growth of, 8–9
- IPv6, 366
 - address allocation, 367–369
 - connection to, 370–374
 - regional registries, 366
- redistribution of unused address space, 6
- regional registries, 7
- Internet Assigned Numbers Authority (IANA), 6
- Internet Control Message Protocol (ICMPv4), 236
- Internet Control Message Protocol for IPv6 (ICMPv6), 102–104, 160
- Internet Engineering Task Force (IETF), 5
- Internet Packet Exchange (IPX), 228
- Internet Protocol Security. *See* IPsec
- Internet Stream Protocol (ST), 12
- Internet Streaming Protocol version 2 (ST2), 13
- Internetwork Packet Exchange (IPX) protocol, 78
- internetworking
 - FreeBSD, 312–313
 - 6to4 tunnels, 319–321
 - managing, 316–317
 - stateless autoconfiguration, 314–315
 - static addresses, 315–316
 - tunnels, 317–319
 - verifying, 313
 - Linux, 322–323
 - 6to4 tunnels, 332
 - managing, 328–329
 - stateless autoconfiguration, 324–326
 - static addresses, 326–328
 - tunnels, 330
 - verifying, 323–324
 - Microsoft Windows, 287–289
 - 6to4 tunnels, 301–305
 - enabling, 289–291
 - managing, 297–298
 - stateless autoconfiguration, 293–296
 - static addresses, 296–297
 - tunnels, 298–301
 - verifying, 291–293
 - Solaris, 305
 - enabling, 306
 - managing, 309–310
 - stateless autoconfiguration, 306–308
 - static addresses, 308–309
 - tunnels, 310–312
 - Tru64 UNIX, 334
 - managing, 336–338
 - stateless autoconfiguration, 334–336
 - static addresses, 336
 - tunnels, 338–340
- intervals between neighbor solicitation, configuring, 111
- Intrasite Automatic Tunnel Addressing Protocol (ISATAP), 256
- IOS (Internet Operating System) configuration, 79
 - enabling IPv6, 79
 - network interfaces, 83–88
 - over data-link technologies, 80–82
- IP (Internet Protocol), 41
 - headers, 41–44
 - extension, 47–52
 - IPv6, 44–47
 - MTU, 52–53
 - TCP, 52
 - UDP, 52
 - Mobile IP protocol, 146
- ip name-server command, 128
- IP Next Generation (IPng), 11
- ip route ipv4-prefix mask null 0 command, 182
- IPng (IP Next Generation), 11
- IPsec (Internet Protocol Security), 29–30
 - AH, 145
 - ESP, 145
- IPv4 (Internet Protocol version 4)
 - ACL denying protocol 41, 250
 - address space, 6–8
 - exhaustion of, 9–11
 - growth, 8–9
 - IANA, 8
 - automatic IP-v4 compatible tunnels, 260–261
 - compatible IPv6 addresses, 74
 - design upgrades to IPv6, 5
 - embedded with Ipv6 addresses, 57
 - header formats, 41–44
 - transition from, 31–32
- IPv5 (Internet Protocol version 5), 12
- IPv6 (Internet Protocol version 6), 366
 - address allocation, 369, 367–369
 - connection to, 370–371
 - address allocation, 374
 - aggregation, 374
 - customer networks, 372–373

- hosts, 375
- NAPs, 371–372
- regional registries, 366
- features of, 16
 - aggregation, 19
 - autoconfiguration, 21–22
 - efficient headers, 25–26
 - Flow Label fields, 26
 - global reachability, 18
 - hierarchy levels, 18
 - IPSec, 29–30
 - larger address spaces, 16–17
 - mobility, 28–29
 - multicast use, 24–25
 - multiple addresses, 20–21
 - Options field, 27
 - renumbering, 22–24
 - transition, 31–32
- headers
 - extension, 47–52
 - formats, 44–47
 - MTU, 52–53
 - TCP, 52
 - UDP, 52
- ipv6 access-list command, 130
- ipv6 adu command, 296
- IPv6 backbone (6bone), 12, 355–356
 - addresses, 360–361
 - architecture, 359
 - qualifying pTLAs, 362–363
 - route registry, 366
 - routing policies, 363–365
 - topology, 357–358
- IPv6 Control Protocol (IPv6CP), 81
- IPv6 exchange point (IPv6 IX), 173
- IPv6 Forum, 376
- ipv6 host command, 128
- ipv6 icmp error-interval command, 126
- IPv6 IX (IPv6 exchange point), 173
- ipv6 nd dad attempts command, 122
- ipv6 nd ns-interval command, 111
- ipv6 nd prefix command, 124
- ipv6 nd reachable-time command, 111
- ipv6 nd suppress-ra command, 118
- ipv6 redirects command, 126
- ipv6 router ospf command, 207
- ipv6 router rip command, 187

- IPv6 stateful address configuration, 22. *See also* autoconfiguration
- IPv6 Technology Preview For Windows 2000, 287
- ipv6 unicast-routing command, 79
- ipv6-prefix parameter, 160
- IPX (Internetwork Packet Exchange) protocol, 78, 228
- ISATAP (Intrasite Automatic Tunnel Addressing Protocol), 256
- IS-IS (Intermediate System to Intermediate System), 193–205
 - redistribution, 182
 - RIPng, 192
- isis circuit-type level-2-only command, 200

J

- Japan IPv6 Promotion Council, 377–378
- Jumbograms, 48, 53

K

- KAME Project, 312, 322

L

- L2TP (Layer 2 Tunneling Protocol), 234
 - large MTUs, 53
- Layer 2 Tunneling Protocol (L2TP), 234
 - legal prefix lengths, 6bone, 364
 - lengths, legal 6bone prefixes, 364
 - level-2 routers, IS-IS, 195
 - levels of addressing hierarchies, 18
 - lifetime values, privacy extensions, 295
 - limitations of NAT-PT, 267
- Link State Packets (LSPs), 193
- link-layer addresses, autoconfiguration, 21–22
- link-local addresses, 23, 62–63, 160, 173
- links
 - ISATAP, 256
 - point-to-point, 239
- Linux, 322–323
 - managing, 328–329
 - stateless autoconfiguration, 324–326

- static addresses, 326–328
- tunnels, 330, 332
- verifying, 323–324
- LIR (Local Internet Registry), 368
- lists
 - ACLs
 - applying, 130
 - creating, 130
 - defining, 130–133
 - managing, 140
 - securing networks, 129
 - extended ACLs, 133–140
 - Potential Touter List, 256
 - prefixes
 - applying, 168
 - defining, 168
 - verifying, 184
- Local Internet Registry (LIR), 368
- local preference attribute, modifying, 172
- logs. *See also* reports, 103
- loopback addresses, 74
- loopback interface configuration, 84
- LSPs (Link State Packets), 193

M

- MAC (Media Access Control), 22
- management
 - ACLs, 140
 - BGP4+, 183–184
 - FreeBSD, 316–317
 - IS-IS, 204
 - Linux, 328–329
 - Microsoft Windows, 297–298
 - NAT-PT, 270
 - OSPFv3, 211
 - RIPng, 192
 - Solaris, 309–310
 - Tru64 UNIX, 336–338
- mapping
 - dynamic NAT-PT, 272
 - multicast addresses, 81
 - NAT-PT, 269
 - route-map command, 170
- routes
 - aggregatable global unicast addresses, 174
 - applying, 171
- masks
 - networks
 - IPv4, 6–8
 - prefixes, 60
 - VLSM, 61
- Maximum Transmission Unit (MTU), 86
- MD5 authentication, 180
- mechanisms
 - automatic IPv4-compatible tunnel, 260
 - DSTM, 274
 - ICMPv6, 103
 - ISATAP, 258
 - NDP, 105–106
 - DAD, 121–123
 - prefix renumbering, 123–125
 - replacing ARP, 107–111
 - router redirection, 125
 - stateless autoconfiguration, 112–121
 - PMTUD, 104–105
 - Teredo, 261
 - transitions, 262
 - ALGs, 262–264
 - NAT-PT, 264–273
 - translation, 273–274
 - tunneling, 261
- Media Access Control (MAC), 22
- messages, update (BGP-4), 161
- Microsoft Research (MSR), 287
- Microsoft Windows, 287–289
 - 6to4 tunnels, 301–305
 - enabling, 289–291
 - managing, 297–298
 - stateless autoconfiguration, 293–296
 - static addresses, 296–297
 - tunnels, 298–301
 - verifying, 291–293
- Mobile IP protocol, 29, 146
- Mobile Wireless Internet Forum (MWIF), 380
- mobility, 28–29
- modes, CEF, 211
- modification
 - local preference attribute, 172
 - NEXT_HOP attributes, 173
 - prefix advertisement parameters, 119

MSR (Microsoft Research), 287
 MTU (Maximum Transmission Unit), 52–53
 configuration, 86
 PMTUD. *See* PMTUD
 tunneling, 236
 multicast addresses, 24–25, 67–76
 mapping, 81
 solicited-node, 71
 multihoming, 20–21
 multihop eBGP peering, 166
 multiple addresses, 20–21
 multiple AS paths, 162
 multiple extension headers, 51
 multiple levels of hierarchy, 18
 multitopology, IS-IS, 197
 MWIF (Mobile Wireless Internet Forum), 380

N

names
 ACLs, 130
 arguments, 168
 BIND, 128
 DNS, 127
 AAAA records, 127–129
 PTR, 129
 FQDN, 230
 ip name-server command, 128
 prefix-list-name argument, 168
 service queries, 231
 NAPs (network access points), 371–372
 NASP (Network Service Access Point), 11
 NAT (Network Address Translation), 5, 13, 236
 National Institute for Research in Computer Science
 and Control (NRIA), 312
 NAT-PT (Network Address Translation Protocol
 Translation), 54, 264
 Naval Research Laboratory (NRL), 312
 NDP (Neighbor Discovery Protocol), 62, 105–106,
 126
 ARP, 107–111
 DAD, 121–123
 prefix renumbering, 123–125
 router redirection, 125
 stateless autoconfiguration, 112–121
 neighbor ipv6-address prefix-list command, 169

neighbors
 adjacency entries, 109
 BGP
 aggregatable global unicast addresses, 174
 applying prefix lists, 168
 assigning, 164
 BGP-4, 161
 deleting, 111
 intervals between solicitation, 111
 static entries, 110
 NET (Network Entity Title) address, 198
 NetBSD. *See also* FreeBSD, 322
 netmasks, 6
 netsh interface ipv6 install command, 289
 netsh interface ipv6 set privacy state=disabled
 command, 295
 netsh interface ipv6 show interface 4 command, 295
 netsh interface ipv6 show interface number
 command, 293
 network access points (NAPs), 371–372
 Network Address Translation (NAT), 5
 tunneling, 236
 network address translation (NAT), 13–15
 Network Address Translation Protocol Translation
 (NAT-PT), 54, 264
 Network Entity Title (NET) address, 198
 Network Layer Protocol Identifier (NLPID), 193
 network layer reachability information (NLRI), 163
 Network Service Access Point (NSAP), 11, 78
 networks
 connection to, 372–373
 FreeBSD, 312–313
 6to4 tunnels, 319–321
 managing, 316–317
 stateless autoconfiguration, 314–315
 static addresses, 315–316
 tunnels, 317–319
 verifying, 313
 interfaces, 83–88
 IS-IS design, 194–197
 Linux, 322–323
 6to4 tunnels, 332
 managing, 328–329
 stateless autoconfiguration, 324–326
 static addresses, 326–328
 tunnels, 330, 332
 verifying, 323–324

- masks
 - IPv4, 6–8
 - prefixes, 60
- Microsoft Windows, 287–289
 - 6to4 tunnels, 301–305
 - enabling, 289–291
 - managing, 297–298
 - stateless autoconfiguration, 293–296
 - static addresses, 296–297
 - tunnels, 298–301
 - verifying, 291–293
- Mobile IP protocol, 146
- reachability (TLVs), 193
- Solaris, 305
 - enabling, 306
 - managing, 309–310
 - stateless autoconfiguration, 306–308
 - static addresses, 308–309
 - tunnels, 310–312
- SSH, 143
- Telnet, 142
- Tru64 UNIX, 334
 - managing, 336–338
 - stateless autoconfiguration, 334–336
 - static addresses, 336
 - tunnels, 338–340
- tunneling, 234–237
 - automatic IPv4, 260–261
 - deploying, 238–254
 - GRE, 254–256
 - ISATAP, 256–259
 - selecting, 261
 - Teredo, 261
- VPN, 234
- Next Header field, 28
- NEXT_HOP
 - attribute, 173
 - values, 162
- Next-generation transition from IPv4 to IPv6 (NGtrans), 31
- next-hop addresses, 160, 192
- NGtrans (Next-Generation transition from IPv4 to IPv6), 31
- nibbles, PTR, 129
- NLPID (Network Layer Protocol Identifier), 193
- NLRI (network layer reachability information), 163

- no adjacency-check command, 195
- no bgp default ipv4-unicast command, 167
- nodes
 - 6bone, 357–358
 - ALGs, 262–264
 - FreeBSD, 314–315
 - ICMPv6, 102–104
 - Mobile IP protocol, 146
 - NAT-PT, 264–273
 - PMTUD, 104–105
 - required IPv6 addresses for, 76
 - solicited-node multicast addresses, 71
 - stacks, 32
- North American IPv6 Task Force, 378
- notations, CIDR, 60
- NRIA (National Institute for Research in Computer Science and Control), 312
- NRL (Naval Research Laboratory), 312
- NSAP (Network Service Access Point) allocation, 78
- numbering
 - debugging, 124
 - prefixes, 123–125
 - renumbering, 22–24

O

- OpenBSD, 322. *See also* FreeBSD
- operating systems, 287
 - FreeBSD, 312. *See also* FreeBSD
 - Linux, 322. *See also* Linux
 - Solaris, 305. *See also* Solaris
 - Tru64 UNIX, 334. *See also* Tru64 UNIX
 - Windows, 287
- optimization
 - of IPv6, 16–32
 - NAT-PT, 272
 - RIPng, 189–190
- Options field, 27, 43
- Organizational Unique Identifier (OUI), 22
- OSPFv3 (Open Shortest Path First version 3), 205–211
- OUI (Organizational Unique Identifier), 22
- output route announcements, filtering, 168
- overriding default parameters, 115

P

packets

- filtering, 137
- Flow Label fields, 26
- ICMPv6, 102–104
- IPX, 228
- LSPs, 193
- multicasting, 24
- NAT, 13–15
- PMTUD, 104–105
- RIPng, 192
- size, 53
- TL, 42
- tunneling, 234–237
 - automatic IPv4 deployment, 260–261
 - deploying, 238–254
 - GRE deployment, 254–256
 - ISATAP deployment, 256–259
 - selecting, 261
 - Teredo, 261

parameters

- modifying, 119
- overriding, 115
- prefix advertisements, 114
- seq-value, 168

passwords, 180. *See also* security

Path MTU Discovery. *See* PMTUD

paths

- administrative distances, 159
- black holes, 196
- multiple AS, 162
- routing tables, 158. *See also* routing

payloads, 41, 43. *See also* ESP

peering

- BGP, 165
 - exchanging routes, 177–179
 - MD5 authentication, 180
- multihop eBGP, 166
- NAPs, 372
 - between pTLAs and 6bone, 358

permitted announcements, 6bone, 364

ping command, 141, 250

ping6 command, 297

plug and play, enabling, 22

PMTUD (Path MTU Discovery), 53, 104–105

pointer (PTR), 129

point-to-point links, 239

policies

- address allocation, 367–369
- change-policies, 171
- routing, 363–365

Potential Router List, 256

preferences, routes, 172

preferred IPv6 address representation, 54

prefixes

- 6bone, 364
- 6to4, 245
 - advertising, 181–183
 - aggregatable global unicast addresses, 66
 - aggregation, 19
 - anycast, 254
 - autoconfiguration, 21–22
 - automatic assignment, 245
 - automatic IPv4-compatible tunnels, 260
 - debugging, 124
 - filtering, 167
 - ISATAP, 256, 258
 - lists
 - applying, 168
 - defining, 168
 - verifying, 184

modifying, 119

for multihoming, 20

NAT-PT, 267

NDP, 112

with network masks, 60

overriding, 115

pTLAs, 360

renumbering, 123–125

viewing, 114

prefix-length, 160

prefix-list-name argument, 168

priorities, administrative distances, 159

privacy extensions, 295

private addressing, 13, 247

production IPv6 Internet, 370–371

- address allocation, 374

- aggregation, 374

- customer networks, 372–373

- hosts, 375

- NAPs, 371–372

prohibited announcements, 6bone, 365

protocols

- ARP, 24
- BGP, 72
 - applying route maps, 171
 - assignment of neighbors, 164
 - exchanging routes, 177–179
 - managing, 183–184
 - MD5 authentication, 180
 - peering, 165
 - route redistribution, 181–183
 - security, 180
- BGP-4, 161
- CLNP, 11, 193
- DECnet, 228
- DHCP, 144
- DVMRP, 234
- HTTP, 144
- ICMPv6, 102–104
- IGP, 184–186
 - EIGRP, 211
 - IS-IS, 193–205
 - OSPFv3, 205–211
 - redistribution, 182
 - RIP, 186–192
- IPSec, 145
 - AH, 145
 - ESP, 145
- IPX, 78
- ISATAP, 256
- L2TP, 234
- Mobile IP, 29, 146
- NAT-PT, 54
- NDP, 62, 105–106, 126
 - DAD, 121–123
 - prefix renumbering, 123–125
 - replacing ARP, 107–111
 - router redirection, 125
 - stateless autoconfiguration, 112–121
- NLPID, 193
- routing, 157
 - administrative distances, 159
 - EGP, 161–177
 - viewing routing tables, 158
- RSVP, 13
- SCMP, 13
- SIPP, 11
- SMTP, 263

- ST, 12
- ST2, 13
- TCP, 52
- TFTP, 143
- translation, 228
- UDP, 52
- providers
 - aggregation, 374
 - IPv6, 371
- pseudo-interfaces
 - stateless autoconfiguration, 294
 - Windows XP, 291
- pTLAs (pseudo-Top-Level Aggregators), 163, 357, 362
- PTR (pointer), 129
- public 6to4 relays, 253

Q

- QoS (quality of service), 12
- qualification of pTLAs on 6bone, 362–363
- quality of service (QoS), 12
- querying
 - addresses, 230
 - naming services, 231

R

- ranges
 - IPv4, 6–8
 - IPX, 78
- ratios of internal and reachable IP addresses, 15
- REACH state, 109
- reachability
 - 6to4 routers, 250
 - TLVs, 193
- real-time data transmission, Flow Label fields, 26
- reassignment of address spaces, 368
- records
 - A6, 129
 - AAAA, 127–129
 - BITSLABEL, 129
 - DNAME, 129
 - PTR, 129
- redirection, routers, 125

- redistribute isis command, 204
- redistribution
 - BGP4+ into IS-IS, 202–203
 - IGP, 182
 - IS-IS, 182
 - RIPng, 182, 203–204
 - routes
 - BGP, 181–183
 - IS-IS, 202–204
 - OSPFv3, 210
 - RIPng, 190–192
 - of unused address space, 6
- reflexive ACLs, 138
- regional Internet registries (RIRs), 7, 12, 366
- registries
 - LIR, 368
 - regional Internet, 7, 12, 366
 - RIR, 12
 - routes (6bone), 366
- relays
 - 6to4, 251
 - FreeBSD, 321
 - Linux, 334
 - Microsoft Windows, 304
 - Teredo, 261
- reliability, administrative distances, 159
- renumbering, 22–24, 123–125
- replacing ARP, 107–111
- reports, ICMPv6, 102–104
- representations
 - IPv4-compatible IPv6 addresses, 75
 - of IPv6 addresses, 54–61
 - link-local addresses, 63
 - loopback addresses, 74
 - multicast addresses, 68
 - reserved anycast addresses, 73
 - site-local addresses, 65
 - solicited-node multicast addresses, 71
 - unspecified addresses, 74
- requests, router advertisements, 120
- required IPv6 addresses, 76
- Reseaux IP Europeans Network Coordination Center (RIPE NCC), 7
- reserved anycast addresses, 73
- resource records
 - A6, 129
 - AAAA, 127–129
 - BITSLABEL, 129
 - DNAME, 129
 - PTR, 129
- Resource Reservation Protocol (RSVP), 13
- responsibilities of IPv6 providers, 371
- restrictions of single SPFs, 194–197
- RIP (Routing Information Protocol), 186–192
- RIPE NCC (Reseaux IP Europeans Network Coordination Center), 7
- RIPng (Routing Information Protocol next generation), 186–192
 - IS-IS, 203–204
 - redistribution, 182
- RIRs (regional Internet registries), 7, 12, 366
- route add -inet6 default command, 315
- route-map command, 170–171
- route-map PreferAS65100 permit 10 command, 172
- router bgp command, 165
- routers
 - 6to4
 - enabling, 248–251
 - relays, 251
 - adjacency, 163, 194
 - advertisements
 - disabling, 117
 - requesting, 120
 - BGP-4, 161
 - BGP4+ configuration, 163
 - black holes, 196
 - border, 245
 - CEF, 211–213
 - dual-stack
 - automatic IPv4-compatible tunnels, 260
 - enabling, 233
 - edge, 247
 - enabling IPv6, 79
 - interfaces, 173
 - ISATAP, 256
 - IS-IS, 195
 - Potential Router List, 256
 - redirection, 125
 - required IPv6 addresses for, 76
 - RIP, 186–192
 - RIPng command, 189–190
 - routing protocols, 157
 - administrative distances, 159
 - viewing tables, 158

- stateless autoconfiguration, 294
- Telnet, 142
- tunneling, 237
- routes
 - aggregation, 19, 374
 - announcements, 168
 - BGP peers, 177–179
 - black holes, 196
 - configuration commands, 159–161
 - default
 - advertising, 189
 - Microsoft Windows, 296
 - Solaris, 308–309
 - FreeBSD, 315–316
 - Global Internet Routing Table, 10
 - Linux, 326–328
 - maps
 - aggregatable global unicast addresses, 173
 - applying, 171
 - redistribution
 - BGP, 181–183
 - IS-IS, 182, 202–204
 - OSPFv3, 210
 - RIPng, 182
 - registries, 366
 - RIPng redistribution, 190–192
 - Tru64 UNIX, 336
 - viewing, 158, 161
- routing
 - aggregation, 374
 - Global Internet Routing Table, 10
 - IS-IS, 193–205
 - policies (6bone), 363–365
 - protocols, 157
 - administrative distances, 159
 - EGP, 161–177
 - viewing routing tables, 158
- Routing header, 49
- Routing Information Protocol next generation. *See* RIPng
- RSVP (Resource Reservation Protocol), 13
- scope, multicast addresses, 69–70
- scripts, tru64 UNIX, 339
- searching 6to4 relays, 253
- Secure Shell (SSH), 143
- security, 145
 - ACLs, 129. *See also* ACLs
 - AH, 145
 - BGP, 180
 - ESP, 30, 145
 - IPSec, 29–30
 - NAT, 14
 - networks, 129
- selection of
 - dual stacks, 230–233
 - tunneling mechanisms, 261
- seq-value parameter, 168
- servers
 - autoconfiguration, 21–22
 - Global Internet Routing Table, 10
 - HTTP, 144
 - ip-name-server command, 128
 - ISATAP, 256
 - NAT, 15
 - SSH, 143
 - Teredo, 261
 - TFTP, 143
 - tunnels, 244
- services, naming, 231
- set ipv6 command, 171
- set ipv6 next-hop command, 171
- shipworms, 261
- show bgp ipv6 command, 183
- show commands
 - CEFv6, 212–213
 - NAT-PT, 270
- show ip prefix-list command, 184
- show ipv6 nat translations command, 270
- show ipv6 neighbors command, 110
- show ipv6 rip command, 192
- show ipv6 route command, 158, 161
- show isis command, 204
- SIIT (Stateless IP/ICMP Translator) algorithm, 264
- Simple Internet Protocol Plus (SIPP), 11
- single SPF restrictions, 194–197
- SIPP (Simple Internet Protocol Plus), 11
- site-local addresses, 63–65
- size, 16–17

S

- scalability, automatic IPv4-compatible tunnels, 261
- SCMP (Stream Control Message Protocol), 13

- address spaces, 16–17
 - packets, 53
 - SMTP (Simple Mail Transfer Protocol), 263
 - SOCKS-based IPv6/IPv4 gateway, 274
 - Solaris, 305
 - enabling, 306
 - managing, 309–310
 - stateless autoconfiguration, 306–308
 - static addresses, 308–309
 - tunnels, 310–312
 - solicitation
 - advertisements, 120
 - neighbors, 107
 - solicited-node multicast addresses, 71
 - space (addresses)
 - aggregatable global unicast, 67
 - architecture, 77–78
 - automatic IPv4-compatible tunnels, 261
 - NAT, 13–15
 - reassignment of, 368
 - size, 16–17
 - specification of router interfaces, 173
 - SPF (Shortest Path First), restrictions, 194–197
 - SSH (Secure Shell), 143
 - ST (Internet Stream Protocol), 12
 - ST2 (Internet Streaming Protocol version 2), 13
 - stacks
 - BIS, 273
 - dual, 227–228
 - ALGs, 262–264
 - applications, 228–229
 - automatic IPv4-compatible tunnels, 260
 - enabling, 233–234
 - hosts, 243
 - selection, 230–233
 - nodes, 32
 - STALE state, 109
 - starting IS-IS, 199
 - state of connections, NAT, 14
 - stateless autoconfiguration
 - DAD. *See* DAD
 - FreeBSD, 314–315
 - Linux, 324–326
 - Microsoft Windows, 293–296
 - NDP, 112–121
 - Solaris, 306–308
 - Tru64 UNIX, 334–336
 - Stateless IP/ICMP Translator (SIIT) algorithm, 264
 - static addresses
 - configuring, 83
 - FreeBSD, 315–316
 - Linux, 326–328
 - Microsoft Windows, 296
 - Solaris, 308–309
 - Tru64 UNIX, 336
 - static NAT-PT, 265, 268
 - static neighbor entries, adding, 110
 - static routes
 - configuration commands, 159–161
 - IS-IS, 202
 - redistribution, 181
 - RIPng, 191
 - strategies
 - coexistence and integration, 227
 - coexistence and transition, 372
 - Stream Control Message Protocol (SCMP), 13
 - subnet-router anycast addresses, 73
 - subnetting, 60
 - successive 16-bit fields, 55
 - summaries, aggregation, 19
 - support, 375
 - 3G, 379
 - BGP-4, 162–177
 - European IPv6 Task Force, 377
 - governments, 380
 - ISATAP, 256
 - Japan IPv6 Promotion Council, 377–378
 - MWIF, 380
 - North American IPv6 Task Force, 378
 - switching, CEF, 211–213
- ## T
-
- tables
 - CEF, 211–213
 - Global Internet Routing Table, 10
 - neighbors, 108
 - adding static entries, 110
 - deleting, 111
 - viewing adjacency entries, 109
 - routing, 157
 - administrative distances, 159
 - viewing routing tables, 158

- TCP (Transmission Control Protocol), 52
 - TCP/UDP Over CLNP-Addressed Networks (TUBA), 11
 - Telnet, 142
 - Teredo tunneling mechanisms, 261
 - TFTP (Trivial File Transfer Protocol), 143
 - Tier-1 providers, 357
 - time intervals between neighbor solicitation, configuring, 111
 - time-based ACLs, 138
 - Time-to-Live. *See* TTL
 - TL (Total Length), 42
 - TLA (Top-Level Aggregator), 163
 - TLVs (Type-Length Values), 193
 - tools
 - HTTP, 144
 - ping command, 141
 - SSH, 143
 - Telnet, 142
 - TFTP, 143
 - traceroute command, 142
 - Top-Level Aggregator (TLA), 163
 - topologies, 6bone, 357–358
 - TOS (Type of Service), 42
 - Total Length (TL), 42
 - traceroute command, 142
 - tracert6 commands, 297
 - traffic
 - 6to4 blocking/filtering, 248
 - CLNS, 193
 - NAPs, 371–372
 - transitions, 31, 372
 - automatic IPv4-compatible tunnels, 260–261
 - DSTM, 274
 - dual stacks, 228
 - applications, 228–229
 - enabling, 233–234
 - selection, 230–233
 - mechanisms, 262
 - ALGs, 262–264
 - NAT-PT, 264–273
 - translation
 - mechanisms, 273–274
 - NAT, 13–15, 236
 - NAT-PT, 264–273
 - protocols, 228
 - trends, 375
 - Trivial File Transfer Protocol (TFTP), 143
 - troubleshooting, 375
 - 3G, 379
 - European IPv6 Task Force, 377
 - governments, 380
 - HTTP, 144
 - ICMPv4, 236
 - Japan IPv6 Promotion Council, 377–378
 - MWIF, 380
 - North American IPv6 Task Force, 378
 - ping command, 141
 - SSH, 143
 - Telnet, 142
 - TFTP, 143
 - traceroute command, 142
 - Tru64 UNIX, 334
 - managing, 336–338
 - stateless autoconfiguration, 334–336
 - static addresses, 336
 - tunnels, 338–340
 - TTL (Time to Live), 26, 43
 - TUBA (TCP/UDP Over CLNP-Addressed Networks), 11
 - tunneling, 227, 234–237
 - 6to4, 319–321
 - automatic IPv4 deployment, 260–261
 - brokers, 243
 - deploying, 238–254
 - GRE
 - deployment, 254–256
 - IS-IS, 200–201
 - ISATAP, 256–259
 - Linux, 330, 332
 - Microsoft Windows, 298–305
 - between pTLAs and 6bone, 359
 - selecting, 261
 - Teredo, 261
 - Solaris, 310–312
 - Tru64 UNIX, 338–340
 - FreeBSD, 317–319
 - Type of Service (TOS), 42
 - Type-Length Values (TLVs), 193
 - types of IPv6 addresses, 61–76
-
- ## U
-
- UDP (User Datagram Protocol), 52

- unicast IP
 - growth, 8–9
 - IANA allocation, 8
 - IPv4, 6–8
- Uniform Resource Locator (URL), 59
- UNIX, 334
- unnumbered interface configuration, 85
- unspecified addresses, 74
- unused address space, redistribution of, 6
- updating BGP-4, 161
- URL (Uniform Resource Locator), 59

V

- values
 - administrative distances, 159
 - Flag fields, 69
 - lifetime privacy extensions, 295
 - MTU, 104–105
 - netmasks, 6
 - NEXT_HOP, 162
 - nibbles, 129
 - seq-value parameter, 168
 - TLVs, 193
 - TTL, 26
- Variable-Length Subnet Masks (VLSMs), 61
- verification
 - BGP4+, 183–184
 - FreeBSD, 313
 - IPv6 configuration, 86
 - OSPFv3, 211

- prefix lists, 184
- IS-IS, 204
- Linux, 323–324
- Microsoft Windows, 291–293
- videoconferencing, Flow Label fields, 26
- viewing
 - ACLs, 140
 - adjacency entries, 109
 - configured tunnel interfaces, 242
 - Global Internet Routing Table, 10
 - interfaces (Windows XP), 291
 - NAT-PT, 270
 - NDP prefix advertisement parameters, 114
 - RIPng packets, 192
 - routes, 161
 - routing tables, 158
- Virtual Private Network (VPN), 234
- VLSMs (Variable-Length Subnet Masks), 61
- VoIP (Voice over IP), 26
- VPN (Virtual Private Network), 234

W

- Windows (Microsoft), 287–289
 - enabling, 289–291
 - managing, 297–298
 - stateless autoconfiguration, 293–296
 - static addresses, 296–297
 - tunnels, 298–305
 - verifying, 291–293