



## Symbols

---

!, 200

## Numerics

---

4DMT line card, 127–128  
911 calling, 11

## A

---

- AAA, 59–60, 88, 154
  - accounting, 155
  - authentication, 154
  - authorization, 154
  - RADIUS, 157
    - accounting phase, 160–161
    - client profiles, 162
    - client/server model, 157
    - profiles, 161
    - service profiles, 162
    - transmission flow, 158–160
    - user profiles, 162–163
  - related RFCs, 154
- AAL (ATM Adaptation Layer), 366–367
  - AAL5, 62
- access protocols, 153
- access VPN services, LT2P, 168
- accounting, 59–60, 155
- accounting phase (RADIUS), 160–161
- ACLs (access control lists), 152
- activating PVCs, 297–298
- adjusting polling intervals, 325
- ADPCM (adaptive differential pulse code modulation), 113
- ADSL (Asynchronous DSL), 13
  - consumer-grade, 13
  - DMT, 16–17
    - DMT2, 17–19
    - G.Lite, 20
  - latency paths, 23
  - PPoA, 82
    - implementations, 86
    - IP addressing, 84–85
  - LCP, 83
  - NCP, 83
  - profiles
    - applying to interfaces, 293
    - creating, 289, 291
  - protocol stack, 83
  - VDSL, 13
- ADSL2, 20
- ADSL2+, 21
- aggregators, 10
  - Cisco 6400 UAC, 240
    - ATM switching configuration, 249–250
    - Layer 3 terminations, 250–261
    - redundancy, 241–248
    - VPN configurations, 262–264
- alarms, viewing, 305–307
- allocating IP addresses, 66
- AM (amplitude modulation), 15
- analog modems versus DSL, 6
- applying
  - ADSL profiles, 293
  - ATM QoS profiles to PVCs, 297
  - DMT profiles to DMT ports, 293
- APS (Automatic Protection Switching), 125.
  - See also* SONET APS
  - BER thresholds, configuring, 248
  - configuration commands, 210–211, 213–214
  - priority requests, 247–248
- architectures
  - data flow, 62–63
  - IP addressing, 63
    - address allocation, 66
    - dynamic, 64
    - NAT, 65
    - PAT, 65
    - PPP/ICP, 65
    - virtual templates, 63
  - IRB, 67
    - connectivity, 68
    - IP addressing, 68–69
    - protocol stack, 67–68
  - of CEMF/CDM, 272
  - point-to-point architecture, 9–11, 18–19, 59–96, 155–166
  - PPoA, 82
    - implementations, 86
    - IP addressing, 84–85
    - LCP, 83

- NCP, 83
  - protocol stack, 83
- PPoE, 74
  - connectivity, 76, 78–79
  - IP addressing, 79
  - protocol stack, 76
- RBE, 70, 72
  - IP addressing, 73
  - protocol stack, 72
- scalability, 58
- selecting, 9–11, 18–19, 59–96, 155–166
- TCP/IP security protocols, 59–60
- asymmetric versus symmetric services, 12
- ATM (Asynchronous Transfer Mode)
  - AAL, 366–367
  - cells, 363
    - headers, 373–375
    - rates, 376
  - classes of service, 364–365
  - connection types, 368–370
    - PVCs, 370
    - PVPs, 372
    - soft-PVCs, 371–372
  - IMA, configuring for DSL-to-ATM switching, 225–233
  - interface configuration commands, 176–177
  - interfaces, configuring on Cisco 827 routers, 194–195
  - PPoA, 82
    - implementations, 86
    - IP addressing, 84–85
    - LCP, 83
    - NCP, 83
    - protocol stack, 83
  - PVCs, configuring for DSL-to-ATM switching, 222
  - PVPs, configuring for DSL-to-ATM switching, 224–225
  - QoS profiles
    - applying to PVCs/SPVCs, 297
    - creating, 287–289
  - SPVCs, configuring for DSL-to-ATM switching, 223–224
  - statistical multiplexing, 364
  - traffic descriptors, 287
  - UBR, 378
  - VBR, 377
  - VCI, reserved numbers, 375
- ATM Interface Performance Data window (CDM Manager), 321–324
  - adjusting polling interval, 325

- ATM Interface Status, viewing in CDM, 308–312
- attaching profiles to ports, 221
- attenuation, 29
- ATU-R (Asymmetric Transceiver Units-Remote), 9, 116
- authentication, 60, 154
  - CHAP, 61, 153
    - configuring on Cisco 827 routers, 178–179
    - directory service conflicts, 156
  - PAP, 61, 153
    - proxy authentication, 155
- authorization, 60, 154
- autodiscovery, Cisco 6xxx routers, 281
- automatic rate adaptation, 40

## B

---

- backing up Cisco 6000 Series IP DSL switch configurations, 284
- bandwidth, demand for in residential market, 3–5
- BER thresholds, configuring for APS, 248
- BERT (Bit Error Rate Testing), 49
- binder group interference, 12
- binder groups, 12
- bit groupings, 16
- bit rate alarm threshold, 24
- bit swapping, 24
- BPDUs (bridge protocol data units), 67
- BRI (basic rate interface), 7
- bridged taps, 35–36
- bundle-enable command, 177

## C

---

- cable modems versus DSL, 7–8
- call start accounting, 160
- call stop accounting, 160
- CAP (Carrierless Amplitude Phase) modulation, 16
- capacitance, 30
- cards, alarm status severity levels, 273
- CBWFQ (class-based weighted fair queuing), 191
- CDM (Cisco DSL Manager). *See also* CEMF
  - architecture, 272
  - CEMF framework

- Chassis Inventory window, 328
- Cisco 6000 Series IP DSL switches, 282
  - chassis deployment, 278–281
  - Command History window, 285
  - Configuration Management and Restore, 283
  - deploying, 275–276
  - IOS Image Download window, 285–286
  - line card deployment, 281
  - Management Information window, 282
  - site deployment, 276–278
  - SNMP Management window, 286
  - System Log window, 285
- Deployment Summary window, 281
- device states, 274
- element management, FCAPS standards, 271–272
- fault management, 304–305
  - events, 305–307
  - status summaries, 308–320
- features, 269
- performance management, 320
  - ATM Interface Performance Data window, 321–325
  - saving historical data, 327–328
  - viewing historical data, 325–327
- profiles, uploading, 303–304
- PVCs
  - activating, 297–298
  - applying ATM QoS profiles, 297
  - configuring, 294–296
  - VCL management, 298–303
- quitting user sessions, 275
- SPVCs
  - activating, 297–298
  - applying ATM QoS profiles, 297
  - configuring, 294–296
- starting user sessions, 274–275
- subscriber management, 270
  - applying ADSL profiles, 293
  - applying DMT profiles, 293
  - creating ADSL profiles, 289–291
  - creating ATM QoS profiles, 287–289
  - creating DMT profiles, 291–293
- Subtend Manager, 329
- views, 272–273
- CE (customer edge) routers, 95
- cell header (ATM), 373–375
- cells, 363
- CEMF (Cisco Element Manager Framework), 270
  - architecture, 272
  - Class Palette window, 276
  - distributed management, 271
  - EMs
    - polling, 273–274
  - fault management, 304–305
    - events, 305–307
    - status summaries, 308–313, 315, 317–320
  - log files, 271
  - quitting user sessions, 275
  - sites, 272
  - starting user sessions, 274–275
  - views, 272–273
- Centralized Repair Service Bureau, 46
- Challenge response (RADIUS), 160
- Change Password response (RADIUS), 160
- CHAP (Challenge Handshake Authentication Protocol), 61, 153
  - configuring on Cisco 827 routers, 178–179
  - directory service conflicts, 156
- chassis (Cisco 6000 series)
  - autodiscovery, 281
  - commissioning, 282
  - deploying, 278–281
  - IP DSL Switches, 272
- Chassis Fault Management window, viewing in CDM, 318
- Chassis Inventory window (CDM), 328
- Chassis view (CDM), 273
- check bytes, 43
- Cisco 6000 Series IP DSL Switch, 203
  - autodiscovery, 281
  - CDM Configuration Management, 282
    - Command History window, 285
    - Configuration Backup and Restore, 283
    - IOS Image Download window, 285–286
    - Management Information window, 282
    - SNMP Management window, 286
    - System Log window, 285
  - chassis, 272
    - viewing inventory summary, 328
  - deploying in CDM, 275–276
    - chassis deployment, 278–281
    - line card deployment, 281
    - site deployment, 276–278
  - DSL-to-ATM switching configuration
    - IMA, 225–230, 232–233
    - PVCs, 222
    - PVPs, 224–225
    - SPVCs, 223–224

- subscriber profiles, 218–221
  - redundancy commands, 210–211, 213–214
  - reload redundancy commands, 216–217
  - secondary unit sync commands, 214–215
  - setup commands, 203–210
  - verifying NI-2 processes, 233–239
  - verifying redundancy states, 217
- Cisco 6015, 135–136
- IMA, 136–137
- Cisco 6160, 129, 131
- Cisco 6260, 131, 134–135
- Cisco 6400, 137–138
- hardware, 138–141
  - NLC, 144–146
  - NRP2 module, 143
  - NSP, 141–142
- Cisco 6400 UAC, 240
- ATM switching configuration, 249–250
  - Layer 3 terminations, 250
    - DHCP, 257
    - PPPoA, 250–256
    - PPPoE, 258–260
    - RADIUS, 258
    - RFC 2684 bridging, 260–261
  - redundancy, 241
    - APS priority requests, 247–248
    - NRP-1, 243
    - NRP-2, 243–244
    - NSPs, 242
    - SONET APS, 245–246
  - VPN configurations, 262–264
- Cisco 826 routers, 111
- Cisco 827 routers
- ATM interface configuration commands, 176–177
  - data configuration, 175–178
    - ATM interface commands, 176–177
    - CHAP, 178–179
    - Ethernet interface commands, 178
    - PPoA, 179, 181–182
    - PPoE, 186–188
    - RBE, 185
    - RFC 2684 bridging, 182–184
    - VPNs, 188
  - Ethernet interface configuration commands, 178
  - troubleshooting, 202
  - voice configuration, 189
    - data network phase, 190–198
    - dial peers, 196–198
    - H.323 signaling, 199
    - multiple PVCs, 201
- Cisco 827-4V routers, 111
- voice signaling concepts, 112–114
    - ITU-T standards support, 113–114
    - LLQ, 112
    - QoS, 113
    - REN, 113
- Cisco 827H routers
- voice signaling concepts, 112–114
    - LLQ, 112
    - QoS, 113
- Cisco 828 routers, 111
- Cisco Configuration Express, 110
- Cisco IOS Firewall suite, 154
- Cisco LRE, 382–383
- use in hospitality industry, 383–384
- Cisco SOHO 70 series routers, 108
- CRWS, 108
  - SOHO 71 router, 109
  - SOHO 76 router, 109
  - SOHO 77H router, 109–110
  - SOHO 78 router, 110
- CiscoShelf, 272
- class maps, configuring on Cisco 827 routers, 193
  - Class Palette window (CEMF), 276
  - classes of service (ATM), 364–365
  - CLECs (Competitive Local Exchange Carriers), 36
    - loop management, 47
  - client profiles (RADIUS), 162
  - client server model, RADIUS functionality, 157
  - CO/Exchange equipment
    - Cisco 6000 series IP DSL Switch, 203
      - DSL-to-ATM switching configuration, 218–233
        - redundancy commands, 210–214
        - reload redundancy commands, 216–217
        - secondary unit sync commands, 214–215
        - setup commands, 203–210
        - verifying NI-2 processes, 233–239
        - verifying redundancy states, 217
    - Cisco 6400 UAC, 240
      - ATM switching configuration, 249–250
      - Layer 3 terminations, 250–261
      - redundancy, 241–248
      - VPN configurations, 262–264
  - IP DSL switches, 114–116
    - Cisco 6015, 135–136
    - Cisco 6160, 129, 131
    - Cisco 6260, 131, 134–135

- line cards, 126–127
  - subtending, 117
- NI-2 features, 118, 122–123
  - APS, 125
  - redundancy, 125
  - switchover process, 125–126
- coding gain, 24
- cold redundancy, 125
- Command History window (CDM), 285
- commands
  - ATM interface configuration
    - commands, 176–177
  - bundle-enable, 177
  - dialer pool 1, 181
  - dialer pool-member 1, 180
  - dsl operating-mode auto, 176
  - encapsulation aal5mux ppp dialer, 180
  - encapsulation ppp, 180, 187
  - Ethernet interface configuration
    - commands, 178
  - hold-queue, 177
  - interface ATM0, 176
  - interface ATM0.1 point-to-point, 177
  - interface Dialer1, 180
  - ip address negotiated, 178, 180
  - ip nat inside, 178
  - ip nat outside, 180
  - mtu 1492, 187
  - no atm ilmi-keepalive, 176
  - no ip address, 176
  - no shut, 176
  - ppp authentication, 178–179
  - ppp chap hostname, 178
  - protocol pppoe, 187
  - pvc 1/32, 177
  - show controllers, 211–213
  - vpdn enable, 187
  - vpdn-group pppoe, 187
- commissioning chassis, 282
- Common view (CDM), 273
- competitors of DSL
  - analog modems, 6
  - cable modems, 7–8
  - ISDN, 7
  - T1/E1 services, 8
  - wireless networking, 8
- components
  - of L2TP, 88
  - of MPLS, 95
- concentrators, Cisco 6400 UAC, 240
  - ATM switching configuration, 249–250
  - Layer 3 terminations, 250–261
  - redundancy, 241–248
  - VPN configurations, 262–264
- Configuration Backup/Restore window (CDM), 283
- configuring
  - APS priority requests, 247–248
  - Cisco 6400 UAC, redundancy, 241–246
  - Cisco 827 routers
    - for data traffic, 175–179, 181–188
    - for voice traffic, 189–195, 197–198, 201
      - ATM interfaces, 194–195
      - class maps, 193
      - dial peers, 196–198
      - EIGRP, 195
      - H.323 signaling, 199
      - policy maps, 194
      - traffic precedence, 192–193
      - traffic queueing, 190–191
  - IP DSL Switches
    - DSL-to-ATM switching, 218–233
    - redundancy commands, 210–214
    - reload redundancy commands, 216–217
    - secondary unit sync commands, 214–215
    - setup commands, 203–210
    - verifying NI-2 processes, 233–239
  - PVCs, 294–296
    - VCL management, 298–303
  - SPVCs, 294–296
    - subtended connections, 329
- congestion, tail drops, 190
- connectivity
  - IRB, 68
  - L2TP, 90–91
  - Layer 3 service selection, 167
  - MPLS, 97
  - PPoE, 76, 78
  - uploading connections into CDM, 303–304
- constellations, 16
- constraint-based routing, 95
- consumer-grade ADSL, 13
- copper impedance mismatches, 39–40
- CPE (customer premise equipment)
  - ATU-R, 9
  - CO/exchange equipment
    - IP DSL switches, 114–115
      - Cisco 6015, 135–136
      - Cisco 6160, 129–131

- Cisco 6260, 131, 134–135
- line cards, 126–127
- STU-Cs, 116
- subtending, 117
- NI-2 features, 118, 122–123
- APS, 125
- redundancy, 125
- switchover process, 125–126
- IAD, 9
- PC, 10
- SOHO
  - Cisco 820 series routers, 110–111
  - Cisco SOHO 70 series routers, 108–110
- creating
  - ADSL profiles, 289–291
  - ATM QoS profiles, 287–289
  - DMT profiles, 291–293
  - PVCs on ATM interfaces, 222
- crosstalk, 12, 29
  - NEXT, 37–39
- CRWS (Cisco Router Web Setup), 108–110
- CSA (Carrier Serving Area) line sharing, 32–33
- CSA (Carrier Serving Area) remote terminals, 31–32

## D

- data rates, 6
  - of VDSL, 13
- data traffic configuration, Cisco 826 routers, 175–178
  - ATM interface commands, 176–177
  - CHAP commands, 178–179
  - Ethernet interface commands, 178
  - PPoA configuration, 179–182
  - PPoE, 186–188
  - RBE, 185
  - RFC 2684 bridging, 182–184
  - VPNs, 188
- decibels, 29
- Decommissioned device states, 274
- defining subscriber profiles, 218–221
- deploying Cisco 6000 Series IP DSL switches in
  - CDM, 275–276
    - chassis deployment, 278–281
    - line card deployment, 281
    - sites, 276–278
- Deployment Summary window (CDM), 281

- detaching subscriber profiles from ports, 221
- device states (CDM), 274
- devices
  - CO/exchange equipment
    - IP DSL switches, 114–117, 126–131, 134–136
  - CPE
    - ATU-R, 9
    - IAD, 9
    - PC, 10
  - modem cards, 10
  - PSC, 11
  - SME
    - Cisco 820 series routers, 110–111
    - Cisco SOHO 70 series routers, 108–110
  - test equipment, 50
  - UAC, 10
- dial peers, configuring on Cisco 827 routers, 196
- dialer pool 1 command, 181
- dialer pool-member 1 command, 180
- digital I/O testing, 46
- directory services, RADIUS/TACACAS+
  - conflicts, 156
- disk mirroring, 243
- displaying
  - APS state information, 211
  - VCL performance Window, 301–302
  - VCL status, 302–303
- DLC (Digital Loop Carrier) systems, 31
- DMT (discrete multitone testing), 16–17, 48–49
  - DMT2, 17–19
  - G.Lite, 20
- DMT profiles
  - applying, 293
  - creating, 291–293
- dsl operating-mode auto command, 176
- DSLAMs
  - IP/DSL switches, 10
  - modem cards, 10
- DSL-specific impairments
  - bridged taps, 35–36
  - copper impedance mismatches, 39–40
  - crosstalk, 37–39
  - load coils, 34
  - remedies for
    - automatic rate adaptation, 40
    - latency, 41–44
    - loop testing, 46–50
    - SNR margin, 45
  - “dying gasp” feature, 110
- dynamic IP addressing, 64

**E**


---

echo cancellation, 24  
 edge nodes, 96  
 EFMA (Ethernet in the First Mile Alliance), 382  
 egress LSRs, 96  
 EHSA (Enhanced High System Availability), 241  
 EIGRP (Enhanced IGRP), configuring on Cisco 827 routers, 195  
 electrical loop characterization, 46  
 element management (CDM)  
   architecture, 272  
   FCAPS standards, 271–272  
 EMI (electromagnetic interference), 30  
 EMs (element managers), polling, 273–274  
 enabling SNMP trap generation, 286  
 encapsulation, L2TP, 89  
 encapsulation aal5mux ppp dialer command, 180  
 encapsulation ppp command, 180, 187  
 Enternet, 159  
 error-correction algorithms, 42  
 Errored state (devices), 274  
 Ethernet, LRE, 381–383  
 Ethernet in the First Mile (EFM), 382  
 Ethernet interface configuration commands, 178  
 events (CDM), viewing, 305–307  
 exiting user sessions in CEMF/CDM, 275

**F**


---

fast-path circuits, 23, 41  
 fault management (CDM), 304–305  
   events, 305–307  
   status summaries, 308  
     ATM Interface Status, 308–312  
     Chassis Fault Management Window, 318  
     IMA Group Status, 312–313  
     IMA Link Status, 314  
     Module Fault Management Window, 319–320  
     SONET Interface Status, 315–318  
 FCAPS standards, CDM functionality, 271–272  
 features of CDM, 269  
 FEC (forward error correction), 23  
 fields of ATM cell header, 373–375  
 firewalls, Cisco IOS Firewall suite, 154  
 flavors of DSL, 12  
 Flexi line card, 126

FM (frequency modulation), 15  
 forwarding packets, MPLS, 93–95  
   components of, 95  
   connectivity, 97  
   LSPs, 95  
 framing modes, 24  
 frequency response measurements, 48  
 FTTB (Fiber to the Basement), 5  
 FTTC (Fiber to the Curb), 5  
 FTTH (Fiber to the Home), 5  
 FTTN (Fiber to the Neighborhood), 5  
 full-rate DMT, 20

**G**


---

G.711 standard (ITU-T), 113  
 G.723 standard (ITU-T), 113  
 G.726 ADPCM standard (ITU-T), 113  
 G.729 standard (ITU-T), 114  
 G.Lite, 20  
 generating SNMP traps, 286  
 ghost connections, 36  
 GRs (Generic Requirements), 31

**H**


---

H.323 signaling (ITU), 114  
   configuring on Cisco 827 routers, 199  
 half-rate DMT, 20  
 half-taps, 35  
 HDSL, 14  
 HDSL2, 14  
 HFC (Hybrid Fiber Coaxial), 5  
 historical performance data  
   saving, 327–328  
   viewing, 325–327  
 hold-queue command, 177  
 hospitality industry, LRE implementations, 383–384  
 hot redundancy, 125

**I**


---

IAD (Internet Access Device), 9  
 IDSL (ISDN over DSL), 15  
 ILECs (incumbent local exchange carriers), 36  
   loop management, 46–47



- IMA (Inverse Multiplexing over ATM), 136–137
    - configuring for DSL-to-ATM switching, 225–228, 230, 232–233
  - IMA Group Status window, viewing in CDM, 312–313
  - IMA Link Status window, viewing in CDM, 314
  - impairments
    - bridged taps, 35–36
    - load coils, 34
  - impairments to DSL implementation
    - copper impedance mismatches, 39–40
    - crosstalk, 37, 39
    - remedies for
      - automatic rate adaptation, 40
      - latency, 41–44
      - loop testing, 46–50
      - SNR margin, 45
  - impedance, 39
  - inductance, 30–32
  - installation of DSL, truck rolls, 10
  - interface ATM0 command, 176
  - interface ATM0.1 point-to-point command, 177
  - interface Dialer1 command, 180
  - interference
    - binder group interference, 12
    - crosstalk, 29, 37–39
  - interleaved data path, 23, 41–44
  - inventory information, viewing for Cisco 6000 Series IP DSL Switch chassis, 328
  - IOS Image Download window (CDM), 285–286
  - ip address negotiated command, 178–180
  - IP addressing, 63
    - address allocation, 66
    - dynamic, 64
    - IRB, 68–69
    - L2TP, 92
    - NAT, 65
    - PAT, 65
    - PPoE, 79
    - PPP/IPCP, 65
    - RBE, 73
    - virtual templates, 63
  - IP DSL switches, 114–115
    - CDM fault management, 304–305
      - events, 305–307
      - status summaries, 308–320
    - chassis, commissioning, 282
    - Cisco 6015, 135–136
      - IMA, 136–137
    - Cisco 6160, 129–131
      - Cisco 6260, 131, 134–135
      - line cards, 126–127
      - STU-Cs, 116
      - subtending, 117, 329
  - ip nat inside command, 178
  - ip nat outside command, 180
  - IP precedence, configuring on Cisco 827 routers, 192–193
  - IP/DSL switches, 10
  - IRB (Integrated Routing and Bridging), 67
    - connectivity, 68
    - IP addressing, 68–69
    - protocol stack, 67–68
  - ISDN versus DSL, 7
  - ITU-T (International Telecommunication Union Telecommunication Standardization Sector)
    - G.711 standard, 113
    - G.723 standard, 113
    - G.726 ADPCM standard, 113
    - G.729 standard, 114
    - H.323 standard, 114
- 
- ## L
- 
- L2TP (Layer 2 Tunneling Protocol), 86, 168
    - components, 88
    - connectivity, 90–91
    - encapsulation, 89
    - IP addressing, 92
    - VPNs, 87
  - label switching, MPLS, 93–95
    - components of, 95
    - connectivity of, 97
    - LSPs, 95
  - LAC (L2TP access concentrator), 88
  - last mile, 4
  - latency paths, 41
    - ADSL, 23
    - interleaved, 42–44
  - Layer 1 connections, 5
  - Layer 2 service selection, 165
  - Layer 3 architectures, 61
    - connection establishment, 167
    - service selection, 166
  - LCP (link control protocol), 83
  - legacy SDSL, 14
  - line cards, 126–127
    - 4DMT, 127–128
    - deploying, 281

- Flexi line card, 126
- preprovisioning, 276
- Line tab (SONET Interface Status Window), 317
- LLQ (low-latency queuing), 112
- LNS (L2TP network server), 88
- load coils, 34
- local loop, 4
  - CLEC loop management, 47
  - ILEC loop management, 46–47
  - limitations of in residential market, 4–5
  - MLT, 46
  - testing, 46–50
- log files, CEMF, 271
- login requests, RADIUS transmission flow, 158–160
  - authentication phase, 160
- LRE (Long-Reach Ethernet), 381–383
  - use in hospitality industry, 383–384
- LSPs (Label Switch Paths), 95

## M

- maintenance, truck rolls, 10
- Management Information window (CDM), 282
- measuring attenuation, 29
- Medium tab (SONET Interface Status Window), 316
- metallic noise, 37
- microcode, 24
- MLT (mechanized loop testing), 46
- modem cards, 10
- modulation schemes
  - CAP, 16
  - DMT, 16–17
    - DMT2, 17–19
    - G.Lite, 20
- Module Fault Management window, viewing in
  - CDM, 319–320
- modules
  - alarm status severity levels, 273
  - subrack discovery, 282
- MPLS (Multiprotocol Label Switching), 93–95
  - components, 95
  - connectivity, 97
  - LSPs, 95
- mtu 1492 command, 187
- multiple PVCs, configuring on Cisco 827 routers, 201–202

## N

- NAT (Network Address Translation), 65, 153
  - RFC 2684 bridging configuration, 184
- NCP (Network Control Protocol), 83
- network architectures, selecting, 9–11, 18–19, 59–96, 155–166
- Network TeleSystems (NTS), 159
- NEXT (near-end crosstalk), 37–39
- NI-2 (network interface second generation)
  - management card, 114–115, 203
  - ADSL profiles
    - applying, 293
    - creating, 289–291
  - ATM QoS profiles, creating, 287–289
  - deploying, 281
  - DMT profiles
    - applying, 293
    - creating, 291–293
  - DSL-to-ATM switching configuration
    - IMA, 225–233
    - profiles, 218–221
    - PVCs, 222
    - PVPs, 224–225
    - SPVCs, 223–224
  - features, 117–118, 122–123
    - APS, 125
    - redundancy, 125
      - switchover process, 125–126
  - NI-2 processes, verifying, 233–239
  - redundancy command, 210–214
  - redundancy states, verifying, 217
  - reload redundancy commands, 216–217
  - secondary unit sync commands, 214–215
  - setup command, 203–210
  - STU-Cs, 116
  - subtending, 117
- NLC (node line card), Cisco 6400, 144–146
- NNIs (Network-to-Network Interfaces), 363
- no atm ilmi-keepalive command, 176
- no ip address command, 176
- no shut command, 176
- noise, measuring, 48
- noise margin, 45
- Normal device state, 274
- NRP2 (Node Router Processor, second generation)
  - module, Cisco 6400, 143
- NSP (Node Switch Processor) cards, 141–142
  - redundancy, 241–242

## O

### objects

- decommissioning, 274
  - views, 272–273
- overhead framing, 24
- overloaded NAT, 154

## P

- packet filtering, ACLs, 152
- packet forwarding, MPLS, 93–95
- components, 95
  - connectivity, 97
  - LSPs, 95
- PAD (PPPoE Active Discovery Terminate)
- packets, 78
- PAP (Password Authentication Protocol), 61, 153
- parametric testing, 46
- Password Authentication Protocol (PAP), 61, 153
- PAT (Port Address Translation), 65
- RFC 2684 bridging configuration, 184
- Path tab (SONET Interface Status Window), 317
- PCMCIA disk mirroring, 243
- PCs, requirements for DSL connectivity, 10
- PE (provider edge) routers, 95
- performance management (CDM), 320
- ATM Interface Performance Data window, 321–324
- performance of VCLs, viewing, 301–302
- performance polling, 273
- adjusting, 325
- physical site surveys, performing, 9–11, 18–19, 59–96, 155–166
- PM (phase modulation), 16
- point-to-point architecture, 9–11, 18–19, 59–96, 155–166
- policy maps, configuring on Cisco 827 routers, 194
- polling functionality of CEMF EMs, 273–274
- POTS dial peers, 196
- power boost, 24
- PPoA (Point-to-Point Protocol over ATM), 82
- configuring on Cisco 827 router, 179, 181–182
  - implementations, 86
  - IP addressing, 84–85
  - LCP, 83
  - NCP, 83
  - protocol stack, 83

- PPoE (Point-to-Point Protocol over Ethernet), 74
- configuring on Cisco 827 routers, 186–188
  - connectivity, 76, 78–79
  - Ethernet, 159
  - IP addressing, 79
  - protocol stack, 76
  - WinPoET, 159
- PPP (Point-to-Point Protocol)
- L2TP, 168
  - PAP, 153
  - PTA, 165
- ppp authentication command, 178–179
- ppp chap hostname command, 178
- PPP Termination Aggregation (PTA), 165
- PPP/IPCP, 65
- preprovisioning, 274–276
- presence polling, 273
- priority requests, SONET APS, 247–248
- profiles
- attaching to ports, 221
  - defining, 218–221
  - RADIUS, 161
    - client profiles, 162
    - service profiles, 162
    - user profiles, 162–163
- uploading into CDM, 303–304
- protocol pppoe command, 187
- proxy authentication, 155
- PSC (POTS splitter chassis), 11
- PTA (PPP Termination Aggregation), 165
- pvc 1/32 command, 177
- PVCs (permanent virtual circuits), 370
- activating, 297–298
  - applying ATM QoS profiles, 297
  - configuring, 294–296
  - creating for DSL-to-ATM switching, 222
  - VCL management, 298–301
    - viewing performance, 301–302
    - viewing status, 302–303
- PVPs (permanent virtual paths), 372
- creating for DSL-to-ATM switching, 224–225

## Q

### QoS

- latency paths, 23
- on Cisco 827-4V routers, 113
- overhead framing, 24
- parameters, 22–24

queuing, configuring on Cisco 827 routers, 190–191  
quitting user sessions in CEMF/CDM, 275

## R

**RADIUS (Remote Authentication Dial-In User Service)**, 60, 155–157  
 accounting phase, 160–161  
 CHAP, directory service conflicts, 156  
 client/server model, 157  
   server requirements, 157  
 encryption method, 155  
 profiles, 161  
   client, 162  
   service, 162  
   user, 162–163  
 transmission flow, 158–160  
 versus TACACS+, 155  
**RADSL (rate-adaptive DSL)**, 6  
**RBE (Routed Bridge Encapsulation)**, 70–72  
 configuring on Cisco 827 routers, 185  
 IP addressing, 73  
 protocol stack, 72  
**RDD (Revised Resistance Design) rule**, 30  
 redundancy  
   configuring for IP DSL Switch, 210–217  
   configuring on Cisco 6400 UAC, 241  
     APS priority requests, 247–248  
     NRP-1, 243  
     NRP-2, 243–244  
     NSPs, 242  
     SONET APS, 245–246  
   NI-2, 125  
   verifying on NI-2, 217  
 Reed-Solomon Encoding, 43  
 regions, CEMF/CDM, 272  
 Reject response (RADIUS), 160  
 reload redundancy commands (IP DSL Switch), 216–217  
 Remote Authentication Dial-In User Service.  
   *See* RADIUS  
 remote terminals, IMA, 136–137  
**REN (Ringer Equivalence Number)**, 113  
 reserved VCI numbers, 375  
 residential customers, local loop, 4–5  
 residential market, FTTH, 5  
 resistance, 30

restoring Cisco 6000 series IP DSL switch  
 configurations, 284  
 return loss, 30  
**RFC 2684 bridging**, configuring on Cisco 827  
 routers, 182–183  
   with NAT, 184  
   with PAT, 183  
**RFCs (Requests For Comments)**  
   AAA-related, 154  
 RouterWare, Inc., 159  
**RSVP (Resource Reservation Protocol)**, configuring  
 with CBWFQ, 191

## S

**SAR (segmentation and reassembly)**, 63  
 saving CDM historical data, 327–328  
 scalability, 58  
**SDSL (Symmetric DSL)**  
   HDSL, 14  
   HDSL2, 14  
   IDSL, 15  
   legacy SDSL, 14  
   SHDSL, 15  
 secondary unit sync commands (IP DSL Switch),  
 214–215  
 secrets (CHAP), 153  
 Section tab (SONET Interface Status Window), 317  
 security  
   AAA, 154  
     accounting, 155  
     authentication, 154  
     authorization, 154  
     RADIUS, 157–163  
     related RFCs, 154  
   access protocols  
     CHAP, 61, 153  
     NAT, 153  
     PAP, 61, 153  
   ACLs, 152  
   firewalls, Cisco IOS Firewall suite, 154  
   proxy authentication, 155  
   RADIUS, 60  
   VPNs, access VPNs, 168  
 selecting latency paths, 23  
 service profiles (RADIUS), 162

- service providers
  - SSG, 163–164
    - Layer 2, 165
    - Layer 3, 166–167
  - truck rolls, 10
- service tests, 49
- sessions, 88
- severity levels of module alarm status, 273
- SHDSL (single-pair high-rate DSL), 15
- show controllers command, 211–213
- site surveys, performing, 9–11, 18–19, 59–96, 155–166
- sites
  - CEMF/CDM, 272
  - deploying, 276–278
- SLC (Subscriber Loop Carrier) systems, 31
- SME (small/medium enterprise) equipment
  - Cisco 820 series routers, 110
    - Cisco 826 router, 111
    - Cisco 827-4V router, 111–114
    - Cisco 827H router, 112–114
    - Cisco 828 router, 111
  - Cisco SOHO 70 series routers, 108
    - CRWS, 108
    - SOHO 71 router, 109
    - SOHO 76 router, 109
    - SOHO 77H router, 109–110
    - SOHO 78 router, 110
  - demand for bandwidth, 4
- SNMP (Simple Network Management Protocol), generating traps, 286
- SNMP Management window (CDM), 286
- SNR (signal-to-noise ratio) margin, 45
- soft-PVCs, 371–372
- SOHO 71 routers, 109
- SOHO 76 routers, 109
- SOHO 77H routers, 109–110
- SOHO 78 routers, 110
- SONET APS (Synchronous Optical Network Automatic Protection Switching)
  - priority requests, 247–248
  - support on Cisco 6400, 245–246
  - verifying, 247
- SONET Interface Status window, viewing in CDM, 315–318
- splitterless DMT, 20
- SPVCs
  - activating, 297–298
  - applying ATM QoS profiles, 297
  - configuring, 294–296
  - creating for DSL-to-ATM switching, 223–224
- SSD (Service Selection Dashboard), 165
- SSG (Service Selection Gateway), 163–164
  - Layer 2, 165
  - Layer 3, 166–167
- RADIUS, 157
  - accounting phase, 160–161
  - client profiles, 162
  - client/server model, 157
  - profiles, 161
  - service profiles, 162
  - transmission flow, 158–160
  - user profiles, 162–163
- standard telephony impairments, 29–32
  - CSA line sharing, 32–33
- starting user sessions in CEMF/CDM, 274–275
- state polling, 273–274
- statistical multiplexing, 364
- status summaries (CDM), viewing, 308
  - ATM Interface Status, 308–312
  - Chassis Fault Management window Status, 318
  - IMA Group Status, 312–313
  - IMA Link Status, 314
  - Module Fault Management window Status, 319–320
  - Sonet Interface Status, 315, 317–318
  - VCLs, 302–303
- stubs, 35
- STU-Cs (Symmetric Transceiver Units-Central office), 116
- subrack discovery, 282
- subscriber management
  - ADSL profiles
    - applying, 293
    - creating, 289–291
  - ATM QoS profiles, creating, 287–289
  - DMT profiles
    - applying, 293
    - creating, 291–293
  - CDM, 270
- subscriber profiles
  - attaching to ports, 221
  - defining, 218–221
- Subtend Manager (CDM), 329
- subtending, 117, 329
- superframes, 62
- symmetric versus asymmetric service, 12
- synchronization, troubleshooting Cisco 827 routers, 202
- System Log window (CDM), 285

---

## T

---

- T1/E1 services
  - spectral interference, 38
  - versus DSL, 8
- TACACS (Terminal Access Controller Access Control System) versus RADIUS, 61
- TACACS+ (Terminal Access Controller Access Control System Plus), 155
- tail drop, 190
- TCP/IP architectures
  - data traffic, configuring on Cisco 827 routers, 175–188
  - security protocols, 59–60
  - voice traffic, configuring on Cisco 827 routers, 189–201
- TC-PAM (Trellis Coded Pulse Amplitude Modulation), 15
- TDR (time domain reflectometry), 48
- TE (traffic engineering), 94
- Telecommunications Act of 1996, 33
- Telnet, uploading profiles into CDM, 303–304
- Terminal Access Controller Access Control System Plus (TACACS+), 155
- test equipment, 50
- testing the local loop, 46–50
- traffic precedence, configuring on Cisco 827 routers, 192–193
- training process, observing on Cisco 827 routers, 202
- transmission services, 5–6
- transmission testing, 46
- traps (SNMP), generating, 286
- Trellis Coding, 43–44
- troubleshooting Cisco 827 routers, 202
- truck rolls, 10
- tunneling protocols, 88
  - L2TP, 86
    - components, 88
    - connectivity, 90–91
    - encapsulation, 89
    - IP addressing, 92
    - VPNs, 87

## U

---

- UACs (Universal Access Concentrators), 10
  - Cisco 6400, 137–138
    - hardware, 138–141
    - NLC module, 144, 146
    - NRP2 module, 143
    - NSP, 141–142
- UBR (unspecified bit rate), 378
- uploading profiles into CDM, 303–304
- user profiles (RADIUS), 162–163

## V

---

- varieties of DSL, 12
  - ADSL, 13
    - consumer-grade, 13
    - VDSL, 13
  - SDSL
    - HDSL, 14
    - HDSL2, 14
    - IDSL, 15
    - legacy SDSL, 14
    - SHDSL, 15
- VBR (variable bit rate), 377
- VC classes, applying to interfaces, 253
- VCIs, reserved numbers, 375
- VCLs
  - configuring, 298–301
  - viewing performance of, 301–302
  - viewing status of, 302–303
- VDSL (very high data rate DSL), 13
- verifying
  - IMA status, 227–233
  - NI-2 processes, 233–239
  - NI-2 redundancy states, 217
  - NLC redundancy, 247
  - NSP redundancy, 242
  - SONET APS, 247
    - BER threshold settings, 249
  - status of Cisco 827 routers, 202
- viewing
  - CDM events, 305–307
  - CDM performance data, 320
    - ATM Interface Performance Data window, 321–325
    - historical data, 325–327

- CDM status summaries, 308
  - ATM Interface Status, 308–312
  - Chassis Fault Management window, 318–320
  - IMA Group Status, 312–313
  - IMA Link Status, 314
  - SONET Interface Status, 315–318
- VCL performance, 301–302
- VCL status, 302–303
- views (CDM), 272–273
- virtual templates, 63
- Virtual Tributary tab (SONET Interface Status Window), 318
- voice traffic configuration, Cisco 827 routers, 189
  - data network phase, 190–198
  - dial peers, 196–198
  - H.323 signaling, 199
  - multiple PVCs, 201
- VoIP dial peers, 196
- VPDN (Virtual Private Dialup Networking), 87, 168
  - activating, 187
- vpdn enable command, 187
- vpdn-group pppoe command, 187
- VPNs, 87
  - access VPNs, L2TP, 168
  - configuring
    - on Cisco 827 routers, 188
    - on Cisco 6400 routers, 262–264
- VPDNs, 168

- wire-based transmission
  - attenuation, 29
  - capacitance, 30
  - crosstalk, 29
  - CSA line sharing, 32–33
  - CSA remote terminals, 31–32
  - EMI, 30
  - inductance, 30
  - resistance, 30
- wireless networking versus DSL, 8
- WRED (weighted random early detection), 190

---

## X

- xDSL services, 5
  - ADSL, 13
    - consumer-grade, 13
    - DMT, 16–17, 19–20
    - latency paths, 23
    - VDSL, 13
  - CAP modulation, 16
  - SDSL
    - HDSL, 14
    - HDSL2, 14
    - IDSL, 15
    - legacy SDSL, 14
    - SHDSL, 15
  - summary table, 21–22
  - varieties, 12

---

## W

- WANs, ATM
  - AAL, 366–367
  - cell header, 373–375
  - cell rates, 376
  - cells, 363
  - classes of service, 364–365
  - connection types, 368–370
  - PVCs, 370
  - PVPs, 372
  - reserved VCI numbers, 375
  - soft-PVCs, 371–372
  - UBR, 378
  - VBR, 377
- web servers, SSD, 165
- WinPoET, 159