

## Symbols

---

? command, 118

## A

---

AAAA03 field (ISL encapsulation frame), 89  
 access layers (VLANs), configuring, 193–196  
 address aliasing, IGMP snooping, 241–242  
 addressing, logical addressing, Ethernet, 9–10  
 adjacency states, 163  
 addresses, MAC (Media Access Control) addresses, 9  
 advertisement requests, VTP servers, 94  
 aging, transparent bridging, 24  
 aging bits (EARL tables), 53  
 algorithms  
   backoff algorithm, 11  
   spanning-tree algorithm, 26  
 aliasing, address aliasing, IGMP snooping, 241–242  
 Alignment Errors field (show port command), 328  
 Aloha Radio System (Ethernet), 5  
 ANSI (American National Standards Institute), 6  
 Application layer (OSI), 4  
 application-specific integrated circuits (ASICs),  
   Supervisor module, 50  
 architectures  
   Catalyst 3750 switches, 74–77  
   Catalyst 5000/5500 switches, 56–57  
   Catalyst 6000/6500 switches, 64–65  
   Catalyst switches, comparing, 79  
 ASICs (application-specific integrated circuits),  
   Supervisor module, 50  
 Auto trunking mode, 92  
 autonegotiation, Ethernet, 14–20  
   configurations, 18–19  
   priority levels, 15  
 autostate, disabling, 179–180  
 auto-synch command, 313

## B

---

BackboneFast, spanning-tree convergence, 257–258  
 backoff algorithm, 11

backplane connections, Catalyst 5500 switches, 57  
 bandwidth, Catalyst 5000/5500 switches, 54  
 best practices (network design), 287  
   building blocks, 289–294  
   campus design, 295–300  
     single points of failure, 302–303  
     traffic flows, 300–301  
   Layer 3 design model, 287–289  
   management VLAN, 110–111  
 blocking, spanning tree blocking, 26  
 boot bootflash command, 327  
 boundary ports, 268  
 BPDU field (ISL encapsulation frame), 89  
 BPDU Filter (portfast), 252  
 BPDU Guard (portfast), 203, 251  
 BPDU messages  
   blocking, 251  
   filtering, 252  
 BPDUs, RSTP (Rapid Spanning Tree Protocol),  
   262–263  
 bridging loops, 25  
 broadcasts, Ethernet, 24  
 buffering, 41  
   port-buffered memory, 41–42  
   shared memory, 42–43  
 building blocks, network design best practices,  
   289–294  
 burned-in addresses, 9  
 bus topologies  
   Ethernet, 9  
   weaknesses, 9  
 buses, Catalyst 5000/5500 switches, 56

## C

---

cabling, faults, detecting, 12  
 calculating MAC addresses for multicast groups,  
   228  
 classic line cards, Catalyst 6000/6500 switches, 62  
 CAM (Content-Addressable Memory), Supervisor  
   module, 50, 53, 226  
 campus design, best practices, 295–300  
   single points of failure, 302–303  
   traffic flows, 300–301

- campus switch design
  - BPDU guard, 203
  - configuring, 171-172
    - channeling, 199-201
    - dynamic routing, 196-198
    - initial configuration, 172-183
    - management interfaces, 167-171
    - planning, 167
    - trunking, 199-201
  - connections, 183-193
  - portfast, 203
- carrier sense multiple access collision detect (CSMA/CD) protocol, Ethernet, 5
- Catalyst Supervisors, 304-307
  - Catalyst 6500 High Availability (hybrid), 304-307
  - Catalyst 6500 High Availability (native), 311-312
  - disappearance of, 324-325
  - LEDs (light emitting diodes), 324
  - MFSC high availability, 307-311
- Catalyst 3750 switches, 74-75
  - data flow, 78-79
  - GBICs (Gigabit Interface Connectors), 75
  - power and cooling, 75
  - Small Form Factor Pluggable (SFP) uplink ports, 75
  - software, downloading, 139
  - stackwise architectures, 76-77
  - switch fabric redundancy, 313-314
- Catalyst 4500 switches, 68
  - chassis, 68-69
  - data flow, 73-74
  - line modules, 71
  - power and cooling, 71-72
  - software, downloading, 139
  - Supervisor modules, 69-71
  - switch fabric redundancy, 313
  - switch fabrics, 69-71
- Catalyst 5000 EARL switches, Supervisor module, 52-53
- Catalyst 5000 switches, 47
- Catalyst 5000/5500 EARL switches, Supervisor module, 54
- Catalyst 5000/5500 switches, 48
  - architectures, 56-57
  - backplane connections, 57
  - bandwidth, 54
  - buses, 56
  - chassis, 48-49
  - data flow, 57-59
  - line modules, 55
  - power and cooling, 49
  - Supervisor module, 49-52
- Catalyst 6000/6500 switches, 59
  - architectures, 64-65
  - chassis, 60
  - data flow, 66-68
  - line modules, 62-63
  - power and cooling, 63
  - shared bus architecture, 64
  - Supervisor modules, 60-62
  - software, downloading, 134-139
  - switch fabrics, 60-62
  - switching modes, 66
- Catalyst 6500 switches
  - CoS (class of service), 208
  - MLS (multilayer switching), 157-160
  - QoS (quality of service), 207
    - classification, 209-212
    - DiffServ (Differentiated Services), 207-208
    - Etherchannel ports, 222
    - Flexwan module, 222
    - IGMP snooping, 222
    - input scheduling, 212-214
    - IntServ (Integrated Services), 207-208
    - marking, 214-219
    - MSFC, 222
    - output scheduling, 219-222
    - policing, 214-218
  - Supervisors
    - High Availability (hybrid), 304-307
    - High Availability (native), 311-312
  - switch fabric redundancy, 312
  - ToS (type of service), 208
- Catalyst OS (operating system), 117
  - Cisco IOS command comparisons, 130
  - configurations, choosing, 132-133
  - Ethernet connections, 127
  - hybrid software, 117-126
  - IOS connections, 127
  - native software, 126-131
  - software, downloading, 134-144

- Catalyst switches, 47
  - see also* specific Catalyst switches
  - architectures, comparing, 79
  - hybrids, 117
  - natives, 117
  - switching fabric, 37
- CEF (Cisco Express Forwarding), 161
  - MLS (multilayer switching), 161–165
- CGMP (Cisco Group Management Protocol), 225, 243–246
  - IGMP, compared, 247
  - IGMP leave process, 246
  - local leave process, 246–247
- channeling switches, 108, 199–201
- chassis
  - Catalyst 4500 switches, 68–69
  - Catalyst 5000/5500 switches, 48–49
  - Catalyst 6000/6500 switches, 60
- Cisco Express Forwarding (CEF), 161
- Cisco Group Management Protocol (CGMP). *See* CGMP (Cisco Group Management Protocol)
- Cisco online resources, LAN switching
  - configuration, 334
- Cisco Product Security Advisories and Notices (PSIRT), 334
- classification, QoS (quality of service), Catalyst 6500, 209–212
- clear command, 117, 175
- clear config all command, 175
- clear trunk command, 101
- clear vtp pruneeligible command, 99
- clusters, 74
- collision back-off ranges, 12
- collision domains, 10
  - transparent bridging, 20–22
    - aging, 24
    - filtering, 23
    - flooding, 23
    - forwarding, 24
- combined power mode, Catalyst 4500 switches, 72
- commands
  - ? command, 118
  - auto-synch command, 313
  - boot bootflash command, 327
  - clear command, 117, 175
  - clear config all command, 175
  - clear trunk command, 101
  - clear vtp pruneeligible command, 99
  - copy running-config startup-config command, 308
  - dir bootflash command, 324
  - enable command, 121
  - enable password command, 121
  - enable secret command, 121
  - erase const\_nvram command, 175
  - exit command, 124
  - help command, 118
  - interface command, 125
  - interface range command, 195
  - interface VLAN 10 command, 125
  - line con 0 command, 121
  - maximum-paths command, 300
  - mls rp ip command, 154
  - mls rp vtp-domain command, 154
  - mls-rp management command, 154
  - no mls ip command, 157
  - no switchport command, 129, 190
  - passive-interface command, 296–297
  - password command, 121
  - ping command, 185, 190
  - rlog command, 159
  - session ? command, 118
  - session 15 command, 125
  - session command, 124
  - set command, 117
  - set enablepass command, 121
  - set mls agingtime fast command, 157
  - set mls enable command, 154
  - set password command, 121
  - set qos map command, 220
  - set spantree portfast command, 260
  - set system name command, 122
  - set vlan command, 124
  - show command, 117
  - show agport command, 106
  - show channel hash command, 106
  - show channel traffic command, 106
  - show config command, 123
  - show controller command, 123
  - show environment all command, 321
  - show environment command, 123
  - show IGMP groupinfo command, 231
  - show interface FastEthernet10/23 command, 189

- show interface gigabitethernet 1/1 command, 128
- show interface GigabitEthernet1/1 command, 185
- show interface gigabitethernet1/2 command, 190
- show interface loopback0 command, 176
- show interface vlan140 command, 196
- show interface VLAN901 command, 187
- show interfaces trunk command, 200
- show ip protocols command, 297
- show log command, 181
- show mac command, 228
- show mls command, 153
- show mls cef command, 164
- show mls rp command, 159
- show mls status command, 159
- show module command, 304, 318–319, 327
- show mroute command, 225
- show multicast statistics command, 237
- show port command, 13
- show port 1/1 command, 121
- show port capabilities command, 16, 103
- show port channel, 104
- show port command, 119, 127, 328
- show process cpu command, 322
- show running-config command, 123
- show scp command, 322
- show snmp command, 205
- show system command, 323
- show tech-support command, 124
- show test command, 325
- show top command, 323
- show udd command, 202
- show version command, 118–119, 318
- show vlan command, 195
- show vtp statistics command, 100
- spantree command, 250, 259
- spantree mode command, 266
- switch console command, 326
- switchport access command, 129
- switchport command, 129
- switchport mode access command, 129
- trace command, 329
- write memory command, 308

- Common Spanning Tree (CST), 268
  - configuration
    - Catalyst OS, choosing, 132–133
    - EIGRP, 196–198
    - Ethernet, autonegotiation, 18-19
    - IOS, choosing, 132–133
    - LAN switching, troubleshooting, 317–318
    - LOO (Loopback 0), 175–178
    - MLS (multilayer switching), 153–156
    - RSTP (Rapid Spanning Tree Protocol), 266
    - sc0 management interface, 175–178
    - SNMP (Simple Network Management Protocol), 204–205
    - switches, 171–172
      - connections, 183–193
      - dynamic routing, 196–198
      - initial configuration, 172–183
      - management interfaces, 167–171
      - planning, 167
    - UDLD (UniDirectional Link Detection), 201–202
    - VLANs, access layers, 193–196
    - VTP (VLAN Trunking Protocol) servers, 97–98, 130, 173–175
  - configuration synchronization, MSFC
    - high-availability, 308–309
  - congestion, head-of-line blocking, 44–45
  - connections, switches, configuring, 183–193
  - Constellation, 59
  - Content-Addressable Memory (CAM), 50, 53, 226
  - convergence
    - RSTP (Rapid Spanning Tree Protocol)
      - direct failures, 265
      - indirect failures, 266
    - spanning-tree convergence, 255
      - BackboneFast, 257–258
      - timers, 255–257
      - UplinkFast, 259–260
  - cooling
    - Catalyst 3750 switches, 75
    - Catalyst 4500 switches, 71–72
    - Catalyst 5000/5500 switches, 49
    - Catalyst 6000/6500 switches, 63
  - copy running-config startup-config command, 308
  - CoS (class of service), Catalyst 6500, 208

Crescendo Communications, Cisco acquisition of, 117

crossbar switch fabrics, Catalyst 6000/6500 switches, 64

crossbar switching, 40–41

cross-over cabling, Ethernet, 8–9

CSMA/CD (carrier sense multiple access collision detect) protocol

- collision back-off ranges, 12
- Ethernet, 5
- operations, 10–13

CST (Common Spanning Tree), 268

cut-through switching mode, 35

## D

DA field (ISL encapsulation frame), 89

data receiving, switching modes, 35–36

data bus (dBUS)

- Catalyst 5000/5500 switches, 56
- Catalyst 6000/6500 switches, 64

data circuit equipment (DCE), 8

data flow

- Catalyst 3750 switches, 78–79
- Catalyst 4500 switches, 73–74
- Catalyst 5000/5500 switches, 57–59
- Catalyst 6000/6500 switches, 66–68

Data Link layer (OSI), 5

data terminating equipment (DTE), 8

DCE (data circuit equipment), 8

Desirable trunking mode, 91

devices, MAC addresses, learning, 21

DFCs (Distributed Forward Cards), 63

Differentiated Services (DiffServ), QoS (quality of service), 207–208

Differentiated Services Code Point (DSCP), 209

dir bootflash command, 324

direct failures, RSTP (Rapid Spanning Tree Protocol), 265

disabling autostate, 179–180

Distributed Forward Cards (DFCs), 63

domains, 10

- collision domains, 10
- VTP domains, 92

downloading Catalyst software, 134–144

DRAM (dynamic random-access memory), Supervisor module, 50

DRM (Dual Router Mode), MSFC high-availability, 307–308

DSCP (Differentiated Services Code Point), 209

DTE (data terminating equipment (DTE), 8

dynamic random-access memory (DRAM), Supervisor module, 50

dynamic routing, switches, 196–198

## E

EARL (Enhanced Address Recognition Logic), 50

- Catalyst 5000 EARL, 52–53
- Catalyst 5000/5500 EARL, 54

EIA (Engineering Industry Association), 6

EIGRP, configuring, 196–198

enable command, 121

enable password command, 121

enable secret command, 121

Encap Frame field (ISL encapsulation frame), 89

encapsulation frame, ISL (Inter-Switch Link) protocol fields, 89

Engineering Industry Association (EIA), 6

Enhanced Address Recognition Logic (EARL). *See* EARL (Enhanced Address Recognition Logic)

erase const\_nvram command, 175

EtherChannel, 102–108

- frame distribution, 102
- logical ports, 103
- management, 103
- ports, QoS (quality of service), 222

Ethernet, 5

- autonegotiation, 14–20
  - configurations, 18–19
- autonegotiations, priority levels, 15
- broadcasts, 24
- connections, 127
- cross-over cabling, 8–9
- CSMA/CD (carrier sense multiple access collision detect) protocol, 5
  - operations, 10–13
- full-duplex Ethernet, 13–14
- logical addressing, 9–10
- multicasts, 24

- shared Ethernet, 11–12
- STP (Spanning Tree Protocol), 24–26
  - blocking, 26
  - operations, 27–29
  - timers, 30
  - topology changes, 30–31
  - transitions, 30
- telephone party lines, compared, 11
- topology, 9
- transmission media, 6
  - Ethernet over coax cabling, 8
  - Ethernet over fiber optics, 7
  - Ethernet over twisted-pair cabling, 6–7
- transparent bridging, 20–22
  - aging, 24
  - filtering, 23
  - flooding, 23
  - forwarding, 24
- types, 5
- Ethernet Out of Band Channel (EOBC)
  - Catalyst 6000/6500 switches, 64
- Ethernet over coax cabling, 8
- Ethernet over fiber optics, 7
- Ethernet over twisted pair cabling, 6–7
- Excessive Collisions field (show port command), 328
- exit command, 124
- external routers, MLS (multilayer switching), 152

## F

---

- fabric-enabled line cards, Catalyst 6000/6500 switches, 62
- fabric-only line cards, Catalyst 6000/6500 switches, 62
- fallback (IGMP), 242–243
- fastleave, IGMP snooping, 240
- faults, cabling, detecting, 12
- FCS Errors field (show port command), 328
- fields, ISL encapsulation frame, 89
- filtering transparent bridging, 23
- flash memory, Supervisor module, 50
- flashing orange LED (Supervisor), 325
- Flexwan module, QoS (quality of service), Catalyst 6500, 222

- flooding
  - multicast flooding, 226–228
    - IGMP snooping, 228–229
  - transparent bridging, 23
- flow through switching mode, Catalyst 6000/6500 switches, 66
- Forward Delay timer (spanning tree), 255
- forwarding
  - data, 45
  - transparent bridging, 24
- fragment-free switching mode, 36
- frames
  - buffering, 41
    - port-buffered memory, 41–42
    - shared memory, 42–43
  - EtherChannel distribution, 102
  - round-robin servicing, 37–38
- full-duplex Ethernet, 13–14
- functionally transparent line module, Catalyst 4500 switches, 71

## G-H

---

- GBICs (Gigabit Interface Connectors)
  - Catalyst 3750 switches, 75
- Giants field (show port command), 328
- green LED (Supervisor), 324–325
- group-specific query messages (IGMP), 226
- hardware addresses. *See* MAC (Media Access Control) addresses
- hardware version checks, LAN switching configuration, 319–327
- head-of-line blocking, 44–45
- Hello timer (spanning tree), 255
- help command, 118
- HSA field (ISL encapsulation frame), 89
- hybrid configurations
  - Catalyst OS, choosing, 132–133
  - IOS, choosing, 132–133
- hybrids
  - Catalyst OS, 117–126
  - natives, compared, 117

**I**

---

- IEEE 802.1Q
  - Layer 2 networks, 90–91
  - tag field, 90
- IGMP (Internet Group Management Protocol), 225
  - CGMP (Cisco Group Management Protocol), compared, 247
  - leave process, 246
  - packets, 226
  - snooping, 228–229
    - address aliasing, 241–242
    - fallback, 242–243
    - fastleave, 240
    - leave process, 238–240
    - membership reports, 229–238
    - QoS (quality of service), 222
  - versions, compared, 225–226
- Index field (ISL encapsulation frame), 89
- indirect failures, RSTP (Rapid Spanning Tree Protocol), 266
- initial configuration, switches, 172–183
- in-line rewrites (Catalyst 5500 switches), 53
- input scheduling, QoS (quality of service), Catalyst 6500, 212–214
- Integrated Services (IntServ), QoS (quality of services), 207–208
- interface command, 125
- interface range command, 195
- interface VLAN 10 command, 125
- interfaces, 127
  - IOS, 183
    - management interfaces, campus switching designs, 167–171
- Internet Group Management Protocol (IGMP). *See* IGMP (Internet Group Management Protocol)
- Inter-Switch Link (ISL) protocol, 89
- IOS
  - Catalyst OS command comparisons, 130
  - configurations, choosing, 132–133
  - connections, 127
  - interfaces, 183
  - new software packaging, 142–144
  - ports, 183
- ISL (Inter-Switch Link) protocol
  - encapsulation frame, fields, 89
  - Layer 2 networks, 89–90

- ISL CRC field (ISL encapsulation frame), 89
- IST (Internal Spanning Tree)
  - MST (Multiple Spanning Tree), 268–270

## J-L

---

- join messages, VTP servers, 95

- LANs (local-area networks), switching configuration

- Cisco online resources, 334
- hardware version checks, 319–327
- Local SPAN, 330–331
- port errors, 327–328
- RSPAN, 331–333
- software version checks, 318–319
- SPAN (Switched Port Analyzer), 330–331
- syslog messages, 328–329
- trace command, 329
- troubleshooting, 317–318

- Late Collisions field (show port command), 328

- Layer 2 networks, 83

- EtherChannel, 102–108
- legacy LANs, 83–84
- replacing, 83
- trunking methods, 87–89
  - IEEE 802.1Q, 90–91
  - ISL (Inter-Switch Link) protocol, 89–90
  - trunking modes, 91–92
  - VTP (VLAN Trunking Protocol), 92–98
- VLANs, 84–87
  - private VLANs, 111–115
  - pruning methods, 98–101
  - valid ranges, 86
  - VLAN 1, 109–111

- Layer 3 networks, design model, 287–289

- layers (OSI), 4

- lower layers, 4
  - Data Link layer, 5
  - Network layer, 4
  - Physical layer, 5
  - Transport layer, 4
- upper layers, 4
  - Application layer, 4
  - Presentation layer, 4
  - Session layer, 4

- learning MAC addresses, 21
- leave group messages (IGMP), 226
- leave process, IGMP snooping, 238–240
- LEDs (light emitting diodes), Supervisors, 324
- legacy LANs, Layer 2, 83–84
- legacy support, RSTP (Rapid Spanning Tree Protocol), 264–265
- Len field (ISL encapsulation frame), 89
- line con 0 command, 121
- line modules
  - Catalyst 4500 switches, 71
  - Catalyst 5000/5500 switches, 55
  - Catalyst 6000/6500 switches, 62–63
- LO0 (Loopback 0), configuring, 175–176, 178
- local leave process, CGMP (Cisco Group Management Protocol), 246–247
- local SPAN, 330–331
- logical addressing, Ethernet, 9–10
- logical ports, EtherChannel, 103
- loops
  - bridging, 25
  - preventing
    - Loop Guard, 254–255
    - portfast, 249–252
    - Root Guard, 252–253
    - STP (Spanning Tree Protocol), 249–255
- Lord of the Rings project, 74

## M

- MAC (Media Access Control) addresses, 9
  - calculating, multicast groups, 228
  - learning, 21
- management bus (mBUS), Catalyst 5000/5500 switches, 56
- management interfaces
  - campus switching designs, 167–171
    - scO, 168, 170–171
  - sc0 management interface, configuring, 175–176, 178
- Management VLAN, 109
  - best practices, 110–111
- marking QoS (quality of service), Catalyst 6500, 214–219
- Master Communications Processor (MCP), Supervisor module, 49
- Maxage optimizers, BackboneFast, 257–258
- Maxage timer (spanning tree), 255–256
- Maximum Response Time field (IGMP), 226
- maximum-paths command, 300
- MCP (Master Communications Processor), Supervisor module, 49
- membership reports, IGMP snooping, 229–238
- memory
  - port-buffered memory, 41–42
  - shared memory, 42–43
- MFSC (Multilayer Switch Feature Card), 117
- MLS (multilayer switching), 147–249
  - adjacency states, 163
  - advantages, 147–148
  - Catalyst 6500, 157–160
  - CEF (Cisco Express Forwarding), 161–165
  - configuring, 153–156
  - external routers, 152
  - packet flow, 150–153
  - router access lists, 156
  - routers, programming on, 149
- mls rp ip command, 154
- mls rp vtp-domain command, 154
- MLSP (Multilayer Switching Protocol), 149
- MLS-RP (Multilayer Switching Route Processor), 149
- mls-rp management command, 154
- MLS-SE (Multilayer Switching Engine), 149
- MMF (multimode fiber) optics, 7
- mode best practices, VTP (VLAN Trunking Protocol), 96–97
- MSFC high availability (Catalyst), 307–311
  - configuration synchronization, 308–309
  - disappearance of, troubleshooting, 326–327
  - DRM (Dual Router Mode), 307–308
  - QoS (quality of service), Catalyst 6500, 222
  - SRM (Single Router Mode), 309–311
- MST (Multiple Spanning Tree), 249, 267
  - CST (Common Spanning Tree), compared, 267
  - IST (Internal Spanning Tree), 268–270
  - PVST+ (per VLAN spanning tree plus)
    - compared, 267
    - connecting to, 279–280
    - regions, 268, 270–279
- multicast flooding, 226–228
  - preventing, IGMP snooping, 228–229
- multicast groups, MAC addresses, calculating, 228



multicast traffic, forwarding, CGMP (Cisco Group Management Protocol), 243–247

multicasts, Ethernet, 24

Multilayer Switch Feature Card (MSFC), 117

multilayer switching (MLS). *See* MLS (multilayer switching)

Multilayer Switching Engine (MLS-SE), 149

Multilayer Switching Protocol (MLSP), 149

Multilayer Switching Route Processor (MLS-RP), 149

Multiple Collisions field (show port command), 328

Multiple Spanning Tree (MST). *See* MST (Multiple Spanning Tree)

## N

native configurations

- Catalyst OS, choosing, 132–133
- IOS, choosing, 132–133

native software, Catalyst OS, 126–131

Negotiate trunking mode, 92

network design, best practices, 287

- building blocks, 289–294
- campus design, 295–303
- Layer 3 design model, 287–289

network devices

- DCE (data circuit equipment), 8
- domains, 10
- DTE (data terminating equipment), 8

Network layer (OSI), 4

NMP (Network Management Processor), 49, 109

no mls ip command, 157

no switchport command, 129, 190

non-blocking switches command, 43

nonvolatile random-access memory (NVRAM), Supervisor module, 49

numbering schemes, VLANs, 171, 296

NVRAM (nonvolatile random-access memory), Supervisor module, 49

## O

Off trunking mode, 91

On trunking mode, 91

orange LED (Supervisor), 324–325

OSI (Open System Interconnection) reference model, 3–4

- lower layers, 4
  - Data Link layer, 5
  - Network layer, 4
  - Physical layer, 5
  - Transport layer, 4
- upper layers, 4
  - Application layer, 4
  - Presentation layer, 4
  - Session layer, 4

output scheduling, QoS (quality of service). Catalyst 6500, 219–222

oversubscribing, switching fabric, 43

## P

packet flow, MLS (multilayer switching), 150–153

packets, IGMP packets, 226

passive-interface command, 296–297

password command, 121

per VLAN spanning tree plus (PVST+). *See* PVST+ (per VLAN spanning tree plus)

Physical layer (OSI), 5

physical star topologies, 9

ping command, 185, 190

pinouts, crossover pinouts, 8

planning

- campus switching designs, configuration, 167
- VLAN numbering, 171

Point-to-Point Protocol (PPP), 168

policing QoS (quality of service), Catalyst 6500, 214–218

port errors, troubleshooting, 327–328

port states, UDLD (Unidirectional Link Detection), 283

portfast, 203

- BPDU Filter, 252
- BPDU Guard, 251
- loops, preventing, 249–252
- Root Guard, 252–253

ports, 127

- boundary ports, 268
- IOS, 183

power

- Catalyst 3750 switches, 75
- Catalyst 4500 switches, 71–72

- Catalyst 5000/5500 switches, 49
- Catalyst 6000/6500 switches, 63
- PPP (Point-to-Point Protocol), 168
- Presentation layer (OSI), 4
- priority levels, autonegotiations, Ethernet, 15
- private VLANs, 111–115
- Product Security Advisories and Notices (PSIRT), 334
- project Constellation, 59
- project Lord of the Rings, 74
- project Synergy, 47
- proposal/agreement process, RSTP (Rapid Spanning Tree Protocol), 263–264
- pruning methods, VLANs, 98–101
- PSIRT (Product Security Advisories and Notices), 334
- PVST+ (per VLAN spanning tree plus), MST (Multiple Spanning Tree)
  - compared, 267
  - connecting to, 279–280

## Q

---

- QoS (quality of service), Catalyst 6500, 207–209
  - classification, 209–212
  - DiffServ (Differentiated Services), 207–208
  - Etherchannel ports, 222
  - Flexwan module, 222
  - IGMP snooping, 222
  - input scheduling, 212–214
  - IntServ (Integrated Services), 207–208
  - marking, 214–219
  - MSFC, 222
  - output scheduling, 219–222
  - policing, 214–218
- query election process (IGMP), 226

## R

---

- Rapid Spanning Tree Protocol (RSTP). *See* RSTP (Rapid Spanning Tree Protocol)
- RCV Errors field (show port command), 328
- red LED (Supervisor), 324–325

- redundant power mode
  - Catalyst 4500 switches, 72
- regions, MST (Multiple Spanning Tree), 268–279
- Res field (ISL encapsulation frame), 89
- Resource Reservation Protocol (RSVP), 207
- Results/Index Bus (rBUS), Catalyst 6000/6500 switches, 64
- results/index bus (rBUS), Catalyst 5000/5500 switches, 56
- rlog command, 159
- RLQ (Root Link Query) protocol, 258
- Root Link Query (RLQ) protocol, 258
- round-robin servicing, 37–38
- router access lists, MLS (multilayer switching), 156
- Router Switch Module (RSM), 117
- routers
  - MLS (multilayer switching), programming on, 149
  - new software packaging, 142
- RPR (Route Processor Redundancy), Catalyst 6500 Supervisor High Availability, 311
- RPR+ (Route Processor Redundancy plus), Catalyst 6500 Supervisor High Availability, 312
- RSFC, 124
- RSM (Router Switch Module), 117, 124
- RSPAN (Remote SPAN), 331–333
- RSTP (Rapid Spanning Tree Protocol), 249, 260–262
  - BPDUs, 262–263
  - configuring, 266
  - direct failures, 265
  - indirect failures, 266
  - legacy support, 264–265
  - proposal/agreement process, 263–264
  - states, 262
  - STP, advantages over, 255
- RSVP (Resource Reservation Protocol), 207
- Runts field (show port command), 328

## S

---

- SA field (ISL encapsulation frame), 89
- SAINT (Synergy Advanced Interface Network Termination), 50
- SAMBA (Synergy Advanced Multipurpose Bus Arbiter), 50

- sc0 management interface
  - configuring, 175–178
  - VLAN 1, 168–171
- Serial Line Internet Protocol (SLIP), 168
- session ? command, 118
- session 15 command, 125
- session command, 124
- Session layer (OSI), 4
- set command, 117, 154
- set enablepass command, 121
- set mls agingtime fast command, 157
- set mls enable command, 154
- set password command, 121
- set qos map command, 220
- set spantree portfast command, 260
- set system name command, 122
- set vlan command, 124
- severity levels, syslog, 180
- SFM (switch fabric module), Catalyst 6000/6500 switches, 61
- SFM II, Catalyst 6000/6500 switches, 61
- shared bus architecture, Catalyst 6000/6500 switches, 64
- shared Ethernet, 11–12
  - STP (Spanning Tree Protocol), 24–26
    - blocking, 26
    - operations, 27, 29
    - timers, 30
    - topology changes, 30–31
    - transitions, 30
- shared-bus switching, 37–39
- show agport command, 106
- show channel hash command, 106
- show channel traffic command, 106
- show commands, 117
- show config command, 123
- show controller command, 123
- show environment all command, 321
- show environment command, 123
- show IGMP groupinfo command, 231
- show interface FastEthernet10/23 command, 189
- show interface gigabitethernet 1/1 command, 128
- show interface GigabitEthernet1/1 command, 185
- show interface gigabitethernet1/2 command, 190
- show interface loopback0 command, 176
- show interface vlan140 command, 196
- show interface VLAN901 command, 187
- show interfaces trunk command, 200
- show ip protocols command, 297
- show log command, 181
- show mac command, 228
- show mls cef command, 164
- show mls command, 153
- show mls rp command, 159
- show mls status command, 159
- show module command, 304, 318–319, 327
- show mroute command, 225
- show multicast statistics command, 237
- show port 1/1 command, 121
- show port capabilities command, 16, 103
- show port channel command, 104
- show port command, 13, 119, 127, 328
- show process cpu command, 322
- show running-config command, 123
- show scp command, 322
- show snmp command, 205
- show system command, 323
- show tech-support command, 124
- show test command, 325
- show top command, 323
- show uddl command, 202
- show version command, 118–119, 318
- show vlan command, 195
- show vtp statistics command, 100
- Simple Network Management Protocol (SNMP),
  - configuring, 204–205
- Single Collisions field (show port command), 328
- single points of failure, campus design, best practices, 302–303
- single router mode, Catalyst 6500 Supervisor High Availability, 312
- SLIP (Serial Line Internet Protocol), 168
- Small Form Factor Pluggable (SFP) uplink ports, Catalyst 3750 switches, 75
- SMF (single mode fiber) optics, 7
- SNMP (Simple Network Management Protocol),
  - configuring, 204–205
  - snooping, IGMP snooping, 228–229
    - address aliasing, 241–242
    - fallback, 242–243
    - fastleave, 240
    - leave process, 238–240
    - membership reports, 229–238
- software, 132
  - Catalyst OS, downloading, 134–144
  - IOS, new packaging, 142–144

- Software Release notes, Catalyst software, upgrading, 134
- software version checks, LAN switching configuration, 318–319
- SPAN (Switched Port Analyzer), 330–331
  - Local SPAN, 330–331
  - RSPAN, 331–333
- spanning tree
  - MST (Multiple Spanning Tree), 249, 267
    - CST (Common Spanning Tree), compared, 267
    - IST (Internal Spanning Tree), 268–270
    - PVST+ (per VLAN spanning tree plus), 267, 279–280
    - regions, 268–279
  - RSTP (Rapid Spanning Tree Protocol), 249, 260–262
    - BPDU, 262–263
    - configuring, 266
    - direct failures, 265
    - indirect failures, 266
    - legacy support, 264–265
    - proposal/agreement process, 263–264
    - states, 262
    - STP, advantages over, 255
  - STP (Spanning Tree Protocol), 24, 249
    - BPDU messages, blocking, 251
    - drawbacks of, 249
    - Ethernet, 24–26
    - Loop Guard, 254–255
    - loop prevention, 249–255
    - portfast, 249–252
    - Root Guard, 252–253
    - RSTP (Rapid Spanning Tree Protocol)
      - legacy support, 264–265
  - UDLD (Unidirectional Link Detection)
    - protocol, 281–282
    - port states, 283
- Spanning Tree Protocol (STP). See STP (Spanning Tree Protocol), 24, 249
- spanning-tree convergence, 255
  - BackboneFast, 257–258
  - timers, 255–257
  - UplinkFast, 259–260
- spantree command, 250, 259
- spantree mode command, 266
- SRM (Single Router Mode)
  - MSFC high-availability, 309–311
- stackwise architectures
  - 3750 switches, 76–77
- states
  - RSTP (Rapid Spanning Tree Protocol), 262
- static bits (EARL tables), 53
- store-and-forward switching mode, 36
- STP (Spanning Tree Protocol), 24, 249
  - BPDU messages, blocking, 251
  - drawbacks of, 249
  - Ethernet, 24–26
    - blocking, 26
    - operations, 27–29
    - timers, 30
    - topology changes, 30–31
    - transitions, 30
  - Loop Guard, 254–255
  - loops, preventing, 249–255
  - portfast, 249–252
  - Root Guard, 252–253
  - RSTP (Rapid Spanning Tree Protocol), legacy support, 264–265
- subset advertisements, VTP servers, 94
- summary advertisements, VTP servers, 93–94
- Supervisor 720 module, Catalyst 6000/6500 switches, 61
- Supervisor I module (Catalyst switches), 50
- Supervisor IA module (Catalyst 6000/6500 switches), 61
- Supervisor II module (Catalyst switches), 51, 69
- Supervisor II+ module (Catalyst 4500 switches), 70
- Supervisor IIG module (Catalyst switches), 51
- Supervisor III module (Catalyst switches), 51, 70
- Supervisor IIIG module (Catalyst switches), 51
- Supervisor IV module (Catalyst 4500 switches), 70
- Supervisor modules
  - Catalyst 4500 switches, 69–71
  - Catalyst 5000/5500 switches, 49–52
  - Catalyst 5000 EARL switches, 52–53
  - Catalyst 5000/5500 EARL switches, 54
  - Catalyst 6000/6500 switches, 60–62
  - Catalyst 6500 High Availability (hybrid), 304–307, 311
    - RPR, 311
    - RPR+, 312
  - single router mode, 312

- disappearance of, troubleshooting, 324–325
- LEDs (light emitting diodes), 324
- MSFC high availability, 307–311
  - configuration synchronization, 308–309
  - DRM (Dual Router Mode), 307–308
  - SRM (Single Router Mode), 309–311
- Supervisor V module (Catalyst 4500 switches), 70
- switch console command, 326
- switch fabric redundancy
  - Catalyst 3750, 313–314
  - Catalyst 4500, 313
  - Catalyst 6500, 312
- switch fabrics
  - Catalyst 4500 switches, 69–71
  - Catalyst 6000/6500 switches, 60–62
- switches
  - autostate, disabling, 179–180
  - Catalyst switches, 47
    - architectures, 79
    - Catalyst 3750 switches, 74–75, 78–79
    - Catalyst 4500 switches, 68–74
    - Catalyst 5000 EARL switches, 52–53
    - Catalyst 5000 switches, 47
    - Catalyst 5000/5500 EARL switches, 54
    - Catalyst 5000/5500 switches, 48–52, 54–59
    - Catalyst 6000/6500 switches, 59–68
  - channeling modes, 108
  - configuring, 171–172
    - channeling, 199–201
    - dynamic routing, 196–198
    - initial configuration, 172–183
    - management interfaces, 167–171
    - planning, 167
    - trunking, 199–201
    - VLAN access layers, 193–196
  - connecting, 183–193
  - connections, configuring, 183–193
  - new software packaging, 144
- switching configuration (LANs)
  - Cisco online resources, 334
  - hardware version checks, 319–327
  - Local SPAN, 330–331
  - port errors, 327–328
  - RSPAN, 331–333
  - software version checks, 318–319
  - SPAN (Switched Port Analyzer), 330–331

- syslog messages, 328–329
- trace command, 329
- troubleshooting, 317–318
- switching fabrics, 37
  - Catalyst 3750 switches, 76–77
  - non-blocking, 43
  - oversubscribing, 43
- switching modes, 35
  - Catalyst 6000/6500 switches, 66
  - cut-through mode, 35
  - fragment-free mode, 36
  - store-and-forward mode, 36
- switchport access command, 129
- switchport command, 129
- switchport mode access command, 129
- Synergy, 47
- Synergy Advanced Interface Network Termination (SAINT), 50
- Synergy Advanced Multipurpose Bus Arbiter (SAMBA), 50
- syslog severity levels, 180
- syslog messages, 328–329
- system logging, 180–183

## T

- tag field (IEEE 802.1Q), 90
- TCAM (ternary CAM), 53
- TDRs (Time Delay Reflectometers), cable faults, detecting, 12
- Telecommunications Industry Association (TIA), 6
- telephone party lines
  - collision domains, 10
  - Ethernet, compared, 11
- ternary CAM (Content Addressable Memory), 53
- TIA (Telecommunications Industry Association), 6
- Time Delay Reflectometers (TDRs), 12
- timers
  - spanning-tree timers, 255–257
  - STP (Spanning Tree Protocol), 30
- token buckets, 215–217
- topologies
  - bus topologies, weaknesses, 9
  - Ethernet, 9
  - physical star topologies, 9
  - STP (Spanning Tree Protocol), changes, 30–31

ToS (type of service), Catalyst 6500, 208  
trace command, 329  
traffic

- congestion, head-of-line blocking, 44–45
- pruning, VLANs, 98–101

traffic flows, campus design, best practices, 300–301  
transitions, STP (Spanning Tree Protocol), 30  
transmission media, Ethernet, 6

- Ethernet over coax cabling, 8
- Ethernet over fiber optics, 7
- Ethernet over twisted-pair cabling, 6–7

transparent bridging, Ethernet, 20–22

- aging, 24
- filtering, 23
- flooding, 23
- forwarding, 24

Transport layer (OSI), 4  
trap bits (EARL tables), 53  
troubleshooting

- LAN switching configuration, 317–318
  - Cisco online resources, 334
  - hardware version checks, 319–327
  - Local SPAN, 330–331
  - port errors, 327–328
  - RSPAN, 331–333
  - software version checks, 318–319
  - SPAN (Switched Port Analyzer), 330–331
  - syslog messages, 328–329
  - trace command, 329
- MSFC, disappearance of, 326–327
- Supervisors, disappearance of, 324–325

truncated switching mode, Catalyst 6000/6500  
switches, 66  
trunking methods, switches, 199–201

- Layer 2 networks, 87–89
  - IEEE 802.1Q, 90–91
  - ISL (Inter-Switch Link) protocol, 89–90
  - trunking modes, 91–92
  - VTP (VLAN Trunking Protocol), 92–98

Type field (ISL encapsulation frame), 89

---

## U

UDLD (Unidirectional Link Detection) protocol, 281–282

- configuring, 201–202
- port states, 283

UplinkFast, spanning-tree convergence, 259–260  
upper layers (OSI), 4

- Application layer, 4
- Data Link layer, 5
- Network layer, 4
- Physical layer, 5
- Presentation layer, 4
- Session layer, 4
- Transport layer, 4

User field (ISL encapsulation frame), 89

---

## V-Z

valid bits (EARL tables), 53  
VLAN 1, 109

- Management VLAN, 109–111

VLAN field (ISL encapsulation frame), 89  
VLAN Trunking Protocol (VTP). *See* VTP (VLAN Trunking Protocol)  
VLANs

- access layers, configuring, 193–196
- Layer 2 networks, 84–87
- numbering, planning, 171
- numbering schemes, 296
- private VLANs, 111–115
- pruning methods, 98–101
- VLAN 1, 109
  - Management VLAN, 109–111
  - sc0 management interface, 168–171

VTP (VLAN Trunking Protocol), 92–95

- advertisement requests, 94
- configuring, 97–98, 130, 173–175
- domains, 92
- join messages, 95
- mode best practices, 96–97
- subset advertisements, 94
- summary advertisements, 93–94
- VLANs, pruning, 98–101

write memory command, 308  
Xmit Errors field (show port command), 328