



Symbols

- /16 address block, 36
- /24 address block, 36
- /8 address block, 35

Numerics

- 10 Gigabit Ethernet, 64
- 10-10 codes, 323–351
- 23B+D, 83
- 2B + D, 83
- 3DES, 236
- 456-Nxx NPA, 246
- 500 Nxx, 247
- 555 numbers, 248
- 66-blocks, 87. *See also* punchdown blocks
- 8xxx toll-free numbers, 247–248
- 900/976 Nxx, 247

A

- ABR, 131, 134, 183
- ABRs (area border routers), 401
- access layer, 201–203
- account scans, 219
- acknowledgements (EIGRP), 413
- active routes (EIGRP), 413
- active splitters, 98
- addresses, 11
 - data link layer, 11
 - MAC, 11
 - network addresses versus device name, 14
 - network layer, 12
 - assigning to devices, 13–14
 - TCP/IP, 33
- adjacencies (OSPF), 404–405
- administrative distance, 165, 384
- administrator access, illicit command execution, 212
- ADSL (Asymmetric Digital Subscriber Line), 53, 96
 - architecture, 97–98
 - data rates, 98–99
 - standards, 99

- agent-based software, 218
- aggregates, 186
- aggregator attribute (BGP), 379
- alternating loopback, 86
- American National Standards Institute (ANSI).
 - See* ANSI
- analog equipment, modems, 53
- analyzing traffic patterns, 182
- AND operation, 366
- ANI (automatic number identification), 243, 246
- Annex A LMI type, 151
- Annex D LMI type, 151
- ANSI (American National Standards Institute), 17
- ANSI T1.617 LMI specification, 151
- applets, 286
- Application layer (OSI), 25
- Application layer (TCP/IP model), 30
- application servers, 43
- area code. *See* NPA
- areas (OSPF), 9, 401
 - inter-area route summarization, 406
 - routing methods, 402
 - types of, 402
- ARP (Address Resolution Protocol), 203
- AS (autonomous system), 9, 158
- ASBRs (autonomous system border routers), 402
- ASN.1 (Abstract Syntax Notation One), 259
- ASNs (Autonomous Systems Numbers), 376
- AS-Path attribute (BGP), 377
- ASPs (Active Server Pages), 286
- assignment of network layer addresses, 13–14
- ATM (Asynchronous Transfer Mode), 123–126
 - CAC, 132
 - cell transmission, 127
 - connections, 126
 - DXI (Data Exchange Interface), 119
 - interfaces, 125–126
 - NNIs, 124
 - QoS parameters, 128, 132
 - service classes, 128, 182–183
 - ABR, 131
 - CBR, 130
 - UBR, 131
 - VBRnrt, 131
 - VBRrt, 130
- traffic contracts, 128–129, 133

- UNI, ILMI, 125
- UPC, 133
- virtual paths, 126
- atomic aggregate attribute (BGP), 379
- attacks
 - brute-force, 229
 - data destruction, 213
 - dictionary, 229
 - DoS, 211–212
 - exploits, 219
 - replay attacks, 406
 - signatures, 219–220
 - unauthorized access, 212
 - via macros, 214
- Attempt state (OSPF), 404
- attributes (BGP), 371, 376–377
 - aggregator, 379
 - AS-Path, 377
 - atomic aggregate, 379
 - local preference, 379
 - MED, 378–379
 - next hop, 378
 - origin, 378
 - weight, 378
- authentication
 - OSPF, 406
 - RIPv2, 365
 - VPNs, 228
 - CHAP, 229
 - digital certificates, 230
 - PAP, 229
 - RADIUS, 230
 - smart cards, 230
 - TACACS+, 231
- autonegotiation, 62
- autonomous networks, 371
- autonomous system (AS), 9
- availability
 - end-to-end diversity, 269
 - measuring, 265–268

B

- B (bearer channels), 83
- back doors, unauthorized access, 213
- backbone, 196, 198
 - hubs, 73
 - routers, 401
- backup power supplies, 272–274
- bandwidth
 - as routing metric, 164
 - CIR, 146
 - DWDM implementations, 316
 - link bandwidth (IGRP), 390
 - oversubscription, 203–204
- BDRs (backup designated routers), 404
- Bellman-Ford algorithms, 163
- best effort services
 - CIR, 146
 - UBR, 131
- BGP (Border Gateway Protocol), 372
 - administrative distance, 384
 - aggregator attribute, 379
 - AS-Path attribute, 377
 - atomic aggregate attribute, 379
 - attributes, 371, 376–377
 - communities, 377
 - confederations, 384
 - IBGP versus EBGp, 373
 - local preference attribute, 379
 - MED, 378–379
 - multihoming, 373
 - next hop, 378
 - origin attribute, 378
 - peering, 381
 - route reflectors, 382–384
 - route selection process, 380–381
 - timers, 385
 - weight, 378
- BIAs (burned-in addresses), 12
- binary representation of IP addresses, 33
- bit buckets, 158
- black-box-based VPNs, 237
- Blocking state (STP), 75
- break-ins, 213
- bridge clips, 88
- bridged taps, 98

bridges, 52, 73–76, 195
 broadcast transmission, 71–72
 broadcasting, 34
 brute-force attacks, 229
 buffering, 15
 burned-in addresses (BIAs), 12
 bus network termination points, 58
 bus topology, 58

C

cable access architecture, 101–102
 cable modems, data rates of, 102
 cabling
 bridged taps, 98
 fiber optic, LTE, 90
 landlines, 83
 UTP, 100
 CAC (Connection Admission Control), 132
 calculating IGRP metrics, 391–392
 CANs (campus area networks), 193
 CAR (committed access rate), traffic policing, 302
 CAs (Certificate Authorities), 230
 casual dialing, 89
 CATV
 cable access architecture, 101–102
 cable modems, data rates of, 102
 DOCSIS, 103
 MCNS, 101
 CBR (constant bit rate), 130, 133, 182
 CDV (Cell Delay Variation), 128, 132
 CDVT (Cell Delay Variation Tolerance), 128
 CE (customer edge) routing, 301
 cells, 8
 discard-eligible, 131
 transmission, 127
 cell-switched WANs, 113
 ATM, 123–124
 CAC, 132
 cell transmission, 127
 connections, 126
 interfaces, 125–126
 NNIs, 124
 QoS parameters, 132
 service classes, 128–131
 traffic contracts, 128–129
 UPC, 133
 virtual paths, 126
 CGI (Common Gateway Interface), 286
 CHAP, 229
 characteristics
 of cell-switched WANs, 113
 of circuit-switched networks, 112
 of OSI layers, 21
 Application layer, 25
 Data-Link layer, 23
 Network layer, 23
 Physical layer, 23
 Presentation layer, 24
 Session layer, 24
 Transport layer, 24
 of OSPF, 399
 of packet-switched networks, 112
 chat, 284
 CIC (Carrier Identification Code), 244
 CICR (Classless Interdomain Routing), 33
 CIR (committed information rate), 146–147
 circuit-switched WANs, 112
 Cisco LocalDirector, 44
 Cisco optical product suite, EoS notice, 317
 clandestine intruders, 217
 Class A addresses, 35
 Class B addresses, 36
 Class C addresses, 36
 Class D addresses, 36
 Class E addresses, 36
 Class of Service. *See* CoS
 classful routing, 33
 classful routing protocols, IGRP. *See* IGRP
 classifying
 routing algorithms, 160
 flat versus hierarchical, 161–162
 host-intelligent versus router-intelligent, 162
 intradomain versus interdomain, 163
 link-state versus distance vector, 163
 single-path versus multiple path, 161
 static versus dynamic, 161
 types of networks, 195
 classless routing, 33
 client platforms, 46
 clipping, 183
 clocking, 183

- clouds, 111
 - CLR (Cell Loss Ratio), 128, 132
 - CMIP (Common Management Interface Protocol), 259
 - CMTS (cable modem termination system), 102
 - CO (central office), 248
 - last mile, 85
 - LEC CO configuration, 89–91
 - lines, 249
 - station subscriber number, 249
 - commands, show ip eigrp topology all, 413
 - communication equipment
 - CSU/DSU, 47, 49
 - DTE/DCE equipment, 49
 - HIPPI, 51
 - HSSI, 51
 - RS-232C, 50
 - RS-422/449, 50
 - V.35, 51
 - V.90, 51
 - multiplexers, 47
 - communities, 377
 - confederations, 384
 - confidentiality breaches, 212
 - congestion, flow control, 14
 - buffering, 15
 - source-quench messages, 15
 - windowing, 15
 - connection-oriented protocols, 10, 29
 - ATM, 123–124
 - CAC, 132
 - cell transmission, 127
 - connections, 126
 - interfaces, 125–126
 - NNIs, 124
 - service classes, 128–131
 - traffic contracts, 128–129
 - UPC, 133
 - virtual paths, 126
 - connectionless protocols, 10, 29
 - UDP, 37
 - convergence mechanisms
 - as routing algorithm design goal, 159
 - EIGRP, 414
 - IGRP, 393
 - flash update, 393
 - hold-downs, 393
 - poison reverse, 394
 - split horizon, 394
 - OSPF, 404–405
 - RIP, 357
 - count-to-infinity, 358, 360
 - hold-down timers, 361
 - split horizon, 360
 - split horizon with poison reverse, 360
 - triggered updates, 361
 - core elements (WANs), 118
 - core layer, 196, 198
 - CoS (Class of Service), 181
 - cost, 212, 353
 - as routing metric, 165
 - count-to-infinity, 358–360
 - RIPv2, 367
 - CPE (customer premise equipment)
 - 66-block installation, 88
 - bridges, 52
 - demarc, 86
 - extended demarc, 88
 - hubs, 52
 - LAN switches, 52
 - routers, 52
 - servers, 43–46
 - CRB (Concurrent Routing and Bridging), 74
 - CRC (cyclical redundancy check), 16, 149–150
 - crosstalk, 50
 - cryptosystems
 - IPSec, 234
 - PGP, 233
 - CSMA/CD, 62
 - CSU/DSU, 47–49
 - CTD (Cell Transfer Delay), 128
 - custom queuing, 197
 - customer-based NNIs, 116
 - cut-through switching, 77
-
- ## D
- D (data) channel, 83
 - DACS (Digital Access and Cross-Connect Systems), 317
 - DACS (Digital Access Cross-Connect Switch), 119
 - data destruction, 213
 - data diddling, 213

- data encapsulation, 26
- data encryption, 233
- data link layer
 - addressing, 11
 - frames, 6
- data rates
 - of ADSL, 98–99
 - of cable modems, 102
- data transfer mode (PVCs), 145
- Data-Link layer (OSI), 23
- database description packets (OSPF), 403
- datagrams, 6
 - fragmentation, 8
- DE (discard eligibility), 147
- dedicated access, 83
- dedicated local access
 - customer premise configuration, 85
 - IXC dedicated, 84–85
 - LEC dedicated, 84
 - punch-down blocks, 87–88
- dedicated PSTN access, 243–245
- default gateways, 158
- default routes, 354
- delay, 164
 - IGRP metric, 390
- demarc, 86
- DES (Data Encryption Standard), 236
- design goals of routing algorithms, 159–160
- detecting unauthorized access, 217
- deterministic networks, 65
- devices, 195
 - bridges, 52, 73–74
 - Spanning Tree, 75–76
 - cable modems, 102
 - CSU/DSU, 47, 49
 - DTE/DCE interfaces, 49
 - HIPPI, 51
 - HSSI, 51
 - RS-232C, 50
 - RS-422/449, 50
 - V.35, 51
 - V.90, 51
 - Frame Relay, 140
 - hubs, 52, 72–73
 - LAN switches, 52
 - modems, 53
 - DSL, 53
 - gradual degradation, 53
 - multiplexers, 47
 - network addresses versus name, 14
 - OSPF routers, 401
 - repeaters, 119
 - routers, 52, 78
 - servers, 43
 - platform servers, 44–46
 - smart cards, 230
 - switches, 76–77
 - WAN core elements, 118
- DHCP (Dynamic Host Configuration Protocol), 202
- dictionary attacks, 229
- DID (Direct Inward Dialing), 249
- DiffServ, 185
- diffusing computation, 411
- digital certificates
 - PKI, 234
 - VPN authentication, 230
- Dijkstra Algorithm, 399
- Disabled state (STP), 75
- discard-eligible cells, 131
- discrete math, Graph Theory, 399
- distance vector routing protocols, 163
 - IGRP. *See* IGRP
 - RIP. *See* RIP
- distribution layer, 199–201
- DLCIs (data-link connection identifiers), 141–144, 148–149
 - local significance, 142
 - universal significance, 142
- DLSw+ (Data Link Switching Plus), 75
- DMZ (demilitarized zone), 214
- DNS (Domain Name System), 14, 281
 - lookup database, 32
 - zones, 14
- DOCSIS (Data Over Cable Service Interface Specification), 101–103
- DOD (Direct Outward Dialing), 249
- DOI (Domain of Interpretation), 235
- domains, 9
- DoS attacks, 211–212
- dotted decimal notation, 33
- Down state (OSPF), 404
- downstream neighbors, 65, 158

DRs (designated routers), 404
 DSL (Digital Subscriber Line), 95. *See also* xDSL
 ADSL standards, 100
 modems, 53
 DSLAM (DSL Access Multiplexer), 53
 DTE/DCE interfaces, 49
 HIPPI, 51
 HSSI, 51
 RS-232C, 50
 RS-422/449, 50
 V.35, 51
 V.90, 51
 DTR (Dedicated Token Ring), 64
 DUAL (Diffusing Update Algorithm) finite state machine, 410–411
 rapid convergence, 414
 dual homing, 66
 Dual Leaky Bucket, 129
 dual rings, 67
 duplex modes, 145
 DWDM (Dense Wave Division Multiplexing), 315–316
 DXC (digital cross connect system), 90
 dynamic addresses, 13–14
 dynamic load balancing, 362
 dynamic routing algorithms, 161

E

E.164 addressing, 149
 EBG (exterior BGP) versus IBGP, 373
 Edge LSRs (Label Switch Routers), 296
 EGPs (Exterior Gateway Protocols), 353
 BGP, 372
 administrative distance, 384
 attributes, 376–377
 confederations, 384
 multihoming, 373
 peering, 381
 route reflectors, 382–384
 route selection, 380–381
 timers, 385
 EIA (Electronic Industries Association), 17
 EIGRP (Enhanced Interior Gateway Routing Protocol), 201
 convergence, 414
 DUAL, 410–411
 neighbor discovery/recovery mechanism, 410
 packets, 413–414
 protocol-specific modules, 411–412
 RTP, 411
 tables, 412
 versus IGRP, 410
 Electronic Industries Association (EIA), 17
 e-mail, 214, 282
 bombs, 214
 spam, 214
 EMI (electromagnetic interference) crosstalk, 50
 encapsulation, 26, 31, 199
 encryption, 233
 DES, 236
 PGP, 233
 end stations, 257
 end system (ES), 8, 158
 end-to-end diversity, 269
 entries, EIGRP topology table, 413
 EoS (end of sales) notice for Cisco optical product suite, 317
 equal cost load sharing, 198
 equal-cost load balancing, 395
 error-checking mechanisms
 CRC, 16
 parity checking, 16
 ES (end system), 8, 158
 Ethernet, 61
 10 Gigabit Ethernet, 64
 CSMA/CD, 62
 Fast Ethernet, 62
 Gigabit Ethernet, 63
 exchange code, 248
 Exchange state (OSPF), 405
 exploits, 219
 Exstart state (OSPF), 405
 extended demarc, 86–88
 external BGP peers, 381
 external intruders, 217

F

- Fast Ethernet, 62
- fast switching, 77
- fault management, 256
- fault-tolerant media, 274
- FCAPS model, 256
- FDDI (Fiber Data Distributed Interface), 59, 66
 - dual homing, 66
 - primary rings, 69
 - secondary rings, 69
- FDM (Frequency Division Multiplexing), 47
- feasible successors
 - EIGRP, 411
 - IGRP, 395
- features of OSPF, 400–401
- fiber optics, 309
 - cabling, LTE, 90
 - DWDM, 315–316
 - GI fiber, 311
 - MMF, 311
 - mode, 310
 - optical switching, 317
 - RI, 309
 - SMF, 311
 - SONET, 311–313
 - optical interface layers, 314–315
 - path elements, 313
 - STS, 313
 - transmission windows, 310
- fields of RIP routing table, 354
- file servers, 43
- firewall-based VPNs, 236
- firewalls, 217
 - DMZ, 214
 - proxy servers, 214
- fixed metrics
 - RIP, 362
 - RIPv2, 368
- flash updates (IGRP), 393
- flat address space, 13
- flat routing systems, 162
- flavors of DSL
 - ADSL, 96
 - architecture, 97–98
 - data rates, 98–99
 - standards, 99

- flexibility as routing algorithm design goal, 160
- flow control, 14
 - buffering, 15
 - source-quench messages, 15
 - windowing, 15
- forged packets, 212
- format of transmitted data, 6
 - cells, 8
 - datagrams, 6
 - frames, 6
 - packets, 7
 - segments, 7
- Forwarding state (STP), 76
- FRADs (Frame Relay Access Devices), 140
- Frame Relay, 140
 - CIR, 146
 - DE, 147
 - error handling, 149–150
 - FRADs, 140
 - LMI specifications, 150–151
 - types of, 151
 - local access loop, 140
 - PVCs, 144–145
 - QoS, 183–184
 - SVCs, 145
 - DLCIs, 148–149
 - E.164 addressing, 149
 - X.121 addressing, 149
 - virtual circuits, 141
 - DLCIs, 142–144
 - parameters, 146
- frames, 6
 - DE, 147
- FTP (file transfer protocol), 283
- FTTC (fiber-to-the-curb), 99
- FTTH (fiber-to-the-home), 99
- Full state (OSPF), 405
- full-duplex communication, 61, 145
- full-mesh topologies, redundancy, 272

G

- GCRA (Generic Cell Rate Algorithm), 129
- GDMO (Guideline for Definition of Managed Objects), 259
- GI (Graded Index) fiber, 311

Gigabit Ethernet, 63
global DLCI addresses, 142
gradual degradation, 53
Graph Theory, 399

H

half-duplex communication, 61, 145
hard loop testing, 86
hardware backup, 274
hardware tokens, 230
HDSL (Hi-Speed Digital Subscriber Line), 100
headers, 26
hello packets
 EIGRP, 413
 OSPF, 402
helper-addressing, 202
hierarchical address space, 13
hierarchical network model, 196
 access layer, 201–203
 core layer, 196, 198
 distribution layer, 199–201
hierarchical routing systems, 162
high availability, 265–268
hijacked SMTP sessions, 213
HIPPI (High-Performance Parallel Interface), 51
Hold Timer (IGRP), 392
hold-down timers, 361
 BGP, 385
 IGRP, 393
hop count
 IGRP, 390
 limitations of RIP, 361–362
host communications, same-layer interaction, 25
host-based IDS, 218
host-intelligent routing algorithms, 162
HSRP (Hot Standby Routing Protocol), 274
HSSI (High-Speed Serial Interface), 51
HTML (HyperText Markup Language), 280
hub-and-spoke topology, 57–58
hubs, 52, 72–73, 195
hyperlinks, 280
hyperspace, 286
hypertext documents, 280

I

IAB (Internet Architecture Board), 17
IBGP (Interior Border Gateway Protocol) versus
 EBGP, 373
ICMP (Internet Control Message Protocol), 37
idle mode (PVCs), 145
IDSL (Integrated Services Digital Network Digital
 Subscriber Line), 100
IDSs (Intrusion Detection Systems), 217
 host-based, 218
 network-based, 219
 placement
 in backbone, 222
 in network perimeter, 220–221
 in server farm, 222
 statistical profiling, 217–220
IEEE (Institute of Electrical and Electronic
 Engineers), 17
IEEE 802.1d, 75–76
IEEE 802.3, 61
 10 Gigabit Ethernet, 64
 CSMA/CD, 62
 Fast Ethernet, 62
 Gigabit Ethernet, 63
IEEE 802.5, 64–65
 downstream neighbor, 65
 DTR, 64
 THT, 65
IGPs (Interior Gateway Protocols), 353
IGRP (Interior Gateway Routing Protocol), 371
 convergence mechanisms, 393
 flash update, 393
 hold-downs, 393
 poison reverse, 394
 split horizon, 394
 load balancing, 394
 equal-cost, 395
 feasible successors, 395
 unequal-cost, 395
 metrics, 389
 calculating, 391–392
 delay, 390
 hop count, 390
 link bandwidth, 390
 load, 391
 MTU, 390

- reliability, 391
- timers, 392
- versus EIGRP, 410
- IKE (Internet Key Exchange), 235
- illicit command execution, 212
- ILMI (Integrated Local Management Interface), 125
- IM (instant messaging), 284
- information formats of transmitted data, 6
 - cells, 8
 - datagrams, 6
 - frames, 6
 - packets, 7
 - segments, 7
- Init state (OSPF), 405
- Institute of Electrical and Electronic Engineers (IEEE), 17
- inter-area route summarization, 406
- interdomain algorithms, 163
- interfaces
 - ATM, 125–126
 - NNIs, 114–116
 - UNIs, 113
- interLATA connections, 84
- intermediate system (IS), 8
- internal BGP peers, 381
- internal intruders, 217
- internal routers (OSPF), 401
- International Organization for Standardization (ISO), 17
- Internet
 - peering, 287–288
 - programming languages, 286–287
 - URLs, 284–285
- Internet Architecture Board (IAB), 17
- Internet layer (TCP/IP model), 31
- Internet protocols, 282
 - chat, 284
 - e-mail, 282
 - FTP, 283
 - Telnet, 282
 - Usenet news, 283
- interworking, 3
 - information formats, 6
 - cells, 8
 - datagrams, 6
 - frames, 6
 - packets, 7
 - segments, 7
 - ISO Hierarchical model, 8
 - intradomain algorithms, 163
 - intraLATA connections, 84
 - intranet servers, 43
 - intrusion detection, 217
 - IP (Internet Protocol), 32. *See also* IP addressing
 - interaction with TCP, 32
 - QoS, 184
 - reliability mechanisms, 184–185
 - routing, 38
 - IP addressing
 - CIDR, 33–34
 - Class A addresses, 35
 - Class B addresses, 36
 - Class C addresses, 36
 - Class D addresses, 36
 - Class E addresses, 36
 - DNS, 281
 - loopback addresses, 34–35
 - network addresses, 35
 - subnet masks, 366
 - VLSM, 33–34
 - IP prefix, 33
 - IPSec, 234
 - LAN-to-LAN VPNs, 235–236
 - IRB (Integrated Routing and Bridging), 75
 - IRC, 284
 - IS (intermediate system), 8), 158
 - ISDN (Integrated Services Digital Network), 83
 - ISO (International Organization for Standardization), 17
 - ISO Hierarchical model, 8
 - network layer addressing, 12
 - ISPs (Internet Service Providers), peering, 287
 - BGP, 381
 - NAPs, 288
 - ITU-T (International Telecommunication Union Telecommunication Standardization Sector), 17
 - M.3000 recommendation, 259
 - Q.933 LMI specification, 151
 - IXCs (inter-exchange carriers), 83
 - dedicated access, 84–85
 - switched access, 244

J-K-L

Java, 286

keepalive timers, BGP, 385

L2F (Layer 2 Forwarding), 232

L2TP (Layer 2 Tunneling Protocol), 233

labels, 296

landlines, 83

LAN-to-LAN VPNs, 235–236

LANs, 3, 193. *See also* VLANs

 broadcast transmission, 71–72

 bus topology, 58

 CPE

 bridges, 52

 hubs, 52

 LAN switches, 52

 routers, 52

 end-to-end diversity, 269

 Ethernet, 61

 10 Gigabit Ethernet, 64

 CSMA/CD, 62

 Fast Ethernet, 62

 Gigabit Ethernet, 63

 FDDI, 66

 dual homing, 66

 primary rings, 69

 secondary rings, 69

 hardware

 bridges, 73–76

 hubs, 72–73

 routers, 78

 switches, 76–77

 hub-and-spoke topology, 57–58

 multicast transmission, 70

 ring topology, 59

 switches, 52

 Token Ring, 64–65

 downstream neighbor, 65

 DTR, 64

 THT, 65

 tree topology, 60

 unicast transmission, 69–70

 workstations, 46

last mile, 85

LATA (Local Access and Transport Area), 84

latch loop testing, 86

Layer-3 switching, 77

Layer-3 VLANs, 175

layers

 of DOCSIS specification, 103

 of OSI Reference Model, 5

 Application layer, 25

 characteristics, 21

 Data-Link layer, 23

 encapsulation, 26

 Network layer, 23

 Physical layer, 23

 Presentation layer, 24

 same-layer interaction, 25

 Session layer, 24

 Transport layer, 24

 of TCP/IP model

 Application layer, 30

 Internet layer, 31

 Network Access layer, 31

 Transport layer, 30

LDP (Label Distribution Protocol), 296

Leaky Bucket, 129

Learning state (STP), 76

LECs (Local Exchange Carriers), 83

 CO configuration, 89, 91

 dedicated PSTN access, 84, 245

 switched PSTN access, 244

LERs (label edge routers), 185

liability, 264

lines, 249

link bandwidth of IGRP, 390

link-state acknowledgement packets (OSPF), 403

link-state algorithms, 163

link-state request packets (OSPF), 403

link-state routing protocols, OSPF. *See* OSPF

link-state update packets (OSPF), 403

Listening state (STP), 76

LMI (Local Management Interface) specifications,
150–151

load balancing, 197, 373

 IGRP, 394

 equal-cost, 395

 feasible successors, 395

 unequal-cost, 395

- load metric, 165
 - IGRP, 391
- load sharing, 198, 373
- Loading state (OSPF), 405
- local access, 83
 - dedicated, 84
 - customer premise configuration, 85–86
 - punchdown blocks, 87–88
 - LEC CO configuration, 89–91
 - switched, 89
- local access loop, Frame Relay, 140
- local loop, 85
- local preference attribute (BGP), 379
- local significance, 142
- logical addresses, 12–14
- long-distance services, 84
 - PIC, accessing, 89
- loopback addresses, 34–35
- loopback testing, 86
- looped topologies, Spanning Tree, 75–76
- lower layers of OSI Reference Model, 22
- LSAs (link-state advertisements), 158, 399
- LSP (label switched path), 296
- LSRs (label switch routers), 185, 296
- LTE (light termination equipment), 90, 314

M

- M.3000 series recommendation (ITU-T), 259
- M13 (Multiplexer DS1/DS3), 118
- MAC addressing, 11
 - VLANs, 175
- macros, 214
- MAEs (Metropolitan Area Exchanges), 289
- mail servers, 44
- management entities, 257
- mandatory attributes (BGP), 376
- masquerades, 217
- Max CTD (Maximum Cell Transfer Delay), 132
- MBS (maximum burst size), 128
- MCNS (Multimedia Cable Network System Partners, Ltd.), 101
- MCR (minimum cell rate), 128
- MD5 (Message Digest 5), 234
- measuring availability, 265–268
- MED (mult-exit discriminator) attribute, 378–379

- media failure, 274
- media translation, 201
- membership, VLANs, 175
- MEMS (Micro Electrical Mechanical Systems), 317
- meshed network topologies, 270, 272
- metrics, 157, 164–166
 - administrative distance, 165, 384
 - bandwidth, 164
 - communication cost, 165
 - delay, 164
 - IGRP, 389
 - calculating, 391–392
 - delay, 390
 - hop count, 390
 - link bandwidth, 390
 - load, 391
 - MTU, 390
 - reliability, 391
 - load, 165
 - path length, 164
 - reliability, 164
- MIB2, 258
- MIBs (Management Information Bases), 258
- MIME (Multimedia Internet Mail Extension), 282
- misfeasors, 217
- mixed-media bridging, 74
- MMF (multimode fiber), 310–311
- modems, 53
 - DSL, 53
 - gradual degradation, 53
 - V.90, 51
- MPLS (Multiprotocol Label Switching), 185
 - CE routing, 301
 - operation, 297–298
 - packet forwarding, 298–299
 - VPNs, 299
 - components, 300
 - tunneling, 300
- MPLS-TE, 185
- MSOs (multiple system operators), 101
- MTBF (Mean-Time-Between Failure), 265
- MTTR (Mean-Time-To-Repair), 265
- MTU (Maximum Transmission Unit), 6, 23
 - IGRP, 390
 - overloading, 8

- multi-port source-route bridges, 75
- multi-tiered network design, 73
- multicast transmission, 70
- multicasting, 34
 - RIPv2, 367
- multihoming, 373
- multipath algorithms, 161
- multiplexers, 47, 118

N

- NANP (North American Numbering Plan)
 - ANIs, 246
 - NPA, 246
 - 456-Nxx, 246
 - 500 Nxx, 247
 - 8xxx toll-free numbers, 247–248
 - 900/976 Nxx, 247
 - exchange code, 248
 - station subscriber number, 249
- NBAR (Network-Based Application Recognition), 182
- neighbor discovery/recovery mechanism, 410
- neighbor table (EIGRP), 412
- NEs (network elements), 259
- NetFlow Accounting, analyzing traffic patterns, 182
- Network Access layer (TCP/IP model), 31
- network access servers, 44
- network addresses, 35
 - assignment of, 13–14
 - data link layer, 11
 - MAC, 11
 - network layer, 12
 - versus device name, 14
- network architecture, hierarchical network model, 196
 - access layer, 201–203
 - core layer, 196–198
 - distribution layer, 199–201
- network layer (OSI Reference Model), 23
 - addresses, 12
 - packets, 7
- network local access, 83
 - customer premise configuration, 85
 - dedicated
 - IXC dedicated, 84–85
 - LEC dedicated, 84
 - LEC CO configuration, 89, 91
 - punchdown blocks, 87–88
 - switched, 89
- network management
 - agents, 257
 - end stations, 257
 - FCAPS model, 256
 - management entities, 257
 - SNMP, 258
 - TMN, 259–260
- network-based IDS, 219
- newsgroups, 284
- next hop, 157–158
- next hop attribute (BGP), 378
- NIUs (network interface units), placement of, 85
- NNIs (network-to-network interfaces), 114–116, 124–126
 - customer-based, 116
 - NSP-based, 116
- NOC (Network Operations Center), 255
- non-client peers, 382
- nonrepudiation, 234
- non-transitive optional attributes, 377
- normal user access, illicit command execution, 212
- NPA (Numbering Plan Assignment), 246
 - 456-Nxx, 246
 - 500 Nxx, 247
 - 8xxx toll-free numbers, 247–248
 - 900/976 Nxx, 247
 - exchange code, 248
 - station subscriber number, 249
- NSPs, NNIs, 116
- N-squared algorithm, 382
- NTUs (network termination units)
 - placement of, 85
- Null authentication (OSPF), 406
- null interface, 158

O

- octets, 32
- opening a socket, 37
- optical networks
 - MPLS, 185
 - SONET, 311–313
 - optical interface layers, 314–315
 - path elements, 313
 - switching, 317
- optimality as routing algorithm design goal, 159
- optional attributes (BGP), 377
- Organizationally Unique Identifier (OUI), 11
- origin attribute (BGP), 378
- OSI Reference Model, 5
 - Application layer, 25
 - Data-Link layer, 23
 - frames, 6
 - encapsulation, 26
 - layer characteristics, 21
 - Network layer, 23
 - packets, 7
 - Physical layer, 23
 - Presentation layer, 24
 - same-layer interaction, 25
 - Session layer, 24
 - Transport layer, 24
- OSPF (Open Shortest Path First)
 - areas, 401
 - types of, 402
 - authentication, 406
 - convergence, 404–405
 - features, 400–401
 - packet types, 402–403
 - route selection process, 399–400
 - route summarization, 405
 - routing methods, 402
- OUI (Organizationally Unique Identifier), 11
- oversubscription, 203–204

P

- packet forwarding, MPLS, 298–299
- packet switching, 157
- packet-switched WANs, 112
- packets, 7, 31
 - EIGRP, 413–414
 - OSPF, 402–403
 - authentication, 406
 - TCP/IP, size limitations, 31
- PAP 9 (Password Authentication Protocol), 229
- parity checking mechanisms, 16
- partners associated with MCNS, 101
- passive routes (EIGRP), 413
- passive splitters, 98
- passwords, dictionary attacks, 229
- path determination, 157
 - routing update messages, 158
- path length, 164
- path of last resort, 157
- PBX (private branch exchange) lines, 249
- PCR (peak cell rate), 128
- peering, 287
 - BGP, 381
 - NAPs, 288
- performance penalties, 390
- PET (Path Terminating Equipment), 314
- PGP (pretty good privacy), 233
- PHB (Per-Hop Behavior), 185
- Physical layer (OSI), 23
- PIC (Presubscribed Interexchange Carrier) code,
 - 89, 244, 323–351
- PKI (Public Key Infrastructure), 234
- placement of IDSs
 - in backbone, 222
 - in network perimeter, 220–221
 - in server farm, 222
- Plain Old Telephone Service (POTS), 83
- platform servers, 44–46
- PNNI (Private Network-to-Network Interface), 125
- poison reverse updates, IGRP, 394
- policing, 133
- policy-based distribution, 200
- port-based VLANs, 175

- ports, 30
 - TCP, 36–37
- POTS (plain old telephone service), 83
 - splitters, 98
- power supplies, redundancy, 272–274
- PPP (Point-to-Point Protocol), 232
- PPTP (Point-to-Point Tunneling Protocol), 232
- Presentation layer (OSI), 24
- primary rings, 69
- print servers, 44
- priority queuing, 197
- programming languages, 280
 - web-based, 286–287
- proxy servers, 44, 214
- PSTN (Public Switched Telephone Network), 83
 - dedicated access, 243, 245
 - switched access, 243–244
- punch-down blocks, 87–88
- PVCs (permanent virtual circuits), 113, 144–145
 - configurable parameters, 146
 - DLCIs, 142–144
 - duplex modes, 145

Q

- QDM (QoS Device Manager), analyzing traffic patterns, 182
- QoS (quality of service), 181
 - analyzing traffic patterns, 182
 - ATM
 - service classes, 182–183
 - traffic parameters, 128, 132
 - DiffServ, 185
 - Frame Relay, 183–184
 - IP reliability mechanisms, 184–185
 - MPLS, 185
- Quality of Service. *See* QoS
- Query packets (EIGRP), 413
- queues
 - Leaky Bucket model, 129
 - policing, 302

R

- RADIUS VPN authentication, 230
- rapid convergence, EIGRP, 414
- recoloring, 302
- redirect bombs, 214
- redundant power systems, 272–274
- redundant WAN links, 270
- refraction, 309
- reliability (IGRP metric), 391
- reliable network components, 164
 - fault-tolerant media, 274
 - hardware backup, 274
 - IP, 184–185
 - meshed network topologies, 270–272
 - redundant power systems, 272–274
 - redundant WAN links, 270
- Remote Access Servers, 44
- remote access VPNs, 227–228
 - authentication, 228–231
 - black-box-based, 237
 - firewall-based, 236
 - L2F, 232
 - L2TP, 233
 - LAN-to-LAN, 235–236
 - PPTP, 232
 - router-based, 238
 - tunneling protocols, 231
- remote login, unauthorized access, 213
- repeaters, 119
- replay attack protection, 406
- Reply packets (EIGRP), 414
- RI (Refractice Index), 309
- ring topology, 59
- RIP (Routing Information Protocol), 203. *See also* RIPv2
 - bandwidth consumption, 362
 - convergence, 357
 - count-to-infinity, 358–360
 - hold-down timers, 361
 - split horizon, 360
 - split horizon with poison reverse, 360
 - triggered updates, 361
 - dynamic load balancing, 362
 - fixed metrics, 362

- hop count limitations, 361–362
 - routing tables, 353–357
 - RIPv2
 - authentication, 365
 - count-to-infinity, 367
 - fixed metrics, 368
 - maximum hop count, 367
 - multicasting, 367
 - next hop identification, 367
 - subnet mask support, 366
 - RJ-48S jack, 86
 - RJ-48X jack, 86
 - RMON (Remote Monitoring), 258
 - robustness as routing algorithm design goal, 159
 - Route Invalid Timer (IGRP), 392
 - route reflectors, 382, 384
 - route selection process
 - BGP, 380–381
 - EIGRP, 410
 - OSPF, 399–400
 - route summarization, OSPF, 405
 - Route-Flush Timer (IGRP), 392
 - routed protocols, 166
 - router-based VPNs, 238
 - router-intelligent routing algorithms, 162
 - routing, 38, 52, 78, 195
 - discovery process, 203
 - LERs, 185
 - LSRs, 185
 - metrics, 164–166
 - bandwidth, 164
 - communication cost, 165
 - delay, 164
 - load, 165
 - path length, 164
 - reliability, 164
 - OSPF, 401
 - area types, 402
 - routing methods, 402
 - states, 404–405
 - path determination, 157
 - source routing, 162
 - routing protocols, 78, 159, 166
 - classifying, 160
 - flat versus hierarchical, 161–162
 - host-intelligent versus router-intelligent, 162
 - intradomain versus interdomain, 163
 - link-state versus distance vector, 163
 - single-path versus multiple path, 161
 - static versus dynamic, 161
 - design goals, 159–160
 - routing tables, 78, 158
 - EIGRP, 412
 - OSPF, LSAs, 400
 - RIP, 353–357
 - routing update messages, 158
 - RS-232C standard, 50
 - RS-422/449 standards, 50
 - RSA Labs, MD5, 234
 - RSM (route-switching module), 175
 - RSRB (Remote Source Route Bridging), 75
 - RTP (reliable transport protocol), 411
-
- ## S
-
- SCR (sustainable cell rate), 128
 - SDH (Synchronous Digital Hierarchy), 311
 - SDSL (Symmetric Digital Subscriber Line), 100
 - secondary rings, 69
 - security, 234
 - attack methods, 213–214
 - authentication
 - RIPv2, 365
 - VPNs, 228–231
 - confidentiality breaches, 212
 - data destruction, 213
 - data diddling, 213
 - DMZ, 214
 - DoS attacks, 211–212
 - encryption, 233
 - firewalls, 217
 - IDSs
 - host-based, 218
 - network-based, 219
 - signature analysis, 218–220
 - statistical profiling, 217
 - IKE, 235
 - illicit command execution, 212
 - IPSec, 234

- network architectures
 - backbone, 222
 - network perimeter, 220–221
 - server farm, 222
- PGP, 233
- unauthorized access, 212
- segments, 7
- self-healing network technologies, SONET, 312
- servers, 43
 - platform servers, 44–46
- service classes (ATM), 128, 182–183
 - ABR, 131
 - CBR, 130
 - UBR, 131
 - VBRnrt, 131
 - VBRrt, 130
- Session layer (OSI), 24
- show ip eigrp topology all command, 413
- signature analysis, 218–220
- simple password authentication, 406
- simplex mode, 145
- simplicity, 159
- single-path algorithms, 161
- size limitations of TCP/IP packets, 31
- SM (single mode fiber), 310
- smart cards, VPN authentication, 230
- SMF (single-mode fiber), 311
- SMTP (Simple Mail Transfer Protocol), hijacked
 - sessions, 213
- SNMP (Simple Network Management Protocol), 258
- sockets, 30, 37
- soft loop testing, 86
- software tokens, 230
- SONET (Synchronous Optical Network), 311
 - operation, 313
 - optical interface layers, 314–315
 - path elements, 313
 - STS, 313
- source routing, 162, 214
- source-quench messages, 15
- source-route translational bridging, 74
- source-route transparent bridging, 74
- spamming, 213–214
- Spanning Tree Protocol, 75–76
- SPF (shortest path first) algorithms, 163, 399

- split horizon, 360
 - IGRP, 394
 - with poison reverse, 360
- stability as routing algorithm design goal, 159
- standards, DOCSIS, 103
- standards bodies, 17
- star topologies, 57–58
- static addresses, 13–14
- static routing algorithms, 161
- station subscriber numbers, 249
- statistical profiling, 217
- STDM (Statistical Time Division Multiplexing), 47
- STE (Section Terminating Equipment), 314
- store and forward switching, 77
- strategic network management, 255
- STS (SONET Transport Signal), 313
- stub areas, 402
- subnet masks, 366
- subnetting, 366
- summarization, OSPF, 405
- SVCs (Switched Virtual Circuits), 113, 124, 145
 - configurable parameters, 146
 - DLCIs, 148–149
 - E.164 addressing, 149
 - X.121 addressing, 149
- switched access, 83, 89, 198, 243–244
- switching, 76–77, 195
 - VLANs, 173–174
 - membership, 175
 - RSM, 175
 - types of, 175
- symmetric key systems, DES, 236

T

- TACACS+ (Terminal Access Controller Access Control System), VPN authentication, 231
- tactical network management, 255
- TCP (Transmission Control Protocol), 32
 - interaction with IP, 32
 - port numbers, 37
 - ports, 36
 - sockets, 37
 - versus UDP, 29

- TCP/IP. *See also* TCP/IP model
 - addressing, 33
 - Internet address structure, 32
 - IP addressing
 - Class A addresses, 35
 - Class B addresses, 36
 - Class C addresses, 36
 - Class D addresses, 36
 - Class E addresses, 36
 - loopback addresses, 34–35
 - network addresses, 35
 - IP routing, 38
 - packets, size limitations, 31
 - TCP
 - port numbers, 37
 - ports, 36
 - sockets, 37
 - versus UDP, 29
- TCP/IP model
 - Application layer, 30
 - Internet layer, 31
 - Network Access layer, 31
 - Transport layer, 30
- TCP/UDP port, 302
- TDM (Time Division Multiplexing), 47
- TE (Traffic Engineering), 185
- Telnet, 282
- terminal servers, 44
- three-tiered hierarchical network model, 196
 - access layer, 201–203
 - core layer, 196–198
 - distribution layer, 199–201
- THT (Token Hold Time), 65
- tie lines, 249
- timers
 - BGP, 385
 - IGRP, 392
- TLDs (top-level domains), 285
- TMN (Telecommunications Management Network), 259–260
- Token Ring, 64–65
 - downstream neighbor, 65
 - DTR, 64
 - THT, 65
- toll-free numbers, 247–248
- topologies
 - bus, 58
 - convergence
 - EIGRP, 414
 - IGRP, 393–394
 - OSPF, 404–405
 - RIP, 357–358, 360–361
 - hub-and-spoke, 57–58
 - ring, 59
 - tree, 60
- topology table (EIGRP), 412–413
- totally stubby areas, 402
- traffic
 - aggregates, 186
 - flow control, 14
 - buffering, 15
 - source-quench messages, 15
 - windowing, 15
 - load balancing, 394–395
 - IGRP, 373
 - patterns, analyzing, 182
- traffic contracts, ATM, 128–129
- traffic policing, 133
 - CAR, 302
- trailers, 26
- transitive optional attributes, 377
- transmission windows, 310
- Transport layer (OSI), 24
- Transport layer (TCP/IP model), 30
- transport protocols, connection-oriented versus
 - connectionless services, 10
- tree topology, 60
- triggered updates, 361
- trunks, 249
- tunneling, 199
 - MPLS VPNs, 300
- tunneling protocols, 231
 - L2F, 232
 - L2TP, 233
 - PPTP, 232
- two-way state (OSPF), 405

U

- UBR (unspecified bit rate), 131, 134, 183
- UDP (User Datagram Protocol), 37
 - versus TCP, 29
- unauthorized access, 212
 - back doors, 213
 - intrusion detection, 217
 - host-based IDS, 218
 - network-based IDS, 219
 - signature analysis, 218–220
 - statistical profiling, 217
 - remote login, 213
 - SMTP session hijacking, 213
- unequal-cost load balancing, 198, 395
- unicast transmission, 34, 69–70
- UNIs (user-to-network interfaces), 113
- universal significance, 142
- UPC (Usage Parameter Control), 133
- Update packets (EIGRP), 413
- Update Timer (IGRP), 392
- upper layers of OSI Reference Model, 22
- URLs (Uniform Resource Locators), 284–285
- Usenet news, 283
- UTP (unshielded twisted pair), 100

V

- V.35 standards, 51
- V.90 standards, 51
- Variable Length Subnet Masks (VLSM), 33
- VBR (Variable Bit Rate), 182
 - VBRnrt, 131, 134
 - VBRrt, 130, 133
- VCs (virtual circuits), 112
- VDSL (Very-High-Data-Rate Digital Subscriber Line), 100
- virtual addresses, 12–14
- virtual circuits, 141
 - DLCIs, 142–144
 - parameters, 146
 - PVCs, 144–145
 - SVCs, 145
 - DLCIs, 148–149
 - E.164 addressing, 149
 - X.121 addressing, 149

- virtual paths, ATM, 126
- viruses, 214
- VLANs (Virtual LANs), 76, 173–174
 - membership, 175
 - types of, 175
 - WAN integration, 175
- VLSM (Variable Length Subnet Masks), 33
- VoFr (Voice over Frame Relay), 183
- voice clipping, 183
- voice networks
 - lines, 249
 - PSTN
 - dedicated access, 245
 - switched access, 244
- VPNs (Virtual Private Networks), 227–228, 299
 - authentication, 228
 - CHAP, 229
 - digital certificates, 230
 - PAP, 229
 - RADIUS, 230
 - smart cards, 230
 - TACACS+, 231
 - black-box-based, 237
 - components, 300
 - firewall-based, 236
 - LAN-to-LAN, 235–236
 - router-based, 238
 - tunneling protocols, 231
 - L2F, 232
 - L2TP, 233
 - PPTP, 232
- VRML (Virtual Reality Modeling Language), 286
- vulnerability to WinNuke attack, testing, 220

W

- WANs, 3, 193
 - architecture, 117
 - ATM, 123–124
 - CAC, 132
 - cell transmission, 127
 - connections, 126
 - interfaces, 125–126
 - NNIs, 124
 - QoS parameters, 132
 - service classes, 128–131, 182–183

- traffic contracts, 128–129
- UPC, 133
- virtual paths, 126
- cell-switched, 113
- circuit-switched, 112
- clouds, 111
- Frame Relay, 140
 - CIR, 146
 - DE, 147
 - error handling, 149–150
 - FRADs, 140
 - LMI specifications, 150–151
 - local access loop, 140
 - PVCs, 144–145
 - QoS, 183–184
 - SVCs, 145
 - virtual circuits, 141–144, 146
- interfaces
 - NNIs, 114, 116
 - UNIs, 113
- network core elements, 118
- oversubscription, 203–204
- packet-switched, 112
- redundant links, 270
- switched access, 198
- VLAN integration, 175
- WDM (Wavelength Division Multiplexing), 47
- web programming languages, 286–287
- web servers, 44
 - proxy servers, 214
- web-hosting centers, 174
- weight attribute (BGP), 378
- weighted fair queuing, 197
- well-known attributes (BGP), 376
- well-known ports, 302
- windowing, 15
- WinNuke attack, 220
- workstations, 46
- WWW
 - DNS, 281
 - Internet protocols, 282
 - chat, 284
 - e-mail, 282
 - FTP, 283
 - Telnet, 282
 - Usenet news, 283

- peering, 287
 - NAPs, 288
 - URLs, 284–285

X-Y-Z

- X.121 addressing, 149
- xDSL, 95
 - ADSL, 96
 - architecture, 97–98
 - data rates, 98–99
 - standards, 99
- XML (eXtensible Markup Language), 287
- zones, 14