



# INDEX

## A

---

- access 17
  - to building risers 12
  - control 38
  - EOS with packet multiplexing 30
  - Ethernet 20
- add operation 36
- add/drop multiplexers (ADMs) 6
- addresses
  - MAC 46–47, 95
  - switching 45–50
  - VPN-IPv4 79
- adjacency, FA 170
- ADM, EOS function inside 24
- administration
  - fault 188
  - LMP 187
  - networks 153
  - provisioning 153
  - NFS 154
- administrative status information 185
- ADMs (add/drop multiplexers) 6
- aggregation, trunks into tunnels 130
- AIS (Alarm Indicator Signal) 188
- Alarm Indicator Signal (AIS) 188
- algorithms, path computation 174
- all-Ethernet networks, building 14
- all-to-one bundling 61
- arbitrary contiguous concatenation, 208. *See also* concatenation
- architecture
  - GMPLS 151–152
    - interfaces 167–168
    - need for 152–157
  - SONET/SDH 204–207
- Asian markets 16
- attributes
  - MEF 50–68
  - routes 78
  - site of origin 79
  - traffic
    - parameters 128
    - trunks 127
- augmented model 159. *See also* signaling
- autodiscovery 103

- availability 54
- avoiding loops 94

## B

---

- backbones
  - L3VPNs 74–81
  - scaling 69
  - traffic forwarding 80
- backdoor loops 95
- backward trunks 127
- bandwidth
  - encoding 183
  - Ethernet 9
  - requirements 27
  - RPR 35–39
  - VCAT 25–28
- benefits of link bundling 173
- BER (bit error rate) 188
- BGP (Border Gateway Protocol) 104
- bidirectional LSPs 183
- billing 153
- binding labels 137–138
- bit error rate (BER) 188
- BLECs (Building Local Exchange Carriers) 9
- block offset 109
- breadth of services 13
- breaking loops 94
- broadcast 47
- broadcast frames 57
- broadcast storms 41
- building all-Ethernet data networks 14
- Building Local Exchange Carriers (BLECs) 9
- building risers, access to 12
- bundling links 172
- Bundling service attribute 61
- bypass tunnels 149

## C

---

- cable modem termination systems (CMTSs) 35
- capabilities, interface switching descriptors 175–177
- carriers, metro Ethernet 10

CBS (Committed Burst Size) 53  
 CCAMP (Common Control and Measurement Plane) 151  
 CE (customer edge) 73  
 central office (CO) 97  
 centralized provisioning, TDM networks 153–154  
 centralized switching, EOS with 32  
 channels  
   control separation 185  
   data separation 185  
   fault handling 185–186  
 CIR (Committed Information Rate) 53  
 circuits, provisioning 153  
 class of service (CoS) parameters 55  
 CMTSs (cable modem termination systems) 35  
 CO (central office) 97  
 Committed Burst Size (CBS) 53  
 Committed Information Rate (CIR) 53  
 Common Control and Measurement Plane (CCAMP) 151  
 comparisons  
   Frame Relay 20  
   GMPLS/MPLS 189–190  
 components  
   links, 172  
   VPN 73–74  
 computation of paths 156, 174  
 concatenation  
   SONET/SDH 207–208  
   VCAT 25–28  
 configuration  
   hub-and-spoke (Gigabit Ethernet) 42  
   L2PE 113  
   PE 113  
   PW 83  
 congestion, TE 122  
 connections  
   EVC 50  
   LCAS 28  
   last-mile 20  
   metro. *See* metro  
   multipoint 20  
   VPN components 73–74  
 constrained-based routing LDP (CR-LDP) 134  
 constraint-based routing 129–130  
 contiguous standard SONET concatenation, 207. *See also* concatenation, SONET/SDH  
 control channels  
   fault handling 185

  separating 185  
 CoS (class of service) parameters 55  
 costs, overbuilding networks 12  
 CPE (customer premises equipment) 7  
 CR-LDP (constrained-based routing LDP) 134  
 cross-connect (XC) 27  
 customer edge (CE) 73  
 customer premises equipment (CPE) 7  
 customers, restrictions to number of 69

## D

---

data channels, separating 185  
 data equipment, EOS interfaces in 34  
 Data Packet Transport (DPT) 35  
 data-link connection identifier (DLCI) 142  
 Decoupled Transparent LAN Service (DTLS) 111  
 delay 54  
 delivering L3VPNs over IP 74–81  
 deployment  
   Ethernet L2 services 82  
   incumbents 13–15  
   international 15–16  
   legacy 70, 71  
   metro 5–8  
   RPR 36  
   services 35–39  
 descriptors, interface switching capability 175–177  
 detour LSPs 148  
 devices  
   CE 73  
   non-bridging as spokes 101  
   P 74  
   PE 73  
 DiffServ codepoints (DSCPs) 56  
 Digital Wrapper (DW) 181  
 discovery, resource topologies 156  
 DLCI (data-link connection identifier) 142  
 documentation. *See* MEF  
 DPT (Data Packet Transport) 35  
 drop operation 36  
 DSCPs (Diffserv codepoints) 56  
 DTLS (Decoupled Transparent LAN Service) 111  
 dual-homed MTU devices 102  
 DW (Digital Wrapper) 181  
 dynamic provisioning model 154–157

## E

---

early service providers of metro Ethernet 9–13  
 eBGP (External BGP) 103  
 edge.core 17  
 E-LAN (Ethernet LAN Service) 51  
 ELS (Ethernet Line Service) 51  
 emulation, links 83  
 encapsulation
 

- Ethernet 86
- GRE 74
- VPLS 93

 encoding
 

- bandwidth 183
- LSP types 181

 end-to-end repair method 147  
 Enterprise Systems Connection (ESCON) 24  
 EOS (extended operating system) 24
 

- interfaces 34
- packet multiplexing at access 30
- packet switching 31–33
- transport services 28–30

 ERO (EXPLICIT\_ROUTE) object 137, 142  
 ESCON (Enterprise Systems Connection) 24  
 establishing trunks, RSVP-TE 134–146  
 Ethernet 8–9
 

- access 20
- early service providers of 9–13
- Gigabit Ethernet. *See* Gigabit Ethernet
- L2VPN services 19
- MEF 50–68
- services
  - over IP/MPLS networks 81–83
  - over MPLS 85–90
  - PW 83–85
  - VPLS 90–116
- over SONET/SDH 23–25
- transport 39–42

 Ethernet LAN Service (E-LAN) 51  
 Ethernet Line Service (ELS) 51  
 Ethernet physical interface attribute 52  
 Ethernet Virtual Connection (EVC) 50  
 European markets 16  
 EVC (Ethernet Virtual Connection) 50  
 existing legacy TDM infrastructure 14  
 expanding capacity 122  
 explicit label control 184

explicit paths, establishing 135  
 EXPLICIT\_ROUTE object (ERO) 137, 142  
 extensions, RSVP 135  
 External BGP (eBGP) 103  
 extranets 75

## F

---

FA (forwarding adjacency) 170  
 facility backups 149  
 fairness, RPR 38  
 fast provisioning 9  
 fast reroute, MPLS 146–149  
 fault handling 185–186  
 fault management 188  
 FCS (frame check sequence) 85  
 FF (Fixed Filter) 139  
 FIB (Forwarding Information Base) 97  
 fiber connectivity (FICON) 24  
 fibers, SRLG 175  
 fiber-switch capable (FSC) interfaces 168  
 FICON (fiber connectivity) 24  
 fields, TLV 184  
 filters 61, 139  
 first mile 5  
 Fixed Filter (FF) 139  
 flexibility of service 11  
 flooding 47  
 FLOW\_SPEC object 145  
 formatting
 

- frames (SONET/SDH) 203
- loop-free topologies 93

 forward operation 36  
 forward trunks 127  
 forwarding
 

- packets 77
- paths 135
- tables 76
- traffic 80

 forwarding adjacency (FA) 170  
 Forwarding Information Base (FIB) 97  
 frame check sequence (FCS) 85  
 Frame Relay
 

- comparisons 20
- VPNs 105

- frames 87
  - service frame delivery attribute 56
  - SONET/SDH 203
- FSC (fiber-switch capable) interfaces 168
- full mesh
  - loop avoidance 94
  - LSPs 97
- functions
  - EOS 24
  - NSP 85
  - Q-in-Q 59

## G

- GARP (Generic Attribute Registration Protocol) 57
- generalized labels 180, 181
- Generalized MPLS. *See* GMPLS
- Generalized Payload Identifier (G-PID) 181
- Generic Attribute Registration Protocol (GARP) 57
- Generic Framing Protocol (GFP) 90
- generic path selection 128
- generic routing encapsulation (GRE) tunnels 74
- geography, variations of deployment 5
- GFP (Generic Framing Protocol) 90
- Gigabit Ethernet
  - hub-and-spoke configuration 42
  - rings 40
- global access control 38
- GMPLS (Generalized MPLS) 151–152
  - inclusion of technology-specific 186–187
  - interfaces 167–168
  - LMP 187
  - MPLS 189–190
  - need for 152–157
  - protection 188–189
  - restoration 188–189
- G-PID (Generalized Payload Identifier) 181
- granularity of bandwidth 9
- GRE (generic routing encapsulation) tunnels 74
- greenfield value proposition 11–13
- groups, SRLG 175

## H-J

- hierarchies
  - LSP 177–180
  - LSPs 170
  - VPLS 97
- hops
  - loose 143
  - strict 143
- hub-and-spoke configuration (Gigabit Ethernet) 42
- iBGP (Internal BGP) 103
- identification
  - interfaces 185
  - PW 84
- IGP (Internet Gateway Protocol) metrics 123
- ILEC (incumbent local exchange carrier) 6
- implementation of RSVP 135
- inclusion of technology-specific parameters 186–187
- incumbent local exchange carrier (ILEC) 6
- incumbents, deployment of 13–15
- infrastructure
  - signaling models 157–159
  - SONET/SDH (Ethernet over) 23–25
- infrastructure existing legacy TDM 14
- installation of physical ports 153
- interfaces
  - EOS 34
  - Frame Relay 20
  - FSC 168
  - GMPLS 167–168
  - identification 185
  - L2 20
  - L2SC 168
  - LSC 168
  - NNI 157
  - PSC 167
  - switching 175, 176, 177
  - TDM 168
  - UNI 50, 157
- Internal BGP (iBGP) 103
- international deployment 15–16
- Internet Gateway Protocol (IGP) metrics 123
- interworking with legacy deployments 70–71
- intranets 75

IP/MPLS networks  
 Ethernet services over 81–83  
 MPLS 85–90  
 PW 83–85  
 VPLS 90–116  
 IPv4, VPN-IPv4 addresses 79  
 IS-IS Traffic Engineering (IS-IS-TE) 169

jitter 55

## L

L2 (Layer 2)  
 backbones 69  
 configuring 113  
 interfaces 20  
 labels 116  
 L2SC (Layer 2 switch capable) interfaces 168  
 L2TP control connection endpoints (LCCEs) 84  
 L2VPN BGP model 106–107  
 L2VPN services 19  
 L3VPN services 74–81  
 Label Distribution Protocol (LDP) 86  
 label switched path. *See* LSP  
 label switched routers (LSRs) 135  
 LABEL\_REQUEST object 137, 141  
 labels  
 binding 137–138  
 explicit control 184  
 generalized 180–181  
 L2PE 116  
 optimizing 180  
 ranges 109  
 sets 182  
 suggested 183  
 switching  
 GMPLS 167–168  
 nonpackets 159  
 troubleshooting 184  
 WAN 115  
 LACP (Link Aggregation Control Protocol) 57  
 lambdas, SRLG 175  
 lambda-switch capable (LSC) interfaces 168

LAN (local-area network)  
 resources 18  
 VPLS 90–116  
 large enterprises (LEs) 5  
 last mile 5, 20  
 Layer 2 (L2)  
 backbones 69  
 configuring 113  
 interfaces 20  
 labels 116  
 Layer 2 switch capable (L2SC) interfaces 168  
 Layer Control Processing packets 57  
 layers, SONET/SDH 204–207  
 LCAS (Link Capacity Adjustment Scheme) 28  
 LCCEs (L2TP control connection endpoints) 84  
 LDP (Label Distribution Protocol) 86  
 BGP signaling 104  
 CR-LDP 134  
 directly connected PEs 87  
 learning  
 MAC addresses 46–47, 95  
 qualified/unqualified 97  
 legacy deployments, interworking with 70–71  
 LEs (large enterprises) 5  
 line overhead (LOH) 187  
 Link Aggregation Control Protocol (LACP) 57  
 Link Capacity Adjustment Scheme (LCAS) 28  
 Link Management Protocol (LMP) 187  
 links  
 bundling 172  
 emulating 83  
 GMPLS protection/restoration 188–189  
 protection types 174  
 unnumbered 171  
 LMP (Link Management Protocol) 187  
 local access control 38  
 local-area network. *See* LAN  
 local link identifiers 172  
 local switching, EOS with 32, 33  
 logical separation, PE 77  
 LOH (line overhead) 187  
 LOL (loss of light) 188  
 loop-free topologies, creating 93  
 loops  
 avoiding 94  
 backdoor 95  
 loose hops 143

- loss 55
- loss of light (LOL) 188
- LSP (label switched path) 80, 126, 135
  - bidirectional 183
  - encoding types 181
  - full mesh 97
  - hierarchies 170, 177–180
  - RSVP tunnels 136
  - traffic trunks
- LSRs (label switched routers) 135

## M

---

- MAC (Media Access Control)
  - addresses 95
  - learning 46–47
  - switching 45–50
  - RPR 35
- management
  - fault 188
  - LMP 187
  - networks 153
  - NFS 154
- Maximum Burst Size (MBS) 53
- Maximum Transmit Unit. *See* MTU
- MBS (Maximum Burst Size) 53
- MDUs (multidwelling units) 5
- Media Access Control. *See* MAC
- MEF (Metro Ethernet Forum) 50–63
  - example of 63–68
- messages
  - Notify 186
  - PATH 141–145
  - RESV 145
- metrics, IGP 123
- metro
  - data view of 16–17
  - deployment 5–8
  - Ethernet 8–13
  - MEF 50–68
  - services 17–19
- Metro Ethernet Forum. *See* MEF
- migration, EOS as transport services 28–30

- modification
  - routing 168–186
  - signaling 168–186
- monitoring services 69
- MP2MP (multipoint-to-multipoint) 82
- MP-BGP (multiprotocol BGP) 77
- MPLS (Multiprotocol Label Switching)
  - Ethernet over 85–90
  - fast reroute 146–149
  - GMPLS 189–190
  - TE 125–130
- MPLS L3VPN 80
- MPLS L3VPNs 75
- MSOs (multiple service operators) 35
- MTU (Maximum Transmit Unit) 87, 99–100
- MTUs (multitenant units) 5
- multicast 47
- multicast frames 56
- multidwelling units (MDUs) 5
- multiple fibers, SRLG 175
- multiple lambdas, SRLG 175
- multiple LSPs, nesting 177–180
- multiple service operators (MSOs) 35
- multiple services 26
- multiple switching capabilities 175–177
- multiple T1 (nXT1) 7
- multiple TE links, bundling 172
- multiplexing 35, 61
- multiplexing packets at access 30
- multipoint connectivity 20
- multipoint-to-multipoint (MP2MP) 82
- multiprotocol BGP (MP-BGP) 77
- multitenant units (MTUs) 5

## N

---

- Native Service Processing (NSP) 85
- need for GMPLS 152–157
- nesting multiple LSPs 177–180
- Network Layer Reachability Information (NLRI) 109
- Network Management System (NMS) 154
- networks
  - all-Ethernet 14
  - GMPLS 151–157

- IP/MPLS
    - Ethernet services over 81–83
    - over MPLS 85–90
    - over VPLS 90–116
    - PW 83–85
  - management 153
  - metro. *See* metro
  - on-net 6
  - OTN 186
  - overbuilding 12
  - reliability
    - equal-cost multipath (TE) 124
    - IGP metrics (TE) 123
    - routing (TE) 124
    - TE 121–122
    - techniques (TE) 123
    - VC overlays (TE) 124
  - ring (RPR) 35–39
  - signaling models 157–159
  - SONET/SDH 183
  - TDM
    - label switching 160–163
    - provisioning 153–154
  - troubleshooting 68–71
  - trunking 48
  - WAN labels 115
  - WDM 163
- NLRI (Network Layer Reachability Information) 109
  - NMS (Network Management System) 154
  - NNI (Network-to-Network Interface) 157
  - nodal fault handling 186
  - node pairs, LMP 187
  - non-bridging devices as spokes 101
  - non-directly connected PEs 88
  - nonpacket label switching 159
  - non-PSC networking devices 152, 157. *See also* routers; TDM
  - Notify messages 186
  - NSP (Native Service Processing) 85
  - numbers, unnumbered links 171
  - nXT1 (multiple T1) 7
- ## O
- 
- O4 189
  - objects
    - ERO 142
    - FLOW\_SPEC 145
    - LABEL\_REQUEST 137, 141
    - RRO 144
    - SENDER\_TEMPLATE 145
    - SESSION 145
    - SESSION\_ATTRIBUTE 144
  - OC12 (12 STS-1s) 26
  - one-to-one backup method 148
  - on-net networks 6
  - Open Shortest Path First for Traffic Engineering (OSPF-TE) 169
  - operations
    - packets 36
    - traffic trunks 127
  - optical cross-connects (OXC) 152
  - optical networks
    - GMPLS 151–157
    - signaling models 157–159
  - optical signal-to-noise ratio (OSNR) 188
  - optical transport network (OTN) 186
  - optimization
    - bandwidth (RPR) 35–39
    - labels 180. *See also* labels
    - routing 168. *See also* routing
    - signaling 177. *See also* signaling
    - TE 121–122
      - equal-cost multipath 124
      - IGP metrics 123
      - routing 124
      - techniques 123
      - VC overlays 124
  - OSNR (optical signal-to-noise ratio) 188
  - OSPF-TE (Open Shortest Path First for Traffic Engineering) 169
  - OTN (optical transport network) 186
  - overbuilding networks 12
  - overlays
    - models 158. *See also* signaling
    - VC 124
  - overprovisioning 122
  - OXC (optical cross-connect) 152



## P

- P (provider) 74
- P2P (point-to-point) 82
- packets
  - DPT 35
  - EOS
    - switching 31–33
    - as transport services 28–30
  - forwarding 77
  - Layer Control Processing 57
  - multiplexing at access 30
  - nonpacket label switching 159
  - operations 36
  - PW 83
  - RPR 35–39
  - switching 45–50
- packet-switch capable (PSC) interfaces 157, 167
- packet-switched network (PSN) tunnels 80
- parameters
  - GMPLD 186–187
  - MEF 50–68
  - traffic attributes 128
- PATH message 141–145
- path overhead (POH) 204
- paths
  - computation 156, 174
  - establishing 135
  - generic selection 128
  - LSP 80
  - LSPs 135
  - RSVP-TE 134–146
- pay as you grow model 11
- PE (provider edge) 73
  - configuring 113
  - LDP with directly connected 87
  - logical separation 77
  - non-directly connected 88
- Peak Information Rate (PIR) 53
- peer model 159. *See also* signaling
- penultimate hop popping 90
- performance. *See also* optimization
  - parameters 54
  - TE 121–122
    - IGP metrics 123
    - techniques 123
- PE-rs 101
- physical ports, installing 153
- PIR (Peak Information Rate) 53
- planning provisioning 153
- POH (path overhead) 204
- point-to-point (P2P) 82
- policing attribute 129
- POP (point of presence) 8
- ports
  - physical 153
  - trunks 48
- preemption attribute 128
- pricing
  - models 13
  - overbuilding networks 12
  - services 15
- priority attribute 128
- protection
  - GMPLS 188–189
  - link types 174
  - TLV fields 184
- protocols
  - BGP signaling 104
  - GFP 90
  - GMPLS 151–152, 157
  - IP 74–81
  - MAC (RPR) 35
  - modifying 168–186
  - RSVP
    - extensions 135
    - implementing 135
  - SRP 38
  - STP 50, 94
- provider (P) 74
- provider edge (PE) 73
  - configuring 113
  - LDP with directly connected 87
  - logical separation 77
  - non-directly connected 88
- provisioning
  - dynamic 154–157
  - path computation 156
  - TDM networks 153–154
- provisioning services 69
- PSC (packet-switch capable) interfaces 157, 167
- PSN (packet-switched network) tunnels 80
- PW (pseudowire) 83–85

## Q-R

---

Q-in-Q function 59  
 qualified learning 97  
  
 ranges, labels 109  
 raw mode 86  
 RD (Route Distinguisher) 79, 103  
 reach of services 13  
 RECORD\_ROUTE object (RRO) 138, 144  
 reducing TDM bandwidth 25–28  
 reference models, VPLS 90  
 regulations 5, 15  
 reliability 68–71  
 reliability of TE 121–122
 

- equal-cost multipath 124
- IGP metrics 123
- routing 124
- techniques 123
- VC overlays 124

 remote link identifiers 172  
 reordering 87  
 requirements
 

- bandwidth 27
- VPLS 91

 resilience attribute 128  
 resiliency, RPR 36  
 resilient packet ring (RPR) 35–39  
 resource attributes 129  
 resource discovery topologies 156  
 resource reservation 135, 138
 

- FF 139
- SE 140
- WF 140

 resources, LAN 18  
 restoration, GMPLS 188–189  
 restrictions to number of customers 69  
 RESV message 145  
 retail models 10  
 rings
 

- Gigabit Ethernet 40
- RPR 35–39
- steering 37
- wrapping 37

 risk, SRLG 175  
 Route Distinguisher (RD) 79, 103  
 route reflectors 105

route target (RT) 103  
 routers
 

- attributes 78
- interfaces, GMPLS 167–168
- RSVP-TE 134–146

 routing
 

- constraint-based 129–130
- CR-LDP 134
- fast reroute 146–149
- GMPLS protection/restoration 188–189
- GRE 74
- LSP 80, 170
- modifying 168–186
- TE 124

 RPR (resilient packet ring) 35–39  
 RRO (RECORD\_ROUTE) object 138, 144  
 RSVP (Resource Reservation Protocol)
 

- extensions 135
- implementing 135
- LSP tunnels 136

 RSVP-TE 134–146  
 RT (route target) 103

## S

---

scalability 9, 68–71
 

- backbones 69
- VPLS 97

 SDH (Synchronous Digital Hierarchy)
 

- architecture 204–207
- concatenation 207–208
- frame formats 203

 SDL (Simple Data Link) 24  
 SE (Shared Explicit) 139–140  
 section overhead (SOH) 187, 204  
 security 61  
 SENDER\_TEMPLATE object 145  
 separation of control/data channels 185  
 service frame delivery attribute 56  
 service multiplexing attribute 61  
 service providers, metro Ethernet 9–13  
 services 17–19
 

- data view of 16–17
- Ethernet
  - over IP/MPLS networks 81–83
  - over MPLS 85–90

- PW 83–85
- VPLS 90–116
  - flexibility of 11
  - MEF 50–68
  - monitoring 69
  - multiple 26
  - pricing 15
  - provisioning 69
  - RPR 35–39
  - time to bring up 11
  - transport (EOS) 28–30
  - VPN components 73–74
- SESSION object 145
- SESSION\_ATTRIBUTE object 138, 144
- sets, labels 182
- Shared Explicit 139–140
- shared risk link group (SRLG) 175
- signaling
  - BGP 104
  - GMPLS protection/restoration 188–189
  - models 157–159
  - modifying 168–186
  - SONET/SDH concatenation 207–208
  - VPLS 93
- Simple Data Link (SDL) 24
- site of origin 79
- small and medium-sized businesses (SMBs) 5
- small office/home office (SOHO) 5
- SMBs (small and medium-sized businesses) 5
- SOH (section overhead) 187, 204
- SOHO (small office/home office) 5
- SONET
  - architecture 204–207
  - concatenation 207–208
  - frame formats 203
- SONET/SDH
  - Ethernet over 23–25
  - label switching 162
  - LSP 161
  - LSRs 161
  - networks 183
- Spanning Tree Protocol (STP) 50, 94
- spans 5
- SPE (Synchronous Payload Envelope) 23, 203
- special reuse protocol (SRP) 38
- speed, Frame Relay speed 20
- spokes, non-bridging devices as 101

- SRLG (shared risk link group) 175
- SRP (special reuse protocol) 38
- stacking 58
- static provisioning, TDM networks 153–154
- steering, ring 37
- STP (Spanning Tree Protocol) 50, 94
- strict hops 143
- STS-1 (50 Mbps) 27
- styles, resource reservation 138. *See also* resource reservation
- subobjects 142, 144
- suggested labels 183
- support
  - VC 20
  - waveband switching 182
- swapping 60
- switches
  - EOS functions inside 24
  - GMPLS 151–152
    - need for 152–157
  - LMP 187
- switching 45–50
  - interfaces 175–177
  - labels
    - GMPLS 167–168
    - nonpackets 159
  - LSP 80
  - packets (EOS) 31–33
  - types 181
  - waveband 182
- Synchronous Payload Envelope (SPE) 23, 203

## T

---

- tables
  - forwarding 76
  - MAC learning 46–47
- tagged mode 86
- tagging VLAN 49–50, 57
- targets
  - RT 103
  - VPNs 78
- TDM (time-division multiplexing) 6
  - existing legacy infrastructure 14

- GMPLS 151–152
  - need for 152–157
- interfaces 168
- label switching 160–163
- network provisioning 153–154
- TE (traffic engineering) 121–122
  - equal-cost multipath 124
  - IGP metrics 123
  - IS-IS-TE 169
  - MPLS 125–130
  - OSPF-TE 169
  - routing 124
  - techniques 123
  - tunnels (MPLS fast reroute) 146–149
  - VC overlays 124
- time to bring up service 11
- time-division multiplexing. *See* TDM
- TLS (Transparent LAN Service) 81
- TLV (type length value) 97, 184
- TOH (transport overhead) 204
- topologies
  - loop-free 93
  - resource discovery 156
- traffic
  - forwarding 80
  - parameters 52, 128
  - trunks 135
    - attributes/operations 127
    - comparing to LSPs 126
- traffic engineering. *See* TE
- translation, VLAN 60
- Transparent LAN Service (TLS) 81
- transport, Ethernet 39–42
- transport overhead (TOH) 204
- transport services, EOS 28–30
- troubleshooting 80, 184
  - congestion 122
  - fault management 188
  - LCAS 28
  - MPLS L3VPN 80
  - networks 68–71
  - Notify messages 186
- trunks, 48
  - RSVP-TE 134–146
  - traffic
    - attributes/operations 127
    - comparing to LSPs 126

- tunnels
  - aggregation 130
  - bypass 149
  - GRE 74
  - LSP hierarchies 177–180
  - MPLS fast reroute 146–149
  - PSN 80
  - RSVP LSP 136
- type length value (TLV) 97, 184
- types
  - of link protection 174
  - of LSP encoding 181
  - of PW 84
  - of service providers 5
  - of VC 88
  - switching 181

---

## U

- U.S. incumbent landscape 13–15
- UNI (User-to-Network Interface) 50, 157
- unicast frames 56
- unnumbered links 171
- unqualified learning 97
- untagged Ethernet packets 49–50
- User-to-Network Interface (UNI) 50, 157

---

## V

- values, TLV fields 184
- variations of deployment 5
- VC (virtual circuit)
  - overlays 124
  - support 20
  - types 88
- VCAT (virtual concatenation) 25–28
- VCI (virtual connection identifier) 142
- virtual circuit. *See* VC
- virtual path identifier (VPI) 142
- Virtual Private LAN (VPLS) 90–116
- virtual router forwarding (VRF) 76
- VLAN (virtual LAN)
  - switching 45–50
  - tagging 49–50, 57
- VLAN Tag Preservation 58

- VLAN Tag Translation or Swapping 60
- VPI (virtual path identifier) 142
- VPLS (Virtual Private LAN) 90–116
- VPN (virtual private network)
  - components 73–74
  - Frame Relay 105
  - L2VPN services 19
  - L3VPNs over IP 74–81
  - of origin 79
  - target 78
- VPN-IPv4 addresses 79
- VRF (virtual router forwarding) 76

## W-X

---

- WAN (wid-area network) labels 115
- waveband switching 182
- WDM (wavelength division
  - multiplexing) 35, 163
- WF (Wildcard Filter) 139, 140
- wholesale models 10
- wrapping, ring 37

  

- XC (cross-connect) 27