



# INDEX

## Numerics

- 100-Mbps Ethernet 71
- 10BASE2 72
- 10-Gigabit Ethernet 71, 74
- 32-bit numbers 241-244

## A

- AAA (authentication, authorization, and accounting) 53
- absorption 397
- accelerated profits, optical networks 383
- acceleration, 99
- access
  - AAA servers 53
  - cable modem 347-348
    - adding 350
    - OSI model 350-351
  - CSMA/CD
    - Ethernets 75-77
  - dialup 323-327
  - servers 86
  - VPNs 100
- acknowledgments (TCP) 218-219
- adaptability, optical networks 384
- add/drop multiplexers (ADMs) 410
  - adding
    - bridges 155, 156
    - cable modems 350
    - DSL 344
- addresses
  - CIDR 251
  - Class A 242
  - Class B 242, 268-273
  - Class C 243, 264-268
  - Class D 243
  - Class E 243-244
  - directed broadcast 267, 274-275
  - DMA 10
  - hosts 257, 265
  - I/O 10, 333
  - IP 239, 240
    - classes 241-244
    - host ID 240-241
- network ID 240
- private 247-248
- public 248-251
- RARP 230-231
- reserved 244-246
- subnet masks 261
- Layer 3
  - multilayer switches 50
  - routers 49
- MAC 15
  - ARP 229
  - bridges, 46. *See also bridges*
  - establishing VLAN memberships 194
  - filtering 47
  - flooding 47
  - root bridges 171
- networks 262-264
- subnetworks 258
  - fields, 259-261
  - identifying 274, 275
- tables 165
- administration
  - networks 262-264
  - traffic 283-284
  - VLAN 193
- administrative distance routing 287
- ADMs (add/drop multiplexers) 410
- ADSL (Asymmetric Digital Subscriber Line) 141, 339. *See also DSL*
- advantages
  - of cable modems 350
  - of DSL 344
  - of DWDM 411-412
- advertisements 295-296
  - hold-down timers 294
  - LSAs 295
- algorithms
  - Dijkstra Shortest Path First 295
  - routing 285-286
- allocating IPv4 addresses 248
- American National Standards Institute (ANSI) 341, 405
- amplifiers
  - EDFAs 400-401
  - OAs 400-401

- analog modems 331-332
  - external 333
  - internal 332
  - PC card 334
  - standards 334-336
- angular separation 395
- ANSI (American National Standards Institute) 341, 405
- AppleTalk Session Protocol (ASP) 31
- applications
  - cable modems 352
  - Layer 4 212
  - Layer 4 segmentation 211
  - TCP/IP 36, 205-206
- application-specific integrated circuits (ASICs) 156, 178
- APS (automatic protection switching) 407
- architecture
  - in-building WLANs 371
  - ISA 5, 332
- ARP (Address Resolution Protocol) 229
- ASICs (application-specific integrated circuits) 156, 178
- ASP (AppleTalk Session Protocol) 31
- assignment of TCP/UDP port numbers 216
- Asymmetric Digital Subscriber Line (ADSL) 141, 339. *See also* DSL
  - ATM (Asynchronous Transfer Mode) 49, 75, 85
  - attachment unit interface (AUI) connector 125
  - attenuation of fiber cables 398
  - AUI (attachment unit interface) connectors 125
  - authentication
    - HDLC 327, 328
    - PPP 326
      - wireless 365
  - authentication, authorization, and accounting (AAA) 53
  - automatic protection switching (APS) 407
  - autonomous systems 291, 302
  - AUX ports 145
  - availability of SANs 97
- backbones 81
- backplanes 8, 156
- back-to-back serial connections 138
- bandwidth 299
- cable modems 347-348
  - adding 350
  - OSI model 350-351
- congestion 158
- domains 45
- DSL 339
  - adding 344
  - encapsulation 343
  - protocols 343
  - standards 341-343
  - types 340
- hubs 152-153
- MANs 95
- optical networks 383-384
  - light 386
  - reflection/refraction 388-390
  - transmission systems 384-388
- routing 286
- VLAN 188-192
- WAN 89
  - router serial connections 137-138
  - serial connections 136-137
- Basic Rate Interface (BRI) 135, 324
- basic service area (BSA) 373
- bending
  - macrobending 396-397
  - microbending 397
- benefits of VLAN 191, 192
- BGP (Border Gateway Protocol) 302
- bidirectional line-switched rings (BLSR) 405-407
- binary conversions 13
  - binary-to-decimal conversions 14
  - binary-to-hex conversions 14-17
- bits 10-13, 264, 269
- bits per second (bps) 394
- blocking states 172
- BLSR (bidirectional line-switched rings) 405-407
- BNC (British Naval Connector) 111
- BOOTP 231
- borrowing bits 264, 269
- boundaries, removing 190
- bps (bits per second) 394
- branch offices 27
- BRI (Basic Rate Interface) 135-140, 324

## B

---

- backbones 81
- backplanes 8, 156

bridges 23, 46-47  
 root 171  
 shared LAN technologies 155  
 wireless 369, 370  
 British Naval Connector (BNC) 111  
 broad coverage, optical networks 383  
 broadcasts  
   addresses 244-245  
   domains 47  
   RARP 230-231  
   subnetworks 256  
   transmissions 154  
   wireless RF bands 360-361  
 BSA (basic service area) 373  
 buffering 156  
 building address tables 165  
 building-to-building WLANs 375-376  
 bus topologies 5, 59  
 business applications, optical networks 383  
 byte-interleaved multiplexing scheme 408-409  
 bytes 10-13

## C

cable modems 347-348  
 adding 350  
 connections 142-143  
 OSI model 350-351  
 cables 21, 107  
   campus LANs 122-123, 131  
   coaxial 110-112  
   connectivity devices 23  
   console connections 144-145  
   Ethernet requirements 123-125  
   fiber optic 112-114, 393  
     attenuation 398  
     filters 399-400  
     geometry 394-398  
     OAs 400-401  
     types of 393-394  
   LANs 121  
   rollover 144-145  
   routers  
     cable 142-143

DSL 141-142  
 STP 109-110  
 UTP 107-108, 127-131  
 WAN 135  
 cache tables (ARP) 229  
 calculations  
   Class C subnets 266  
   subnetworks 263, 271  
 call routes 84  
 call setup services (WAN) 84  
 campus LANs  
   cabling 131  
   Ethernets 122-123  
 cancellation effects 107  
 CAP (carrierless amplitude phase) 342  
 capacity  
   of DWDM 409-412  
   of optical networks 383  
   of WAN 89  
 carrier sense multiple access collision detect (CSMA/CD) 75  
 carrierless amplitude phase (CAP) 342  
 CD-ROM 5  
 cells, switching 83  
 central office (CO) 83, 87, 339  
 central processing unit (CPU) 5  
 CHAP (Challenge Handshake Authentication Protocol) 323, 327  
 Cheapernets 111  
 chipping sequences 363  
 CIDR (classless interdomain routing) 248-251  
 circuit-switched WAN technologies 83  
 Cisco 827 ADSL Router 340  
 Cisco AS5400 Series Universal Access Server 50  
 Cisco AS5400 Series Universal Gateway 50  
 Cisco Internetworking Operating Software. *See* IOS  
 Cisco ONS 15454 Dense Wavelength-Division Multiplexing (DWDM) Optical Network System 52  
 Cisco SN 5420 Storage Router 98  
 cladding, fiber optic cables 113  
 Class A addresses 242  
 Class B addresses 242, 268-273  
 Class B Subnet fields 262  
 Class C addresses 243, 264-268  
 Class D addresses 243  
 Class E addresses 243-244

- classes, IP addresses 241-246
- classful addressing 241
- classless interdomain routing (CIDR) 248-251
- CLI (command-line interface) 193
- clients 22, 96-97
- CLNP (Connectionless Network Protocol) 300
- CLNS (Connectionless Network Service) 300
- clocking 137
- CN (content network) 98, 99
- CO (central office) 83, 87, 339
- coaxial cables 21, 110-112, 143
- codec 332
- collisions 45
  - congestion 158
  - hubs 153
  - microsegmentation 163-164
- colors 386
- COM (common equipment) 145
- command-line interface (CLI) 193
- commands, ping 229
- common equipment (COM) 145
- communication 32, 384-390
  - encapsulation 32-33
  - IP addressing 239-240
    - classes 241-244
    - host ID 240-241
    - network ID 240
    - private 247-248
    - public 248-251
    - reserved 244-246
  - peer-to-peer 34
  - TCP 203
  - TCP/IP 36
    - application layer 36
    - Internet layer 37
    - network access layer 37
    - stacks 204, 205
    - transport layer 37
  - VLAN 192, 195-196
  - wireless 357-360
    - LANs 369-376
    - RF bands 360-361
    - security 364-365
    - signals 358-360
    - SS 361-362
- comparisons
  - Ethernet media requirements 124
  - laptops/PCs 9-10
  - media 116
  - OSI/TCP/IP 37-38
  - routed/routing protocols 281
  - topologies 57
- compatibility of OSI 28-29
  - application layer 30
  - data link layer 31
  - network layer 31
  - physical layer 31
  - presentation layer 30
  - session layer 30
  - transport layer 31
- components
  - fiber-optic cable 393-394
  - networks 26
    - branch offices 27
    - home offices 27
    - mobile users 27
  - PC 5-8
  - PCI 5
  - VLAN 192
- composite metrics 298
- computing subnetworks 263
- concentrators, Ethernets 152
- configuration, 188-192
  - console connections 144-145
  - multicell 373
  - point-to-multipoint 376
  - point-to-point 376
  - router subnetworks 257
  - single-cell 373
  - subnetworks 262-264
  - VLAN 188-192
- conflicts, SANs 96-97
- congestion 158
- Connectionless Network Protocol (CLNP) 300
- Connectionless Network Service (CLNS) 300
- connections
  - ADSL 141-142
  - analog modems 331-332
    - external 333
    - internal 332-336
  - cable modems 347-348
    - adding 350

- OSI model 350-351
- campus LANs 122-123, 131
- console 144-145
- devices 23
- fiber-optic cables 393
  - attenuation 398
  - filters 399-400
  - geometry 394, 398
  - OAs 400-401
  - types of 393-394
- FICON 412
- full/partial-mesh topologies 62-63
- jumpers 333
- LAN
  - Ethernets 69
  - LLC 70-71
  - MAC 70
  - switches 164-166
- Layer 4 211
  - flow control 212
  - functions 211-212
  - protocols 213-217
  - TCP 217-221
- MANs 95
- media 21, 125-126
- NICs 10
- OSI 28-29
  - application layer 30
  - data link layer 31
  - network layer 31
  - physical layer 31
  - presentation layer 30
  - session layer 30
  - transport layer 31
- PCI 5
- requirements 123-125
- routers
  - cable 142-143
  - DSL 141-142
  - ISDN BRI 139-140
- serial
  - routers (WAN) 137-138
  - WAN 136-137
- subnetworks 255-261
- TCP 217-221
- trunking 195-197
- VLAN 188-192
- VPNs 100-101
- WAN 83, 135
- WLANS 369-370
- connectivity, VLAN 195-196
- connectors
  - AUI 125
  - BNC 111
  - F 143
  - fiber optic cables 114
  - losses 395
  - RJ-45 125
- console connections, configuring 144-145
- content network (CN) 98-99
- convergence 294
  - EIGRP 299
  - hold-down timers 294
  - routing 285
- conversions
  - binary-to-decimal 14
  - binary-to-hex 14-17
  - decimal-to-binary 13
  - E/O/E 410
  - GBIC 74
  - hex-to-binary 17
  - optical networks 385
- converters, GBIC 126
- cores, fiber optic cables 113
- cost
  - of routing 286
  - of SANs 97
- CPE (customer premises equipment) 87
- CPU (central processing unit) 5
- crossover cables, UTP implementation 129
- crosstalk 107
- CSMA/CD (carrier sense multiple access collision detect) 75-77
- customer premises equipment (CPE) 87
- customizing
  - serial connections 136-137
  - subnet masks
    - Class B addresses 268-273
    - Class C addresses 264-268
- cut-through switching 168

**D**

dark currents 385  
data communication equipment (DCE) 86-88, 137  
data link layer  
    cable modems 351  
    devices 45  
        bridges 46-47  
        NICs 45  
        switches 48  
    WAN 91  
data terminal equipment (DTE) 86-88  
data transmission, DWDM 410  
database servers 22  
data-buffering capabilities 156  
datagrams  
    IP 226-229  
    Protocol field 227  
data-link connection identifiers (DLCIs) 84  
DAVIC (Digital Audio Video Control) 341  
dB/km (decibels per kilometer) 399  
DCE (data communication equipment) 86-88, 137  
decibels per kilometer (dB/km) 399  
decimal conversions 14  
decimal-to-binary conversions 13  
dedicated communication  
    Layer 2 switching devices 177-179  
    Layer 3 switching devices 179  
    Layer 4 switching devices 181-183  
dedicated connections 83  
dedicated networks 96-97  
de-encapsulation 33, 280  
delay  
    propagation 156  
    routing 286  
deleting loops 171  
delivery, CN 98-99  
demarc points 87  
dense wavelength-division multiplexing (DWDM)  
    405  
density, ports 156  
design of flat networks 179  
designation ports 171  
Destination Service Access Point (DSAP) 70  
detectors 385  
determining optimal routing paths 282

devices  
    connectivity 23  
    DSL 50, 51  
    Layer 1 43  
        hubs 44  
        repeaters 43  
    Layer 2 45  
        bridges 46-47  
        NICs 45  
        switches 48  
    Layer 3 49  
        multilayer switches 50  
        routers 49  
    LEDs 388-390  
    multilayer switching 177  
        Layer 2 177-179  
        Layer 3 179  
        Layer 4 181-183  
    NT1 139  
    optical 50-51  
    PC components 5-8  
    TCP communication 203  
    trunking 197  
    voice 50-51  
WAN 82, 85  
    access servers 86  
    CSUs/DSUs 86  
    modems 86  
    routers 85  
    switches 85  
DHCP (Dynamic Host Configuration Protocol) 225,  
    231, 351  
dialup access 323  
    CHAP 327  
    HDLC 327-328  
    ISDN 323-324  
    PAP 326  
    PPP 324-326  
Digital Audio Video Council (DAVIC) 341  
digital networks, SDH 95  
digital subscriber line access multiplexer (DSLAM)  
    51  
digital subscriber line. *See* DSL  
digits 15. *See also* symbols  
Dijkstra Shortest Path First (SPF) algorithm 295  
diodes (LEDs) 387  
direct memory address (DMA) 10

directed broadcast addresses 245, 267, 274-275  
 direct-sequence spread spectrum (DSSS) 357  
 disabled states 172  
 discrete multitone (DMT) 342  
 dispersion 394  
 distance effects on wireless signals 359  
 distance-vector protocols 293-294  
 distribution of OSPF 299-300  
 DLCIs (data-link connection identifiers) 84  
 DMA (direct memory address) 10  
 DMT (discrete multitone) 342  
 domains  
     bandwidth 45  
     broadcasts 47  
     collisions 45  
 dotted-decimal notations 241  
 downstream rates 340, 348  
 drives  
     CD-ROM 5  
     floppy disks 6  
     hard disk 6  
 DSAP (Destination Service Access Point) 70  
 DSL (digital subscriber line) 27, 339  
     adding 344  
     devices 50-51  
     encapsulation 343  
     protocols 343  
     router connections 141-142  
     standards 341-343  
     types 340  
 DSL access multiplexers (DSLAMs) 339  
 DSLAM (digital subscriber line access multiplexer) 51, 339  
 DSSS (direct-sequence spread spectrum) 357, 362  
 DTE (data terminal equipment) 86-88, 137  
 DWDM (dense wavelength-division multiplexing) 405-412  
     advantages of 411-412  
     long-haul 412  
     metro 412  
 Dynamic Host Configuration Protocol (DHCP) 225, 231, 351  
 dynamic link-state routing protocols 301  
 dynamic provisioning 411

## E

E/O/E (electrical/optical/electrical) conversion 410  
 echo requests/replies 229  
 ECSA (Exchange Carriers Standards Association) 405  
 EDFA (erbium-doped fiber amplifiers) 400-401  
 effects  
     of distance on wireless signals 359  
     of noise on wireless signals 360  
 EGP (exterior gateway protocols) 291-292  
 EIGRP (Enhanced Interior Gateway Routing Protocol) 182, 299  
 election, root bridges 171  
 electrical/optical/electrical (E/O/E) conversion 410  
 electromagnetic interference (EMI) 108  
 e-mail  
     sending 25  
     TCP/IP stacks 204-205  
 encapsulation 32, 280  
     DSL 343  
     HDLC 327-328  
     PPP 325  
 encryption 364-365  
 end-face separation 395  
 endpoints, Layer 4 211-212  
 end-to-end flexibility, optical networks 384  
 end-to-end transport services 211  
 engines, ASIC 180  
 Enhanced Interior Gateway Routing Protocol (EIGRP) 182  
 Enterprise System Connection (ESCON) 411  
 EPROM (erasable programmable read-only memory) 8  
 erbium-doped fiber amplifiers (EDFAs) 400-401  
 ESCON (Enterprise System Connection) 411  
 establishing VLAN memberships 193-195  
 Ethernets 71  
     10-Gigabit Ethernets 74  
     campus LAN 122-123  
     concentrators 152  
     CSMA/CD 75-77  
     Fast Ethernet 72-73  
     GBIC 126  
     Gigabit Ethernets 73-74  
     IEEE 802.3 72  
     LAN 69

LLC 70-71  
 MAC 70  
 media requirements 123-125  
 repeaters 152  
 star topologies 59  
 transmissions 77  
 VLAN 197

ETSI (European Telecommunications Standards Institute) 341

Exchange Carriers Standards Association (ECSA) 405

expansion cards 5

expansion slots 5

extended service areas 373

extended star topologies, 59. *See also* star topologies

exterior gateway protocols (EGPs) 291-292

external analog modems 333

extranets 99-100

## F

F connectors 143

Fast Ethernet 71-73

fastest paths, selecting 298

FCS (frame check sequence) 32

FDDI (Fiber Distributed Data Interface) 49

FHSS (frequency-hopping spread spectrum) 357, 362

fiber connectivity (FICON) 412

Fiber Distributed Data Interface (FDDI) 49

fiber optic cables 21, 112-114, 393

- attenuation 398
- filters 399-400
- geometry 394, 398
- OAs 400-401
- types of 393-394

FICON (fiber connectivity) 412

fields

- IP datagrams 226-227
- Protocol 227
- TCP 213-214
- UDP 214

File Transfer Protocol (FTP) 25, 183, 351

files

- servers 22
- TCP/IP stacks 204-205

filling routing tables 283-284

filters

- fiber cables 399-400
- MAC addresses 47

firewalls 52

flat network designs 179

flexibility 285, 411

flooding

- LSAs 295
- MAC addresses 47
- messages 166
- ports 165

floppy disk drives 6

flow control

- Layer 4 212
- TC 220-221

formatting

- IP datagrams 226-227
- TCP headers 213-214
- UDP headers 214

formulas, calculating subnetworks 263

forwarding states 172

fragment-free switching 169

frame check sequence (FCS) 32

Frame Relay 84

frequency-hopping spread spectrum (FHSS) 357

FTP (File Transfer Protocol) 25, 183, 351

full-duplex communication

- Layer 2 switching devices 177-179
- Layer 3 switching devices 179
- Layer 4 switching devices 181-183

full-duplex transmissions 77, 167

full-mesh topologies 62-63

functions

- Layer 4 211
- routing 279-280

## G

gateways 50-51

GBIC (Gigabit Interface Converter) 74, 126

geometry, fiber cables 394, 398

GHz (gigahertz) 12

Gigabit Ethernet 71-74

Gigabit Interface Converter (GBIC) 74, 126

gigahertz (GHz) 12

graphical user interface (GUI) 193

groups, VLAN 188-192

guarantee of loop-free path selection 302

## H

half-duplex transmissions 77  
 hard disk drives 6  
 hardware, campus LANs 122-123  
 HDLC (High-Level Data Link Control) 91, 323-328  
 headers  
   de-encapsulation 33  
   encapsulation 32  
   TCP 181, 213-214  
   UDP 181, 214  
 hertz (Hz) 12  
 hexadecimal conversions 14-17  
 hex-to-binary conversions 17  
 hierarchies  
   SDH 95  
   SONET 406-409  
 High-Level Data Link Control (HDLC) 91, 323-328  
 high-level signals 385  
 high-speed backplanes 156  
 high-speed cable connections 142-143  
 hold-down timers 294  
 home offices 27  
 hop counts  
   RIP 297  
   routing 286  
 host addresses, subnetworks 257  
 Host field, computing usable subnetworks 263  
 host ID 239-241  
 hosts  
   addresses 265  
   classes of IP addresses 246  
   Layer 4 211  
     connecting TCP 217-221  
     flow control 212  
     functions 211-212  
     protocols 213-217  
   ranges 266, 271  
   TCP/IP 228-229  
 hot-swappable input/output devices (GBIC) 126  
 HTML (Hypertext Markup Language) 24  
 HTTP (Hypertext Transfer Protocol) 24, 352  
 hubs 23, 44  
   collisions 153  
   console connections 144-145  
   shared LAN technologies 152-153  
   transmissions 154

hybrid protocols 296, 299  
 Hypertext Markup Language (HTML) 24  
 Hypertext Transfer Protocol (HTTP) 24, 352  
 Hz (hertz) 12

## I

I/O (input/output) 10, 333  
 ICMP (Internet Control Management Protocol) 228-229  
 identification  
   subnet addresses 274-275  
   VLAN 197  
 IEEE (Institute of Electrical and Electronic Engineers) 70  
   802.1Q 197  
   802.3 72  
   802.3u 73  
 IGP (interior gateway protocols) 291-292  
 IGRP (Interior Gateway Routing Protocol) 287, 293, 298  
 IMAP (Internet Message Access Protocol) 25  
 implementation  
   campus LANs 122-123  
   Ethernet media requirements 123-125  
   HDLC 327-328  
   ICMP 228-229  
   LAN  
     Ethernet 71  
     physical layers 121  
   physical layers 125  
   serial connections 138  
   UTP 127-131  
   VLAN  
     components 192  
     establishing memberships 193-195  
   WAN physical layer 135  
   WLAN 372  
   in-building WLANs 370-375  
   index of refraction (IOR) 390  
   Industry-Standard Architecture (ISA) 5, 332  
   infrared (IR) 115  
   infrastructures  
     CN 98-99  
     switches 158  
   initiation of RARP 230-231

- input/output (I/O) 10, 333  
 installation of NICs 10  
 Institute of Electrical and Electronic Engineers. *See*  
     IEEE  
 integrated IS-IS 301  
 Integrated Services Digital Network (ISDN) 82, 323  
 interconnections 96. *See also* connections  
 interfaces 8
  - address tables 165
  - AUI connectors 125
  - BRI 135, 324
  - CLI 193
  - FDDI 49
  - GBIC 74, 126
  - GUI 193
  - ISDN BRI connections 139-140
  - modular serial port 139
  - NICs 9-10
  - PRI 324
  - routing 279-280
  - WAN 89
 interior gateway protocol (IGP) 291-292  
 Interior Gateway Routing Protocol (IGRP) 287, 293, 298  
 Intermediate System-to-Intermediate System (IS-IS) 182  
 internal analog modems 332  
 International Organization for Standardization (ISO) 323  
 International Telecommunications Union (ITU-T) 334, 341  
 Internet
  - layer 37, 225-226
  - WAN 81
 Internet Message Access Protocol (IMAP) 25  
 Internet Network Information Center (InterNIC) 247  
 Internet Protocol. *See* IP  
 Internet service provider. *See* ISP  
 Internetwork Packet Exchange. *See* IPX  
 internetworks
  - OSPF 299-300
  - transporting packets 282
 InterNIC (Internet Network Information Center) 247  
 interoperability
  - analog modems 334-336
  - VLAN 192
 interrupt request (IRQ) 10, 333  
 Inter-Switch Link (ISL) 197  
 inter-VLAN communication 192  
 inter-VLAN connectivity 195-196  
 intranets 99-100  
 IOR (index of refraction) 390  
 IOS (Cisco Internetworking Operating Software) 22  
 IP (Internet Protocol) 31, 205
  - addressing 239-240
  - classes 241-244
  - host ID 240-241
  - multilayer switches 50
  - network ID 240
  - private 247-248
  - public 248-251
  - RARP 230-231
  - reserved 244-246
  - subnet masks 261
  - datagrams 226-229
 IPv4 (Internet Protocol version 4) 248  
 IPv6 (Internet Protocol version 6) 248  
 IPX (Internetwork Packet Exchange) 31, 180  
 IR (infrared) 115  
 IRQ (interrupt request line) 10, 333  
 ISA (Industry-Standard Architecture) 332  
 ISDN (Integrated Services Digital Network) 82, 323-324
  - BRI 139-140
  - dialup access 323-324
  - WAN 135
 IS-IS (Intermediate System-to-Intermediate System) 182, 300-301  
 ISL (Inter-Switch Link) 197  
 ISO (International Organization for Standardization) 323  
 ISP (Internet service provider) 81, 248  
 ITU-T (International Telecommunications Union) 334, 341

**J**

- 
- jumpers, modems 333

# K

- Kb (kilobit) 12
- KB (kilobyte) 10-12
- kbps (kilobits per second) 12
- kBps (kilobytes per second) 12

# L

- lambdas, fiber-optic cables 399-400
- LAN (local-area network) 23
  - 10-Gigabit Ethernet 75
  - bridges 46-47
  - campus, 131
  - Ethernets 69, 71
    - LLC 70-71
    - MAC 70
  - intranets 99-100
  - NICs 9-10
  - physical layer 121
  - ring topologies 61
  - shared technologies 151-152, 158
    - bridges 155
    - hubs 152-153
    - switches 156-157
  - sharing 187-188
  - star topologies 59
  - switches 48, 163
    - full-duplex transmissions 167
    - microsegmentation 163-164
    - modes 167-168
    - operations 164-166
    - STP 169-172
  - VLAN 187
- LAPB (Link Access Procedure, Balanced) 91
- LAPD (Link Access Procedure on the D channel) 91
- LAPF (Link Access Procedure to Frame mode
  - bearer services) 91
- laptops 9, 10, 372
- last mile loops 87
- Layer 1
  - devices 43
  - hubs 44
  - repeaters 43
- DSL 343
- WAN 89

## Layer 2

- devices 45
  - bridges 46-47
  - NICs 45
  - switches 48
- switching devices 177-179
- WAN 91

## Layer 3

- devices 49
  - multilayer switches 50
  - routers 49
- switching devices 179
- TCP/IP stacks 204-205
- VLAN 195

## Layer 4 211

- flow control 212
- functions 211-212
- Protocol field 227
- protocols 213-217
- switching devices 181-183
- TCP 217-221
- TCP/IP stacks 204-205

## layers 29

- application 30, 36
- cable modems 350-351
- data link 31, 91
- de-encapsulation 33
- encapsulation 32
- Internet 225-226
- network 31
- network access 37
- PDUs 34
- physical 31
  - implementations 125
  - WAN 89, 135

## presentation 30

- session 30
- TCP/IP 37, 38
- transport 31, 211
  - connecting TCP 217-221
  - flow control 212
  - functions 211-212
  - Protocol field 227
  - protocols 213-217
  - TCP/IP 37

- LEAP (lightweight EAP) 365
- learning states 172

## M

---

- leased lines 83
  - LEDs (light-emitting devices) 388-390
  - light 386
  - light-emitting devices (LEDs) 388-390
  - lightweight EAP (LEAP) 365
  - limitations
    - of cable modems 350
    - of DSL 344
    - of RIP 297
    - of shared LANs 188
  - line overhead (LOH) 406
  - linear bus topologies 23
  - Link Access Procedure, Balanced (LAPB) 91
  - line-terminating equipment (LTE) 406
  - Link Access Procedure on the D channel (LAPD) 91
  - Link Access Procedures to Frame mode bearer services (LAPF) 91
  - link-state protocols 295
  - listening states 172
  - LLC (Logical Link Control) 70-71
  - load, routing 286
  - local ARP 229
  - local loops 87
  - local-area network. *See* LAN
  - Logical Link Control. *See* LLC
  - logical ring topologies 61
  - logical topologies 23, 57
  - LOH (line overhead) 406
  - long-haul DWDM 412
  - loops
    - BGP 302
    - deleting 171
    - local 87
    - RIP 297
    - routing 294
    - split horizons 294
  - loss factors, fiber-optic cables 395
  - low overhead, routing 285
  - lower bandwidth, EIGRP 299
  - low-level signals 385
  - LSAs (link-state advertisements) 295
  - LTE (line-terminating equipment) 406
- 
- MAC (Media Access Control)** 15, 70
    - 10-Gigabit Ethernet 75
    - addresses
      - ARP 229
      - bridges 46
      - building tables 165
      - establishing VLAN memberships 194
      - filtering 47
      - flooding 47
      - NICs 45
      - root bridges 171
    - Macintosh OS 22
    - macrobending 396-397
    - maintenance, routing tables 283-284
    - MAN (metropolitan-area network) 23, 75, 95
    - management
      - console connections 144-145
      - networks 262-264
      - SANs 97
      - traffic 283-284
      - VLAN 193
    - masks
      - subnet 258-261
      - subnetworks 264-273
      - VLSM 298
    - Mb (megabit) 12
    - MB (megabyte) 10, 12
    - Mbps (megabits per second) 12
    - MBps (megabytes per second) 12
    - MCNS (Multimedia Cable Network System Partners) 350
    - measurements 10-13
    - media 21, 107
      - 10-Gigabit Ethernets 74
      - coaxial cables 110-112
      - comparing 116
      - connections 125-126
      - fiber optic cables 112-114
      - Gigabit Ethernets 73-74
      - requirements 123-125
      - STP 109-110
      - UTP 107-108
      - wireless 115
    - Media Access Control. *See* MAC
    - megabits (Mb), 12

- megabits per second (Mbps) 12
- megabyte (MB) 10, 12
- megabytes per second (MBps) 12
- megahertz (MHz) 12
- memberships, VLAN 193-195
- memory 6
  - buffers 156
  - DMS 10
- mesh topologies 23
- messages
  - flooding 166
  - ICMP 228-229
  - routing 284
  - TCP communication 203
- metrics 279-280, 298
- metro DWDM 412
- metropolitan-area network. *See* MAN
- MHz (megahertz) 12
- microbending 397
- microprocessors 6
- microsegmentation (LAN) 163-164
- midspan meet 405
- mobile users 27
- models
  - OSI 28-29
    - application layer 30
    - data link layer 31
    - network layer 31
    - physical layer 31
    - presentation layer 30
    - session layer 30
    - transport layer 31
  - TCP/IP 36
    - application layer 36
    - comparing OSI 37-38
    - Internet layer 37
    - network access layer 37
    - transport layer 37
- modems. *See also* connections
  - analog 331-332
    - external 333
    - internal 332
    - standard 334-336
  - cable 27, 347-348
    - adding 350
  - OSI model 350-351
- DSL 339
  - adding 344
  - encapsulation 343
  - protocols 343
  - standards 341-343
  - types 340
- PC card 334
- WAN 86
- modes, LAN switches 167-168
- modular serial port interfaces 139
- modulation
  - SS 361, 362
  - wireless 359
- motherboards 6
- mouse ports 8
- multicast addresses 243
- multicast transmissions 154
- multicell configurations 373
- multilayer switches 50, 177
  - Layer 2 177-179
  - Layer 3 179
  - Layer 4 181-183
- Multimedia Cable Network System Partners (MCNS) 350
- multimode fiber optic cable 113, 394
- multiple devices, trunking 197
- multiple networks
  - masks 258-261
  - subnetworks 255-258
- multiplexing
  - ADMs 410
  - DWDM 405, 409-412
  - OADMs 400
  - SONET 408-409
  - TDM 84
  - WDM 387

## N

- 
- NAY (Network Address Translation) 248
  - NCPs (network control protocols) 325
  - network access layer, TCP/IP 37
  - Network Address Translation (NAT) 248
  - network control protocols (NCPs) 325
  - Network File System. *See* NFS
  - network ID 239-240

network layer 351  
network operating system (NOS) 22  
Network Termination 1 (NT1) 139  
networks 21, 88  
    AAA servers 53  
    addresses 244, 262-264  
    applications 24-25  
    building-to-building WLANs 375-376  
    bus topologies 59  
    campus LANs 122-123  
    cards 8  
    CHAP 327  
    clients 22  
    CN 98-99  
    communication 32  
        de-encapsulation 33  
        encapsulation 32  
        peer-to-peer 34  
        TCP/IP 36-37  
    congestion 158  
    connectivity devices 23  
    Ethernets 71  
        LAN 69  
        LLC 70-71  
        MAC 70  
    firewalls 52  
    flat designs 179  
    in-building WLANs 370-375  
    IOS 22  
    IP addressing 239-240  
        classes 241-244  
        host ID 240-241  
        network ID 240  
        private 247-248  
        public 248-251  
        reserved 244-246  
    ISDN 82  
        dialup access 323-324  
        WAN 135  
    LAN 23  
        bridges 155  
        hubs 152-153  
        microsegmentation 163-164  
        shared-technologies 151-152, 158  
        switches 156-157  
        wireless communications 369-376  
    logical topologies 23  
    MAN 23, 95

media 21, 107  
    coaxial cables 110-112  
    comparing 116  
    fiber-optic cables 112-114  
    STP 109-110  
    UTP 107-108  
    wireless 115  
NIC 9-10, 21  
NOS 22  
optical 384  
    business applications 383  
    light 386  
    reflection/refraction 388-390  
    transmission systems 384-388  
OSI 28-29  
    application layer 30  
    data link layer 31  
    network layer 31  
    physical layer 31  
    presentation layer 30  
    session layer 30  
    transport layer 31  
PAP 326  
PC 26  
    branch offices 27  
    components 5-8  
    home offices 27  
    mobile users 27  
physical topologies 23  
PPP dialup access 324-326  
protocols 22  
PSTN 86  
ring topologies 61  
routing 279  
SANs 96-97  
scaling 155-156  
servers 22  
shared LAN 187-188  
subnetworks 255-258  
    Class B addresses 268-273  
    Class C addresses 264-268  
    masks 258-261  
topologies  
    comparing 57  
    full-mesh 62-63  
    partial-mesh 62-63  
    star 59

- VLAN components 192
- VPNs 100-101
- WAN 23
  - connections 83
  - CSUs/DSUs 86
  - data link layer 91
  - devices 85
  - Internet 81
  - modems 86
  - physical layer 89
  - provider services 83-84
  - router serial connections 137-138
  - routers 85
  - serial connections 136-137
  - service providers 87-88
  - signaling 89
  - switches 85
  - Technology 82
- WAN access servers 86
- wireless 358-360
- NFS (Network File System) 31
- NIC (Network Interface Card) 9, 21, 45
  - CSMA/CD 76
  - installing 10
  - wireless 115
- noise
  - effects on wireless signals 360
  - optical networks 385
- nonroot bridges 171
- NOS (Network Operating System) 22
- Novell NetWare 22
- NT1 (Network Termination) 139
- numbering
  - binary-to-decimal conversions 14
  - binary-to-hex conversions 14-17
  - decimal-to-binary conversions 13
  - hex-to-binary conversions 17
  - IP addresses 239-244
  - ports 215-217
  - TCP acknowledgement/sequence 219
- O**
  - OADMs (optical add/drop multiplexers) 400
  - OAM&P (operations, administration, maintenance, and provisioning) 405
  - OAs (optical amplifiers) 400-401
  - one-to-two splitters, cable modems 348
  - Open Shortest Path First (OSPF) 182, 299-300
  - Open System Interconnection. *See* OSI
  - operating software 22
  - operating systems 22, 230-231
  - operations, administration, maintenance, and provisioning (OAM&P) 405
  - operations, LAN switches 164-166
  - optical add/drop multiplexers (OADMs) 400
  - optical amplifiers (OAs) 400-401
  - optical devices 50-51
  - optical fibers 393
    - attenuation 398
    - filters 399-400
    - geometry 394, 398
    - OAs 400-401
    - types of 393-394
  - optical networks 384-390
    - business applications 383
    - light 386
    - reflection/refraction 388-390
    - transmission systems 384-388
  - optical transports 405
    - APS 407
    - multiplexing 408-409
    - overhead hierarchies 406
    - rings 407
    - SDH-based TDM transport 408
  - optical-to-electrical converters 385
  - optimization
    - congestion 158
    - routing 285
    - SANs 97
  - options
    - serial connections 136-137
    - VLAN 193-195
  - Organizationally Unique Identifier (OUI) 70
  - OSI (Open System Interconnection) 30-31
    - cable modems 350-351
    - de-encapsulation 33
    - encapsulation 32
    - IS-IS 300-301
    - LAN 121
    - Layer 1
      - devices 43
      - repeaters 43
      - hubs 44

- Layer 2
  - bridges 46-47
  - devices 45
  - NICs 45
  - switches 48
- Layer 3
  - devices 49
  - multilayer 50
  - routers 49
- network layer 225-226
- TCP/IP
  - comparing 37-38
  - stacks 204,-205
- WAN 82
- OSPF (Open Shortest Path First) 182, 299-300
- OUI (Organizationally Unique Identifier) 70
- overhead hierarchies, SONET 406

## P

---

- packets 230-231
  - encapsulation 280
  - FTP 183
  - internetworks 282
  - IP 226-227
  - routing 279-280
  - split horizons 294
- packet-switched WAN technologies 83
- PAP (Password Authentication Protocol) 323-326
- parallel ports 8
- parameters, wireless 358-359
- partial-mesh topologies 62-63
- Password Authentication Protocol (PAP) 323
- path overhead (POH) 406
- paths
  - autonomous systems 302
  - BGP 302
  - routing 282
  - selecting 298
- path-terminating equipment (PTE) 406
- PBX (private branch exchange) 139
- PC (personal computer) 5-8
  - binary-to-decimal conversions 14
  - binary-to-hex conversions 14-17
  - card analog modems 334
  - comparing 9-10
  - decimal-to-binary conversions 13
- hex-to-binary conversions 17
- laptops 9-10
- measurement 10-13
- networks 26
  - branch offices 27
  - home offices 27
  - mobile users 27
- PCB (printed circuit board) 6
- PCI (peripheral component interconnect) 5
- PCM (pulse code modulation) 332
- PDUs (protocol data units) 34, 351
- peer connections 100-101
- peer-to-peer communication 34
- performance, SANs 97
- peripheral component interconnect (PCI) 5, 332
- permanent virtual circuits (PVCs) 84
- personal computer. *See PC*
- physical boundaries, removing (VLAN) 190
- physical layer, 121
  - cable modems 350-351
  - devices 43
    - hubs 44
    - repeaters 43
  - implementations 125
  - LAN 121
  - WAN 89, 135
- physical topologies 23, 57
- ping command 229
- planning network addressing 262-264
- plenum cables 112
- POH (path overhead) 406
- point of presence (POP) 83
- point-to-multipoint configuration 376
- point-to-point configuration 376
- point-to-point lines 83
- Point-to-Point Protocol (PPP) 91, 323
- poison reverse updates 295
- POP (point of presence) 83
- POP3 (Post Office Protocol 3) 25
- portable PCs 372
- ports 8
  - AUX 145
  - density 156
  - designating 171
  - flooding 165
  - root 171
  - STP states 172
  - VLAN 193-195

- Post Office Protocol 3 (POP3) 25  
Post, Telephone, and Telegraph (PTT) 89  
power cords 8  
power supplies 6  
PPP (Point-to-Point Protocol) 91, 323-326  
    dialup access 324-326  
    WAN 135  
PRI (Primary Rate Interface) 324  
printed circuit board (PCB) 6  
printing servers 22  
private branch exchange (PBX) 139  
private IP addresses 247-248  
programs. *See* applications  
propagation delay 156  
properties, hubs 45  
protocol data units (PDUs) 34, 351  
Protocol field 227  
protocols 22  
    10-Gigabit Ethernets 74  
    ARP 229  
    ASP 31  
    BOOTP 231  
    cable modems 351  
    CHAP 323  
    CLNP 300  
    data link layer (WAN) 91  
    de-encapsulation 33  
    DHCP 225, 231  
    dialup access 324-326  
        CHAP 327  
        ISDN 323-324  
        PAP 326  
    distance-vector 293-294  
    DSL 343  
    EAP 365  
    EIGRP 182, 299  
    encapsulation 32  
    Fast Ethernet 72-73  
    FTP 25, 183  
    Gigabit Ethernets 73-74  
    HDLC 327-328  
    HTTP 24  
    hybrid 296  
    ICMP 228-229  
    IGRP 293, 298  
    IMAP 25  
    IP 31, 205 226-227  
    Layer 4 213-221  
    link-state 295  
    LLC 70-71  
    MAC 70  
    NCPs 325  
    PAP 323  
    physical layer 89  
    POP3 25  
    PPP 91, 135, 323  
    RARP 230-231  
    RIP 182, 293-297  
    routing 279-280, 291-296  
        administrative distance 287  
        algorithms 285  
        BGP 302  
        comparing routed protocols 281  
        EGP 291-292  
        IGP 291-292  
        IS-IS 300-301  
        metrics 285-286  
    SDLC 91  
    SLIP 91  
    SNMP 25  
    STP 163, 169-172  
    TCP 31, 203-205  
    TCP/IP  
        applications 205-206  
        Internet layer 225-226  
        stacks 204-205  
    Telnet 25  
    UDP 31  
    VLAN 193  
provider services 83-88  
PSTN (Public Switched Telephone Network) 86, 331  
PTE (path-terminating equipment) 406  
PTT (Post, Telephone, and Telegraph) 89  
public IP addresses 247-251  
Public Switched Telephone Network (PSTN) 86, 331  
pulse code modulation (PCM) 332  
PVCs (permanent virtual circuits) 84

**Q**

- QAM (quadrature amplitude modulation) 348
- QoS (quality of service) 50, 180
- QPSK (quaternary phase-shift keying) 351

**R**

- radio frequencies. *See RF*
- RAM (random-access memory) 6
- ranges 351
  - hosts 266, 271-275
  - IP addresses 244
- rapid convergence, routing 285
- RARP (Reverse ARP) 225-231
- Rayleigh scattering 398
- RBOCs (regional Bell operating companies) 82, 405
- RC4 stream ciphers 364
- RD (receive) signals 129
- read-only memory (ROM) 8
- receive (RD) signals 129
- receivers, optical 385
- reflection 388-390
- refraction 388, 390
- regional Bell operating companies (RBOCs) 82, 405
- reliability
  - of optical networks 383
  - of routing 286
- remote operating systems, initiating 230-231
- removing physical boundaries (VLAN) 190
- repeaters 43, 152
- replies, echo 229
- requests
  - echo 229
  - RARP 230-231
  - WWW 24
- requirements, Ethernets 123-125
- reserved IP addresses 244-246
- responses, WWW 24
- Reverse ARP (RARP) 225-231
- RF (radio frequencies) 115, 348
  - coaxial cable 143
  - wireless 357-360
    - bands 360-361
    - signals 358-360

- rings 127
- SONET 407
- topologies 23, 61
- RIP (Routing Information Protocol) 182, 293-297
- RJ-45 connector 125
- roaming 373
- robustness, routing 285
- rollover cables 144, 145
- ROM (read-only memory) 8
- root bridges 171
- root ports 171
- routed protocols, comparing to routing protocols 281
- routers 23, 139-140
  - cable connections 142-143
  - Cisco SN 5420 Storage 98
  - DSL connections 141-142
  - firewalls 52
  - ISDN BRI connections 139-140
  - poison reverse updates 295
  - subnetworks 257
  - VLAN 188-192, 197
  - WAN 85, 86
- routes, call 84
- routing 279
  - administrative distance 287
  - algorithms 285
  - CIDR 248-251
  - encapsulation 280
  - functions 279-280
  - IS-IS 300-301
  - loops 294
  - messages 284
  - metrics 279-280
  - OSPF 299-300
  - paths 282
  - protocols 291-292
    - BGP 302
    - comparing routed protocols 281
    - distance-vector protocols 293-294
    - EIGRP 299
    - hybrid protocols 296
    - IGP 291-292
    - IGRP 298
    - IS-IS 300-301
    - link-state protocols 295
    - tables 283-284
  - Routing Information Protocol (RIP) 182, 293-297

# S

---

- SANs (storage-area network) 96, 97
- SC type connectors 114
- scalability
  - of DWDM 411
  - of networks 155-156
  - of SANs 97
- SDH (Synchronous Digital Hierarchy) 95, 405
- SDH-based TDM transport 408
- SDLC (Synchronous Data Link Control Protocol) 91
- SDSL (symmetric DSL) 339. *See also* DSL
- section overhead (SOH) 406
- section-terminating equipment (STE) 406
- security
  - firewalls 52
  - optical networks 384
  - routing 279-280
  - wireless 364-365
- segmentation, 34
  - bridges 155-156
  - LAN microsegmentation 163-164
  - Layer 4 211-212
  - ports 171
  - TCP headers 213-214
  - UDP headers 214
  - VLAN 188-192
- selection
  - of fastest paths (IGRP) 298
  - of NICs 10
  - of paths via BGP 302
- sending e-mail 25
- separation, traffic 195-196
- Sequenced Packet Exchange. *See* SPX
- sequences, TCP 219
- serial connections 136-138
- Serial Line Interface Protocol (SLIP) 91
- serial ports 8
- servers 22
  - AAA 53
  - access (WAN) 86
  - firewalls 52
  - SANs 96, 97
- services
  - call setup (WAN) 84
  - end-to-end transport 211
- Frame Relay 84
- ISDN 324
- providers 83-88
- WINS 232
- shared LAN technologies 151-152, 158
  - bridges 155
  - hubs 152-153
  - switches 156-157
- shared LANs 187-188
- Signaling System 7 (SS7) 84
- signals 84, 89
  - Layer 1 devices 43
    - hubs 44
    - repeaters 43
  - media 107
    - coaxial 110-112
    - comparing 116
    - fiber optical 112-114
    - STP 109-110
    - UTP 107-108
    - wireless 115
  - optical networks 385
  - wireless 358-360
- Simple Network Management Protocol. *See* SNMP
- simplicity of routing 285
- single mode fiber optic cable 113
- single-cell configuration 373
- single-mode fiber 394
- SLIP (Serial Line Interface Protocol) 91
- small office, home office (SOHO) 143
- SNMP (Simple Network Management Protocol) 25, 351
- sockets 8
- software. *See* applications
- SOH (section overhead) 406
- SOHO (small office, home office) 143
- SONET (Synchronous Optical Network) 95, 405
  - APS 407
  - DWDM 409, 412
  - multiplexing 408-409
  - overhead hierarchies 406
  - rings 407
  - SDH-based TDM transport 408
- sound cards 8
- Source Service Access Point (SSAP) 70
- space efficiency, optical networks 384
- Spanning-Tree Protocol (STP) 163

- specifications
  - Ethernets 72, 123-125
  - Fast Ethernet 73
  - Gigabit Ethernets 73
- speed, WAN links 89
- SPF (Shortest Path First) 295
- split horizons 294
- splitters
  - cable modems 348
  - two-way 143
- SPX (Sequenced Packet Exchange) 31
- SQL (Structured Query Language) 31
- SS (spread spectrum) 361-362
- SS7 (Signaling System 7) 84
- SSAP (Source Service Access Point) 70
- ST fiber-optic connectors 114
- stability of routing 285
- stacks 204-205
- standards
  - analog modems 334-336
  - DSL 341-343
  - interfaces 90
  - LAN 69
    - LLC 70-71
    - MAC 70
  - WAN signaling 89
- star topologies 23, 59
- states, STP 172
- STE (section-terminating equipment) 406
- storage, Cisco SN 5420 Storage Router 98
- storage-area networks. *See* SANs
- store-and-forward switching 167-168
- STP (Spanning-Tree Protocol) 109-110, 163-172
- straight-through UTP implementation 129
- Structured Query Language. *See* SQL
- subnets 23
- subnetworks 255-258
  - addresses 274-275
  - Class B addresses 268-273
  - Class C addresses 264-268
  - creating 262-264
  - masks 258-261
  - VLSM 298
- supernetting 250
- switches 23, 48
  - CO 87
  - console connections 144-145
- cut-through 168
- fragment-free 169
- infrastructures 158
- LAN 163
  - full-duplex transmissions 167
  - microsegmentation 163-164
  - modes 167-168
  - operations 164-166
  - STP 169-172
- multilayer 50
- routing 279-280
- shared LAN 156-157
- store-and-forward 167-168
- VLAN 192
  - establishing memberships 193-195
  - trunking 197
- WAN 85
- switching
  - APS 407
  - cells 83
  - multilayer devices 177
    - Layer 2 177-179
    - Layer 3 179
    - Layer 4 181-183
- symmetric DSL (SDSL) 339
- synchronization of transmissions 137
- Synchronous Data Link Control Protocol (SDLC)
  - 91
- Synchronous Digital Hierarchy (SDH) 95, 405
- Synchronous Optical Network. *See* SONET
- system units 8

## T

---

- T (terminal) 139
- tables
  - addresses 165
  - ARP cache tables 229
  - routing 283-284
    - distance-vector protocols 293-294
    - functions 279-280
    - paths 282
- TCP (Transmission Control Protocol) 31, 205
  - acknowledgement/sequence numbers 219
  - cable modems 351
  - communication 203

- connecting 217-221
- headers 181, 213-214
- layer 4 213-217
- port numbers 215-217
- windowing 220-221
- TCP/IP (Transmission Control Protocol/Internet Protocol) 36, 204-205
  - application layer 36
  - applications 205-206
  - ARP cache tables 229
  - BOOTP 231
  - DHCP 231
  - ICMP 228, 229
  - Internet layer 37, 225-226
  - network access layer 37
  - OSI 37-38
  - transport layer 37
- TC-PAM (trellis-coded pulse amplitude modulation) 342
- TD (transmit) 129
- TDM (time-division multiplexing) 84, 408
- technology, WAN 82
- Telnet protocol 25
- terahertz (THz) 400
- terminal (T) 139
- terminal emulation, TCP/IP stacks 204-205
- testing ICMP 229
- Thicknet 111
- thin Ethernet 72
- three-way handshakes 217-218
- ticks, routing 286
- Time To Live (TTL) 181
- time-division multiplexing (TDM) 84
- timers, hold-down 294
- tips 127
- toll 88
- tool networks 88
- topologies
  - bus 59
  - comparing 57
  - full-mesh 62-63
  - LAN physical layers 121
  - logical 23
  - partial-mesh 62-63
  - physical 23
  - star 59
- total internal reflection 113
- tracking routing tables 284
- traffic
  - bridges 46-47
  - broadcast 256
  - congestion 158
  - management 283-284
  - optical networks 383-384
    - light 386
    - reflection/refraction 388-390
    - transmission systems 384-388
  - SANs 96-97
  - switches 48
  - VLAN 195-196
  - WAN 82, 135
- transfers
  - encapsulation 280
  - files 204-205
- Transmission Control Protocol. *See TCP*
- transmissions
  - 10-Gigabit Ethernets 74
  - analog modems 331-332
    - external 333
    - internal 332
    - standards 334-336
  - broadcast 154
  - DWDM 410
  - Ethernets 75-77
  - fiber-optic cables 398
  - full-duplex LAN switches 167
  - Gigabit Ethernets 73-74
  - hubs 154
  - LAN switches 164-166
  - Layer 1 devices 43
    - hubs 44
    - repeaters 43
  - multicast 154
  - optical networks 384-390
  - PC card modems 334
  - synchronizing 137
  - unicast 154
  - WAN 137-138
    - serial connections 136-137
    - signaling standards 89
  - wireless 357-360
    - RF bands 360-361
    - security 364-365
    - SS 361-362

transmit (TD) signals 129  
transparency, DWDM 411  
transponders 410  
transport layer 211  
    cable modems 352  
    flow control 212  
    functions 211-212  
    Protocol field 227  
    protocols 213-217  
    TCP 217-221  
    TCP/IP 37  
transport protocols, VLAN 193  
transporting packets, internetworks 282  
trellis-coded pulse amplitude modulation (TC-PAM)  
    342  
troubleshooting  
    fiber-optic cables 394-398  
    ICMP 229  
    networks 158  
    PC components 5-8  
    routing tables 282-284  
trunking 195-197  
TTL (Time To Live) 21, 181  
twisted-pair cable 107  
    STP 109-110  
    UTP 107-108  
two-way splitters 143  
types  
    of DSL 340  
    of fiber cables 393-394  
    of modems 332-334  
    of connection media 125-126  
    of connections 83  
    of media 107  
        coaxial cables 110-112  
        comparing 116  
        fiber optic cables 112-114  
        STP 109-110  
        UTP 107-108  
        wireless 115  
    of physical layers 135  
    of wireless communication 357-360

## U

---

UDP (User Datagram Protocol) 31  
    cable modems 351  
    headers 181, 214  
    Layer 4 213-217  
    port numbers 215-217  
unicast transmissions 154  
unidirectional path-switched rings (UPSR) 405-407  
Universal Serial Bus (USB) 8, 333  
UNIX 22  
unshielded twisted-pair (UTP) 123  
updates  
    poison reverse 295  
    routing messages 284  
UPSR (unidirectional path-switched rings) 405-407  
upstream rates 340, 348  
usable addresses, identifying 274-275  
USB (Universal Serial Bus) 8, 333  
User Datagram Protocol. *See UDP*  
UTP (unshielded twisted-pair) 107-108, 123-131

## V

---

vampire taps 111  
variable-length subnet mask (VLSM) 298  
video cards 8  
virtual LAN. *See VLAN*  
virtual private networks. *See VPNs*  
VLAN (virtual LAN) 48, 187-192  
    components 192  
    connectivity 195, 196  
    interpretability 192  
    management 193  
    membership 193, 195  
    physical boundaries 190  
    routers 192  
    shared LANs 187, 188  
    switches 192  
    transport protocols 193  
    trunking 197  
VLSM (variable-length subnet mask) 298  
voice, devices 50, 51  
VPNs (virtual private networks) 100-101

# W

- WAN (wide-area network) 23
  - 10-Gigabit Ethernet 75
  - connections 83
  - data link layer 91
  - devices 85
    - access servers 86
    - CSUs/DSUs 86
    - modems 86
    - routers 85
    - switches 85
  - Frame Relay 84
  - Internet 81
  - physical layer 89
    - cabling 135
  - provider services 83-84
  - serial connections 136-138
  - service providers 87-88
  - signaling 89
  - TDM 84
  - technology 82
- wavelength-division multiplexing (WDM) 387
- wavelengths
  - DWDM 409, 412
  - fiber-optic cables 399-400
  - light 386
- WDM (wavelength-division multiplexing) 387
- wide-area network. *See* WAN
- windowing TCP 220-221
- Windows 2000 Server 22
- Windows 95 22
- Windows Internet Naming Service (WINS) 232
- Windows NT 22
- WINS (Windows Internet Naming Service) 232
- wireless communication 115, 357-360
  - LANs 369-376
  - MANs 95
  - RF bands 360-361
  - security 364-365
  - signals 358-360
  - SS 361-62
- WLANs (wireless LANs) 369-370
  - building-to-building 375, 376
  - in-building 370, 371, 372, 375
- WWW (World Wide Web) 24

# X-Z

- X-Window System 31