

Numerics

- 0 CIR (zero CIR), 45
- 75 percent rule, network planning, 44

A

- AAL5 (ATM adaptation layer, 5), 235
- access
 - bandwidth optimization, 413
 - SVCs
 - configuring, 315–321
 - implementing, 318
 - monitoring, 321–324
 - virtual interfaces, 293–295
- active TCP/IP header compression, 424. *See also* TCP/IP
- Adaptive Frame Relay Traffic Shaping for Interface Congestion. *See also* congestion
 - case study, 279–285
 - configuring, 274–276
 - verifying, 276–278
- adaptive shaping
 - BECN, 117–118
 - ForeSight, 118–119
- ADD_LINK_ACK message, 386
- ADD_LINK_REJ message, 387
- adding subrate shapers, 565
- addresses
 - ELMI
 - configuring, 366–369
 - MIB, 369–377
 - registering, 358–360
 - global significance, 97
 - local significance, 95. *See also* local significance
 - SVC, 317
 - X.121, 339
- administration
 - broadcast traffic, 54–56
 - bundles, 386, 387
 - congestion, 51, 483–484
 - configuring, 168
 - monitoring, 178–188
 - queuing, 487
 - RSVP, 612–617
 - switched PVCs, 161
 - ELMI Address Registration, 358
 - links, 384–386
 - network planning, 40–45
 - performance, 50–54
 - SNMP, 370
- advertisements, SAP, 494
- agents, MIB SNMP, 370
- AIM (Advanced Integration Modules), 417
- Airline X.25 (AX25), 337
- algorithms
 - compression, 429
 - leaky bucket, 116
 - Lempel-Ziv compression, 415
 - LSZ, 54
 - Predictor compression, 416
 - Stacker compression, 415
 - token bucket, 116
 - Van Jacobson's, 423
 - WFQ, 486
- Annex G, 331, 334–335
 - case study, 345–353
 - implementing, 335–336
 - monitoring, 350
 - troubleshooting, 350
- answers to review questions, 623–641
- any-to-any connectivity, remote sites, 313
- Application Specific Integrated Circuit (ASIC), 228
- applications
 - LFI, 572
 - LLQ, 538–547
 - provisioning bandwidth, 43
 - PVCs/SVCs, 314–315
 - real-time, 42
- architecture, hierarchical queuing, 487, 495
- ASIC (Application Specific Integrated Circuit), 228
- assignment of DLCIs, 94–98
- association
 - FRTS map classes, 125–127
 - virtual template interfaces, 574
- Asynchronous Transfer Mode. *See* ATM
- ATM (Asynchronous Transfer Mode), 227
 - Cisco, 2600 series routers, 254
 - Cisco, 3600 series routers, 254–255

- Cisco, 7200 series routers, 255
 - CLP, 237–240
 - configuring, 255–265
 - congestion, 240–241
 - DE, 237–240
 - Frame Relay protocol, 229–230
 - FRF.5, 231–237
 - FRF.8.1, 241–252
 - IMA, 254
 - interworking, 230–231
 - overview of, 228–229
 - platform support, 253
 - ATM adaptation layer, 5 (AAL5), 235
 - authentication, 287
 - autonotification, 358–360
 - configuring, 366–369
 - MIB, 369–377
 - Autosense (ELMI QoS), 357–366
 - avoidance (congestion)
 - RED, 596
 - WRED, 594–599
 - configuring, 599–602
 - troubleshooting, 602–605
 - AX25 (Airline X.25), 337
- ## B
-
- B channels, switching on, 159
 - backups
 - bandwidth-on-demand, 313–314
 - VCs, 56–57
 - Backward Explicit Congestion Notification (BECN), 51
 - bandwidth
 - CBWFQ, 522
 - compression
 - algorithms, 429
 - CIR, 414
 - CPU, 431
 - DCP, 54
 - design, 430–432
 - Express Header configuration, 429
 - FRF.8 configuration, 439
 - FRF.9 configuration, 421–423
 - function of, 414–415
 - hardware/software, 416–418, 460–465
 - latency, 431
 - loss-less compression algorithm schemes, 415
 - memory, 431
 - monitoring, 432–447
 - nonreversible data compression schemes, 415
 - payloads, 435
 - Predictor, 416
 - ratios, 416, 432
 - RTP header configuration, 426–429, 444
 - schemes, 418–420
 - speed, 431
 - Stacker, 415
 - TCP/IP, 423, 441
 - troubleshooting, 447
 - LFI, 571
 - optimizing, 413
 - planning, 43
 - requirements, 40
 - reservations services, 610
 - troubleshooting, 530
 - virtual template interfaces, 574
 - bandwidth percent command, 531
 - bandwidth-on-demand, 313–314
 - Bc (committed burst), 45
 - Be (excess burst), 45
 - BECN (Backward Explicit Congestion Notification), 51, 117–118
 - BFE (Blacker Front End), 337
 - bidirectional mode, End-to-End Keepalive, 199
 - B-ISDN (Broadband Integrated Services Digital Network), 228
 - bit mapping
 - CLP to DE, 240, 250
 - DE to CLP, 238, 248
 - Blacker Front End (BFE), 337
 - bottlenecks
 - RED, 596
 - WRED, 594–599
 - configuring, 599–602
 - troubleshooting, 602–605
 - broadband connections, ATM, 228–229
 - Broadband Integrated Services Digital Network (B-ISDN), 228
 - broadcasts
 - configuring, 146–147

- managing, 54–56
- queues, 493–494
- bundles
 - configuring, 386–388
 - load balancing, 392–397
 - managing, 387
 - resiliency, 404
 - tearing down, 388

C

-
- capacity, planning bandwidth, 40, 43
 - case studies
 - Adaptive Frame Relay Traffic Shaping for Interface Congestion, 279–285
 - Annex G, 345–353
 - LFI, 581
 - fragmentation, 477–479
 - PPP, 301–308
 - SVCs, 326–329
 - CBWFQ (Class-Based Weighted Fair Queuing), 487, 513, 518–520
 - configuring, 521–526
 - LLQ/PQ, 531–537
 - troubleshooting, 526–531
 - WFQ, 520
 - CEF (Cisco Express Forwarding), 429
 - cell loss priority (CLP), 230, 237–240
 - Challenge Handshake Authentication Protocol (CHAP), 287
 - channels, switching B channels, 159
 - CHAP (Challenge Handshake Authentication Protocol), 287
 - CIR (committed information rate), 110
 - Frame Relay subscription, 44
 - maximum, 47
 - MINCIR, 613
 - moderated, 46
 - planning, 45–47
 - reducing, 414
 - zero CIR, 45
 - circuits
 - Cisco, 90i IDSL Channel Unit, 289
 - compression, 54
 - Cisco, 2600 series routers, ATM, 254
 - Cisco, 3600 series routers, ATM, 254–255
 - Cisco, 7200 series routers, ATM, 255
 - Cisco, 90i IDSL Channel Unit, 289
 - Cisco Express Forwarding (CEF), 429
 - Cisco Frame Relay Enhanced LMI. *See* ELMi
 - Cisco Frame Relay Switching Enhancements feature, 158–161
 - configuring, 162
 - monitoring, 171–188
 - Cisco IOS MLP LFI feature, 573. *See also* LFI
 - Cisco MC3810 platform, 253
 - Class-Based Weighted Fair Queuing (CBWFQ), 487, 513, 518–520
 - configuring, 521–526
 - LLQ/PQ, 531–537
 - troubleshooting, 526–531
 - WFQ, 520
 - classes
 - associating, 125–127
 - FRTS, 120–125
 - classification of mission-critical traffic, 50
 - class-map commands, configuring, 515–518
 - CLI (command-line interface), configuring, 66
 - clockrate command, 92
 - CLP (cell loss priority), 230, 237–240
 - cnfport IGX switch port configuration command, 363
 - commands
 - bandwidth percent, 531
 - class-map, 515–518
 - clockrate, 92
 - cnfport IGX port configuration, 363
 - debug, 102–104
 - debug frame-relay end-to-end keepalive event, 212
 - debug frame-relay events, 102
 - debug frame-relay lmi, 103
 - debug frame-relay packet, 103
 - debug priority, 506
 - encapsulation
 - encapsulation frame-relay, 67
 - encapsulation x25, 336
 - frame-relay
 - frame-relay adaptive-shaping foresight, 118
 - frame-relay address registration ip, 368
 - frame-relay broadcast-queue, 494
 - frame-relay cir, 122
 - frame-relay congestion threshold de, 182
 - frame-relay congestion threshold ecn, 182

- frame-relay congestion-management, 169
- frame-relay de-group, 145
- frame-relay fragment, 456
- frame-relay holdq, 488
- frame-relay idle-timer, 320
- frame-relay interface, 125
- frame-relay interface-dlci, 87
- frame-relay intf-type dce interface, 92
- frame-relay map, 72, 80
- frame-relay mincir, 123
- frame-relay policing, 166
- frame-relay qos-autosense, 361
- frame-relay route, 92
- frame-relay svc, 319
- frame-relay switching, 92, 162
- frame-relay traffic-shaping, 164, 457
- frame-relay traffic-shaping interface configuration, 120
- hold-queue interface configuration, 595
- max reserved-bandwidth, 611
- no shutdown, 69
- policy-map global configuration, 556
- service-policy, 518
- shape, 522
- show
 - LFI, 577–580
 - MFR, 98–101, 397–408
 - show compress, 438, 465
 - show frame-relay end-to-end keepalive, 204
 - show frame-relay fragment, 470
 - show frame-relay lmi, 71
 - show frame-relay map, 82, 100, 321
 - show frame-relay pvc, 182, 240, 365
 - show frame-relay qos-autosense, 364
 - show frame-relay route, 101
 - show frame-relay vofr global EXEC, 473
 - show interface, 70, 142
 - show interface global EXEC, 322
 - show interface serial, 337
 - show interface serial privileged EXEC mode, 98
 - show interface serial type/number global EXEC, 277
 - show interface type slot/port privileged EXEC mode, 69
 - show ip tcp header-compression, 465
 - show policy-map privileged EXEC, 526
 - show traffic-shape, 132
 - show x25 map, 343
- snmp-server community, 368
- X.25, 339
- committed burst (Bc), 45
- committed information rate (CIR), 110
 - Frame Relay subscription, 44
 - maximum, 47
 - MINCIR, 613
 - moderated, 46
 - planning, 45–47
 - reducing, 414
 - zero CIR, 45
- Common Part Convergence Sublayer (CPCS), 232
- Common Part Indicator (CPI), 234
- comparisons
 - ATM/Frame Relay protocol, 229–230
 - CBWFQ to WFQ, 520
 - hardware/software compression, 416–418
 - PVCs/SVCs, 312, 314–315
 - Tail Drop/WRED, 600
- compatibility of hardware/software compression, 461
- components
 - BECN adaptive shaping, 117–118
 - ForeSight adaptive shaping, 118–119
- Compressed RTP (CRTP), 427
- compression, 53, 413
 - algorithms, 429
 - CIR, 414
 - CPU, 431
 - DCP, 54
 - design, 430–432
 - Express Header configuration, 429
 - FRF.8 configuration, 439
 - FRF.9 configuration, 421–423
 - function of, 414–415
 - hardware/software, 416–418, 460–465
 - latency, 431
 - loss-less compression algorithm schemes, 415
 - memory, 431
 - monitoring, 432–447
 - nonreversible data compression schemes, 415
 - payloads, 435
 - Predictor, 416
 - ratios, 416, 432
 - RTP header configuration, 426–429, 444
 - schemes, 418–420

- speed, 431
- Stacker, 415
- TCP/IP, 423, 441
- troubleshooting, 447
- Compression Service Adaptors (CSA), 417, 465
- conditions, FRF.12 Fragmentation, 460
- configuration, 66, 73
 - Adaptive Frame Relay Traffic Shaping for Interface Congestion, 274–276
 - bundles, 386–388
 - CBWFQ, 521–526
 - Cisco Frame Relay Switching Enhancements feature, 162
 - compression
 - algorithms, 429
 - CIR, 414
 - CPU, 431
 - DCP, 54
 - design, 430–432
 - Express Header configuration, 429
 - FRF.8 configuration, 439
 - FRF.9 configuration, 421–423
 - function of, 414–415
 - hardware/software, 416–418, 460–465
 - latency, 431
 - loss-less compression algorithm schemes, 415
 - memory, 431
 - monitoring, 432–447
 - nonreversible data compression schemes, 415
 - payloads, 435
 - Predictor, 416
 - ratios, 416, 432
 - RTP header configuration, 426–429, 444
 - schemes, 418–420
 - speed, 431
 - Stacker, 415
 - TCP/IP, 423, 441
 - troubleshooting, 447
 - congestion management, 168. *See also* congestion
 - dynamic mapping, 77–79
 - ELMI, 360–369
 - encapsulation, 67–70
 - End-to-End Keepalive, 197–202
 - Express Header Compression, 429
 - Fragmentation at the Interface, 552–556
 - Frame Relay IP RTP Priority feature, 446
 - FRF.12 Fragmentations, 460
 - FRF.5, 255–262
 - FRF.8.1, 262–265
 - FRTS, 119–120
 - associating map classes, 125–127
 - BECN adaptive shaping, 117–118
 - broadcast queues, 146–147
 - DE, 144–146
 - DLCI priority levels, 147
 - enabling, 113–117
 - ForeSight adaptive shaping, 118–119
 - generic traffic shaping, 147–148
 - map classes, 120–125
 - monitoring, 127–144
 - overview of, 112–113
 - hardware compression, 461–465
 - keepalives, 74
 - hierarchical queuing architecture, 487
 - LAPF parameters, 321
 - LLQ, 533
 - LMI, 70–77
 - local significance, 94–98
 - MQC, 514–518
 - Multilink Frame Relay, 384
 - initializing, 386–388
 - load balancing, 392–397
 - Multilink Frame Relay Link Integrity Protocol, 384–386
 - parameters, 388–392
 - routers, 390–397
 - packet-by-packet payload compression, 420
 - parameters, 339
 - PIPQ, 497–503
 - policing, 166
 - PPP
 - case study, 301–308
 - frame formats, 291–293
 - interfaces, 293–295
 - monitoring, 295–299
 - requirements, 287–288
 - RFC, 1973 implementation, 288–291
 - routers, 574–582
 - RSVP, 612–617
 - RTP header compression, 426–429
 - static mapping, 79–83
 - subinterfaces, 83–90

- SVCs, 315–324
- switches, 90–94
- TCP/IP header compression, 423–426
- threshold queue depth, 272
- traffic shaping, 164
- UFM ports, 363
- virtual template interfaces, 293, 574
- WFQ interfaces, 519
- WRED, 599–602
- X.25, 336–344
- congestion, 270–271
 - ATM, 240–241
 - BECN/FECN, 51
 - compression, 53
 - algorithms, 429
 - CIR, 414
 - CPU, 431
 - DCP, 54
 - design, 430–432
 - Express Header configuration, 429
 - FRF.8 configuration, 439
 - FRF.9 configuration, 421–423
 - function of, 414–415
 - hardware/software, 416–418, 460–465
 - latency, 431
 - loss-less compression algorithm schemes, 415
 - memory, 431
 - monitoring, 432–447
 - nonreversible data compression schemes, 415
 - payloads, 435
 - Predictor, 416
 - ratios, 416, 432
 - RTP header configuration, 426–429, 444
 - schemes, 418–420
 - speed, 431
 - Stacker, 415
 - TCP/IP, 423, 441
 - troubleshooting, 447
 - DE, 144–146
 - FRF.8.1, 252
 - FRTS, 110
 - management, 483–484
 - configuring, 168
 - monitoring, 178–188
 - queuing, 487
 - RSVP, 612–617
 - switched PVCs, 161
 - managing, 51
 - map-class, 273
 - notification, 124
 - RED, 596
 - Tail Drop, 595
 - traffic shaping, 271–274
 - WRED, 594–599
 - configuring, 599–602
 - troubleshooting, 602–605
- congestive-discard-threshold option, 519
- connections. *See also* networks
 - ATM, 228–229
 - bandwidth. *See* bandwidth
 - broadband. *See* broadband
 - DLCI, 94–98
 - ELMI Address Registration, 359
 - End-to-End Keepalive, 207
 - frame mode setup, 316
 - ping utility, 324
 - point-to-point subinterfaces, 87
 - PPP
 - requirements, 287–288
 - RFC, 1973 implementation, 288–291
 - queuing, 484–487, 495
 - remote sites, 313
 - RSVP, 609
 - SVCs, 323
 - troubleshooting, 102–104
 - verifying, 98
 - X.25, 338
- control messages, 316
- convergence, 232
- CPCS-UU (CPCS User-to-User notification), 234
- CPE (customer premised equipment), 288
- CPI (Common Part Indicator), 234
- CPU (central processing unit) compression, 431
- CQ (custom queuing), 52, 485
- CRC (cyclic redundancy check), 229
- credit, 115
- CRTP (Compressed RTP), 427
- CSA (Compression Service Adaptors), 417, 465
- custom queuing (CQ), 52, 485
- customer premises equipment (CPE), 288

customization

- Adaptive Frame Relay Traffic Shaping for Interface Congestion, 274–276

- bundles, 386–388

- CBWFQ, 521–526

- Cisco Frame Relay Switching Enhancements feature, 162

- compression

- algorithms, 429

- CIR, 414

- CPU, 431

- DCP, 54

- design, 430–432

- Express Header configuration, 429

- FRF.8 configuration, 439

- FRF.9 configuration, 421–423

- function of, 414–415

- hardware/software, 416–418, 460–465

- latency, 431

- loss-less compression algorithm schemes, 415

- memory, 431

- monitoring, 432–447

- nonreversible data compression schemes, 415

- payloads, 435

- Predictor, 416

- ratios, 416, 432

- RTP header configuration, 426–429, 444

- schemes, 418–420

- speed, 431

- Stacker, 415

- TCP/IP, 423, 441

- troubleshooting, 447

- congestion management, 168. *See also* congestion

- dynamic mapping, 77–79

- ELMI, 360–369

- encapsulation, 67–70

- End-to-End Keepalive, 197–202

- Express Header Compression, 429

- Fragmentation at the Interface, 552–556

- Frame Relay IP RTP Priority feature, 446

- FRF.12 Fragmentations, 460

- FRF.5, 255–262

- FRF.8.1, 262–265

- FRTS, 119–120

- associating map classes, 125–127

- BECN adaptive shaping, 117–118

- broadcast queues, 146–147

- DE, 144–146

- DLCI priority levels, 147

- enabling, 113–117

- ForeSight adaptive shaping, 118–119

- generic traffic shaping, 147–148

- map classes, 120–125

- monitoring, 127–144

- overview of, 112–113

- hardware compression, 461–465

- keepalives, 74

- hierarchical queuing architecture, 487

- LAPF parameters, 321

- LLQ, 533

- LMI, 70–77

- local significance, 94–98

- MQC, 514–518

- Multilink Frame Relay, 384

- initializing, 386–388

- load balancing, 392–397

- Multilink Frame Relay Link Integrity

- Protocol, 384–386

- parameters, 388–392

- routers, 390–397

- packet-by-packet payload compression, 420

- parameters, 339

- PIPQ, 497–503

- policing, 166

- PPP

- case study, 301–308

- frame formats, 291–293

- interfaces, 293–295

- monitoring, 295–299

- requirements, 287–288

- RFC, 1973 implementation, 288–291

- routers, 574–582

- RSVP, 612–617

- RTP header compression, 426–429

- static mapping, 79–83

- subinterfaces, 83–90

- SVCs, 315–324

- switches, 90–94

- TCP/IP header compression, 423–426

- threshold queue depth, 272

- traffic shaping, 164

- UFM ports, 363

- virtual template interfaces, 293, 574

- WFQ interfaces, 519

WRED, 599–602
 X.25, 336–344
 cyclic redundancy check (CRC), 229

D

data circuit-terminating equipment (DCE), 318
 Data Compression Protocol (DCP), 54
 Data Link Connection Identifier (DLCI)
 assignment, 94–98
 ForeSight adaptive shaping, 119
 priority levels, 147
 Data Network Identification Codes (DNICs), 339
 data payload compression schemes, 419
 data rates, troubleshooting mismatch, 111
 data terminal equipment (DTE), 318
 data traffic, RSVP, 609–611
 data-stream compression, 460. *See also* compression
 DCCs (International Data Country Codes), 339
 DCE (data circuit-terminating equipment), 318, 357
 DCP (Data Compression Protocol), 54
 DDN (Defense Data Network), 337
 DE (discard eligibility), 230
 ATM, 237–240
 configuring, 144–146
 debug commands, 102–104
 debug frame-relay end-to-end keepalive event
 command, 212
 debug frame-relay events command, 102
 debug frame-relay lmi command, 103
 debug frame-relay packet command, 103
 debug priority command, 506
 debugging. *See also* troubleshooting
 Annex G, 353
 End-to-End Keepalive, 211–212
 Defense Data Network (DDN), 337
 Defense Information Systems Agency (DISA), 317
 delay
 LFI, 571
 MLP, 575
 deleting
 connections, 359
 FRTS, 545
 deployment of ELMQ QoS Autosense, 358

design
 Adaptive Frame Relay Traffic Shaping for
 Interface Congestion, 274–276
 bundles, 386–388
 CBWFQ, 521–526
 Cisco Frame Relay Switching Enhancements
 feature, 162
 compression
 algorithms, 429
 CIR, 414
 CPU, 431
 DCP, 54
 design, 430–432
 Express Header configuration, 429
 FRF.8 configuration, 439
 FRF.9 configuration, 421–423
 function of, 414–415
 hardware/software, 416–418, 460–465
 latency, 431
 loss-less compression algorithm schemes,
 415
 memory, 431
 monitoring, 432–447
 nonreversible data compression schemes,
 415
 payloads, 435
 Predictor, 416
 ratios, 416, 432
 RTP header configuration, 426–429, 444
 schemes, 418–420
 speed, 431
 Stacker, 415
 TCP/IP, 423, 441
 troubleshooting, 447
 congestion management, 168. *See also* congestion
 dynamic mapping, 77–79
 ELMQ, 360–369
 encapsulation, 67–70
 End-to-End Keepalive, 197–202
 Express Header Compression, 429
 Fragmentation at the Interface, 552–556
 Frame Relay IP RTP Priority feature, 446
 FRF.12 Fragmentations, 460
 FRF.5, 255–262
 FRF.8.1, 262–265
 FRTS, 119–120

- associating map classes, 125–127
 - BECN adaptive shaping, 117–118
 - broadcast queues, 146–147
 - DE, 144–146
 - DLCI priority levels, 147
 - enabling, 113–117
 - ForeSight adaptive shaping, 118–119
 - generic traffic shaping, 147–148
 - map classes, 120–125
 - monitoring, 127–144
 - overview of, 112–113
 - hardware compression, 461–465
 - keepalives, 74
 - hierarchical queuing architecture, 487
 - LAPF parameters, 321
 - LLQ, 533
 - LMI, 70–77
 - local significance, 94–98
 - MQC, 514–518
 - Multilink Frame Relay, 384
 - initializing, 386–388
 - load balancing, 392–397
 - Multilink Frame Relay Link Integrity Protocol, 384–386
 - parameters, 388–392
 - routers, 390–397
 - packet-by-packet payload compression, 420
 - parameters, 339
 - PIPQ, 497–503
 - policing, 166
 - PPP
 - case study, 301–308
 - frame formats, 291–293
 - interfaces, 293–295
 - monitoring, 295–299
 - requirements, 287–288
 - RFC, 1973 implementation, 288–291
 - routers, 574–582
 - RSVP, 612–617
 - RTP header compression, 426–429
 - static mapping, 79–83
 - subinterfaces, 83–90
 - SVCs, 315–324
 - switches, 90–94
 - TCP/IP header compression, 423–426
 - threshold queue depth, 272
 - traffic shaping, 164
 - UFM ports, 363
 - virtual template interfaces, 293, 574
 - WFQ interfaces, 519
 - WRED, 599–602
 - X.25, 336–344
 - destination service-assess point (DSAP), 247
 - devices, 197–201
 - configuring, 201–202
 - monitoring, 202–211
 - troubleshooting, 211–212
 - DiffServ (differentiated services), 513
 - DISA (Defense Information Systems Agency), 317
 - discard eligibility (DE), 230
 - ATM, 237–240
 - configuring, 144–146
 - distributed class-based WFQ, 487
 - Distributed Traffic Shaping (DTS), 522
 - distributed WFQ, 487
 - DLCI (Data Link Connection Identifier)
 - assignment, 94–98
 - ForeSight adaptive shaping, 119
 - priority levels, 147
 - DNICs (Data Network Identification Codes), 339
 - DSAP (destination service-assess point), 247
 - DTE (data terminal equipment), 318, 357
 - DTS (Distributed Traffic Shaping), 522
 - dual-FIFO, 491
 - dynamic mapping, configuring, 77–79
 - dynamic throttling, output, 138
 - dynamic-queues option, 519
- ## E
-
- E.164 addressing schemes, 317
 - edge routers, 459
 - EFCI (Explicit Forward Congestion Indication), 241
 - egress interfaces, FRTS, 115
 - ELMI (Cisco Frame Relay Enhanced LMI), 355
 - Address Registration, 358–360
 - configuring, 366–369
 - MIB, 369–377
 - configuring, 360–369
 - QoS
 - Autosense, 357–358
 - configuring, 360–366
 - inability to obtain, 356

enabling. *See also* configuration

- ELMI, 360–369
- encapsulation, 67–70, 575
- FRF.12 Fragmentation, 457–459
- FRTS, 113–117, 120
- interleaving, 575
- MLP, 574
- PIPQ, 497–503
- SVCs, 319
- switching, 162
- WRED
 - interfaces, 599
 - traffic policies, 600
- X.25, 336–344

encapsulation

- Annex G, 334–335
- configuring, 67–70
- implementing, 335–336
- LFI, 575
- matching, 72
- MFR interfaces, 395
- PIPQ, 495–497
 - configuring, 497–503
 - troubleshooting, 503–511
- PPP frame formats, 291–293
- queuing, 487
- SVCs, 318
- TCP/IP header compression, 424
- verifying, 69
- X.25, 336–344

encapsulation frame-relay command, 67

encapsulation x25 command, 336

end systems, RSVP, 609–611

End-to-End Fragmentation, 462, 553

End-to-End FRF.12 Fragmentation, 455–457

End-to-End Keepalives, 197–201

- configuring, 201–202
- monitoring, 202–211
- troubleshooting, 211–212

end-to-end mapping, inability to obtain, 356

ERP (Enterprise Resource Planning), 40

establishment

- of bundle links, 386
- of link, 384–386

Ethernet interfaces, Layer, 3 queues, 594

events, windows, 198

excess burst (Be), 45

existing CIR, reducing, 414

existing networks, compression design, 430

Explicit Forward Congestion Indication (EFCI), 241

Express Header Compression configuration, 429

F

Fast Ethernet interfaces, Layer, 3 queues, 594

fast switching, 115, 429

FECCN (Forward Explicit Congestion Notification), 51

FIFO (First-In-First-Out), 485, 491

flow-based WFQ, 486

flow-based WRED, 600

flowcharts, leaky buckets/token buckets, 116

ForeSight, FRTS adaptive shaping, 118–119

formatting

- Adaptive Frame Relay Traffic Shaping for Interface Congestion, 274–276
- bundles, 386–388
- CBWFQ, 521–526
- Cisco Frame Relay Switching Enhancements feature, 162
- compression
 - algorithms, 429
 - CIR, 414
 - CPU, 431
 - DCP, 54
 - design, 430–432
 - Express Header configuration, 429
 - FRF.8 configuration, 439
 - FRF.9 configuration, 421–423
 - function of, 414–415
 - hardware/software, 416–418, 460–465
 - latency, 431
 - loss-less compression algorithm schemes, 415
 - memory, 431
 - monitoring, 432–447
 - nonreversible data compression schemes, 415
 - payloads, 435
 - Predictor, 416
 - ratios, 416, 432
 - RTP header configuration, 426–429, 444
 - schemes, 418–420
 - speed, 431

- Stacker, 415
- TCP/IP, 423, 441
- troubleshooting, 447
- congestion management, 168. *See also* congestion
- dynamic mapping, 77–79
- ELMI, 360–369
- encapsulation, 67–70
- End-to-End Keepalive, 197–202
- Express Header Compression, 429
- Fragmentation at the Interface, 552–556
- Frame Relay IP RTP Priority feature, 446
- FRF.12 Fragmentations, 460
- FRF.5, 255–262
- FRF.8.1, 262–265
- FRTS, 119–120
 - associating map classes, 125–127
 - BECN adaptive shaping, 117–118
 - broadcast queues, 146–147
 - DE, 144–146
 - DLCI priority levels, 147
 - enabling, 113–117
 - ForeSight adaptive shaping, 118–119
 - generic traffic shaping, 147–148
 - map classes, 120–125
 - monitoring, 127–144
 - overview of, 112–113
- hardware compression, 461–465
- keepalives, 74
- hierarchical queuing architecture, 487
- LAPF parameters, 321
- LLQ, 533
- LMI, 70–77
- local significance, 94–98
- MQC, 514–518
- Multilink Frame Relay, 384
 - initializing, 386–388
 - load balancing, 392–397
 - Multilink Frame Relay Link Integrity Protocol, 384–386
 - parameters, 388–392
 - routers, 390–397
- packet-by-packet payload compression, 420
- parameters, 339
- PIPQ, 497–503
- policing, 166
- PPP
 - case study, 301–308
 - frame formats, 291–293
 - interfaces, 293–295
 - monitoring, 295–299
 - requirements, 287–288
 - RFC, 1973 implementation, 288–291
- routers, 574–582
- RSVP, 612–617
- RTP header compression, 426–429
- static mapping, 79–83
- subinterfaces, 83–90
- SVCs, 315–324
- switches, 90–94
- TCP/IP header compression, 423–426
- threshold queue depth, 272
- traffic shaping, 164
- UFM ports, 363
- virtual template interfaces, 293, 574
- WFQ interfaces, 519
- WRED, 599–602
- X.25, 336–344
- Forward Explicit Congestion Notification (FECN), 51
- fragmentation, 451
 - case studies, 477–479
 - configuring, 553
 - hardware compression, 460–465
 - implementing, 455
 - FRF.11 Annex C, 465
 - FRF.12, 455–465
 - LFI, 571
 - proprietary formats, 466
 - sizing, 575
 - switched PVCs
 - configuring FRF.12 Fragmentation, 460
 - FRF.12 support, 457
 - troubleshooting, 467–476
- Fragmentation at the Interface feature, 552–556
 - configuring, 558–563
 - troubleshooting, 561–568
- Frame Relay CIR subscription, 44–47
- Frame Relay Forum Implementation Agreement Document Number FRF.5, 231
- Frame Relay IP RTP Priority, configuring, 446
- Frame Relay PIPQ, 487
- Frame Relay Service Specific Convergence Sublayer (FR-SSCS), 232
- Frame Relay Traffic Shaping. *See* FRTS
- frame-relay commands
 - frame-relay adaptive-shaping foresight command, 118

- frame-relay address registration ip command, 368
- frame-relay broadcast-queue command, 494
- frame-relay cir command, 122
- frame-relay class interface command, 125
- frame-relay congestion threshold de command, 182
- frame-relay congestion threshold ecn command, 182
- frame-relay congestion-management command, 169
- frame-relay de-group command, 145
- frame-relay fragment command, 456
- frame-relay holdq command, 488
- frame-relay idle-timer command, 320
- frame-relay interface-dlci command, 87
- frame-relay intf-type dce interface configuration command, 92
- frame-relay map command, 72, 80
- frame-relay mincir command, 123
- frame-relay policing command, 166
- frame-relay qos-autosense command, 361
- frame-relay route command, 92
- frame-relay svc command, 319
- frame-relay switching command, 92, 162
- frame-relay traffic-shaping command, 164, 457
- frame-relay traffic-shaping interface configuration command, 120

frames

- Annex G, 334–336
- compression, 53
- formats, 291–293
- modes, 316
- transmission, 553

FRF.11 Annex C Fragmentation, 465–466

FRF.12 Fragmentation, 455–465

FRF.5, configuring, 231–237, 255–262

FRF.8.1, 241–252, 262–265

FRF.9, 421–423, 439

FR-SSCS (Frame Relay Service Specific Convergence Sublayer), 232

FRTS (Frame Relay Traffic Shaping). *See also* traffic BECN, 117–118

- broadcast queues, 146–147
- configuration, 119–120
 - associating map classes, 125–127
 - mapping classes, 120–125
 - monitoring, 127–144

- data rate mismatch, 111
- DE, 144–146
- deleting, 545
- DLCI priority levels, 147
- enabling, 113–117
- ForeSight adaptive shaping, 118–119
- generic traffic shaping, 147–148
- oversubscription, 110–111
- overview of, 112–113
- fully meshed topologies, 48, 49
- functionality of fragmentation, 556
- functions. *See also* commands
 - Annex G, 334–335
 - implementing, 335–336

G

- global significance addressing, 97
- GTS (Generic Traffic Shaping), 147–148, 522

H

hardware

- compression, 416–418
 - algorithms, 429
 - CIR, 414
 - CPU, 431
 - DCP, 54
 - design, 430–432
 - Express Header configuration, 429
 - FRF.8 configuration, 439
 - FRF.9 configuration, 421–423
 - function of, 414–415
 - hardware/software, 416–418, 460–465
 - latency, 431
 - loss-less compression algorithm schemes, 415
 - memory, 431
 - monitoring, 432–447
 - nonreversible data compression schemes, 415
 - payloads, 435
 - Predictor, 416
 - ratios, 416, 432
 - RTP header configuration, 426–429, 444

- schemes, 418–420
 - speed, 431
 - Stacker, 415
 - TCP/IP, 423, 441
 - troubleshooting, 447
 - configuring, 66
 - Header Error Control (HEC), 229
 - headers
 - compression, 53
 - Express Compression configuration, 429
 - packet compression schemes, 419
 - RTP
 - compression configuration, 426–429
 - verifying compression, 444
 - TCP/IP
 - compression configuration, 423–426
 - verifying compression, 441
 - UDP, 426
 - HEC (Header Error Control), 229
 - HELLO messages, 387
 - hierarchical queuing architecture, 487–495
 - High Speed Serial Interface (HSSI), 494
 - hold-queue interface configuration command, 595
 - HSSI (High Speed Serial Interface), 494
 - hub-and-spoke networks
 - broadcast queues configuration, 146–147
 - compression design, 430
-
- I**
- IDNs (International Data Numbers), 339
 - IDSL (ISDN Digital Subscriber Line), 288–289
 - IfIndex (interface indexes), 359
 - IMA (Inverse Multiplexing over ATM), 254
 - implementation
 - Adaptive Frame Relay Traffic Shaping for Interface Congestion, 274–276
 - bundles, 386–388
 - CBWFQ, 521–526
 - Cisco Frame Relay Switching Enhancements feature, 162
 - compression
 - algorithms, 429
 - CIR, 414
 - CPU, 431
 - DCP, 54
 - design, 430–432
 - Express Header configuration, 429
 - FRF.8 configuration, 439
 - FRF.9 configuration, 421–423
 - function of, 414–415
 - hardware/software, 416–418, 460–465
 - latency, 431
 - loss-less compression algorithm schemes, 415
 - memory, 431
 - monitoring, 432–447
 - nonreversible data compression schemes, 415
 - payloads, 435
 - Predictor, 416
 - ratios, 416, 432
 - RTP header configuration, 426–429, 444
 - schemes, 418–420
 - speed, 431
 - Stacker, 415
 - TCP/IP, 423, 441
 - troubleshooting, 447
 - congestion management, 168. *See also* congestion dynamic mapping, 77–79
 - ELMI, 360–369
 - encapsulation, 67–70
 - End-to-End Keepalive, 197–202
 - Express Header Compression, 429
 - Fragmentation at the Interface, 552–556
 - Frame Relay IP RTP Priority feature, 446
 - FRF.12 Fragmentations, 460
 - FRF.5, 255–262
 - FRF.8.1, 262–265
 - FRTS, 119–120
 - associating map classes, 125–127
 - BECN adaptive shaping, 117–118
 - broadcast queues, 146–147
 - DE, 144–146
 - DLCI priority levels, 147
 - enabling, 113–117
 - ForeSight adaptive shaping, 118–119
 - generic traffic shaping, 147–148
 - map classes, 120–125
 - monitoring, 127–144
 - overview of, 112–113
 - hardware compression, 461–465
 - keepalives, 74

- hierarchical queuing architecture, 487
- LAPF parameters, 321
- LLQ, 533
- LMI, 70–77
- local significance, 94–98
- MQC, 514–518
- Multilink Frame Relay, 384
 - initializing, 386–388
 - load balancing, 392–397
 - Multilink Frame Relay Link Integrity Protocol, 384–386
 - parameters, 388–392
 - routers, 390–397
- packet-by-packet payload compression, 420
- parameters, 339
- PIPQ, 497–503
- policing, 166
- PPP
 - case study, 301–308
 - frame formats, 291–293
 - interfaces, 293–295
 - monitoring, 295–299
 - requirements, 287–288
 - RFC, 1973 implementation, 288–291
- routers, 574–582
- RSVP, 612–617
- RTP header compression, 426–429
- static mapping, 79–83
- subinterfaces, 83–90
- SVCs, 315–324
- switches, 90–94
- TCP/IP header compression, 423–426
- threshold queue depth, 272
- traffic shaping, 164
- UFM ports, 363
- virtual template interfaces, 293, 576
- WFQ interfaces, 519
- WRED, 599–602
- X.25, 336–344
- incoming switched interfaces, 166
- increasing bandwidth, troubleshooting, 530
- indexes, IfIndex, 359
- ingress interfaces, monitoring, 175–178
- initialization of Multilink Frame Relay, 386–388
- Integrated Services Digital Network (ISDN), 57, 159
- interface indexes (IfIndex), 359
- interface-level queuing, 488
- interfaces
 - configuring, 66
 - congestion, 270–271
 - monitoring, 183
 - traffic shaping, 271–274
 - encapsulation, 67–70
 - Fast Ethernet Layer, 3 queues, 594
 - Fragmentation at the Interface feature, 552–556
 - configuring, 558–563
 - troubleshooting, 563–570
 - FRTS, 113
 - HSSI, 494
 - incoming switched, 166
 - ingress, 175–178
 - ISDN B channels, 159
 - LMI, 70–77
 - map classes, 126
 - mapping, 82
 - MQC, 513
 - configuring, 514–515
 - customizing class-map commands, 517–520
 - Multilink Frame Relay, 389
 - NNI, 93, 455
 - PIPQ, 495–497
 - configuring, 497–503
 - troubleshooting, 503–511
 - PP, 293–295
 - queuing strategies, 498
 - split horizons, 62
 - subinterfaces
 - configuring, 83–86
 - point-to-point, 87–90
 - troubleshooting, 60–62
 - subrate shaping, 556
 - UNI, 118, 455
 - UNI DCE, 161
 - VIP2, 422
 - virtual templates, 574
 - WFQ, 519
 - WRED, 601
 - X.25, 336–344
- interleaving
 - enabling, 575
 - frames for transmission, 553
 - LFI, 573. *See also* LFI
- internal timers, End-to-End Keepalive, 198
- International Data Country Codes (DCCs), 339

International Data Numbers (IDNs), 339
 interworking, ATM, 230–231
 Inverse Multiplexing over ATM (IMA), 254
 IP RTP Priority feature, configuring, 446
 ISDN (Integrated Services Digital Network), 57, 159
 ISDN Digital Subscriber Line (IDSL), 288

J

jitters, 173. *See also* LFI
 JPEG (Joint Photographic Experts Group), 415

K

keepalives, configuring, 74, 198

L

LAPF (Link Access Procedures to Frame), 315, 321
 latency, compression, 431
 Layer, 3
 queuing, 596
 SVC user call states, 316
 LCI (logical channel identifier), 338
 LCP (Link Control Protocol), 288
 leaky bucket algorithm, 116
 legacy Frame Relay Traffic Shaping feature,
 fragmentation, 554
 Lempel-Ziv compression algorithm, 415
 levels, configuring DLCI, 147
 LFI (Link Fragmentation and Interleaving), 571
 case studies, 581
 configuring, 574–582
 troubleshooting, 577–580
 line cards, VIP2, 422
 Link Access Procedures to Frame (LAPF), 315, 321
 Link Control Protocol (LCP), 288
 Link Fragmentation and Interleaving. *See* LFI
 link-layer efficiency mechanisms, 571
 links, 384–386
 bundles, 386
 LFI, 571
 load balancing, 392–397
 lists, configuring DE, 144–146

LLC (logical link control), 244
 LLQ (Low Latency Queuing), 487
 CBWFQ, 531–537
 configuring, 533
 Fragmentation at the Interface feature, 554–558
 configuring, 558–563
 troubleshooting, 561–568
 troubleshooting, 539–547
 load balancing, Multilink Frame Relay, 392–397
 local significance, DLCI assignment, 94–98
 logical channel identifier (LCI), 338
 logical link control (LLC), 244
 lookups, process switching, 114
 loss-less compression algorithm schemes, 415
 Low Latency Queuing (LLQ), 487
 LSZ algorithms, 54

M

MAC (Media Access Control) process switching, 114
 maintenance of links, 384–386. *See also*
 troubleshooting
 management, 384–386
 broadcast traffic, 54–56
 bundles, 386, 387
 congestion, 51, 483–484
 configuring, 168
 monitoring, 178–188
 queuing, 487
 RSVP, 612–617
 switched PVCs, 161
 ELMI Address Registration, 358
 links, 384–386
 network planning, 40–45
 performance, 50–54
 SNMP, 370
 map classes
 congestion, 273
 FRTS, 120–127
 SVCs, 318, 320
 mapping
 dynamic, 77–79
 end-to-end, 356
 static, 79–83
 matching, encapsulation, 72
 maximum CIR, 47

- maximum transmission unit (MTU)
 - LFI, 572
- max-reserved-bandwidth command, 611
- measurement intervals, 117
- memory, compression of, 431
- messages
 - ADD_LINK_ACK, 386
 - ADD_LINK_REJ, 387
 - control, 316
 - HELLO, 387
 - Multilink Frame Relay Link Integrity Protocols, 384–386
 - REMOVE_LINK_ACK, 388
- MIB (Management Information Base) ELMI Address Registration, 369–377
- MINCIR (Minimum CIR), 118, 272, 613
- mission-critical traffic, classifying, 50
- mixes, protocols, 41
- MLP (Multilink Point-to-Point Protocol), 571, 574
- models, Frame Relay/X.25 interworking, 334
- moderated CIR, 46
- modes
 - End-to-End Keepalive, 199
 - frame connection setup, 316
- Modular Quality of Service Command Line Interface. *See* MQC
- modules
 - CSA, 465
 - hardware/software compression, 461
- monitoring
 - Annex G, 350
 - CBWFQ, 526–531
 - Cisco Frame Relay Switching Enhancements feature, 171–188
 - compression, 432–447
 - congestion management, 178–188
 - End-to-End Keepalive, 202–211
 - Fragmentation at the Interface feature, 561–568
 - fragmentation, 467–476
 - FRTS, 127–144
 - LFI, 577–581
 - LLQ, 538–547
 - Multilink Frame Relay, 397–408
 - PIPQ, 503–511
 - PPP, 295–299
 - RSVP, 617–619
 - SVCs, 321–324
 - switched PVCs, 173–175
 - WRED, 602–605
- MQC (Modular Quality of Service Command Line Interface), 513
 - CBWFQ, 521–526
 - configuring, 514–518
- MTU (maximum transmission unit), 572
- Multilink Frame Relay, 381
 - configuring, 384
 - implementing, 389–397
 - initializing, 386–388
 - interfaces, 389
 - load balkanizing, 392–397
 - Multilink Frame Relay Link Integrity Protocol, 384–386
 - parameters, 388–392
 - routers, 390–397
 - troubleshooting, 397–408
- multimedia, ATM, 228–229
- multiplexing, 235
 - IMA, 254
 - TDM, 290
- multipoint subinterfaces, 62, 89–90

N

- Narrowband Integrated Services Digital Networks (N-ISDN), 228
- NCP (Network Control Protocol), 288
- Network Layer Protocol ID (NLPID), 292
- networks
 - broadcast traffic, 54–56
 - CIR, 45–47
 - compression design, 430
 - EMI QoS Autosense, 357–366
 - performance, 50–54
 - planning, 40–45
 - queuing, 484–487
 - configuring PIPQ, 497–503
 - hierarchical architecture, 487–495
 - PIPQ, 495–497
 - troubleshooting PIPQ, 503–511
 - RSVP, 609
 - split horizons, 58–60
 - static mapping, 82
 - subinterfaces, 60–62

- SVCs, 311–313
 - any-to-any connectivity, 313
 - bandwidth-on-demand, 313–314
 - case study, 326–329
 - configuring, 315–321
 - implementing, 318
 - monitoring, 321–324
 - topologies, 47–50
 - VCs, 56–57
 - N-ISDN (Narrowband Integrated Services Digital Networks), 228
 - NLPID (Network Layer Protocol ID), 292
 - NNI (Network-to-Network Interface), 93, 455
 - no shutdown command, 69
 - nonreversible data compression schemes, 415
 - notification
 - congestion, 124
 - ELMI Address Registration, 358–360
 - configuring, 366–369
 - MIB, 369–377
-
- O**
-
- operations, 384–392, 397–408
 - optimization. *See also* customization
 - bandwidth, 413
 - Cisco Frame Relay Switching Enhancements feature, 158–161
 - performance, 50–54
 - options
 - Adaptive Frame Relay Traffic Shaping for Interface Congestion, 274–276
 - bundles, 386–388
 - CBWFQ, 521–526
 - Cisco Frame Relay Switching Enhancements feature, 162
 - compression
 - algorithms, 429
 - CIR, 414
 - CPU, 431
 - DCP, 54
 - design, 430–432
 - Express Header configuration, 429
 - FRF.8 configuration, 439
 - FRF.9 configuration, 421–423
 - function of, 414–415
 - hardware/software, 416–418, 460–465
 - latency, 431
 - loss-less compression algorithm schemes, 415
 - memory, 431
 - monitoring, 432–447
 - nonreversible data compression schemes, 415
 - payloads, 435
 - Predictor, 416
 - ratios, 416, 432
 - RTP header configuration, 426–429, 444
 - schemes, 418–420
 - speed, 431
 - Stacker, 415
 - TCP/IP, 423, 441
 - troubleshooting, 447
 - congestion management, 168. *See also* congestion dynamic mapping, 77–79
 - ELMI, 360–369
 - encapsulation, 67–70
 - End-to-End Keepalive, 197–202
 - Express Header Compression, 429
 - Fragmentation at the Interface, 552–556
 - Frame Relay IP RTP Priority feature, 446
 - FRF.12 Fragmentations, 460
 - FRF.5, 255–262
 - FRF.8.1, 262–265
 - FRTS, 119–120
 - associating map classes, 125–127
 - BECN adaptive shaping, 117–118
 - broadcast queues, 146–147
 - DE, 144–146
 - DLCI priority levels, 147
 - enabling, 113–117
 - ForeSight adaptive shaping, 118–119
 - generic traffic shaping, 147–148
 - map classes, 120–125
 - monitoring, 127–144
 - overview of, 112–113
 - hardware compression, 461–465
 - keepalives, 74
 - hierarchical queuing architecture, 487
 - LAPF parameters, 321
 - LLQ, 533
 - LMI, 70–77
 - local significance, 94–98

- MQC, 514–518
- Multilink Frame Relay, 384
 - initializing, 386–388
 - load balancing, 392–397
 - Multilink Frame Relay Link Integrity Protocol, 384–386
 - parameters, 388–392
 - routers, 390–397
- packet-by-packet payload compression, 420
- parameters, 339
- PIPQ, 497–503
- policing, 166
- PPP
 - case study, 301–308
 - frame formats, 291–293
 - interfaces, 293–295
 - monitoring, 295–299
 - requirements, 287–288
 - RFC, 1973 implementation, 288–291
- routers, 574–582
- RSVP, 614–619
- RTP header compression, 426–429
- static mapping, 79–83
- subinterfaces, 83–90
- SVCs, 315–324
- switches, 90–94
- TCP/IP header compression, 423–426
- threshold queue depth, 272
- traffic shaping, 164
- UFM ports, 363
- virtual template interfaces, 293, 574
- WFQ interfaces, 521
- WRED, 599–602
- X.25, 336–344
- outgoing switched PVCs, configuring, 164
- output
 - compression, 435
 - show interface, 142
 - throttling, 138
- oversubscription, troubleshooting, 110–111

P

- packet header compression schemes, 419
- packet-by-packet payload compression configuration, 420

- packets
 - compression, 53
 - congestion, 270–274
 - dropping, 594–599
 - configuring WRED, 601–604
 - troubleshooting WRED, 602–605
 - End-to-End Keepalive, 205
 - FRTS, 113
 - real-time, 577
 - SAP, 494
 - Tail Drop, 597
- PAP (Password Authentication Protocol), 287
- parameters
 - FRTS, 120–125
 - LAPF, 321
 - Multilink Frame Relay, 388–392
 - policing, 166
 - QoS, 356
 - X.25 SVC connections, 339
- partially meshed networks, static mapping, 82
- partially meshed topologies, 49, 61
- passive TCP/IP header compression, 424. *See also* TCP/IP
- passive-reply modes, End-to-End Keepalive, 200
- Password Authentication Protocol (PAP), 287
- patterns, traffic, 42. *See also* compression
- payload type (PT), 230
- payloads
 - compression, 435
 - data payload compression schemes, 419
 - FRF.9
 - compression, 421–423
 - verifying, 439
 - packet-by-packet compression, 420
- peers, End-to-End FRF.12 Fragmentation, 457
- performance
 - Adaptive Frame Relay Traffic Shaping for Interface Congestion, 274–276
 - bundles, 386–388
 - CBWFQ, 521–526
 - Cisco Frame Relay Switching Enhancements feature, 162
 - compression
 - algorithms, 429
 - CIR, 414
 - CPU, 431
 - DCP, 54
 - design, 430–432

- Express Header configuration, 429
- FRF.8 configuration, 439
- FRF.9 configuration, 421–423
- function of, 414–415
- hardware/software, 416–418, 460–465
- latency, 431
- loss-less compression algorithm schemes, 415
- memory, 431
- monitoring, 432–447
- nonreversible data compression schemes, 415
- payloads, 435
- Predictor, 416
- ratios, 416, 432
- RTP header configuration, 426–429, 444
- schemes, 418–420
- speed, 431
- Stacker, 415
- TCP/IP, 423, 441
- troubleshooting, 447
- congestion management, 168. *See also* congestion
- dynamic mapping, 77–79
- ELMI, 360–369
- encapsulation, 67–70
- End-to-End Keepalive, 197–202
- Express Header Compression, 429
- Fragmentation at the Interface, 552–556
- Frame Relay IP RTP Priority feature, 446
- FRF.12 Fragmentations, 460
- FRF.5, 255–262
- FRF.8.1, 262–265
- FRTS, 119–120
 - associating map classes, 125–127
 - BECN adaptive shaping, 117–118
 - broadcast queues, 146–147
 - DE, 144–146
 - DLCI priority levels, 147
 - enabling, 113–117
 - ForeSight adaptive shaping, 118–119
 - generic traffic shaping, 147–148
 - map classes, 120–125
 - monitoring, 127–144
 - overview of, 112–113
- hardware compression, 461–465
- keepalives, 74
- hierarchical queuing architecture, 487
- LAPF parameters, 321
- LLQ, 533
- LMI, 70–77
- local significance, 94–98
- MQC, 514–518
- Multilink Frame Relay, 384
 - initializing, 386–388
 - load balancing, 392–397
 - Multilink Frame Relay Link Integrity Protocol, 384–386
 - parameters, 388–392
 - routers, 390–397
- packet-by-packet payload compression, 420
- parameters, 339
- PIPQ, 497–503
- policing, 166
- PPP
 - case study, 301–308
 - frame formats, 291–293
 - interfaces, 293–295
 - monitoring, 295–299
 - requirements, 287–288
 - RFC, 1973 implementation, 288–291
- routers, 574–582
- RSVP, 612–617
- RTP header compression, 426–429
- static mapping, 79–83
- subinterfaces, 83–90
- SVCs, 315–324
- switches, 90–94
- TCP/IP header compression, 423–426
- threshold queue depth, 272
- traffic shaping, 164
- UFM ports, 363
- virtual template interfaces, 293, 576
- WFQ interfaces, 519
- WRED, 599–602
- X.25, 336–344
- permanent virtual circuit (PVC), 287
- per-PVC level queues, 522
- physical interfaces, 84. *See also* interfaces
- ping utility, SVCs, 324
- PIPQ (PVC Interface Priority Queuing), 495–497
 - configuring, 497–503
 - troubleshooting, 503–511

- planning. *See also* configuration
 - bandwidth provisioning, 43
 - CIR subscription, 45–47
 - ERP, 40
 - networks, 40–45
 - backing up VCs, 56–57
 - customizing topologies, 47–50
 - managing broadcast traffic, 54–56
 - performance management, 50–54
 - split horizons, 58–60
 - subinterfaces, 60–62
- platforms
 - Cisco MC3810, 253
 - support, 253
- Point-to-Point Protocol. *See* PPP
- point-to-point subinterfaces, configuring, 87–90
- poison reverse, 58
- policies, traffic, 600
- policing, 160
 - incoming switched interfaces, 166
 - ingress interfaces, 175–178
 - parameters, 166
- policy-map global configuration command, 556
- ports, UFM, 363. *See also* connections; networks
- PPP (Point-to-Point Protocol), 287
 - case study, 301–308
 - frame formats, 291–293
 - monitoring, 295–299
 - requirements, 287–288
 - RFC, 1973 implementation, 288–291
 - virtual access interfaces, 293–295
 - virtual template interfaces, 293–295
- PQ (priority queuing), 52, 485
 - CBWFQ, 531–537
 - PIPQ, 495–497
 - configuring, 497–503
 - troubleshooting, 503–511
- Predictor compression algorithm, 416
- preferences
 - Adaptive Frame Relay Traffic Shaping for Interface Congestion, 274–276
 - bundles, 386–388
 - CBWFQ, 521–526
 - Cisco Frame Relay Switching Enhancements feature, 162
 - compression
 - algorithms, 429
 - CIR, 414
 - CPU, 431
 - DCP, 54
 - design, 430–432
 - Express Header configuration, 429
 - FRF.8 configuration, 439
 - FRF.9 configuration, 421–423
 - function of, 414–415
 - hardware/software, 416–418, 460–465
 - latency, 431
 - loss-less compression algorithm schemes, 415
 - memory, 431
 - monitoring, 432–447
 - nonreversible data compression schemes, 415
 - payloads, 435
 - Predictor, 416
 - ratios, 416, 432
 - RTP header configuration, 426–429, 444
 - schemes, 418–420
 - speed, 431
 - Stacker, 415
 - TCP/IP, 423, 441
 - troubleshooting, 447
 - congestion management, 168. *See also* congestion dynamic mapping, 77–79
 - ELMI, 360–369
 - encapsulation, 67–70
 - End-to-End Keepalive, 197–202
 - Express Header Compression, 429
 - Fragmentation at the Interface, 552–556
 - Frame Relay IP RTP Priority feature, 446
 - FRF.12 Fragmentations, 460
 - FRF.5, 255–262
 - FRF.8.1, 262–265
 - FRTS, 119–120
 - associating map classes, 125–127
 - BECN adaptive shaping, 117–118
 - broadcast queues, 146–147
 - DE, 144–146
 - DLCI priority levels, 147
 - enabling, 113–117
 - ForeSight adaptive shaping, 118–119
 - generic traffic shaping, 147–148
 - map classes, 120–125
 - monitoring, 127–144
 - overview of, 112–113
 - hardware compression, 461–465

- keepalives, 74
- hierarchical queuing architecture, 487
- LAPF parameters, 321
- LLQ, 533
- LMI, 70–77
- local significance, 94–98
- MQC, 514–518
- Multilink Frame Relay, 384
 - initializing, 386–388
 - load balancing, 392–397
 - Multilink Frame Relay Link Integrity Protocol, 384–386
 - parameters, 388–392
 - routers, 390–397
- packet-by-packet payload compression, 420
- parameters, 339
- PIPQ, 497–503
- policing, 166
- PPP
 - case study, 301–308
 - frame formats, 291–293
 - interfaces, 293–295
 - monitoring, 295–299
 - requirements, 287–288
 - RFC, 1973 implementation, 288–291
- routers, 574–582
- RSVP, 612–617
- RTP header compression, 426–429
- static mapping, 79–83
- subinterfaces, 83–90
- SVCs, 315–324
- switches, 90–94
- TCP/IP header compression, 423–426
- threshold queue depth, 272
- traffic shaping, 164
- UFM ports, 363
- virtual template interfaces, 293, 574
- WFQ interfaces, 519
- WRED, 599–602
- X.25, 336–344
- premium traffic class, 525
- priority, configuring DLCI levels, 147
- priority queuing (PQ), 52, 485
 - CBWFQ, 531–537
 - PIPQ, 495–497
 - configuring, 497–503
 - troubleshooting, 503–511
- processing
 - switching, 114
 - X.25, 336–344
- proprietary fragmentation formats, 466
- protocols
 - broadcast traffic, 55
 - CHAP, 287
 - DCP, 54
 - End-to-End Keepalive, 197–201
 - configuring, 201–202
 - monitoring, 202–211
 - troubleshooting, 211–212
 - Frame Relay, 229–230
 - LCP, 288
 - mixes, 41
 - MLP
 - enabling, 574
 - LFI, 573
 - Multilink Frame Relay Link Integrity, 384–386
 - NCP, 288
 - PAP, 287
 - PPP, 287
 - RIP, 55
 - RSVP, 609
 - SNAP, 244
 - SNMP
 - ELMI Address Registration, 367
 - MIB agents, 370
 - UDP headers, 426
- provisioning bandwidth, 43
- PT (payload type), 230
- PVCs (permanent virtual circuits), 287
 - bandwidth-on-demand, 313–314
 - compression, 54
 - configuring, 164
 - monitoring, 173–175
 - queuing, 488
 - SVCs
 - comparing, 314–315
 - comparing to, 312
 - switched
 - configuring FRF.12 Fragmentation, 460
 - FRF.12 Fragmentation support, 457–459
 - traffic shaping, 159

Q

- Q.933 operations, 73, 315
- QoS (Quality of Service), 357–366. *See also* performance
- questions, answers to review, 623–641
- queuing, 52, 484–491
 - broadcasts, 146–147
 - CBWFQ, 518–520
 - configuring, 520–526
 - LLQ/PQ, 531–537
 - troubleshooting, 526–531
 - congestion, 270–274
 - CQ, 52
 - depth, 272
 - Fragmentation at the Interface feature, 552–556
 - configuring, 556–561
 - troubleshooting, 561–568
 - hierarchical architecture, 487
 - Layer, 3, 594
 - LLQ, 538–547
 - map classes, 121
 - PIPQ, 495–497
 - configuring, 497–503
 - troubleshooting, 503–511
 - PQ, 52
 - Tail Drop, 595
 - WFQ, 519

R

- Random Early Detection (RED), 506, 596
- rates
 - output, 138
 - traffic, 139
- ratios, compression, 416, 432
- real-time applications, 42
 - bandwidth, 43
 - LFI, 572
- real-time interactive traffic, RSVP, 609–611
- real-time packets, 577
- real-time traffic, 573
- RED (Random Early Detection), 506, 596
- reduction of CIR, 414
- redundancy services, 56

- registration of ELMI addresses, 358–360
 - configuring, 366–369
 - MIB, 369–377
- regulation of output traffic rates, 139
- remote sites, any-to-any connectivity, 313
- REMOVE_LINK messages, 388
- REMOVE_LINK_ACK messages, 388
- reply mode, End-to-End Keepalives, 200
- request mode, End-to-End Keepalives, 200
- requests, End-to-End Keepalives, 198
- requirements
 - bandwidth, 40
 - PPP, 287–288
- reservable-queues option, 519
- reservation services, bandwidth, 612
- resiliency, verifying bundles, 404
- Resource Reservation Protocol. *See* RSVP
- restrictions
 - FRF.12 Fragmentation, 460
 - Multilink Frame Relay, 389
 - PIPQ, 497
- review questions, answers to, 623–641
- RFC, 1973 implementation, PPP, 288–291
- RIP (Routing Information Protocol), 55
- Route Switch Processor (RSP), 417
- routers
 - Annex G, 347
 - CBWFQ, 523
 - Cisco, 2600 series, 254
 - Cisco, 3600 series, 254–255
 - Cisco, 7200 series, 255
 - Cisco Frame Relay Switching Enhancements
 - feature
 - configuring, 162
 - monitoring, 171–188
 - compression
 - algorithms, 429
 - CIR, 414
 - CPU, 431
 - DCP, 54
 - design, 430–432
 - Express Header configuration, 429
 - FRF.8 configuration, 439
 - FRF.9 configuration, 421–423
 - function of, 414–415
 - hardware/software, 416–418, 460–465
 - latency, 431

- loss-less compression algorithm schemes, 415
- memory, 431
- monitoring, 432–447
- nonreversible data compression schemes, 415
- payloads, 435
- Predictor, 416
- ratios, 416, 432
- RTP header configuration, 426–429, 444
- schemes, 418–420
- speed, 431
- Stacker, 415
- TCP/IP, 423, 441
- configuring, 66
- congestion, 483–484
- edge, 459
- ELMI QoS Autosense, 357–366
- End-to-End Keepalives, 201–202
- flow-based WRED, 598
- Fragmentation at the Interface feature, 556
- FRF.9 payload compression, 423
- LFI
 - case studies, 581
 - configuring, 574–582
 - troubleshooting, 579–582
- LLQ, 536
- Multilink Frame Relay, 390–397
- subinterfaces, 60–62
- switches, 90–94
- Routing Information Protocol (RIP), 55
- RSP (Route Switch Processor), 417
- RSVP (Resource Reservation Protocol), 609–611
 - configuring, 612–617
 - troubleshooting, 617–619
- RTP (Real-time Transport Protocol)
 - header compression configuration, 426–429
 - verifying, 444
- data payload, 419
- packet header, 419
- packet-by-packet payload configuration, 420
- fragmentation, 455, 467–476
 - FRF.11, 465–466
 - FRF.12, 455–465
- segmentation and reassembly (SAR), 229
- serial interfaces
 - encapsulation, 67–70
 - ISDN B channels, 159
 - X.25, 336–344
- serialization, 571
- Service Advertising Packets (SAP), 494
- service-policy command, 518
- services
 - bandwidth reservation, 610
 - SVCs
 - configuring, 315–321
 - implementing, 318
 - monitoring, 321–324
 - user-on-demand, 313–314
- shape command, 522
- shaping
 - adaptive
 - BECN, 117–118
 - Firesight, 118–119
 - generic traffic, 147–148
 - subrate, 554, 565
 - traffic, 51, 109
 - Adaptive Frame Relay Traffic Shaping for Interface Congestion, 274
 - congestion, 271–274
 - ELMI QoS Autosense, 358
- show commands
 - connections, 98–101
 - LFI, 577–580
 - MFR, 397–408
 - show compress command, 438, 465
 - show frame-relay end-to-end keepalive command, 204
 - show frame-relay fragment command, 470
 - show frame-relay lmi command, 71
 - show frame-relay lmi privileged EXEC mode, 100
 - show frame-relay lmi privileged EXEC mode command, 100
 - show frame-relay map command, 82, 100, 321

S

- SAP (Service Advertising Packets), 494
- SAR (segmentation and reassembly), 229
- saving bandwidth, 413
- schemes
 - compression, 418–419

- show frame-relay pvc command, 100, 130, 182, 240, 365, 490
 - show frame-relay qos-autosense command, 364
 - show frame-relay route commands, 101
 - show frame-relay vofr global EXEC command, 473
 - show interface command, 70, 142
 - show interface global EXEC command, 322
 - show interface serial command, 337
 - show interface serial privileged EXEC mode command, 98
 - show interface serial type/number global EXEC command, 277
 - show interface type slot/port privileged EXEC mode command, 69
 - show ip tcp header-compression command, 465
 - show policy-map privileged EXEC command, 526
 - show traffic-shape command, 132
 - show x25 map command, 343
 - signaling
 - RSVP, 609
 - SVC operations, 316
 - sizing
 - fragments, 575
 - frames, 53
 - SMDS (Switched Multimegabit Data Service), 147
 - SNAP (Subnetwork Access Protocol), 244
 - SNMP (Simple Network Management Protocol)
 - ELMI Address Registration, 367
 - manager, 370
 - snmp-server community command, 368
 - software
 - compression, 416–418, 461
 - FRF.9 payload compression, 439
 - source service-assess point (SSAP), 247
 - speed, compression, 431
 - split horizons
 - interfaces, 62
 - subinterfaces, 83–86
 - troubleshooting, 58–60
 - SSAP (source service assess-point), 247
 - Stacker compression algorithm, 415
 - star topologies, 48
 - static compression ratios, 432
 - static mapping, configuring, 79–83
 - status
 - End-to-End Keepalive, 207
 - keepalives, 198
 - subinterfaces
 - configuring, 83–86
 - map classes
 - associating, 126
 - point-to-point, 87–90
 - troubleshooting, 60–62
 - Subnetwork Access Protocol (SNAP), 244
 - subrate shaping
 - adding, 565
 - interfaces, 554
 - subscriptions
 - Frame Relay, 44
 - planning, 45–47
 - support. *See also* troubleshooting
 - platforms, 253
 - RSVP, 612–617, 617–619
 - SVCs (switched virtual circuits), 311–313
 - any-to-any connectivity, 313
 - bandwidth-on-demand, 313–314
 - case study, 326–329
 - compression, 54
 - configuring, 164, 315–321
 - congestion management, 161
 - FRF.12 Fragmentation, 460
 - implementing, 318
 - monitoring, 173–175, 321–324
 - PVCs, 314–315
 - traffic shaping on, 159
 - X.25, 339
 - switches
 - Cisco Frame Relay Switching Enhancements
 - feature, 158–161
 - configuring, 90–94
 - ELMI QoS Autosense, 357–358, 360–366
 - QoS, 356
 - switching
 - enabling, 162
 - Express Header Compression, 429
 - fast, 115
 - process, 114
 - synchronization of compression, 415
-
- ## T
- T_HELLO timers, 386
 - Tail Drop, 595
 - troubleshooting, 602–605
 - WRED, 600

- TCP (Transmission Control Protocol), 597
- TCP/IP (Transmission Control Protocol/Internet Protocol)
 - compression configuration, 423–426
 - verifying compression, 441
- TDM (time division multiplexing), 290
- tearing down
 - bundles, 386–388
 - links, 384–386
- templates
 - creating, 574
 - virtual interfaces, 293–295
- thresholds, queue depth, 272
- throttling output, 138
- time-division multiplexing (TDM), 290
- timers
 - End-to-End Keepalive, 198
 - T_HELLO, 386
- token bucket algorithms, 116
- tools, ping, 324
- topologies
 - fully meshed, 48
 - options, 47–50
 - partially meshed, 49, 61
 - star, 48
- traffic
 - Adaptive Frame Relay Traffic Shaping for Interface Congestion, 274
 - Annex G, 334–336
 - ATM, 228–229
 - broadcast, 54–56
 - classes, 521–526
 - class-map commands, 515–518
 - compression
 - algorithms, 429
 - CIR, 414
 - CPU, 431
 - DCP, 54
 - design, 430–432
 - Express Header configuration, 429
 - FRF.8 configuration, 439
 - FRF.9 configuration, 421–423
 - function of, 414–415
 - hardware/software, 416–418, 460–465
 - latency, 431
 - loss-less compression algorithm schemes, 415
 - memory, 431
 - monitoring, 432–447
 - nonreversible data compression schemes, 415
 - payloads, 435
 - Predictor, 416
 - ratios, 416, 432
 - RTP header configuration, 426–429, 444
 - schemes, 418–420
 - speed, 431
 - Stacker, 415
 - TCP/IP, 423, 441
 - FRTS, 109
 - LFI, 571
 - LLQ, 538–547
 - mission-critical, 50
 - patterns, 42
 - policies, 602
 - policing, 160
 - protocol mixes, 41
 - RSVP, 609–611
 - shaping, 51
 - configuring, 164
 - congestion, 271–274
 - ELMI QoS Autosense, 358
 - generic, 147–148
 - on switched PVCs, 159
- translation modes, FRF.8.1, 244
- transmissions, interleaving frames, 555
- Transmission Control Protocol. *See* TCP
- Transmission Control Protocol/Internet Protocol. *See* TCP/IP
- transparent modes, FRF.8.1, 247
- troubleshooting, 58
 - Annex G, 350
 - bandwidth, 530
 - CBWFQ, 526–531
 - compression, 447
 - congestion, 270–271, 483–484
 - ATM, 240–241
 - compression, 53
 - FRF.8.1, 252
 - FRTS, 110
 - managing, 51
 - queuing, 487
 - RED, 596
 - traffic shaping, 271–274
 - WRED, 594–599
 - connections, 102–104, 207

- data rate mismatch, 111
- End-to-End Keepalive, 211–212
- fragmentation, 455, 467–476
 - FRF.11 Annex C, 465–466
 - FRF.12, 455–465
- Fragmentation at the Interface feature, 561–568
- LLQ, 538–547
- Multilink Frame Relay, 397–408
- oversubscription, 110–111
- PIPQ, 503–511
- PPP
 - case study, 301–308
 - monitoring, 295–299
- routers, 577–580
- RSVP, 617–619
- split horizons, 58–60, 83–86
- subinterfaces, 60–62
- SVCs, 324
- VCs, 56–57
- WRED, 602–605
- tunneling Annex G, 334
- types of LMI, 70–77

U

- UDP (User Datagram Protocol) headers, 426
- UFM (Universal Frame-Relay Module), 363
- UNI (User-to-Network Interface), 118, 455
- UNI DCE interfaces, policing, 161
- user call states, SVC, 316
- user requirements, planning networks, 40
- user-on-demand services, 313–314
- utilities, ping, 324

V

- values, MINCIR, 118
- Van Jacobson's algorithms, 423
- VCI (virtual circuit identifiers), 229
- VCs (virtual circuits)
 - backing up, 56–57
 - LFI
 - case studies, 581
 - configuring, 574–582
 - troubleshooting, 577–580
- point-to-point subinterfaces, 87–90

- verification
 - Adaptive Frame Relay Traffic Shaping for Interface Congestion, 276–278
 - bundle resiliency, 404
 - congestion, 178–188, 432–447
 - connections, 98–101
 - ELMI
 - Address Registration, 371
 - QoS Autosense, 361
 - encapsulation, 69
 - End-to-End Keepalive, 202–211
 - Frame Relay Switching Enhancements feature, 171–188
 - FRF.5 configuration, 258
 - FRF.9 payload compression, 439
 - PIPQ, 499
 - policing, 175–178
 - regulation of output traffic rates, 139
 - RSVP support, 614–617
 - RTP header compression, 444
 - SVC connections, 323
 - switched PVCs, 173–175
 - TCP/IP header compression, 441
- version negotiation, ELMI Address Registration, 360
- viewing compression, 435
- VIP2 (Versatile Interface Processor), 422
- virtual access interfaces, 293–295
- virtual circuit identifiers. *See* VCIs
- virtual circuits. *See* VCs
- virtual template interfaces, 293–295, 574
- VoIP (Voice over IP), 555, 572
- VPI (virtual path identifier), 229

W

- WFQ (Weighted Fair Queuing), 485
 - CBWFQ, 520
 - overview of, 519
- window events, 198
- WRED (Weighted Random Early Detection), 506, 595
 - configuring, 599–602
 - congestion avoidance mechanisms, 594–599
 - fragmentation, 555
 - Tail Drop, 600
 - troubleshooting, 602–605

X

X.121 addressing, 317, 339
X.25, 331
 Annex G, 334–336, 345–353
 configuring, 336–344

Z

zero CIR (0 CIR), 45