



## Numerics

---

2B+D (ISDN), 173  
 2Q2T (2 queues 2 thresholds), 946  
 4-QAM. *See* QAM  
 4B/5B encoding procedure (100Base-X), 113  
 10/100 switching, 489  
 10BaseT Ethernet, 110  
 10GE (10 Gigabit Ethernet) networks, 379  
 16-QAM, 308  
 64-QAM, 308  
 100BaseT2, 115–116  
 100BaseT4, 114  
 100BaseX Ethernet, 112–113  
   PMD sublayers, 112  
   4B/5B encoding, 113  
 100 Mbps Ethernet, 111  
 802.3 IPX encapsulation type, 600  
 1000BaseT Ethernet, 117–118  
   master/slave loop timing, 120  
 1000BaseX, 120–121  
   selecting components, 128

## A

---

A bit, setting, 473  
 AAA (Authentication, Authorization, and Accounting), 208  
 AAL1 (ATM adaptation layer 1), 258  
 AARP (AppleTalk Address Resolution Protocol), 612–613, 617  
   address gleanig, 618  
   AMT (address mapping table), 617  
   operation, 618  
 ABM (asynchronous balanced mode), 219  
 ABR (available bit rate), 258  
 access classes, SMDS, 191  
 Access control field (Level 2 PDUs), 194  
 access mode, switch ports, 487  
 access networks, 316  
 access servers, 48  
 Access-Control Byte field (Token Ring), 1014  
 accounting management, standardization, 88  
 ACF/VTAM (Advanced Communication Facility/Virtual Telecommunication Access Method), 633  
 acknowledged connectionless service (LLC), 220  
 acknowledgements  
   EIGRP, 679  
   RSVP, 772  
 ACLs (access control lists), 926  
 ACSE (Association Control Service Element), 565  
 active link, dual homing, 145  
 active monitor, Token Ring, 1012  
 active state, topology-table entries, 678  
 activity factor, DOCSIS, 366  
 adapative rate-based flow control, 691  
 adaptation layer  
   ATM reference model, 501–503  
   SEAL, 503  
 adaptive equalization, 343  
 adaptive pacing, 548–549  
 Address Administration fields, DSP, 561  
 Address field  
   LAPB frames, 229  
   PPP frames, 182  
   RIP packets, 759  
   SDLC frames, 217  
 address gleanig (AARP), 618  
 Address Resolution Protocol, 23, 579, 1026  
 address signaling, 256  
 addresses. *See also* addressing  
   comparing to names, 28  
   flat, 26  
   hierarchical, 26  
   mapping, 23  
   name binding, 622  
   network layer, 24  
   SNPA, 742  
   static, 27  
 addresses classes (IP), 573–574  
 addressing  
   AppleTalk, 616–617  
   ATM, 503–504  
     fields, 506  
     formats, 505  
     NSAP format, 504–505  
     private, 505  
     subnetwork model, 504  
   broadcast, 38  
   DECnet Phase IV, 651–652  
   dynamic, 27  
   entity names, 621  
   internetworks  
     data link layer, 21  
     MAC, 22

- IPv6, 590
- IPX, 599
- network layer, 560
  - end-system NSAPs, 561
  - NSAP Address fields, 560–561
- physical, 14
- SIP, 281
- SMDS, 191
- SMRP, 782
- VoATM, 260–261
- VoFR, 262–263
- X.121, 230
- adjacencies
  - NSLP, maintaining over LANs, 723
  - OSPF, 734
- adjacent channels, 330
- ADPCM (adaptive differential pulse code modulation), 264
- ADSL (Asymmetric Digital Subscriber Line), 337–339
  - CAP, 342
  - DMT, 342
    - latency, 344
    - speed, 344
  - downstream data rates, 338
  - error correction, 340
  - performance, 340
  - signaling, 342–343
  - standards, 344
- ADSP (AppleTalk Data Stream Protocol), 625
- Advanced Communication Facility/Virtual Telecommunication Access Method, 633
- advertisements (SAP), filtering, 601
- AEP (AppleTalk Echo Protocol), 624
- AFI (Address-Family Identifier) field, 759
  - RIP packets, 761
  - RIP 2 packets, 760
- AFI (Authority and Format Identifier), 560
  - ATM addresses, 504
  - VoATM addressing, 261
- AFP (AppleTalk Filing Protocol), 625–627
- agents, 86
  - SNMP, 898, 1003
- AH (authentication header), 236
- Alarm group (RMON), 894
- A-law, 257, 264
- alert signaling, 256
- Alerting message, 403–404
- allocating multicast addresses, MADCAP, 717
- ALO (At-Least-Once) transactions, 624
- alternativeCapabilitySet, creating, 407
- American National Standards Institute, 31, 344
- AMI (Alternate Mark Inversion), 345
- amplification, adaptive equalization, 343
- amplitude, 330
- AMT (address mapping table), 613
  - AARP, 617
  - timers, 618
- analog signals, 330
  - multipath, 306
- analog voice interfaces, 256
- ANDing, 578
- ANR (Automatic Network Routing), 690
- ANSI (American National Standards Institute), 31, 344
- antenna gain, 330
- antenna spacing, VOFDM systems, 315
- Anycast RP, 716
- anycasting, IPv6, 592
- AONs (all-optical networks), 374
- AppleTalk
  - AARP, 617
    - address gleaning, 618
    - AMT, 617
    - operation, 618
  - addresses, 616–617
  - AEP, 624
  - ATP, 624
  - AURP, 622–623
    - encapsulation, 623
    - exterior routers, 622
    - tunnels, 622
  - data-link layers, 612
  - DDP, 618–619
  - ELAP, 612–613
  - EtherTalk, 612
  - extended networks, 610
  - FDDITalk, 615
  - history, 607
  - implementing over EIGRP, 676
  - LocalTalk, 613
    - node IDs, 614
  - mapping to OSI reference model, 627
  - media-access implementations, 612
  - networks, 609
  - nodes, 609
  - nonextended networks, 610

- physical layers, 612
- SMRP, 779–780
- sockets, 608
- TokenTalk, TLAP, 615
- transport layer, 619
  - NBP, 620–622
  - RTMP, 620
- upper layer protocols
  - ADSP, 625
  - AFP, 627
  - ASP, 626
  - PAP, 627
  - ZIP, 626
- upper-layer protocols, 624–625
- zones, 610–611
- AppleTalk Phase 1, 607
- application layer
  - DECnet/OSI DNA, 657
  - NetWare, 602
- application layer (OSI model), 9, 17, 564, 586
  - AppleTalk, 625
  - application processes, 565–566
  - CASEs, 565
- application models, 814
- application processes, 565–566
- applications
  - distributed intelligence, 822
  - NBAR (network-based application recognition), 926
  - stovepipe, 820
  - telephony, future of, 285
  - voice/data integration, 253–254
- APPN (Advanced Peer-to-Peer Networking), 639, 689–690
  - APPN connection network, 691
  - BIUs, format, 643–644
  - border nodes, 692
  - configuration services, 641
  - COS, 686–687
  - directory services, 641
  - DLUR/S, 691
  - IBM network management, 885
  - intermediate nodes, 683
  - ISR, 690
  - least-cost path, 643
  - locate requests, 643
  - Node type 2.1 routing, 689
  - nodes, 639
  - PIUs, format, 645
  - routing services, 642
  - services, 642–643
  - session services, 643
  - session-establishment process, 643
  - TPRI, 687
- ARB (adaptive rate-based) flow control, 691
- architectures
  - AppleTalk, 612
  - ATM LANE, 512
  - ATM reference model, 499–500
    - adaptation layers, 501–503
    - physical layer, 501
  - DECnet Phase IV, 650
  - DECnet Phase IV DNA, relationship to OSI model, 650
  - DECnet/OSI, 652
  - DECnet/OSI DNA, relationship to OSI model, 652
  - IBM network management, 888
  - IS-IS, 742
  - LANs, 38–39
  - network management, 86
  - QoS, 919–923
    - end-to-end capabilities, 922–923
    - signaling, 920
  - SNA, 634–635
- Area field (DSP), 561
- areas, 19, 739
  - NLSP, 722
  - OSPF, 732–733
- ARM (asynchronous response mode), 219
- ARP (Address Resolution Protocol), 23, 579, 1026
- AS (autonomous system), 19, 732
- ASCE (Association Control Service Element), 657
- ASEs (application service elements), 564, 657
  - CASEs, 565
  - SASEs, 565
- ASN.1 (Abstract Syntax Notation 1), 657
  - identifiers, 817
  - managed objects, data types, 902
- ASP (AppleTalk Session Protocol), 624–626
- AS-path attribute (BGP), 667
- ASs (autonomous systems), 663
- assigning
  - AppleTalk addresses, 616–617
  - buckets to cache engine, 845
- associated bit rates
  - CODECs, 412
- asymmetric connections, 37

- asymmetric switching, 489
  - ATDM (asynchronous time-division multiplexing), 30
  - ATM (Asynchronous Transfer Mode). *See also* VoATM
    - AAL1, 258
    - addressing, 503–504
      - AFI (authority and format identifier), 504
      - fields, 506
      - NSAP encoding, 504–505
      - private, 505
      - subnetwork model, 504
    - cell format, 494–495
    - connection-management messages, 509
    - connections, 506, 509
    - devices, 495
    - label switching, 531
    - LANE
      - configuration, 517
      - data transfer, 518–519
      - initialization, 517
    - leaves, 506
    - MPOA, 519
    - multicasting, 507
    - reference model, 499–500
      - adaptation layers, 501–503
      - physical layer, 501
    - signaling, connection establishment, 509
    - switching, 69
      - cell delineation, 501
      - cell header format, 496–498
      - cell-rate decoupling, 501
      - endpoints, 495
      - HEC (header error control), 501
      - ILMI, 510
      - ITU-T standards, 494
      - multicast server, 507
      - network interfaces, 496
      - PNNI, 510
      - point-to-multipoint connections, overlaid, 507
      - QoS, 508
      - services, 498–499
      - signaling, 508
      - timing requirements, 502
      - VBR traffic, 502
      - VCs, 498
    - transmission path, 499
    - virtual path, 499
    - VP multicast, 507
    - ATM Forum, UNI 3.1 specification, 508
    - ATM LANE (LAN Emulation), 511
      - architecture, 512
      - components of, 514
      - connection types, 515
      - VCCs, 515
    - AToM (Any Transport over MPLS), 246
    - ATP (AppleTalk Transaction Protocol), 624
    - attacks
      - DDOS, vulnerability of Internet, 7
      - DoS, resource reservation, 20
    - attributes (BGP), 664
      - AS-path, 667
      - community, 669
      - directory entries, 817
      - local preference, 665
      - MED, 666
      - next-hop, 667
      - origin, 666
      - syntax, 817
      - weight, 664
    - AURP (AppleTalk Update-Based Routing Protocol), 622–623
      - encapsulation, 623
      - exterior routers, 622
      - tunnels, 622
    - authentication, 206
      - EAP. *See* EAP
      - PEAP, 456
    - automatic neighbor discovery, IS-IS packets, 744
    - automatic route selection, IGRP, 696
    - autonegotiation, 124–125
    - autonegotiation sublayer (Ethernet), 110
    - autonomous systems, 75, 579
    - autoreconfiguration, 1012
    - availability of resources, 421
    - available bit rate (ABR), 258
- 
- ## B
- B channels, 202
  - B8ZS (binary 8 zero substitution), 202
  - backbone, 79
    - campus networks, 131
    - CMTS, selecting, 364
    - core networks, 316
    - OSPF, 732

- back-end authentication, RADIUS for EAP, 453–454
- bandwidth, 81, 330
  - FDDI, modal dispersion, 138
  - guaranteeing, 944
  - HFC, 355
  - HSSI, 168
  - LAN switching, 489
  - modifying, 421
  - VoIP, requirements, 266–269
- Banyan VINES (Virtual Integrated Network Service), 1020
  - ARP, 1026
  - ICP, 1026
  - media access, 1020
  - network layer, 1021
  - RTP, 1025
  - transport layer services, 1027
  - upper-layer protocols, 1027
  - VIP (VINES Internetwork Protocol), 1021–1023
- baseball rule, 257
- baseband transmission, signal encoding, 106–108
- baseline wander, 107–108
- baselining QoS, 922
- basic telephony service, 256
  - analog voice interfaces, 256
  - E&M signaling, 257
  - FXS (foreign exchange service) interfaces, 256
  - ground start, 257
  - LAN-based, 285–286
  - loop start mode, 257
  - media transport, 256
  - sampling, 257
  - supervision signaling, 256
- BAsize field (Level 3 PDUs), 193
- BBN (Bolt, Beranek, and Newman), 731
- beaconing, 1012
- BECN (Backward Explicit Congestion Notification), 157–158, 162, 935
- Bellman-Ford routing algorithms, 80
- Berkeley Software Distribution, 569
- best effort traffic, 764
- best route selection
  - BGP, 671
  - metrics, 80–81
- best-effort delivery, 922
  - DDP, 618–619
  - LocalTalk, 613
- BEtag field (Level 3 PDUs), 193
- BGP (Border Gateway Protocol), 663
  - AS-path attribute, 667
  - attributes, 664, 714
  - CIDR, 664
  - community attribute, 669
  - local preference attribute, 665
  - MED attribute, 666
  - MPLS VPNs, 243–245
  - next-hop attribute, 667
  - origin attribute, 666
  - path selection, 671
  - weight attribute, 664
- BIAs (burned-in addresses), 23
- bidirectional multipoint-to-multipoint connections, ATM, 506
- binary 8 zero substitution (B8ZS), 202
- bindings (labels), 532
- BIS (border intermediate system), 752
- bit ordering, translational bridging, 471
- bit robbing, 258
- BIUs (basic information unit)
  - fields, 643–645
  - format, 643–644
- black holes, 159
  - IS-IS, 750
- blocking bridge ports, 465
- border intermediate system (BIS), 752
- border nodes, 692
- boundary functions (SNA), 683
- BPDU (bridge protocol data unit), 19, 467
- BPSK (binary phase shift keying), 308
- BRI (Basic Rate Interface), 173, 201
  - ISDN terminal adapters, 49
- bridge entities, 97
- bridging, 65–67
  - comparing to routing, 73
  - source-route, 66
  - SRB, 479
    - route selection, 480–481
  - SRT, 476
  - translational, 473–475
    - challenges of, 471–472
    - explorer frames, 472
    - ring number, 474
  - transparent, 463
    - configuration messages, 467
    - filtering, 464
    - loops, 464

- STA, 465–467
  - topology-change messages, 467–468
  - versus switching, 66
- broadband, 330
- broadcast domains, 486
- broadcast subnetworks, ES-IS, 740
- broadcasting, 38
  - directed broadcasts (XNS), 1018
  - IPv6, 591
    - anycast, 592
    - multicast, 592
    - unicast, 591
- browser-based client caching, 840
- BSD (Berkeley Software Distribution), 569
- BTA (basic trading area), 330
- buckets, assigning to cache engine, 845
- buffer credit, 861, 873
- buffering, 28
  - local bridges, 67
- building distributors, 131
- bundles, 207–208
- Burst mode, MAC addresses, 102
- BUS (Broadcast and Unknown Server), 514
  - ELAN membership, 518
- bus topologies, 38
  - LocalTalk networks, 613
- business case model, DOCSIS, 365–368
- business policies, DEN policy model, 822–823
- business PONs, 375
- byte-swapped addresses, DECnet Phase IV, 652

## C

---

- C bits, setting, 473
- C/R bit (Frame Relay), 162
- CA (Certificate Authority), EAP-TLS, 456
- cabling
  - backbone, 131
  - CDDI, 147
  - horizontal, 131
  - HSSI, 168
  - ISO/IEC 11801 cable model, 130
  - link crossover requirements, 122
  - UDP, selecting, 123
  - UTP, autonegotiation, 124–125
- CAC (connection admission control), 284
- cache engine clusters, fault tolerance, 846
- caching, 837–838
  - browser-based client caching, 840
  - Cisco Cache Engine, fresh content, 851–852
  - proxy servers, 839
  - reload/refresh command, 853
  - standalone caches, 840
  - TTL, configuring, 852
  - web pages
    - WCCP, 841–850
    - Web Cache Control Protocol, 842–843
- calculating
  - hop count, RTMP, 620
  - load, 81
  - STA, 467
- call admission gateways, 417–419
- call admission control, 271
- call clearing mode (PLP), 227
- call control management, 406–410
- call disengage, 421
- call flow
  - H.323, 274
  - MGCP, 278
  - SIP, 281, 429–431
- call legs, 399
- Call Proceeding message, 402–403
- Call Reference field (Frame Relay LMI), 163
- call setup
  - H.323, 274, 401–402
  - PLP, 227
- call signaling channels, 203
- call teardown, RLC messages, 405
- campus distributors, 131
- canonical formats, bit ordering, 472
- canureach frames, 547
- CAP (Carrierless Amplitude and Phase), 342
  - comparing to DMT, 343
- capabilities exchange (DLSw), 546–547
  - H.245 control channels, 406
- capability statements (SMI), 905
- CAR (committed access rate), 927, 939
  - D-CAR, 928
- carrier networks, switches, 47
- carrier sense multiple access collision detect.
  - See* CSMA/CD
- CAS (Channel Associated Signaling), 203, 258
- CASEs (common-application service elements), 565
- Catalyst 2924XL switch, 66
- Catalyst 6500 switch, 66
- CATV
  - DOCSIS, 351
    - business case model, 365–368
    - cable plant infrastructure, 366

- CMTS hardware specif, 363
  - CMTS ser, 360–361
  - future applications, 368
  - layer definitions, 357–359
- downstream specifications, 355–357
- head-end, 352
- HFC, bandwidth, 355
- MSOs (multiple system operators), 351
- one-way operation, 353
- RING topography, 354
- two-way operation, 353
- CBR (constant bit rate), 258, 501
- CCM (Control Channel Management), 381
- CCRSE (Commitment, Concurrence, and Recovery Service Elements), 565
- CCS (common channel signaling), 258
- CDDI (Copper Distributed Data Interface), 138, 147
- CDMA (code division multiple access), 313, 331
- cell delineation, ATM switching, 501
- cell-based MPLS, 525
  - label switching, 531
- cell-rate decoupling, 501
- cells (ATM), 18
  - format, 494–495
  - header format, 496, 498
  - setting the CLP bit, 508
- CELP (code excited linear prediction), 264
- centralized call control, 284
  - MGCP, 277
- centralized call control models, 263
- centralized multipoint conferencing, 398
- CGMP (Cisco Group Management Protocol), 707
- challenges
  - of internetworking, 7
  - of translational bridging, 471–472
- change management (IBM), 887
- Channel Associated Signaling, 203, 258
- CHAP (Challenge Handshake Authentication Protocol), 206
- characteristics
  - of directories, 818
  - of HSSI, 167–168
  - of IGRP, 695–696
  - of OSI layers, 9
  - of OSPF, 731
  - of TG, 687
- Checksum field (IDP packets), 1017
- CIDR (classless interdomain routing), 664
- CIM (Common Information Model), 813–814
  - DEN, 814–815
- CIR (committed information rate), 263
- circuit establishment, DLSw, 546–548
- Circuit Priority field (DLSw message header), 552
- circuit termination phase (SVCs), 47
- circuit-emulation services, 501
- circuit-switched calls, ISDN, 175, 178
- circuit-switched networks, ATM
  - addressing, 503–506
  - cell format, 494–495
  - connection-establishment process, 508–509
  - connection-management messages, 509–510
  - connections, 506–507
  - devices, 495
  - ILMI, 510–511
  - LANE, 511–518
  - multicasting, 507–508
  - network interfaces, 496
  - QoS, 508
  - signaling, 508–509
- Cisco 3640 routers, startup output, 54
- Cisco Cache Engine, fresh content, 851–852
- Cisco IOS Software
  - CLI command modes, 55
  - displaying version, 56–57
  - enable password, setting, 57
  - idle timer, 209
  - QoS, 917–918
    - architecture, 919–923
    - congestion, 937
    - D-CAR, 928
    - end-to-end capabilities, 922–923
    - flows, 917
    - for packetized voice, 948
    - guaranteed, 944
    - link efficiency mechanisms, 942–944
    - management, 945–946
    - MPLS, 947
    - NBAR, 928
    - on Ethernet, 946–947
    - PBR, 926–927
    - policy control architecture, 947
    - signaling, 920
    - streaming video, 949
    - tools, 918
    - within a single network element, 920–921



- reloads, 61
- router name, configuring, 57
- running configuration, viewing, 57–58
- upgrading, 61–62
- WCCP, 841–843
  - dynamic client bypass, 847, 849
  - hierarchical deployment, 843
  - network-based shared caching, 842
  - overload bypass, 847
  - reverse proxy caching, 850
  - scalable clustering, 845
  - transparent caching, 842–843
- Web Cache Control Protocol, cache engine operation, 842–843
- Cisco web site, 41
- class D addresses, 702
- classes of IP addresses, 573–574
- class of service. *See* COS
- classes of Transport Protocols (DECnet/OSI), 655
- classifying packets, 925
  - in MPLS, 536
- QoS
  - CAR, 927
  - D-CAR, 928
  - NBAR, 928
  - PBR, 926
- CLECs (competitive local exchange carriers), 393
- CLI command modes, 55
- client-aware tunneling, 241–242
- clients
  - EAP, conversations, 454
  - LECs, 514
  - MPC, 519
  - sockets, 608
  - UAC, 426
- client-transparent tunneling, 241
- clock recovery, 107
- clouds, 46
- CLP (Cell Loss Priority) bit (ATM cells), 498
  - setting, 508
- cluster controllers, 635
- clustering cache engines, 845–846
- CMIP (Common Management Information Protocol), 565
- CMNS (Connection-Mode Network Service), 559
- CMTS
  - backbone, selecting, 364
  - DOCSIS server specifications, 360–361
  - hardware specifications, 363–364
  - keepalive messages, 361
  - telco return data service, 365
- coax cable, 331
- coaxial bus topologies, Ethernet, 94
- Code field (EAP), 452
- CODECs (coder/decoders), 201, 264
  - audio, 411–414
    - master/slave determination, 408
  - bandwidth requirements, 267–269
  - capability exchanges, 406
  - comfort noise, 267
  - delay, 267, 271
  - measuring speech performance, 265–266
  - playout buffer, 270
  - VAD, 267
  - voice/data integration, 252
- codes
  - REL, 405
  - TLV, 748–749
- collision domains, 37
- collisions, 614
  - Token Ring networks, 1011
- comfort noise, 267
- Command field
  - RIP v2 packets, 760
  - RIP packets, 759
- command modes (CLI), 55
- commands
  - dialer-in-band, 209
  - ping, 581
  - show queue, 934
  - show version, 56–57
  - SNMP, 899
- Common Information Model (CIM), 813
- common-operations services (IBM), 887
- communication cost, 81
- communication phases, SVCs, 46
- communication protocols, 10
- community attribute (BGP), 669
- comparing, 318
  - AMI and HDSL, 345
  - bridges and switches, 66
  - CAP and DMT, 343
  - DLSw and SRB, 543
  - DOCSIS and OSI layers, 359
  - H.323 and MGCP, 283
  - H.323 and SIP, 280
  - HDLC and SDLC, 219

- link-state and distance vector routing
  - algorithms, 80
  - routing and bridging, 73
  - VoIP alternatives, 283
  - WLAN standards, 318
  - X.25 and Frame Relay, 153
- competitive local exchange carriers (CLECs), 393
- complexity, QAM/DFE, 311
- compliance statements (SMI), 905
- components of ATM LANE, 514
- composite metric (IGRP), calculating, 696
- compression schemes
  - ADPCM, 264
  - presentation layer (OSI), 16
- computer telephony integration, 253
- concentrators, FDDI, 141
- confederation, 752
- conferencing, MCU, 398
- configuration
  - ES-IS, 740–742
  - LANE, 517
  - Setup messages, H.323 network devices, 401–402
- configuration management (IBM), 886
  - standardization, 87–88
- configuration messages, transparent bridging, 467
- configuration mode, 55
- configuration services, APPN, 641
- configuring
  - router name, 57
  - Web caching, TTL, 852
- confirmation messages (RSVP), 771
- CONFREQ (configure request), 206
- congestion
  - flow control, 28
  - Frame Relay, controlling, 157–158
- congestion management, 920, 928
  - class-based WFQ, 935–936
  - custom queuing, 930
  - FIFO queuing, 929
  - flow-based WFQ, 931–935
  - priority queuing, 929–930
- congestion-avoidance methods, 937
  - flow RED, 938–939
  - WRED, 937–938
- Connect message, 404
- connecting FDDI devices, 140–141
- connection establishment
  - PPP, 205–207
  - TCP, 582
- connectionless network service, 559
- connectionless transport protocols, 20
- connectionless transport service, 562
- connection-management messages (ATM), 509
- connection-oriented network service, 559
  - LLC, 219
- connection-oriented transport protocols, 20, 562
- connections
  - asymmetric, 37
  - ATM, 506
  - ATM LANE, 515
  - MGCP, 277
  - SS7 networks, VoIP, 431
- connectivity
  - dialup. *See* dialup
  - RSVP, tunneling, 770
  - WANs, 47
- CONP (Connection-Oriented Network Protocol), 559
- constant bit rate (CBR), 258, 501
- containment, 811–81
- contention, LANs, 37
- context-sensitive help (CLI), 56
- control component of MPLS, 532
- control connections (LANE), 515
- Control field
  - LAPB frames, 229
  - PPP frames, 183
  - SDLC frames, 217
- control information, OSI layers, 12
- control message header, DLSw, 550–553
- control messages, IGMP, 708
- control plane, G.ASON, 383
- control points (CPs), 637
- controlled-delay service, 765
- convergence, 77
  - EIGRP, 675
- conversations, EAP, 454
- converters (RF systems), 331
- converting analog signals to digital, 257–258
- copying images to Flash memory, 62
- core networks, 316
  - optical, 374
- COS (class of service), 642, 685
  - APPN routing, 686–687
  - subarea routing, 685

- cost, IPv6, 593
- cost savings of voice/data integration, 252–253
- counter-rotating rings, FDDI, 137
- counters (SNMP SMI), 903
- CPE (customer premises equipment), 171
  - wireless technologies, 315
- CPs (control points), 637
- CP-to-CP sessions, 641
- CRC (cyclical redundancy check), 29
  - Frame Relay, 158
- CRC field (Level 2/3 PDU), 195–195
- creating SMRP groups, 785
- CS (convergence sublayer), AAL3/4, 503
- CSA-CELP (conjugate structure algebraic CELP), 264
- CSMA/CD (carrier sense multiple access collision detect), 36–37, 100–102, 614
  - half-duplex, 37
  - switching, 125–126
- CSNP (complete sequence number packet), 724
- CSU/DSU, 49
- CTI (computer telephone integration), 253
- cut-through switching, 66–68, 488
- CVM (Cisco Voice Manager), 284

## D

---

- D channel, LAPD, 175
- DA (destination address), Ethernet frames, 98
- DAC (dual-attachment concentrator), FDDI, 141
- DAP (Data-Access Protocol), 656
- DARPA (Defense Advanced Research Projects Agency), 569
- DAS (dual-attachment station) ports, 140
- data (information units), 12
- data communication equipment. *See* DCE
- data communications standards, 203–205
- data compression schemes, OSI presentation layer, 16
- Data field
  - Ethernet frames, 99
  - FDDI frames, 146
  - LAPB frames, 229
  - PPP frames, 183
- data flows, 765
  - flow specifications, QoS, 766
  - RSVP, 764
    - reservations, 766
    - traffic types, 765

- sessions, 765
- data link layer (OSI model), 9, 14–15, 558
  - LAPB (Link Access Procedure, Balanced), 228
  - LLAP, CSMA/CA, 614
  - media access, DECnet, 653
- data link layer (DNA), 650
- data link layer addresses, 21
- data link layers (AppleTalk), 612
- data link protocols, DQDB, 190–191
- data links, LMDS, 318
- data modeling, 809
  - containment, 811–812
- data terminal equipment. *See* DTE
- data transfer
  - LANE, 518–519
  - PVCs, 47
  - SVCs, 46
- data transfer mode (PLP), 227
- data transmission process, ELAP, 613
- data units, 19
- data/command frames (Token Ring), fields, 1014
- databases
  - LSDB, 744
  - MIBs, 900
- data-direct VCCs, 515
- datagrams, 18
- data-stream service, 1027
- dB (decibel), 331
- DBS (direct broadcast satellite), 351
- D-CAR (distributed CAR), 928
- DCC (data country code), ATM private addresses, 505
- DCE (data circuit-terminating equipment), 154–155
  - X.25, 223
- DCE (data communication equipment), 94
  - modems, 203, 205
- DDCMP (Digital Data Communications Message Protocol), 653
- DDOS (distributed denial of service) attacks, vulnerability of Internet, 7
- DDP (Datagram Delivery Protocol), 618–619
  - dynamically assigned sockets, 609
  - FLAP encapsulation, 615–616
  - packets, 627
  - transmission process, 619
- DDR (dial-on-demand routing), 47
- DE (Discard Eligibility) bit, 163
  - Frame Relay, 157–158
- decentralized multipoint conferencing, 398

- DECnet
  - history, 649–650
  - media access, 653
- DECnet Phase IV
  - addressing, 651–652
  - DNA, relationship to OSI reference model, 650
  - network application layer, 656
  - network management layer, 656
  - NSP, 655
  - routing, 654
  - session control layer, 657
  - transport layer, 655
  - Transport Protocol classes, 655
  - upper layers, 656–658
- default path, MPOA, 519
- delay
  - VoATM, 262
  - VoIP, 267, 271
- delay spread, 305
- delay-sensitive traffic, 765
- deleting SMRP groups, 785
- delta frames, 765
- demodulators, 332
- demultiplexing, 29–30
- DEN (directory-enabled networks), 814–815
  - application of, 829–830
  - business policy modeling, 822–823
  - directories, characteristics, 818
  - directory services, 815
    - intelligent networking, 823
  - in Cisco products, 830–831
  - network management, 825–827
  - policies, 825
  - schema, 814, 827
- dense mode (PIM), 713
- deploying
  - ATM LANE, 512
  - Frame Relay networks, 159–160
    - private enterprise, 161
    - public carrier-provided, 160
  - wireless solution, 317
- derivative protocols, SDLC, 218–220
- design constraints of VoIP, 266–271
- design goals
  - of routing algorithms, 77
  - of XNS, 1015
- Designated Intermediate System (DIS), 744
- designated nodes, SMRP, 783
- designated routers (OSPF), 734
- Destination Address field (FDDI), 146
- Destination host number field, IDP packets, 1017
- Destination network number field, IDP packets, 1017
- Destination socket number field, IDP packets, 1017
- destination unreachable messages, 581
- destination/next hop routing table, example, 74
- destination-based routing
  - MPLS, 528, 532
    - forwarding component, 529–530
  - QoS, 536
- deterministic networks, 37
  - Token Ring, 1012
- development of FDDI, 138
- device models, 814
- devices, 40
  - agents (SNMP), 898, 1003
  - ATM, 495
    - proxy servers, 518
  - bridges, 65, 67
    - buffering, 67
    - MAC-layer, 67
  - business policy implementation, 823
  - CableLabs Certified, 351
  - CableLabs Qualified, 351
  - CODECs, 201
  - codecs
    - bandwidth requirements, 267–269
    - delay, 267, 271
    - measuring sp, 265–266
    - VAD, 267
  - configuration management, 87–88
  - Ethernet, 94
  - FDDI, connecting, 140–141
  - Frame Relay, 154–155
  - gateways, 579
  - H.323 network, 273–274, 395–398
    - audio CODECs, 411–414
    - H.225, 400–406
    - H.225 RAS, 414–421
    - H.245, 406–410
    - H.450, 410–411
    - protocols, 398
  - hardware addresses, mapping to network addresses, 618
  - hubs, 40
  - ISDN, 171–172
  - LAN extenders, 40
  - link-layer, 65–66

- LLC, supported services, 220
- load, 81
- managed (SNMP), 898
- MGC (media gateway controller), 276
- models, 203–205
- QDM (Quality of Service Device Manager), 922, 946
- repeaters, 40
- routers
  - dial backup, 47
  - dial-on-demand, 47
- SMDS, 187
- switches, 65, 68
  - ATM, 69
  - LANs, 70
  - performance, 65
  - ports, 66
- terminal adapters, 202
- WANs, 47–48
  - access servers, 48
  - CSU/DSU, 49
  - ISDN terminal adapters, 49
  - modems, 49
  - switches, 47
- waveform codecs, 264
- X.25
  - DCE, 223
  - PAD, 224
- DFE (decision feedback equalization), 311
- DGKs (directory gatekeepers), 397
- DHSS (direct sequence spread spectrum), 312
- dial backup, 47
- dial peers, H.323 network devices, 397
- dialer interface, 209
- dialer map-based interfaces, 209
- dialer profiles, 209
- dialer-in-band command, 209
- dialup
  - AAA, 208
  - BRI, 201
  - connection costs, 210
  - dialer interface, 209
  - flexibility, 210
  - interesting traffic, 209
  - MMP, 208
  - modems, 203, 205
  - PPP
    - authentication, 206
    - connection establishment, 205–207
    - TI/EI, 202–203
    - WANs, 47
- differential ECL (emitter-coupled logic), HSSI, 168
- differentiated service (QoS), 922
  - signaling, 926
- digital certificates, PKI support with EAP, 455–456
- Digital Corporation
  - DECnet. *See* DECnet
  - DNA. *See* DNA
- digital signals, multipath, 306
- Dijkstra algorithm, 731
- directed broadcasts (XNS), 1018
- directed multicasts (XNS), 1018
- directories, 815
  - attributes, 817
  - characteristics, 818
  - hierarchical structure, 816–817
- directory gatekeepers (DGKs), 397
- directory services, 815, 818–819
  - APPN, 641
  - intelligent networking, 823
- DIS (Designated Intermediate System), 744
  - election process, 750
- disappearing member endpoints (SMRP), detecting, 786
- discovery process
  - EIGRP, 676
  - gatekeepers, 416
  - IDRP, 581–582
  - PNNI, 510
- displaying, Cisco router version, 56–57
- distance vector routing algorithms, 80, 695
- distinct reservations, 766
- distributed call management schemes, VoIP, 263
- distributed management, SNMP, 910
- Distributed Queue Dual Bus, 190
- distribution manager, NetView, 890
- distribution methods, LDP, 528
- distribution of intelligence in networked applications, 822
- distribution trees
  - shared trees, 709, 711
  - source trees, 708–709
- DIT (directory information tree), 816–817
- DLC (data link control), 636
- DLC (digital loop carrier) systems, 340
- DLC Header Length field (DLSw message header), 552

- DLCI (data-link connection identifier), 161–162
  - Frame Relay, 157
- DLSw (Data Link Switching), 541
  - adaptive pacing, 548–549
  - canureach frames, 547
  - capabilities exchange, 546–547
  - circuit establishment, 546–548
  - comparing to SRB, 543
  - flow control, 546, 548
    - granted units, 549
  - icanreach frames, 547
  - message formats, 550–553
  - SNA support, 544
  - SSP, 545
  - version 2, 541–542
- DLSw+ (Data Link Switching Plus), 542
- DLUR/S (Dependent Logical-Unit Requestor/Server), 691
- DLUS (Dependent Logical-Unit Server), 691
- DMA (direct memory access), 636
- DMT
  - comparing to CAP, 343
  - latency, 344
  - power consumption, 343
  - speed, 344
- DNA (Digital Network Architecture)
  - DECnet Phase IV, 650
    - network application layer, 656
    - network management layer, 656
    - session control layer, 657
    - upper layers, 656–657
    - user layer, 656
  - DECnet/OSI, 652
    - upper layers, 657–658
- DNIC (Data Network Identification Code) field (X.121), 230
- DNS (Domain Name System), 28
- DOCSIS (Data Over Cable Service Interface Specification), 351
  - bandwidth availability, 355–357
  - business case model, 365–368
  - cable plant infrastructure, 366
  - CMTS
    - CM server specifications, 360–361
    - hardware specifications, 363
    - Telco return data service, 365
    - uBR7246 deployment, 364
    - future applications, 368
    - layer definitions, 357–359
    - QPSK, nominal upstream data rates, 359–360
- domains, 19, 732, 739
  - IDRP, 751–752
  - NLSP, 722
  - routing, 75, 79
- DoS attacks, 796
  - resource reservation, 20
- dotted decimal notation, 572
- downstream cable specifications, 355–357
- downstream data rates, ADSL, 338
- downstream-on-demand distribution, 529
- DPT (Dynamic Packet Transport), 439–440
  - packet format, 445
  - resiliency, 443
- DQDB (Distributed Queue Dual Bus), 190
- DRP (DECnet Routing Protocol), 654
- DS (Directory Services), 565
- DS0 (digital service 0), 202
- DS1 (digital service 1), 202
- DSAP (destination service access point) field (SDLC), 220
- DSL (Digital Subscriber Line)
  - ADSL, 337–338, 340
    - CAP, 342
    - downstream data rate, 338
    - error correction, 340
    - performance, 340
    - signaling, 342–343
    - standards, 344
  - G.SHDSL, 346
  - HDSL, 345
  - HDSL-2, 346
  - IDSL, 346
  - SDSL, 345
  - VDSL, 347
- DSP (Digital Signal Processor), 251
- DSP (domain-specific part) fields, 560–561
  - ATM addresses, 504
- DSSS (direct sequence spread spectrum), 312
- DTE (data terminal equipment), 94, 154–155
  - HSSI, 167
    - characteristics, 167–168
    - peer-to-peer intelligence, 168
- DTL (designated transit list), 510
- DUAL (Diffusing Update Algorithm), 675
  - feasible successors, 676
- dual homing (FDDI), 144

- dual-ring topology
  - FDDI, 137, 142–143
- duplication of resources, 6
- DWDM (Dense Wavelength Division Multiplexing), 373
- D-WFQ (distributed weighted fair queuing), 935
- dynamic addresses, 27
  - AppleTalk, 616–617
- dynamic client bypass, WCCP, 847, 849
- dynamic routing algorithms, 79, 580
- dynamically assigned sockets, 609

## E

---

- E&M signaling, 257
- E.164 addresses, 503–504
  - ATM, NSAP encoding, 504–505
- EA (Extended Address), 162
- EAP (Extensible Authentication Protocol), 451–453
  - conversations, 454
  - implementing, 456–457
  - PKI support, 455–456
  - RADIUS, 453–454
- EAP-TLS (EAP Transport Layer Security), 456
- early token release, 1012
- EBGP (External BGP), 663
- echo cancellation, 341
- echo request messages (ICMP), 581
- ECL (emitter-coupled logic), 168
- economic advantages of voice/data integration, 252–253
- edge LSRs, 524
- efficiency of routing algorithms, 77
- egress switches, 510
- EIA (Electronic Industries Association), 31
- EIGRP (Enhanced IGRP)
  - AppleTalk implementation, 676
  - DUAL, 675
  - finite-state machine, 676
  - metrics, 678
  - neighbor discovery/recovery mechanism, 676
  - neighbor tables, 677
  - packet types, 679
  - partial updates, 675
  - protocol-dependent modules, 677
  - route-tagging, 678
  - RTP, 676
  - topology tables, 677
- EIRP (effective isotropic radiated power), 332
- ELANs (emulated LANs), joining, 518
- ELAP (EtherTalk Link Access Protocol), 612–613
- electromagnetic spectrum, 332
- ELLC (Enhanced Logical Link Control), 636
- embedded MAC addresses, translational bridging, 472
- EN (end nodes), 640
- enable passwords, setting, 57
- encapsulation, 13
  - AURP, 623
  - DDP packets, FLAP, 615–616
  - ELAP, 613
  - IEEE 802.3, 68
  - IPX, 600
  - TLAP, 615
- encoding techniques, Ethernet, 108
- end communications layer (DNA), 650
- End Delimiter field
  - FDDI, 146
  - Token Ring, 1014
- end systems (ESs), 19, 75, 739
  - point-to-multipoint connections, 506
  - polling, 86
- End System-to-Intermediate System (ES-IS), 740–742
- end-node directory service negotiation (APPN), 642
- endpoints
  - ATM, 495
  - H.245 control channel capability exchange, 406
  - master/slave determination, 407
  - MGCP, 277
  - MGs (media gateways), 276
  - SIP, 279, 421–431
- end-to-end delay, VoIP design constraints, 267
- end-to-end signaling, SIP, 421–431
- enpoints, MGCP, 276
- enterprise networks
  - DEN, 830
  - voice/data integration
    - cost savings, 253
    - web caching, 837
- entity names, 620
- entity types, 620
- entries
  - EIGRP topology tables, 677
    - route states, 678
  - IP routing tables, 580
  - RIP routing tables, 761

- EP (Error Protocol), 1019
- EPONs (Ethernet passive optical networks), 375
- error checking, 16
  - FCS field (Ethernet), 99
  - forward error-correcting codes, 108
- error correction, ADSL, 340
- error messages (RSVP), 771
- error notification, 15
- Error Protocol (EP), 1019
- error rates, modulation schemes, 308
- error-checking schemes, 29
- ES hello messages (ESHs), 740
- ESCON (Enterprise Systems Connection), 636
- ESD (end-of-stream delimiter), 113
- ESF (extended super frame), 202
- ESHs (ES hello messages), 740
- ESI (end station identifier), NSAP format ATM addresses, 504
- ESI (End System Identifier) field (ATM addresses), 506
- ES-IS (End System-to-Intermediate System), 740–742
- establishing
  - adjacencies (NLSP), 723
  - ATM connections, 509–510
  - RSVP multicast sessions, 766
  - X.25 sessions, 225
- establishment phase (SVCs), 46
- Ethernet, 38
  - 10BaseT, 110
  - 100 Mbps, 111
  - 100BaseT2, 115–116
  - 100BaseT4, 114
  - 100BaseX, 112–113
  - 1000BaseT, 117–118
    - master/slave loop timing, 120
  - 1000BaseX, 120–121, 128
  - autonegotiation, 124–125
  - autonegotiation sublayer, 110
  - baseband transmission, signal encoding, 106–108
  - baseline wander, 107
  - clock recovery, 107
  - devices, 94
  - encoding techniques, 108
  - fabric, 859
  - Gigabit Ethernet, 1000BaseT, 117–118
  - history, 93
  - intermediate nodes, 94
  - link aggregation, 131–132
  - MAC addresses, 705
  - MAC sublayer, 98
    - frame format, 98–99
    - frame reception, 104
    - frame transmission, 100–104
    - VLAN tagging option, 105
  - migrating to higher-speed networks, 132–133
  - multiple-rate, 129–131
  - network management, 132
  - NICs, multispeed, 126
  - physical layers, 106
  - QoS, 946–947
  - SRT, 476
  - switching, 125–126
  - topologies, 94
  - translational bridging, 473–475
    - challenges of, 471–472
  - transparent bridging, 65
- Ethernet version 2, IPX encapsulation type, 600
- EtherTalk, 612
- EtherTalk Link Access Protocol, 612–613
- ETSI (European Technical Standards Institute), 344
- events, MGCP, 278
- Events group (RMON), 895
- evolution of voice/data integration, 283–284
- examples
  - of destination/next hop routing table, 74
  - of SMRP transaction session, 787
- exception-notification packets, 1026
- exchange capabilities, SDP, 425–426
- execute command, IBM common operations services, 887
- explicit routes, 684–685
- explicit scopes
  - FF (fixed-filter) reservations, 767
  - SE (shared-explicit) reservations, 767
- explorer frames, 472
  - RIF field, 481
  - SRB, 480
- extended AppleTalk networks, 610
- extended DDP packets, 627
- extended long-haul networks, 378
- Extended-SuperFrames, 258
- extenders (LAN), 40



Extensible Authentication Protocol. *See* EAP  
extensions  
    EAP, 456–457  
    Frame Relay, 154  
    LMI, 158  
exterior gateways, 579  
exterior routers, 580, 622  
External BGP (EBGP), 663  
external routes, EIGRP, 678

## F

---

fabric, 859  
failure domains, 1012  
Fast Ethernet, 111  
    100BaseT2, 115–116  
    100BaseT4, 114  
    100BaseX, 112–113  
    CSMA/CD, 101  
fast fading, 307  
fault management  
    standardization, 88  
    Token Ring, 1012–1013  
fault tolerance  
    FDDI, 142  
        dual homing, 144  
        dual ring, 142–143  
        optical bypass switch, 143  
    of cache clusters, 846  
FCS (Frame Check Sequence) field  
    Ethernet frames, 99  
    FDDI frames, 146  
    Frame Relay LMI, 164  
    LAPB frames, 229  
    PPP frames, 183  
    SDLC frames, 217  
    Token Ring, 1014  
FDDI (Fiber Distributed Data Interface)  
    concentrators, 141  
    DAS ports, 140  
    development, 138  
    devices, connecting, 140–141  
    dual-ring architecture, 137  
    dual-ring topology, 142–143  
    fault tolerance, 142  
        dual homing, 144  
        dual ring, 142–143  
        optical bypass switch, 143  
    frame format, 145–146  
    modal dispersion, 138  
    multi-mode fiber, 138  
    SAS, 140  
    single-mode fiber, 138  
    specifications, 139  
    transmission media, 138  
FDDITalk, 615  
FDDITalk Link Access Protocol (FLAP), 615  
FDM (frequency-division multiplexing), 30,  
    311–313, 341  
feasible successors (EIGRP), 676  
FECN (Forward Explicit Congestion Notification),  
    157–158, 162, 935  
FEPs (front-end processors), 635  
FF (fixed-filter) reservations, 767  
FHSS (frequency hopping spread spectrum),  
    312–313  
FIB (forwarding information base), 528  
Fibre Channel, 861–862  
    addressing, 869  
    classes of service, 872  
    connection methodology, 866, 868  
    distributed fabric services, 875–876  
    fabric routing, 873  
    flow control, 873  
    frame format, 870, 872  
    port types, 864–866  
    topologies, 863  
fields  
    ATM addresses, 506  
    ATM cell headers, 497–498  
    ATM cells, 496, 498  
    BIUs, 643–645  
    configuration messages, 468  
    DDP packets, 629  
    DLSw message headers, 551–553  
    EAP, 452  
    FDDI frames, 146  
    Frame Relay, 161–162, 164  
    IDP packets, 1017–1018  
    IP packets, 571–572  
    IPX packets, 602  
    LAPB frames, 229  
    Level 1 LAN Hello packets, 728–729  
    Level 3 PDUs, 192–193  
    OSPF header, 734  
    PIUs, 645–646  
    PLP, 228

- PPP frames, 182–183
- RIF, 481–482
- RIP packets, 758–759
- RSVP message headers, 772–774
- RSVP objects, 774–775
- SDLC frames, 216–217
- SDP, 425–426
- SMRP packets, 787–788
- SNMPv1 PDUs, 913
- SNMPv2 PDUs, 912
- SRB frames, 481–482
- statusDeterminationNumber, 407
- TCP packets, 585
- TLV, 748–749
- Token Ring frames, 1013–1014
- transparent bridge configuration messages, 468
- VIP packets, 1023–1024
- WAN hello packets, 727
- FIFO queues, 929
- filtering, 464
  - frames, 66
  - SAP advertisements, 601
- Filters group (RMON), 895
- fixed wireless, 332
- Flag field
  - LAPB frames, 229
  - SLDC frames, 216
- Flag field
  - Frame Relay LMIs, 163
  - PPP frames, 182
- FLAP (FDDITalk Link Access Protocol), 615
- Flash memory, 53
- flat address space, 26
- flat routing algorithms, 79
- flexibility
  - of dialup, 210
  - of routing algorithms, 78
- flooding LSPs, 724, 749
- floor distributors, 131
- flow control, 15–16, 28, 104
  - ARB (adaptive rate-based), 691
  - DLSw, 546–548
    - adaptive pacing, 548–549
    - granted units, 549
  - SIP, 429–431
  - QoS classification, 925–927
  - TCP, 582
  - windowing, 28
- flow specifications, RSVP, 764–766
- Flow-Control Byte field (DLSw message header), 551
- flush procedure, LANE, 518–519
- flush timer, IGRP, 697
- footprints, 332
- forking, 428
- format
  - of ATM cells, 494–498
  - of ATM private addresses, 505
  - of configuration messages, 468
  - of DDP packets, 627
  - of FDDI frames, 145
    - fields, 146
  - of Frame Relay frames, 161–164
  - of IPX packets, 602
  - of LAPB frames, 229
  - of RIP 2 packets, 759
  - of RIP packets, 758–759
  - of RSVP packets
    - message header fields, 772–774
    - object fields, 774–775
  - of SDLC frames, 216–217
  - of Token Ring frames, 1013
- forward error-correcting codes, 108
- forwarding
  - LAN switches, 488
  - packets, 75
- forwarding component (MPLS), 526, 530
  - label encapsulation, 531
- forwarding information base (FIB), 528
- FQDNs (fully qualified distinguished names), 816
- fragmentation, 272
- Frame Control field (FDDI), 146
- Frame Direction field (DLSw message header), 552
- frame reception of MAC sublayer, 104
- Frame Relay, 153
  - C/R bit, 162
  - comparing to X.25, 153
  - congestion-control, 157
    - CRC, 158
    - DE, 158
  - DCEs, 154–155
  - DLCIs, 162
  - DTEs, 154–155
  - EA (Extended Address), 162
  - frames, 161–162, 164
  - implementing, 159–160
  - LMI, 154, 158, 163–164

- prioritizing voice frames, 263
- private enterprise networks, implementing, 161
- public carrier-provided networks, implementing, 160
- RS-232 specification, 155
- standardization, 154
- VCs, 155
  - DLCIs, 157
  - PVCs, 156
  - SVCs, 156
- Frame Status field
  - Token Ring frames, 1014
  - FDDI frames, 147
- frame transmission, MAC sublayer, 100–104
- frame-based MPLS, 525–526
- frames, 547
  - best-effort delivery, LocalTalk, 613
  - cut-through switching, 68
  - Ethernet, broadcast/multicast bit, 704
  - explorer, 472
    - SRB, 480
  - FDDI, 145–146, 616
  - filtering, 66
  - Frame Relay, 161–164
    - LMI, 163–164
    - standard, 161–162
  - giants, 488
  - icanreach, 547
  - I-frames (SDLC), 217
  - ISDN, physical layer, 173–174
  - LAPB, 228
    - format, 229
  - LCP, 184
  - PPP, 182–183
  - RIF, fields, 481–482
  - runts, 488
  - SDLC, 216–217
  - Token Ring
    - fields, 1013–1014
    - reservation field, 1012
    - RIF field, 472
  - VLAN-tagged, 105
- frame-status bits, 472
- framing, ESF, 202
- frequency reuse, 332
- fresh content, Cisco Cache Engine, 851–852

- freshness factor, 852
- FRF.12, 263
- FRTS (frame relay traffic shaping), 941–942
- FSC (Fiber Switch-Capable) LSRs, 380
- FSPF (Fabric Shortest Path First), 873
- FTAM (File Transfer, Access, and Management), 565
- FTTH (Fiber To The Home), 373
- full peering model (UCP), 385
- full-duplex operation, 37, 103, 582
  - LAN switching, 486
- fully connected multipoint tunnels, AURP, 623
- future of telephony applications, 285
- FXO (foreign exchange office), 256
- FXS (foreign exchange service) interfaces, 256

---

## G

- G.ASON (Automatic Switched Optical Networks), 382
  - control plane, 383
  - UCP, 383
    - overlay model, 384
    - peer model, 384–385
- G.SHDSL, 346
- gain, 332
- Garcia-Luna-Aceves, J.J., 675
- gatekeeper routed signaling (GRS), 414
- gatekeepers
  - discovery, 416
  - H.225 RAS, 414–421
  - H.323 network devices, 273, 397
  - interzone calling, 419
- gateways, 579. *See also* MGs (media gateways)
  - bandwidth, modifying, 421
  - call admission, 417–419
  - call legs, 399
  - H.323, 273
  - registration, 416
  - unregistration, 417
- gauges (SNMP SMI), 903
- GE (Gigabit Ethernet) networks, 379
- general topology subnetworks, ES-IS, 740
- generic token cards, 453
- Get operation (SNMPv1), 903
- GetBulk operation (SNMPv2), 905
  - PDU format, 912
- GetNext operation (SNMPv1), 904

- GFC (Generic Flow Control) field (ATM cells), 497
  - GFI (General Formate Identifier) field (PLP packets), 228
  - giants, 488
  - Gigabit Ethernet, 117–118
    - 1000BaseT, 117–118
    - 1000BaseX, 120–121
    - CSMA/CD, 101
  - glare, 257
  - gleaning addresses (AARP), 618
  - global addressing extension (LMI), 158
  - global internetworks, 722
  - global multicasts (XNS), 1018
  - globally scoped addresses, 703
  - glop addressing, 704
  - GMPLS (Generalized Multiprotocol Label Switching), 379
    - LMP, 380
      - CCM, 381
      - link property, 381
    - LSRs, 379–380
    - UNI, 382
  - goals
    - of network management, 87–89
    - of routing algorithms, 77
  - granted units, 549
  - graph theory, 465
  - graphic image formats, 17
  - ground start, 257
  - groups
    - capability exchanges, 407
    - CODECs, 412
    - confederation, 752
    - RMON, 894–895
  - groups (multicast), CGMP, 707
  - GRS (gatekeeper routed signaling), 414
  - GTS (generic traffic shaping), 940
  - guaranteed service (QoS), 765, 922
    - RSVP, 944
- ## H
- 
- H.232, SCNs (switched circuit networks), 274
  - H.225 RAS, 414–421
    - H.323 network devices, 400–406
  - H.245 protocol
    - H.323 network devices, 406–410
  - H.323, 272, 395–398. *See also* SIP
    - audio CODECs, 411–414
    - call flow, 274
    - comparing to MGCP, 283
    - comparing to SIP, 280
    - devices, 273–274
    - gatekeeper, 273
    - H.225, 400–406
    - H.225 RAS, 414–421
    - H.245, 406–410
    - H.450, 410–411
    - MC (multipoint controller), 274
    - MCU (multipoint control unit), 273
    - MP (multipoint processor), 274
    - point-to-point conference, 274
    - protocols, 398
    - videoconferencing, 765
  - H.450 protocol, H.323 network devices, 410–411
  - half-duplex transmission, 37, 100–102
  - handling delay, VoIP, 267
  - handshakes, 614
    - three-way, 583
  - hardware addresses, mapping to network addresses, 618
  - hardware monitor, NetView, 890
  - hardware specifications, CMTS, 363–364
  - HDLC (High-Level Data Link Control), 181, 218–219
    - comparing to SDLC, 219
    - transfer modes, 219
  - HDSL (High Bit-Rate DSL), 345–346
  - HE (Header extension) field (Level 3 PDUs), 193
  - head-end location (CATV), 352, 366
  - header compression, RTP, 267
  - Header Length field (DLSw message header), 551
  - Header Number field (DLSw message header), 551
  - headers, 12
    - 802.2, 220
    - cells, 18
    - DLSw, 550–553
    - encapsulation, 13
    - IPv6, 589–590
    - OSPF, fields, 734
    - prepending to DDP packets, 616
    - RSVP messages, 772–774
    - SAR PDUs, 503
  - HEC (header error control), 501
    - ATM cells, 498
  - HEL (Header Extension Length) field (Level 3 PDUs), 193

- hello packets, 723
    - EIGRP, 679
    - IS-IS, 744–746
    - LANs, sending over NLSP, 724
    - NLSP
      - LANs, 727–729
      - WANs, 726–727
  - Hello protocol, 24
    - OSPF, 734
  - help function, NetView, 890
  - HFC (hybrid fiber coax)
    - bandwidth, 355
    - RING topography, 354
  - hierarchical address space, 26
    - NLSP, 725
  - hierarchical deployment, WCCP, 843
  - hierarchical organization of AppleTalk
    - components, 607
  - hierarchical routing, 79, 532
    - NLSP
      - sending LAN hello packets, 724
  - hierarchical structure
    - MIBs, 900
    - of directories, 816–817
    - repositories in data modeling, 811–812
  - High Bit-Rate DSL (HDSL), 345–346
  - high-speed networks, migrating to, 132–133
  - history
    - of AppleTalk, 607
    - of DECnet, 649–650
    - of Ethernet, 93
    - of internetworking, 5–6
    - of LAN switching, 486
    - of RSVP, 763
    - of SRB, 479
    - of transparent bridging, 463
  - History group (RMON), 894
  - HLPI (Higher layer protocol identifier) field (Level 3 PDUs), 193
  - HO-DSP (High-Order Domain-Specific Part) field (ATM addresses), 506
  - holddowns, IGRP, 696
  - hold-time variable, IGRP, 697
  - hop count, 81
    - RIP, 758
    - RTMP, calculating, 620
  - hops, 599
  - horizontal cabling, 131
  - Host group (RMON), 894
  - host-intelligent routing algorithms, 80
  - hosts, ES-IS, 740–742
  - HostTopN group (RMON), 894
  - H-series recommendations (ITU-T), 272
  - HSSI (High-Speed Serial Interface), 167
    - bandwidth, 168
    - cabling, 168
    - characteristics, 167–168
    - differential ECL, 168
    - loopback testing, 168
  - HTTP caching standards, fresh content, 851–852
  - hubs, 40
- 
- IAB (Internet Activities Board), 31
  - IBGP (Interior BGP), 663
  - IBM
    - establishment controllers, 217
    - network management, 885
      - change management, 887
      - configuration management, 886
      - ONA, 888
      - operations management, 887
      - performance and accounting management, 886
      - platforms, 889–890
      - problem management, 886
      - SystemView, 888
  - SNA routing
    - APPN, 689–691
    - APPN connection networks, 691
    - COS, 685–687
    - explicit routes, 684–685
    - session connectors, 683
    - subarea routing, 688
    - TGs, 684
    - ToS, 948
    - virtual routes, 684–685
  - SRB, history of, 479
  - icanreach frames, 547
  - ICD (international code designator)
    - ATM private addresses, 505
  - ICMP (Internet Control Message Protocol), 581
  - ICP (Internet Control Protocol), 1021, 1026
  - Identifier field, EAP, 452
  - IDI (initial domain identifier), 504, 560

- idle mode (PLP), 227
- idle timer, 209
- IDN (International Data Number) field (X.121), 230
- IDP (initial domain part) fields, 560
- IDP (Internet Datagram Protocol), 1017–1018
- IDRP (ICMP Router-Discovery Protocol), 581–582
- IDRP (Interdomain Routing Protocol), 751–752
- IDSL (ISDN DSL), 346
- IEEE (Institute of Electrical and Electronic Engineers) specifications, 31
  - IEEE 802.2, LLC, 219–220
  - IEEE 802.3, 94
    - connecting to IEEE 802.5, 68
    - physical layer, 98
  - IEEE 802.5, 1009
  - IEEE802.2, headers, 220
- IEs (information elements)
  - Alerting message, 403–404
  - Call Proceeding message, 402–403
  - Call Setup message, 401
  - Connect message, 404
  - REL message, 405–406
  - RLC message, 405–406
- IETF (Internet Engineering Task Force)
  - Internet drafts, MCML (Multiclass Extensions to Multilink PPP), 942
  - Policy Framework working group, 823
- I-frames, 217, 228
- IGMP (Internet Group Management Protocol), 706–707
- IGMP snooping, 708
- IGPs (Interior Gateway Protocols), 580, 663
- IGRP (Interior Gateway Routing Protocol)
  - automatic route selection, 696
  - characteristics, 695–696
  - flush timer, 697
  - holddowns, 696
  - hold-time variable, 697
  - invalid timer, 697
  - metric, 696
  - multipath routing, 696
  - split horizon, 697
  - stability, 696–697
  - timers, 697
  - triggered updates, 696
- IKE, 238–240
- ILECs (incumbent local exchange carriers), 393
- ILMI (Integrated Local Management Interface), 510
- image formats, 17
- images, copying to Flash memory, 62
- implementing
  - ATM LANE, 512
  - EAP, 456–457
  - Frame Relay, 159–160
    - private enterprise networks, 161
    - public carrier-provided networks, 160
  - STA on bridged segments, 474
- implications of RSVP reservation styles, 767
- IMS (If-Modified-Since), 852
- IMTs (intermachine trunks), 393
- incumbent local exchange carriers (ILECs), 393
- Inform operation (SNMPv2), 905
- Information and Padding field (Level 3 PDUs), 193
- information elements (IEs). *See* IFs
- information formats
  - cells, 18
  - datagrams, 18
  - messages, 18
  - packets, 18
  - segments, 18
- information header, DLSSw, 550–553
- information modeling, 809–811
  - CIM (Common Information Model), 813–814
  - DEN, 814–815
    - application of, 829–830
    - business policy model, 822–823
    - directory services, 818–819
    - in Cisco products, 830–831
    - intelligent networking, 819, 821–822
    - network management, 825–827
    - schema, 814
    - schemata, 827
  - directories, 815
    - attributes, 817
    - characteristics, 818
  - information distribution, 818
- information modules (SNMPv2), 904
- information requests, 421
- information units, 12
- infrastructure
  - PKI, EAP support, 455–456
  - VoIP, 394
- ingress switches, 510

- initiating RSVP multicast sessions, 766
- integers (SNMP SMI), 903
- integrated IS-IS, 742
- intelligent networking
  - DEN, 819, 821–822
  - directory services, 823
- interaction between layers (OSI model), 11
- interarea routing, 732
- interdomain ISs, 19, 75
- interdomain routing algorithms, 80
- Interdomain Routing Protocol (IDRP), 751–752
- interesting traffic, 209
- interface serial number, 23
- interfaces
  - ATM, 496
  - dialer, 209
  - HSSI, 167
    - characteristics, 167–168
    - loopback testing, 168
- Interior BGP (IBGP), 663
- interior gateways, 579
- interior routers, 580
- intermachine trunks (IMTs), 393
- intermediate nodes, 94
- intermediate system (IS), 739
- Intermediate System-to-Intermediate System (IS-IS), 742–749
- internal routes, EIGRP, 678
- International Organization for Standardization.  
*See* ISO
- Internet, vulnerability of, 7
- Internet Control Protocol (ICP), 1021, 1026
- Internet Protocol Device Control (IPDC), 276
- Internet protocols, mapping to OSI layers, 569
- internetworking, 5
  - addresses
    - data link layer, 21
    - dynamic, 27
    - MAC, 22
    - mapping, 23
    - network layer, 24
    - static, 27
  - challenges of, 7
  - history of, 6
  - information formats
    - cells, 18
    - datagrams, 18
    - messages, 18
    - packets, 18
    - segments, 18
  - names, 28
  - standards organizations, 30–31
- interoperability of DEN, 826
- interzone calling, gatekeepers, 419
- intra-area routing, 732
- intradomain ISs, 19, 75
- intradomain routing algorithms, 80
- invalid timer (IGRP), 697
- IP (Internet Protocol), 570
  - address classes, 573–574
  - addressing, 572
    - RIP 2 packets, 760
  - application layer protocols, 586
  - logical AND operation, 578
  - packet format, 571–572
  - subnet masks, 575–578
- IP multicasting
  - class D addresses, 702
  - Ethernet MAC address mapping, 705
  - globally scoped addresses, 703
  - glop addressing, 704
  - IGMP, 706–707
  - Layer 2 multicast addresses, 704
  - limited scope addresses, 704
  - reserved local link addresses, 703
- IP precedence bits
  - setting, 926–927
  - weight, 934
- IP routing tables, 580
- IP spoofing attacks, 796
- IPDC (Internet Protocol Device Protocol), 276
- IPPV, 357
- IPSec, 234
  - AH, 236
  - ESP, 236
  - IKE, 238–240
  - SAs, 238
  - transport mode, 237
  - tunnel mode, 237
- IPv6
  - addressing, 590
  - broadcasting methods, 591
    - anycast, 592
    - multicast, 592
    - unicast, 591
  - packet headers, 590

IPX (Internetwork Packet Exchange), 599  
   addresses, 599  
   encapsulation types, 600  
   packet format, 602  
   SAP, 601  
     filters, 601  
   ticks, 599  
 IS (intermediate system), 19, 739  
 IS hello message (ISH) packets, 740  
 iSCSI protocol, 876  
   frame format, 877  
   services, 879–880  
 ISDN (Integrated Services Digital Network), 45  
   BRI, 201  
   devices, 171  
   frames, physical layer, 173–174  
   LAPD, 175  
   PRI, 173  
   reference points, 172  
   services, 173  
   signaling, 175, 178  
   terminal adapters, 49  
 ISH (IS hello message) packets, 740  
 ISI (intersymbol interference), 306  
 IS-IS (Intermediate System-to-Intermediate System), 742–749  
 ISL (Inter-Switch Link), 488  
 ISO (International Organization for Standardization), 31, 393  
   network management model, 87  
     accounting management, 88  
     configuration management, 87–88  
     fault management, 88  
     performance management, 87  
     security management, 88–89  
   OSI reference model, 7  
 ISO/IEC 11801 cable model, 129–131  
 isolated LANs, 6  
 ISR (intermediate session routing), 690  
 ISs (intermediate systems), 75, 82  
 ITU-T (International Telecommunications Union Telecommunications Standardization Sector), 31  
   ATM standards, 494  
     addressing, 503–504  
   G.ASON (Automatic Switched Optical Networks), 382  
     control plane, 383  
     UCP, 383–385

  H-series recommendations, 272  
     voice-coding standards, 265  
   IWF (interworking function) cards, 315

## J-K

  jitter, 270  
   joining  
     ELANs, 518  
     SMRP groups, 785  
  
   key frames, 765

## L

L2SC (Layer 2 Switch-Capable) LSRs, 379  
 L2TP (Layer 2 Tunneling Protocol), 240  
   client-aware tunneling, 241–242  
   client-transparent tunneling, 241  
   security, 243  
 L2VPNs, 245–246  
 label bindings, 528  
 label swapping, 529  
 label switching, ATM, 531  
 labels, 524  
 Lamar, Heddy, 312  
 LAN Network Manager, 890  
 LAN protocols, 10, 36  
   FDDI, 137  
 LAN switching  
 LAN-based telephony solutions, 285–286  
 LANE  
   ELAN membership, 518  
   configuration, 517  
   control connections, 515  
   data transfer, 518–519  
   flush procedure, 518–519  
   initialization, 517  
   LEC registration, 517  
   SSRP (Simple Server Redundancy Protocol), 514  
 LANE (LAN Emulation), 511  
   architecture, 512  
   components, 514  
   connection types, 515  
 LAN-PBX, 285  
 LANs (local-area networks), 5, 36. *See also* WLANs



- asymmetric connections, 37
- collision domains, 37
- collisions, 37
- contention, 37
- devices, 40
  - extenders, 40
  - hubs, 40
  - repeaters, 40
- Ethernet/IEEE802.3, 38
  - transparent devices, 65
- FDDI
  - concentrators, 141
  - DAS ports, 140
  - development, 138
  - devices, connecting, 140–141
  - dual ring topology, 142–143
  - frame format, 145–146
  - SAS, 140
  - specifications, 139
  - transmission media, 138
- full-duplex mode, 37
- isolation, 6
- LLC, 219–220
- media-access, 36
- microsegmentation, 485
- NLSP
  - adjacencies, 723
  - hello packets, 727, 729
  - receipt-confirmation process, 724
- remote bridges, 67
- ring topology, 38
- SRB, 479
  - frame format, 481–482
- star topology, 39
- switches, 37
- switching, 70
  - asymmetric, 489
  - bandwidth, 489
  - forwarding, 488
  - full-duplex operation, 486
  - history, 486
  - Layer 2, 489
  - Layer 3, 489
  - multilayer, 489
  - segmentation, 66
  - switch ports, 487
  - symmetric, 489
  - VLANs, 486, 488
- Token Ring, 1009
  - active monitor, 1012
  - determinism, 1012
  - early token release, 1012
  - failure domains, 1012
  - fault-management, 1012–1013
  - frame fields, 1013–1014
  - NAUN, 1013
  - physical connections, 1010
  - priority system, 1012
  - token-passing, 1011
- topologies, 38
- translational bridging, 473–475
  - challenges of, 471–472
- transmission methods, 38
- tree topology, 39
- LAPB (Link Access Procedure, Balanced), 219, 228–229
- LAPD (Link Access Procedure, D channel), 175
- Largest Frame Size field (DLSw message header), 552
- latency
  - cut-through switching, 68
  - DMT, 344
  - VoATM, 262
  - VoIP, 267, 271
- Layer 2 LAN switches, 489
- Layer 2 multicast addresses, 704
- Layer 2 switching, multicast, 707
- Layer 3 LAN switching, 489
- layer definitions of DOCSIS specification, 357–359
- layered information models,
  - AppleTalk protocol suite, mapping to OSI layers, 627
  - ATM reference model, 499–500
    - adaptation layers, 501–503
    - physical layer, 501
  - CIM, 813–814
  - DNA, relationship to OSI reference model, 650
  - EAP-TLS, 456
  - OSI model
    - application, 17
    - characteristics, 9
    - data link, 14–15
    - information exchange, 12–13
    - interaction between, 11
    - LAN switching, 489
    - network, 15
    - physical, 13–14

- presentation, 16
  - services, 11–12
  - session, 13, 16
  - transport, 16
- LCI (Logical Channel Identifier) field (PLP packets), 228
- LCP (Link Control Protocol), 206. *See also* NCP frames, 184
  - link quality determination, 183
  - link termination, 183
- LD-CELP (low delay CELP), 264
- LDP (Label Distribution Protocol), 525, 528, 532
- LDUP (LDAP Duplication and Update Protocol), 820
- leaking routes, 751
- learning process of transparent bridges, 463
- leased lines, 44
- least-cost path, APPN, 643
- leave group messages (IGMP), 707
- leaves, 506
- leaving SMRP groups, 785
- LECs (LAN emulation clients), 514
  - registering with LES, 517
- LECS (LAN Emulation Configuration Server), 514
- legacy DDR, 209
- LEN (low-entry networking) nodes, 639, 642, 689
- Length field
  - EAP, 452
  - Ethernet frames, 99
  - IDP packets, 1017
  - Level 3 PDUs, 193
- LES (LAN Emulation Server), 514, 517
- Level 1 routers (NLSP), 722, 739
- Level 2 PDUs, 194
- Level 2 routers (NLSP), 722, 739
- Level 3 PDUs, 189, 192–193
- Level 3 routers (NLSP), 722
- LFI (link fragmentation interleaving) 942
- limitations of IDSL, 347
- limited scope addresses, 704
- link aggregation, 131–132
- Link Control Protocol. *See* LCP
- link crossover requirements, 122
- link efficiency mechanisms, 921, 942, 944
  - LFI, 942
  - RTP header compression, 943
- link layer (OSI model), devices, 65–66
- link local addresses, 703
- link quality determination phase (LCP), 183
- link state database (LSDB), 744
- link state packets (LSPs), 744, 749
- link-access protocols, ELAP, 613
- link-establishment frames (LCP), 184
- link-failure recovery, HPR, 691
- link-maintenance frames (LCP), 184
- links
  - dual homing (FDDI), 145
  - efficiency, 921
  - point-to-point, 44, 181–182
  - reliability, 81
  - serialization delay, 921
  - wireless, LMDS, 318
- link-state advertisements, 74
- link-state routing protocols, 80
  - backbone, 732
  - NLSP, 721
    - adjacencies, 723
    - hello packets, 726–729
    - hierarchical routing, 722
    - LSPs, 724
    - reachability, 723
    - receipt-confirmation process, 724
    - WAN links, maintaining, 723
  - OSPF, 731
    - areas, 732–733
    - metrics, 735
    - packet format, 734
    - routing hierarchy, 732
    - TOS-based routing, 735
    - variable-length subnet masks, 736
    - SPF algorithm, 734
- link-termination frames (LCP), 184
- LLAP (LocalTalk Link Access Protocol), 613
- LLC sublayer (Logical Link Control), 15, 97, 219–220
  - bridging, 67
  - devices, supported services, 220
- LMDS (Local Multipoint Distribution Service), 333
  - data links, 318
- LMI (Local Management Interface), 154, 158
  - frames, 163–164
- LMI DLCI field, 163
- LMP (Link Management Protocol), 380
  - CCM, 381
  - link property, 381
- LNM (LAN Network Manager), 890
- load, 81
- local bridges, 67

- local form-session identifiers, 689
- local preference attribute (BGP), 665
- LocalTalk, 612–613
  - CSMA/CD, 614
  - node IDs, 614
  - TokenTalk, 614
- LOCATE requests (APPN), 643
- location requests, 419
- location servers, SIP, 280
- logical addresses, 24
- logical AND operation, 578
- logical tree topology, 39
- logical units (LUs), 637
- long-haul networks, 376–378
- look ahead, 270
- loop start mode, 257
- loopback testing, HSSI, 168
- loops (routing), 77
  - maintenance signaling methods, 409
  - split horizon, 697
  - transparent bridging, 464
- LOS (line of sight), 333
- lower layers of OSI reference model, 9
- low-latency queuing, 936
- LSC (Lambda Switch-Capable) LSRs, 380
- LSCs (label switch controllers), 525
- LSDB (link state database), 744
- LSP (link state packets), 744, 749
- LSPs (label-switched paths), 524
- LSRs (label switch routers), 379–380, 524
- LUs (logical units), 637
- LVCs (label virtual circuits), 524

## M

---

- MAC (Media Access Control) sublayer, 15, 98
  - addressing, 22
    - embedded, 472
    - reconciliation sublayer, 109
    - STA, 465
  - bridging, 67
  - Burst mode, 102
  - frame format, 98–99
  - frame reception, 104
  - frame transmission, 100–104
  - link aggregation, 131–132
  - VLAN tagging option, 105
- MADCAP (Multicast Address Dynamic Client Allocation Protocol), 717
- managed devices, 898
  - data representation, 902
- managed objects (MIB), 900
  - ASN.1 data types, 902
  - SMI-specific data types, 903
- management
  - call control, 406–410
  - dial peers, H.323 network devices, 397
  - SIP, 421–431
- management proxies, 86
- managing Ethernet networks, 132
- Manchester encoding, 108
  - 10BaseT Ethernet, 110
- MANs (metropolitan-area networks)
  - DQDB, 190–191
- mapping addresses, 23
  - multicast addresses to network layer (SMRP), 782
  - names to addresses, 28
- market viability, voice/data integration, 252
- marking packets, 272
- masquerading (SNMP), 906
- master/slave determination, H.323 network devices, 407
- master/slave loop timing, 1000Base-T, 120
- Matrix group (RMON), 895
- MBGP (Multiprotocol Border Gateway Protocol), 714
- MC (multipoint controller), 274
- MCML (Multiclass Extensions to Multilink PPP), 942
- MCNS (Multimedia Cable Network System Partners, Ltd.), 351
- MCU (multipoint control unit), 273, 396–398
- MDI (medium-dependent interface), 110
- measuring
  - QoS service levels, 922
  - voice quality, 265–266
- MED (multi-exit discriminator) attribute (BGP), 666
- media access
  - Banyan VINES, 1020
  - CSMA/CD, half-duplex, 100–103
  - DECnet, 653
  - XNS, 1016
- Media Gateway Control Protocol. *See* MGCP
- media-access implementations, LANs, 36
  - AppleTalk, 612
  - CSMA/CD, 36–37

- media-access protocols
  - LLAP (LocalTalk Link Access Protocol), 613
  - NetWare, 598
- media transport, basic telephony service, 256
- MEGACO, 276
- membership
  - ELANs, 518
  - multicast groups, 706–710
- memorizing OSI reference model layers, 8
- memory, 53
  - NVRAM
    - saving running configuration, 58
    - startup config, viewing, 58–59
- Message ID field (Level 2 PDUs), 194
- Message Length field (DLSw message header), 551
- Message Type field
  - DLSw message header, 551
  - Frame Relay LMI, 163–164
- messages, 18
  - Alerting, 403–404
  - ATM connection requests, negotiation, 509
  - BPDU, 467
  - Call Proceeding, 402–403
  - configuration (transparent bridging), 467
  - confirmation (RSVP), 771
  - Connect, 404
  - connection signaling requests (ATM), 509
  - connection-management (ATM), 509
  - DLSw, 550–553
  - error (RSVP), 771
  - Frame Relay VC status, 158
  - ICMP, 581
  - IGMP version 2, 707
  - ISDN, 175, 178
  - leave group (IGMP), 707
  - link-state advertisements, 74
  - MGCP, 277
  - path (RSVP), 771
  - path-error (RSVP), 771
  - RAS. *See also* RAS, 415
  - REL, 405–406
  - reservation-request, 768
  - reservation-request (RSVP), 771
  - RLC, 405–406
  - routing updates, 74
    - RIP, 757
  - RSVP, 772–774
  - Setup, H.323 network, 401–402
  - SIP, 281, 422–425
- SNMP
  - Trap PDUs, 913
  - version1, 911
  - version 2, 911
  - source-quench, 28
  - system messages, severity levels, 60
  - teardown (RSVP), 772
  - topology-change (transparent bridging), 467–468
- Metric field
  - RIPv2 packets, 760
  - RIP packets, 759
- metric-notification packets, 1026
- metrics, 74, 80–81
  - EIGRP, 678
  - IGRP, 696
  - OSPF, 735
  - RIP, 758
- metro access networks, 376
- metro optical networks, 374
- MGC (media gateway controller), 276
- MGCP (Media Gateway Control Protocol), 275–277
  - call flow, 278
  - centralized call control, 277
  - comparing to H.323, 283
  - comparing to SIP, 283
  - events, 278
  - messages, 277
  - MGC, 276
  - MGs, 276
  - reliability, 278
  - signals, 278
- MGs (media gateways), 276
- MHS (message handling service), NetWare, 602
- MHSRP (Multigroup Hot-Standby Router Protocol), 846
- MIBs (Management Information Bases), 900
- microsegmentation, 485
- microwave communication systems, QAM, 304–308
- migrating to higher speed networks, 132–133
- millimeterwave, 307
- minimizing delay on Frame Relay networks, 263
- mitigating security threats, 801
- mixed media bridging
  - SRT, 476
  - STA, 474
  - translational bridging, 473–475
- MMDS (multichannel multipoint distribution service), 333

- MMP (multichassis multilink PPP), 207–208
- mnemonics, memorizing OSI reference model layers, 8
- mobile wireless, 333
- modal dispersion, 138
- modems, 49, 203–205
  - ADSL, 338
  - ISDN terminal adapters, 49
- modes of switch ports, 487
- modification
  - bandwidth, 421
- modulation
  - ADPCM, 264
  - ADSL, 342–343
  - BPSK, symbols, 308
  - BPSK, 308
  - PCM, 264
  - PSK, 308
  - QAM, 308 311
  - QPSK, 308
- MOP (Maintenance Operations Protocol), 656
- MOS (mean opinion score), 265–266
- MP (multipoint processor), 274
- MPCs (multiprotocol clients), 519
- MPLS (Multiprotocol Label Switching), 947
  - AToM, 246
  - cell-based label-switching, 531
  - control component, 532
  - downstream on-demand distribution, 529
  - downstream unsolicited distribution, 529
  - forwarding component, 526, 530
    - label encapsulation, 531
  - frame-based, 525–526
  - hierarchical routing, 532
  - label bindings, 528
  - label swapping, 529
  - QoS, 535–536
  - traffic engineering, 751
- MPLS-based VPNs, 533–535
  - BGP, 243–245
  - L2VPNs, 245–246
- MPOA (Multiprotocol over ATM), 519
- MPS (multiprotocol servers), 519
- MSAU (multistation access unit), 1009
- MSDP (Multicast Source Discovery Protocol), 715–716
- MSOs (multiple system operators), 351
- MTP (Multicast Transaction Protocol), 782–783
- MTU (maximum transfer unit) sizes, translational bridging, 472
- Mu-law, 264
- multicast gatekeeper discovery, 416
- multiaccess networks, Hello protocol (OSPF), 734
- multicast forward VCCs, 515
- multicast forwarding
  - RPF, 711–712
  - MBGP, 714
- multicast groups
  - class D addresses, 702
  - IGMP, 706–707
  - membership, 710
- multicast routes
  - SMRP, 784
- multicast send VCCs, 515
- multicast server, 507
- multicast transfers, mixed-media networks, 475
- multicast transmission, 38
- multicast update packets
  - EIGRP, 679
- multicasting
  - ATM, 507
  - CGMP, 707
  - distribution trees
    - shared trees, 709, 711
    - source trees, 708–709
  - Ethernet MAC address mapping, 705
  - globally scoped addresses, 703
  - glop addressing, 704
  - IGMP snooping, 708
  - IPv6, 592
  - Layer 2 addresses, 704
  - Layer 2 multicast addresses, 704
  - Layer 2 switching environments, 707
  - limited scope addresses, 704
  - link local addresses, 703
  - PIM, 713
    - dense mode, 713
    - sparse mode, 713
    - sparse-dense Mode, 714
  - reserved local link addresses, 703
  - sessions, 765
    - RSVP, 766
  - SMRP
    - address management, 782
    - forwarding datagrams, 786
    - group management, 785
    - topology maps, 786

multicasting extension (LMI), 159  
 multicasts  
     directed multicasts (XNS), 1018  
     global multicasts (XNS), 1018  
 multihoming WCCP, 846  
 multilayer LAN switches, 489  
 multilink PPP, 207–208  
 multi-mode fiber (FDDI), 138  
 multipath, 304, 306  
     in analog systems, 306  
     in non-LOS environments, 307  
     ISI, 306  
     spatial diversity, 314  
 multipath routing, IGRP, 696  
 multipath routing algorithms, 79  
 multiple authentication mechanisms. *See* EAP  
 MULTIPLE\_FRAME\_ESTABLISHED, 202  
 multiple-rate Ethernet, 129–131  
 multiplexing, 16, 29–30, 582  
     statistical, Frame Relay, 153  
     VCs, X.25, 225–226  
     VLANs, 488  
 Multipoint control unit (MCU), 396, 398  
 multipoint tunnels, AURP, 623  
 multipoint-to-multipoint connections, 506  
 multispeed NICs, 126  
 MZAP (Multicast-Scope Zone Announcement Protocol), 717

---

**N**  
 name binding, 622  
 name confirmation (NBP), 622  
 name lookup (NBP), 622  
 name recognition (NBP), 622  
 names  
     comparing to addresses, 28  
     internetworks, 28  
 naming Cisco IOS routers, 57  
 NAS (Network Access Server), EAP, 453–454  
 NAUN (nearest active upstream neighbor), 1013  
 NAUs (network addressable units), 637, 688  
 NBAR (network-based application recognition), 926–928  
 NBP (Name Binding Protocol), 620–622  
 NCP (NetWare Core Protocol), 602  
 NCP (Network Control Protocol), 181, 207  
 NDS (NetWare Directory Services), 601

negotiation  
     ATM connection requests, 509  
     LCP, 206  
 neighbor discovery/recovery mechanism, EIGRP, 676–677  
 neighbors  
     LSP, 749  
     NAUN, 1013  
 NET (network entity title), 561, 741  
 NetView (IBM), 889  
 NetWare  
     application layer services, 602  
     IPX, 599  
         addresses, 599  
         SAP, 601  
     media-access protocols, 598  
     NetBIOS emulation software, 602  
     remote procedure calls, 597  
     RPC, 602  
     transport protocols, 601  
     upper-layer protocols, 602  
 NetWare Core Protocol (NCP), 602  
 NetWare Shell, 602  
 Network Access Server (NAS)  
     EAP, 453–454  
     EAP conversations, 454  
 network addresses, mapping to hardware addresses, 618  
     SNMP SMI, 903  
 network application layer  
     DECnet Phase IV, 656  
     DNA, 650  
 network control information field (Level 2 PDUs), 194  
 network entity title (NET), 741  
 network integrated web caching, 839  
 network interfaces, ATM, 496  
 network layer  
     addressing, end-system NSAPs, 561  
     Banyan VINEs, 1021  
     Hello protocol, 24  
     OSI protocol suite, 15, 558–560  
     PPP protocol configuration, 183  
     XNS, 1017  
 network layer addresses, 24  
 network management, 85, 922–923  
     accounting management, 88  
     agents, 86  
     architecture, 86

- as wireless solution, 316–317
- configuration management, 87–88
- DEN, 825–827
- Ethernet, 132
- fault management, 88
- history of, 85
- IBM
  - change management, 887
  - configuration management, 886
  - ONA, 888
  - operations management, 887
  - performance and accounting management, 886
  - platforms, 889–890
  - problem management, 886
  - SystemView, 888
- management proxies, 86
- performance management, 87
- QoS, 917–918
  - architecture, 919–923
  - flows, 917
  - signaling, 920
  - tools, 918
- security management, 88–89
- SNMP
  - commands, 899
  - data representation, 902
  - distributed management, 910
  - messages, 911–913
  - MIBs, 900
  - security, 906–907
  - version 1, 902–904
  - version 2, 904–906
- standardization, 87
- network management layer
  - DECnet Phase IV, 656
  - DNA, 650
- network models, 814
- network numbers, SMRP, 782
- network protocols, 10, 82
- network service access point (NSAP), 741
- network-based shared caching, WCCP, 842
- Next Hop field (RIP 2 packets), 760
- next hops, 75
- next-hop attribute (BGP), 667
- NICE (Network Information and Control Exchange) protocol, 656
- NICs (network interface cards), 94
  - ATM LANE, 512
  - autonegotiation, 124–125
  - multispeed, 126
  - UTP-based, selecting, 123
- NIU (network interface unit), wireless, 315
- NLMs (NetWare loadable modules), 602
- NLOS (non-line-of-sight), 333
- NLSP (NetWare Link Services Protocol), 721
  - adjacencies, 723
    - maintaining over LANs, 723
  - CSNP (complete sequence number packet), 724
  - hello packets
    - LANs, 724, 727, 729
    - WANs, 726–727
  - hierarchical addressing, 725
  - hierarchical routing, 722
  - LSPs (link-state packets), 724
  - receipt-confirmation process, 724
  - scalability, 721–722
  - WAN links, maintaining, 723
- NMSs (network management systems), 898
- OSS (Operational Support System), 316
- NNI (Network-to-Network Interface), 382–387
- NNs (network nodes), 640
- node addresses, DECnet Phase IV, 651–652
- node IDs (LocalTalk), 614
- node management, SMRP, 783
- Node type 2.1 routing, 689
- nodes
  - AppleTalk, 609
    - name binding, 622
    - reachability, 624
    - zones, 611
  - APPN, 639
  - LENs, directory services, 642
  - LocalTalk, CSMA/CA, 614
  - SDLC, 215–216
  - SNA, 638
- noise-mitigating countermeasures, CMTS, 363
- noncanonical formats, bit ordering, 472
- nonextended AppleTalk networks, 610
- non-line-of-sight microwave systems, multipath, 304–307
- notification messages, MGCP, 277
- Novell
  - IPX encapsulation types, 600
  - NLSP, 721
    - adjacencies, 723
    - hierarchical routing, 722

NRM (normal response mode), 219  
 NSAP (network service access point), 741  
 NSAP encoding  
   Address fields, 560–561  
   ATM addresses, 504–505  
   end-system NSAPs, 561  
   shortcuts, 519  
 n-selector, 561  
 NSP (Network Services Protocol), 655  
 NT1 (network termination type 1), 171  
 NT2 (network termination type 2), 171  
 NVEs (Network-Visible Entities), 620–622  
 NVRAM (nonvolatile RAM), 53  
   running configuration, saving to NVRAM, 58  
   startup config, viewing, 58–59  
 Nyquist's theorem, 201, 257

## O

object classes, RSVP, 774–775  
 object identifier (MIB), 900  
 objective scoring (voice quality), MOS tests, 265  
 object-oriented information modeling, 809–811  
   CIM (Common Information Model), 813–814  
   DEN, 814–815  
     application of, 829–830  
     business policy model, 822–823  
     directory services, 818–819  
     in Cisco products, 830–831  
     intelligent networking, 819, 821–822  
     network management, 825–827  
     schemata, 827  
   data models, hierarchical structure, 811–812  
   directories, 815  
 OCP-NNI (Optical Control Plane Network-to-Network Interface), 387  
 OCP-UNI (Optical Control Plane User Network Interface), 385–386  
 OFDM (orthogonal frequency-division multiplexing), 311, 313–314  
 ommand-control facility, NetView, 890  
 ONA (Open Network Architecture), 885, 888  
 one-time password (OTP), 453  
 one-way hash, 207  
 one-way operation, CATV, 353  
 on-pass connection establishment (ATM), 509  
 ONTs (Optical Network Terminals), 375  
 ONUs (Optical Network Units), 375  
 opaques (SNMP SMI), 903  
 Open System Interconnection. *See* OSI  
 operational model, RSVP, 768  
   general operation, 769  
   tunneling, 770  
   weighted fair queuing, 770  
 operational states, Frame Relay PVCs, 156  
 operations management (IBM), 887  
 optical bypass switch (FDDI), 143  
 optical fiber, comparing to copper media, 138  
 optical networking, 373  
   10GE networks, 379  
   AOMs, 374  
   core optical networks, 374  
   DWDM, 373  
   EPONs, 375  
   extended long-haul networks, 378  
   FTTH, 373  
   G.ASON, 382  
     control plane, 383  
     UCP, 383–385  
   GE networks, 379  
   GMPLS, 379  
     LMP, 380–381  
     LSRs, 379–380  
     UNI, 382  
   long-haul networks, 376–377  
   metro, 374  
   metro access networks, 376  
   OCP-NNI, 387  
   OCP-UNI, 385–386  
   PONs, 375  
   protection and restoration, 387–388  
   transparent optical networks, 376  
   ULH networks, 378  
 optimality, routing algorithms, 77  
 origin attribute (BGP), 666  
 Origin Data-Link Correlator field (DLSw message header), 553  
 Origin DLC Port ID field (DLSw message header), 553  
 Origin LSAP field (DLSw message header), 552  
 Origin MAC Address field (DLSw message header), 552  
 Origin Transport ID field (DLSw message header), 553  
 OSI (Open System Interconnection), 393  
   *See also* OSI reference model  
   IDRP, 751–752



- networks, 739
- operations, 740
  - ES-IS, 740–742
  - IDRP, 751–752
  - IS-IS, 742–749
  - LSP, 749
- OSI reference model, 7
  - application layer, 17, 564–565
  - data link layer, 14–15, 65–66, 558
  - LAN switching, 489
  - layers
    - characteristics, 9
    - control information, 12
    - information exchange, 12–13
    - interaction between, 11
    - services, 11–12
  - mapping to AppleTalk protocol suite, 627
  - media-access implementations, AppleTalk, 612
  - network layer, 15, 558
    - addressing, 560–561
    - connectionless network service, 559
    - connection-oriented network service, 559
  - physical layer, 13–14, 558
  - presentation layer, 16, 563
  - relationship to DECnet Phase IV DNA network architecture, 650
  - relationship to DECnet/OSI DNA network architecture, 652
  - relationship to IEEE 802.3, 96–97
  - session layer, 13, 16, 562
  - transport layer, 16, 562
  - upper-layer protocols
    - AppleTalk implementations, 624–625
    - transparency, 66
- OSPF (Open Shortest Path First), 731
  - adjacencies, 734
  - area partitioning, 732
  - areas, 732–733
  - backbone, 732
  - designated routers, 734
  - Hello protocol, 734
  - metrics, 735
  - packet format, 734
  - routing hierarchy, 732
  - TOS-based routing, 735
  - variable-length subnet masks, 736
- OSS (Operational Support System), 316
- OTNs (Optical Transport Networks), 376
- OTP (one-time password), 453

- OUI (Organizationally Unique Identifier), 23
- output, Cisco 3640 startup, 54
- overhead bits, link efficiency, 921
- overlaid point-to-multipoint connections, 507
- overlay model (UCP), 384
- overload bypass, WCCP, 847

---

## P

---

- P/F (poll/final) bit (SDLC), 217
- Packet Capture group (RMON), 895
- packet communication model, XNS, 1016
- Packet Exchange Protocol (PEP), 1019
- packet scheduler, RSVP, 769
- packet sniffers, 795
- packet switching, 46
- Packet type field, IDP packets, 1017
- packet-based networks
  - VoATM, voice quality, 255
  - VoFR, 262
    - addressing, 262–263
    - signaling, 262
    - voice quality, 263
  - voice/data integration
    - applications, 253–254
    - market viability, 252
    - QoS, 948
    - VoATM, 254–255
  - VoIP, 255, 263
- packets, 18
  - CSNP (complete sequence number packet), 724
  - DDP, 627
    - encapsulation, 615
    - FLAP encapsulation, 615–616
  - EIGRP, 679
  - encapsulation, AURP, 623
  - error-checking, 29
  - exception notifications, 1026
  - forwarding, 75
  - fragmentation, 272
  - IDP (Internet Datagram Protocol), fields, 1017–1018
  - interesting traffic, 209
  - IP, 571–572
  - IPv6
    - header format, 589
    - headers, 590
  - IPX, 602

- ISH, 740
- IS-IS, 744–746
- LSP, 744, 749
- LSPs (link-state packets), 724
- metric notifications, 1026
- multicast transmission, 38
- multiplexing, 29–30
- OSPF, 734
- path determination, 74
- PLP, fields, 228
- RIP, format, 758–759
- RIP v2, 759
- RSVP
  - message header fields, 772, 774
  - object fields, 774–775
- SIP, 421–431
- SMRP, 787–788
- SPP, 1018
- SRP, 445–447
- tagging, 272
- tail drops, 937
- TCP, 585
- tracking, 583
- unreliable datagram service, 1027
- variable-length, 153
- packet-switched networks, Frame Relay, 153
- PAD (packet assembler/disassembler), 224
- PAP (Password Authentication Protocol), 206
- PAP (Printer Access Protocol), 624, 627
- PAR (Positive Acknowledgment and Retransmission), 583
- parabolic antenna, 333
- partial deployment, RSVP, 770
- partially connected multipoint tunnels
  - AURP, 623
- passive link (dual homing), 145
- passive state, topology-table entries, 678
- passwords, OTP, 453
- path attributes (BGP), 714
- path control network (SNA), 635
- path cost, bridge ports, 465
- path determination, 74
  - convergence, 77
  - destination/next hop routing table, 74
  - link-state advertisements, 74
  - metrics, 80–81
- path length, 81
- path loss, 333
- path messages (RSVP), 771
- path selection, BGP, 671
- path-error messages (RSVP), 771
- path-teardown messages (RSVP), 772
- payload, link efficiency, 921
- payload (cells), 18
- Payload length field (Level 2 PDUs), 195
- PBR (policy-based routing), 926
- PBXs (private branch exchanges), 171, 394
- PCM (pulse code modulated) voice, 264
- PCS (media-dependent physical coding sublayer), 110
- PDLM (Packet Description Language Module), 928
- PDUs (protocol data units), 19
  - cells (SIP), 189–190
    - Level 2, 194
    - Level 3, 192–193
  - SAR (segmentation and reassembly), 503
  - SIP Level 3, fields, 192–193
  - SNMPv2 messages, 911–913
- peak factor, DOCSIS, 366
- PEAP (Protected EAP), 456
- peer model (UCP), 384–385
- peer-based networking, APPN, 639
  - node types, 639
  - services, 640–641, 643
- peer-to-peer intelligence, HSSI, 168
- penetration rate, DOCSIS, 366
- PEP (Packet Exchange Protocol), 1019
- performance
  - ADSL, 340
  - network management, 85
    - agents, 86
    - architecture, 86
    - history of, 85
    - management proxies, 86
    - standardization, 87–89
  - switches, 65
  - VoATM, 255
- performance and accounting management (IBM), 886
- performance monitor, NetView, 890
- peripheral nodes, 638
- Perlman, Radia, 731
- PGM (Pragmatic General Multicast), 717
- phases of communication, SVC s, 46
- physical addressing, 14
- physical connections, Token Ring, 1010
- physical entities, SNA, 635
- physical layer, 9, 558

- AppleTalk, 612
- ATM reference model, 501
- DNA, 650
- IEEE 802.3, 98, 106–109
- ISDN frames, 173–174
- media access, DECnet, 653
- PPP, requirements, 182
- X.21bis, 228
- physical models, 814
- physical units, 637
- piecemeal deployment, RSVP, 770
- PIM (protocol-independent multicast), 713
  - dense mode, 713
  - sparse mode, 713
    - MSDP, 715
  - sparse-dense Mode, 714
- ping command, 581
- PIUs (path information units), 645–646
- PKI (Public Key Infrastructure), 235
  - EAP, 445–456
- PLAR (Private Line Automatic Ringdown)
  - circuits, 283
- platforms, IBM network management, 889–890
- playout buffer, 270
- PLP (Packet-Layer Protocol), 227–228
- PMA (physical medium attachment), 110
- PMD (physical medium-dependent) sublayer, 112, 139, 501
- PNNI (private network-to-network interface), 261, 510
- point-to-multipoint connections
  - ATM, 506
  - overlaid, 507
- point-to-point conferences (H.323), 274
- point-to-point connections
  - ATM, 506
  - Ethernet, 94
- point-to-point links, 44
- Point-to-Point Protocol. *See* PPP
- point-to-point subnetworks, ES-IS, 740
- point-to-point tunnels, AURP, 623
- poison-reverse updates, 697
- policies
  - DEN, 825
  - QoS, 271–272
  - QPM, 946
- policing, 271
  - CAR, 927
  - traffic, 921
- policing traffic, CAR, 939
- Policy Framework working group, 823
- policy models, 814
- polling, 86
- PONs (passive optical networks), 375
  - customer requirements, 375
- popularity of routing, 73
- ports
  - FDDI DAS, 140
  - on switches, 66
- Positive Acknowledgment and Retransmission (PAR), 583
- POTS (plain old telephone service), 201
- power consumption, DMT, 343
- PPP (Point-to-Point Protocol), 181
  - authentication, 206
  - connection establishment, 205–207
  - frames, 182–183
  - L2TP, 240
  - LCP
    - frames, 184
    - link quality determination, 183
    - link termination, 183
  - link layer, 182–183
  - NCPs, 181
  - network layer protocol configuration, 183
  - physical layer requirements, 182
- PQCBWFQ (priority queue class-based WFQ), 936
- PRE (preamble),
  - Ethernet frames, 98
  - FDDI frames, 146
- precedence bits, setting, 926–927
- predefined community attributes (BGP), 669
- predictive codecs, 264–265
- predictive service, 765
- preempted service (optical networks), 388
- premises networks, 315
- prepending headers to DDP packets, 616
- presentation layer (OSI model), 16, 563, 657
  - AppleTalk, 625
- PRI (Primary Rate Interface), 173, 203
- primaries (SDLC), 216
- primary nodes
  - SMRP, 783
  - SDLC, 215
- prioritizing Frame Relay traffic, 263
- priority field (Token Ring), 1012
- priority queue class-based weighted fair queuing, 936

priority system, Token Ring, 1012  
 private addressing schemes, VoATM, 260–261  
 private ATM addressing, 505  
 private branch exchange (PBX), 171, 394  
 private enterprise networks, Frame Relay, 161  
 private networks, DDOS attacks, 7  
 private network-to-network interface, 261, 510  
 private NNIs, 496  
 private UNIs, 496  
 privileged mode, 55  
 proactive performance management, 87  
 problem management (IBM), 886  
 processors, 53  
 propagation delay, VoIP, 267  
 proprietary trunk protocols, 488  
 Protected EAP (PEAP), 456  
 protected service restoration, optical networks, 387–388  
 Protocol Data Units. *See* PDUs  
 Protocol Discriminator field (Frame Relay LMI), 163  
 Protocol field (PPP frames), 183  
 Protocol ID field (DLsw message header), 551  
 protocol operations (SNMPv2), 905  
 protocol-dependent modules, EIGRP, 677  
 proxy (H.323), 273  
 proxy servers, 518, 839  
     SIP, 280  
 PSC (Packet Switch-Capable) LSRs, 379  
 PSEs (packet-switching exchanges), X.25, 226  
 PSK (phase shift keying), 308  
 PSTN (public switched telephone network), 393  
 PS-users (presentation-service users), 563  
 PT (payload type) field, ATM cells, 498  
 PTI (Packet Type Identifier) field (PLP packets), 228  
 public addressing schemes, VoATM, 260–261  
 public carrier-provided networks, Frame Relay, 160  
 Public Key Infrastructure (PKI), EAP, 455–456  
 public NNIs, 496  
 public switched telephone network, 393  
 public UNIs, 496  
 PUs (physical units), 637  
 PVCs (permanent virtual circuits), 47  
     CIR, 263  
     Frame Relay, 156  
     X.25, 226

## Q

Q.2931 public network signaling protocol, 508  
 QAM (quadrature amplitude modulation, 308  
     with DFE, 311  
 QDM (Quality of Service Device Manager), 922, 946  
 QLLC (Qualified Logical Link Control), 220  
 QoS (quality of service), 271–272, 395, 917–918  
     architecture, 919–923  
         end-to-end, 922–923  
         signaling, 920  
         within a single network element, 920–921  
     ATM, 508  
     baselining, 922  
     CAR, 927–928  
     classification, 925  
     congestion management, 928  
         class-based WFQ, 935–936  
         custom queuing, 930  
         FIFO queuing, 929  
         flow-based WFQ, 931–935  
         priority queuing, 929–930  
     congestion-avoidance tools, 937  
         flow RED, 938–939  
         WRED, 937–938  
     differentiated service, signaling, 926  
     flows, 917  
     for packetized voice, 948  
     for streaming video, 949  
     guaranteed, 944  
     link efficiency mechanisms, 942–944  
         LFI, 942–943  
     management, 922, 945–946  
     MPLS, 535–536, 947  
     NBAR, 928  
     on Ethernet, 946–947  
     PBR (policy-based routing), 926  
     policy control architecture, 947  
     Precedence bits, weight, 934  
     RSVP, 763, 766  
         confirmation messages, 771  
         error messages, 771  
         operational model, 769–770  
         path messages, 771  
         path-error messages, 771  
         reservation-request messages, 771  
         teardown messages, 772  
     service levels, 922–923

- tools, 918
- traffic policing, CAR, 939
- traffic shaping
  - FRTS, 941–942
  - GTS, 940
- QPM (QoS Policy Manager), 946
- QPM (Quality of Service Policy Manager), 922
- QPSK (quadrature phase shift keying), 308
  - nominal DOCSIS upstream data rates, 359–360
- qualifier bit (QLLC), 220
- quality of service (QoS), 395
- queries, EIGRP, 679
- queuing management, 920
- queuing methods, 920
  - D-WFQ, 935
  - WRR, 946
- queuing multicast transactions, MTP, 783
- quick mode (IKE), 240

## R

---

- radio frequency spread spectrum, 312
- RADIUS (Remote Access Dial-In User Service), 208, 453–454
- RARP (Reverse Address Resolution Protocol), 579
- rate-sensitive traffic, 765
- RD (routing domain), 752
- RDI (routing domain identifier), 752
- RDNs (relative distinguished names), 816
- reachability
  - AppleTalk nodes, 624
  - NLSP, 723
- reactive performance management, 87
- read command (SNMP), 899
- real-time services, SIP, 421–431
- receipt-confirmation process, NLSP, 724
- receivers, resource reservations, 768
- reconciliation sublayer (MAC addresses), 109
- RED (Random Early Detection), 271
- redirect message (ICMP), 581
- redundancy
  - cache clusters, 846
  - fault management, Token Ring networks, 1012–1013
  - FDDI, 142
    - dual homing, 144
    - dual ring topology, 142–143
    - optical bypass switch, 143
- reference points, ISDN, 172
- registrars, SIP, 280
- registration process
  - CM, DOCSIS specification, 361
  - gateways, 416
  - LECs, 517
- REL (Release) message, 405–406
- reliability, 81
  - MGCP, 278
  - UDP, 585–586
- reliable message service, 1027
- reliable transport services, 582
- reload/refresh command, 853
- reloading, 61
- remote bridges, 67
- Remote Data-Link Correlator field (DLSw message header), 551
- Remote DLC Port ID field (DLSw message header), 551
- remote procedure calls, 597
- remote-access VPNs, 234
- repeaters, 40
- replies, EIGRP, 679
- repositories
  - data modeling, 811–812
  - directories, 815
  - directory services, 815
- request-queue entries, MTP, 783
- requests
  - gatekeeper discovery, 416
  - information, 421
  - location, 419
  - modes, 409
  - SIP messages, 422–425
- requirements
  - ATM traffic, timing, 502
  - bandwidth, VoIP, 266–269
  - link crossover, 122
  - PPP physical layer operation, 182
- reservation field (Token Ring), 1012
- reservation-request messages (RSVP), 771
- reservation-request teardown messages (RSVP), 772
- reservations, 766
- reserved local link addresses, 703
- residential PONs, 375
- resource-management service, IBM common-operations services, 887

- resources
  - availability, 421
  - entity names, 621
- response-queue entries, MTP, 783
- responses, SIP, 422–425
- restarting mode (PLP), 228
- Reverse Address Resolution Protocol, 759
- reverse proxy caching, WCCP, 850
- RFCs (Requests for Comments), 569
  - RFC 1006, TP0 over TCP, 655
- RIB (routing information base), 752
- RIF (routing information field), 472
  - fields, 481–482
  - SRB, 481
  - translational bridging, 475
- RII (routing information indicator) bit, 481
- ring number, translational bridges, 474
- ring topologies, 38
- RIP (Routing Information Protocol)
  - AFI, 759
  - metric, 758
  - packets, 758–759
  - RFCs, 757
  - routing table entries, 761
  - routing updates, 757
  - stability, 758
  - timers, 758
- RIPv2, packet format, 759
- RLC (Release Complete) message, 405–406
- RMON (Remote Monitoring), 893
  - groups, 894–895
- robbed-bit signaling, 203, 258
- robustness
  - DEN, 829
  - QPSK, 308
  - routing algorithms, 77
- ROM, 53
- root bridge, selecting (STA), 466
- root path cost, 466
- root ports, 466
- ROSE (Remote Operations Service Element), 565, 657
- round-trip delay determination, 408
- route selection, SRB, 480–481
- route states, EIGRP topology-tables, 678
- Route Tag field (RIP v2 packets), 760
- routed protocols, 82
- router of last resort, 79
- router-intelligent routing algorithms, 80
- routers
  - dial backup, 47
  - dial-on-demand, 47
  - discovery
    - EIGRP, 676
    - ES-IS, 740–742
    - IDRP, 751–752
    - memory, 53
    - reloading, 61
    - version, displaying, 56–57
  - routes, leaking, 751
  - route-tagging, EIGRP, 678
  - route-timeout timer (RIP), 758
  - routing
    - autonomous systems, 75
    - backbone, 79
    - comparing to bridging, 73
    - DECnet, 654
    - discovery process, PNNI, 510
    - domains, 79
    - EIGRP
      - neighbor tables, 677
      - topology tables, 677
    - hierarchical, 532
    - IDRP, 752
    - loops, 77
    - metric, 74
    - metrics, 74, 80–81
    - path determination, 74
    - popularity of, 73
    - SNA
      - APPN, 692
      - APPN connection network, 691
      - APPN routing, 689–691
      - COS, 685–687
      - explicit routes, 684–685
      - session connectors, 683
      - subarea routing, 688
      - TGs, 684
      - virtual routes, 684–685
    - update messages, 74
    - VoATM, 261
  - routing algorithms
    - convergence, 77
    - design goals, 77
    - distance vector, 80
    - dynamic, 79
    - efficiency, 77
    - flat, 79

- flexibility, 78
- hierarchical, 79
- host-intelligent, 80
- interdomain, 80
- intradomain, 80
- link-state, 80
- multipath, 79
- optimality, 77
- robustness, 77
- router-intelligent, 80
- single-path, 79
- static, 78–79
- Routing Control field (SRB frames), 481–482
- routing delay, 81
- routing designator field (SRB frames), 482
- routing domain identifier (RDI), 752
- routing domains, 75
- routing information base (RIB), 752
- routing layer (DNA), 650
- routing loops, split horizon, 697
- routing protocols, 10
  - BGP, 663
    - attributes, 664–670
    - CIDR, 664
  - distance vector, 695
  - NLSP, 721
    - adjacencies, 723
    - hello packets, 726–727, 729
    - hierarchical addressing, 725
    - hierarchical routing, 722
    - LSPs, 724
    - reachability, 723
    - receipt-confirmation process, 724
    - scalability, 721
    - sending LAN hello packets, 724
    - WAN links, maintaining, 723
  - OSPF, 731
    - areas, 732–733
    - backbone, 732
    - metrics, 735
    - packet format, 734
    - routing hierarchy, 732
    - TOS-based routing, 735
  - RIP
    - metric, 758
    - packet format, 758–759
    - RFCs, 757
    - stability, 758
    - timers, 758
  - RIPv2, packet format, 759
  - SMRP, 779–780
    - example transaction session, 787
    - forwarding multicast datagrams, 786
    - MTP (Multicast Transaction Protocol), 782–783
    - multicast address management, 782
    - multicast group management, 785
    - multicast routes, 784
    - node management, 783
    - packet format, 787–788
    - terminology, 779–780
    - topology maps, 786
  - SPF algorithms, 734
- routing tables
  - example, 74
  - RIP, 761
  - RTMP, 620
- routing updates, RIP, 757
- routing-update timer, RIP, 758
- RPs (rendezvous points), 709
  - Anycast RP, 716
- RPC (Remote Procedure Call), NetWare, 602
- RPF (Reverse Path Forwarding), 711–714
- RS (redirect servers), SIP, 280
- RS-232 specification, 155
- RSS (route-selection services), 687
- RSVP (Resource Reservation Protocol), 944
  - confirmation messages, 771
  - data flows, 764–765
    - traffic types, 765
  - error messages, 771
  - history, 763
  - multicast sessions, initiating, 766
  - object classes, 774–775
  - operational model, 768
    - general operation, 769
    - tunneling, 770
    - weighted fair queuing, 770
  - packets, format, 772, 774–775
  - path messages, 771
  - path-error messages, 771
  - QoS, 766
  - reservation request messages, 771
  - reservation styles, 766
    - implications, 767
  - scheduler, 769
  - soft state, 768
  - teardown messages, 772

RTCP (RTP Control Protocol), 409  
 RTMP (Routing Table Maintenance Protocol), 620  
 RTP (Rapid-Transport Protocol), 690  
 RTP (real-time protocol), 409  
 RTP (Reliable Transport Protocol), 676  
 RTP (Routing Table Protocol), 1021, 1025  
 RTP Control Protocol (RTCP), 409  
 RTP header compression, 267, 944  
 RTSE (Reliable Transfer Service Element), 565, 657  
 RTU (rooftop units), 315  
 running configuration, viewing, 57–58  
 runs, 488

## S

SA (source address), Ethernet frames, 98  
 sampling, Nyquist theorem, 201, 257  
 SAN (storage area networking) model, 857–858, 860–861  
 SAP (service access point), 11–12  
 SAP (Service Advertisement Protocol), 601, 1015  
 SAR (segmentation and reassembly) sublayer, AAL3/4, 503  
 SAs, 238  
 SAS (single-attachment station), FDDI, 140  
 SASEs (specific-application service elements), 565  
 saving running configuration to NVRAM, 58  
 scalability
 

- NLSP, 721–722
- SIP, 280

 scalable clustering, WCCP, 845  
 scalar objects (SNMP), 900  
 scheduler (RSVP), 769  
 schemata, 809
 

- DEN, 814

 SCNs (switched circuit networks), 274  
 scopes
 

- explicit, FF (fixed-filter) reservations, 767
- wildcard, WF (wildcard-filter) reservations, 766

 SDLC (Synchronous Data Link Control)
 

- comparing to HDLC, 219
- derivative protocols, 218–220
- frames, 216–217
- primaries, 216
- primary nodes, 215
- secondaries, 216
- secondary nodes, 215

SDP (Session Description Protocol), 425–426  
 SDSL (Symmetric Digital Subscriber Line), 345  
 SDUs (Service Data Units), 19, 189  
 SE (shared-explicit) reservations, 767  
 SEAL (simple and efficient adaptation layer), 503  
 secondary nodes (SLDC), 215–216  
 secure VPNs, 233  
 security
 

- DDOS attacks, vulnerability of Internet, 7
- DOS attacks, resource reservation, 20
- EAP-TLS, 456
- IPSec, 234
  - AH, 236
  - ESP, 236
  - IKE, 238–240
  - SAs, 238
    - transport mode, 237
    - tunnel mode, 237
- L2TP, 243
  - policies, 797–798
- SNMP, 906–907
- threats, mitigating, 801
- tools, 802–803
- VPNs
  - client-aware tunneling, 242
  - client-transparent tunneling, 241
  - L2TP, 240
    - vulnerabilities, 794–797

 security management, standardization, 88–89  
 security wheel, 798, 800  
 segment type field (Level 2 PDUs), 194  
 segmentation, LAN switches, 66  
 Segmentation unit field (Level 2 PDUs), 194  
 segments, 18
 

- microsegmentation, 485

 SEL (selector byte), NSAP format ATM addresses, 504  
 SEL (selector field), ATM addresses, 506  
 selecting
 

- 1000BaseX components, 128
- CMTS backbone, 364
- QoS type of service, 923
- root bridge (STA), 466
- routes, SRB, 480–481
- UTP-based components, 123

 selecting best path
 

- BGP, 671
- metrics, 80–81

 Selector field (DSP), 561



- senders, resource reservations, 768
- Sequenced Packet Protocol (SPP), 1018
- serialization delay, 921
- servers
  - CA, EAP-TLS, 456
  - DOCSIS CMTS specifications, 360–361
  - RADIUS, EAP authentication, 453–454
  - UAS, 426
- service levels (QoS), 922
  - differentiated service, signaling, 926
- services
  - APPN, 642–643
    - configuration services, 641
    - directory services, 641
    - routing services, 642
    - session services, 643
  - ATM, 498–499
  - flow specifications, 764
    - RSVP traffic types, 765
  - H.450, 410–411
  - ISDN, 173
  - LLC, 219–220
  - OSI layers, 11–12
  - SIP, 421–431
- session connectors (SNA), 683
- session control layer, DECnet Phase IV, 657
- session control layer (DNA), 650
- Session Description Protocol (SDP), 425–426
- session establishment, APPN, 643
- Session Initiation Protocol. See SIP, 421
- session layer, DECnet/OSI DNA, 658
- session layer protocols
  - ADSP, 625
  - AppleTalk, 625
  - ASP, 626
  - PAP, 627
  - ZIP, 626
- session protocol (OSI protocol suite), 562
- session service, 563
- sessions, 765
  - AppleTalk, 626
  - multicast, 765
  - RSVP multicast, initiating, 766
  - simplex, 765
  - X.25, establishing, 225
- sessions layer (OSI model), 13, 16
- Set operation (SNMPv1), 904
- setting IP precedence bits, 926–927
- setting CLP bit, 508
- setting the C bit, 473
- Setup messages, H.323 network devices, 401–402
- severity levels for system messages, 60
- S-frames (supervisory frames), 228
- shaping traffic, 921
  - FRTS, 941–942
  - GTS, 940
- shared reservations, 766
- shared trees, 709, 711
- short DDP packets, 627
- shortcuts (MPOA), 519
- shortcuts (NSAP addresses), 519
- show queue command, 934
- show version command, 56–57
- signaling
  - ADSL, 342–343
  - ATM, 508
    - connection establishment, 509
  - basband transmission, 106–108
  - basic telephony service, 256
  - DSSS (direct sequence spread spectrum), 312
  - end-to-end, SIP, 421–431
  - FHSS, 313
  - ISDN, 175, 178
  - maintenance loops method, 409
  - QoS, 920
  - robbed bit, 258
  - SIP, 279–280
    - VoATM, 259–260
    - VoFR, 262
    - VoIP, comparing alternatives, 283
- signaling rate, HSSI, 167
- signaling transfer points (STPs), 393
- Simple Gateway Control Protocol, 276
- simplex sessions, 765
- single-mode fiber (FDDI), 138
- single-path routing algorithms, 79
- SIP (Session Initiation Protocol), 279–280, 421–431
  - addressing, 281
  - call flow, 281
  - comparing to MGCP, 283
  - endpoints, 279
  - Level 2 PDUs, 194
  - Level 3 PDUs, 189, 192–193
  - messages, 281
  - methods, 281
- SIP (SMDS Interface Protocol), 188
- Skinny Station Protocol, 285

- sliding windows, 583
- slot time, 101
- SMDS (Switched Multimegabit Data Service), 187
  - AAL3/4, 503
  - access classes, 191
  - addressing, 191
    - Level 2 PDU, 194
    - Level 3 PDU, 192–193
  - network components, 187
  - SDUs (service data units), 189
  - SIP (SMDS Interface Protocol), 188
- SMI (Structure of Management Information), 902–904
- SMRP (Simple Multicast Routing Protocol), 779–780
  - example transaction session, 787
  - MTP (Multicast Transaction Protocol), 782–783
    - multicast address management, 782
    - multicast routes, 784
  - multicasting
    - forwarding datagrams, 786
    - group management, 785
  - node management, 783
  - packet format, 787–788
  - terminology, 779–780
  - topology maps, 786
- SMT (Station Management) specification, FDDI, 139
- SNA
  - APPN, 639, 689–691
    - border nodes, 692
    - DLUR/S, 691
    - ISR, 690
    - nodes, 639
    - Node type 2.1 routing, 689
    - routing services, 642
    - services, 641–643
    - session services, 643
  - architecture, 634
  - COS, 685
    - APPN routing, 686–687
    - subarea routing, 685
  - DLC, 636
  - explicit routes, 684–685
  - IBM network management, 885
  - NAUs, 637
  - nodes, 638
  - path control network, 635
  - physical entities, 635
  - session connectors, 683
  - subarea routing, 688
    - TGs, 684
    - ToS, 948
    - virtual routes, 684–685
- SNAP, 600
- SNI (SNA network interconnection) gateways, 683
- SNI (subscriber network interface)
  - SMDS, 187
- SNMP (Simple Network Management Protocol)
  - agents, 898, 1003
  - commands, 899
  - data representation, 902
  - distributed management, 910
  - managed devices, 898
  - managed objects
    - ASN.1 data types, 902
    - SMI-specific data types, 903
  - MIBs, 900
  - security, 906–907
  - traversal operations, 899
  - USM model, 909–910
  - VACM, 910
  - version 1, 902
    - message formats, 911, 913
    - MIB tables, 903
    - protocol operations, 903–904
    - SMI, 902–903
  - version 2, 904, 906
    - information modules, 904
    - messages, 911
    - protocol operations, 905
    - SMI, 904
- snooping, 708
- SNPA (subnetwork point of attachment), 742
- sockets, 608
  - ATP (AppleTalk Transaction Protocol), 624
  - well-known, 1018
- SOF (Start-of-frame) delimiter, Ethernet, 98
- soft savings, packet-based voice systems, 251
- soft state (RSVP), 768
- software agents, 86
- solutions, wireless, 316–317
  - access networks, 316
  - core networks, 316
  - deployment, 317
  - premises networks, 315
- Source Address field (FDDI), 146

- Source host number field (IPD packets), 1018
- Source network number field (IDP packets), 1018
- source routing, 80
- source trees, 708–709
- source-quench messages, 28
- source-route bridging, 65–66
- source-route transparent bridging, 65
- sparse mode (PIM), 713–716
- sparse-dense Mode (PIM), 714
- spatial diversity, 314
- specifications
  - ATM, 494
  - CDDI cable, 147
  - FDDI, 139
- spectrum management, CMTS, 363
- SPF (Shortest Path First) algorithm, 731, 734
- split horizon, 697
- SPP (Sequenced Packet Protocol), 1018
- spread spectrum, 312
  - FHSS, 313
- SPT (shortest path tree), 709
- SPX (Sequenced Packet Exchange), 601
- SRB (source-route bridging), 479
  - comparing to DLSw, 543
  - explorer frames, 480
  - frames
    - Routing Control field, 481–482
    - routing designator fields, 482
  - RIF (routing information field), 481–482
  - route selection, 480–481
  - translational bridging, 473–475
- SRP (Spatial Reuse Protocol), 441
  - multicast support, 448
  - packets, 442, 445–447
- SRP-fa, 442
- SRT (source-route transparent bridging), 476
- SS7 (Signaling System 7) networks, connecting, 431
- SSAPs (session-service access points), 562
- SSCP (system services control point), SNA COS, 685–686
- SSCPs (system services control points), 637, 688
- SSD (start-of-stream delimiter), 113
- SSP (Switch-to-Switch Protocol), 541, 545
- SSP Flags field (DLSw message header), 552
- SSRP (Simple Server Redundancy Protocol), 514
- SS-users, 562
- STA (spanning-tree algorithm), 465–467
  - BPDU, 467
  - bridge ports
    - path cost, 465
  - calculating, 467
  - mixed media implementations, 474
  - translational bridging, 473
- stability
  - IGRP, 696–697
  - RIP, 758
- standalone caches, 840
- standard Frame Relay frames, 161–162
- standardization of network management, 87
  - accounting management, 88
  - configuration management, 87–88
  - fault management, 88
  - performance management, 87
  - security management, 88–89
- standards
  - ADSL, 344
  - data communications, 203, 205
  - Frame Relay, 154
  - ITU-T, H-series recommendations, 272
  - OSI network layer, 559
  - voice coding, ITU-T, 265
  - voice/data integration, 251
- standards organizations, 30–31
- standby condition, bridge ports, 465
- star topology, 39
  - Token Ring, 1009, 1012
- start delimiter, Token Ring frames, 1014
- Start Delimiter (FDDI frames), 146
- Start Delimiter field (Token Ring), 1013
- starting RSVP multicast sessions, 766
- Start-of-frame delimiter (SOF), 98
- startup config, viewing, 58–59
- static addresses, 27
- static routing, 580
- static routing algorithms, 78–79
- Station field (DSP), 561
- statistical multiplexing, 30
  - Frame Relay, 153
- Statistics group (RMON), 894
- status messages, LMI, 158
- status monitor, NetView, 890
- statusDeterminationNumber field, 407
- storage networking, 857–858, 860–861
- store-and-forward switching, 68, 488
- storing web pages, 837–838
  - browser-based client caching, 840
  - proxy servers, 839

- standalone caches, 840
- WCCP, 841–843, 845, 847, 849–850
- Web Cache Control Protocol, 842–843
- stovepipe application designs, 820
- STPs (signaling transfer points), 393
- stranded groups (SMRP), detecting, 786
- streaming video, QoS, 949
- StreetTalk, 1027
- styles of RSVP reservations, implications, 767
- subarea nodes, 638
- subarea routing, 688
  - COS, 685
- subfields
  - DNIC, 230
  - of Routing Control field, 481
  - Routing Control field, 482
  - Routing Designator field, 482
- sublayers
  - AAL3/4, 503
  - data link layer (OSI model), 15
- Subnet Mask field (RIP 2 packets), 760
- subnet masks, 575–578
- subnets, 575
  - ATM, 504
  - VLANs, 486
- subnetwork point of attachment (SNPA), 742
- subnetworks, ES-IS, 740–742
- subsystems, security management, 88–89
- summarization, EIGRP, 675
- SuperFrames, 258
- supervision signaling, 256
  - basic telephony service, 256
- Supervisory frames (SDLC), 217
- SVCs (switched virtual circuits)
  - Frame Relay, 156
  - X.25, 226–227
  - phases of communication, 46
- switch ports, modes, 487
- switched circuits, 45
  - dial backup, 47
- Switched Multimegabit Data Service. *See* SMDS
- switching, 37, 65–66, 68, 75
  - 10/100, 489
  - asymmetric, 489
  - ATM, 69
    - cell delineation, 501
    - cell header format, 496, 498
    - cell-rate decoupling, 501
    - endpoints, 495
    - HEC, 501
    - ILMI, 510
    - LANE, 511–512
    - leaves, 506
    - MPOA, 519
    - multicast server, 507
    - multicasting, 507
    - network interfaces, 496
    - PNNI, 510
    - QoS, 508
    - services, 498–499
    - signaling, 508
    - transmission path, 499
    - VBR traffic, 502
    - VCCs, 515
    - VCs, 498
    - virtual paths, 499
    - VP multicast, 507
  - Catalyst 2924XL, 66
  - Catalyst 6500, 66
  - comparing to bridging, 66
  - CSMA/CD networks, 125–126
  - cut-through, 66, 488
  - full-duplex mode, 37
  - LANs, 70
  - Layer 2 multicasting, 707
  - performance, 65
  - PSEs, X.25, 226
  - store-and-forward, 488
  - symmetric, 489
  - WANs, 47
- Switch-to-Switch Protocol, 541, 545
- symbols, 308
  - ISI (intersymbol interference), 306
- Symmetric Digital Subscriber Line (SDSL), 345
- symmetric switching, 489
- synchronization, directory services, 819–820
- syntax, directory attributes, 817
- system messages, severity levels, 60
- system models, 814
- system services control poin, 637, 688
- SystemView (IBM), 888

---

## T

- T1/E1, 202–203
  - CAS, 203
  - PRI, 203

- T2 (node type 2), 638
- T4 (node type 4), 638
- T5 (node type 5), 638
- tables
  - capabilityTable, 407
  - SNMP MIB, 903
  - ZIT (Zone Information Table), 626
- tabular objects (SNMP), 900
- TACACS, 208
- tag switching, 947
  - QoS, 535–536
- tagging packets, 272
- tail drops, 937
- Target Data-Link Correlator field (DLSw message header), 553
- Target LSAP field (DLSw message header), 552
- Target MAC Address field (DLSw message header), 552
- TC (transmission convergence) sublayer, 501
- TCP (Transmission Control Protocol), 582
  - connection establishment, 582
  - flow control, 582
  - multiplexing, 582
  - packets, 585
  - sliding window, 583
- TDM (time-division multiplexing), 30, 202, 393
- TE1 (terminal equipment type 1), 171, 396
- TE2 (terminal equipment type 2), 171
- teardown messages (RSVP), 772
- technology breakthroughs, voice/data integration, 251–252
- telco return data service, 365
- telephony service. *See* basic telephony service
- terminal adapters (ISDN), 49, 202
- terminal equipment type 1 (TE1), 396
- terminals, H.323, 273, 396, 407
- terminology, SMRP, 779–780
- TFTP (Trivial File Transfer Protocol) servers,
  - CMTS DOCSIS specification, 360
- TG (transmission group), 684, 687
- threats to network security, 794–797
  - mitigating, 801
  - solutions, 798–800
- three-way handshakes, 583
- throughput, full-duplex operation, 486
- ticks, 599
- time slots, MULTIPLE\_FRAME\_ESTABLISHED, 202
- time ticks (SNMP SMI), 903
- time variation, 307
- time-division multiplexing, 30, 202, 393
- time-exceeded message (ICMP), 581
- timers
  - AMT, 618
  - IGR, 697
  - RIP, 758
- time-sharing networks, 5
- timing requirements, ATM traffic, 502
- TLAP (TokenTalk Link Access Protocol), 614–615
- TLVS, 748–749
- TOD (Time of Day) servers, CMTS DOCSIS
  - specification, 360
- token buckets, 927
- token passing LANs, FDDI, 138
- Token Ring, 1009
  - active monitor, 1012
  - autoreconfiguration, 1012
  - data/command frames, fields, 1014
  - determinism, 1012
  - early token release, 1012
  - failure domains, 1012
  - fault management, 1012–1013
  - frame fields, 1013–1014
  - frame-status bits, 472
  - NAUN, 1013
  - physical connections, 1010
  - priority system, 1012
  - RIF field handling, 472
  - source-route bridging, 65
  - SRT, 476
  - star topology, 1012
  - token passing, 1011
  - translational bridging, 473–475
    - challenges of, 471–472
- token-passing LANs, 37
  - FDDI, 137, 145
  - switches, 37
  - Token Ring, 1011
- TokenTalk, 614
  - TLAP, 615
- topologies
  - areas, 19
  - bus, 613
  - campus, 131
  - data link layer, 14–15
  - domains, 19, 79
  - dual ring (FDDI), 142–143
  - Ethernet, 94

- LANs, 38–39
- loops, 465–467
- ring, 38
- Token Ring, 1009, 1012
- topology maps, SMRP, 786
- topology tables
  - EIGRP, 677
  - route states, 678
- topology-change messages, transparent bridging, 467–468
- ToS (Type of Service), 735, 948
- TP0 (Transport Protocol Class 0), 562
- TP1 (Transport Protocol Class 1), 562
- TP2 (Transport Protocol Class 2), 562
- TP3 (Transport Protocol Class 3), 562
- TP4 (Transport Protocol Class 4), 562
- TP-PMD (Twisted-Pair Physical Medium Dependent) standard, 147
- TPRI (transmission priority), APPN, 687
- tracking
  - gatekeepers, 397
  - packets, 583
- traffic, 729
  - ATM
    - timing requirements, 502
    - VBR, 502
  - bandwidth, 81
  - CBR (constant bit rate), 501
  - classification method, 926, 928
  - classification methods
    - CAR, 927
    - D-, 928
  - collisions, 614
  - congestion management, 920, 928
    - class-based WFQ, 935–936
    - custom queuing, 930
    - FIFO queuing, 929
    - flow-based WFQ, 931–933, 935
    - priority queuing, 929–930
  - congestion-avoidance techniques, 937
    - flow RED, 938–939
    - WRED, 937–938
  - data flows
    - flow specifications, 764–765
    - RSVP, 765
  - differentiated service, 922
  - filtering, 464
  - flow control, 28
    - ARB (adaptive rate-based), 691
    - DLSw, 546
    - QoS, 918
  - Frame Relay
    - controlling, 157–158
    - prioritizing, 263
    - guaranteed service, 922
    - interesting, 209
  - LAN switching, bandwidth, 489
  - MPLS engineering, 751
  - multiplexing, 29–30
  - policing, 271, 921
    - CAR, 939
  - QoS classification, 925
  - queue management, 920
  - shaping, 921
    - FRTS, 941–942
    - GTS, 940
  - VLANs, multiplexing, 488
- traffic contracts, 508
- traffic engineering, 537
- traffic localization, web caching, 838–839
- traffic policing, 508
- traffic shaping, 271, 508
- trailers, 12
  - encapsulation, 13
- transaction services, ATP, 624
- transfer modes, HDLC, 219
- translational bridging, 65, 68, 473–475
  - challenges of, 471–472
  - explorer frames, 472
  - ring number, 474
- transmission media, FDDI, 138
- transmission methods, LANs, 38
- transmission path (ATM), 499
- transmission process, DDP, 619
- transparency
  - upper-layer protocols, 66
  - WCCP, 842
- transparent bridging, 65, 463
  - configuration messages, 467–468
  - filtering, 464
  - history, 463
  - loops, 464
  - SRT, 476
  - STA, 465
    - calculating, 467
    - designated bridge selection, 466
    - root bridge selection, 466
  - topology-change messages, 467–468
  - translational bridging, 473–475

- transparent caching, WCCP, 842–843
- transparent optical networks, 376
- Transport control field, IDP packets, 1017
- Transport ID field (DLSw message header), 553
- transport layer protocols, 16, 562
  - ATP, 624
  - AppleTalk, 619
    - NBP, 620, 622
    - RTMP, 620
  - DECnet Phase IV, 655
  - TCP, 582
    - connection establishment, 583
    - packets, 584–585
    - PAR, 583
    - sliding windows, 584
- transport layer services
  - Banyan VINES, 1027
- transport mode (IPSec), 237
- Transport Protocol Classes, 562
- transport protocols
  - connectionless, 20
  - connection-oriented, 20
  - DECnet/OSI, 655
  - PGM (Pragmatic General Multicast), 717
  - SPX, 601
  - UDP, 585–586
  - XNS, 1018–1019
- trap command (SNMP), 899, 904
- traversal operations (SNMP), 899
- tree topologies, 39
- triggered updates, IGRP, 696
- troubleshooting IBM problem management, 887
- trunks, 487
- trusted VPNs, 233
- TTL (time-to-live), configuring web content, 852
- tunnel mode (IPSec), 237
  - SMRP, 783
- tunneling
  - AURP, 622
  - RSVP, 770
- two-way operation, CATV, 353
- two-way transmission, 103–104
- Type field (EAP), 452–453

---

## U

---

- UAC (user agent client), 426
- UAS (user agent server), 426
- UBR (unspecified bit rate), 258
- UCP (unified control plane), 383
  - overlay model, 384
  - peer model, 384–385
- UDP (User Datagram Protocol), 585–586
  - AURP encapsulation, 623
- U-frames (unnumbered frames), 228
- u-law, 257
- ULH (ultra long-haul) networks, 378
- unacknowledged connectionless service (LLC), 219
- UNI (user-to-network interface), 382
  - OCP-UNI, 385–386
- UNI 3.1 specification, 508
- unicast gatekeeper discovery, 416
- unicast sessions, 765
- unicast transfers, mixed-media networks, 475
- unicast transmission, LANs, 38
- unicast update packets, EIGRP, 679
- unicasting, IPv6, 591
- Unified Messaging systems, 253
- unified namespace directories, 818
- unified network management, DEN, 821
- U-NII (Unlicensed National Information Infrastructure), 334
- UNIs, 496
- Unnumbered frames (SDLC), 217
- Unnumbered Information Indicator field (Frame Relay LMI), 163
- Un-PBX, 285
- unprotecting service protection (optical networks), 388
- unreachable destinations, RIP, 758
- unregistration, gateways, 417
- unreliable datagram service, 1027
- unsigned integers (SNMP SMI), 903
- unspecified bit rate (UBR), 258
- Unused field (RIP 2 packets), 760
- update messages, 74
- update packets, EIGRP, 679
- update timer, IGRP, 697

- updates
  - IGRP, triggered updates, 696
  - RIP, 757
- upgrading Cisco IOS Software, 61–62
- upper layers
  - DECnet Phase IV, 656–657
  - DECnet/OSI, 657–658
  - OSI reference model, 9
- upper-layer protocols
  - AppleTalk, 624–625
    - ADSP, 625
    - AFP, 627
    - ASP, 626
    - PAP, 627
    - ZIP, 626
  - Banyan VINES, 1027
  - NetWare, 602
  - transparency, 66
- upstream amplifiers, two-way HFC, 353
- upstream CATV specifications, 355–357
- URLs
  - browser-based client caching, 840
  - web caching, 837–838
- user agent client (UAC), 426
- user agent server (UAS), 426
- User Data field (PLP packets), 228
- user layer
  - DECnet Phase IV, 656
  - DNA, 650
- user mode, 55
- user models, 814
- user-user IEs
  - Alerting message, 403–404
  - Call Proceeding message, 402–403
  - Call Setup message, 401
  - Connect message, 404
  - REL message, 405–406
  - RLC message, 405–406
- user-user IEs, 401. *See also* IEs
- USM (user-based security model), 909–910
- UTP
  - autonegotiation, 124–125
  - horizontal cabling, 131
  - selecting, 123

## V

- V.34 connectivity, 201
- V.90 modems, 205
- VACM (view-based access model), 910
- VAD (voice activity detection), 267
- variable bit rate (VBR), 258, 502
- variable-length packets, 153
- variable-length subnet masks, 736
- VBR (variable bit rate), 258, 502
- VCCs, 515
- VCI (Virtual Channel Identifier) field, ATM
  - cells, 497
- VCs (virtual circuits)
  - Frame Relay, 155–156
    - DLCIs, 157
    - status messages, 158
  - PVCs, 47
  - SVCs, phases of communication, 46
  - VINES transport layer, 1027
  - X.25, 225–226
- VCs (virtual channels), 498
- VDSL (Very-High-Data-Rate DSL), 347
- Version field (RIP 2 packets), 760
- Version Number field (DLSw message header), 551
- video
  - capability exchanges, 406
  - QoS, 949
  - SIP, 421–431
- videoconferencing, H.323, 272, 765
- viewing
  - running configuration, 57–58
  - startup config, 58–59
- VINES (Virtual Integrated Network Service), 1020
  - ARP, 1026
  - ICP, 1026
  - media access, 1020
  - network layer, 1021
  - RTP, 1025
  - transport layer services, 1027
  - upper-layer protocols, 1027
- VIP (VINES Internetworking Protocol), 1021–1023
- virtual addresses, 24
- virtual circuits, 16, 46
  - WANs, 46–47
- virtual connections, ATM, 498
- Virtual Integrated Network Service (VINES), 1021–1023



- virtual paths, 499
  - virtual ring, 544
  - virtual routes, 684–685
  - virtual telecommunication access method (VTAM), 637
  - VLAN tagging, MAC sublayer, 105
  - VLANs (virtual LANs), 486
    - multiplexing, 488
    - proprietary trunk protocols, 488
    - trunks, 487
  - VLSM (variable-length subnet masking), EIGRP, 675
  - VoATM (Voice over ATM), 254–255
    - addressing, 260–261
    - delay, 262
    - routing, 261
    - signaling, 259–260
    - voice quality, 255
  - VOFDM (vectored orthogonal frequency-division multiplexing), 314–315
  - VoFR (Voice over Frame Relay), 255, 262
    - addressing, 262–263
    - signaling, 262
    - voice quality, 263
  - Voice over Frame Relay. *See* VoFR
  - Voice over IP. *See* VoIP
  - voice quality, 265–266
    - VoATM, 255
    - VoFR, 263
  - voice/data integration, 948
    - applications, 253–254
    - codec technology, 252
    - economic advantages of, 252–253
    - evolution, 283–284
    - H.323, 272
      - call flow, 274–275
      - devices, 273–274
    - market viability, 252
    - MGCP, 275–276
      - protocol definitions, 277–278
    - SIP, 279–280
      - addressing, 281
      - call flow, 281
      - messages, 281
    - standards, 251
    - VoATM, 258
      - addressing, 260–261
      - routing, 261
      - signaling, 259–260
  - VoIP (Voice over IP), 255, 393
    - centralized call management schemes, 263
    - comparing alternatives, 283
    - design constraints, 266–269
      - delay, 267, 271
    - distributed call management schemes, 263
    - H.323 network devices, 395–398
      - audio CODECs, 411–414
      - H.225, 400–406
      - H.225 RAS, 414–421
      - H.245, 406–410
      - H.450, 410–411
      - protocols, 398
    - infrastructure, 394
    - jitter, 270
    - QoS, 271–272
    - SS7 networks, connecting, 431
  - VP multicast, 507
  - VPI (Virtual Path Identifier) field, ATM cells, 497
  - VPNs (virtual private networks), 233
    - applications, 234
    - L2TP, 240
      - client-aware tunneling, 241–242
      - client-transparent tunneling, 241
      - security, 243
    - MPLS VPNs
      - BGP, 243–245
      - L2VPNs, 245–246
    - MPLS-based, 533, 535
  - VPWS (Virtual Private Wire Service), 246
  - VTAM (virtual telecommunication access method), 637
  - vulnerability of Internet, 7
- 
- ## W
- WANs, 5, 10, 43
    - access servers, 48
    - CSU/DSU, 49
    - development of, 6
    - devices, 47–48
    - dialup services, 47
    - Frame Relay, 153
      - comparing to X.25, 153
      - congestion-control mechanisms, 157–158
    - DCEs, 154–155
    - DLCIs, 157
    - DTEs, 154–155

- frames, 161–162, 164
- implementing, 159–160
- LMI, 154, 158
- private enterprise networks, 161
- public carrier-provided networks, 160
- PVCs, 156
- RS-232 specification, 155
- standardization, 154
- SVCs, 156
- VCs, 155
- hello packets, 723
- HSSI, 167
  - bandwidth, 168
  - characteristics, 167–168
  - loopback testing, 168
- ISDN terminal adapters, 49
- leased lines, 44
- modems, 49
- NLSP
  - hello packets, 726–727
  - receipt-confirmation process, 724
- packet switching, 46
- point-to-point links, 44
- remote bridging, 67
- switched circuits, 45
- switches, 47
- virtual circuits, 46–47
- X.25, 223
  - DCE, 223
  - LAPB, 228
  - PAD, 224
  - PLP, 227
  - PVCs, 226
  - session establishment, 225
  - VCs, 225–226
  - X.121 addressing, 230
  - X.21bis, 228
- WAP (Wireless Access Protocol), 334
- waveform codecs, 264
- WCCP (Web Cache Control Protocol), 841–843
  - cache engine operation, 842–843
  - dynamic client bypass, 847, 849
  - hierarchical deployment, 843
  - multihoming, 846
  - network-based shared caching, 842
  - overload bypass, 847
  - proxy servers, 839
  - reverse proxy caching, 850
  - scalable clustering, 845
  - standalone servers, 840
  - transparent caching, 842–843
- WDM (wave-division multiplexing), 373
- web caching, 837–838
  - browser-based client caching, 840
  - Cisco Cache Engine, fresh content, 851–852
  - network integrated, 839
  - reload/refresh command, 853
  - traffic localization, 838–839
  - TTL, configuring, 852
- web pages, caching. *See* WCCP
- web sites, Cisco Systems, 41
- weight attribute (BGP), 664
- weights, 934
- well-known socket numbers, 1018
- WF (weighted field), 687
- WF (wildcard-filter) reservations, 766
- WFQ (weighted fair queuing), 770
  - IP precedence, 934–935
- wildcard notation, shared trees, 710
- windowing, 28
- wire, 308
- wireless technologies
  - DSSS, 312
  - FDM (frequency-division multiplexing), 313
  - FHSS, 313
  - LMDS data links, 318
  - microwave, multipath, 304, 306
  - OFDM, 313–314
  - QAM, DFE, 311
  - solutions, components of
    - access networks, 316
    - core networks, 316
    - deployment, 317
    - network management, 316–317
    - premises networks, 315
  - spatial diversity, 314
  - spread spectrum, 312
  - VOFDM (vectored orthogonal frequency-division multiplexing), 314–315
- WLANs (wireless LANs), standards
  - comparison, 318
- WRED (weighted random early detection), 271
- write command (SNMP), 899
- WRR (weighted round robin), 946

## X

---

- X+ field (SIP Level 3 PDUs), 192–193
- X.121 addressing, 230
- X.21bis, 228
- X.25 protocol suite, 223, 226
  - comparing to Frame Relay, 153
  - DCE (data circuit-terminating equipment), 223
  - devices, PAD, 224
  - LAPB frames, 228–229
  - LAPB (Link Access Procedure, Balanced), 228
  - PLP, 227–228
  - PVCs, 226
  - session establishment, 225
  - VCs, 225–226
  - X.121 addressing, 230
  - X.21bis, 228
- Xerox, history of Ethernet, 93
- XmplsATM, 525
- XNS (Xerox Network Systems), 1015
  - design objectives, 1015
  - directed broadcasts, 1018
  - directed multicasts, 1018
  - global multicasts, 1018
  - media access, 1016
  - network layer, 1017
  - packet communication model, 1016
  - transport layer functions, 1018–1019
- XO (Exactly-Once) transactions, 624

## Z

---

- Zero field (RIP packets), 759
- ZIP (Zone Information Protocol), 617, 626
- ZIT (Zone Information Table), 626
- zones
  - AppleTalk, 610–611
  - managing H.323 network devices, 397