

# INDEX

## A

---

- aaa option, 100
- AAA server
  - aaa option, 100
  - address assignment, 190
  - assigned DHCP server, 191
  - authorization of static home addresses, 193
  - home addressing, 190
  - load-sa option, 100
  - local pool selection, 191
  - overview, 96, 98–100
  - permanent option, 100
  - RADIUS, 100–101
  - TACACS+, 101
- AAA-based dynamic key generation, 220–221
- access links, 29
- active-standby home agent configuration, 108
- address assignment, 190
- address fields, 42, 44–45
- agent advertisements
  - handover, 28–33
  - location discovery, 28
  - move detection, 28–33
  - overview, 24–27
  - router advertisement, 24
  - router solicitation, 24
- agent selection, 154–155
- algorithm security, 61–62
- asymmetric links
  - configuration, 167–168
  - example, 168–169
  - overview, 166–167
- authentication, 41
- authentication options, 234–236
- authentication response extension, 72

## B

---

- baseline topology
  - IOS Mobile IP
    - correspondent node configuration, 79
    - foreign agent configuration, 83–85
    - home agent configuration, 80–81, 83

- intermediate system configuration, 79
- mobile node configuration, 85–86
- overview, 77, 79
- bootstrap, 236–238
- broadcast support, 38

## C

---

- call model, 194–195
  - example, 197–198
  - objects matching, 199–200
- campus mobility
  - AAA server
    - overview, 96, 98–100
    - RADIUS, 100–101
    - TACACS+, 101
  - Cisco Zero Configuration Client, 102–103
  - Home Agent Redundancy
    - configuration commands, 107–108, 110–113, 115
    - overview, 104–106
  - overview, 95–96
- Care-of Address (CoA)
  - collocated CoA (CCoA), 22
  - foreign agent CoA, 22
  - overview, 21
- cdma2000 technology, 209–210, 212
- challenge extension, 71
- Cisco Dynamic Security Association and Key Distribution, 70
  - authentication response extension, 72
  - challenge extension, 71
  - configuration extensions, 72
  - domain extension, 71
  - security association setup extension, 71
  - session index extension, 71
- Cisco Enterprise MIB, 199
- Cisco Mobile Networks
  - asymmetric links
    - configuration, 167–168
    - example, 168–169
    - overview, 166–167
  - Collocated Care-of Address support, 170
  - dynamic Collocated Care-of Address, 171–172

- examples, 173–174
- static Colocated Care-of Address, 171
- using Colocated Care-of Address, 172–173
- Foreign Agent enhancements
  - IRDP options, 161
  - local routing to mobile networks, 162–164
  - overview, 161
- Home Agent enhancements
  - network mobility, configuration for, 159–160
  - overview, 157
  - Priority Home Agent Assignment, 160–161
  - redundancy feature, 159
- IPSec and mobile router, 176–177
- mobile router
  - agent selection, 154–155
  - configuration, 150–151
  - interface, 151–152
  - IPSec and, 176–177
  - interface-level configuration, 153–154
  - Mobile IP registration, 155
  - mobile networks, 147–148, 150
  - overview, 147
  - redundancy, 165–166
  - routing to and from, 156
  - overview, 145–146
  - quality of service (QoS), 174, 176
- Cisco SWAN (Structured Wireless-Aware Network), 217–219
- Cisco Zero Configuration Client, 102–103
- Colocated Care-of Address, 22
  - support for, 170
    - dynamic Colocated Care-of Address, 171–172
    - examples, 173–174
    - static Colocated Care-of Address, 171
    - using Colocated Care-of Address, 172–173
- communications mobility
  - challenges of
    - location discovery, 6–7
    - move detection, 7
    - overview, 5
    - path (re)establishment, 8
    - update signaling, 7

- location discovery, 6–7
  - proactive approach, 6
  - reactive approach, 6
- move detection, 7
- path (re)establishment, 8
- update signaling, 7
- components
  - Care-of Address (CoA), 21
    - colocated CoA (CCoA), 22
    - foreign agent CoA, 22
  - Correspondent Node (CN), 22
  - Foreign Agent, 22
  - Home Address, 19, 21
  - Home Agent, 21
  - Home Network, 19, 21
  - Mobile Node, 18
  - overview, 18
- configuration extensions, 72
- Correspondent Node (CN)
  - configuration, 79
  - overview, 22

---

## D

- data traffic, amount of, 197
- delivery, 46–48
  - handover other than returning home, 47
  - handover returning home, 48
- deregistration, 38
- DHCP server, 191
- DHCP-based address assignment, 189
- domain extension, 71
- dynamic addressing, 184
- dynamic Colocated Care-of Address, 171–172
- dynamic home address assignment, 186–187
  - DHCP-based address assignment, 189
  - fixed addressing on the CLI, 187
  - local pool address assignment, 188–189
- dynamic keying
  - Cisco Dynamic Security Association and Key Distribution, 70
    - authentication response extension, 72
    - challenge extension, 71
    - configuration extensions, 72
    - domain extension, 71
    - security association setup extension, 71
    - session index extension, 71

- overview, 69
- standards-based dynamic keying, 69
- dynamic routing protocol, 15
- dynamic tunnels eliminating need for host route propagation, 16–17

## E

---

- encapsulation, 51
- end devices signaling their own routing updates, 16

## F

---

- FA challenge, 66
- fixed addressing on the CLI, 187
- FLASH-OFDM technology, 215–216
- Foreign Agent,
  - configuration, 83–85, 124
  - enhancements
    - IRDP options, 161
    - local routing to mobile networks, 162–164
    - overview, 161
  - evaluation/troubleshooting, 89–90
  - overview, 22, 129
- Foreign Agent CoA, 22
- frequency of mobility, 196
- future issues
  - AAA-based dynamic key generation, 220–221
  - Cisco SWAN, 217–219
  - MANET, 242–246
  - Mobile IPv6, 221
    - authentication options, 234–236
    - bootstrap, 236–238
    - fast handover mechanism, 240–242
    - HMIPv6, 238–239
    - latency, 240, 242
    - Mobile IPv4 compared, 229–242
    - network access identifiers, 234
    - protocol operation, 221–229
    - transition to, 233
  - public access networks, 207–208
    - cdma2000 technology, 209–210, 212
    - FLASH-OFDM technology, 215–216
    - GSM technology, 213–214
    - wireless LAN, 208–209

## G

---

- GNAE (Generalized Authentication Extension), 58
- GPRS, 213–214
- GSM technology, 213–214

## H

---

- handover
  - other than returning home, 47
  - overview, 33
  - returning home, 48
- handover policy
  - move detection, 28–29
    - link-state triggers, 31, 33
    - new network algorithm, 30
    - steady-state algorithm, 29
- hierarchical mobile IPv6 (HMIPv6), 238–239
- Home Address, 19, 21
- home addressing
  - management
    - AAA server, 190–191
    - dynamic addressing, 184
    - dynamic home address assignment, 186–189
      - fixed addressing on the CLI, 187
      - overview, 183–184
      - static addressing, 184
      - static home addressing with NAI, 192–193
      - static home addressing without NAI, 186
      - virtual networks, 184, 186
- Home Agent
  - configuration. *See* Home Agent configuration
  - enhancements
  - evaluation/troubleshooting, 87
  - NAT, 128
  - network mobility, configuration for, 159–160
    - overview, 157
    - Priority Home Agent Assignment, 160–161
    - redundancy. *See* Home Agent Redundancy
  - overview, 21
- Home Agent configuration, 124, 129
- Home Agent final configuration, 83
- mobile host configuration, 81

- overview, 80
- physical home network configuration, 80
- security association configuration, 83
- virtual home network configuration, 81
- Home Agent Redundancy, 159
  - configuration commands, 107–108
    - active-standby home agent configuration, 108
    - peer-peer home agent configuration, 110–113, 115
  - overview, 104–106
- Home Network, 19, 21
- host route propagation, dynamic tunnels eliminating need for, 16–17

---

## I–J

- identification, 36–37
- incompatibilities, 203
- ingress filtering, 121
- intermediate system configuration, 79
- IOS Mobile IP
  - baseline topology
    - correspondent node configuration, 79
    - foreign agent configuration, 83–86
    - home agent configuration, 80–81, 83
    - intermediate system configuration, 79
    - overview, 77, 79
  - operation and evaluation/troubleshooting
    - foreign agent, 89–90
    - home agent, 87
    - mobile node, 88–89
    - overview, 86
    - routing tables, 90–91
- IPSec
  - and Mobile IP, 130, 132
  - Mobile IP over IPSec over Mobile IP, 132
  - and mobile router, 176–177
- IRDP options, 161

---

## K–L

- keys, 62
- latency, 240, 242
- Layer 2 protocol, 9
- Layer 3 protocol, 9
- Layers 4–7 protocol, 9
- Leung, Kent, 207
- link-state triggers, 31, 33
- load-sa option, 100
- local authorization of static home addresses, 192
- local pool address assignment, 188–189
- local pool selection, 191
- local routing to mobile networks, 162–164
- location discovery, 6–7, 23
  - overview, 28
  - proactive approach, 6
  - reactive approach, 6
- location privacy, 72

---

## M

- management
  - home addressing
    - AAA server, 190–191
    - dynamic addressing, 184
    - dynamic home address assignment, 186–189
    - fixed addressing on the CLI, 187
    - overview, 183–184
    - static addressing, 184
    - static home addressing with NAI, 192–193
    - static home addressing without NAI, 186
    - virtual networks, 184, 186
- MANET (Mobile Ad Hoc Network), 242–246
- messaging, 224
  - ICMP messages, 228–229
  - move detection, 224
  - registration messages, 224–225
  - route optimization messages, 225–227
- metro mobility
  - example, 138, 140–141
  - Network Address Translation (NAT)
    - Home Agent, 128

- Mobile IP NAT configuration, 128–129
    - overview, 126
    - UDP tunneling, 127–128
  - overview, 119–120
  - resource revocation
    - overview, 133–135
  - Registration Revocation configuration, 138
  - Registration Revocation example, 136–137
  - revocation support extension and messages, 135–136
  - reverse tunneling
    - configuration, 124–125
    - delivery style, 122–123
    - overview, 120, 122
    - signaling, 123–124
  - tunnel path MTU, 125
  - VPN integration
    - IPSec and Mobile IP, 130, 132
    - Mobile IP over IPSec over Mobile IP, 132
    - overview, 129–130
- MN-AAA Authentication Extension, 67–68
- MN-FA Authentication Extension, 64–65
- mobile host configuration, 81
- Mobile IP
- agent advertisements
    - handover, 33
    - location discovery, 28
    - move detection, 28–31, 33
    - overview, 24–27
    - router advertisement, 24
    - router solicitation, 24
  - components
    - Care-of Address (CoA), 21–22
    - Correspondent Node (CN), 22
    - Foreign Agent, 22
    - Home Address, 19, 21
    - Home Agent, 21
    - Home Network, 19, 21
    - Mobile Node, 18
    - overview, 18
  - dynamic routing protocol, 15
  - dynamic tunnels eliminating need for host route propagation, 16–17
  - end devices signaling their own routing updates, 16
  - example, 49–50
  - and IPSec, 130, 132
  - over IPSec over Mobile IP, 132
  - overview, 10–11, 13, 15
  - protocol concepts
    - location discovery, 23
    - move detection, 23
    - overview, 22
    - path (re)establishment, 23
    - update signaling, 23
  - registration, 155
    - address fields, 42, 44–45
    - authentication, 41
    - delivery, 46–48
    - identification, 36–37
    - overview, 34–36
    - reply codes, 45–46
    - services, 37–39
  - tunneling, 50
    - encapsulation, 51
    - triangle routing, 51, 53
- Mobile IP Nat configuration
- Foreign Agent, 129
  - Home Agent configuration, 129
  - overview, 128
- Mobile IPv6, 221
- authentication options, 234–236
  - bootstrap, 236–238
  - fast handover mechanism, 240–242
  - HMIPv6, 238–239
  - latency, 240, 242
  - Mobile IPv4 compared, 229–242
  - network access identifiers, 234
  - protocol operation, 221–222
    - messaging, 224–229
    - route optimization, 223
  - transition to, 233
- mobile networks, 147–148, 150
- Mobile Node
- configuration, 85–86
  - evaluation/troubleshooting, 88–89
  - overview, 18
- mobile router
- agent selection, 154–155
  - configuration, 150–151
  - interface, 151–152
  - interface-level configuration, 153–154
  - Mobile IP registration, 155

- mobile networks, 147–148, 150
- overview, 147
- redundancy, 165–166
- routing to and from, 156
- mobility
  - Nomadic laptop mobility protocol, 10
  - OSI protocol stack and full
    - combining mobility protocols, 10
    - Layer 2 protocol, 9
    - Layer 3 protocol, 9
    - Layers 4-7 protocol, 9
    - overview, 8
  - overview, 4
- move detection, 7, 23
  - handover policy, 28–29
    - link-state triggers, 31, 33
    - new network algorithm, 30
    - steady-state algorithm, 29

## N

- network access identifiers (NAI), 234
- Network Address Translation (NAT)
  - Home Agent, 128
  - Mobile IP NAT configuration
    - Foreign Agent, 129
    - Home Agent configuration, 129
    - overview, 128
  - overview, 126
  - UDP tunneling, 127–128
- network management
  - call model, objects matching, 199–200
  - Cisco Enterprise MIB, 199
  - overview, 198
  - RFC 2006 MIB, 199
  - system log messages, 200
- new network algorithm, 30
- nodes, number of, 195–196
- nomadicity, 4, 10
- nonces replay protection, 64

## O

- operation and evaluation/troubleshooting
  - IOS Mobile IP
    - Foreign Agent, 89–90
    - Home Agent, 87
    - Mobile Node, 88–89
    - overview, 86
    - routing tables, 90–91
  - overview, 200
  - path MTU discovery, 200–201
  - security association incompatibilities, 202
  - tunnel transit, 202
  - uRPF, 202
- OSI protocol stack
  - full mobility and
    - combining mobility protocols, 10
    - Layer 2 protocol, 9
    - Layer 3 protocol, 9
    - Layers 4-7 protocol, 9
    - overview, 8

## P

- path (re)establishment, 8, 23
- path MTU discovery, 200–201
- peer-peer home agent configuration, 110–113, 115
- permanent option, 100
- physical home network configuration, 80
- Priority Home Agent Assignment, 160–161
- proactive approach, 6
- proactive handover, 33
- protocol authentication extensions
  - algorithms, 61–62
  - FA challenge, 66
  - GNAE, 58
  - keys, 62
  - MN-AAA Authentication Extension, 67–68
  - MN-FA Authentication Extension, 64–65
  - overview, 58–59
  - replay protection methods, 62–64
  - security associations, 59–60
  - SPI, 61
- protocol concepts
  - location discovery, 23
  - move detection, 23

- overview, 22
- path (re)establishment, 23
- update signaling, 23
- public access networks, 207–208
  - cdma2000 technology, 209–210, 212
  - FLASH-OFDM technology, 215–216
  - GSM technology, 213–214
  - wireless LAN, 208–209
- public wireless LAN, 208–209

## Q

- quality of service (QoS), 174, 176

## R

- RADIUS, 100–101
- reactive approach, 6
- redundancy, 165–166
- registration
  - address fields, 42, 44–45
  - authentication, 41
  - delivery, 46–48
    - handover other than returning home, 47
    - handover returning home, 48
  - deregistration, 38
  - identification, 36–37
  - overview, 34–36
  - reply codes, 45–46
  - services, 37–39
    - broadcast support, 38
    - simultaneous bindings, 39
- Registration Revocation configuration, 138
- Registration Revocation example, 136–137
- replay protection methods
  - nonces replay protection, 64
  - overview, 62
  - timestamp replay protection, 63–64
- reply codes, 45–46
- resource revocation
  - overview, 133–135
  - Registration Revocation configuration, 138
  - Registration Revocation example, 136–137
  - revocation support extension and messages, 135–136

- reverse tunneling
  - configuration, 124–125
  - delivery style, 122–123
  - overview, 120, 122
  - signaling, 123–124
- revocation support extension and messages, 135–136
- RFC 2006 MIB, 199
- rogue reflectors, 135
- rogue repeaters, 135
- route optimization, 223
- router advertisement, 24
- router solicitation, 24
- routing tables, 90–91
- routing updates, end devices signaling their own, 16

## S

- scalability
  - amount of data traffic, 197
  - call model, 194–195
  - example, 197–198
  - frequency of mobility, 196
  - number of nodes, 195–196
  - number of tunnels, 197
  - overview, 194
- security
  - dynamic keying
    - Cisco Dynamic Security Association and Key Distribution, 70–72
    - overview, 69
    - standards-based dynamic keying, 69
  - location privacy, 72
  - overview, 57
  - protocol authentication extensions
    - algorithms, 61–62
    - FA challenge, 66
    - GNAE, 58
    - keys, 62
    - MN-AAA Authentication Extension, 67–68
    - MN-FA Authentication Extension, 64–65
    - overview, 58–59
    - replay protection methods, 62–64
    - security associations, 59–60
    - SPI, 61

- security association configuration, 83
- security association incompatibilities, 203
- security association setup extension, 71
- security associations, 59–60
- security context, 59
- services, 37–39
  - broadcast support, 38
  - simultaneous bindings, 39
- session index extension, 71
- simultaneous bindings, 39
- single-router topology, 91–92
- SPI (security parameter index), 61
- spoofing, 121
- standards-based dynamic keying, 69
- static addressing, 184
- static Colocated Care-of Address, 171
- static home addressing with NAI, 192
  - AAA authorization of static home addresses, 193
  - local authorization of static home addresses, 192
- static home addressing without NAI, 186
- steady-state algorithm, 29
- system log messages, 200

## T

---

- TACACS+, 101
- timestamp replay protection, 63–64
- triangle routing, 51, 53
- troubleshooting. *See* operation and evaluation/
  - troubleshooting
- tunnel path MTU, 125
- tunnel template, 176
- tunnel transit, 202
- tunneling, 50
  - encapsulation, 51
  - number of tunnels, 197
  - triangle routing, 51, 53

## U

---

- UDP tunneling, 127–128
- UMTS, 213–214
- unicast Reverse Path Forwarding (uRPF), 121, 202
- update signaling, 7, 23

## V

---

- virtual home network configuration, 81
- virtual networks, 184, 186
- VPN integration, 129–130

## W–Z

---

- WiFi, 208–209
- wireless technology, 4