



Numerics

802.1q headers, 44

A

AAA attribute

- control planes, 308-309
 - MPLS-based wholesale services, 312
- per-VRF AAA, 234-240
 - accounting, 246-247
 - templates, 241-246
- VRFs, 218-225
 - VHG, 225-227

access cards, 18

access networks, DSL networks, 7-8

access requirements, VPNs, 74-75

accounting

- bridged access networks, 53
- MPLS-VPNs, 214
- per-VRF AAA, 246-247
- PPP, 64-65

address alignment, VPNs, 23

address allocation

- IPv6, 326
- MPLS-based wholesale services, 311

address assignments

- DOCSIS networks, 40-41
- ETTX, 47-49
- PPPoA, 60-63
- RBE networks, 35-37

address management, MPLS-VPNs, 215

address routing, MPLS-based wholesale services, 311

address space size, IPv6, 325-326

address spoofing, bridged access networks, 49-50

addresses

- IPv6, 323, 326-328
 - on-demand address pools, 249-251
 - address assignments, 252-254
 - host-route solution, 251-252
 - overlapping, assigning and managing, 248-254
 - single address, downloading with PPPoA, 60
- "Advanced Topics in MPLS-TE Deployment", 139

aggregation routers, cost considerations, 72

AH header (IPSec), 93

Alverstand, Harald, 334

Any Transport over MPLS (AToM), 335-336

Anycast addresses (IPv6), 328

architectures

- broadband access, bridged access networks, 28-53
- centralized architectures, VPNs, 71-74
- PPP networks, 54
 - accounting, 64-65
 - authentication, 64-65
 - PPPoA, 59-63
 - PPPoE, 54-58
 - QoS (quality of service), 63
 - security, 65

assigning overlapping addresses, 248-254

ATM (Asynchronous Transfer Mode)

- MPLS, compared, 140
- PPPoA, 59

- address assignments, 60-63
- configuration, 59

atm pppatm passive command, 59

AToM (Any Transport over MPLS), 335-336

attributes

- AAA attribute
 - control planes, 308-309, 312
 - per-VRF AAA, 234-247
 - VRFs, 218-227
- BPG, 156-157
- iBGP, 156
- MPLS-VPN reference architecture, 156-158

authentication

- bridged access networks, 53
- IPSec, 93
- IPv6, 324
- MPLS-VPNs, 214
- PPP, 64-65
- VPNs, 21-22

authorizations

- MPLS-VPNs, 214
- remote-access networks, 53

autoconfiguration, IPv6, 329-330

availability, MPLS-VPNs, 212-213

B

- bba-group commands, 58
- BGP (Border Gateway Protocol), 153
 - attributes, 156–157
 - VRF-Lite PEs, routing between, 290–298
- billing mechanisms, DSL services, 5
- bindings, dynamic bindings
 - DHCP servers, 227–230
 - PBR, 231–232
 - SSG, 232–233
 - VHGs, 225, 227
 - VRF Select, 233
 - VRFs, 217–221, 223–225
- BISDN (Broadband Integrated Services Digital Network), 4
- Border Gateway Protocol (BGP). *See* BGP (Border Gateway Protocol)
- BRAS (Broadband Remote Access Server), 332
- bridged access networks, 28–29
 - accounting, 53
 - address spoofing, 49
 - advantages of, 28
 - authentication, 53
 - cabling, DOCSIS, 37–41
 - DSL, RFC 2684, 29–37
 - Ethernet, ETTX, 42–49
 - RBE, 29–30, 32
 - address assignments, 35–37
 - configuration, 32
 - downstream traffic, 30
 - neighbor-to-neighbor traffic, 31
 - packet flow, 30, 34
 - QoS, 33
 - routing, 33–35
 - security, 49–53
- broadband access, 4
 - DSL networks, 6–8
 - popularity of, 3
 - providers, 5–6
 - service models, 8–9
 - VPNs, 27
 - bridged access networks, 28–53
 - PPP, 54–65
 - PPP networks, 54
- Broadband Integrated Services Digital Network (BISDN), 4

- Broadband Remote Access Server (BRAS), 332
- broadcast traffic weaknesses, bridged access networks, 50
- business subscribers, broadband, 9

C

- cabling
 - bridged access networks, 37–41
 - DOCSIS standard, 37–41
 - security, 51
- cable dhcp-giaddr command, 41
- cable helper-address command, 41
- cable source-verify command, 51
- cable subscribers, VRFs, mapping to, 172–176
- campus hop-to-hop topology, VRF-Lite PEs, routing between, 272–281
- CAs (certificate authorities), 96
- case studies
 - D/V/V over Ethernet, 313–321
 - network design, 314–316
 - open access, 317–321
 - service definitions, 313–314
 - managed LNS, 302–312
 - MPLS-based wholesale services, 309–312
 - service definitions, 304–305
 - wholesale services, 305–309
- CE routers, MPLS-VPN architecture, 171
- centralized architectures, VPNs, 71–74
- certificate authorities (CAs), 96
- CIDR (classless interdomain routing), 326
- circuit aggregation, LACs, 306
- circuit-id field (Option 82), 229
- circuits, Layer 2 circuits, dynamically provisioning, 177
- Cisco IOS (Internetwork Operating System)
 - DOCSIS configuration, 39–40
 - MPLS-VPN configuration, 158–162
 - VRs, implementing, 262–263
- classless interdomain routing (CIDR), 326
- client-based service selection, 22
- clients
 - D/V/V over Ethernet, 314–315
 - managed LNS, 306
 - MPLS-based wholesale services, 310

 commands

- atm pppatm passive, 59
- bba-group, 58
- cable dhcp-giaddr, 41
- cable helper-address, 41
- cable source-verify, 51
- crypto isakmp policy, 96
- debug, 285
- debug ip packet, 259
- debug pppoe, 191
- ip helper-address, 36
- ip rsvp, 151
- ipx routing, 85
- keyring, 268
- l2tp tunnel no-session-limit, 129
- load-ppols, 61
- match identity group, 270
- option vpn, 229
- ping, 161
- ppoe enable, 186
- qos-preclassify, 114
- rbe nasip, 36
- redistribute connected, 187
- redistribute static BGP, 187
- router rip, 286
- service-policy, 63
- show crypto ipsec, 101
- show crypto ipsec sa, 100
- show ip interface brief, 83
- show ip route, 83, 154
- show ip vrf, 191
- show ipx interface, 85
- show route, 37
- show vpdn, 191
- test, 186
- test pppoe, 191
- traceroute, 161
- tunnel designation, 287
- tunnel destination, 80
- tunnel mode gre multipoint, 111
- tunnel protect, 111
- tunnel source, 80
- tunnel vrf, 289
- vpdn-group, 58, 199

confidentiality

- GRE, 88
- IPSec, 113

configuration

- cleaning up, VRs, 261
- DOCSIS, IOS configuration, 39–40
- ETTX, 46
- GRE, 78–87
- IPSec, 95–97
 - checking, 104
 - encrypted GRE, 101–104, 106
 - site-to-site IPSec, 98–100
- IPv6, autoconfiguration, 329–330
- L2TP, 120–121, 124–125, 127
- MPLS-TE tunnels, 151–152
- MPLS-VPNs
 - IOS configuration, 158–159, 161–162
 - multi-VRF CE, 206–209
 - PPP Termination configuration, 183–189
- PPPoA, 59
- PPPoE, 56–58
- RBE networks, 32
- two-box VHG, 196–199, 201

connections, VRs (virtual routers), 260

conservative retention mode, LSRs, 146

control plane, AAA attribute, 308–309

CPE-based VPNs, 11, 257

- access requirements, 75
- network-based VPNs, compared, 264–265

crypto isakmp policy command, 96

 D

D/V/V over Ethernet

- case study, 313–321
 - network design, 314–316
 - open access, 317–321
 - service definitions, 313–314
- clients, 314–315
- data confidentiality, VPNs, 16, 210
- Data Over Cable Service Interface Specification (DOCSIS). *See* DOCSIS (Data Over Cable Service Interface Specification)
- DBS (Dynamic Bandwidth Selection), 63
- debug commands, 285
- debug ip packet command, 259
- debug pppoe command, 191
- “Deploying MPLS for Traffic Engineering”, 139

- deployment scenarios, IPv6, 330
 - Enterprise, 330
 - retail ISPs, 331–332
 - wholesale ISPs, 333
- design
 - GRE, 87–91
 - IPSec, 113–115
 - L2TP, 133–135
- Destination Address field (IPv6 headers), 325
- Destination options (IPv6), 329
- device-level redundancies, VPNs, 18
- device-local pools, overlapping device-local pools, assigning and managing, 248
- DHCP servers
 - dynamic bindings, 227–230
 - VPNs, 227–231
- DiffServ
 - LSPs, 165
 - MPLS, 164
- DiffServ-aware TE (DS-TE). *See* DS-TE (DiffServ-aware TE)
- direct PPP termination, monitoring, 190–196
- distributed architectures, VPNs, 71–74
- DMVPNs (dynamic multicast VPNs), IPSec, 107–111
- DOCSIS (Data Over Cable Service Interface Specification), 28
 - address assignment, 40–41
 - cable modem standards, 37–41
 - IOS configuration, 39–40
 - protocol stack, 38
 - SFIDs, 172
- DoS (denial of service) attacks, bridged access networks, 50
- downloading PPPoA pools, 60–61
- downstream traffic, RBE networks, 30
- DSL (digital subscriber line), 6–8
 - billing mechanisms, 5
 - bridged access networks, RFC 2684, 29–37
 - security, 50–51
 - service models, 8–9
 - subscribers, 3
 - mapping to, 175–176
- DSL Access Multiplexers (DSLAMs), 8
- DSL Forum, broadband popularity statistics, 3
- DSLAMs (DSL Access Multiplexers), 8
- dynamic allocation, VRFs, VPNs, 217–218

- Dynamic Bandwidth Selection (DBS), 63
- dynamic bindings
 - DHCP servers, 227–230
 - PBR, 231–232
 - SSG, 232–233
 - VHGs, 225, 227
 - VRF Select, 233
 - VRFs, 217–225
- dynamic multicast VPNs, IPSec, 108
- dynamically provisioning Layer 2 circuits, 177

E

- Edge LSR, 141
- EIGRP (Enhanced Interior Gateway Routing Protocol), 72, 111
- EMF (Ethernet in the First Mile), 7
- encapsulation
 - GRE, 76, 267
 - IPSec, 94–95, 268
 - MPLS, 143–144
 - RBE, 176
- encrypted GRE, configuration, 101–106
- encryption
 - encrypted GRE, configuration, 101–106
 - IPSec, 93
- Enhanced Interior Gateway Routing Protocol (EIGRP), 72, 111
- Enterprise, IPv6, deployment, 330
- ESP header (IPSec), 93
- Ethernet, 28
 - bridged access networks, ETTX, 42–49
 - D/V/V over Ethernet, case study, 313–321
 - DOCSIS, 28
 - laptops, 28
 - LRE, 42, 45
 - PPPoE, 54–56
 - configuration, 56–58
 - service selection and discovery, 58
 - security, 51, 53
- Ethernet in the First Mile (EFM), 7
- Ethernet subscribers, VRFs, mapping to, 174–175
- Ethernet switches, 8

ETTX, 42–49
 address assignment, 47–49
 configuration, 46
 QoS (quality of service), 46–47
 residential ETTX, 43
 extensions, IPv6, 324, 328–329

F

fields, IPv6 headers, 325
 fish problems, TE (Traffic Engineering), 147
 Flow Label field (IPv6 headers), 324
 flow labeling, IPv6, 324
 follows, 240
 fragmentation
 GRE, 91
 IPSec, 114
 MPLS-VPNs, 214
 VPNs, 20
 Frame Relay networks, unnumbered interfaces, 31
 frames, 63
 framework (VPNs), 16
 address alignment, 23
 authentication, 21–22
 availability, 18–19
 data confidentiality, 16
 efficient operation, 17
 efficient routing, 17
 fragmentation, 20
 IP addressing, 22
 Layer 3 services, 23
 multicast, 19
 QoS, 19–20
 resiliency, 18–19
 service selection, 22–23

G

Global addresses (IPv6), 328
 GRE (generic routing encapsulation), 76
 availability, 88
 confidentiality, 88
 configuration, 78–87
 design, 87–91
 efficient operation, 88

encapsulation, 76, 267
 fragmentation, 91
 headers, 77
 IPSec configuration, 101–106
 network-based IP VPNs, building, 266–267
 QoS, 90
 resiliency, 88
 routing, 88
 site VPNs, 76–91

H

headers
 802.1q, 44
 GRE, 77
 IPv4, 323
 IPv6, 323
 fields, 325
 PPPoE, 55
 Hop Limit field (IPv6 headers), 325
 Hop-by-Hop options (IPv6), 329
 host-route solution, overlapping on-demand address
 pools, 251–252
 HSRP, 18
 hub-and-spoke systems, VPNs, 70
 hub-and-spoke topology, 162

I

iBGP (internal Border Gateway Protocol), 72, 156
 attribute exchange, 156
 identifications, remote-access networks, 53
 IGP (Interior Gateway Protocol), 72
 IKE (Internet Key Exchange), IPSec, 94
 implementation, VRs (virtual routers), Cisco IOS,
 262–263
 independent delivery, label distribution, 145
 infrastructure VPNs, 69
 ink protection problems, 148
 inter-exchange carriers (IXCs), 326
 interfaces, routed interfaces, VRF mapping, 175
 Interior Gateway Protocol (IGP), 72
 internal Border Gateway Protocol (iBGP). *See* iBGP
 (internal Border Gateway Protocol)

- Internet Key Exchange (IKE). *See* IKE (Internet Key Exchange)
 - Internet Protocol (IP). *See* IP (Internet Protocol)
 - Internet Service Providers (ISPs). *See* ISPs (Internet Service Providers)
 - IOS (Internetwork Operating System)
 - DOCSIS configuration, 39–40
 - MPLS-VPN configuration, 158–162
 - VR implementation, 262–263
 - IP (Internet Protocol)
 - See also* IPv6 (Internet Protocol version 6)
 - addressing
 - MPLS-VPNs, 215
 - VPNs, 22
 - aggregation, LNS, 307–308
 - packet forwarding, 141–143
 - routing, network-level redundancies, 18
 - TE, 146–148
 - fish problems, 147
 - link congestion, 146–151
 - link congestion problems, 150
 - link protection, 146
 - link protection problems, 150
 - load balancing, 146
 - load-balancing problems, 147, 150
 - ip helper-address command, 36
 - ip rsvp command, 151
 - IP Switching, 140
 - IP VPNs, 257
 - building
 - GRE, 266–267
 - IPSec, 267–271
 - tunnels, 263–266
 - VRs, 257
 - IP-based VPNs, 10–15
 - IPSec
 - availability, 114
 - confidentiality, 113
 - configuration
 - checking, 104
 - encrypted GRE, 101–104, 106
 - site-to-site IPSec, 98–100
 - design, 113–115
 - DMVPNs, 107–111
 - dynamic multicast VPNs, 108
 - efficient operation, 114
 - encapsulation, 268
 - fragmentation, 114
 - multicasting, 114
 - network-based IP VPNs, building, 267–271
 - QoS, 114
 - remote access, 112–113
 - resiliency, 114
 - routing, 114
 - service selection, 115
 - VPNs, 91–93
 - authentication, 93
 - configuration, 95–97
 - encryption, 93
 - IKE, 94
 - transport mode encapsulation, 94–95
 - tunnel mode encapsulation, 94–95
 - IPv6 (Internet Protocol version 6), 323–325
 - See also* IP (Internet Protocol)
 - address allocation, 326
 - address space size, 325–326
 - address types, 328
 - addressing, 323, 326–328
 - authentication, 324
 - autoconfiguration, 329–330
 - deployment scenarios, 330
 - Enterprise, 330
 - retail ISPs, 331–332
 - wholesale ISPs, 333
 - extensions, 324, 328–329
 - flow labeling, 324
 - headers, fields, 325
 - privacy capabilities, 324
 - security, 324
 - ipx routing command, 85
 - ISPs (Internet Service Providers)
 - broadband access, 5–6
 - MPLS-based wholesale services, 311
 - retail ISPs, IPv6, 331–332
 - wholesale ISPs, IPv6, 333
 - IXCs (inter-exchange carriers), 326
-
- ## K-L
- keyring command, 268
 - Kumaraswamy, Jay, 139
 - L2 services, 338
 - L2TP, 336–337

- configuration, 120–121, 124–127
- design, 133–135
- scaling, 127–133
- VPNs, 115–120
 - session setup, 119–120
 - tunnel setup, 117–118
- L2TP Access Concentrator (LACs). *See* LACs (L2TP Access Concentrators)
- L2TP Network Server (LNS). *See* LNS (L2TP Network Server)
- l2tp tunnel no-session-limit command, 129
- L2VPNs (Layer 2 VPNs), 323, 334, 337–338
 - pseudo-wires, 334–337
- L3 services, MPLS-VPNs, 215
- label distribution
 - MPLS, LDP, 144–146
 - timing of, 145–146
- Label Distribution Protocol (LDP). *See* LDP (Label Distribution Protocol)
- label switch router (LSR). *See* LSR (label switch router)
- labels
 - distribution, MPLS, 144
 - switching, 140
- label-switched paths (LSPs), 142
- LACs (L2TP Access Concentrators), 116
 - circuit aggregation, 306
- laptops, Ethernet, 28
- Layer 2 and 3 core networks, VPNs, building over, 12–13
- Layer 2 circuits, dynamically provisioning, 177
- LDP (Label Distribution Protocol), 142
 - MPLS, 144–146
- liberal retention mode, LSRs, 146
- link congestion, TE (traffic engineering), 146, 150
- Link local addresses (IPv6), 328
- Link Local Use Addresses allocation (IPv6 addresses), 327
- link protection
 - MPLS, 151
 - TE, 146–150
- LNS (L2TP Network Server), 116, 302
 - IP aggregation, 307–308
 - managed LNS, case study, 302–312
- load balancing, 19
 - TE, 146–150
- load-pools command, 61

- LRE (Long Reach Ethernet), 42, 45
- LSPs (label-switched paths), 142
 - DiffServ, 165
- LSRs (label switch routers), 141
 - conservative retention mode, 146
 - independent delivery, 145
 - label distribution, 144
 - liberal retention mode, 146
 - on-demand delivery, 145
 - ordered delivery, 145
 - unsolicited delivery, 145

M

- managed LNS
 - case study, 302–312
 - MPLS-based wholesale services, 309–312
 - service definitions, 304–305
 - wholesale services, 305–309
 - IP aggregation, 307–308
 - service availability, 309
- mapping
 - cable subscribers to VRFs, 172–176
 - DSL subscribers to VRFs, 175–176
 - Ethernet subscribers to VRFs, 174–175
- match identity group command, 270
- maximum transmission units (MTUs). *See* MTUs (maximum transmission units)
- metropolitan-area networks (MANs). *See* MANs (metropolitan-area networks)
- monitoring
 - direct PPP termination, 190–196
 - two-box VHG, 202–206
- MPLS (Multiprotocol Label Switching), 139
 - accounting, 214
 - address management, 215
 - ATM, compared, 140
 - authentication, 214
 - authorization, 214
 - availability, 212–213
 - CE, 171
 - configuration, PPP Termination, 183–189
 - data confidentiality, 210
 - DHCP servers, 227–231
 - DiffServ, 164
 - direct PPP termination, monitoring, 190–196

- efficient operation, 210
- efficient routing, 211
- encapsulation, 143–144
- fragmentation, 214
- IP addressing, 215
- L3 services, 215
- label distribution, LDP, 144–146
- link protection, 151
- multicasting, 212
- multi-VRF CE configuration, 206–209
- network taxonomy, 142
- overlapping addresses, assigning and managing, 248–254
- packet forwarding, 141–143
- PE, 169–172
- popularity of, 140
- proxy RADIUS, 234–240
- QoS, 163, 213
 - packet headers, 163–164
 - pipes, 164–166
 - tunnels, 164–166
- requirements, 210
- resiliency, 212–213
- service selection, 214
- shim header, 143
- TE, 146
 - DS-TE, 167
 - fish problems, 147
 - link congestion, 146–151
 - link congestion problems, 150
 - link protection, 146
 - link protection problems, 148, 150
 - load balancing, 146
 - load-balancing problems, 147, 150
- tunnel-load balancing, 150
- two-box VHG, monitoring, 202–206
- VHG, 177–182
- VRFs, 172–176, 217–227
- wholesale VPNs, 217

“MPLS Architecture Overview”, 139

MPLS VPNs

- peer model, 14–15
- IOS configuration, 158–162
- MPLS-VPN reference architecture, 152–158
- VRs (virtual routers), 260

- MPLS-based wholesale services, 309–310
 - AAA control plane, 312
 - address allocation, 311
 - address routing, 311
 - clients, 310
 - ISP PE, 311
 - multicasting, 312
 - PTA PE, 310–311
 - QoS, 312
- MPLS-TE tunnels, configuring, 151–152
- MTU (maximum transmission unit), debugging, 20
- multicast VPNs, 19
- Multicast addresses (IPv6), 327–328
- multicasting
 - MPLS-based wholesale services, 312
 - MPLS-VPNs, 212
- multipoint tunnels, 111
- Multiprotocol Label Switching (MPLS). *See* MPLS (Multiprotocol Label Switching)
- multi-VRF CE, configuration, 206–209

N

- neighbor-to-neighbor traffic, RBE networks, 31
- network address translation, VPNs, 135–136
- network availability, managed LNS, 309
- network design
 - D/V/V over Ethernet, 314–316
 - design checks, 301
- network VPNs, tunnels, 264
- network-based IP VPNs, 11
 - access requirements, 75
 - building
 - GRE, 266–267
 - IPSec, 267–271
 - tunnels, 263–266
 - CPE-based VPNs, compared, 264–265
- network-level redundancies, VPNs, 18–19
- Next Header field (IPv6 headers), 325
- Next Hop Server (NHS), 111
- NHRP, 111
- NHS (Next Hop Server), 111
- nodes, tunnels, 70
- non-IP traffic site VPNs, GRE
 - (generic routing encapsulation), 76–91
 - configuration, 78–87

- design, 87–91
- encapsulation, 76
- headers, 77
- N-squared problem, tunnels, 70

O

- ODAP (On Demand Address Pools), 62, 249–251, 309
 - address assignments, 252–254
 - host-route solution, 251–252
- on-demand delivery, label distribution, 145
- Open Access
 - D/V/V over Ethernet, adding, 317–321
 - VPNs, 135
 - Network Address Translation, 135–136
 - policy-based routing, 136
- Open Shortest Path First (OSPF), 72
- operators, broadband access, 4–8
- option vpn command, 229
- ordered delivery, label distribution, 145
- Osborne, Eric, 139
- OSPF (Open Shortest Path First), 72
- overlapping addresses, assigning and managing, 248–254
- overlay VPNs, 13–14

P

- packet flow, RBE networks, 30, 34
- packet forwarding, 141–143
- packet headers, QoS (quality of service), 163–164
- Payload Length field (IPv6 headers), 325
- PBR (policy-based routing), dynamic bindings, 231–232
- peer model, MPLS VPNs, 14–15
- penultimate hop popping (PHP), 142, 164
- per-VRF AAA, 234–240
 - accounting, 246–247
 - templates, 241–246
- PEs
 - pseudo-wires, 334–337
 - MPLS-VPN architecture, 169–172
 - VRF-Lite PEs, routing between, 271–281, 284–298
- PHP (penultimate hop popping), 142, 164
- ping command, 161
- pipes, QoS (quality of service), 164–166
- point of presence (POP). *See* POP (point of presence)
- Point-to-Point Protocol (PPP). *See* PPP (Point-to-Point Protocol)
- Point-to-Point Protocol over ATM (PPPoA). *See* PPPoA (Point-to-Point Protocol over ATM)
- point-to-point tunnels, 257
 - VPNs, 69
- policy-based routing, VPNs, 136
- pools
 - downloading at startup, PPPoA, 60–61
 - ODAP, 62
- POP (point of presence), 72
 - broadband POP, 73
- port-based authentication, PPP (Point-to-Point Protocol), 65
- PPP (Point-to-Protocol) networks, 54
 - accounting, 64–65
 - authentication, 64–65
 - PPPoA (PPP over ATM), 59–63
 - PPPoE (PPP over Ethernet), 54–58
 - QoS, 63
 - security, 65
 - termination, monitoring, 190–196
 - VRF mapping, 176
- PPP Termination configuration, MPLS-VPN architecture, 183–189
- PPPoA (PPP over ATM), 59
 - address assignments, 60–63
 - configuration, 59
- PPPoE (PPP over Ethernet), 54–56
 - configuration, 56–58, 183–189
 - service selection and discovery, 58
- pppoe enable command, 186
- Priority field (IPv6 headers), 324
- private VLANs, 52
- processor cards, 18
- protocol stacks
 - DOCSIS, 38
 - VHG, 196
- Provider-Based Unicast Address allocation (IPv6 addresses), 327
- providers, broadband access, 5–6

- provisioning, Layer 2 circuits, dynamically
 - provisioning, 177
- proxy RADIUS, VPNs, 234–240
- pseudo-wires, PEs, 334–337
- PTA PE, MPLS-based wholesale services, 310–311

Q-R

- QoS (quality of service)
 - ETTX, 46–47
 - GRE, 90
 - MPLS, 163
 - packet headers, 163–164
 - pipes, 164–166
 - tunnels, 164–166
 - MPLS-based wholesale services, 312
 - MPLS-VPNs, 213
 - PPP, 63
 - RBE networks, 33
 - VPNs, 19–20
- qos-preclassify command, 114
- RBE (routed bridge encapsulation), 169, 176
 - bridged access networks, 29–30, 32
 - address assignments, 35–37
 - configuration, 32
 - downstream traffic, 30
 - neighbor-to-neighbor traffic, 31
 - packet flow, 30, 34
 - QoS, 33
 - routing, 33–35
 - VRF mapping, 176
- rbe nasip command, 36
- redistribute connected command, 187
- redistribute static BGP command, 187
- remote access, IPSec, 112–113
- remote-access networks, 53
- remote-id field (Option 82), 229
- Reserved allocation (IPv6 addresses), 326
- Reserved for IPX allocation (IPv6 addresses), 327
- Reserved for Neutral-Interconnect-Based Unicast
 - Addresses allocation (IPv6 addresses), 327
- Reserved for NSAP allocation (IPv6 addresses), 326
- residential subscribers, broadband, 9
- resiliency, MPLS-VPNs, 212–213
- retail ISPs, IPv6, 331–332
- retail providers, broadband access, 5

- retrofitting tunnels, 77
- RFC 2547, MPLS-VPN reference architecture, 152–158
- RIP, VRF-Lite PEs, routing between, 281, 284–289
- RIP to BGP topology, 290, 293–297
- Routed Bridge Encapsulation (RBE). *See* RBE (Routed Bridge Encapsulation)
- routed interfaces, DSL subscribers, VRF mapping, 175
- route-distinguisher attribute (BGP), 157
- router rip command, 286
- routers
 - cost considerations, 72
 - VRs (virtual routers), 257–262
 - configuration cleanup, 261
 - connecting, 260
 - implementation, 262–263
 - IP VPNs, 257
 - logical router process, 258
 - multiple VRs on single device, 258
 - operational neatness, 262
 - services, 258, 261
 - VRF-Lite, 257
- route-target attribute (BGP), 157
- routing
 - addresses, MPLS-based wholesale services, 311
 - RBE networks, 33–35
 - VPNs, 17, 211
 - VRF-Lite PEs, routing between, 271–298

S

- SAs (security associations), 92
- scaling networks, L2TP, 127–133
- SCCRQs (Start-Control-Connction-Requests), 117
- security
 - bridged access networks, 49–53
 - address spoofing, 49
 - authentication, 53
 - cable broadband networks, 51
 - DSL broadband networks, 50–51
 - Ethernet networks, 51, 53
 - IPv6, 324
 - PPP, 65
- security associations (SAs), 92

Security Parameters Index (SPI) field, ESP header, 92

server selection override field (Option 82), 230

service availability, managed LNS, 309

service definitions, D/V/V over Ethernet, 313–314

service flow IDs (SFIDs). *See* SFIDs (service flow IDs)

service models, broadband access, 8–9

service selection

- MPLS-VPNs, 214
- VPNs, 22–23

service selection and discovery, PPPoE (Point-to-Point Protocol over Ethernet), 58

service-policy command, 63

SFIDs (service flow IDs), 173

- DOCSIS 1.1 specifications, 172

shim headers (MPLS), 143

show crypto ipsec command, 101

show crypto ipsec sa command, 100

show ip interface brief command, 83

show ip route command, 83, 154

show ip vrf command, 191

show ipx interface command, 85

show route command, 37

show vpdn command, 191

Site local addresses (IPv6), 328

Site Local Use Addresses allocation (IPv6 addresses), 327

site VPNs

- GRE, 76–91
 - configuration, 78–87
 - design, 87–91
 - encapsulation, 76
 - headers, 77
- IPSec, requirements, 113
- requirements, 210
- tunnels, 263

site-to-site IPSec, configuration, 98–100

site-to-site VPNs, 10–11, 69

- access requirements, 74
- CPE-based, 70

Source Address field (IPv6 headers), 325

SSG (Service Selection Gateway), dynamic bindings, 232–233

Start-Control-Connection-Requests (SCCRQs), 117

stateful autoconfiguration, IPv6, 329–330

stateless autoconfiguration, IPv6, 329–330

subnet selection option field (Option 82), 230

T

Tag Switching, 140

tag switching, 140

TE (Traffic Engineering), 140

- DS-TE (DiffServ-aware TE), 167
- fish problems, 147
- link congestion, 146–151
- link congestion problems, 150
- link protection, 146
- link protection problems, 148, 150
- load balancing, 146
- load-balancing problems, 147, 150
- MPLS, 146

telecommuter VPNs, 10, 69

- access requirements, 75
- IPSec, design requirements, 113
- requirements, 210

telnet commands, 161

templates, per-VRF AAA, 241–246

termination, 183

- PPP, monitoring, 190–196

test command, 186

test pppoe command, 191

timing, label distribution, 145–146

topologies, VHG, 197

traceroute command, 161

Traffic Engineering (TE). *See* TE (Traffic Engineering)

transport mode encapsulation, IPSec, 94–95

trunk cards, 18

tunnel destination command, 80, 287

Tunnel Endpoint Discovery (TED), 108

tunnel mode encapsulation, IPSec, 94–95

tunnel mode gre multipoint command, 111

tunnel protect command, 111

tunnel source command, 80

tunnel vrf command, 289

tunnel-load balancing, MPLS, 150

tunnels

- MPLS, QoS, 164–166
- MPLS-TE tunnels, configuring, 151–152
- multipoint tunnels, 111
- network VPNs, 264
- network-based IP VPNs, building, 263–266
- nodes, 70
- N-squared problem, 70

- point-to-point tunnels, 257
- retrofitting, 77
- site VPNs, 263
- TED, 108
- tunnel protection, 111
- VPNs, 69–70
- two-box VHG, 196–201
 - monitoring, 202–206
- two-box VHG (virtual home gateway), 180

U-V

- Unassigned allocation (IPv6 addresses), 326–327
- Unicast addresses (IPv6), 328
- unnumbered interfaces, Frame Relay networks, 31
- unsolicited delivery, label distribution, 145
- Version field (IPv6 headers), 324
- VHGs (Virtual Home Gateways), 170
 - AAA attribute (VRF), 225–227
 - dynamic bindings, 225–227
 - protocol stack, 196
 - topology, 197
 - two-box VHG, 180, 196–199, 201
- Video On Demand (VOD) infrastructure, 314
- virtual private networks (VPNs). *See* VPNs (virtual private networks)
- VLANs (Virtual LANs), 51
 - private VLANs, 52
- vpdn-group command, 199
- vpdn-group commands, 58
- vpn-id field (Option 82), 230
- VPNs (virtual private networks), 10, 27, 69, 140
 - access requirements, 74–75
 - accounting, 214
 - address management, 215
 - authentication, 214
 - authorization, 214
 - availability, 212–213
 - bridged access networks
 - accounting, 53
 - authentication, 53
 - cable, 37–41
 - Ethernet, 42–49
 - security, 49–53
 - bridges access networks, 28–29
 - DSL, 29–37
 - centralized architecture, 71–74
 - CPE VPNs, 257
 - CPE-based VPNs, 11
 - access requirements, 75
 - data confidentiality, 210
 - deployment, 10
 - DHCP servers, 227–231
 - distributed architecture, 71–74
 - efficient operation, 210
 - efficient routing, 211
 - fragmentation, 214
 - framework, 16
 - address alignment, 23
 - authentication, 21–22
 - availability, 18–19
 - data confidentiality, 16
 - efficient operation, 17
 - efficient routing, 17
 - fragmentation, 20
 - IP addressing, 22
 - Layer 3 services, 23
 - multicast, 19
 - QoS, 19–20
 - resiliency, 18–19
 - service selection, 22–23
 - hub-and-spoke systems, 70
 - infrastructure VPNs, 69
 - Internet access, 11
 - IP addressing, 215
 - IP VPNs, 257
 - IP-based VPNs, 10–15
 - IPSec, 91–93
 - authentication, 93
 - configuration, 95–104, 106
 - design, 113–115
 - DMVPNs, 107–111
 - dynamic multicast VPNs, 108
 - encryption, 93
 - IKE, 94
 - remote access, 112–113
 - transport mode encapsulation, 94–95
 - tunnel mode encapsulation, 94–95
 - IPv6, 323–325
 - address space size, 325–326
 - addressing, 326–328

- autoconfiguration, 329–330
- deployment scenarios, 330–333
- extensions, 328–329
- L2TP, 115–120
 - configuration, 120–127
 - design, 133–135
 - scaling, 127–133
 - session setup, 119–120
 - tunnel setup, 117–118
- L2VPNs (Layer 2 VPNs), 323, 334, 337–338
 - pseudo wires, 334–337
- L3 services, 215
- Layer 2 and 3 core networks, building over, 12–13
- MPLS-VPN architecture, 169
 - CE, 171
 - IOS configuration, 158–162
 - PE, 169–172
 - peer model, 14–15
 - VHG, 177–182
 - VRFs, 172–176
- MPLS-VPN reference architecture, 152–156
 - attributes, 156–158
- multicasting, 212
- network VPNs, tunnels, 264
- network-based IP VPNs, building, 263–271
- network-based VPNs, 11
 - access requirements, 75
- Open Access, 135
 - Network Address Translation, 135–136
 - policy-based routing, 136
- overlapping addresses, assigning and managing, 248–254
- overlay VPNs, 13–14
- PPP (Point-to-Point Protocol) networks, 54
 - accounting, 64–65
 - authentication, 64–65
 - PPPoA, 59–63
 - PPPoE, 54–58
 - QoS, 63
 - security, 65
- proxy RADIUS, 234–240
- QoS (quality of service), 213
- resiliency, 212–213
- service selection, 214
- site VPNs
 - GRE, 76–91
 - requirements, 210
 - tunnels, 263
- site-to-site VPNs, 10–11, 69
 - access requirements, 74
 - CPE-based, 70
- telecommuter VPNs, 10, 69
 - access requirements, 75
 - requirements, 210
- tunnels, 69–70
- two-box VHG, monitoring, 202–206
- VRFs
 - AAA attribute, 218–221, 223–227
 - dynamic VRF allocation, 217–218
- VRs, 258–262
 - implementing, 262–263
- wholesale VPNs, 11, 217
 - access requirements, 75
 - requirements, 210
- VRF Select, dynamic bindings, 233
- VRF-Lite, 257, 262
 - PEs, routing between, 271–281, 284–298
- VRF (VPN Routing and Forwarding), 158–159
 - AAA attribute, 218–225
 - VHG, 225–227
 - binding, 218
 - cable subscribers, mapping to, 172–176
 - DSL subscribers, mapping to, 175–176
 - dynamic allocation, 217–218
 - Ethernet subscribers, mapping to, 174–175
 - MPLS-VPN architecture, 172–176
 - multi-VRF CE, 206–209
 - names, 218–221, 223–225
 - options, 161
 - per-VRF AAA, 234–240
 - accounting, 246–247
 - templates, 241–246
- VRs (virtual routers), 257–262
 - configurations, cleaning up, 261
 - connecting, 260
 - implementation, Cisco IOS, 262–263
 - IP VPNs, 257
 - logical router process, 258
 - MPLS VPNs, 260

- multiple VRs, single device, 258
- operational neatness, 262
- services, 258, 261
- VRF-Lite, 257

W

- web-based service selection, 22
- wholesale ISPs, IPv6, 333
- wholesale providers, broadband access, 5
- wholesale services
 - managed LNS case study, 305–309
 - MPLS-based wholesale services, 309–310
 - AAA control plane, 312
 - address allocation, 311
 - address routing, 311
 - clients, 310
 - ISP PE, 311
 - multicasting, 312
 - PTA PE, 310–311
 - QoS, 312
- wholesale VPNs, 11, 217
 - access requirements, 75
 - IPSec, design requirements, 113
 - requirements, 210