



Symbols

<backspace> command, 770
 <down arrow> command, 770
 <Enter> command, 770
 ? command, 769
 <Return> command, 770
 <Tab> command, 770
 <up arrow> command, 770

Numerics

32-bit dotted decimal notation, 18
 6to4 tunneling, 58–59

A

ABRs (area border routers), 223, 276–277
 configuring OSPF passing routes between areas, 311
 route summarization configuration example, 289
 access (vty), denying, 691
 Access layer, 6–7
 access lists, 43, 63, 450, 673–674, 829
 configuration exercise, 68–71
 configuring, 676
 NAT, 39–40
 verification, 693
 creating, 677
 distribute lists, 735
 effects of placing on routers, 681
 extended
 configuring, 683–686
 example, 689–690
 in distribute lists, 734
 placement, 690–691
 process flow, 682
 extensions, backwards compatibility, 674
 route maps, 42
 displaying, 471, 860
 implementing, 465–470, 860
 sequence numbering, 43–44, 452
 standard, 674
 example, 680–681
 numbering, 674
 types of, 674
 vty, 691
 wildcard masks, 676
 examples, 677
 implicit, 679
 access-class command, 692, 777
 access-list 64 permit 10.3.1.0 command, 463
 access-list command, 463, 777–778
 ACKs (EIGRP), 180
 ACL-based NATs, 70
 active routes
 EIGRP, 181, 201
 vs. passive routes, 149
 active state troubleshooting (BGP), 571
 AD (advertised distance), 157
 adding EIGRP to Novell RIP/SAP network, 704
 additive keyword (set community command), 745
 addressing
 6to4 tunnel addresses, 59
 CLNS
 NET addresses, 368
 NSAP addresses, 365–366
 discovery (HSRP), 700–701
 integrated IS-IS NET, 382
 IPv6, 47
 aggregation, 49
 format, 48
 types, 48
 nonscalable network addressing, 15–16
 redistribution, 754–757
 address-violation command, 785
 adjacencies
 broadcast networks, 242–243
 EIGRP, 148
 IS-IS routing, 356
 LANs, 381
 link-state database, 379–380
 nonbroadcast multiaccess networks, 244
 OSPF, 223
 OSPF neighbor adjacency establishment
 exchange process and adjacency states, 229–233
 Hello protocol, 228

- point-to-point links, 241
- WANs, 382
- administrative distance, 423
 - IP routing protocols, 113–114
 - modifying, 457–458, 463
 - overview, 456
 - redistribution example, 459–463
 - route selection, 455
 - routing protocols, 423
 - static routes, 515
- advanced distance vector routing protocols, 517
 - B, 515–516, 542, 573, 597
 - BGP, 512
 - appropriate use of, 513, 861
 - ASs, 507–508
 - CIDR, 605–606
 - creating summary addresses, 611–612
 - default routes, 516–517
 - message types, 523–525, 569, 572, 863
 - paths, 515
 - resetting sessions, 557–559
 - RFCs, 510
 - route selection, 543–545, 616
 - static routes, 514–516
 - synchronization rule, 541
 - tables, 522, 862
 - troubleshooting, 568
 - verifying operation, 564–567
- EIGRP, 146
 - configuring, 166
 - DUAL, 157, 161–165, 201, 837
 - feasible successors, 147
 - going active on a route, 181
 - hello packets, 148, 836
 - hold time, 152
 - load balancing, 173–174
 - neighbor tables, 146
 - operational characteristics, 146
 - packets, 148, 836
 - query scoping, 182
 - reliability, 151
 - route summarization, 170–173
 - routing process, 144
 - scalability variables, 181–182, 191
 - successors, 146
 - summarization, 145
 - tiered network model, 192
 - topology tables, 146, 152
 - verifying operation, 192–193
 - WAN links, 175–176, 180
- advanced IP addressing, 3
 - benefits of optimized IP addressing plans, 11–13
 - planning, 4
 - scalable network addressing example, 14
- advertised distance (AD), 157
- advertising
 - networks into BGP, 638
 - networks into IGP, 638–639
- AFI (authority and format identifier), 366
- aggregate addressing (BGP), 606
- aggregate-address command, 611, 867
- aggregation (IPv6 addresses), 49
- aggregator attribute (BGP), 606, 867
- APNIC (Asia Pacific-NIC), 509
- appletalk cable-range command, 779
- AppleTalk commands, 779
- AppleTalk configuration commands, 779
- appletalk discovery command, 779
- appletalk protocol command, 779
- appletalk routing command, 780
- appletalk zone command, 780
- application layer (OSI model), 813
- applying
 - prefix lists to BGP, 734–740
 - route maps to updates, 742
- area authentication, 721
- area border routers. *See* ABRs, 223, 276
- area stub command, 296
- areas
 - configuring, 712–717
 - IS-IS routing, 363
 - NSSAs, 300–302, 709–711
 - OSPF, 293
 - stubby areas, 295
 - configuration, 296
 - routing tables, 300
 - totally stubby areas, 297
 - configuration, 298
 - routing tables, 300
- ARIN (American Registry for Internet Numbers), 508
- AS (autonomous system), 419, 507–508
 - multihoming, 627
 - default routes from all providers, 628, 640
 - examples, 635–637
 - full routing table from each provider, 631–633
 - partial routing table from each provider, 629

- redistribution, 422–423
 - advertising networks into BGP, 637
 - advertising networks into IGP, 638–639
 - best path selection, 422
 - configuring, examples, 757–760
 - defining default metric, 435–436, 477
 - static routes, 442–444
 - verifying operation, 464
 - ASBRs (autonomous system boundary routers), 275–277, 290
 - AS-path attribute (BGP), 528
 - assigned TCP port numbers, 686–687
 - assigned UDP port numbers, 688
 - atomic aggregate attribute (BGP), 606, 867
 - att, 529, 531
 - attributes, 527, 532
 - BG, 528
 - BGP, 525–526
 - communities, 743
 - defined BGP attributes, 527
 - MED, 534
 - optional attributes, 526
 - optional transitive, 742
 - type codes, 527
 - weight, 535–536
 - authentication (IS-IS), 719–723
 - authority and format identifier (AFI), 366
 - autoconfiguration, 50
 - auto-cost reference-bandwidth command, 285
 - automatic network-boundary summarization
 - classful routing protocols, 100
 - classless routing protocols, 107
 - automatic summarization
 - BGP, 119
 - disabling, 172
 - EIGRP, 172
 - autonomous system boundary routers, 275–277, 290
 - autonomous system. *See* AS
 - auto-summary command, 108
- B**
-
- backbone layer, 6
 - backwards compatibility (IP access list extensions), 674
 - bandwidth (EIGRP), 176
 - bandwidth command, 775, 781
 - banner command, 773
 - BDRs, 243
 - electing, 242
 - setting priorities, 243
 - believability, 422–423
 - best paths (BGP)
 - selecting paths, 543–545
 - selection process, 616
 - best route selection, 422
 - BGP (Border Gateway Protocol), 507, 740
 - administrative distance, modifying, 458–459
 - aggregator attribute, 606, 867
 - appropriate use of, 513, 861
 - AS path, 507–508, 519
 - AS-path attribute, 528
 - atomic aggregate attribute, 606, 867
 - attributes, 525–526
 - defined BGP attributes, 527
 - optional attributes, 526
 - type codes, 527
 - automatic route summarization, 119
 - BGP-4, 511
 - CIDR, 605–606
 - communicative use of TCP, 518
 - community attribute, 533
 - community lists, 744
 - configuration commands, 546
 - configuration mode, 547
 - configuring
 - configuration examples, 560–564
 - defining BGP neighbors, 548
 - defining networks that BGP advertises, 555–556
 - defining source IP addresses, 549–550
 - EBGP multihop, 552–553
 - examples, 729–732
 - default routes, 516–517
 - distribute lists, 732–735
 - floating static routes, 515–516
 - IBGP full mesh, 538
 - IGP adjacencies, 537
 - keepalive messages, 524–525
 - local-preference attribute, 532–533
 - MED attribute, 534
 - message types, 523
 - multihoming
 - default routes from all providers, 628, 640
 - examples, 635–637
 - types of multihoming, 627

- neighbor relationships, 517, 520
 - external BGP neighbors, 520, 534
 - internal BGP neighbors, 521
- next-hop attribute, 529, 531, 553
- notification messages, 525
- open message, 524–525, 569, 572, 863
- operation overview, 536
- optional transitive attributes, 742
- origin attribute, 532
- partial-mesh and full-mesh examples, 538–540
- path manipulation, 614–617
- path of last resort, 515
- path selection, 544–545
- path vector, 519
- peer groups
 - configuring, 546–547
 - disabling, 549
- policy-based routing, 512
- prefix lists
 - announcing to Internet, 628
 - characteristics, 735
 - configuring, 736–739
 - exact matches, 737
 - sequence numbers, 739
 - verifying, 740–741
- prefixes, applying, 734
- redistribution, 637–639
- resetting sessions, 557–559
- RFCs, 510
- route manipulation
 - configuring weight, 626
 - setting local preference, 618–621
 - setting the MED with route maps, 622–626
- route selection, 543–545, 616
- route summarization, 608–610
- scalability, 511–512
- split horizon, 537, 746
- static routes, 514–515
 - administrative distance, 515
 - example, 516
- synchronization, disabling, 556
- synchronization rule, 541–542, 573, 597
- tables, 522, 611–613, 862
- TCP, 517
- terminology and concepts, 517
- troubleshooting
 - active state, 571
 - debug ip bgp updates command output, 568
 - idle states, 570
 - neighbor states, 569
- TTL, configuring, 552
- update messages, 524–526
- use between ASs, 509
- verifying operation, 564
 - show ip bgp command output, 564–566
 - show ip bgp neighbors command output, 566
 - show ip bgp summary command output, 567
 - weight attribute, 535–536
- BGP-4, 511
- BGP4+, 61
- bgp always-compare-med command, 535
- bgp bestpath missing-as-worst command, 544
- bgp cluster-id command, 752
- bidirectional communication, 230
- binary notation, 665
- black holes, 541
- boot system command, 773
- Border Gateway Protocol. *See* BGP
- boundary routers, 419
- broadcast keyword, 67, 99
- broadcast networks, 242–243, 376–377
- broadcast storms, 695
- broadcasts, helper addresses, 695–696
 - configuring, 697–698
 - example, 698–700
 - forwarding to multiple servers, 699–700
 - server placement, 696

C

- calculating
 - costs of E1 and E2 routes, 284
 - EIGRP metric, 154–155
 - OSPF metric, 285
 - subnet masks, 670–672
 - VLSMs, 26
- Catalyst 2950 Switches, 782
- Catalyst switches, 785
 - configuration commands, 785
 - interface configuration commands, 786
- CDP (Cisco Discovery Protocol), 97–99

- cdp enable command, 775, 786
- cdp run command, 773
- cdp timer global command, 99
- cells, 814
- characteristics
 - BGP prefix lists, 735
 - OSI model, 806
- CIDR (classless interdomain routing), 3, 32–34
 - BGP, 605–606
 - example, 33–34
 - vs. route summarization, 34
- Cisco Discovery Protocol (CDP), 97
- Cisco IOS, 773
 - configuration file commands, 773
 - EXEC commands, 775, 780
 - interface configuration commands, 774
 - IP configuration commands, 777
 - IPX commands, 778
- Cisco IOS Release 10.3, 674
- Class C networks, 33
- classes (IP addresses), 668–669
- classful addressing, 669
- classful routing protocols, 100, 104–105
 - automatic network-boundary summarization, 100
 - route summarization, 32
 - routing tables, 103
 - summarizing routes in discontinuous networks, 102
- classless interdomain routing. *See* CIDR
- classless routing protocols
 - automatic network-boundary summarization, 107
 - concepts, 106
 - forwarding, 125
 - migrating to, 122–134
 - route summarization, 28
 - subnetting requirements, 107
- clear counters command, 770
- clear frame-relay-inarp command, 780
- clear ip bgp command, 557–559
- clear ip bgp peer-group command, 547
- clear ip nat translation command, 775
- clear ip route * command, 131
- clear line command, 770
- clients
 - route reflectors, 748
 - verifying, 753
- CLNP (Connectionless Network Protocol), 355
- CLNS (Connectionless Network Service), 355–356
 - IS-IS operations
 - criteria and path selection, 383–384
 - integrated IS-IS NET addressing, 382
 - intra-area and interarea addressing and routing, 370–372
 - IS-IS PDUs, 373–375
 - link-state database synchronization and adjacency, 379–380
 - show commands, 385–389
 - topologies, 376–378
 - NET addresses, 368
 - NSAP addresses, 365–366
 - troubleshooting, 385
- clock rate command, 775
- clock set command, 770
- cluster IDs, 748, 752
- cluster lists, 748
- clusters, 748, 751
- commands
 - access-class, 692
 - aggregate-address, 611, 867
 - AppleTalk, 779
 - AppleTalk configuration, 779
 - bgp always-compare-med, 535
 - bgp bestpath missing-as-worst, 544
 - bgp cluster-id, 752
 - BGP configuration, 546
 - Catalyst 1900/Catalyst 2950 Switch IOS, 782
 - Catalyst switch configuration, 785–786
 - clear ip bgp, 557
 - clear ip bgp peer-group, 547
 - configuration (WAN interfaces), 781
 - debug eigrp packets, 193
 - debug ip policy, 471
 - default-information originate, 291
 - default-information originate always, 517
 - distance bgp, 458–459
 - distribute list-out, 448
 - ICND router, 769–770
 - interface configuration, 774–775
 - IP, 775–776
 - ip access group, 678
 - ip community list, 744
 - ip default network, 444
 - ip default-gateway, 444
 - ip default-network, 443–444
 - ip forward-protocol, 698–699
 - ip helper address, 697–698

- ip helper-address, 698
- ip prefix-lists, 736–739
- ip route, 93, 515
- ip subnet zero, 17
- ip summary address eigrp, 172
- ip unnumbered, 694
- IPX configuration, 778
- line vty, 692
- match community, 744
- match length, 467
- maximum-paths, 545
- neighbor distribute list, 733–734
- neighbor peer-group, 547
- neighbor prefix list, 737
- neighbor route-reflector-client, 753
- neighbor send-community, 743, 745
- neighbor weight, 626
- network, 555, 608, 639
- no synchronization, 638
- ping, 471
- redistribute, 712
- route map, 43–44, 452
- set community, 742
- set default interface, 467–469
- set ip default next-hop, 468
- set ip next-hop, 467
- set ip precedence, 469
- show interfaces, 155
- show ip bgp neighbors, 567, 753
- show ip eigrp, 193
- show ip eigrp neighbors, 150, 192
- show ip eigrp topology, 152, 192
- show ip eigrp traffic, 193
- show ip ospf database, 713
- show ip policy, 471, 475, 860
- show ip prefix-list, 740
- show ip prefix-list detail, 741
- show ip protocols, 193
- show ip route, 93
- show ip route eigrp, 193
- traceroute, 464, 471
- traffic-share, 175
- variance 2, 175
- variance 4, 175
- WAN configuration, 781–782
- communication protocols, 807
- communities, 741
- community attribute (BGP), 533, 742
- community lists (BGP), 744
- comparing configuration file commands, 773
- Complete sequence number PDUs, 373
- config-register command, 774
- configuration commands, 785
 - Catalyst switch interface, 786
 - IP, 777
 - WAN interfaces, 781
- configuration exercises
 - basic connectivity, 64
 - BGP path manipulation using MED and local preference with route maps, 650–658
- configuring
 - BGP route summarization, 641–649
 - EBGP for two neighbors, 574–578, 582–590
 - full-mesh IBGP, 579–582, 592–599
 - IBGP for two neighbors, 582–590
 - integrated IS-IS in multiple areas, 397–405
 - OSPF for complex Frame Relay networks, 312–315, 325–332
 - OSPF for multiple areas and Frame Relay NBMA, 309–311, 322–324
 - OSPF in a single area, 2557–258
 - OSPF virtual links, 319–321, 345–349
 - PBR, 484–487, 498–502
 - redistribution, 478–481, 487–496
- equipment requirements, 64, 122, 202, 255, 478
- NAT using access lists and route maps, 68–71
- OSPF databases, 316–319, 334, 337–341
- tuning
 - EIGRP, 202–214
 - redistribution, 482–484, 496–498
- configuration file commands, 773
- configuration register, 766–767
- configure network command, 773
- configure overwrite-network command, 773
- configure terminal command, 770, 783
- configuring
 - access lists, 676, 693
 - BGP, 546
 - configuration examples, 560–564
 - defining BGP neighbors, 548
 - defining networks that BGP advertises, 555–556
 - defining source IP addresses, 549–550
 - EBGP multihop, 552–553
 - examples, 729–732

- loopback interfaces, 550
- peer groups, 546–547
- summary addresses, 611–612
- TTL, 552
- BGP prefix lists, 736–739
- distribute lists, 447
- EIGRP, 166
 - basic configuration example, 167–168
 - default routes, 169–170
 - examples, 706–709
 - link utilization, 176, 179
 - multipoint interfaces, 176
 - summarization, 172–173
 - wildcard mask, 168
- extended IP access lists, 683–686
- helper addresses, 697–698
- integrated IS-IS
 - configuring, 390
 - enabling IS-IS on routers, 391
 - integrated IS-IS
 - NET configuration, 392
 - optimization, 393–394
 - scalable IS-IS in large networks, 395
 - verification, 396–397
- IP access lists, 678
- IP dynamic routing protocol, 96
- IP routing protocols, 95
- IS-IS authentication, 719, 723
- migration to a classless routing protocol, 122–134
- multihomed connections, 627
- multihoming
 - no special tuning, 635
 - no special tuning example, 636
 - weight attributes changed, 637
- NAT with access lists, 39–40
- NAT with route maps, 41, 44–45
- NSSA, 710
- ODR, 98
- OSPF
 - areas, 712–713
 - manipulating OSPF router ID, 238
 - multiple areas, 714–717
 - NSSAs, 710–711
 - single area, 235–238, 255–258
 - verifying operations, 236–238
 - virtual links, 304–307
- PBR, 465–466, 470
- policy routing, 470
- prefix lists, 736
- redistribution, 426–427
 - access lists, 448
 - examples, 757–760
 - redistribute command for EIGRP, 431–432
 - redistribute command for IS-IS, 433–434
 - redistribute command for OSPF, 429–430
 - redistribute command for RIP, 428
- RIP, 97
- RIPv2, 111
- route leaking, 727
- route maps, 452
- route reflectors, 752
- secondary IP addresses, 416
- static default routes, 94
- static routes, 93, 442–444
- subnet zero, 17
- connect command, 770
- connecting internal routers to edge routers, 70
- Connectionless Network Protocol (CLNP), 355
- Connectionless Network Service. *See* CLNS
- connections (multihoming), 627
 - default routes from all providers, 628, 640
 - examples, 635–637
 - full routing table from each provider, 631–633
 - partial routing table from each provider, 629
- control information (OSI model), 809
- controller command, 781
- controlling
 - routing update traffic, 441
 - default routes, 443–444
 - distribute lists, 445–449
 - route maps, 450–454
 - static routes, 442
 - vty access, 691
- converting
 - between decimal and binary IP addresses, 667
 - decimal-to-binary, 665
- copy flash tftp command, 770
- copy ftp: nvram:startup-config command, 773
- copy ftp: system:running-config command, 773
- copy nvram tftp://{host}/{file} command, 783
- copy rcp running-config command, 773
- copy rcp startup-config command, 773
- copy rcp: nvram:startup-config command, 773
- copy rcp: system:running-config command, 773
- copy running-config rcp command, 773

copy running-config startup-config command, 770, 773

copy running-config tftp command, 770, 773

copy startup-config running config command, 770

copy startup-config tftp command, 770

copy system:running-config ftp: command, 773

copy system:running-config nvram:startup-config command, 773

copy system:running-config rcp: command, 773

copy system:running-config tftp: command, 773

copy tftp flash command, 770

copy tftp running-config command, 771, 773

copy tftp startup-config command, 771, 773

copy tftp: nvram:startup-config command, 773

copy tftp: system:running-config command, 773

Core layer, 6

creating

- access lists, 677
- BGP community lists, 744
- default routes in OSPF, 290
- static routes, 93
- summary addresses (BGP), 611–613
- summary routes, 172

Ctrl+a command, 769

Ctrl+b command, 769

Ctrl+c command, 769

Ctrl+e command, 769

Ctrl+f command, 770

Ctrl+n command, 770

Ctrl+p command, 770

Ctrl+r command, 770

Ctrl+Shift+6 x command, 770

Ctrl+u command, 770

Ctrl+w command, 770

Ctrl+z command, 770, 773

D

d, 435–436, 477

data link layer (OSI model), 810, 813

data units, 814–815

databases

- IP forwarding, 384
- LSDBs, 282
- OSPF, configuration exercises, 316–319

datagrams, 814

debug appletalk routing command, 779

debug command, 193, 771

debug dialer command, 780

debug eigrp neighbors command, 775

debug eigrp packets command, 193, 197–198

debug frame-relay lmi command, 780

debug ip bgp events command, 569

debug ip bgp updates command, 568

debug ip eigrp command, 193, 199, 775

debug ip igrp command, 775–776

debug ip ispf adj command, 253

debug ip nat command, 776

debug ip ospf adj command, 307

debug ip ospf events command, 775–776

debug ip ospf packet command, 234, 775–776

debug ip policy command, 471, 474

debug ip rip command, 130, 776

debug ipx routing activity command, 778

debug ipx sap activity command, 778

debug isdn q921 command, 780

debug isdn q931 command, 780

debug ppp authentication command, 780

debug ppp error command, 780

debug ppp negotiation command, 780

debugging BGP session establishment, 569

decimal-to-binary conversion chart, 665

default-information originate always command, 105, 517

default-information originate command, 131, 290–291, 292

default metric

- changing, 435
- defining for redistribution, 435–436, 477
- redistribution, configuration example, 759

default-metric command, 435

default routes, 443–444, 516–517

- creating in OSPF, 290
- EIGRP, 169–170, 206
- OSPF, 291

default seed metrics, 424

defining

- BGP prefix lists, 734–735
- OSPF adjacencies, 223
- route maps, 43–44, 452
- source IP addresses (BGP), 549–550

denying

- prefix lists, 736
- vtv access, 691

depletion (IP addresses, 34
description command, 775
designing
 networks
 benefits of good design, 8
 flexibility, 11
 functional structure design, 4
 predictability, 10
 scalability, 9
 scalable network design, 4
 route reflectors, 749–751
destination addresses, 474
DHCP (Dynamic Host Configuration Protocol), 8
dialer idle-timeout command, 781
dialer load-threshold command, 781
dialer map command, 781
dialer pool command, 781
dialer pool-member command, 781
dialer string command, 515, 781
dialer-group command, 781
dialer-list list command, 781
dialer-list protocol command, 781
diameter limit (EIGRP for IPX), 704
Diffused Update Algorithm (DUAL), 143, 157,
 161–165, 201, 837
disable command, 771
disabling
 automatic summarization, 110, 172
 BGP peer groups, 549
 BGP synchronization, 556
disconnect command, 771
discontiguous networks, summarizing routes, 102
discovery (address), 700–701
displaying route maps, 471, 860
distance bgp command, 458–459
distance command, 461–463
distance vector routing protocols, 146, 221. *See also*
 advanced distance vector routing protocols
distribute lists, 445, 732, 735
 configuring, 447
 controlling redistribution, 449
 extended access lists, 734
 in vs. out, 447
 processing, 445
distribute-list command, 445
distribute-list out command, 448
Distribution layer, 6–7
domain authentication, 723
don't care bits, 677

dotted decimal notation, 18
DRs, 242–243
DUAL (Diffused Update Algorithm), 143, 157, 161,
 163–165, 201, 837
dual-stack transition, 57
duplex command, 786
Dynamic Host Configuration Protocol (DHCP), 8
dynamic IGP routes, redistributing into BGP, 638
dynamic routing, 95–96

E

E1 routes, 284
E2 routes, 284
EBGP (External BGP), 520
 configuring
 for two neighbors (configuration exercise),
 582–590
 weight, 626
 multihop, 552–553
 next hop, 529
 setting the MED with route maps, 622–626
edge routers
 connecting to internal routers, 70
 setup, 66
 translating to, 71
EGPs, 532–533
 BGP (exterior gateway protocols), 507, 861
 aggregator attribute, 606, 867
 appropriate use of, 513, 861
 AS-path attribute, 528
 ASs, 507–508
 atomic aggregate attribute, 606, 867
 attribute type codes, 527
 attributes, 526
 CIDR, 605–606
 community attribute, 533
 creating summary addresses, 611–612
 default routes, 516–517
 floating static routes, 515–516
 MED attribute, 534
 message types, 523–525, 569,
 572, 863
 neighbors, 517
 next-hop attribute, 529–531
 origin attribute, 532

- path of last resort, 515
 - peer group configuration, 546
 - policy-based routing, 512
 - resetting sessions, 557–559
 - RFCs, 510
 - route selection, 543–545, 616
 - static routes, 514–516
 - synchronization rule, 541–542, 573, 597
 - tables, 522, 862
 - troubleshooting, 568
 - verifying operation, 564–567
 - weight attribute, 535–536
- EIGRP, 143, 153
- ACKs, 180
 - for AppleTalk, 705
 - automatic network-boundary summarization, 107
 - autosummarization, 173
 - auto-summary command, 108
 - bandwidth, 176
 - configuring, 166
 - basic configuration example, 167–168
 - default routes, 169–170
 - examples, 706–709
 - wildcard mask, 168
 - debug eigrp packets command, 197–198
 - debug ip eigrp command, 199
 - default metric, 433–436
 - default routes, 206
 - default-metric command, 435
 - disabling automatic summarization, 110
 - feasible routes, 175
 - feasible successors, 147
 - going active on a route, 181
 - hold time, 150–152
 - for IPX, 704
 - K-values, 150
 - limiting query range, 185
 - with a stub, 188–190
 - with summarization, 186
 - link utilization, 176, 179
 - load balancing, 173–174
 - metric, 146
 - calculation example, 156
 - K-values, 155
 - variables, 154–155
 - metric-value parameters, 432
 - multipoint interfaces, 176
 - neighbor relationship
 - route selection, 154–155
 - Seq number, 151
 - split horizon, 154
 - uptime, 150
 - neighbor table, 146, 150
 - operational characteristics, 146
 - packets, 148, 836
 - query scoping, 182
 - redistribute command, 431–432
 - redistribution between OSPF and EIGRP, 420
 - route summarization, 103, 145, 170–173
 - routing process, 144
 - routing table, 157, 161–165, 201, 837
 - scalability
 - rules, 191
 - variables, 181–182, 191
 - scalable internetworks, 180
 - sequence numbers vs. serial numbers, 198
 - show ip eigrp topology command, 196
 - show ip protocols command, 195
 - show ip route command, 193
 - successors, 146
 - summarization (configuration exercise), 205
 - terminology, 146
 - tiered network model, 192
 - topology table, 152
 - topology tables, 146
 - update and query example, 182–184
 - verifying operation, 192–193
 - WAN links, configuring, 175–176, 180
 - eigrp log-neighbor-changes command, 182
 - eigrp stub command, 189
 - electing DRs, 242
 - enable command, 771
 - enable password command, 774
 - enable secret command, 774
 - encapsulation, 809
 - encapsulation command, 782
 - encapsulation dot1q command, 775
 - encapsulation isl command, 775
 - end command, 774
 - end systems (ESs), 357
 - equal-access command, 472
 - erase nvram: command, 773
 - erase startup-config command, 771, 784
 - error checking, 812
 - error recovery, 812
 - Esc+b command, 770

Esc+f command, 770
 ESs (end systems), 357
 EUI-64 format, 50
 EXEC commands, 775
 exec-timeout 0 0 command, 774
 exit command, 771, 774
 extended access lists, 44, 466

- configuring, 683–686
- in distribute lists, 734
- example, 689–690
- placement, 690–691
- process flow, 682

 extended IP access lists, wildcard masks, 676
 extending

- IP addresses, 665
 - CIDR, 32–34
 - subnetting, 16–17
- IP classful addresses, 669

 extension headers (IPv6), 55
 external BGP neighbors, 520, 534
 external OSPF routes, 284
 external routes

- EIGRP, 154
- summarization, 287

F

fast-switched policy routing, 470
 faulty design in route reflectors, 751
 FD (feasible distance), 157–158
 feasible routes (EIGRP), 175
 feasible successors (FS), 159

- EIGRP, 147
- requirements, 159

 feedback, 421, 454
 filtering, 448, 465–470, 860

- BGP, 732
- packets, 673–674
- routes, 42–43, 63, 450, 829
- routing updates (configuration exercise), 493
- with prefix lists, 736–737

 Fixed Length Subnet Masking (FLSM), 19
 flapping, 28
 flexibility of good network design, 11
 floating static routes, 115, 515–516
 flooding subprotocol, 379
 flow control, 811–812

FLSM (Fixed Length Subnet Masking), 19
 flush, 119
 forcing EIGRP autosummarization, 173
 frame relay

- interfaces, EIGRP configuration, 176–179
- NBMA, 246–248
- topologies, 244

 frame-relay interface dlci command, 782
 frame-relay inverse-arp command, 782
 frame-relay lmi-type command, 782
 frame-relay map command, 782
 frames, 813
 framing command, 782
 FS (feasible successor), 159
 full-mesh neighbor environment (BGP), 538–540
 full-mesh topology, 244
 fully meshed core layer, 6
 functional structure design, 4

G

general configuration commands, 773–774
 general interface configuration commands, 774–775
 generating default routes (OSPF), 291
 geographic structured design, 5
 global configuration commands, 17
 goals of redistribution, 439
 going active on a route, 181
 guidelines of static routing configuration, 443

H

H (Handle), 150
 headers, 809, 813
 hello interval (EIGRP), 148, 836
 Hello packets, 148, 836
 Hello PDUs, 373
 Hello protocol, 228
 helper addresses, 695–696

- configuring, 697–698
- example, 698–700
- server placement, 696

- hierarchical addressing, 13
 - benefits, 12
 - planning, 12
 - summary numbers, 12
- hierarchical layers, 6
 - access layer, 7
 - distribution layer, 7
 - fully meshed core layer, 6
 - hub-and-spoke core layer, 7
- history size command, 774
- hold time, 149–152, 200, 524
- holddown, 119
- hop-by-hop routing paradigm, 512
- hostname command, 774, 785
- hosts per class (IP addresses), 668–669
- HSRP (Hot Standby Router Protocol), 700–701
- hub-and-spoke core layer, 7
- hybrid routing protocols, 837
 - EIGRP, 143, 146
 - configuring, 166
 - DUAL, 157, 161–165, 201
 - feasible successors, 147
 - going active on a route, 181
 - hello packets, 148
 - hold time, 152
 - load balancing, 173–174
 - neighbor tables, 146
 - operational characteristics, 146
 - packets, 148, 836
 - query scoping, 182
 - reliability, 151
 - route summarization, 170–173
 - routing process, 144
 - scalability variables, 181–182, 191
 - successors, 146
 - summarization, 145
 - tiered network models, 192
 - topology table, 152
 - topology tables, 146
 - verifying operation, 192–193
 - WAN links, 175–176, 180
- IANA (Internet Assigned Numbers Authority), 508
- IBGP (Internal BGP), 521
 - configuring
 - full-mesh IBGP (configuration exercise), 592–599
 - for two neighbors (configuration exercise), 582–590
 - full mesh, 538
 - full-mesh confutation exercise example, 579–582
 - next hop, 529
 - setting local preference, 618–621
 - split horizon rule, 537
- ICMP messages, 675
- ICND router commands, 769–770
- IDI (initial domain identifier), 366
- idle state troubleshooting (BGP), 570
- IDP (initial domain part), 366
- IEEE (Institute of Electrical and Electronic Engineers), 811
- IGPs (interior gateway protocols), 507, 861
 - dynamic routes, 638
 - IGP adjacencies, 537
 - redistribution, 637–639
- IGRP
 - default metric, 433–436
 - default-metric command, 435
 - metric-value parameters, 432
 - passive-interface command, 436
 - redistribution configuration example, 757–758
 - route summarization, 103
- implementing route summarization, 31
- implicit denies, 736
- implicit deny any entries (access lists), 676
- implicit wildcard masks, 679
- In, 309, 398, 574
- information exchange process (OSI model), 809–810
- information formats, 813–814
- initial domain identifier (IDI), 366
- initial domain part (IDP), 366
- injecting default routes into areas (OSPF), 291
- inserting routes into IP routing tables, 116
- inside global IP addresses, 36, 828
- inside local IP addresses, 36, 828

- integrated IS-IS, 360
 - configuring
 - enabling IS-IS on routers, 391
 - NET, 392
 - optimization, 393–394
 - scalable IS-IS in large networks, 395
 - verification, 396–397
 - in an IP and CLNS environment, 382
 - IP forwarding databases, 384
- Integrated IS-ISv6, 60
- interarea addressing and routing, 370–372
- interarea route summarization, 287
- interarea routes, 728
- interface authentication, 720
- interface command, 774–775, 785
- interface configuration commands, 774–775
- interface vlan 1 command, 785
- interfaces
 - loopback, 695
 - unnumbered, 694–695
- Intermediate System Hellos (ISHS), 360
- Intermediate System-to-Intermediate System Protocol. *See* IS-IS
- internal BGP neighbors, 521
- internal routers
 - downloading configuration files, 73
 - EIGRP, 154
- International Organization for Standardization (ISO), 355
- internetworks, 191
- intra-area addressing and routing, 370–372
- intra-area routing, 387
- invalid, 119
- IP
 - advanced IP addressing, 3
 - benefits of optimized IP addressing plans, 11–13
 - planning, 4
 - scalable network addressing example, 14
 - configuration commands, 777
- ip access group command, 678
- IP access lists, 673–674
 - backwards compatibility, 674
 - configuring, 693
 - creating, 677
 - extended
 - example, 689–690
 - in distribute lists, 734
 - standard, 674
 - configuring, 676–678
 - example, 680–681
 - numbering, 674
 - processing, 676
 - wildcard masks, 676, 679
- ip access-group command, 777
- ip access-list command, 777
- ip address command, 777, 785
- IP addressing
 - CIDR, 32–34, 605–606
 - classes, 668–669
 - classful, 669
 - configuring secondary addresses, 416
 - converting between decimal and
 - binary, 667
 - depletion, 34
 - dotted decimal notation, 18
 - EXEC commands, 775–776
 - extending, 665
 - helper addresses, 695–696
 - configuring, 697–698
 - example, 698–700
 - server placement, 696
 - hierarchical, 12
 - IPv6
 - address aggregation, 49
 - address autoconfiguration, 50
 - address format, 47
 - address types, 48
 - addressing, 47
 - benefits, 46
 - features, 46
 - packet format, 52–55
 - renumbering, 51
 - routing protocols, 59–61
 - to IPv4 interoperability, 56
 - job aids, 663
 - migrating to a new space, 415
 - NAT, 35
 - configuring with access lists, 39–40
 - configuring with route maps, 41
 - features supported, 37
 - overlapping networks, 38
 - route maps examples, 44–45
 - terminology, 36
 - network masks, 18–19
 - planning new allocation during routing protocol migration, 413–414

- redistribution example, 754–757
- route summarization
 - implementation, 31
 - in IP routing protocols, 32
 - operation in Cisco routers, 31
 - planning nonscalable network addressing, 15–16
- subnet masks
 - calculating, 670–672
 - prefixes, 18, 672–673
- subnetting, 16–17
- summarizing in a VLSM-designed network, 30
- unnumbered interfaces, 694–695
- VLSMs, 20, 26
- ip classless command, 104–105, 190, 777
- ip community list command, 744
- IP configuration commands, 777–778
- ip default network command, 444
- ip default-gateway command, 444, 785
- ip default-network command, 443–444
- ip domain-lookup command, 777
- ip eigrp hello-interval command, 149
- IP forwarding databases, 384
- ip forward-protocol command, 698–699
- ip helper-address command, 697–698
- ip host command, 777
- ip inside source command, 42
- ip name-server command, 777
- ip nat command, 777
- IP NAT inside interface, 37
- ip nat inside source list command, 71
- IP NAT tables, 36
- ip netmask-format command, 777
- ip policy route-map equal-access command, 473
- ip prefix-list command, 736–739
- ip rip receive version interface command, 111
- ip rip send version interface command, 111
- ip route command, 93, 515, 777
- IP route filtering, 448
- ip route-cache policy command, 470
- IP routing, 91
 - classful routing tables, 103
 - classless
 - optimizing, 134
 - optimizing routes, 125
 - dynamic routing, 95–96
 - holddown, 119
 - integrated IS-IS operations, 382
 - ODR, 97–98
 - protocol chart comparisons, 117–121
 - protocol comparisons
 - administrative distance, 113–114
 - floating static routes, 115
 - inserting routes into IP routing tables, 116
 - static routing, 91–92
 - configuring, 93
 - configuring static default routes, 94
- IP routing protocols, migrating to multiple, 411
 - IP address allocation, 413–414
 - migration considerations, 412
 - new IP address spaces, 415–416
 - new routing protocols, 417–418
 - redistribution, 418–423
 - redistribution, configuring, 426–434
 - redistribution, example, 438
 - redistribution, implementation considerations, 425
- ip subnet zero command, 17
- ip subnet-zero global configuration command, 17
- ip summary address eigrp command, 172
- ip summary-address rip interface command, 112
- ip unnumbered command, 694
- IPv4
 - access lists, 673
 - converting IP addresses between decimal and binary, 667
 - determining IP address classes, 668
 - IPv6 interoperability, 56
- IPv6
 - 6to4 tunneling, 58–59
 - address aggregation, 49
 - address format, 47
 - address types, 48
 - addressing, 47
 - autoconfiguration, 50
 - renumbering, 51
 - benefits of, 46
 - dual-stack transition, 57
 - features, 46
 - manually configured tunnels, 58
 - overlay tunnels, 57
 - packet format, 52
 - IPv4 header format, 52
 - IPv6 extension headers, 55
 - IPv6 header format, 54
 - SCTP, 54
 - routing protocols, 59
 - BGP4+, 61

- Integrated IS-ISv6, 60
 - OSPFv3, 60
 - RIPing, 60
 - to IPv4 interoperability, 56
- IPv6 extension headers, 55
- IPv6 header format, 54
- ipx access-group command, 778
- IPX commands, 778
- IPX configuration commands, 778–779
- ipx delay command, 779
- ipx input-sap-filter command, 779
- ipx maximum-paths command, 779
- ipx network command, 779
- ipx output-sap-filter command, 779
- ipx routing command, 779
- isdn spid1 command, 782
- isdn spid2 command, 782
- isdn switch-type command, 782
- ISHs (Intermediate System Hellos), 360
- IS-IS (Intermediate System-to-Intermediate System Protocol), 355, 372, 717
 - area routing, 383–384
 - authentication, 719–723
 - CLNS environments
 - intra-area and interarea addressing and routing, 370–372
 - IS-IS PDUs, 373–375
 - link-state database synchronization and adjacency, 379–380
 - topologies, 376–378
- configuring, 390
 - enabling IS-IS on routers, 391
 - NET, 392
 - optimization, 393–394
 - scalable IS-IS in large networks, 395
 - verification, 396–397
- history of, 362
- identifying systems, 367
- in an IP and CLNS environment, 382
 - criteria and path selection for IS-IS area routing, 383–384
 - show commands, 385–389
- NSAP address structure, 366
- OSI routing levels, 360–361
- PDUs, 373–375
- redistribute command, 433–434
- route leaking, 725–729
 - route summarization, 103
- routing, 356
 - adjacencies, 356
 - ES-IS, 359
 - integrated design principles, 358
 - issues and complications, 359
 - TLVs, 717–718
 - troubleshooting, 396–397
 - vs. OSPF, 362–364
- isis priority command, 377
- ISO (International Organization for Standardization), 355
- ISPs (Internet service providers), 510
 - multihoming, 627
 - default routes from all providers, 628, 640
 - examples, 635–637
 - full routing table from each provider, 631–633
 - partial routing table from each provider, 629
 - redistribution into IGP, 639

J – L

- job aids
 - decimal-to-binary conversion chart, 665
 - IP addresses, 663
 - subnetting, 663
- keepalive messages (BGP), 524–525
- K-values, 150, 155
- L0 routing, 361
- L1 routing, 361
- L2 routing, 361
- L3 routing, 361
- LANs
 - adjacencies, 381
 - protocols, 807
- limiting vty access, 691
- line command, 774
- line vty command, 692
- linecode command, 782
- link utilization (EIGRP), 176, 179
- link-state acknowledgment (LSAck), 225
- link-state advertisements. *See* LSAs
- link-state database synchronization and adjacency, 379–380
- link-state databases. *See* LSDBs

- link-state packets, 374–375
- link-state PDUs, 373
- link-state routing protocols
 - OSPF, 291, 709–711
 - overview, 219–220
- link-state sequence numbers, 233
- LLC (Logical Link Control), 811
- load balancing
 - BGP, 543
 - EIGRP, 173–175
- local preference
 - changing for all routes, 618
 - changing with route maps, 620–621
 - example, 619
- local preference attribute (BGP), 532–533
- logging synchronous command, 774
- login command, 774, 785
- logout command, 771
- loopback interfaces, 239–240, 695
- loops, redistribution considerations, 421
- lost passwords, 764–767
- lower layers (OSI model), 806
- LSAck (link-state acknowledgment), 225
- LSAs (link-state advertisements), 276
 - type 7, 709–710
 - types, 278
 - type 1 LSAs, 279
 - type 2 LSAs, 280
 - type 3 LSAs, 281
 - type 4 LSAs, 281
 - type 5 LSAs, 282
- LSDB synchronization, 379–381
- LSDBs (link-state databases), 276–278, 282

M

- MAC (Media Access Control), 811
- mac-address-table permanent command, 785
- mac-address-table restricted static command, 785
- mac-address-table static command, 786
- manual summarization, 173
- manually configured tunnels, 58
- masks
 - network masks, 18–19
 - subnets, 16
- match community command, 744
- match ip address command, 466
- match length command, 467
- maximum-paths command, 545
- MED, setting with route maps, 622–626
- MED attribute (BGP), 534
- media-type command, 775
- messages, 814
 - BGP, 523–525, 569, 572, 863
 - ICMP, 675
- metric command, 293
- metrics, 96
 - changing default metrics, 435
 - EIGRP, 146
 - for AppleTalk, 705
 - for IPX, 704
 - K-values, 155–157. *See also* DUAL variables, 154–155
 - seed metrics, 424
- metric-value parameters (EIGRP & IGRP), 432
- migrating
 - to classless routing protocols, 122–134
 - to multiple IP routing protocols, 411
 - IP address allocation, 413–416
 - migration considerations, 412
 - new routing protocols, 417–418
 - redistribution, 418–425
 - redistribution, configuration, 426–434
 - redistribution, example, 438
 - to new IP address space, 415
 - to route reflectors, 750–751
- modifying
 - administrative distance, 457–458, 463
 - BGP, 553
 - weights in multihomed routes, 636
 - more nvrn:startup-config command, 773
 - more system: running-config command, 773
- multiaccess networks, 151–152
- multicast addresses, 48
- multihoming, 627
 - configuring
 - no special tuning example, 635–636
 - weight attributes changed, 637
 - default routes from all providers, 628, 640
 - types of, 627
- multiple path selection (BGP), 545
- multiple-area OSPF, configuring, 714–717
- multiplexing, 812
- multipoint interfaces, 176
- multipoint subinterfaces, 252

N

- NAT (Network Address Translation), 3, 34–35
 - configuration exercise commands, 69
 - configuring with access lists, 39
 - extended access list translation, 40
 - configuring with route maps, 41
 - features supported, 37
 - overlapping networks, 38
 - route maps
 - example, 44–45
 - translating internal addresses, 72
 - route maps
 - terminology, 36
- NBMA
 - configuration in nonbroadcast mode, 247
 - OSPF commands for NBMA frame relay, 246–248
 - OSPF over NBMA topology summary, 254
 - topologies, 245
- neighbor distribute list command, 733–734
- neighbor peer-group command, 547
- neighbor prefix list command, 737
- neighbor relationships
 - EIGRP
 - DUAL, 157, 162–165
 - EIGRP Hello packets, 148
 - route selection, 154–155
 - Seq number, 151
 - split horizon, 154
 - uptime, 150
- neighbor route-reflector-client command, 753
- neighbor send-community command, 743, 745
- neighbor table (EIGRP), 146, 150
- neighbor update-source command, 550
- neighbor weight command, 626
- neighbors
 - BGP, 517, 520
 - external BGP neighbors, 520
 - internal BGP neighbors, 521
 - peer group configuration, 546
 - feasible successors (EIGRP), 147
- NET, 392
- NET addresses, 368
- Network Address Translation. *See* NAT
- network boundary summarization, 607
- network command, 96, 555, 608–610, 639, 777
- network layer
 - OSI model, 811
 - packets, 813
- network statement, 95
- networks
 - broadcast, 376
 - Class C, 33
 - designing
 - benefits of good design, 8
 - flexibility, 11
 - functional structure design, 4
 - predictability, 10
 - scalability, 9
 - scalable network design, 4
 - discontiguous, 3
 - masks, 18–19
 - multiaccess, 151–152
 - point-to-point, 378
 - protocols, 807
 - scalable networks, 19
- networks per class (IP addresses), 668–669
- next-hop attribute (BGP), 529–553
- no auto-summary command, 107
- no ip classless command, 67, 105, 133
- no passive interface command, 437
- no shut command, 311
- no synchronization command, 638
- nonbroadcast multiaccess networks, 244
- nonclients, 748
- nonscalable internetworks, 191
- nonscalable network addressing, 15–16
- notification messages (BGP), 525
- NSAP addresses, 365–366
- NSEL, 368
- NSSAs (not-so-stubby areas), 300–302, 709–711
- numbering standard IP access lists, 674

O

- obtaining VLSM calculators, 26
- ODR (On-Demand Routing), 97–99
- of, 719
- one-way redistribution, 425
- Open System Interconnection model. *See* OSI model
- operation, 393
- operational characteristics (EIGRP), 146

- optimizing
 - classless routes, 125, 134
 - IS-IS, 393–394
- optional attributes (BGP), 526
- optional nontransitive attributes (BGP), 534
- optional transitive attributes, 533, 606, 742, 867
- options
 - ip prefix-list, 737–739
 - neighbor prefix list commands, 737
- origin attribute (BGP), 532
- OSI (Open System Interconnection) protocols, 355, 360–361
- OSI (Open System Interconnection) model
 - application layer, 813
 - characteristics, 806
 - communication between layers, 807
 - control information, 809
 - data link layer, 810
 - information exchange process, 809–810
 - layer services, 808
 - lower layers, 806
 - network layer, 811
 - physical layer, 810
 - presentation layer, 812
 - protocols, 807
 - transport layer, 811
 - upper layers, 806
- OSPF
 - adjacency behavior for a point-to-point links, 241
 - adjacency behavior for broadcast networks, 242–243
 - adjacency behavior for nonbroadcast multiaccess networks, 244
 - areas, 293
 - NSSAs, 300–302
 - stubby areas, 295–296, 300
 - totally stubby areas, 297–300
 - calculating the costs of E1 and E2 routes, 284
 - calculation, 224–225
 - changing the cost metric, 285
 - Cisco-specific modes for neighborship, 251
 - commands for NBMA frame relay, 246–248
 - configuration exercises
 - configuring for complex Frame Relay networks, 312–315
 - configuring for multiple areas and frame relay NBMA, 309–311
 - configuring OSPF for complex Frame Relay networks, 325–332
 - configuring OSPF for multiple areas and Frame Relay NBMA, 322–324
 - configuring the OSPF virtual link, 319–321
 - OSPF databases, 316–319, 334, 337–341
 - virtual links, 345–349
 - configuring
 - manipulating OSPF router ID, 238
 - single area, 235–238, 255–258
 - verifying operations, 236–238
 - debug ip ospf adj command, 253
 - default route generation, 291
 - default static routes, 517
 - defining
 - adjacencies, 223
 - OSPF areas, 221–222
 - design guidelines, 278
 - frame relay topologies, 244
 - link-state routing protocols overview, 219–220
 - link-state sequence numbers, 233
 - loopback interfaces, 239
 - LSA types, 278
 - type 1 LSAs, 279
 - type 2 LSAs, 280
 - type 3 LSAs, 281
 - type 4 LSAs, 281
 - type 5 LSAs, 282
 - LSDBs, 282
 - multiple-area configuration example, 714–717
 - multipoint subinterfaces, 252
 - neighbor adjacency establishment
 - exchange process and adjacency states, 229–233
 - Hello protocol, 228
 - NSSAs, 709–711
 - over NBMA topology summary, 254
 - packet types, 226–227
 - point-to-multipoint mode, 249
 - redistribution between OSPF and EIGRP, 420
 - route summarization, 103, 286–287
 - commands, 288–289
 - creating default routes, 290–292
 - routing tables, 283
 - single-area configuration, 712–713
 - subinterfaces, 251
 - using multiple areas, 277

- virtual links, 303
 - configuring, 304–307
 - verifying operation, 307
- vs. IS-IS, 362–364
- OSPF routers
 - traffic control, 277
 - types of, 276
- OSPFv3, 60
- outside global IP addresses, 36, 828
- outside local IP addresses, 36, 828
- overlay tunnels, 57
- overload keyword (ip inside source command), 42

P

- packet filtering
 - access lists, 673–674
 - configuring, 676
 - extensions, backwards compatibility, 674
 - standard, 674
 - standard IP access lists, 678
- packets, 813
 - EIGRP, 148, 836
 - ACKs, suppressing, 180
 - hello, 148, 836
 - queries, 182
 - reliability, 151
 - IPv6 packet format, 52
 - IPv4 header format, 52
 - IPv6 extension headers, 55
 - IPv6 header format, 54
 - SCTP, 54
 - OSPF, 226–227
- parameters (ip route command), 515
- Partial sequence number PDUs, 373
- partial updates (EIGRP), 143
- partial-mesh neighbor example (BGP), 538, 540
- partial-mesh topology, 244
- passive routes vs. active routes, 149
- passive-interface command, 436–437, 756
- password command, 774, 786
- password recovery, 764–767
- path manipulation
 - route maps, 614–615
 - configuring weight, 626
 - route selection decision process, 615–617
 - setting local preference, 618–621
 - setting the MED, 622–626

- path of last resort, 515
- path vectors, 512
- PBR
 - application, 465
 - configuring, 465–466, 470
 - configuration exercise, 484–487, 498–502
 - examples, 475
 - based on destination address, 474–475
 - connecting two ISPs, 471–473
 - fast-switched, 470
 - route maps, 42–43, 63, 450, 829
 - implementing, 465–470, 860
 - sequence numbering, 43–44, 452
 - verifying, 471, 860
- PDUs, 373–375, 815
- peer groups
 - BGP
 - configuring, 546
 - disabling, 549
 - compatibility with route reflectors, 752
 - configuring, 547
- peers. *See also* neighbors
- phantom routers, 700
- physical layer (OSI model), 810
- physical topology (route reflector design), 751
- ping command, 471, 771, 784
- ping ipx command, 778
- planning hierarchical addressing schemes, 12
- point-to-multipoint mode, 245, 249
- point-to-point interfaces, 443
- point-to-point links
 - adjacency behavior, 241
 - LSDB synchronization, 381
- point-to-point networks, 378
- policy-based routing (BGP), 512
- port names
 - TCP, 686–687
 - UDP, 688
- port numbers, 117, 686
- port secure command, 786
- port secure max-mac-count command, 786
- port security action command, 786
- port security command, 786
- port security max-mac-count command, 786
- ppp authentication command, 782
- predefined well-known community
 - numbers, 744
- predictability of good network design, 10

prefix lists

- announcing to Internet, 628
- applying to BGP, 734
- characteristics, 735
- configuring, 736–739
- exact matches, 737
- example, 740
- sequence numbers, 739
- verifying, 740–741

prefixes (subnet masks), 18, 672–673

presentation layer (OSI model), 812

pri-group command, 782

processing

- distribute lists, 445
- flow (extended IP access lists), 682
- standard IP access lists, 676

protocols, 807

IP routing

- administrative distance, 113–114
- floating static routes, 115
- inserting routes into IP routing tables, 116
- protocol chart comparisons, 117–121

OSPF

- adjacency behavior for broadcast networks, 242–243
- adjacency behavior for nonbroadcast multiaccess networks, 244
- adjacency behavior for point-to-point links, 241
- calculation, 224–225
- Cisco-specific modes for neighborhood, 251
- commands for NBMA frame relay, 246–248
- configuring for a single area, 235–238
- debug ip ospf adj command, 253
- defining adjacencies, 223
- defining an OSPF area, 221–222
- exchange process, 229, 231, 233
- frame relay topologies, 244
- Hello protocol, 228
- link-state routing protocols overview, 219–220
- link-state sequence numbers, 233
- multipoint subinterfaces, 252
- over NBMA topology summary, 254
- packet types, 226–227
- point-to-multipoint mode, 249
- subinterfaces, 251

routing

- characteristics, 99
- classful, 100–105
- classless, 106–107
- IPv6, 59–61
- route summarization, 103

proxy ARP, 701

Pv4 header format, 52

Q – R

queries, 205

- EIGRP, 148, 836
- scoping, 182

recovering passwords, 764–767

redistribute command, 712

- EIGRP, 431–432
- IS-IS, 433–434
- OSPF, 429
- RIP, 428
- subnets keyword, 756

redistribute connected command, 440

redistribute rip route-map redis-rip subnets command, 454

redistribution, 418–421, 455. *See also* route selection

- access lists, 448
- addressing, 754–757
- administrative distance, 422
- administrative distance example, 459–463
- best path selection, 422
- into BGP, 637
- configuring, 426–427
 - configuration exercises, 478–481, 487–496
 - examples, 757–760
 - redistribute command for EIGRP, 431–432
 - redistribute command for IS-IS, 433–434
 - redistribute command for OSPF, 429–430
 - redistribute command for RIP, 428

controlling with distribute lists, 449

default metric, 435–436, 477

EIGRP for AppleTalk, 705

EIGRP for IPX, 704

goal of, 439

- into IGP, 638–639
 - implementation considerations, 421–422
 - administrative distance, 423
 - seed metrics, 423
 - techniques, 425
 - one-way, 425
 - requirements, 420
 - route maps, 454
 - static routes
 - configuring, 442–444
 - subnets, 431
 - tuning
 - configuration exercise, 496–498
 - configuration exercises, 482, 484
 - using filtering, 760
 - verifying, 464
- reliability (EIGRP), 151
- Reliable Transport Protocol (RTP), 151
- reload command, 771
- renumbering (IPv6), 51
- replies (EIGRP), 148, 836
- reserved TCP port numbers, 686–687
- reserved UDP port numbers, 688
- resetting BGP sessions, 557–559
- restricting vty access, 691
- restrictions
 - route reflectors, 752
 - unnumbered interfaces, 694
- resume command, 771
- retransmission list (RTP), 151
- RFC 1700
- RIP (Routing Information Protocol), 95
 - configuring, 97
 - IGP adjacencies, 537
 - passive-interface command, 436
 - redistribute command, 428
 - redistribution, 758
- RIPE-NIC (Reseaux IP Europeennes-Network Information Center), 509
- RIPing, 60
- RIPv1
 - characteristics, 110
 - ip classless command, 105
 - route summarization, 103
- RIPv2
 - automatic network-boundary summarization, 107
 - auto-summary command, 108
 - characteristics, 110
 - configuration commands, 111
 - configuration example, 112
 - disabling automatic summarization, 110
 - route summarization, 103
- ro, 457–458
- route aggregation, 27
- route filtering (access lists)
 - configuring, 448
 - route, 43–44, 452
 - route maps, 42–43, 63, 450, 465–470, 829, 860
- route leaking, 725–729
- route map command, 43–44, 452
- route maps
 - avoiding route feedback, 454
 - BGP path manipulation, 614–615
 - configuring weight, 626
 - local preference, 618
 - route selection decision process, 615–617
 - setting local preference, 618–621
 - setting the MED with route maps, 622–626
 - changing local preference, 620–621
 - configuring, 452
 - configuration exercise, 68–71
 - NAT, 41, 44–45
 - controlling routing updates, 450, 453
 - applications, 451
 - redistribution, 454
 - displaying, 471, 860
 - PBR, 42–44, 63, 450–452, 465–470, 829, 860
 - sequence numbering, 43–44, 452
 - translating internal addresses, 72
 - tuning redistribution, 484
- route reflectors, 747
 - benefits of, 748
 - clients, 748
 - cluster IDs, 748, 752
 - cluster lists, 748
 - clusters, 748
 - compatibility with peer groups, 752
 - configuring, 752
 - design, 749
 - example, 749–750
 - faulty, 751
 - example, 753
 - migrating to, 750–751
 - nonclients, 748
 - operation, 750
 - restrictions, 752

- routing loops, 748
 - verifying, 753
 - route selection
 - administrative distance, 455, 459–463
 - EIGRP, 154–155
 - route summarization, 27, 103
 - calculation example, 30
 - CIDR, 32–34
 - classful routing protocols, 32
 - EIGRP, 145, 170–171
 - implementation, 31
 - operation in Cisco routers, 31
 - OSPF, 286–287
 - commands, 288–289
 - creating default routes, 290–292
 - overview, 27–28
 - VLSMs, 20
 - route summarization IP routing protocols, 32
 - router bgp command, 547
 - router eigrp command, 777
 - router IDs
 - loopback interfaces, 240
 - OSPF, 238
 - router igrp command, 777
 - router ospf command, 777
 - router rip command, 777
 - routers
 - ABRs, 223
 - boundary routers, 419
 - classful routing protocols, 101
 - route summarization, 31
 - routing
 - active vs. passive, 149
 - controlling update traffic, 441
 - default routes, 443–444
 - distribute lists, 445–449
 - route maps, 450–454
 - static routes, 442
 - feedback, 421
 - flush, 119
 - interarea, 728
 - intra-area, 387
 - invalid, 119
 - IP, 91
 - administrative distance, 113–114
 - dynamic routing, 95–96
 - floating static routes, 115
 - inserting routes into IP routing tables, 116
 - optimizing classless routes, 134
 - protocol chart comparisons, 117–121
 - static routing, 91–94
 - IS-IS, 356
 - adjacencies, 356
 - area routing, 383–384
 - ES-IS, 359
 - integrated design principles, 358
 - issues and complications, 359
 - OSI routing levels, 360–361
 - vs. OSPF, 362–364
 - levels, 372
 - loops, 748
 - ODR, 97
 - optimizing classless routes, 125
 - OSPF, 283–284
 - packets to the next hop, 468
 - passive-interface command, 437
 - protocols, 811
 - selecting, 423
 - setting local preference (BGP), 618–621
 - successors, 146
 - traffic, verifying redistribution operation, 464
- routing algorithms, 96
- Routing Information Protocol. *See* RIP
- routing policies
 - prefix lists
 - applying to BGP, 734
 - characteristics, 735
 - configuring, 736–739
 - exact matches, 737
 - example, 740
 - sequence numbers, 739
 - verifying, 740–741
- routing protocols, 807
 - administrative distance, 423
 - advanced distance vector, 146
 - believability, 422–423
 - characteristics, 99
 - classful, 100, 104–105
 - automatic network-boundary summarization, 100
 - route, 32
 - routing tables, 103
 - summarizing routes in discontinuous networks, 102
 - classless
 - automatic network-boundary summarization, 107
 - concepts, 106

- forwarding, 125
 - migrating to, 122–134
 - subnetting requirements, 107
 - distance-vector, 221
 - IP
 - holddown, 119
 - migrating to multiple, 411
 - IPv6, 59
 - BGP4+, 61
 - OSPFv3, 60
 - RIPing, 60
 - RIPinIntegrated IS-ISv6, 60
 - migrating to new, 417–423
 - next-hop router information, 159
 - redistribution
 - configuring, 426–434
 - example, 438
 - one-way, 425
 - route summarization, 32, 103
 - scalability
 - compared to other protocols, 511
 - compared to other routing protocols, 512
 - transitioning between, 412
 - routing tables
 - after redistribution, 440
 - BGP routers, 511
 - classful, 103
 - EIGRP, 157, 161–165, 201, 837
 - ODR routes, 99
 - OSPF, 283
 - totally stubby areas, 300
 - RTO (retransmit timeout), 150
 - RTP (Reliable Transport Protocol), 151
- S**
-
- scalability
 - comparing, 511–512
 - EIGRP, 191
 - good network design, 9
 - optimizing classless routes, 125
 - OSPF AS, 222
 - scalable networks
 - addressing example, 14
 - design considerations, 4
 - EIGRP, 180
 - flexibility, 11
 - geographic structured design, 5
 - hierarchical layers, 6
 - predictability, 10
 - implementing VLSM, 19
 - IPv6
 - address aggregation, 49
 - address configuration, 50
 - address format, 47
 - address types, 48
 - addressing, 47
 - benefits, 46
 - features, 46
 - packet format, 52–55
 - renumbering, 51
 - to IPv4 interoperability, 56
 - VLSMse, 22
 - SCTP (Stream Control Transmission Protocol), 54
 - SDUs, 815
 - secondary IP addresses, configuring, 416
 - seed metrics, 424
 - segments, 814
 - selecting
 - best routes, 422, 457–458
 - BGP best paths, 616
 - routes
 - EIGRP for AppleTalk, 705
 - EIGRP for IPX, 704
 - sending communities attribute to neighbors (BGP), 743
 - sequence numbers
 - BGP prefix lists, 739
 - EIGRP, 151
 - vs. serial numbers, 198
 - serial interfaces
 - EIGRP, 176
 - unnumbered, 694–695
 - serial numbers vs. sequence numbers, 198
 - server placement, 696
 - service password-encryption command, 774
 - service timestamps command, 774
 - services (OSI model), 808
 - sessions (TCP), 686
 - set community command, 742
 - additive keyword, 745
 - set default interface command, 467–469
 - set ip default next-hop command, 468
 - set ip next-hop command, 467
 - set ip precedence command, 469
 - set ip tos command, 469

- setup command, 771
- show access-lists command, 771
- show appletalk globals command, 779
- show appletalk interface command, 779
- show appletalk route command, 779
- show appletalk zone command, 779
- show cdp entry command, 771
- show cdp interface command, 99, 771, 784
- show cdp neighbors command, 771, 784
- show cdp neighbors detail command, 771, 784
- show cdp traffic command, 771
- show clns neighbors command, 389
- show clns protocol command, 388
- show clns route command, 387
- show clock command, 771
- show commands, 385
- show configuration command, 773
- show controller command, 771
- show dialer command, 780–781
- show flash command, 772
- show frame-relay lmi command, 780
- show frame-relay map command, 780
- show frame-relay pvc command, 780
- show frame-relay traffic command, 781
- show history command, 772, 784
- show hosts command, 776
- show interface switchport command, 784
- show interface vlan 1 command, 784
- show interfaces command, 155, 772, 784
- show ip access-list command, 776
- show ip bgp command, 565
- show ip bgp neighbors command, 753
 - example output, 567
 - output example, 566
- show ip bgp summary command, 567
- show ip command, 784
- show ip eigrp neighbors command, 150, 192, 776
- show ip eigrp topology command, 152, 192, 196, 776
- show ip eigrp traffic command, 193, 776
- show ip interface command, 776
- show ip nat statistics command, 776
- show ip nat translations command, 45, 776
- show ip ospf database command, 713, 757
- show ip ospf database external command, 337
- show ip ospf interface command, 776
- show ip ospf neighbor command, 238, 776
- show ip ospf virtual-links command, 307
- show ip policy command, 471, 475, 860
- show ip prefix-list command, 740
- show ip prefix-list detail command, 741
- show ip protocols command, 193–195, 776
- show ip route command, 93, 103, 173, 193, 284, 732, 776
- show ip route eigrp command, 193, 776
- show ip route isis command, 396
- show ipx access-list command, 778
- show ipx interface command, 778
- show ipx route command, 778
- show ipx servers command, 778
- show ipx traffic command, 778
- show isdn active command, 781
- show isdn status command, 781
- show isis topology command, 386
- show logging command, 474
- show mac-address table security command, 784
- show mac-address-table command, 784
- show mac-address-table secure command, 784
- show port security command, 784
- show processes command, 772
- show running-config command, 772–773, 784
- show sessions command, 772
- show spanning-tree vlan command, 784
- show spantree command, 784
- show startup-config command, 772–773
- show terminal command, 772
- show trunk command, 784
- show users command, 772
- show version command, 772, 784
- show versions command, 784
- show vlan brief command, 784
- show vlan command, 784
- show vlan-membership command, 784
- show vtp command, 784
- show vtp domain command, 785
- show vtp status command, 785
- shutdown command, 775, 786
- SIA (stuck in active) mode, 840
- SIA (stuck-in-active) routes, 182
- single-area OSPF, configuring, 712–713
- SNAP (Subnetwork Access Protocol), 99
- snmp-server command, 786
- SPF (shortest path first) calculations, 219
- SPF algorithm, 415
- split horizon
 - EIGRP, 154
 - route reflectors, 747. *See also* route reflectors clients, 748

- cluster IDs, 748
- cluster lists, 748
- clusters, 748
- compatibility with peer groups, 752
- configuring, 752
- design, 749–750
- example, 753
- faulty design, 751
- migrating to, 750–751
- restrictions, 752
- rule, 537
- verifying, 753
- split horizon (BGP), 746
- SRTT (smooth round trip timer), 150
- standard IP access lists, 44, 466, 674
 - configuring, 678
 - example, 680–681
 - numbering, 674
 - processing, 676
 - wildcard masks, 676
- star topology, 244
- state, 42–43, 63, 450, 829
- stateless autoconfiguration method, 50
- static default routes, configuring, 94
- static routes, 442, 514–515
 - administrative distance, 515
 - conf, 444
 - configuring, 442–444
 - ex, 516
 - floating, 115
- static routing, 91–92
 - configuring, 93
 - configuring static default routes, 94
- Stream Control Transmission Protocol (SCTP), 54
- stub areas, 294–295
 - configuration, 296
 - NSSAs, 709–711
 - routing tables, 300
- stubs
 - configuring, 205
 - limiting EIGRP query range, 188–190
- subinterfaces, 251
- subnet addresses (WAN links), 24
- subnet masks, 16, 669
 - calculating, 670–672
 - prefixes, 18, 672–673
- subnet zero, 17
- subnets, redistributing, 431
- subnets keyword (redistribute command), 756
- subnetting, 16–17
 - classless routing protocols, 107
 - extending IP addresses, 17
 - job aids, 663
- Subnetwork Access Protocol (SNAP), 99
- summarization (route), 27, 103
 - BGP route summarization, 608–610
 - calculation example, 30
 - CIDR, 32, 34
 - EIGRP, 145, 170–171
 - configuration exercise, 205
 - configuring, 172–173
 - implementation, 31
 - in IP routing protocols, 32
 - limiting EIGRP query range, 186
 - multiple Class C addresses, 33
 - network boundary, 607
 - operation in Cisco routers, 31
 - OSPF, 286–287
 - commands, 288–289
 - creating default routes, 290–292
 - overview, 27–28
 - vs. CIDR, 34
 - VLSMs, 20, 30
- summarized networks, 15
- summary addresses, 611–613
- summary numbers, 12
- summary-address command, 173, 289
- supernetting, 27
- suppressing ACKs, 180
- switchport access command, 786–787
- switchport mode command, 786–787
- synchronization, disabling, 556
- synchronization rule (BGP), 541–542, 573, 597

T

- tables (BGP), 522, 862
- TCP (Transmission Control Protocol), 517
- TCP load distribution, 37
- TCP port names, 686–687
- TCP sessions, 686
- TCP/IP applications, 813
- telnet command, 772
- term ip netmask-format command, 776
- terminal editing command, 772

- terminal history size command, 772
- terminal monitor command, 772
- terminology
 - EIGRP, 146
 - NAT, 36
- that, 418
- the wire, 17
- third-party next hops, 530
- tiered network model, 181, 192
- timers basic command, 99
- TLVs (type, length, and value), 717–718
- to, 618
- topologies
 - frame relay, 244
 - IS-IS in CLNS environments, 376
 - broadcast networks, 376–377
 - point-to-point networks, 378
 - NBMA, 245
 - route reflector design, 751
- topology tables (EIGRP), 146, 152
- totally stubby areas, 297
 - configuration, 298
 - routing tables, 300
- traceroute command, 464, 471, 772
- traffic
 - controlling routing update traffic, 441
 - default routes, 443–444
 - distribute lists, 445–449
 - route maps, 450–454
 - static routes, 442
 - EIGRP load balancing, 173–174
 - restricting (passive-interface command), 437
- traffic-share command, 175, 778
- trailers, 809, 813
- transport layer (OSI model), 811
- troubleshooting
 - avoiding route feedback with route maps, 454
 - BGP
 - active state, 571
 - debug ip bgp updates command output, 568
 - idle states, 570
 - neighbor states, 569
 - CLNS, 385
 - IS-IS, 396–397
- trunk command, 786–787
- TTL (time-to-live), 552
- tuning
 - IS-IS, 394

- redistribution (configuration exercise), 482–484, 496–498
- tunnels
 - 6to4 tunneling, 58–59
 - manually configured, 58
- type 1 LSAs, 279
- type 2 LSAs, 280
- type 3 LSAs, 281
- type 4 LSAs, 281
- type 5 LSAs, 282
- type 7 LSAs, 709–710
- type codes
 - BGP attributes, 527
- type, length, and value. *See* TLV, 717

U

- UDP (User Datagram Protocol), 110
- UDP port names, 688
- undebug command, 772
- unicast addresses, 48
 - helper addresses, 695–700
 - configuring, 697–698
 - server placement, 696
- unnumbered interfaces, 694–695
- update messages (BGP), 524–526
- update policies, 547
- update reliability (IP routing protocols), 117
- updates (EIGRP), 148, 836
- upper layers (OSI model), 806
 - (EIGRP), 150
- User Datagram Protocol (UDP), 110
- username command, 782
- utilities, confreg, 764

V

- variable-length subnet masking (VLSMs), 98
- variable-length subnet masking. *See* VLSMs
- variance command, 174, 778
- variance 2 command, 175
- variance 4 command, 175
- verifying
 - access list configuration, 693

- BGP operation, 564
 - show ip bgp command output, 564, 566
 - show ip bgp neighbors command output, 566
 - show ip bgp summary command output, 567
- EIGRP connectivity, 197–198
- EIGRP operation, 192–193
- IS-IS configuration, 396–397
- OSPF operations, 236, 238
- OSPF routing process at edge and internal routers, 332
- OSPF virtual link operation, 307
- PBR, 471
- policy based routing, 471, 860
- prefix lists, 740
- redistribution operation, 464
- route reflectors, 753
- viewing route maps, 471, 860
- virtual circuit management, 812
- virtual links
 - OSPF, 303
 - configuration exercise, 319, 321
 - configuration exercises, 345–349
 - configuring, 304–307
 - verifying operation, 307
- vlan command, 786
- vlan database command, 786
- vlan-membership command, 786–787
- VLSMs (variable-length subnet masks), 3, 98
 - calculators, 22–26
 - conserving IP addresses, 20
 - implementing in scalable networks, 19
 - oute summarization, 20
 - summarizing addresses in a VLSM-designed network, 30
- vty, denying access, 691

W–Z

- WAN commands, 780–782
- WAN configuration commands, 781–782
- WAN links, configuring, 175–176, 180
- WAN protocols, 807
- WANs
 - adjacencies, 382
 - Cisco IOS EXEC commands, 780
 - subnet addresses for WAN links, 24
- weight attribute, configuring, 626
- weight attribute (BGP), 535–536
- weighted fair queuing (WFQ), 469
- weighted random early detection (WRED), 469
- weights (multihomed routes), modifying, 636
- well-known attributes (BGP), 526
- well-known mandatory attributes
 - AS-path, 528
 - next-hop, 529–531
 - origin, 532
- WFQ (weighted fair queuing), 469
- wildcard masks, 676
 - examples, 677
 - implicit, 679
- WRED (weighted random early detection), 469
- write erase command, 773
- write memory command, 773
- write network command, 773
- write terminal command, 773