

## Symbols

---

- ! (exclamation point) character, 102
- # (pound sign) character, 102

## Numerics

---

- 10 Gigabit Ethernet, 52
- 10-Mbps Ethernet, 46
- 10/100/1000-Mbps auto-negotiation architecture, 742–744
- 802.1D, compatibility with RSTP, 223
- 802.1Q packet tagging, 683
- 802.1X
  - configuration exercise, 607–610
  - network access security, 598–600
  - port authorization state, 599–600

## A

---

- AAA
  - accounting, 593, 596–597
  - authentication, 591–593
  - authorization, 592–594
  - configuration exercise, 607–610
- aaa authentication login command, 593
- aaa new-model command, 90, 593
- access layer, 17
- accounting, 593, 596–597
- ACLs (access control lists), 4, 586–587
  - QoS ACLs, 601
  - RACLs, 602
  - security, 601
  - VACLs, 602
- Address Resolution Protocol (ARP), 11
- addressing
  - Fibre Channel, 638
  - MAC address notification, 304–305
- adjacencies, 379
- adjacency tables, 363
- ADSL (asymmetric digital subscriber line), 54

- aggressive mode UDLD, 320–322
  - configuration exercises, 333–334
  - versus Loop Guard, 265
- AppleTalk Remote Access (ARA), 592
- ARA (AppleTalk Remote Access), 592
- arbitrated loop topology, 640
- Architecture for Voice, Video and Integrated Data.
  - See* Cisco AVVID
- architectures (Fibre Channel), 637
- ARP (Address Resolution Protocol), 11
- ASICs (application-specific integrated circuits), 4, 268
- assured forwarding, 399, 400
- asymmetric digital subscriber line (ADSL), 54
- attenuation, 680
- authentication, 591–593
  - VTP, 171
- authorization, 592–594
- auth-proxy, 594
- auto-negotiation
  - 10/100/1000-Mbps architecture, 742–744
  - concerns, 51
  - control register auto-negotiation bit description, 745
  - mixing with manual configurations, 744
  - purpose of, 741
- auto-RP, 470
- AVPs, 592
- AVVID. *See* Cisco AVVID

## B

---

- baby giants, 155, 315
- BackboneFast, 250
  - configuration exercise, 274–276
  - configuring, 254
  - link failures, 252
- black holes, preventing, 261–264
- blocking state, 195
- boot system flash command, 100
- bootstrap routers (BSRs), 471
- BPDU Guard, 248, 255

- BPDUs (Bridge Protocol Data Units), 192
  - filtering, 256
  - format, 219
  - frame formats, 193
  - skewing, 257
  - TCN, 203
  - timers, 194
- bridge IDs, 191
- bridge virtual interface (BVI), 347
- bridges, signaling topology changes, 202–204
- bridging loops, 188
  - Loop Guard, 263
  - preventing, 190
  - troubleshooting, 270
- broadcast, 454
- broadcast domains, 6
- broadcast suppression, 311–312
- BSRs (bootstrap routers), 471
- buffer-to-buffer credit, 654
- Building Access submodule, 22, 25, 437
- Building Distribution submodule, 22, 25, 438
- burst size, 418
- BVI (bridge virtual interface), 347

## C

- CAM (content addressable memory), 368
- Campus Backbone layer, 65
- Campus Backbone submodule, 22, 25
- Campus Infrastructure module, 55
- campus networks
  - designing
    - large campus networks, 60–63
    - medium-sized campus networks, 58–59
    - small campus, 57
  - integrating storage networking, 647
  - VLANs, 128–129
- campuses, 19
- case studies
  - aggressive mode UDLD, 322–327
  - designing a Cisco multilayer switched network, 69–70
- Catalyst 2950 switches, 37, 627–628
  - power redundancy, 523
  - WRR, 425
- Catalyst 2955 switches, 37

- Catalyst 2970 switches, 425
- Catalyst 3550 switches, 36, 625–626
  - metro Ethernet solutions, 665
  - power redundancy, 523
  - updating software versions, 102
- Catalyst 3750 switches, 36, 623–624
  - metro Ethernet solutions, 664
  - SRR, 425
- Catalyst 4500 switches, 36, 620–621
  - metro Ethernet solutions, 664
  - redundant power supplies, 521–522
- Catalyst 6500 switches, 34, 613, 663
  - configuring
    - Q-in-Q tunneling, 690
    - WRR, 423
  - deployment scenarios, 620
  - image naming, 98
  - line cards, 616
  - metro Ethernet solutions, 663
  - OS, 80
  - redundant power supplies, 521–522
  - service modules, 615
  - SRM, 516
    - configuring, 518
    - displaying status, 519
    - failure scenario, 518
  - Supervisor Engine I, 616
  - Supervisor Engine II, 617
  - Supervisor Engine 720, 618
  - VACL actions, 602
- Catalyst 7600 switches, 663
- Catalyst QoS trust concept, 405
- Catalyst switches
  - authorization, 592
  - BackboneFast, 253
  - bridge IDs, 191
  - Cisco IOS–based
    - SPAN, 706
  - configuring
    - as VTP servers, 172
    - multicast, 485
    - multilayer switching, 361
  - configuring voice VLANs (configuration exercise), 577, 578, 579, 580, 581
  - EtherChannel, 282
  - L2 traceroute availability, 724
  - Loop Guard, 264

- metro Ethernet positions, 663
  - MST support, 230
  - multilayer, 342
  - policing, 418
  - port authorization state of 802.1X, 599–600
  - pVLANs, 143
  - QoS fundamentals, 401–402
    - classification, 404–412
    - congestion avoidance, 427–430
    - congestion management, 420–426
    - marking, 413–415
    - traffic conditioning, 416–419
  - redundant Supervisor Engine uplink modules, 520
  - redundant Supervisor Engines, 508–510
    - route processor redundancy, 510–511
    - RPR+, 512–515
  - RPVST+ support, 217
  - RSPAN feature support, 716
  - security, 585
    - ACLs, 586–587
    - disabling the integrated HTTP daemon, 589
    - disabling unneeded services, 588
    - passwords, 586
    - physical access, 587
  - software images, 95–98
  - troubleshooting, 104
    - configuration commands, 106
    - connecting to switches via console ports, 108
    - debug commands, impact and use, 106
    - IP connectivity, 109
    - show and debug commands, 105
  - updating software versions, 99–102
  - VMPS support, 131
  - wavelengths, 677
- CDP, 293–294
  - minimizing use of, 589
- CDWM, 678–679
- CEF (Cisco Express Forwarding), 361–363, 514
- CEF-based MLS, 361–363
  - configuration, 375
    - viewing Layer 3 Engine adjacency table, 378
    - viewing Layer 3 Engine CEF table, 376
  - distributed switching, 365–366
  - load sharing, 374
  - sample operation, 372
  - switching table architectures
    - CAM, 368
    - TCAM, 369–371
  - troubleshooting
    - configuration exercise, 382–386
    - debugging CEF on Layer 3 Engine, 380
    - methodology, 381
    - verification, 375
- CEF-based MMLS, 480
- CGMP (Cisco Group Management Protocol), 483–484
- channeling (EtherChannel), 282
- chromatic dispersion, 680
- Cisco AVVID, 14, 38
  - applications, 15
  - network topology, 15
  - supported components, 14
- Cisco AVVID IP telephony solution, 568
- Cisco Catalyst switches. *See also* Catalyst switches
  - configuration of management parameters, 83
  - clock and NTP settings, 86–88
  - DNS, 92
  - management IP address, 85
  - system logging, 92
  - system names, 84
  - Telnet and SSHs, 89–91
- managing configurations, 93
- overview, 34
- Cisco CatOS
  - compared to Cisco IOS (Native Mode), 80, 83
  - configuring VLANs, 136
  - converting to Cisco IOS (Native Mode), 103
  - feature parity with Cisco IOS (Native Mode), 81–82
  - MDGs, 303–304
  - switches, 86
    - configuration changes, 94
    - displaying STP information, 214
    - DNS lookup, 92
    - passwords, 89
    - syslog destination, 93
    - time adjustments, 88
    - verifying trunking configurations, 163
- Cisco CatOS–based switches
  - L2 traceroute command output, 726
  - SPAN configuration, 708
- Cisco Express Forwarding (CEF), 361–363, 514
- Cisco Group Management Protocol (CGMP), 483–484

- Cisco IFS, 95
  - determining IFS size and contents, 97
  - formatting and copying images, 95
  - prefix descriptions, 96
- Cisco IOS
  - configuring
    - AAA authorization, 596
    - Catalyst switches (exercise), 111–117
    - IEEE 802.1Q trunking, 160–161
    - ISL trunking, 159
  - debug command, 105
  - file system, 95
    - determining size and contents, 97
    - image naming, 97–98
  - global configuration mode, 133–135
  - hybrid mode, 98
  - image upgrading, 101
  - Native Mode
    - compared to Cisco CatOS, 80, 83
    - converting to from Cisco CatOS, 103
    - feature parity with Cisco CatOS, 81–82
    - naming conventions, 98
    - show command, 105
  - switches
    - configuring for SSH, 91
    - DNS, 92
    - DNS lookup, 92
    - L2 traceroute command output, 725
    - NTP settings, 88
    - SPAN configuration, 709
    - syslog destination, 93
    - time adjustments, 88
  - verifying trunking configurations, 161–162
  - VLAN database configuration mode, 133
  - voice VLANs, 570
- Cisco IOS Server Load Balancing. *See* SLB
- Cisco IP phone daisy-chain topology, 569
- Cisco LRE (Long-Reach Ethernet), 54
- Cisco MDS 9000 multilayer switches, 649
  - iSCSI/FCIP, 651
    - multipath forwarding, 652
  - port channeling, 652
  - VSANs, 650
  - zoning, 653
- Cisco metro solutions, 660
  - example, 661
  - generic hierarchy, 662
    - metro Ethernet switching products, 662
      - Catalyst 3550 switches, 665
      - Catalyst 4500 switches, 664
      - Catalyst 6500/Cisco 7600 switches, 663
    - optical platforms, 662
- Cisco SN 542x iSCSI routers, 654–655
- Cisco StackWise technology, 624
- Cisco storage solutions, 648
  - Cisco MDS 9000 multilayer switches, 649–652
  - Cisco SN 542x iSCSI routers, 654–655
- classification, 404–409
  - NBAR, 410–412
  - policy-based routing, 412
- clear vlan command, 137
- CLI (command-line interface), 79
- clock settings (Cisco Catalyst switches), 86–88
- commands (SCSI), 634
- Common Spanning Tree (CST), 225
- community VLANs, 142
- components
  - CEF, 363
  - Cisco AVVID, 14
  - Internet Connectivity module, 29
  - Remote Access module, 30
  - VPN module, 30
- compression (header compression), 435
- configuration exercises
  - 802.1X, 606–610
  - AAA, 606–610
  - aggressive mode UDLD, 333–334
- configuring
  - BackboneFast, 274–276
  - Cisco IOS–based Catalyst switches, 111–117
  - HSRP, 560–562
  - multicast in multilayer switched networks, 494–498
  - QoS on Catalyst Switches, 440–446
  - Root Guard, 277
  - RPR+, 557–559
  - spanning-tree priorities and spanning-tree port cost, 234–241
  - UplinkFast, 277
  - VLAN, trunking, and VTP in multilayer switched networks, 176–180
  - voice VLANs on a Catalyst switch, 577–581
- EtherChannel, 328–332

- inter-VLAN routing using SVI on Building
  - Distribution switch, 358
  - troubleshooting CEF-based MLS, 382–386
  - VACLs, 607, 610
- configuring, 542
  - AAA accounting, 596–597
  - AAA authentication, 593
  - AAA authorization, 594
  - aggressive mode UDLD, 326
  - baby giant and jumbo frame support, 318
  - BackboneFast, 254, 274–276
  - broadcast and multicast suppression, 312
  - burst size, 418
  - CEF-based MLS, 375
    - viewing Layer 3 Engine adjacency table, 378
    - viewing Layer 3 Engine CEF table, 376
  - Cisco IOS–based Catalyst switches, 111–117
  - debounce timer feature, 310
  - DHCP snooping, 315
  - DNS lookup, 92
  - err-disable timer, 298
  - EtherChannel, 288–290
  - FCIP, 647
  - HSRP, 534–541
  - IEEE 802.1Q trunking, 160–161
  - inter-VLAN routing, verifying configuration, 350
  - iSCSI, 644
  - ISL trunking, 159
  - LACP, 285
  - MAC address notification, 305
  - management parameters of Cisco Catalyst switches, 83
    - management IP address, 85
    - system names, 84
  - marking, 415
  - MDGs, 304
  - MST, 230–233
  - multicast, 485–486
    - IGMP snooping, 487
    - sparse-dense mode with BSR, 487
  - multilayer switched networks, 79, 361
  - NAM, 728
  - policing, 419
  - PortFast, 247–248
  - protocol filtering, 307
  - PVST+
    - port cost, 210
    - root bridges, 209
  - Root Guard, 260, 277
  - RPR+, 515
  - RSPAN, 717–718
  - SPAN, 708
  - SRM, 518
  - STP, 211–213, 236
  - switches for SSH, 91
  - syslog destination, 93
  - UDLD, 322
  - UplinkFast, 249, 277
  - VACL with the capture option, 722
  - virtual servers, 554
  - VLANs, 133–137
    - private VLANs, 147
    - verifying configuration, 138–139
  - VTP, 171–174
  - WRED, 431
  - WRR on Catalyst 6500 switches, 423
- congestion avoidance
  - tail drop, 427
  - WRED, 428–430
- congestion management, 420
  - FIFO queuing, 421
  - priority queuing, 425–426
  - WRR, 422–424
- console ports, connecting to switches, 108
- content addressable memory (CAM), 368
- converting Cisco CatOS to Cisco IOS (Native Mode), 103
- copy command, 93
- copy running-config startup-config command, 514
- copy tftp flash command, 100
- copying images on the Cisco IFS, 95
- core layer, 17
- core LSRs, 697
- CQ (custom queuing), 426
- creating
  - loop-free spanning trees
    - planning root bridge selection, 198–199
    - root bridge election, 198
    - selection of root and designated ports, 200
  - VLANs, 135–137
- crypto key generate command, 90
- CST (Common Spanning Tree), 225

custom queuing (CQ), 426  
CWDM GBIC modules, 679  
CWDM OADM modules, 679

## D

---

DAS (Direct Attached Storage), 633  
data paths (Catalyst 6500 switches), 615  
data-link technologies, 45

- 10 Gigabit Ethernet, 52
- 10-Mbps Ethernet, 46
- Fast Ethernet, 47
- Fast Ethernet and Gigabit Ethernet auto-negotiation, 51
- GBICs, 53
- Gigabit Ethernet, 48–50
- LRE, 54

debounce timer feature, 309

- configuring, 310
- enabling, 309

debug all command, 107  
debug command, 107  
debugging CEF on the Layer 3 Engine, 380  
default gateway router redundancy, 523

- GLBP, 547
- HSRP, 527–542
- IRDP, 525
- proxy ARP, 524
- static default gateway configuration, 526
- VRRP, 543–546

deleting VLANs, 135–136  
deploying IP telephony solutions, 575  
designing

- multilayer switched networks
  - case study, 69–70
  - Cisco Catalyst switches and data-link technologies, 55
  - configuration, 79
  - data-link technologies, 45
  - large campus networks, 60–63
  - medium-sized campus networks, 58–59
  - selecting Layer 2 or Layer 3 switches, 56
  - Server Farm module, 63–66
  - small campus networks, 57
- networks (IP telephony), 567–574

DHCP snooping, 313–314

DHCP-based management IP configuration, 307–308  
DiffServ (differentiated services) model, 389, 396

- IP precedence bit mappings, 398
- packet classification, 397

directed VLAN service (DVS), 669  
Direct Attached Storage (DAS), 633  
disabled state, 195  
disabling

- CDP, 589
- integrated HTTP daemon, 589
- Telnet access, 116
- unnneeded or unused services, 588

discard adjacency, 379  
distance limitations

- Ethernet wire, 48
- Gigabit Ethernet, 50

distributed switching, 366  
distribution layer, 17  
DNS, configuring on switches, 92  
drop adjacency, 379  
DSCP, 405  
duplex mismatch, 266  
DVS (directed VLAN service), 669  
DWDM

- metro Ethernet, 674–675
- OADMs, 678
- optical multiplexers, 678
- wavelengths, 676

dynamic VLANs, 131

## E

---

E-Commerce module, 28  
EDFAs (eribium doped fiber amplifiers), 678  
Edge Distribution module, 24  
Edge Distribution submodule, 23  
egress LER, 697  
EIGRP (Enhanced Interior Gateway Routing Protocol), 62  
electing a root bridge, 198  
EMI (Enhanced Multilayer Image), 625  
enabling

- debounce timer feature, 309
- NDE as source for NAM, 732
- passwords, 89

encapsulation dot1Q 1 native command, 349

- end-to-end VLANs, benefits in campus networks, 129
- Enhanced Interior Gateway Routing Protocol (EIGRP), 62
- Enhanced Multilayer Image (EMI), 625
- enhancing network performance
  - critical success tasks, 704
  - monitoring with RSPAN, 714
    - configuring, 717–718
    - guidelines and restrictions, 714–715
  - monitoring with VACL with the capture option, 721–722
  - SPAN, 705–706
    - configuring, 708
    - guidelines and restrictions, 706
    - monitoring CPU interface of switches, 711–712
  - VSPAN
    - configuration, 710
    - guidelines and restrictions, 707
- Enterprise Campus, 21
  - infrastructure, 22
  - meeting the needs of Enterprise networks, 25
  - sample implementation, 24
  - submodules, 22–24
- Enterprise Composite Network Model, 12, 17
  - Campus Infrastructure module, 55
  - Enterprise Campus, 21–24
  - Enterprise Edge, 19, 26
    - E-Commerce module, 28
    - Internet Connectivity module, 29
    - modules, 27
    - Remote Access module, 30
    - sample implementation, 31
    - VPN module, 30
    - WAN module, 30
  - Gigabit Ethernet, deployment strategies, 49
  - IP telephony deployment best practices, 575
  - overview, 18
  - sample implementation, 20
  - Service Provider Edge, 19, 31
    - ISP module, 32
    - PSTN module, 32
    - sample implementation, 33
- Enterprise Edge, 19, 26, 68
  - E-Commerce module, 28
  - Internet Connectivity module, 29
  - modules, 27
  - Remote Access module, 30
  - sample implementation, 31
  - VPN module, 30
  - WAN module, 30
- Enterprise Edge submodule, 25
- enterprise MANs, 665
- enterprise networks, storage, 64
- EoMPLS (Ethernet over Multiprotocol Label Switching), 691–693
  - characteristics, 694–695
  - frames, 696–697
  - functionality, 694
  - multipoint, 698
- erase startup-config command, 94
- erbium doped fiber amplifiers (EDFAs), 678
- err-disable timer, 298
- ESCON (Ethernet, Enterprise Systems Connection), 661
- EtherChannel, 282
  - configuration example, 287–290
  - configuration exercises, 328–332
  - guidelines, 286
  - LACP modes, 285–286
  - link redundancy, 507
  - load balancing, 290–292
  - PAgP modes, 284
- Ethernet
  - 10 Gigabit Ethernet, 52
  - 10-Mbps Ethernet, 46
  - baby giants, 315
  - Fast Ethernet, 47
  - Gigabit Ethernet, 48
    - deployment strategies, 49
    - distance limitations, 50
  - jumbo frames, 317–318
  - metro Ethernet, 54, 665
    - CDWM, 678–679
    - connectivity and transport, 666–669
    - DWDM, 675
    - EoMPLS, 691–697
    - EoMPLS multipoint, 698
    - optical distance challenges, 680–681
    - Q-in-Q Catalyst configuration, 689
    - SONET, 670–672
    - tunneling, 681–687
    - WDM, 673–674

EtherChannel (*continued*)

- metro Ethernet switching products, 662–663
    - Catalyst 3550 switches, 665
    - Catalyst 4500 switches, 664
  - trunking modes, 158
  - wire standards and maximum distances, 48
- Ethernet over Multiprotocol Label Switching. *See* EoMPLS
- Ethernet, Enterprise Systems Connection (ESCON), 661
- EtherType fields, 686
- exclamation point (!) character, 102
- expedited forwarding, 400

---

**F**

- Fast Ethernet, 47, 51
- fast link pulses (FLPs), 742
- FCID (Fibre Channel\_ID), 638
- FCIP (Fibre Channel over IP), 633
  - configuring, 647
  - implementing, 646
  - overview, 646
- FEC (Forwarding Equivalence Class), 697
- Fibre Channel, 636
  - addressing, 638
  - architecture, 637
  - buffer-to-buffer credit, 654
  - comparison with IP, 641
  - port types, 639
  - topologies, 639–640
- Fibre Channel over IP. *See* FCIP
- Fibre Channel\_ID (FCID), 638
- FIBs, 363
- FICON (Fibre Connection), 661
- FIFO queuing, 421
- file systems, 95
- filtering
  - BPDU, 256
  - DHCP snooping, 313
- flooding, blocking unicast flooding on desired ports, 302
- FLPs (fast link pulses), 742
- formatting images on the Cisco IFS, 95
- forward delay timer, 195

- Forwarding Equivalence Class (FEC), 697
- forwarding loops, preventing, 261, 264
- forwarding state, 195
- Frame Relay, ATM, and PPP module, 33
- frames
  - baby giants, 155, 315
  - BPDU, 193
  - corruption, 268
  - EoMPLS, 696
  - IEEE 802.1Q, 154
  - ISL, 151
  - jumbo, 317–318
- functional areas (Enterprise Composite Network Model), 20

---

**G**

- GBICs (Gigabit Interface Converters), 53
- Gigabit Ethernet, 48
  - deployment strategies, 49
  - distance limitations, 50
  - Fast Ethernet and Gigabit Ethernet auto-negotiation, 51
- GLBP (Gateway Load Balancing Protocol), 547
- global configuration mode, 135
- globally scoped addresses, 458
- GLOP addressing, 459
- groups, multicast, 456

---

**H**

- hardware-switching, 4
- header compression, 435
- hello time timer, 195
- high availability, 503–504, 507
  - IP telephony solutions, 574
- Host Side IGMP Library (HSIL), 478
- Hot Standby Router Protocol. *See* HSRP
- HSIL (Host Side IGMP Library), 478
- HSRP (Hot Standby Routing Protocol), 7, 527, 542
  - configuration exercise, 560–562
  - configuring, 534–542
  - load balancing, 532
  - states, 529



virtual MAC address, 530  
 virtual router, 528  
 Hybrid OS, 80

**I**

---

IEEE 802.1D, 191. *See also* STP  
 IEEE 802.1Q, 150  
   implementing, 152–155  
   trunking, 207  
     configuring, 160–161  
     verifying configuration, 161–163  
 IEEE 802.1Q-in-Q tunneling, 157  
 IEEE 802.1w. *See* RSTP  
 IGMP  
   IGMPv1, 473  
   IGMPv2, 474–475  
   IGMPv3, 476  
     query message field description, 476  
     report packet field description, 477  
   IGMPv3 lite, 478  
   snooping, 482, 487  
 image naming (Cisco IOS), 97–98  
 images  
   loading on a Catalyst switch, 100  
   transport methods, 103  
 implementing  
   FCIP, 646  
   IEEE 802.1Q, 152–155  
   iSCSI, 642  
   ISL, 150–152  
   pVLANs, 143  
   redundant Supervisor Engine uplink modules,  
     520  
   VSANs, 650  
   zoning, 653  
 infrastructure (Enterprise Campus), 22  
 inpkts keyword, 708  
 integrated services (IntServ) model, 389, 395  
 intelligent, 627  
 interfaces (Catalyst 6500 switches), 614  
 Internet Connectivity module, 29  
 Internet service providers (ISPs), 5  
 Internetwork Packet Exchange (IPX), 592  
 Inter-Switch Link (ISL), 150

inter-VLAN routing, 339–341  
   configuration exercise, 358  
   IP broadcast forwarding, 352–353  
   multilayer Catalyst switches, 341–344  
     bridge virtual interface, 347  
     switch virtual interface, 345–346  
   router on a stick, 347–349  
   UDP broadcast forwarding, 353  
   verifying configuration, 350  
 IntServ (integrated services) model, 389, 395  
 IP  
   addresses, 457–459  
   comparison with Fibre Channel, 641  
   gateways, 643  
 IP helper-address command, 353  
 IP multicast protocol, 484–485  
   IGMP  
     IGMPv1, 473  
     IGMPv2, 475  
     IGMPv3, 476–477  
     IGMPv3 lite, 478  
   PIM, 466  
     automating distribution of RP, 469  
     PIM sparse-dense mode, 469  
     PIM-DM, 467  
     PIM-SM, 468  
     version comparison and compatibility, 472–473  
 IP multicast shared tree distribution, 464  
 IP multicast source distribution tree, 464  
 IP RTP Priority, 432–433  
 IP telephony  
   deployment best practices, 575  
   high availability, 574  
   network design recommendations, 567–568  
     network bandwidth provisioning, 571  
     network management, 573  
     power considerations, 572  
     QoS, 568  
     security, 574  
     voice (auxiliary) VLANs, 569–570  
 IPX (Internetwork Packet Exchange), 592  
 IRDP, 525  
 iSCSI (IP over SCSI), 633  
   configuring, 644  
   implementing, 642  
   IP gateways, 642–643  
   overview, 642

- ISL (Inter-Switch Link), 150
  - implementing, 150, 152
  - trunking
    - configuring, 159
    - verifying configuration, 161–163
- isolated VLANs, 142
- ISP module, 32
- ISPs (Internet service providers), 5
- ITU grid, 677

## J–L

---

- JBODs (just a bunch of disks), 634
- jitter, 393
- jumbo frames, 317, 318
- just a bunch of disks (JBODs), 634
- L2 traceroute command
  - availability on Catalyst switches, 724
  - output from Cisco IOS–based switches, 725
- LACP
  - configuring, 285
  - modes, 285–286
- large campus networks, 60, 63
- latency, 392
- Layer 2
  - Cisco CatOS, 80
  - legacy switches, 6
  - multicast protocols, 481
    - CGMP snooping, 483–484
    - IGMP snooping, 482
  - multilayer switching, 12
  - protocols
    - CDP, 293–294
    - UDLD, 319
  - switching, 6, 9
- Layer 3
  - marking, 413
  - multilayer switching, 12
  - protocol filtering, 306–307
  - switching, 7, 10, 14
    - ARP, 11
    - packet rewriting, 10
    - routing protocol support, 343
    - viewing Layer 3 Engine adjacency table, 378
    - viewing Layer 3 Engine CEF table, 376

- Layer 4
  - performance, 8
  - QoS marking, 6
  - terminology, 7
- Layer 7 switching, 8
- layers
  - multilayer switched networks, 5
  - Network Design Hierarchical Model, 17
  - PDUs, 9
  - Server Farm module, 65
- leaky token buck algorithm, 417
- learning state, 195
- LFI (link fragmentation and interleaving), 435
- limited-scope addresses, 459
- line cards (Catalyst 6500 switches), 616
- link-efficiency mechanisms, 434–435
- links
  - failures, 252
  - redundancy, 507
  - spanning-tree path cost, 191
  - unidirectional link failures, 267
- listening state, 195
- LLQ (low-latency queuing), 432
- load balancing
  - EtherChannel, 290–292
  - HSRP, 532
- load sharing (CEF-based MLS), 374
- local VLANs, benefits in campus networks, 129
- Loop, 264
- Loop Guard, 261–264
  - Root Guard, 264
  - versus aggressive mode UDLD, 265
- loop-free spanning trees, creating
  - planning root bridge selection, 198–199
  - root bridge election, 198
  - selection of root and designated ports, 200
- loops
  - bridging, preventing, 190
  - bridging loops, 188
- low-latency queuing (LLQ), 432

## M

---

- MAC addresses, 191
  - notification, 304–305
- managing Catalyst switch configurations, 93

- mappings (VLANs), 156
- marking, 413
  - configuring, 415
  - Layer 3, 415
- max age timer, 195
- MDGs (Multiple Default Gateways), 303–304
- metro Ethernet, 54, 665
  - CDWM, 678–679
  - connectivity and transport, 666–667
    - DVS, 669
    - TLS, 668
  - DWDM, 675
  - EoMPLS, 691–693
    - characteristics, 695
    - frames, 696–697
    - functionality, 694
      - multipoint, 698
  - optical distance challenges, 680–681
  - SONET, 670–672
  - tunneling, 681
    - 802.1Q packet tagging, 683
    - no tunneling, 682
    - Q-in-Q Catalyst configuration, 689
    - tag stacking (Q-in-Q tunneling), 684–687
  - WDM, 673–674
- metro Ethernet switching products, 662–663
  - Catalyst 3550 switches, 665
  - Catalyst 4500 switches, 664
- metro solutions. *See* Cisco metro solutions
- MFIB (multicast forwarding information base), 481
- MFSC (Multilayer Feature Switch Card) model, 103
- MLS (multilayer switching), 361
  - CEF-based MLS, 363
    - configuration, 375
    - distributed switching, 366
    - load sharing, 374
    - sample operation, 372
    - switching table architectures, 368–371
    - troubleshooting, 380–386
    - verification, 375
    - viewing Layer 3 Engine adjacency table, 378
    - viewing Layer 3 Engine CEF table, 376
  - traditional MLS, 362
- mls nde sender command, 731
- MMLS (multicast multilayer switching), 479
- mode rpr-plus command, 559
- monitoring IP multicast traffic, 489–493
- monitoring performance
  - RSPAN, 714
    - configuring, 717–718
    - guidelines and restrictions, 714–715
    - VACL with the capture option, 721–722
- moving configurations from one device/component to another, 93
- MSFC (Multilayer Switch Feature Card), 79, 616
- MST (Multiple Spanning Tree), 224–226
  - 802.1Q, 225
    - configuring, 230–233
  - IST instances, 228
  - instances, 229
  - PVST+, 225
  - regions, 227
- multicast
  - configuring, 485–487
  - forwarding tree, 463
    - shared trees, 464
    - source trees, 463
  - group membership, 456
  - hardware-based switching methods, 479
    - CEF-based MMLS, 480
    - MFIB, 481
    - MMLS, 480
  - IP address structure, 457
    - GLOP addresses, 459
    - reserved link local addresses, 458
  - overview, 453–455
  - RPF, 460–461
  - suppression, 312
- multicast forwarding information base (MFIB), 481
- multicast multilayer switching (MMLS), 479
- multilayer Catalyst switches, inter-VLAN routing, 341–344
  - bridge virtual interface, 347
  - IP broadcast forwarding, 352–353
  - router on a stick, 347–349
  - switch virtual interface, 345–346
  - UDP broadcast forwarding, 353
  - verifying configuration, 350
- Multilayer Switch Feature Card (MSFC), 79, 103, 616

- multilayer switched networks, 5
  - Catalyst switch security, 585–587
  - Cisco AVVID, 14
    - applications, 15
    - supported components, 14
  - configuring, 79
  - data-link technologies, 45
    - 10 Gigabit Ethernet, 52
    - 10-Mbps Ethernet, 46
    - Fast Ethernet, 47
    - Fast Ethernet and Gigabit Ethernet auto-negotiation, 51
    - GBICs, 53
    - Gigabit Ethernet, 48–50
    - LRE, 54
  - default gateway router redundancy, 523
    - GLBP, 547
    - HSRP, 527–542
    - IRDP, 525
    - proxy ARP, 524
    - static default gateway configuration, 526
    - VRRP, 543–546
  - designing
    - case study, 69–70
    - Cisco Catalyst switches and data-link technologies, 55
    - large campus networks, 60–63
    - medium-sized campus networks, 58–59
    - selecting Layer 2 or Layer 3 switches, 56
    - Server Farm module, 63–66
    - small campus networks, 57
  - DHCP snooping, 314
  - Enterprise Composite Network Model, 12, 17
    - Enterprise Campus, 21
    - Enterprise Edge, 19, 26–31
    - overview, 18
    - Service Provider Edge, 19, 31–33
    - submodules, 22–24
  - Enterprise Edge, 68
  - EtherChannel, 287
  - introduction, 3
  - IP multicast protocol, 484–485
    - IGMP, 473–478
    - PIM, 466–469, 472–473
  - Layer 2
    - design properties, 9
    - switching, 6
  - Layer 3, 10, 14
    - ARP, 11
    - packet rewriting, 10
    - switching, 7
  - Layer 4
    - performance, 8
    - terminology, 7
  - Layer 7 switching, 8
  - multicast
    - group membership, 456
    - IP address structure, 457–459
    - overview, 453–455
    - RPF, 460–461
  - multicast forwarding tree, 463
    - shared trees, 464
    - source trees, 463
  - multicast hardware-based switching methods, 479
    - CEF-based MMLS, 480
    - MFIB, 481
    - MMLS, 480
  - OSI reference model, 5
  - QoS, 388–389, 436
    - assured forwarding, 399–400
    - Building Access submodule, 437
    - Building Distribution submodule, 438
    - Campus Backbone, 439
    - Catalyst fundamentals, 401–415
    - congestion avoidance, 427–430
    - congestion management, 420–426
    - DiffServ model, 396–398
    - expedited forwarding, 400
    - IntServ model, 395
    - jitter, 393
    - latency, 392
    - need for, 390–391
    - packet loss, 394
    - service models, 395
    - traffic conditioning, 416–419
  - routed ports, 344
  - trunking, 149
- multilayer switching. *See* MLS
- multipath forwarding, 652
- Multiple Default Gateways (MDGs), 303–304
- Multiple Spanning Tree. *See* MST, 224

# N

- NAM (Network Analysis Module), 727
  - performance monitoring in Catalyst 6500 switches, 727
    - autostart collections, 732
    - configuration, 728
    - data sources, 730
    - NDE as data source, 732
    - troubleshooting common problems, 735
    - verifying configuration, 734
  - versions, 727
  - naming images (Cisco IOS), 97–98
- NAT (network address translation), 4
- NBAR, 410–412
- NDE (NetFlow Data Export), 730
  - as a traffic source for NAM, 731
  - enabling, 732
- network address translation (NAT), 4
- Network Analysis Module. *See* NAM
- Network Design Hierarchical Model layers, 17
- Network Management Processor (NMP), 616
- Network Management submodule, 23–25
- Network Time Protocol (NTP), 7
- networks, 224, 484
  - bandwidth provisioning, 571
  - designing IP telephony systems, 567–574
  - enhancing performance
    - critical success tasks, 704
    - monitoring CPU interface of switches with SPAN, 711–712
    - SPAN, 705–708
    - VSPAN, 707, 710
  - Ethernet (metro), 54
  - high availability, 503–504, 507
  - management, considerations for IP telephony solutions, 573
  - monitoring performance
    - RSPAN, 714–718
    - VACL with the capture option, 721–722
  - port security, 295
    - blocking unicast flooding on desired ports, 302
    - restricting traffic based on host MAC addresses, 300–301
    - traffic based on host MAC addresses, 296–299
  - security
    - ACLs, 601
    - network access (802.1X), 598–600
    - private VLANs, 604
    - QoS, 605
  - storage networking
    - campus network integration, 647
    - Cisco SN 542x iSCSI routers, 654–655
    - Cisco storage solutions, 648–652
    - FCIP, 646
    - Fibre Channel, 636–641
    - iSCSI, 642
    - overview, 634–635
  - VLANs, 128
    - configuring, 133–137, 147
    - deleting, 136
    - dynamic, 131
    - implementing in campus networks, 128–129
    - ranges, 132
    - ranges and mappings, 156
    - service provider–managed VLAN services, 157
    - static, 131
    - troubleshooting, 140–145
    - trunking, 148–155
      - trunking configuration, 159–163
      - trunking modes and methods, 157–158
      - trunking troubleshooting, 163
      - verifying configuration, 138–139
- NLPs (normal link pulses), 742
- NMP (Network Management Processor), 616
- no monitor session command, 716
- no switchport command, 289
- no switchport interface command, 344
- node World Wide name (nWWn), 638
- nonlinearities, 681
- non-RPF multicast traffic, 461
- normal link pulses (NLPs), 742
- NTP (Network Time Protocol), 7
- NTP settings (Cisco Catalyst switches), 86–88
- null adjacency, 379
- nWWn (node World Wide name), 638

## O

- OADMs (optical add/drop multiplexers), 678–679
- OIR (Online Insertion and Removal) of standby Supervisor Engines, 513
- ONS, 662
- Open Shortest Path First (OSPF), 62
- optical add/drop multiplexers (OADMs), 678
- optical platforms (Cisco metro solutions), 662
- OS
  - Cisco CatOS compared to Cisco IOS (Native Mode), 80
  - Hybrid OS, 80
- OSI reference model, 5
- OSPF (Open Shortest Path First), 62

## P

- packets
  - loss, 101, 394
  - rewriting, 11
  - VoIP, 571
- PAgP modes, 284
- passwords, 89, 586
- PBR (policy-based routing), 412
- PDUs (protocol data units), 8
- Per VLAN Spanning Tree Plus. *See* PVST+
- performance
  - enhancing
    - critical success tasks, 704
    - SPAN, 705–708, 711–712
    - VSPAN, 707, 710
  - Layer 4 switching, 8
- performance monitoring, NAM (Catalyst 6500 switches), 727
  - autostart collections, 732
  - configuration, 728
  - data sources, 730
  - NDE as data source, 732
  - troubleshooting common problems, 735
  - verifying configuration, 734
- permanent filters, 301
- PFC (Policy Feature Card), 616
- PIM, 466
  - automating distribution of RP, 469
  - dense mode, 467
  - PIM sparse-dense mode, 469
  - PIM-SM, 468
    - version comparison and compatibility, 472–473
- PIM sparse-dense mode, 469
- PIM-DM (dense mode), 467
- PIM-SM (sparse mode), 468
- plain old telephone service (POTS), 54
- PMD (polarization mode dispersion), 680
- point-to-point topology, 639
- polarization mode dispersion (PMD), 680
- policing, 417
  - burst size, 418
  - configuring, 419
- policy-based routing (PBR), 412
- Policy Feature Card (PFC), 616
- PortFast, 246
  - BPDU filtering, 257
  - configuration errors, 268
  - configuring, 248
- ports
  - channeling, 652
  - checking status, 272
  - configuring cost, 210
  - EtherChannel, 286
  - Fibre Channel, 639
  - Root Guard, 258–260
  - roles (RSTP), 218
  - routed, 344
  - security, 295
    - blocking unicast flooding on desired ports, 302
    - restricting traffic based on host MAC addresses, 300–301
    - traffic based on host MAC addresses, 296–299
    - spanning-tree port states, 196
- POTS (plain old telephone service), 54
- pound sign (#) character, 102
- power (loss of), 572
- power supplies, redundancy, 521–522
- preventing bridging loops, 190
- priority queuing, 425
- private VLANs, 604
  - configuring, 147
  - troubleshooting, 142–145
- protocol data units (PDUs), 8

protocols

- Layer 2
  - CDP, 293, 294
  - multicast, 481–484
- MST, 232
- storage networking
  - FCIP, 646
  - Fibre Channel, 636–641
  - iSCSI, 642
- STP, 187
- trunking, 150
  - IEEE 802.1Q, 152–155
  - ISL, 150–152
  - VTP, 163–173
- UDLD, 319
- proxy ARP, 524
- pruning, 167
- PSTN module, 32
- punt adjacency, 379
- pVLANs
  - configuring, 147
  - port structure, 143
  - troubleshooting, 142–145
- PVST+ (Per VLAN Spanning Tree Plus), 205
  - configuring
    - port cost, 210
    - root bridges, 209
  - MAC address allocation and reduction, 206
  - MST, 225

## Q

- Q-in-Q Catalyst configuration, 689
- Q-in-Q STP, 687
- Q-in-Q tunneling, 684–688
- QoS (quality of service), 4, 388–389, 605
  - Catalyst switches, 401–402
    - classification, 404–412
    - congestion avoidance, 427–430
    - congestion management, 420–426
    - marking, 413–415
    - traffic conditioning, 416–419
  - classification, 567
  - jitter, 393
  - latency, 392
  - marking in Layer 4, 6

- multilayer switched networks, 436
  - Building Access submodule, 437
  - Building Distribution submodule, 438
  - Campus Backbone, 439
- need for, 390–391
- packet loss, 393–394
- service models, 395
  - assured forwarding, 399–400
  - DiffServ model, 396
    - IP precedence bit mappings, 398
    - packet classification, 397
  - expedited forwarding, 400
  - IntServ model, 395
- WANs
  - IP RTP Priority, 432–433
  - link-efficiency mechanisms, 435
  - LLQ, 432
  - WFQ, 431
- QoS ACLs, 601
- quality of service. *See* QoS

## R

- RACLs (router access control lists), 601–602
- RADIUS, 592
- random early detection (RED), 428–429
- ranges (VLANs), 132, 156
- Rapid Spanning Tree Protocol. *See* RSTP
- rapid transition to forwarding, 220–221
- RED (random early detection), 428–429
- redundancy, 504
  - Catalyst 6500 switch SRM, 516
    - configuring, 518
    - displaying status, 519
    - failure scenario, 518
  - default gateway routers, 523
    - GLBP, 547
    - HSRP, 527–542
    - IRDP, 525
    - proxy ARP, 524
    - static default gateway configuration, 526
    - VRRP, 543–546
  - link redundancy, 507
  - redundant power supplies, 521–522
  - redundant Supervisor Engine, uplink modules, 520

redundancy (*continued*)  
  route processor, 510–511  
  RPR+, 512–513  
    configuring, 515  
    switchover, 514  
Redundant Power Systems (RPSs), 523  
redundant Supervisor Engines, 508–510  
  route processor redundancy, 510–511  
  RPR+, 512–515  
redundant switched networks, 506  
Remote Access module, 30  
remote RSPAN, 714–715  
reserved link local addresses, 458  
resiliency (STP), 255  
resource errors, 268  
restricting traffic based on host MAC addresses, 300  
root bridges  
  configuring, 209  
  election, 198  
  planning selection, 198–199  
  selection (sample selection), 201  
Root Guard, 258–259  
  configuration exercise, 277  
  configuring, 260  
  Loop Guard, 264  
root port selection (sample scenario), 202  
route processor redundancy, 510–511  
router access control lists (ACLs), 601  
router on a stick feature, 347–349  
routers  
  BSRs, 471  
  redundancy, 516–519  
routing  
  inter-VLAN routing, 339–341  
    bridge virtual interface, 347  
    IP broadcast forwarding, 352–353  
    multilayer Catalyst switches, 341–344  
    router on a stick, 347–349  
    switch virtual interface, 345–346  
    UDP broadcast forwarding, 353  
    verifying configuration, 350  
  protocols, support for Cisco Catalyst Layer 3 switches, 343  
RPF (Reverse Path Forwarding), 460–461  
RPR+, 512–513  
  configuring, 515, 557–559  
  switchover, 514

RPSs (Redundant Power Systems), 523  
RSPAN  
  configuring, 717–718  
  guidelines and restrictions, 714–715  
  performance monitoring, 714  
  remote, 714–715  
  session support, 721  
RSTP (Rapid Spanning Tree Protocol), 216  
  802.1D compatibility, 223  
  BPDU format, 219  
  port roles, 218  
  rapid transition to forwarding, 220–221  
  topology change mechanism, 222–223

---

## S

SANs, 64, 651  
SCSI (Small Computer System Interface), 634  
SCSI over IP. *See* iSCSI  
secondary VLANs, 142  
Secure-HTTP (S-HTTP), 7  
security  
  AAA  
    accounting, 593, 596–597  
    authentication, 591–593  
    authorization, 592–594  
  ACLs, 601  
  Catalyst switch configurations, 585  
    ACLs, 586–587  
    disabling the integrated HTTP daemon, 589  
    disabling unneeded services, 588  
    passwords, 586  
    physical access, 587  
  IP telephony solutions, 574  
  network access (802.1X), 598–600  
  ports, 295  
    blocking unicast flooding on desired ports, 302  
    restricting traffic based on host MAC addresses, 300–301  
    traffic based on host MAC addresses, 296–299  
  private VLANs, 604  
  QoS, 605  
  SNMP, 590  
  STP, 590



- system logging, 590
- system warning banners, 588
- Server Farm access layer, 65–67
- Server Farm distribution layer, 65
- Server Farm module, 63
  - infrastructure architecture, 65–66
  - SANs, 64
  - switches, 64
- Server Farm submodule, 23–25
- servers (VTP), 172
- Service Provider Edge, 31
  - ISP module, 32
  - PSTN module, 32
  - sample implementation, 33
- service provider–managed VLAN services, 157
- set boot system flash command, 100
- shaped round robin (SRR), 425
- shaping, 416
- Shared STP (SSTP), 208
- shared trees, 464
- show adjacency command, 379
- show adjacency detail command, 379
- show command, 105
- show current command, 231
- show interfaces command, 139
- show ip cef command, 376
- show ip cef detail command, 376
- show ip mroute command, 489
- show ip pim interface command, 492
- show ip pim interface count command, 493
- show mac address-table interface command, 139
- show pending command, 231
- show processes cpu command, 272
- show running-config command, 139
- show spanning-tree command, 212
- show vlan command, 138
- show VTP domain command, 174
- show vtp status command, 174
- S-HTTP (Secure-HTTP), 7
- Single Router Mode (SRM), 516
  - configuring, 518
  - displaying status, 519
  - failure scenario, 518
- size (Cisco IFS), 97
- SLB (Cisco IOS Server Load Balancing), 550
  - configuring
    - the server farm with real servers, 552–553
    - virtual servers, 554–555
  - modes of operation, 552
- slow throughput, troubleshooting, 141
- small campus networks, 57
- Small Computer System Interface (SCSI), 634
- SMI (Standard Multilayer Image), 625
- SNAP (Subnetwork Access Protocol), 293
- SNMP, security, 590
- snooping (DHCP), 313–314
- software, updating versions, 99–102
- software-switching, 4
- SONET, 670–672
- source trees, 463
- Source-Specific Multicast (SSM), 458
- SPAN (Switched Port Analyzer), 651, 705–706
  - configuring, 708
  - guidelines and restrictions, 706
  - monitoring CPU interface of switches, 711–712
  - session support, 721
  - troubleshooting Catalyst 6500 switches, 713
- spanning tree protocol. *See* STP
- Spanning-Tree Algorithm (STA), 190
- spanning-tree path cost, 191
- spanning-tree port states, 194–196
- sparse-dense mode with BSR, 487
- SRM (Single Router Mode), 516
  - configuring, 518
  - displaying status, 519
  - failure scenario, 518
- SRR (shaped round robin), 425, 664
- SSH (Secure Shell), 89–90
  - accessing switches during an upgrade, 100
  - configuring switches for, 91
  - establishing IP connectivity, 109
  - software support, 90
- SSM (Source-Specific Multicast), 458
- SSTP (Shared STP), 208
- STA (Spanning-Tree Algorithm), 190
- Standard Multilayer Image (SMI), 625
- static default gateway configuration, 526
- static filters, 301
- static VLANs, 131
- steady state STP, 321
- storage (enterprise networks), 64

- storage networking
  - campus network integration, 647
  - Cisco storage solution, 648
    - Cisco MDS 9000 multilayer switches, 649–652
    - Cisco SN 542x iSCSI routers, 654–655
  - overview, 634–635
  - protocols
    - FCIP, 646
    - Fibre Channel, 636–641
    - iSCSI, 642
- STP (spanning tree protocol), 187, 191
  - BackboneFast, 250
    - configuring, 254
    - link failures, 252
  - BPDU s, 192
    - frame format, 193
    - timers, 194
  - bridge IDs, 191
  - configuring, 211–213, 236
  - enhancements, 246
  - events debug, 271
  - IEEE 802.1Q trunks, 207
  - Multiple Spanning Tree (MST), 224–226
    - 802.1Q, 225
    - configuring, 230–233
    - IST instances, 228
    - MST instances, 229
    - PVST+, 225
    - regions, 227
  - operation overview, 197
    - planning root bridge selection, 198–199
    - root bridge election, 198
    - selection of root and designated ports, 200
  - overview, 187
  - port path cost, 210
  - PortFast, 246–248
  - PVST+. *See* PVST+
  - Q-in-Q STP, 687
  - resiliency, 255
    - BPDU filtering, 256
    - BPDU Guard, 255
    - BPDU skewing, 257–258
    - Root Guard, 258–260
  - RSTP, 216
    - BPDU format, 219
    - port roles, 218
    - rapid transition to forwarding, 220–221
    - topology change mechanism, 222–223
  - sample election process scenario, 201–202
  - security, 590
  - spanning-tree path cost, 191
  - spanning-tree port states, 194–196
  - topology changes, 202–204
  - troubleshooting, 266
    - duplex mismatch, 266
    - frame corruption, 268
    - inappropriate STP diameter parameter tuning, 269
    - methodology, 270–272
    - PortFast configuration errors, 268
    - resource errors, 268
    - unidirectional link failures, 267
  - UplinkFast, 248–249
- STS-1 (synchronous transport signal-level 1), 671
- subnets, routing packets between, 7
- Subnetwork Access Protocol (SNAP), 293
- Supervisor Engine I, 616
- Supervisor Engine II, 617
- Supervisor Engine 720, 618
- Supervisor Engines
  - OIR, 513
  - redundancy, 508–510
    - route processor redundancy, 510–512
  - RPF+, 515
  - RPR+, 513–514
  - uplink modules, 520
- suppression
  - broadcast, 311–312
  - multicast, 312
- Switched Fabric topology (Fibre Channel), 640
- Switched Port Analyzer. *See* SPAN
- switches
  - Cisco Catalyst switches
    - Catalyst 2950, 627–628
    - Catalyst 3550, 625–626
    - Catalyst 3750, 623–624
    - Catalyst 4500, 620–621
    - Catalyst 6500, 613–618
    - clock and NTP settings, 86–88

- configuration of management parameters, 83–85
- DNS, 92
- managing configurations, 93
- system switches, 92
- Telnet and SSH, 89–91
- troubleshooting, 104–109
- updating software versions, 99–102
- Cisco CatOS, 86
  - displaying STP information, 214
  - MDGs, 303–304
  - passwords, 89
- Cisco IOS
  - DNS, 92
  - NTP settings, 88
- Cisco MDS 9000 multilayer switches, 649
- configuring for SSH, 91
- converting to Cisco IOS (Native Mode) from Cisco CatOS, 103
- high availability, 503–507
- legacy Layer 2 switches, 6
- multilayer, 12
- Root Guard, 259
- Server Farm module, 64
- VTP-transparent switches, 166
- switching
  - distributed, 366
  - hardware-switching, 4
  - Layer 2, 6, 9
  - Layer 3, 7, 10, 14
    - ARP, 11
    - packet rewriting, 10
  - Layer 4
    - performance, 8
    - terminology, 7
  - Layer 7, 8
  - software-switching, 4
  - table architectures
    - CAM tables, 368
    - TCAM, 369–371
  - terminology, 5
- switchport command, 289, 706
- synchronous data, 660
- synchronous transport signal-level 1 (STS-1), 671
- system logging, 92, 590
- system names, configuring meaningful names, 84

## T

- TACACS+, 592
- tag stacking (Q-in-Q tunneling), 684–687
- tail drop, 427
- TC (Topology Change) bit set, 203
- TCAM (ternary content addressable memory), 4
- TCN, 203
- Technology Ability field, 743
- Telnet, 89
  - accessing switches during an upgrade, 100
  - disabling access, 116
  - establishing IP connectivity, 109
- terminology
  - Layer 4 switching, 7
  - switching, 5
- ternary content addressable memory (TCAM), 4
- TFTP, packet loss, 101
- throughput, troubleshooting slow, 141
- time stamping, 86
- TLS (transparent LAN service), 668
- topologies, 569
  - Fibre Channel, 639–640
  - metro Ethernet, 55
  - multiple Ethernet technologies, 46
- topology change mechanism (RSTP), 222–223
- traffic, 394
  - conditioning
    - policing, 417–419
    - shaping, 416
  - congestion avoidance
    - tail drop, 427
    - WRED, 428–430
  - congestion management, 420
    - custom queuing, 426
    - FIFO queuing, 421
    - priority queuing, 425
    - WRR, 422–424
  - DHCP snooping, 314
  - load balancing (EtherChannel), 290–292
  - monitoring, 489–493
    - restricting based on host MAC addresses, 300
- TrafficDirector application, 728
- transparent LAN service (TLS), 668

## troubleshooting

- Catalyst switches, 104
  - Catalyst 6500 switches using SPAN, 713
  - configuration commands, 106
  - connecting to switches via console ports, 108
  - debug commands, impact and use, 106
  - IP connectivity, 109
  - show and debug commands, 105
- CEF-based MLS
  - configuration exercise, 382–386
  - debugging CEF on Layer 3 Engine, 380
  - methodology, 381
- forwarding loops and black holes, 261, 264
- L2 traceroute command
  - availability on Catalyst switches, 724
  - output from Cisco IOS-based switches, 725
- NAM, 735
- preventing bridging loops, 190
- STP, 266
  - duplex mismatch, 266
  - frame corruption, 268
  - inappropriate STP diameter parameter tuning, 269
  - methodology, 270–272
  - PortFast configuration errors, 268
  - resource errors, 268
  - unidirectional link failures, 267
- trunking, 163
- VLANs, 140
  - communication issues, 141
  - private VLANs, 142–145
  - slow throughput, 141
- VTP, 175
- trunking, 651
  - limiting connections, 590
  - protocols, 163–173
  - troubleshooting, 163
  - VLANs, 148
    - configuration, 159–161
    - IEEE 802.1Q, 152–155
    - ISL, 150–152
    - modes and methods, 157–158
    - multilayer switched networks, 149
    - protocols, 150
    - verifying configurations, 161, 162, 163
- trusting DSCP, 405

## tunneling

- IEEE 802.1Q-in-Q tunneling, 157
- metro Ethernet, 681
  - 802.1Q packet tagging, 683
  - no tunneling, 682
- Q-in-Q Catalyst configuration, 689
- tag stacking (Q-in-Q tunneling), 684–687

---

**U**

- UDLD (Unidirectional Link Detection) protocol, 245, 319–322
  - case study, 325
  - configuring, 322
- UDP broadcast forwarding, 353
- unicast flooding, blocking on desired ports, 302
- unicast suppression, 312
- unidirectional links
  - failures, 267
  - Loop Guard, 263
- updating software versions on Catalyst switches, 99–102
- UplinkFast, 248
  - configuration exercise, 277
  - configuring, 249
- UTP (unshielded twisted-pair), 47

---

**V**

- VACLs (VLAN access control lists), 601–602
  - capture option, monitoring performance, 721–722
  - configuration exercise, 607, 610
- verifying
  - CEF-based MLS, 375
  - IP multicast traffic, 489–493
  - STP configuration, 211–213
  - VLAN configuration, 138–139
  - VTP configuration, 174
- Virtual Private Networks, 3
- Virtual Router Redundancy Protocol. *See* VRRP
- Virtual Switched Port Analyzer. *See* VSPAN
- VLAN access control lists (VACLs), 601
- VLAN management policy servers (VMPSs), 131

- VLANs (Virtual LANs), 6, 125, 128
    - configuring, 133–137
      - private VLANs, 147
      - verifying configuration, 138–139
    - deleting, 136
    - dynamic, 131
    - implementing in campus networks, 128–129
    - inter-VLAN routing, 339–341
      - IP broadcast forwarding, 352–353
      - multilayer Catalyst switches, 341–344
      - router on a stick, 347–349
      - switch virtual interface, 345–347
      - UDP broadcast forwarding, 353
      - verifying configuration, 350
    - load balancing, 224
    - private VLANs as a security feature, 604
    - propagated, 590
    - PVST+, 205
    - ranges and mappings, 132, 156
    - service provider–managed VLAN services, 157
    - static, 131
    - troubleshooting, 140
      - communication issues, 141
      - private VLANs, 142–145
      - slow throughput, 141
    - trunking, 148
      - configuration, 159–161
      - IEEE 802.1Q, 152–155
      - ISL, 150–152
      - modes and methods, 157–158
      - multilayer switched networks, 149
      - protocols, 150
      - troubleshooting, 163
      - verifying configurations, 161–163
    - voice, 569
  - VMPSs (VLAN management policy servers), 131
  - voice (auxiliary) VLANs, 569–570
    - configuration exercise, 577–581
  - VoIP
    - IP telephony QoS features, 568
    - packets, 571
  - VPN module, 30
  - VPNs (Virtual Private Networks), 3
  - VRRP (Virtual Router Redundancy Protocol), 7, 543–545
    - configuring, 545–546
    - operation details, 545
  - VSANs, 650, 653
  - VSPAN (Virtual Switched Port Analyzer), 705, 710
    - configuration, 710
    - guidelines and restrictions, 707
  - VTP, 163–164
    - advertisements, 166
    - authentication, 171
    - configuring, 171–173
    - modes of operation, 165
    - pruning, 167
    - troubleshooting, 175
    - versions, 168–170
  - VTP-transparent switches, 166
  - VTYs, securing access to, 587
- ## W–Z
- 
- WAN module, 30
  - WANs, QoS
    - IP RTP Priority, 433
    - link-efficiency mechanisms, 435
    - LLQ, 432
    - WFQ, 431
  - warning banners, 588
  - wavelengths (electromagnetic spectrum), 675
  - WDM (Wave Division Multiplexing), 673–675
  - WFQ (weighted fair queuing), 431
  - WRED (weighted random early detection), 428–431
  - write erase command, 94
  - WRR (weighted round robin), 422–425
  - WS-SVC-NAM-1, 727
  - WS-SVC-NAM-2, 727
  - WS-X6380-NAM, 727
  - zoning, 653