



## Numerics

---

802.11 networks, QoS, 276

## A

---

ABR (available bit rate), 294

Abstract Syntax Notation One (ASN.1), 147

access. *See also* security

storage-area networks, 269

transactions, 232

access control lists (ACLs), 81, 95

accountability, delivery of service, 133

accounting, 143

accounts, transactions, 230

acknowledgments (ACKs), 60, 254

ACLs (access control lists), 81, 95

active agents, 192

Address Resolution Protocol (ARP), 236

administration. *See also* management

APM, 5

benefits of, 16

end-to-end systems, 7

isolation, 7–8

lifecycles, 9

monitoring SLAs, 9

overview of, 6

sharing information, 8

CRM systems, 74

oversight, 26

QPM, 109

SLAs, 67–68

system, 13

TCO, 25

tools, 79

configuration, 83–84

DiffServ, 101–102

FIFO, 92–93

IntServ, 98–99

MPLS, 85–88

networks resource allocation, 80–81

non-work-conserving queuing, 96–98

provisioning, 83–84

queuing, 91–92

RSVP, 99–101

TE, 89–90

traffic-handling mechanisms, 81–83

work-conserving queuing, 93–96

agents, 146–147, 192

capture, 234

embedded, 72

enabling, 148

profiling, 39

SAA, 72, 158, 199

agreements (SLAs)

Cisco NetFlow, 73–74

defining, 65–66

delivery, 66–67

management, 67–68

monitoring, 76–77

profiling, 74–76

requirements, 68–73

alarms, 142

algorithms

queuing, 82, 91. *See also* queuing

queue-servicing, 81

alignment, business/technical methodologies, 30–32

allocation

ports, 243

QoS, 297

resources, 80–81, 108–109

amalgamation, 62

analysis

business-impact, 124

capacity planning, 183–186

failure, 181

modeling, 51

predictive performance, 15

queries, 257–258

root-cause, 142, 150

SLA compliance, 180

systems, 77

TCO, 25–27

thresholds, 49

triggers, 14

virtual environments, 176

analyzers

data, 204

network, 234

profiling, 38

- any-to-any communication, 270
- APIs (application programming interfaces), 190
- APMs (application performance management), 5, 127
  - benefits of, 16
  - end-to-end systems, 7
  - isolation, 7–8
  - lifecycles, 9
  - monitoring SLAs, 9
  - overview of, 6
  - services, 132–134
  - sharing information, 8
- application programming interfaces (APIs), 190
- application-aware probes, 158
- application-development teams, 13
- applications, 13, 29
  - analyzers, 38
  - architecture, 217–219, 256
  - assessment, 14
  - bandwidth-bounded, 42, 59–61
  - baselining, 48
  - business-critical, 29
  - capture points, 55
  - characterizing, 45
  - classification, 40–42, 289–290
  - coexisting, 28
  - data flow, 49
  - delivery, 11, 61–63
  - deployment, 50
  - end-to-end models, 284–297
  - interactive, 217
  - latency-bounded, 40, 58–59
  - mission-critical, 291
  - monitoring, 198, 205
  - probes, 72
  - status, 43
  - storage solutions, 272
  - threads, 40
  - turns, 37, 243
  - web-based, 291
  - workloads, 10
- architecture
  - applications, 217–219, 256
  - delivery requirements, 221–222
  - hub-and-spoke, 135
  - policy management, 109–112
- ARP (Address Resolution Protocol), 236
- ASN.1 (Abstract Syntax Notation One), 147

- assessment
  - applications, 14
  - demarcation points, 128–130
  - new application impact, 52
- assignment
  - associated applications, 24
  - demarcation points, 128–130
  - QoS, 134–137
- ATM (Asynchronous Transfer Mode), 86
- authentication, 110
- authorized transactions, 230
- automation
  - capacity planning, 185
  - polling, 146
- availability, 157
  - defining, 65–66
  - delivery, 66–67
- available bit rate (ABR), 294
- average bytes per frame, viewing, 241

---

## B

---

- background
  - data, 177
  - traffic, 118, 177. *See also* traffic
- backplane utilization, 160
- balancing metrics, 154
- bandwidth, 42
  - application consumption of, 7
  - increasing, 61
  - optimizing, 59–61
  - priority, 29
  - profiling, 36
  - windows, 254
- base networks, building, 118
- base transactions, defining, 43, 230. *See also* transactions
- baselining, 47–50, 155
  - businesses, 122
  - collection, 185
  - environments, 43
  - establishing, 287
  - infrastructure, 107–108
  - performance, 173–174
  - technical baselines, 121
- BC (committed burst), 135
- Be (excess burst), 135

- benchmarking, 121
  - benefits of
    - APM, 16
    - TCO, 27
  - Berkeley Standard Distribution (BSD), 204
  - BGP (Border Gateway Protocol), 83
  - big bang deployments, 119–120
  - big-picture view, 216
  - bits, DE, 135
  - Border Gateway Protocol (BGP), 83
  - bottlenecks, identifying, 289
  - boundaries, defining transactions, 248
  - BPDU (bridge protocol data unit), 204
  - branches, transactions, 232
  - bridge protocol data unit (BPDU), 204
  - broadcast traffic (etherStatsBroadcastPkts), 161
  - BSD (Berkeley Standard Distribution), 204
  - BSM (business service management), 133
  - building
    - baseline environments, 43
    - baselines, 48
  - business applications, 7
  - business baselines, 122
  - business criteria category (SLAs), 68–69
  - business management, 150
  - business objectives, 132–134
  - business requirements, 127
  - business service management (BSM), 133
  - business transactions
    - optimizing, 253–259
    - profiling, 229–246
  - business-critical applications
    - defining, 22–24
    - priority, 29–30
    - requirements, 27–29
    - TCO, 25–27
    - technical alignment, 30–32
  - business-impact analysis, 124
  - bytes
    - transfers, 245
    - viewing, 241
  - TCO, 25
  - TE, 90
  - validating, 179
  - capacity
    - increasing, 61
    - planning, 66, 174, 183–186
  - capturing
    - capture points, 55
    - data, 54
    - traces, 218–219, 234–235
    - traffic, 218
    - transactions, 236
  - CAR (committed access rate), 81
  - case studies
    - QoS, 259–265
    - SLAs, 246–253
    - transactions
      - optimizing, 253–259
      - profiling, 229–246
  - categorizing business transactions, 230
  - CBR (constant bit rate), 294
  - CBWFQ (class-based weighted fair queuing), 81, 95
  - CDP (Cisco Discovery Protocol), 149
  - Cell Loss Priority (CLP), 135
  - cell switching, ATM, 86
  - central site (hub), 135
  - channel service unit/data service unit (CSU/DSU), 295
  - characterizing applications, 45
  - CIFS (Common Internet File System), 271
  - CIR (committed information rate), 135
  - Cisco Discovery Protocol (CDP), 149
  - Cisco IOS
    - show commands, 201
    - traffic-conditioning mechanisms, 136
  - Cisco NetFlow, 31, 73–74
  - Cisco Networking Service (CNS), 148, 213
  - Cisco Tag Switching implementations, 86
  - Cisco Works, 31
  - class-based weighted fair queuing (CBWFQ), 81, 95
  - classification, 81, 84, 135–136
    - applications, 40–42, 289–290
    - devices, 112
    - management systems, 141–151
  - clean transactions, 235
  - cleaning traces, 236
  - CLEC (competitive local exchange carrier), 291
- 
- C**
- calculations
    - measurements, 72
    - SPF, 90

- CLI (command-line interface), 109, 147, 199–204
- client, network, and server (CNS), 148, 213
- clients
  - overloading, 220
  - processing time, 252
- CLP (Cell Loss Priority), 135
- CNS (Cisco Networking Service), 148, 213
- CNS (client, network, and server), 148, 213
- coexisting applications, 28
- collection
  - baselining, 185
  - key date points, 70
  - methods, 72
  - metrics, 157–165
  - points, 246–253
- collisions, Ethernet, 161
- command-line interface (CLI), 109, 147
- commands
  - debug, 202–203
  - frame-relay ip rtp header-compression, 263
  - get, 245
  - ip rtp compression-connections, 264
  - ip rtp header-compression, 263
  - show, 201
  - show processes cpu, 204
  - snmpwalk, 49
- committed access rate (CAR), 81
- committed burst (Bc), 135
- committed information rate (CIR), 135
- Common Internet File System (CIFS), 271
- Common Open Policy Service (COPS), 110
- common sense, 179
- communication
  - deployment, 124
  - directory systems, 110
  - SLAs, 67
- comparing trace files, 237–246
- competitive local exchange carrier (CLEC), 291
- complex transactions, 230
- compliance, SLA analysis of, 180
- computing resources, forecasting, 10
- Compuware Application Vantage, 234
- configuration
  - baselining, 48
  - CLI, 109
  - management, 143
  - metrics, 250
  - QoS, 109, 297
  - RSPAN, 164
  - SPAN, 163
  - storage-area networks, 269–276
  - TCO, 25–27
  - thresholds, 49
  - validation, 180
- conflict-prevention tools, SLAs, 67
- congestion, troubleshooting, 176
- congestion-avoidance (WRED) procedures, 135
- connections
  - any-to-any communication, 270
  - bandwidth-bounded applications, 42
  - critical switched ports, 71
  - latency, 35
  - WLANs, 276–284
- consistency
  - APM, 6
  - transaction captures, 236
- constant bit rate (CBR), 294
- constraint-based routing, 90
- consumption, monitoring, 10
- contingency plans, deployment, 121–124
- control consoles, reporting to, 192
- conversation, 38
  - capture points, 235
  - paths, 157, 247
- conversational maps, 240
- COPS (Common Open Policy Service), 110
- core devices, QoS, 113
- core networks, CPE measurements, 72
- correlation of events, 142
- CPE (customer premises equipment), 72, 295
- CQ (custom queuing), 81, 94
- credit, SLAs, 66
- critical switched port connections, 71
- CRM (customer relationship management), 74
- cRTP (Real-Time Transport Protocol header compression), 263
- CSU/DSU (channel service unit/data service unit), 295
- custom queuing (CQ), 81, 94
- customer premises equipment (CPE), 72, 295
- customer relationship management (CRM), 74
- customer service, SLAs, 66

## D

- data analyzers, 204
- data collection, 108. *See also* baselining
- data flow, application, 49
- data link connection identifier (DLCI), 88
- Data Link Switching (DLSw), 75
- data transfers, 290
- database administrator (DBA), 211
- database management system (DBMS), 160
- data-collection method, 159
- DBA (database administrator), 211
- DBMS (database management system), 160
- DE (Discard Eligible) bits, 135
- debug commands, 202–203
- defining
  - base transactions, 43, 230
  - business-critical applications, 22–24
  - demarcation points, 130
  - location of metric collection points, 246–248
  - metrics, 153–159
  - routes, 177
  - SLAs, 246–253
  - transactions, 231, 248
- delay
  - calculations, 182
  - CNS reporting, 213
  - distance, 191
  - introduction of, 27
  - measurement of, 108
  - ping, 51
  - processing, 191
  - protocols, 191
  - queuing, 191
  - SLAs, 65
  - transmission, 190
- deleting leading/trailing data, 236
- delivery
  - applications, 11
  - business objectives, 132–134
  - management, 141–151
  - monitoring
    - collecting metrics, 159–165
    - defining metrics, 153–159
    - identifying cycles, 167–168
    - operating multiple systems, 151–153
    - reporting mechanisms, 165–167
    - pyramid model, 139–141
    - responsibilities, 12
    - traffic, 274
    - troubleshooting, 221–222
    - verifying, 61–63
- demarcation points, assigning, 128–130
- dense wavelength-division multiplexing (DWDM), 88
- dependency failures, 220
- deployment
  - application-deployment teams, 13
  - applications, 50, 57
  - baselining, 155
  - big bang, 119–120
  - contingency plans, 121–124
  - domains, 112–113
  - infrastructure, 107–108
  - NetFlow, 165
  - pilot, 113–115
  - policy management architecture, 109–112
  - predictive modeling, 117–119
  - profiling, 43–46
  - QoS resource allocation, 108–109
  - reporting, 124
  - staged, 119–120
  - TCO, 26
  - teams, 13
  - verification, 115–117
  - VoIP, 260
  - WLANs, 281
- deposit systems, 230
- DES (discrete-event simulation), 50, 181
- design
  - baselining, 48
  - CLI, 109
  - management, 143
  - metrics, 250
  - QoS, 109, 297
  - RSPAN, 164
  - SPAN, 163
  - storage-area networks, 269–276
  - TCO, 25–27
  - thresholds, 49
  - validation, 180
  - WLANs, 279
- development of application-development teams, 13

## devices

- capture points, 55
- classification, 112
- configuration, 109
- core, 113
- CPE, 72, 295
- edge, 112
- NAS, 271
- networks, 81
- PEPs, 110
- storage-area networks, 269–276

DHCP (Dynamic Host Configuration Protocol), 84

diagnostics, 142. *See also* troubleshooting

- CLI, 199–204
- GUI, 204–206
- proactive troubleshooting, 175–178
- systems, 77
- tools, 77
- validating changes, 178–180

differentiated services (DiffServ), 88

DiffServ, 101–102

DiffServ codepoint (DSCP), 101

direct costs, TCO, 26

direct sequence spread spectrum (DSSS), 276

directory systems communication, 110

disaster recovery. *See also* troubleshooting

- planning, 123
- tools, 121

Discard Eligible (DE) bits, 135

discovery, protocols, 158

discrete-event simulation (DES), 50, 181

distance delay, 191

distributed weighted random early detection (DWRED), 98

distribution, transactions, 232

division of end-to-end systems, 11

DLCI (data link connection identifier), 88

DLSw (Data Link Switching), 75

documentation, 25–27

domain policies, 112–113

downstream alarm suppression, 142

downtime, 26

dropping, 136

- frames, 251
- schemes, 91
- traffic, 135

DSCP (DiffServ codepoint), 101

DSSS (direct sequence spread spectrum), 276

DWDM (dense wavelength-division multiplexing), 88

DWRED (distributed weighted random early detection), 98

dynamic environments, proactive planning, 174–175

Dynamic Host Configuration Protocol (DHCP), 84

## E

---

edge devices, QoS, 112

edge nodes, 135

efficiency, OSS, 141

EIGRP (Enhanced Interior Gateway Routing Protocol), 83

element management system (EMS), 145

embedded agents, 72

EMS (element management system), 145

emulation, traffic, 287

enabling

- debugging, 203
- technologies, 180–181

endpoints, TE, 89

end-to-end delivery systems

- enabling technologies, 180–181
- planning, 188–194

end-to-end management, 188

end-to-end models, 284–297

end-to-end networks, 134–137

end-to-end QoS, 291

end-to-end systems

- APM, 7
- division of, 11

end-users, 26. *See also* users

engineering, networks, 13

Enhanced Interior Gateway Routing Protocol (EIGRP), 83

enterprise APMs, 9. *See also* APMs

enterprise networks, 293

enterprise operational support system, 141–151

environments

- lab, 54
- production, 54
- testing, 53

- virtual, 50, 117
- VoIP, 259–265
- equivalence, 183
- ERC (error recovery code), 271
- errors, 161. *See also* troubleshooting
- essential applications. *See also* applications
  - defining, 22–24
  - priority, 29–30
  - requirements, 27–29
  - TCO, 25–27
  - technical alignment, 30–32
- Ethernet collisions, 161
- etherStatsTable (polling), 160
- ETSI (European Telecommunications Standards Institute), 315
- evaluation, TCO, 26
- events, 142
- excess burst (Be), 135
- expenses, TCO, 25–27
- explicit traffic, 118
- extensions, TE, 90
- external probes, 72

## F

---

- failures. *See also* troubleshooting
  - analysis, 181
  - TCO, 25
- fault
  - fault-conditions, 219–220
  - management, 143
  - processing, 211
  - solutions, 175. *See also* troubleshooting
- FC (Fibre Channel), 269
- FCP (Fibre Channel Protocol), 271
- FDDI (Fiber Distributed Data Interface), 149
- FEC (forwarding equivalence class), 87
- FHSS (frequency hopping spread spectrum), 276
- Fiber Distributed Data Interface (FDDI), 149
- Fibre Channel (FC), 269
- Fibre Channel Protocol (FCP), 271
- FIFO (first in, first out), 92–93
- files
  - flat, 160
  - NFS, 271
  - trace, 237–246

- first-level help desks, 12
- flat files, 160
- flow
  - application data, 49
  - conversational paths, 247
  - identifying, 81
  - profiling, 38
  - SANs, 273
  - transactions, 241
- flow-based WFQ, 94
- flow-based WRED, 98
- flowcharts
  - pilot deployments, 114
  - SLAs, 223
  - troubleshooting, 178
  - validation, 179
- focus, key areas of business, 23
- forecasting resources, 10
- forwarding, 90, 135
- forwarding equivalence class (FEC), 87
- Frame Relay, 135
- frame-relay ip rtp header-compression
  - command, 263
- frames
  - average bytes per, 241
  - dropped/lost, 251
  - FC, 271
  - latency-bounded applications, 40
  - threads, 40
  - windows, 254
- framework systems, 198. *See also* monitoring
- frequency of transactions, 24, 232
- frequency hopping spread spectrum (FHSS), 276
- functions. *See also* commands
  - business transactions, 229–246, 253–259
  - investigating, 24
  - management systems, 143
  - verification, 116
- future equipment costs, 26

## G

---

- get command, 245
- get process (SNMP), 49
- GET statements, 257



GFR (guaranteed frame rate), 294  
 goals  
   lack of in methodologies, 31  
   performance, 31–32  
   setting, 28  
 guaranteed frame rate (GFR), 294  
 GUI (graphical user interface), 152, 204–206

## H

handing over problems, 289  
 hardware  
   baselining, 48  
   external probes, 72  
 HBA (host bus adapter), 271  
 help desks, 12  
 hierarchies, reporting, 212  
 high utilization, 159  
 hooks, management of, 190  
 host bus adapter (HBA), 271  
 hub-and-spoke architecture, 135  
 hybrid simulation, 181

## I

ICMP (Internet Control Message Protocol), 158, 190  
 idle time, TCO, 26  
 IETF (Internet Engineering Task Force), 86, 303, 315  
 IGPs (interior gateway protocols), 90  
 ILEC (incumbent local exchange carrier), 291  
 impact of business-critical applications, 22  
 impact of new applications, 52  
 implementation. *See also* configuration  
   QoS, 96, 259–265  
   triggers, 13–14  
 increasing  
   capacity, 61  
   performance, 258. *See also* performance  
 incumbent local exchange carrier (ILEC), 291  
 inefficient applications, 220

information technology (IT)  
   management, 211–215  
   organizational charts, 12  
 infrastructure  
   baselining, 107–108  
   planning, 29  
   scaling, 285  
   VoIP, 260  
 installation  
   TCO, 25–27  
   WLANs, 281  
 interaction  
   applications, 217  
   reduction of, 60  
   video/voice, 290  
 interconnection, SANs, 269  
 inter-exchange carrier (IXC), 291  
 interfaces  
   APIs, 190  
   CLI, 109, 147  
   FDDI, 149  
   GUI, 152, 204–206  
   IP tunnel, 90  
 interior gateway protocols (IGPs), 90  
 International Organization for Standardization (ISO), 143  
 International Telecommunication Union (ITU), 315  
 Internet Control Message Protocol (ICMP), 158, 190  
 Internet Engineering Task Force (IETF), 86, 303, 315  
 Internet service providers (ISPs), 89, 291, 294  
 Intserv (integrated services), 98–99  
 intuition, 179  
 IP (Internet Protocol) tunnel interfaces, 90  
 ip rtp compression-connections command, 264  
 ip rtp header-compression command, 263  
 ISO (International Organization for Standardization), 143  
 isolation  
   APM, 7–8  
   events, 142  
   performance, 216. *See also* performance  
 ISPs (Internet service providers), 89, 291, 294  
 IT (information technology)  
   management, 211–215  
   organizational charts, 12  
 ITU (International Telecommunication Union), 315  
 IXC (inter-exchange carrier), 291

## J–L

---

### jitter

- priority, 29
- profiling, 36
- QoS parameters, 108
- SLAs, 65
- VoIP, 261

kbps (kilobits per second), 36

key areas of focus, 23, 29

key data collection points, 70

kilobits per second (kbps), 36

KPIs (key performance indicators), 62, 76

lab environments, 54

label switch router (LSR), 87

label switched path (LSP), 87

label switching, 83–90. *See also* MPLS

### latency

- jitter, 36
- priority, 29
- profiling, 35
- QoS parameters, 108
- traces, 218
- transactions, 236, 251

latency-bounded applications, 40, 58–59

LDAP (Lightweight Directory Access Protocol), 110

leading data, deleting, 236

leaky buckets, 96

levels, baselining, 173–174

LFNs (long fat networks), 275

lifecycles, APM, 9

Lightweight Directory Access Protocol (LDAP), 110

limitations of responsibilities/skills, 130–131

### links

- DLSw, 75
- management, 90
- RF, 280

link-state IGPs, 90

LLQ (low-latency queuing), 95, 262

load thresholds, 250

loading, 23–24

### locations

- capture points, 234
- metric collection points, 246–248

long fat networks (LFNs), 275

long-term monitoring, 218

long-term triggers, 15

### loss

- priority, 29
- QoS parameters, 108
- SLAs, 65
- transaction captures, 236

lost frames, 251

low-latency queuing (LLQ), 95, 262

LSP (label switched path), 87

LSR (label switch router), 87

## M

---

MAC (Media Access Control), 149

maintenance. *See also* troubleshooting

MTTR, 65

TCO, 25–27

### management

- accounting, 143
- APM, 5, 132–134
  - benefits of, 16
  - end-to-end systems, 7
  - isolation, 7–8
  - lifecycles, 9
  - monitoring SLAs, 9
  - overview of, 6
  - sharing information, 8

BSM, 133

business, 150–152

configuration, 143

CRM systems, 74

EMS, 145

end-to-end models, 188, 284–297

events, 142

fault, 143

hooks, 190

IT organizational, 211–215

links, 90

operations, 150

oversight, 26

performance, 144, 154

policies, 109–112

proactive application, 175

pyramid model, 140

QPM, 109, 204, 297

RF links, 280

- security, 145
- service, 150
- SLAs, 67–68
- SLM, 62
- system, 13, 141–151
- TCO, 25
- tools, 79
  - configuration, 83–84
  - DiffServ, 101–102
  - FIFO, 92–93
  - IntServ, 98–99
  - MPLS, 85–88
  - network resource allocation, 80–81
  - non-work-conserving queuing, 96–98
  - provisioning, 83–84
  - queuing, 91–92
  - RSVP, 99–101
  - TE, 89–90
  - traffic-handling mechanisms, 81–83
  - work-conserving queuing, 93–96
- traffic, 285–286
- users, 187
- Management Information Bases (MIBs), 48, 118, 200
- Management Interface Bases (MIBs), 147
- managers (SNMP), 147
- mapping
  - conversational, 240
  - priorities, 185
  - services, 74–76
- markers, 135
- marking, 102, 135–136
- matching demarcation points, 130
- maximum transmission unit (MTU), 263
- mean time to repair (MTTR), 65
- measurements, 159
  - availability, 157
  - bandwidth, 36
  - capacity planning, 184
  - CPE/core networks, 72
  - delay, 108
  - external probes, 72
  - latency, 40
  - methods, 72
  - NetFlow, 165
- Media Access Control (MAC), 149
- merging statistics, 237–246
- messages, debug, 203
- metering, 136
- methodologies
  - business and technical, 30–32
  - profiling, 43–46
  - troubleshooting, 206–211
- methods
  - collection, 72
  - data-collection, 159
  - measurements, 72
  - of deployment, 120
- metrics. *See also* requirements
  - average bytes per frame, 241
  - balancing, 154
  - collecting, 159–165
  - collection points, 246–248
  - defining, 153–159
  - monitoring, 62
  - profiling, 61
  - SLAs, 246–253
    - Cisco NetFlow, 73–74
    - defining, 65–66
    - delivery, 66–67
    - management, 67–68
    - monitoring, 76–77
    - profiling, 68–76
  - tracking, 249–253
- MIBs (Management Information Bases), 48, 118, 200
- MIBs (Management Interface Bases), 147
- milliseconds (ms), 108
- mirroring ports, 163
- mission-critical applications, 291
- mission-critical activities, 7
- models
  - analytical, 51
  - business management, 152
  - delivery responsibilities, 12
  - DES, 51
  - end-to-end, 284–297
  - predictive modeling, 117–119
  - pyramid, 139–141
  - scenario, 183
  - simulation, 45, 52
  - virtual, 178
  - virtual-environment methods, 50
- modification
  - baselining, 48

- CLI, 109
  - management, 143
  - metrics, 250
  - QoS, 109, 297
  - RSPAN, 164
  - SLAs, 259
  - SPAN, 163
  - storage-area networks, 269–276
  - TCO, 25–27
  - thresholds, 49
  - validation, 180
  - monitoring
    - agents, 192
    - APM, 127, 132–134
    - applications, 198, 205
    - average bytes per frame, 241
    - capacity planning, 184
    - delivery
      - classifying management, 141–151
      - collecting metrics, 159–165
      - defining metrics, 153–159
      - identifying cycles, 167–168
      - multiple systems, 151–153
      - pyramid model, 139–141
      - reporting mechanisms, 165–167
    - demarcation points, 128–130
    - end-to-end delivery systems, 192
    - Ethernet collisions, 161
    - long-term, 218
    - metrics, 61–62, 249–253
    - networks, 198
    - period of, 62
    - polling, 162
    - ports, 163
    - predictive modeling, 117–119
    - real-time troubleshooting, 66
    - resource-consumption data, 10
    - SLAs, 9, 66, 76–77
    - toolsets, 217
  - MPLS (Multiprotocol Label Switching), 83–88
  - ms (milliseconds), 108
  - MTTR (mean time to repair), 65
  - MTU (maximum transmission unit), 263
  - multicast traffic (etherStatsMulticastPkts), 161
  - multimedia applications, 217
  - multiple systems, operating, 151–153
  - Multiprotocol Label Switching (MPLS), 83–88
- ## N
- 
- NAS (network-attached storage), 271–272
  - NBAR (network-based application recognition), 81
  - NE (network element), 145
  - near-real-time network monitoring capabilities, 161
  - NetFlow, 73–74, 161, 165
  - network element (NE), 145
  - Network File System (NFS), 149, 271
  - network interface cards (NICs), 76, 281
  - network management systems (NMS), 49, 145
  - Network Node Manager (NNM), 49
  - network operations center (NOC), 154
  - network service providers (NSPs), 291
  - networkability, 15
  - network-attached storage (NAS), 271
  - network-based application recognition (NBAR), 81
  - networks
    - analyzers, 38, 234
    - BSM, 133
    - CNS delay reporting, 213
    - devices, 81
    - engineering, 13
    - enterprise, 293
    - forecasting, 10
    - latency, 35
    - monitoring, 198
    - operations, 13
    - pipes, 159
    - planning, 13
    - resource allocation, 80–81
    - security, 13
    - SLAs
      - Cisco NetFlow, 73–74
      - defining, 65–66
      - delivery, 66–67
      - management, 67–68
      - monitoring, 76–77
      - profiling, 74–76
      - requirements, 68–73
    - SP, 262
    - statistics, 237–246
    - TCO, 25–27
    - transmission paths, 294
    - unified views of, 176
    - VPNs, 65
    - WLANs, 276–284

NFS (Network File System), 149, 271  
 NICs (network interface cards), 76, 281  
 NMS (network management systems), 49, 145  
 NNM (Network Mode Manager), 49  
 NOC (network operations center), 154  
 nodes, 135  
 non-work-conserving queuing mechanisms,  
 96–98  
 notification, single-point-of-failure, 142  
 NSPs (network service providers), 291  
 number of metrics, selecting, 154  
 numbers, ports, 243

## O

object identifier (OID), 48, 147  
 objectives, loading, 23  
 objects, polling, 49  
 OBJECT-TYPE constructs, 148  
 OID (object identifier), 48, 147  
 Open Shortest Path First (OSPF), 83  
 operating costs, TCO, 25  
 operating multiple systems, 151–153  
 operational objectives, 174–175  
 operational support system (OSS), 141–151  
 operational systems, 77  
 operations management, 150. *See also* management  
 OPNET  
 ACE, 234  
 IT Guru, 216  
 optimization  
 architecture, 256  
 bandwidth-bounded applications, 59–61  
 delivery, 221–222  
 end-to-end models, 286  
 latency-bounded applications, 58–59  
 SAN traffic delivery, 274  
 servers, 255  
 TE, 89  
 transactions, 253–259  
 windows, 254  
 organizational charts, IT, 12  
 OSPF (Open Shortest Path First), 83  
 OSS (operational support system), 141–151  
 overloading clients/servers, 220  
 oversight, management, 26

## P

packet-by-packet traffic, 177  
 packets  
 BPDU, 204  
 flow, 38  
 latency, 35  
 loss  
 SLAs, 65  
 transaction captures, 236  
 marking, 102  
 webtraffic, 265  
 parallel fault processing, 212  
 passive agents, 192  
 passive probes, 72  
 paths  
 capture points, 234  
 conversation, 157  
 conversational flows, 247  
 LSP, 87  
 TE, 89–90  
 transmission, 294  
 patterns, traffic, 107–108  
 PDP (policy decision point), 109  
 PDUs (protocol data units), 147  
 peer support, 26  
 penalties, SLAs, 187  
 PEPs (policy enforcement points), 109  
 performance. *See also* optimization  
 APM, 5, 127  
 benefits of, 16  
 end-to-end systems, 7  
 isolation, 7–8  
 lifecycles, 9  
 meeting service needs, 132–134  
 monitoring SLAs, 9  
 overview of, 6  
 sharing information, 8  
 baselining, 173–174  
 demarcation points, 128–130  
 dynamic environments, 174–175  
 end-to-end models, 284–297  
 goals, 31–32  
 increasing, 258  
 KPI, 76  
 management, 144, 154  
 polling, 163

- SLAs, 246–253
  - Cisco NetFlow, 73–74
  - defining, 65–66
  - delivery, 66–67
  - management, 67–68
  - monitoring, 76–77
  - profiling, 74–76
  - requirements, 68–73
- troubleshooting, 142, 180, 216, 221
- permanent virtual circuit (PVC), 261
- phases, capacity planning, 185
- PHB (per-hop behavior), 101
- physical connectivity, transactions, 232
- pilot deployments, 113–115
- ping
  - delay, 51
  - response times, 158
- planning, 13
  - capacity, 66, 174, 183–186
  - deployment, 121–124
  - disaster recovery plans, 123
  - dynamic environments, 174–175
  - end-to-end delivery, 188–194
  - infrastructure, 29
  - networks, 13
  - performance, 173–174
  - pilot deployments, 115
  - proactive troubleshooting, 175–178
    - enabling technologies, 180–181
    - validating changes, 178–180
  - scenario modeling, 181–183
  - SLMs, 186–188
  - systems, 13
- policies, 24
  - architecture management, 109–112
  - domains, 112–113
  - QoS, 109, 297
  - suppression, 142
- policing, 135
- policy decision point (PDP), 109
- policy enforcement points (PEPs), 109
- polling, 146, 161
  - data, 160
  - monitor, 162
  - OIDs, 48
  - performance, 163
  - records, 49
- SNMP, 161
  - threshold, 162
- portfolio transactions, 230
- ports
  - allocation, 243
  - critical switched connections, 71
  - mirroring, 163
  - monitoring, 163
- POST statements, 257
- PQ (priority queuing), 81, 94, 261
- PQCBWFQ (priority queue class-based weighted fair queuing), 95
- predeployment testing, 116. *See also* deployment
- predictability, SLAs, 65
- predicted access points, transactions, 232
- predictive modeling, 117–119
- predictive performance analysis, 15
- priorities, mapping, 185
- prioritization, 184
  - business-critical applications, 29–30
  - CLP, 135
- priority queue class-based weighted fair queuing (PQCBWFQ), 95
- priority queuing (PQ), 81, 94, 261
- priority schemes, 23
- proactive fault processing, 212
- proactive planning
  - capacity planning, 183–186
  - dynamic environments, 174–175
  - end-to-end delivery, 188–194
  - performance, 173–174
  - scenario modeling, 181–183
  - SLMs, 186–188
  - troubleshooting, 175–178
    - enabling technologies, 180–181
    - validating changes, 178–180
- probes
  - application-aware, 158
  - capture, 234
  - external, 72
  - passive, 72
  - profiling, 39
  - software, 72
- processes
  - capture, 234
  - OSS, 141
  - timing of transactions, 24

processing, 190  
 delay, 191  
 faults, 211  
 time, 252

production environments, 54

productivity, TCO, 25

profiling, 24, 35  
 agents, 39  
 analyzers, 38  
 applications, 29, 37, 40  
 bandwidth, 36  
 conversation, 38  
 flow, 38  
 jitter, 36  
 latency, 35  
 methodologies, 43–46  
 metrics, 61  
 probes, 39  
 SAA, 39  
 SLAs, 74–76  
 transactions, 229–246

profits, TCO, 27

projecting future resource needs, 184

propagation, 190

protocol data units (PDUs), 147

protocols, 190  
 analyzers, 38  
 baselining, 107–108  
 delay, 191  
 discovery, 158  
 effect of, 51  
 QoS, 134–137  
 routing, 83  
 SNMP, 49  
 TCP, 37

provisioning network devices, 81

PSTN (Public Switched Telephone Network), 259

purchasing, TCO, 25

PVC (permanent virtual circuit), 261

pyramid model, monitoring delivery, 139–141

configuration, 83–84

core devices, 113

devices, 81

DiffServ, 101–102

edge devices, 112

end-to-end, 291

FIFO, 92–93

implementation, 96

IntServ, 98–99

network resource allocation, 80

policies, 297

provisioning, 83–84

queuing, 91–92

resource allocation, 108–109

RFCs, 303–312

RSVP, 99–101

services, 294

standards  
 ETSI, 316  
 IETF, 315  
 ITU, 315–316

traffic-handling mechanisms, 81–83

troubleshooting tools, 198  
 application monitoring, 198  
 network monitoring, 198

VoIPs, 259–265

WAN, 295

QPM (QoS Policy Manager), 109, 204, 297

quality, APM, 6

quality of service. *See* QoS

quantity of metrics, selecting, 154

queries  
 amount of data transferred, 245  
 analysis, 257–258  
 repeating, 244

queuing, 81, 91–92, 190  
 algorithms, 82  
 business transactions, 230  
 delay, 191  
 FIFO, 92  
 simulators, 182  
 types of, 81

## Q

QoS (quality of service), 35, 84  
 802.11 networks, 276  
 allocation, 297  
 assigning, 134–137

## R

radio frequency (RF), 277, 280

RAID (redundant array of inexpensive disks), 271

random early detection (RED), 81, 98

- RCA (root-cause analysis), 142, 150
  - reallocation, 184
  - Real-Time Transport Protocol header (cRTP), 263
  - real-time troubleshooting, 66
  - records
    - capture time, 236
    - polling, 49
    - transaction time, 239
    - UDP, 165
  - recovery
    - disaster, 121
    - ERC, 271
  - RED (random early detection), 81, 98
  - reduction
    - of data, 59
    - of interactions, 60
    - of window sizes, 60
  - redundancy, 157
  - redundant array of inexpensive disks (RAID), 271
  - relocation of servers, 61
  - re-marking traffic, 135
  - remote monitoring (RMON), 149
  - Remote Switched Port Analyzer (RSPAN), 163
  - repairability of MTTR, 65
  - repeating queries, 244
  - reporting, 165–167
    - CNS delay, 213
    - deployment, 124
    - hierarchies, 212
    - profiling, 46
    - to control consoles, 192
  - Request For Comment (RFC), 303–312
  - requests, VC, 86
  - requirements
    - business, 127
    - business-critical applications, 27–29
    - delivery, 221–222
    - end-to-end delivery systems, 188
    - QoS, 108
    - SLAs, 68–73
  - Resource Reservation Protocol (RSVP), 90
  - resources
    - allocation, 80–81
    - forecasting, 10
    - monitoring, 10
    - QoS allocation, 108–109
    - requirements, 231
    - response times, 51, 157
      - APM, 6
      - business-critical application requirements, 28
      - SLAs
        - defining, 65–66
        - delivery, 66–67
    - responsibilities
      - delivery models, 12
      - limitations of, 130–131
    - results, profiling, 46
    - retransmissions, TCP, 255–256
    - revenue
      - key areas of business focus, 23
      - streams, 24
      - TCO, 25–27
    - reviewing
      - SLAs, 186–188, 222–224
      - traces, 237
    - RF (radio frequency), 277, 280
    - RFC (Request For Comment), 303–312
    - RMON (remote monitoring), 149
    - rollouts, 115, 185
    - root-cause analysis (RCA), 142, 150
    - round-trip time (RTT), 275
    - routers, LSR, 87
    - routes, defining, 177
    - routing
      - constraint-based, 90
      - protocols, 83
      - ns, 90
    - RSVP (Resource Reservation Protocol), 90, 99–101
    - RTT (round-trip time), 275
    - rules
      - capture, 236
      - SLAs, 130
- 
- ## S
- 
- SAA (Service Assurance Agent), 39, 72, 158, 199
  - SAA/RTR (Service Assurance Agent/Response Time Reporter), 205
  - SACK (selective acknowledgement), 276
  - SANs (storage-area networks), 269–276
  - scaling
    - infrastructure, 285
    - TCP windows, 275



- scenario modeling, 181–183
- schemes
  - dropping, 91
  - queuing, 91
- security
  - management, 145
  - networks, 13
- selection of deployments, 119–120
- selective acknowledgment (SACK), 276
- serialization, 190
- server message block (SMB), 76
- servers, 269–276
  - CNS delay reporting, 213
  - conversational maps, 240
  - optimization, 255
  - overloading, 220
  - processing time, 252
  - relocating, 61
- Service Assurance Agent (SAA), 39, 72, 158, 199
- Service Assurance Agent/Response Time Reporter (SAA/RTR), 205
- service level agreements. *See* SLAs
- service level management, 9, 62, 186–188
- service provider (SP) networks, 262
- services, 81
  - APM, 6
  - BSM, 133
  - customer, 66
  - IntServ, 98–99
  - management, 150
  - mapping, 74–76
  - meeting needs of, 132–134
  - NetFlow, 165
  - QoS, 294
  - troubleshooting, 222–224
  - validation, 66
- sessions, RSPAN, 164
- setsockopt, 254
- shaping traffic, 135, 275–276
- sharing information, APM, 8
- show commands, 201
- show processes cpu command, 204
- shortest path first (SPF), 90
- signaled mechanisms, 83
- Simple Network Management Protocol (SNMP), 147
- simple transactions, 230
- simulation
  - DES, 181
  - hybrid, 181
  - models, 45, 52
- simulators, calculations, 182
- single-point-of-failure notification, 142
- single-transaction monetary functions, 231
- site surveys, WLANs, 277–279, 281
- sizes, windows, 60, 254
- skills, limitations of, 130–131
- SLAs (service level agreements), 9, 102, 130
  - Cisco NetFlow, 73–74
  - compliance analysis, 180
  - defining, 65–66, 246–253
  - delivery, 66–67
  - management, 67–68
  - monitoring, 76–77
  - penalties, 187
  - profiling, 74–76
  - requirements, 68–73
  - reviewing, 222–224
- SLM (service level management), 9, 62, 186–188
- slow delivery, TCO, 25
- SMB (server message block), 76
- Sniffer, 234
- SNMP (Simple Network Management Protocol), 147
  - agents, 148
  - data-collection methods, 160
  - get process, 49
  - MIB, 48
  - polling, 161
- snmpwalk tool, 48–49
- soft costs, 26
- software
  - baselining, 48
  - probes, 72
- SP (service provider) networks, 262
- SPAN (Switched Port Analyzer), 163
- specialized support, 12
- SPF (shortest path first), 90
- staged deployments, 119–120
- standards, QoS, 315–316
- statements
  - GET, 257
  - inquiries, 230
  - POST, 257

- statistics
  - error, 161
  - merging, 237–246
  - traffic, 161
  - types of, 51
- status, applications, 43
- storage-area networks (SANs), 269–276
- strategic connection points, demarcation points, 130
- strategies, APM, 10–11
- streaming video/voice, 290
- streams, revenue, 24
- stress, verifying functions under, 116
- sub-branches, transactions, 232
- support
  - demarcation points, 128
  - future services, 185
  - peer, 26
  - specialized, 12
  - TCO, 25
- suppression of events, 142
- Switched Port Analyzer (SPAN), 163
- switched port connections, 71
- switches, LSR, 87
- switching, DLSW, 75
- synthetic transactions, 75
- syslog protocol, 149
- systems, 13
  - administration, 13
  - BSM, 133
  - DBMS, 160
  - design, 25
  - EMS, 145
  - management, 141–151
  - multiple, 151–153
  - NFS, 149
  - NMS, 145
  - polling, 146
  - retransmissions, 255–256
  - SAN, 274
  - turns, 37, 243
  - windows
    - scaling, 275
    - sizing, 254
- TDM (time-division multiplexing), 95
- TE (traffic engineering), 88–90
- teams
  - application-deployment, 13
  - application-development, 13
- technical alignments, 30–32
- technical baselines, 121
- technical criteria category (SLAs), 69–70
- technical requirements, 27
- technologies, enabling, 180–181
- telecommunication costs, 26
- Telnet, 147, 159
- testing. *See also* troubleshooting; verification
  - environments, 53
  - predeployment, 116
- threads, applications, 40
- thresholds, 142
  - analyzing, 49
  - capacity, 185
  - load, 250
  - metrics, 250
  - polling, 162
- time
  - processing, 252
  - RTT, 275
  - transactions, 239
- time-division multiplexing (TDM), 95
- time-sensitive conditions, thresholds, 142
- timing, 24
- token buckets, 96
- tools
  - collection, 249
  - diagnostic, 199
    - CLI, 199–204
    - GUI, 204–206
  - disaster recovery, 121
  - management, 79
    - configuration, 83–84
    - DiffServ, 101–102
    - FIFO, 92–93
    - IntServ, 98–99
    - MPLS, 85–88

---

## T

- tail drop, 82, 97, 135
- targets, transactions, 248
- tasks, 38, 217
- TCO (total cost of ownership), 25–27
- TCP (Transmission Control Protocol)
  - ACKs, 254

- network resource allocation, 80–81
- non-work-conserving queuing, 96–98
- provisioning, 83–84
- queuing, 91–92
- RSVP, 99–101
- TE, 89–90
- traffic-handling mechanisms, 81–83
- work-conserving queuing, 93–96
- pyramid model, 139–141
- snmpwalk, 48–49
- troubleshooting, 198
  - application monitoring, 198
  - network monitoring, 198
- toolsets, monitoring, 217
- top-down (pushed) mechanisms, 83
- topologies, building, 118
- ToS (Type of Service), 101
- total cost of ownership (TCO), 25–27
- total traffic (etherStatsOctets), 161
- traces
  - capturing, 218–219, 234–235
  - files, 237–246
  - reviewing, 237
- tracking
  - metrics, 249–253
  - SLAs, 246–253
- traffic, 118
  - capturing, 218
  - Cisco IO traffic-conditioning mechanisms, 136
  - defining, 177
  - delivery, 274
  - dropping, 135
  - emulation, 287
  - end-to-end models, 284–297
  - jitter, 261
  - network resource allocation, 80
  - packet-by-packet, 177
  - patterns, 107–108
  - QoS, 134–137
  - real-time troubleshooting, 66
  - re-marking, 135
  - RSPAN, 164
  - shaping, 135, 275–276
  - simulation models, 45
  - simulators, 182
  - statistics, 161
  - voice (WLANs), 282
  - webtraffic packets, 265
- traffic engineering (TE), 88–90
- traffic-conditioning implementations, 134
- traffic-handling mechanisms, 81–83
- traffic-shaping mechanisms, 96
- trailing data, deleting, 236
- trances, cleaning, 236
- transactions, 38, 217
  - base, 43
  - capturing, 236
  - defining, 27
  - flow, 241
  - optimizing, 253–259
  - profiling, 229–246
  - synthetic, 75
  - targets, 248
  - timing, 24
- transfers
  - amount of data, 245
  - data, 290
- transmissions
  - delay, 190
  - paths, 294
- traps, 147
- triggers
  - implementation, 13
  - transactions, 250
- troubleshooting, 142
  - delivery, 221–222
  - dependency failures, 220
  - diagnostic tools, 199
    - CLI, 199–204
    - GUI, 204–206
  - disaster recovery, 121
  - end-to-end models, 284–297
  - fault-conditions, 219–220
  - flowcharts, 178
  - IT organizational, 211–215
  - jitter, 261
  - methodologies, 206–211
  - MTTR, 65
  - performance, 180, 216
  - proactive, 175–180
  - real-time, 66
  - services, 222–224
  - tools, 198
  - transactions, 238
  - triggers, 14
  - WLANs, 281
- tuning, 289. *See also* optimization
- tunneling, IP interfaces, 90

- turns
  - application, 37
  - TCP, 243
- Type of Service (ToS), 101
- types
  - of queuing, 81
  - of statistics, 51

## U–V

---

- UBR (unspecified bit rate), 294
- UDP (User Datagram Protocol), 165
- unified views of networks, 176
- UNIX, snmpwalk tool, 48–49
- unspecified bit rate (UBR), 294
- updates, SLAs, 259
- upgrades, 221
- User Datagram Protocol (UDP), 165
- users
  - management, 187
  - TCO, 25
  - transactions, 232
- utilization, 159
- validation
  - configuration, 180
  - services, 66
- values, business, 231
- VC (virtual circuit) requests, 86
- vendor specifications, 179
- variable bit rate (non-real time), 294
- variable bit rate (real time) (VBR), 294
- verification
  - delivery, 61–63
  - deployment, 115–117
  - performance increase, 258
- video
  - interactive, 290
  - streaming, 290
- videoconferencing, 108
- viewing
  - average bytes per frame, 241
  - profiling results, 46

- virtual circuit (VC) requests, 86
- virtual environments
  - creating, 117
  - scenario modeling, 182
  - troubleshooting, 176
  - validating, 179
- virtual models, creating, 178
- virtual private networks (VPNs), 65, 86
- virtual-environment modeling methods, 50
- VLANs (virtual LANs)
  - key data collection points, 71
  - RSPAN, 164
- voice
  - interactive, 290
  - streaming, 290
  - WLANs, 282
- VoIP (Voice over IP), 96, 259–265, 282
- VPNs (virtual private networks), 65, 86

## W–Z

---

- WAN (wide-area network)
  - jitter, 261
  - QoS, 295
  - SP clouds, 262
- web-based applications, 291
- webtraffic packets, 265
- weighted fair queuing (WFQ), 81
- weighted random early detection (WRED), 81, 98, 135, 276
- WFQ (weighted fair queuing), 81
- wide-area network. *See* WAN
- windowing, TCP, 254
- windows
  - sizing, 60, 254
  - TCP, 275
- wireless LANs, 276–284
- wires, reduction of data on, 59
- WLANs (wireless LANs), 276–284
- work-conserving queuing, 93–96
- workloads, applications, 10
- WRED (weighted random early detection), 81, 98, 135, 276