



Symbols

- \$ (dollar sign), scroll line indicator, 325
- > (greater than symbol), CLI prompt, 318

Numerics

- 10BASE2, 57
- 10BASE5, 57
- 10BASE-T, 58
- 100BASE-F, 58
- 100BASE-T, 58

A

- AAA servers, 78
- abbreviating commands, 321
- access layer (hierarchical network model), 50
- access points, 127
- access technologies, 293
 - ATM, 301
 - DSL, 296–299
 - Frame Relay, 299–300
 - HDLC, 294–295
 - ISDN, 295–296
 - PPP, 293–294
 - SONET, 302–303
- access VPNs, 110
- accounting, 79
- acknowledgment process, TCP three-way handshakes, 210
- address classes, 229–231
- address space, calculating, 249–250
- addresses, network layer, 70–71
- adds, moves, and changes, 412–414
- administratively disabling routers, 358
- ADSL (asymmetric DSL), 297
- analog modems, 305
- APNIC (Asia Pacific Network Information Centre), 236
- application layer
 - OSI model, 34
 - TCP/IP protocol stack, 40
- applications. *See also* network applications
 - TCP/IP, 202
- ARIN (American Registry for Internet Numbers), 229, 236
- ARP (Address Resolution Protocol), 258
 - local ARP, 192
 - messages, 193
- ARP cache, 192

- ASICs (application-specific integrated circuits), 66
- assigning
 - IP addresses, 233
 - name to Catalyst switch, 345
 - name to Cisco routers, 352
- asynchronous router connections, 148–149
- ATM (Asynchronous Transfer Mode), 301
 - virtual circuits, 302
- AUIs (attachment unit interfaces), 133, 357
- authentication, 79
- authentication phase (PPP), 294
- authorization, 79
- Autoinstall utility, 401
- autonomous systems, 264
- auxiliary connections, 149

B

- backbone layer, 51
- backoff algorithms, 61
- backplane components, 10
- backup IOS images, 409–411
- balanced hybrid routing protocols, 268–269
 - EIGRP, 271
- bandwidth, 73, 143
 - on Ethernet LANs, 159
 - on point-to-point WAN connections, 288
- base 16 numbering system, 22
 - converting to binary, 23–26
 - converting to decimal, 23–24
- best path selection, 267
- BGP (Border Gateway Protocol), 272
- binary numbering system, 14
 - converting to decimal, 20
 - converting to hexadecimal, 25
- bits, 14–15
 - tokens, 54
- boot field, router configuration, 400
- boot system command, 397
- boot system flash command, 397
- boot system rom command, 397
- boot system tftp command, 397
- booting Cisco IOS devices, 332
 - Catalyst switches, 332–337
 - Cisco routers, 337–343, 395
- bootloader, 396
- bootstrap code, 395, 397
- branch offices, 48
- BRI (Basic Rate Interface), 296
- bridging, 67, 162–163
 - frame forwarding decision process, 67
 - transparent, 67
- broadcast addresses, 157, 232, 247–248
 - local broadcasts, 233

broadcast domains, 59
 bus, 9
 bus topology, 28, 52–53
 bytes, 15, 228

C

cable modems, 306–308
 cabling, 121
 coaxial cable, 123–124
 comparing media, 128–129
 fiber-optic cable, 125–126
 LAN technologies, selecting,
 131–133, 136–139
 twisted-pair cable
 STP, 122–123
 UTP, 121–122
 WAN connections, 147
 calculating
 address space, 249–250
 subnet masks, 245–246
 campus networks, 49–50
 Ethernet technologies, 132–133
 connection media, 133, 136
 connector requirements, 133
 UTP implementation, 136–139
 Catalyst switches
 configuring from CLI, 345
 assigning name, 345
 default gateway, 346
 default IP address, 345
 verifying startup status, 346–350
 starting up, 332, 334–337
 CDP (Cisco Discovery Protocol), 377
 device tracking features, 379
 disabling on a device, 380
 displaying device information, 379–382
 interface status, 383
 traffic information, 382–383
 information exchange, 378
 packets, 379
 preventing other devices from obtaining
 information, 380
 re-enabling on a device, 380
 cdp command, 387
 cdp enable command, 380
 CD-R/W (compact disc read/write), 8
 CD-ROM drives, 8
 cell-switching, ATM, 301
 CIDR (classless interdomain routing), 238
 circuit switching, 286
 DSL, 296–299
 ISDN, 295–296
 Cisco 827 ADSL Routers, 147
 Cisco AS5400 Series Universal Gateway, 77

Cisco content networking solution, 109
 Cisco Discovery Protocol. *See* CDP
 Cisco Fast Step software, 317
 Cisco IOS Software, 28
 booting, 332
 CLI, 318
 command history buffer, 322
 console error messages, 321
 context-sensitive help, 320–321
 displaying user exec commands,
 319–320
 editing mode, 324–325
 help sytem example, 323–324
 privileged mode, 318
 closing sessions, 318
 configuring, 316–317
 images
 backing up, 410–411
 components of, 410
 loading from network server, 411–412
 managing configuration changes, 362–364
 sub-configuration mode, 326
 terminal mode, 326
 Cisco ONS 15454 networking system, 78
 Cisco routers
 administratively disabling, 358
 booting sequence, 395
 bootstrap code, 397
 configuration register values, 397
 configuring from CLI, 351–352
 assigning a name, 352
 MOTD banner, 353
 restricting access, 353–354
 interfaces, configuring, 355–360
 ROM microcode, 396–397
 starting up, 337–338
 configuration command script, 342–343
 initial global parameters, 339–341
 initial protocol configuration, 341
 system configuration dialog, 339–340
 cladding, 125
 Class A addresses, 229
 Class B addresses, 230
 Class C addresses, 230
 Class D addresses, 230
 Class E addresses, 230
 classful addressing, 229–231, 234, 238
 depletion of IP addresses, 236–237
 high order bits, 231
 subnetting, 242
 clear line command, 390
 CLI
 closing sessions, 318
 commands
 abbreviating, 321
 history buffer, 322
 scrolling through, 325
 configuring Catalyst switches, 345–350

- configuring Cisco routers, 351–352
 - assigning a name, 352
 - interfaces, 355–360
 - MOTD banner, 353–354
 - console error messages, 321
 - context-sensitive help, 320–321
 - help system, example, 323–324
 - privileged mode, 318
 - prompt, 318
 - user exec mode commands, displaying, 319–320
- clock speed, 6, 15–16
- closing CLI sessions, 318
- CNs (content networks), 108
 - Cisco content networking solution, 109
- CO (central office) switch, 94
- coaxial cable, 123–124
- coding schemes, 15
- collision domains, 59, 158–159
 - backoff algorithms, 61
 - CSMA/CD, 61
 - hubs, 61
- collisions, 59
- command history buffer (CLI), 322
- commands
 - abbreviating, 321
 - boot system, 397
 - boot system flash, 397
 - boot system rom, 397
 - cdp, 387
 - cdp enable, 380
 - clear line, 390
 - config-register, 399–400
 - configure terminal, 326, 404
 - connect, 387
 - copy flash tftp, 410
 - copy running-config tftp, 404
 - copy running-configuration startup-configuration, 403
 - copy running-configuration tftp, 403
 - copy startup-configuration running-configuration, 403
 - copy tftp flash, 411–412
 - copy tftp running-config, 404
 - debug, 414–416
 - disconnect, 390
 - editing, 324–325
 - erase startup-configuration, 404
 - exec-timeout, 354
 - netboot, 397
 - no cdp enable, 380
 - ping, 390–391
 - recalling, 322
 - resume, 389
 - scrolling through, 325
 - sho, 379
 - show cdp, 379
 - show cdp interface, 383
 - show cdp neighbors, 380–381
 - show cdp neighbors detail, 381
 - show cdp traffic, 382–383
 - show flash, 401, 409
 - show interfaces, 349, 358
 - show interfaces serial 0, 357
 - show running-config, 401–402
 - show sessions, 388
 - show startup-config, 401–402
 - show user, 388–389
 - show version, 398
 - shutdown, 358
 - telnet, 387
 - trace, 391
 - where (UNIX), 389
 - who (UNIX), 389
- communication between VLANs, 176
- comparing media types, 128–129
- computer networking, 27
- computers. *See* PC components
- config-register command, 399–400
- configuration register, 396–397
 - boot field settings, 400
 - default settings, changing, 399
 - displaying, 398
- configure terminal command, 326, 404
- configuring
 - Catalyst switches
 - from CLI, 345
 - assigning name, 345
 - default gateway, 346
 - default IP address, 345
 - verifying startup status, 346–350
 - Cisco IOS Software, 316
 - from console terminal, 317
 - from remote terminal, 317
 - sub-configuration mode, 326
 - terminal mode, 326
 - Cisco routers
 - active configuration, 402
 - backup configuration, 402
 - copying NVRAM configuration to RAM, 403
 - copying running configuration to NVRAM, 403
 - deleting NVRAM files, 404
 - from CLI, 351–354
 - interfaces, 355–360
 - moving configuration/system files, 408
 - TCP/IP, DHCP, 195
- connect command, 387
- connecting to remote devices via Telnet, 387–388

- connection establishment, TCP three-way handshakes, 210
 - connection types
 - Ethernet, 133, 136
 - WANs, 285
 - circuit switched, 286
 - packet-switched, 287
 - point-to-point, 287
 - bandwidth, 288
 - multiplexing, 289, 291
 - connectionless protocols, 75
 - UDP, 205
 - connection-oriented protocols, 75
 - TCP, 205
 - connectivity, verifying on devices, 390–391
 - connectors, 57–59
 - console error messages (CLI), 321
 - context-sensitive help (CLI), 320–321
 - convergence, 260
 - converting
 - binary to decimal, 20
 - decimal to binary, 16–17, 20
 - copy flash tftp command, 410
 - copy running-config tftp command, 404
 - copy running-configuration startup-configuration, 403
 - copy running-configuration tftp command, 403
 - copy startup-configuration running-configuration, 403
 - copy tftp flash command, 411–412
 - copy tftp running-config command, 404
 - core layer (hierarchical network model), 51
 - corporate internetworking, 47–48
 - CoS services, 65
 - CPE (customer premises equipment), 94
 - CPU, clock speed, 6, 15–16
 - creating network map, 383–384
 - CSMA/CD (carrier sense multiple access collision detect), 61, 86–87
 - CSU/DSU (channel service unit/data service unit), 98, 356
 - cut-through switching, 165
- ## D
-
- DARPA (Defense Advanced Research Projects Agency), 185
 - data communications process, 36
 - de-encapsulation, 38–39
 - encapsulation, 36–37
 - Data field (MAC sublayer frames), 64
 - data link layer (OSI reference model), 35, 155
 - bridges, 67
 - frame forwarding decision process, 67
 - CoS services, 65
 - internetworking device functionality, 62
 - LLC sublayer frames, 64–65
 - MAC sublayer frames, 63–64
 - switches, 68–69
 - data link layer protocols, 102–103
 - datagrams, 204
 - acknowledgment numbers, 212
 - DCE (data circuit-terminating equipment), 98, 144, 299, 356
 - debug commands, 414–416
 - decimal-to-binary conversion, 16–17, 20
 - de-encapsulation, 38–39
 - default gateway, configuring on Catalyst switch, 346
 - default IP address, configuring on Catalyst switch, 345
 - default masks, 246
 - delay, 73, 261
 - demarc, 94
 - dense WDM (DWDM), 291
 - depletion of IP addresses, 236–238
 - design goals of routing protocols, 259
 - detail argument, show cdp neighbors command, 381
 - devices, 96. *See also* PC components
 - AAA servers, 78
 - adds, moves, and changes, 412–414
 - bridges, 67
 - Catalyst switches, startup, 332, 334–337
 - CDP
 - displaying information, 379
 - preventing other devices from obtaining, 380
 - re-enabling, 380
 - Cisco IOS Software
 - CLI, 318
 - configuring, 316–317
 - managing configuration changes, 362–364
 - Cisco routers, startup, 337–343
 - collision domains, 158–159
 - connecting via Telnet, 387–388
 - CSU/DSU, 98
 - debugging, 414–416
 - displaying interface status, 383
 - displaying status with CDP, 379–380
 - DSLAMs, 77
 - firewalls, 78
 - hubs, 60, 157
 - interfaces, displaying configuration, 383
 - modems, 97, 305
 - analog, 305
 - cable, 306–308
 - neighboring, displaying CDP information, 379–381
 - network connectivity, verifying, 390–391

- remote
 - Telnet sessions, displaying, 388–389
 - Telnet sessions, establishing, 387
 - Telnet sessions, re-establishing, 389
 - Telnet sessions, suspending, 389
 - Telnet sessions, verifying, 388–389
 - removable storage, 8
 - repeaters, 59
 - routers, 96, 255
 - encapsulation process, 256
 - functions performed, 74
 - routing tables, 257
 - routes, displaying, 391
 - selecting, 77
 - startup, 332
 - switches, 68–69, 76, 96
 - traffic, displaying information, 382
 - URL prefixes, 407
 - virtual circuits, 97
 - voice gateways, 77
 - DHCP (Dynamic Host Configuration Protocol), 195
 - directed broadcasts, 233, 247
 - disconnect command, 390
 - displaying
 - active Telnet sessions, 388–389
 - device information with CDP, 379–380
 - interface status, 383
 - neighboring device information, 379–382
 - traffic information, 382–383
 - user EXEC mode commands, 319–320
 - distance vector routing protocols, 265, 270
 - RIP, 269
 - distribution layer (hierarchical network model), 51
 - DIX Ethernet, 86
 - DLCIs (data-link connection identifiers), 300
 - documenting network topology, 383–384, 390
 - with ping command, 390
 - with traceroute command, 391–392
 - dotted decimal notation, 72, 229
 - download speed, units of measurement, 15
 - DS3 (digital signal level 3), 301
 - DSL (Digital Subscriber Line), 296–297
 - standards, 297–299
 - WAN connections, 147
 - DSLAMs, 77
 - DTE (data terminal equipment), 144, 299, 356
 - DUAL (Diffusing Update Algorithm) finite-state machine, 269–271
 - dual-ring topology, 54
 - dynamic routes, 257
- ## E
-
- editing mode (CLI), 324–325
 - EEPROM (erasable programmable read-only memory), 12
 - EGPs (Exterior Gateway Protocols), 264
 - BGP, 272
 - EIA/TIA-232 standard, 101
 - EIA/TIA-568 (SP-2840) Commercial Building Telecommunications Wiring Standards, 133
 - EIGRP (Enhanced IGRP), 268–271
 - email client applications, 30
 - EMI (electromagnetic interference), 121
 - enable passwords, 340
 - enable secret passwords, 340
 - encapsulation, 36–37, 203
 - routing process, 256
 - ending Telnet sessions, 390
 - enterprise services, 51
 - entries in routing tables, 258–259
 - error messages, CLI, 321
 - establishing VLAN membership, 176
 - Ethernet, 85, 87–88, 155
 - bandwidth consumption, 159
 - bridging, 162–163
 - collision domains, 158–159
 - connection media, 133, 136
 - connector requirements, 133
 - CSMA/CD, 61, 86
 - Fast Ethernet, 90–91
 - Gigabit Ethernet, 91–92
 - hubs, 60
 - IEEE 802.3 physical layer wiring standards, 57–59
 - segments, 155
 - communication between devices, 157–158
 - maximum lengths, 156
 - selecting for campus networks, 132–133
 - switching, 163–164
 - bandwidth allocation, 165
 - flooding, 168
 - frames, 167
 - identifying features, 164–165
 - loops, 168–169
 - OSI layer functionality, 166
 - STP, 170
 - UTP implementation, 136–139
 - VLANs, 173–174
 - benefits of, 175
 - communication between, 176
 - components of, 175
 - establishing membership, 176
 - expansion buses, 9
 - EXEC sessions, 315
 - exec-timeout 0 0 command, 354
 - expansion cards, 9

- expansion slots, 9
 - PCMCIA, 10
- extended star topology, 53
- exterior routing protocols, 264
- extranet VPNs, 112

F

- Fast Ethernet, 90–91
- FCS field (MAC sublayer frames), 64
- FDM (frequency-division multiplexing), 290
- fiber-optic cable, 125–126
- Fibre Channel, 107
- fields
 - of IP header, 187–191
 - of MAC sublayer frames, 63–64
 - of TCP header, 205–206
 - of UDP header, 207
- firewalls, 78
- fixed serial ports, 144
- Flash memory, 362, 396
 - displaying contents of, 401
- flooding, 67, 168, 247
- floppy disk drives, 8
- flow control, 201
 - windowing, 213–214
- forwarding tables, 67
- Frame Relay, 96, 299–300
 - virtual circuits, 300
- frames, 167
 - LLC sublayer, 64–65
 - MAC sublayer, 63–64
- FTP (File Transfer Protocol), 30, 202
- full-mesh topologies, 54–55
- functionality of transport layer (TCP/IP), 202
 - encapsulation, 203–204
 - network connections, 203

G

- GBICs (Gigabit Interface Converters), 92, 135
- GHz (gigahertz), 6, 16
- Gigabit Ethernet, 91–92
- global commands, 326, 352
- global configuration mode, 351
- group interconnection of corporate internetworks, 48

H

- hard disk drive, 8
- HDLC (High-Level Data Link Control), 102, 294–295

- headers
 - IP, field descriptions, 187–191
 - TCP, field descriptions, 205–206
 - UDP, field descriptions, 207
- help system (Cisco IOS Software)
 - command history buffer, 322
 - console error messages, 321
 - context-sensitive help, 320–321
- help system (CLI), example, 323–324
- hexadecimal numbering system, 14, 22
 - converting to binary, 23–26
 - converting to decimal, 23–24
- hierarchical networking models
 - campus networks, 49–50
 - three-layer, 50
 - access layer, 50
 - core layer, 51
 - distribution layer, 51
- high order bits, 231
- hop count, 259
- hops, 73
- host addresses, 234
- hot-swapping, 413
- HSSI (High-Speed Serial Interface), 101
- HTTP (Hypertext Transfer Protocol), 29
- hubs, 60, 157
- hybrid routing protocols, 268–269
 - EIGRP, 271

I

- I/O address, 12
- IANA (Internet Assigned Numbers Authority), 191, 235
 - well-known port numbers, 209
- ICMP (Internet Control Message Protocol), 191
 - messages, 191–192
 - unreliable packet delivery, 192
- identifying IP addresses, 249–250
- IEEE (Institute of Electrical and Electronic Engineers), 86
- IEEE 802.3 standard, physical layer wiring standards, 57–59
- IETF (Internet Engineering Task Force), RFCs, 102
- IFS (IOS File System), 407
- IGPs (Interior Gateway Protocols), 264
- IGRP (Internet Gateway Routing Protocol), 266, 270
- IHL (IP header length field), 187
- images (IOS)
 - backing up, 410–411
 - backup, 409–410
 - components of, 410
 - loading from Flash into RAM, 400

- loading from network server, 411–412
 - specifying source to load, 397
- input devices, 10
- installing NICs, 12
- interfaces, 10, 73
 - configuring on Cisco routers, 355–360
 - displaying status information, 383
 - routers, 396
 - displaying configuration information, 383
 - traffic, displaying information, 382
 - switches, displaying configuration information, 383
- internal reflection, 126
- Internet, 104
- Internet layer (TCP/IP protocol stack), 41, 186
 - ARP, 192–193
 - DHCP, 195
 - ICMP, 191–192
 - IP, header field descriptions, 187–191
 - RARP, 195
- internetworking devices, selecting, 77
- InterNIC (Internet Network Information Center), 235
- intranet VPNs, 111
- IOS. *See* Cisco IOS Software
- IOS File System, 407
- IP (Internet Protocol), header field descriptions, 187–191
- IP addresses, 71, 227
 - address classes, 229–231
 - assigning, 233
 - broadcast addresses, 232, 247–248
 - local broadcasts, 233
 - CIDR, 238
 - classful addressing, 234
 - depletion of, 236–237
 - dotted decimal notation, 229
 - high order bits, 231
 - host addresses, 234
 - identifying, 249–250
 - IPv6, 237
 - octets, 228
 - private, 235–236
 - public, 235–236
 - subnet planning, 251–252
 - subnetting, 242–243
 - default masks, 246
 - subnet masks, 244–246
- IPv6, 237–238
- IRQ (interrupt request line), 12
- ISA (Industry Standard Architecture) expansion buses, 9
- ISCSI (Internet Small Computer System Interface over IP), 108
- ISDN (Integrated Services Digital Network), 295–296
 - BRI connections, 146–147

- IS-IS (Intermediate System-to-Intermediate System), 268
- ISO (International Organization for Standardization), 32
- ISPs (Internet service providers), 104

J–K

- JAM signals, 88

- kb (kilobit), 15
- kB (kilobyte), 15
- kbps (kilobits per second), 15
- kBps (kilobytes per second), 15
- Kevlar shielding, 125

L

- LANs, 28
 - cabling options, selecting, 131–133, 136–139
 - data link layer, 86
 - Ethernet, 85–88, 155
 - bandwidth consumption, 159
 - bridging, 162–163
 - collision domains, 158–159
 - communication between devices, 157–158
 - CSMA/CD, 86
 - Fast Ethernet, 90–91
 - Gigabit Ethernet, 91–92
 - segments, 155–156
 - switching, 163–164
 - bandwidth allocation, 165
 - flooding, 168
 - frames, 167
 - identifying features, 164–165
 - loops, 168–169
 - OSI layer functionality, 166
 - STP, 170
- LAPB (Link Access Procedure, Balanced), 102
- LAPF (Link Access Procedure for Frame Relay), 102
- laptops versus PCs, 10
- last mile, 94
- Layer 1 devices, 60
- Layer 2 switching, 66, 155, 163–164
 - bandwidth allocation, 165
 - flooding, 168
 - frames, 167
 - identifying features, 164–165
 - loops, 168–169
 - OSI layer functionality, 166
 - STP, 170

layers of OSI model

- application layer, 34
- correlated TCP/IP protocol stack layers, 185
- data link layer, 35
 - bridges, 67
 - CoS services, 65
 - frame forwarding decision process, 67
 - internetworking device functionality, 62
 - LLC sublayer frames, 64–65
 - MAC sublayer frames, 63–64
 - switches, 68–69
- de-encapsulation process, 38
- encapsulation process, 37
- functions of, 33
- multilayer devices, 76
- network layer, 35
 - addresses, 70–71
 - internetworking device functionality, 69–70
 - IP addressing, 71
 - logical addresses, 71
 - QoS marking, 72
 - router operation, 73–74
- physical layer, 35
 - broadcast domains, 59
 - collision domains, 59
 - connectors, 57–59
 - hubs, 60
 - internetworking device functionality, 56–57
 - media, 57–59
 - repeaters, 59
- presentation layer, 34
- session layer, 34
- transport layer, 35
 - internetworking device functionality, 75–76

layers of TCP/IP protocol stack, 40–41

- applications, 202
- Internet layer, 186
 - ARP, 192–193
 - DHCP, 195
 - ICMP, 191–192
 - IP, 187, 189–191
 - RARP, 195
- transport layer, 199
 - encapsulation, 203–204
 - functionality, 202–203
 - message exchange process, 200
 - TCP, 200, 205–214
 - UDP, 201–202, 207–210

LCP (Link Control Protocol), 294

leased lines, 287

LEDs on Catalyst 2950 Series switch, 334–337

Length field (MAC sublayer frames), 64

link types, 100

link-state database, 267

link-state routing protocols, 266–268

- OSPF, 271–272

LLC sublayer frame structure, 64–65

loading IOS image files from network server, 411–412

local ARP, 192

local broadcast, 233

local loop, 94

local ports, 381

logging synchronous command, 355

logical addresses, 71

logical AND operation, 245

logical topologies, 28, 52–54

looping, 269

loops, 168–169

- preventing with STP, 170

low overhead, as routing protocol design goal, 259

LSAs (link-state advertisements), 267

M

MAC addresses, 63

MAC sublayer (data link layer), frame structure, 63–64

main office, 47

major commands, 326, 352

managing configuration changes on Cisco IOS Software, 362–364

MANs (metropolitan-area networks), 28, 103–104

mapping network environment, 383–384

maximum Ethernet segment lengths, 156

Mb (megabit), 15

MB (megabyte), 15

Mbps (megabits per second), 15

MBps (megabytes per second), 15

MD5 (message digest 5), 340

media, 28

- on physical layer, 57–59

membership (VLANs), establishing, 176

memory, 7–8

- bytes, 15
- EEPROM, 12
- Flash, 396
 - displaying contents of, 401
- I/O address, 12
- NVRAM, 396
- RAM, 396
- ROM, 396–397
 - routers, displaying information, 409

mesh topologies, 28, 54–55

messages

- ARP, 193
- ICMP, 191–192
- transport layer (TCP/IP), exchange process, 200

metrics, 73, 260–262

MHz (megahertz), 6, 16
 microsegmentation, 68, 164
 mobile users, 48
 modems, 97, 305
 analog, 305
 cable, 306–308
 modular serial ports, 145
 MOTD (message-of-the-day) banners, configuring, 353
 motherboard, 7
 expansion buses, 9
 multicast transmission, 158
 multilayer switches, 76
 multimode fiber-optic cable, 126
 multiplexing point-to-point WAN connections, 289–291

N

NAT (Network Address Translation), 236
 NCPs (Network Control Programs), 294
 neighboring devices, displaying CDP information, 379–381
 netboot command, 397
 network access layer (TCP/IP protocol stack), 41
 network addresses, 73
 network applications, 29–30
 network environment, documenting, 383–384
 network ID, 233
 network layer (OSI reference model), 35
 addresses, 70–71
 internetworking device functionality, 69–70
 IP addressing, 71
 logical addresses, 71
 QoS marking, 72
 router operation, 73–74
 network topology, documenting, 390
 with ping command, 390
 with traceroute command, 391–392
 NICs (network interface cards), 6, 11, 27
 installing, 12
 wireless, 126
 no cdp enable command, 380
 no cdp run command, 380
 NOS (network operating system), 28
 notebook computers, 10
 NT1 devices, 146
 numbering systems
 binary, 14
 converting to decimal, 20
 converting to hexadecimal, 25
 decimal, converting to binary, 16–17, 20
 hexadecimal, 14, 22
 converting to binary, 23–26
 converting to decimal, 23–24
 NVRAM (non-volatile RAM), 362, 396

O

OC (optical carrier) standards, 302
 octets, 71, 228
 OIR (online insertion and removal), 413
 open networking systems, 32
 optical networking, Cisco ONS 15454 networking system, 78
 optimization, 259
 OSI reference model, 32
 application layer, 34
 data communications process, 36
 de-encapsulation, 38–39
 encapsulation, 36–37
 data link layer, 35, 155
 bridges, 67
 CoS services, 65
 frame forwarding decision process, 67
 internetworking device functionality, 62
 LLC sublayer frames, 64–65
 MAC sublayer frames, 63–64
 switches, 68–69
 layers correlated to TCP/IP protocol stack, 185
 physical layer
 cabling, 121
 coaxial cable, 123–124
 comparing media, 128–129
 fiber-optic cable, 125–126
 selecting LAN cabling options, 131–133, 136
 twisted-pair cable, 121–123
 UTP implementation, 136–139
 WAN implementations, 141–147
 wireless, 126–128
 multilayer devices, 76
 network layer, 35
 addresses, 70–71
 internetworking device functionality, 69–70
 logical addresses, 71
 QoS marking, 72
 router operation, 73–74
 peer-to-peer communication, 39–40
 physical layer, 35
 broadcast domains, 59
 collision domains, 59
 connectors, 57–59
 hubs, 60
 internetworking device functionality, 56–57
 media, 57–59
 repeaters, 59
 presentation layer, 34
 session layer, 34
 transport layer, 35
 internetworking device functionality, 75–76

OSPF (Open Shortest Path First), 267–272
 OUI (Organizational Unique Identifier), 63
 output devices, 10

P

packets
 CDP, 379
 encapsulation during routing process, 256
 IP, 187
 packet-switching, 287
 parallel ports, 10
 partial-mesh topologies, 54–55
 path determination, 257–258
 BGP, 272
 metrics, 260–262
 PC components
 backplane components, 10
 CPU, 6
 expansion buses, 9
 memory, 7–8
 I/O address, 12
 motherboard, 7
 NICs, 11–12
 parallel ports, 10
 power supply, 9
 storage devices, 8
 system unit, 9
 PCB (printed circuit board), 7
 PCI (Peripheral Component Interface) expansion buses, 9
 PCMCIA (Personal Computer Memory Card International Association) expansion slots, 10
 PDUs (protocol data units), 39
 peer layers, 36
 peer-to-peer communication, 39–40
 performing adds, moves, and changes, 412–414
 physical layer (OSI model), 35
 broadcast domains, 59
 cabling, 121
 coaxial cable, 123–124
 fiber-optic cable, 125–126
 twisted-pair cable, 121–123
 collision domains, 59
 comparing media, 128–129
 connectors, 57–59
 hubs, 60
 internetworking device functionality, 56–57
 media, 57–59
 repeaters, 59
 selecting LAN cabling options, 131
 Ethernet in campus, 132–133

 Ethernet in campus networks, 133, 136–139
 WAN implementations, 141–142
 asynchronous router connections, 148–149
 auxiliary connections, 149
 cable connections, 147
 DSL connections, 147
 ISDN BRI connections, 146–147
 serial connections, 142–145
 wireless, 126–128
 physical layer protocols, 100–101
 physical topologies, 28, 52–93
 ping command, 192, 390–391
 point of presence, 94
 point-to-point WANs, 287
 bandwidth, 288
 multiplexing, 289, 291
 POP3 (Post Office Protocol 3), 29
 port LED display modes, 334–335
 port numbers, 75, 208–210
 ports, 10
 POST (power-on self-test)
 LED display status, 335–337
 router booting sequence, 395
 power supply (PCs), 9
 PPP (Point-to-Point Protocol), 102, 293–294
 presentation layer (OSI model), 34
 PRI (Primary Rate Interface), 296
 private IP addresses, 235–236
 privileged mode (CLI), 318
 proprietary networking systems, 32
 Protocol field (IP header), 190
 protocols, 28, 32
 CDP, 383
 connection-oriented, 75
 public IP addresses, 235–236
 PVCs, 302

Q

QAM (Quadrature Amplitude Modulation), 307
 QoS (quality of service), 72
 question mark (?), displaying commonly used commands, 319–320

R

RAM (random-access memory), 7, 362, 396
 RARP (Reverse Address Resolution Protocol), 195
 read-write memory, 7

- recalling commands, 322
 - re-establishing suspended Telnet sessions, 389–390
 - reliable data delivery services, 201
 - reliable transport-layer services, 203
 - remote connections, establishing with Telnet, 387–388
 - remote device Telnet sessions
 - displaying, 388–389
 - establishing, 387
 - re-establishing, 389
 - suspending, 389
 - verifying, 388–389
 - remote-access locations, 48
 - removable storage devices, 8
 - repeaters, 59
 - requirements for Ethernet LAN media, 133
 - reserved network addresses, 232
 - restricting access to Cisco routers, 353–354
 - resume command, 389
 - RFCs (requests for comments), 102
 - ring topologies, 28, 54
 - RIP (Routing Information Protocol), 266, 269
 - RIPE NCC (Réseaux IP Européens Network Coordination Centre), 236
 - RIPv1, 269
 - robustness as routing protocol design goal, 259
 - ROM (read-only memory), 7
 - microcode, 396–397, 401
 - ROM monitor mode, 399
 - routed protocols, 257
 - routers, 96, 255
 - booting sequence, 395
 - bootstrap code, 395
 - configuring
 - active configuration, 402
 - backup configuration, 402
 - copying into RAM, 403
 - copying RAM configuration to TFTP server, 403
 - copying running configuration to NVRAM, 403
 - copying saved NVRAM configuration to RAM, 403
 - deleting NVRAM files, 404
 - displaying current configuration running in RAM, 402
 - displaying current configuration saved in NVRAM, 402
 - downloading from TFTP server, 404
 - loading parameters into RAM, 401
 - moving configuration/system files, 408
 - running configuration, 401
 - uploading to TFTP server, 404
 - configuration register, 396
 - boot field settings, 400
 - default settings, changing, 399
 - displaying, 398
 - listing setting for, 399
 - encapsulation process, 256
 - functions, 74
 - IFS, 407
 - interfaces, 396
 - displaying configuration information, 383
 - traffic, displaying information, 382
 - memory, displaying information, 409
 - neighboring devices, displaying CDP information, 380–381
 - ROM microcode, 396–397, 401
 - ROM monitor mode, 399
 - routing tables, 257
 - routing by rumor, 265
 - routing protocols, 257, 263
 - autonomous systems, 264
 - balanced hybrid, EIGRP, 271
 - design goals, 259
 - distance vector, 265
 - IGRP, 270
 - RIP, 269
 - EGPs, BGP, 272
 - hybrid, 268–269
 - IGPs, 264
 - link-state, 266–268
 - OSPF, 271–272
 - metrics, 260–262
 - path determination, 257–258
 - routing tables, 258–259
 - routing tables, 257–259
 - rxboot code, 396
- ## S
-
- SANs (storage area networks), 106–108
 - SAPs (service access points), 75
 - scrolling through commands, 325
 - SDH (Synchronous Digital Hierarchy), 302–303
 - SDLC (Synchronous Data Link Control), 102
 - SDSL (symmetric DSL), 297
 - security
 - configuring on Cisco routers, 353–354
 - firewalls, 78
 - segmentation, 162
 - microsegmentation, 164
 - segments, 155, 204
 - communication between devices, 157–158
 - bandwidth consumption, 159
 - collision domains, 158–159
 - maximum lengths, 156

- VLANs, 173–174
 - benefits of, 175
 - communication between, 176
 - components of, 175
 - establishing membership, 176
- selecting
 - internetworking devices, 77
 - LAN cabling options, 131–133, 136–139
 - NICs, 12
- self-healing network architectures, 103
- serial connections, WANs, 142–145
- serial interfaces, configuring on Cisco routers, 356–360
- serial ports, 10
- serial WAN connections, 287
- session layer (OSI model), 34
- sessions, 75,
- setup dialog, Cisco IOS Software, 316, 338
- Setup utility, 401
- shared networks, limitations of, 160
- shielding, Kevlar, 125
- show cdp command, 379
- show cdp interface command, 383
- show cdp neighbors command, 380–381
- show cdp neighbors detail command, 381
- show cdp traffic command, 382–383
- show flash command, 401, 409
- show interfaces command, 349, 358
- show interfaces serial 0 command, 357
- show running-config command, 401–402
- show sessions command, 388
- show startup config command, 401
- show startup-config command, 402
- show user command, 388–389
- show version command, 398
- shutdown command, 358
- signaling, 96–100
- single-mode fiber-optic cable, 126
- single-ring topology, 54
- SLIP (Serial Line Internet Protocol), 102
- “smart serial” connectors, 143
- SMTP (Simple Mail Transfer Protocol), 202
- SNAP (Subnetwork Access Point) frames, 65
- SNMP (Simple Network Management Protocol), 30
- SONET (Synchronous Optical Network), 302–303
- Source Quench messages (ICMP), 191
- SPF (shortest path first) algorithm, 267
- SS7 (Signaling System 7), 96
- standards
 - DSL-related, 297–299
 - IEEE 802.3, physical layer wiring, 57–59
 - physical layer, 101
- star topology, 28, 53
- starting up Cisco IOS devices, 316, 332
 - Catalyst switches, 332–337
 - Cisco routers, 337–343

- static routes, 257
- statistical multiplexing, 291
- storage devices, 8
- store-and-forward switching, 164
- STP (Spanning Tree Protocol), 121–123, 170
- sub-configuration mode (Cisco IOS Software), 326
- subnet masks, 244–246
- subnets, 242–243
 - default masks, calculating, 246
 - identifying IP addresses, 249–250
 - logical AND operation, 245
 - planning, 251–252
 - subnet masks, 244–246
- supernetting, 238
- suspending Telnet sessions, 389
- SVCs (switched virtual circuits), 302
- switched circuits, 286
- switching, 68–69, 96–97, 155, 163–164.
 - See also* Catalyst switches
 - bandwidth allocation, 165
 - CDP information, displaying, 379
 - flooding, 168
 - frames, 167
 - identifying features, 164–165
 - interfaces, displaying configuration information, 383
 - loops, 168–169
 - multilayers switches, 76
 - OSI layer functionality, 166
 - STP, 170
- SYNs, 210
- system configuration dialog, 338
- system unit, 9

T

- T1 lines, 288
- T3 lines, 288
- TCP (Transmission Control Protocol), 200, 205
 - header fields, 205–206
 - port numbers, 208–210
 - windowing, 213–214
- TCP/IP protocol stack, 40, 185
 - correlated OSI reference model layers, 185
 - Internet layer, 186
 - ARP, 192–193
 - DHCP, 195
 - ICMP, 191–192
 - IP, 187, 189–191
 - RARP, 195

- transport layer, 199
 - applications, 202
 - encapsulation, 203–204
 - functionality, 202–203
 - message exchange process, 200
 - TCP, 200, 205–214
 - UDP, 201–202, 207–210
- versus OSI reference model, 40–42
- TDM (time-division multiplexing), 96, 289
- telecommuting, 48
- Telnet, 30, 202
 - connecting to remote devices, 387–389
 - sessions
 - displaying, 388–389
 - establishing to remot, 387
 - re-establishing, 389–390
 - suspending, 389
 - terminating, 390
 - verifying, 388–389
- terminal mode (Cisco IOS Software), 326
- terminating Telnet sessions, 390
- TFTP (Trivial File Transport Protocol), 202, 404
- Thicknet, 57, 124
- Thinnet, 57, 124
- three-layer hierarchical networking model, 50
 - access layer, 50
 - core layer, 51
 - distribution layer, 51
- three-way handshakes, 210
- tokens, 54
- toll network, 94
- topologies
 - bus, 52–53
 - extended star, 53
 - logical, 28
 - ring, 54
 - versus physical, 52
 - mesh, 54–55
 - physical, 28
 - star, 53
- trace command, 391
- traceroute command, documenting network topology, 391–392
- traffic, displaying device information, 382
- transparent bridging, 67
- transport layer (OSI model), 35
 - internetworking device functionality, 75–76
- transport layer (TCP/IP protocol stack), 41, 199
 - functionality, 202
 - encapsulation, 203–204
 - network connections, 203
 - message exchange process, 200

- TCP, 200
 - flow control, 213–214
 - header fields, 205–206
 - port numbers, 208–210
 - three-way handshakes, 210
- UDP, 201–202
 - header fields, 207
 - port numbers, 208–210
- troubleshooting with debug command, 414–416
- twisted-pair cable
 - STP, 122–123
 - UTP, 121–122
- Type field (MAC sublayer frames), 64

U

- UDP (User Datagram Protocol), 201–202
 - flow control, windowing, 213–214
 - header fields, 207
 - messages, 392
 - port numbers, 208–210
- unicast transmission, 157
- unreliable packet delivery, ICMP, 192
- URL prefixes, 407
- user EXEC mode commands, displaying, 319–320
- UTP (unshielded twisted-pair), 121–122

V

- V.24 standard, 101
- V.35 standard, 101
- verifying
 - active Telnet sessions, 388–389
 - Catalyst switch startup status, 346–350
- video cards, 10
- virtual circuits, 97, 200, 300
 - ATM, 302
- VLANs, 173–174
 - benefits of, 175
 - communication between, 176
 - components of, 175
 - establishing membership, 176
- voice gateways, 77
- VPI/VCI (virtual path/channel identifier), 301
- VPNs, 109
 - access VPNs, 110
 - extranet VPNs, 112
 - intranet VPNs, 111

W

- WANs, 94–96
 - access technologies, 293
 - ATM, 301
 - DSL, 296–299
 - Frame Relay, 299–300
 - HDLC, 294–295
 - ISDN, 295–296
 - PPP, 293–294
 - SONET, 302–303
 - asynchronous router connections, 148–149
 - circuit-switched, 286
 - connection technologies, 285
 - data link layer protocols, 102–103
 - devices, 96
 - CSU/DSU, 98
 - modems, 97
 - routers, 96
 - switches, 96
 - virtual circuits, 97
 - link types, 100
 - modems, 305
 - analog, 305
 - cable, 306–308
 - packet-switched, 287
 - physical layer, 100–101, 141–142
 - cable connections, 147
 - DSL connections, 147
 - ISDN BRI connections, 146–147
 - serial connections, 142–145
 - point-to-point, 287
 - bandwidth, 288
 - multiplexing, 289–291
 - provider service types, 96
 - service providers, 98–100
 - signaling standards, 98–100
- WDM (wavelength division multiplexing), 291
- well-known port numbers, 209
- where command (UNIX), 389
- who command (UNIX), 389
- windowing, TCP flow control, 213–214
- wireless networks, 126, 128
- wiring, IEEE 802.3 standards, 57, 59

X–Z

- X.21 standard, 101
- xDSL, 297