

Numerics

- 802.1p tagging, 63, 65
- 802.1q tagging, 63, 65
- 802.1q tunneling, 62–63
 - asymmetrical links, 65
 - restrictions, 67–68
 - tagging process, 66

A

- AAL (ATM Adaptation Layer), 94–95
- AAL5
 - CPCS-SDU mode, 242–243
 - packet cell relay mode, 245–246
 - single cell relay mode, 243–244
- AAL5_SDUoL2TPv3
 - configuring, 439–440, 447
 - control plane, 444
 - data plane, 445–447
 - verifying configuration, 440–443, 449–450
- AAL5oMPLS, case study configuration, 224–229
- ABM (Asynchronous Balanced Mode), 71
- ABR (available bit rate), 102
- access mode, VPLS configuration, 582
- ACFC (Address and Control Field Compression), 78
- Address field
 - Frame Relay frames, 80
 - HDLC frames, 73
 - PPP frames, 78
- adjusted MTU, 462
- advertisement messages (LDP), 118, 123–124
- advertising VCCV, 313–314
- any-to-any local switching
 - ATM attachment circuits, 557
 - Ethernet-to-VLAN, 556–557
- ARM (Asynchronous Response Mode), 71
- associating VPLS attachment circuits to VFI, 586
- asymmetrical links, 65
- ATM (Asynchronous Transfer Mode)
 - AAL5 CPCS-SDU mode, 242–243
 - AAL5oMPLS, case study configuration, 224–229
 - ATMoMPLS, 198
 - AAL5 transport, 198–201
 - cell transport, 201–203
 - cell format, 97
 - cell packing, 487–491
 - Cell Relay operational modes, configuring, 450–452
 - CRoMPLS, case study configuration, 230–233
 - encapsulation, 94–95
 - ILMI, 98–101
 - interaction with pseudowire protocols, 94
 - legacy Layer 2 VPNs, 30–31
 - OAM, 98–101
 - OAM emulation, 478–487
 - packet cell relay mode, 245–246
 - single cell relay mode, 243–244
 - traffic management, 102
 - traffic policing, 102–107
 - traffic shaping, 107–109
- ATM Forum Traffic Management 4.0 standard, 103
- ATM layer (ATM), 94
- ATM transport over L2TPv3, 404–406
- ATMoMPLS, cell packing
 - configuring, 238–240
 - verifying configuration, 240–242
- ATM-Specific Sublayer, 399
- ATM-to-ATM local switching, 551–553
- AToM (Any Transport over MPLS), 11, 33–34
 - control word negotiation, 129–130
 - encapsulation
 - ATM, 132–133
 - Ethernet, 136–137
 - Frame Relay, 134–135
 - HDLC, 135
 - PPP, 135–136
 - hardware support, verifying, 236–238
 - label stacking, 35–37
 - LDP
 - LDP peers, 116
 - packets, 116
 - pseudowire label binding, 126–127
 - pseudowires, 34–35
 - establishing, 128–129
- QoS, 320
 - intermediate markings, 325
 - queuing, 323–324

- traffic marking, 320–322
- traffic policing, 322–323
- selection criteria
 - advanced network services, 39–40
 - existing network installation base, 38
 - interoperability, 40
 - network operation complexity, 40
- sequence numbers, 131–132
- supported Layer 2 protocols, 37–38
- attachment circuits
 - associating to VFI, 586
 - ATM and local switching, 557
 - Layer 2 local switching, 549
 - ATM-to-ATM, 551–553
 - Ethernet-to-Ethernet, 553–555
 - Frame Relay-to-Frame Relay, 549
 - like-to-like, 511
 - VPLS configuration, 581–582
- auto-discovery mechanism, 22
- AVPs (Attribute-Value Pairs), 336

B

- basic LDP discovery, 120
- BGP IPv4 label distribution with IGP redistribution, 294–310
- BGP-based VPLS, 575–576
- BPDU Guard, 62
- BPDU, 58
- bridged IW, 512–514
 - ATM AAL5-to-VLAN using AToM, case study, 526–529
 - case study, 517
 - environment considerations, 529
 - MTU, 515–516
 - using AToM, case study, 518–522
 - using L2TPv3, case study, 523–525
- byte stuffing, 73

C

- calculating
 - EoMPLS MTU size requirements, 144–146
 - required LDP sessions for VPLS deployment, 576

- case studies
 - AAL5_SDUoL2TPv3
 - configuring, 439–440
 - control plane, 443–444
 - data plane, 445–447
 - verifying configuration, 440–442
 - ATM_CoL2TPv3
 - configuring, 447
 - verifying configuration, 449–450
 - EoMPLS transport, 149
 - port-based, 154–155, 157
 - port-based, switch configuration, 167, 169
 - pseudowire class template
 - configuration, 173
 - VLAN rewrite, 160–161, 169–173
 - VLAN-based, 157–160
 - VLAN-based, switch configuration, 161–166
 - Equal-Cost Multipath, 253–256
 - Frame Relay over L2TPv3
 - configuring, 431–432
 - data plane, 436–438
 - verifying configuration, 433–435
 - HDLC over L2TPv3
 - configuring, 408–409, 411
 - data plane details, 415–417
 - verifying configuration, 411–415
 - IW, 516–517
 - bridged, 529
 - bridged using AToM, 518–522, 526–529
 - bridged using L2TPv3, 523–525
 - routed, 530–548
 - point-to-point L2TPv3 transport
 - Ethernet port-to-port dynamic session, 376–383
 - Ethernet port-to-port manual session, 360–368
 - Ethernet port-to-port manual session with keepalive, 368–376
 - Ethernet VLAN-to-VLAN dynamic session, 383–391
 - IP topology, 358–360
 - PPP over L2TPv3
 - configuring, 417–419
 - control plane negotiation, 423–427
 - data plane, 428–431
 - verifying configuration, 419–422
 - Unequal-Cost Multipath, 252–253

- WANs over L2TPv3, 395
 - ATM transport, 404–406
 - configuring, 407–408
 - control plane, 395–396
 - data plane, 396–398
 - Frame Relay transport, 403–404
 - HDLC pseudowire transport, 402
 - L2-Specific Sublayer, 398–400
 - MTU considerations, 400–401
 - PPP transport, 402–403
 - WANs over MPLS, configuring, 203–205
 - AAL5oMPLS, 224–229
 - CRoMPLS, 230–233
 - FRoMPLS, 218–224
 - HDLCoMPLS, 207–213
 - PPPoMPLS, 214–218
 - CBR (constant bit rate), 102
 - CBR.1 traffic policing, 104
 - CE routers, 6
 - vlan-based EoMPLS transport,
 - configuring, 158
 - cell format (ATM), 97
 - cell packing, 487–491
 - configuring, 238–240
 - verifying configuration, 240–242
 - Cell Relay modes (ATM), configuring, 450–452
 - character stuffing, 73
 - Cisco 12000 series routers, VLAN rewrite,
 - configuring, 169–171
 - port VLAN ID inconsistency issue, 173
 - Cisco HDLC versus standard HDLC, 401
 - Cisco LMI, 83
 - Cisco Unified VPN suite, 115
 - local switching, 549
 - ATM attachment circuits, 557
 - ATM-to-ATM, 551–553
 - Ethernet-to-Ethernet, 553–555
 - Ethernet-to-VLAN, 556–557
 - Frame Relay-to-Frame Relay, 549
 - CLP field (ATM cells), 98
 - combining PMTUD and DF bit, 470–478
 - commands
 - connect, 558–559
 - debug acircuit event, 180
 - debug mpls l2transport signaling message, 179
 - debug mpls l2transport packet data, 182
 - debug mpls l2transport signaling message, 155
 - interworking, 517
 - l2tp-class, 355–357
 - pseudowire-class, 354–355
 - remote circuit id, 171
 - show arp, 156
 - show connection, 534
 - show ip traffic, 459
 - show mpls l2transport vc, 174–176, 183, 592
 - show mpls forwarding-table, 153, 178
 - show mpls ldp discovery, 176
 - show mpls ldp neighbor, 153
 - show processes cpu, 458
 - show sss circuits, 559
 - xconnect, 352–353
 - comparing EoMPLS modes, 147
 - configuring
 - AAL5_SDUoL2TPv3, 439–440
 - control plane, 443–444
 - data plane, 445–447
 - verifying configuration, 440–442
 - ATM, Cell Relay modes, 450–452
 - ATM_CoL2TPv3, 447
 - verifying configuration, 449–450
 - ATMoMPLS, cell packing, 238–242
 - AToM pseudowire over GRE tunnel, 282–286
 - cell packing, 487–491
 - EoMPLS transport, case studies, 149, 154–173
 - Ethernet port-to-port dynamic session, 376–378
 - data plane details, 381–383
 - verifying configuration, 378–380
 - Ethernet port-to-port manual session, 360–363
 - data plane details, 366–368
 - verifying configuration, 363–365
 - Ethernet port-to-port manual session with
 - keepalive, 368–371
 - data plane details, 373–376
 - verifying configuration, 370–372
 - Ethernet VLAN-to-VLAN dynamic session,
 - 383–385
 - control plane details, 387–389
 - frame encapsulation, 389–391
 - verifying configuration, 385–387
 - Frame Relay over L2TPv3, 431–432
 - data plane, 436–438
 - verifying configuration, 433–435

- HDLCoL2TPv3, 408–411
 - data plane details, 415–417
 - verifying configuration, 411–415
- L2TPv3
 - l2tp-class command, 355–357
 - pseudowire-class command, 354–355
 - xconnect command, 352–353
- LDP authentication for pseudowire signaling, 311–312
- OAM emulation, 482–487
- PPPoL2TPv3, 417–419
 - control plane negotiation, 423–427
 - data plane, 428, 430–431
 - verifying configuration, 419–422
- preferred path, 256–258
 - with IP routing, 258–264
 - with MPLS Traffic Engineering tunnels, 264–275
- pseudowires, 21–22
- QoS
 - input service policies, 504–506
 - queuing, 503–504
 - traffic marking, 491–497
 - traffic policing, 497–502
- VPLS, 581
 - access mode, 582
 - attachment circuits, 581–582
 - dot1Q-tunnel mode, 584–585
 - example configuration, 587–592
 - Layer 2 protocol tunneling, 594–597
 - multihoming, 598–602
 - per-VLAN MAC address limiting, 592
 - QoS, 593–594
 - trunk mode, 583–584
 - VFI, 585–586
- WAN protocols over L2TPv3, 407–408
- WAN protocols MPLS, 203–205
 - AAL5oMPLS, 224–229
 - CRoMPLS, 230–233
 - FRoMPLS, 218–224
 - HDLCoMPLS, 207–213
 - PPPoMPLS, 214–218
- WANs over MPLS pseudowires
 - control plane, 187–188
 - control word negotiation, 190–191
 - data plane encapsulation, 189
 - MTU requirements, 191–192
 - pseudowire types, 188–189
 - connect command, 558–559
 - conservative label retention mode, 125
 - control connection mechanism (L2TPV3), 341
 - control channel signaling, 343–347
 - Control Message Authentication, 346
 - control message to encapsulation, 341–343
 - Control field (Frame Relay frames), 81
 - Control field (HDLC frames), 73
 - Control field (PPP frames), 78
 - Control Message Authentication (L2TPv3), 346
 - control messages, L2TPv3, 42
 - control packets, L2TPv3, 42
 - control plane
 - configuring WAN protocols over MPLS pseudowires, 187–188
 - L2TPv3, 41
 - PE device system architecture, 19
 - control word negotiation
 - AToM, 129–130
 - configuring WAN protocols over MPLS pseudowires, 190–191
 - criteria
 - for AToM selection
 - advanced network services, 39–40
 - existing network installation base, 38
 - interoperability, 40
 - network operation complexity, 40
 - for L2TPv3 selection, 44
 - advanced network services, 45
 - existing network installation base, 45
 - interoperability, 46
 - network operation complexity, 46
 - CRoL2TPv3, 487–491
 - CRoMPLS (cell relay transport over MPLS), 201–203
 - case study configuration, 230–233
 - CS (convergence sublayer) PDUs, 94–95
 - CSMA-CD, 51
 - CS-PDU, 95

D

- data encapsulation, L2TPv3, 336
 - Demultiplexing Sublayer field, 338–339
 - Encapsulation Sublayer field, 339–340
 - packet-switched network layer, 337–338

- data plane
 - connectivity, verifying, 315–319
 - encapsulation, configuring WAN protocols over MPLS pseudowires, 189
 - PE device system architecture, 18
 - debug acircuit event command, 180
 - debug mpls l2transport packet data command, 182
 - debug mpls l2transport signaling message command, 155, 179
 - debugging EoMPLS on PE routers, 179–181, 183
 - decoding LDP label mapping messages, 234, 236
 - Demultiplexing Sublayer field (L2TPv3), 338–339
 - DF bit, combining with PMTUD, 470–478
 - DiffServ, 491
 - discovery mechanisms (LDP), 119–120
 - discovery messages (LDP), 118
 - displaying VPLS pseudowire status, 592
 - DLCIs, 5
 - DLSw, legacy Layer 2 VPNs, 31
 - dot1Q-tunnel mode, VPLS configuration, 584–585
 - downstream on demand label advertisement mode, 124
 - draft-kompella, 23–26
 - draft-martini, 24
 - DTE (data terminal equipment), 83
 - DTP (Dynamic Trunking Protocol), 62
 - dual leaky bucket model, 91
 - dynamic protocol signaling, 22
 - for Frame Relay-to-PPP-IW using L2TPv3, 564–565
 - for VLAN-to-bridged IW using L2TPv3, 562–563
 - IW, 559
 - UTI, fields, 334
 - encapsulation layer (pseudowire emulation), 17
 - Encapsulation Sublayer field (L2TPv3), 339–340
 - enhanced Layer 2 VPNs, 8–11
 - AToM, 11
 - EoMPLS (Ethernet over MPLS), 139
 - debugging on PE routers, 179–183
 - label disposition, 147–148
 - label imposition, 147–148
 - label stack, 140
 - MTU size requirements, 140–144
 - calculating, 144–146
 - packets
 - fields, 142
 - format, 140
 - supported VC types, 146–147
 - transport, case studies, 149
 - port-based, 154–157
 - port-based, switch configuration, 167–169
 - preconfiguration requirements, 150–153
 - pseudowire class template configuration, 173
 - VLAN rewrite, 160–161, 169–173
 - VLAN-based, 157–160
 - VLAN-based, switch configuration, 161–166
 - troubleshooting
 - on routers, 174–179
 - on switches, 183–185
 - Equal-Cost Cost Multipath, 253, 255–256
 - establishing AToM pseudowires, 128–129
 - Ethernet
 - CSMA-CD, 51
 - frames, 52
 - Metro Ethernet, 54–56
 - port-to-port dynamic session, 376
 - configuring, 377–378
 - data plane details, 381–383
 - verifying configuration, 378–380
 - port-to-port manual session
 - configuring, 360–363, 368–371
 - data plane details, 366–368, 373–376
-
- E**
- ECMP (Equal-Cost Multipath), 249
 - encapsulation
 - AToM
 - for ATM transport, 132–133
 - for Ethernet transport, 136–137
 - for Frame Relay transport, 134–135
 - for HDLC transport, 135
 - for PPP transport, 135–136
 - ATM, 94
 - AAL, 95
 - cell format, 97
 - for Ethernet-to-VLAN local switching Ethernet IW, 559–560
 - for Frame Relay-to-VLAN IP IW using AToM, 560–562

- verifying configuration, 363–365, 370–372
- VLAN-to-VLAN dynamic session
 - configuring, 383–385
 - control plane details, 387–389
 - frame encapsulation, 389–391
 - verifying configuration, 385–387
- Ethernet II frames, 52–53
- Ethernet IW, 512–514
 - ATM AAL5-to-VLAN using AToM, case study, 526–529
 - case study, 517
 - environment considerations, 529
 - MTU, 515–516
 - using AToM, case study, 518–522
 - using L2TPv3, case study, 523–525
- Ethernet-to-Ethernet local switching, 553, 555
- Ethernet-to-VLAN local switching, 556–557
- EVCS (Ethernet Virtual Connection Service), 571–572
- evolution of L2TPv3, 333
- example VPLS configuration, 587–592
- extended LDP discovery, 120

F

- Fast Reroute, 275–281
- F-bit (forward unknown TLV bit), 119
- FCS field
 - Frame Relay frames, 81
 - HDLC frames, 75
 - PPP frames, 78
- FEC (Forwarding Equivalence Class), 122
- fields
 - of LDP messages, 118
 - of UTI encapsulation, 334
- Flag field
 - Frame Relay frames, 80
 - HDLC frames, 72
 - PPP frames, 78
- flooding, VPLS, 574
- forwarding, VPLS, 574
- fragmentation
 - adjusted MTU, 462
 - avoiding in L2TPv3 networks, 456–461
 - PMTUD, 461–478

- post-fragmentation, 463
- prefragmentation, 464
- frame format
 - HDLC, 72–76
 - PPP, 77–78
- Frame Relay, 78
 - encapsulation, 79
 - frame format, 80–82
 - FRoMPLS, 195–197
 - case study configuration, 218–224
 - interaction with pseudowire protocols, 79
 - legacy Layer 2 VPNs, 30–31
 - LMI, 83
 - message format, 83–85
 - status enquiry messages, 85–86
 - status messages, 87
 - update status messages, 87
 - over L2TPv3, 403–404
 - configuring, 431–432
 - data plane, 436–438
 - verifying configuration, 433–435
 - traffic management, 90
 - traffic policing, 90–91
 - traffic shaping, 92–93
- Frame Relay-to-Frame Relay local switching, 549
- frames, Ethernet, 52–53
- FRoMPLS, case study configuration, 218–224
- full-mesh VPLS topological model, 577

G-H

- Gang of Four, 83
 - LMI implementation versus Annex A/D, 89–90
- Generic Label TLV encoding, 123
- GFC (Generic Flow Control) field (ATM cells), 97
- goals of RFC 1547, 76
- hardware support for AToM, verifying, 236–238
- HDLC
 - Cisco implementation, 72
 - frame format, 72–76
 - modes of operation, 71
 - over L2TPv3
 - configuring, 408–411
 - data plane details, 415–417
 - verifying configuration, 411–415
 - pseudowire transport, 402

HDLCoMPLS, 193
 case study configuration, 207–213
 HDLCPW configuration, 457
 HEC field (ATM cells), 98
 hidden VLANs, 147
 hierarchical VPLS, 578
 with MPLS access network, 578
 with QnQ access network, 579
 hop popping, 148
 hub-and-spoke VPLS topological model, 577

I

IEEE 802.3 SNAP frame format, 53
 IETF working groups, IETF standardization, 22–23
 draft-kompella, 24–26
 draft-martini, 24
 “Illegal C-bit” status code, 130
 ILMI (Interim Local Management Interface),
 98–101
 implementing PMTUD, 464–465
 Information field
 Frame Relay frames, 81
 HDLC frames, 75
 PPP frames, 78
 input service policies, configuring, 504–506
 inter-AS pseudowire emulation with IGP
 redistribution, 294–310
 intermediate markings, ATOM, 325
 internal VLAN tags, 582
 interworking command, 517
 IP accounting, 493
 IP topology for point-to-point L2TPv3 transport
 case studies, 358–360
 IPLS (IP-only LAN Service), 27
 ISO 3309 standard, HDLC frame format, 72–76
 IW (interworking), 511
 bridged, 512–514
 case study, 517–529
 case studies, 516–517
 connect command, 558–559
 encapsulation, 559
 for Ethernet-to-VLAN local switching
 Ethernet IW, 559–560

 for Frame Relay-to-VLAN IP IW using
 ATOM, 560–562
 for Frame Relay-to-PPP-IW using
 L2TPv3, 564–565
 for VLAN-to-bridged IW using L2TPv3,
 562–563
 MTU, 515–516
 routed, 512–515
 case study, 530
 Frame Relay-to-ATM, case study,
 547–548
 Frame Relay-to-PPP using L2TPv3,
 case study, 537–544
 Frame Relay-to-VLAN using ATOM, case
 study, 530–536
 MTU considerations, 544–547

J-L

jumbo frames, 68

L2-Specific Sublayer, 398–400
 l2tp-class command, syntax, 355–357
 L2TPv3, 41, 336
 AAL5_SDUoL2TPv3
 configuring, 439–440
 control plane, 443–444
 data plane, 445–447
 verifying configuration, 440–442
 ATM transport, 404–406
 CRoL2TPv3, 487–491
 OAM emulation, 478–4487
 ATM_CoL2TPv3
 configuring, 447
 verifying configuration, 449–450
 AVPs, 336
 configuring
 l2tp-class command, 355–357
 pseudowire-class command, 354–355
 xconnect command, 352–353
 connectivity model, 336
 control connection, 341
 control channel signaling, 343–347
 Control Message Authentication, 346
 control message to encapsulation,
 341–343

- control messages, 42
- control packets, 42
- control plane, 41
- data encapsulation, 336
 - Demultiplexing Sublayer field, 338–339
 - Encapsulation Sublayer field, 339–340
 - packet-switched network layer, 337–338
- evolution of, 333
- fragmentation, avoiding, 456–461
- Frame Relay transport, 403–404
 - configuring, 431–432
 - data plane, 436, 438
 - verifying configuration, 433–435
- HDLC pseudowire transport, 402
- HDLC transport
 - configuring, 408–411
 - data plane details, 415–417
 - verifying configuration, 411–415
- LCCEs, 41
- MTU considerations, 400–401
- operation, 42–43
- over WAN protocols, configuring, 407–408
- PMTUD, 455
 - avoiding fragmentation, 461–464
 - combining with DF bit, 470–478
 - implementing, 464–465
 - switching statistics, displaying, 468–470
 - triggering, 466–467
- point-to-point LAN transport, 351, 358–360
 - Ethernet port-to-port dynamic session, 376–383
 - Ethernet port-to-port manual session, 360–368
 - Ethernet port-to-port manual session with keepalive, 368–370, 373–376
 - verifying configuration, 370–372
 - Ethernet VLAN-to-VLAN dynamic session, 383–385, 387–391
- PPP transport, 402–403
 - configuring, 417–419
 - control plane negotiation, 423–427
 - data plane, 428–431
 - verifying configuration, 419–422
- QoS, 491
 - input service policies, 504–506
 - queuing, 503–504
 - traffic marking, 491–497
 - traffic policing, 497–502
- selection criteria, 44
 - advanced network services, 45
 - existing network installation base, 45
 - interoperability, 46
 - network operation complexity, 46
 - session negotiation, 346
 - supported Layer 2 protocols, 43–44
- label advertisement mode (MPLS), 124
- label bindings, 122
- label disposition, 147–148
- label distribution control mode (MPLS), 124
- label distribution protocol, 115
- label imposition, 147–148
- Label Mapping messages, 123
 - decoding, 234–236
- label retention mode (MPLS), 125
- label spaces, 116
- label stacking, 116
 - AToM, 35–37
- Label TLV encodings, 123
- Label Withdraw messages, 124
- Layer 2 local switching, 549
 - ATM-to-ATM, 551–553
 - Ethernet-to-Ethernet, 553–555
 - Frame Relay-to-Frame Relay, 549
- Layer 2 protocol tunneling, configuring for VPLS, 594–597
- Layer 2 protocols supported by L2TPv3, 43–44
- Layer 2 VPN forwarder, 35
- Layer 2-specific matching and setting, 326
 - ATM over MPLS QoS, 328
 - Ethernet over MPLS QoS, 326
 - Frame Relay over MPLS QoS, 327
- Layer 3 VPNs, 6
 - limitations of, 7–8
- LCCEs (L2TP Control Connection Endpoints), 41, 456
- LDP (Label Distribution Protocol), 115
 - advertisement messages, 123–124
 - authentication for pseudowire signaling, configuring, 311–312
 - discovery, 119–121
 - label advertisement mode, 124
 - label bindings, 122
 - label distribution control mode, 124
 - label mapping messages, decoding, 234, 236

- label retention mode, 125
- LSRs
 - discovery mechanisms, 119–120
 - session establishment, 121
- messages, 118
 - fields, 118–119
- packets, 116
- peers, 116
- security, 125
- LDP Identifier field (LDP packets), 117
- LDP-based VPLS, 575–576
- leaky bucket model, 91
 - ATM, 102
- legacy Layer 2 VPNs
 - ATM, 30–31
 - DLSw, 31
 - Frame Relay, 30–31
 - VPDNs, 31–32
- liberal label retention mode, 125
- like-to-like attachment circuits, 511
- limitations
 - of Layer 3 VPNs, 7–8
 - of STP, 60–61
- LMI (Local Management Interface), 83
 - message format, 83–85
 - status enquiry messages, 85–86
 - status messages, 87
 - update status messages, 87
- load sharing, 249–250
 - Equal-Cost Cost Multipath, 253–256
 - preferred path, configuring, 256–275
 - Unequal Cost Multipath, 252–253
- local emulation mode (OAM), 478
- local switching, 549
 - ATM attachment circuits, 557
 - ATM-to-ATM, 551–553
 - Ethernet-to-Ethernet, 553–555
 - Ethernet-to-VLAN, 556–557
 - Frame Relay-to-Frame Relay, 549
- loopback cells (OAM), 101
- LSPs, FEC, 122
- LSRs, 115
 - LDP discovery mechanisms, 119–120
 - session establishment, 121

M

- manual pseudowire configuration, 21
- messages, 123
 - LDP, 118
 - advertisement, 123–124
 - fields, 118
 - LMI, 83–85
 - status, 87
 - status enquiry, 85–86
 - update status, 87
- Metro Ethernet, 54–56
- MPLS
 - AToM, 33–34
 - ATM encapsulation, 132–133
 - control word negotiation, 129–130
 - Ethernet encapsulation, 136–137
 - Frame Relay encapsulation, 134–135
 - HDLCoMPLS, 135
 - label stacking, 35–37
 - PPP encapsulation, 135–136
 - pseudowire label binding, 126–127
 - pseudowires, 34–35
 - pseudowires, establishing, 128–129
 - selection criteria, 38–40
 - sequence numbers, 131–132
 - supported Layer 2 protocols, 37–38
 - HDLCoMPLS, 193
 - LDP, 115
 - advertisement messages, 123–124
 - discovery mechanisms, 119
 - label advertisement mode, 124
 - label bindings, 122
 - label distribution and management, 121
 - label distribution control mode, 124
 - label retention mode, 125
 - label space, 116
 - messages, 118–119
 - packets, 116–117
 - security, 125
 - session establishment, 121
 - traffic engineering
 - Fast Reroute, 275, 277–281
 - tunnels, preferred path configuration, 264–275
 - WAN protocol over pseudowire configuration
 - control plane, 187–188

- control word negotiation, 190–191
- data plane encapsulation, 189
- MTU requirements, 191–192
- pseudowire types, 188–189
- MQC (Modular QoS CLI) configuration, 491
- traffic marking, 495–497
- MSTP (Multiple Spanning Tree Protocol), 598–602
- MTU
 - adjusted MTU, 462
 - IP IW considerations, 544–545, 547
 - L2TPv3 transport overhead, 400–401
 - requirements
 - configuring WAN protocols over MPLS pseudowires, 191–192
 - for EoMPLS, 140–146
- multi-AS networks, pseudowire emulation, 287
- interconnecting pseudowires with dedicated circuits, 288, 290–293
- multihoming VPLS, 580, 598–602
- multipoint connectivity, VPLS, 569
 - configuring, 581–586
 - EVCS, 572
 - example configuration, 587–592
 - flooding, 574
 - forwarding, 574
 - full-mesh topological model, 577
 - hierarchical VPLS, 578–579
 - hub-and-spoke topological model, 577
 - Layer 2 protocol tunneling, 594–597
 - multihoming, 598, 600–602
 - network reference model, 570
 - partial-mesh topological model, 578
 - per-VLAN MAC address limiting, 592
 - QoS, 593–594
 - redundancy, 580
 - signaling, 575–576
 - TLS, 571
 - topological models, 577
 - virtual switches, 572–573

N-O

- native service processing (pseudowire emulation), 20
- NLPID field (Frame Relay frames), 82
- notification messages (LDP), 118
- NRM (Normal Response Mode), 71

- OAM, 98, 100–101
 - loopback cells, 101
 - operational modes, 478
- OAM emulation, 478–487
- OUI field (Frame Relay frames), 82
- out-of-order packets, sequencing, 131–132

P

- packet cell relay mode (ATM), 245–246
- packets
 - EoMPLS, 140
 - fields, 142
 - label disposition, 147–148
 - label imposition, 147–148
 - LDP, 116
 - out-of-order, sequencing, 131–132
- packet-switched network layer (L2TPv3), 337–338
- Padding field (Frame Relay frames), 81
- PARC (Palo Alto Research Center), 51
- partial-mesh VPLS topological model, 578
- payload layer (pseudowire emulation), 17
- PDU Length field (LDP packets), 117
- PE device system architecture
 - control plane, 19
 - data plane, 18
- PE routers
 - debugging EoMPLS operation, 179–181, 183
 - VLAN rewrite configuration, 160–161
 - VLAN-based EoMPLS transport configuration, 157
- PE switches, VLAN-based EoMPLS configuration, 162–163
- PEP (pseudowire encapsulation processor), 20
- per-interface label space, 116
- per-platform label space, 116
- PHP (Penultimate Hop Popping), 148
- physical layer (ATM), 94
- PID field (Frame Relay frames), 82
- PMTUD (path maximum transmission unit discovery), 455
 - combining with DF bit, 470–478
 - fragmentation, avoiding, 461–464
 - implementing, 464–465
 - switching statistics, displaying, 468–470
 - triggering, 466–467

- point-to-point LAN transport, 351, 358–360
 - Ethernet port-to-port dynamic session
 - configuring, 376–377
 - data plane details, 381–383
 - verifying configuration, 378–380
 - Ethernet port-to-port manual session, 360–363
 - data plane details, 366–368
 - verifying, 363, 365
 - Ethernet port-to-port manual session with
 - keepalive, 368–370
 - data plane details, 373–376
 - verifying configuration, 370–372
 - Ethernet VLAN-to-VLAN dynamic session,
 - configuring, 383–391
- policing
 - ATM traffic, 102
 - CBR.1, 104
 - UBR.1, 107
 - UBR.2, 107
 - VBR.1, 104
 - VBR.2, 105
 - VBR.3, 105
 - Frame Relay, 90–91
- port transparency, configuring for EoMPLS
 - port-based transport, 154
- port-based EoMPLS transport, port-based EoMPLS
 - transport configuration
 - case study, 154–157
 - switch configuration case study, 167–169
- port-tunneling mode (EoMPLS), 146–147
- post-fragmentation, 463
- PPP (Point-to-Point Protocol)
 - encapsulation, 76–77
 - frame format, 77–78
 - PPPoMPLS, 194–195
 - case study configuration, 214–218
- PPP over L2TPv3, 402–403
 - configuring, 417–419
 - control plane negotiation, 423–427
 - data plane, 428–431
 - verifying configuration, 419–422
- preferred path
 - configuring, 256–258
 - with IP routing, configuring, 258–259, 261–264
 - with MPLS Traffic Engineering tunnels,
 - configuring, 264–275
- pre-fragmentation, 464
- Protocol field (HDLC frames), 74
- Protocol field (PPP frames), 78
- protocol layers of pseudowire emulation, 17, 19
- pseudowire class template configuration, case
 - study, 173
- pseudowire emulation, 16. *See also* pseudowires
 - auto-discovery mechanism, 22
 - configuring, 21–22
 - in multi-AS networks, 287
 - interconnecting psuedowires with
 - dedicated circuits, 288–293
 - native service processing, 20
 - network reference model, 16
 - PE device system architecture
 - control plane, 19
 - data plane, 18
 - PEP, 20
 - protocol layers, 17–19
 - standardization
 - draft-kompella, 24–26
 - draft-martini, 24
 - IETF working groups, 22–23
 - transporting over PSN, 21
- Pseudowire ID FEC element encoding, 126–127
- pseudowire label binding, 126–127
- pseudowire-class command, syntax, 354–355
- pseudowires
 - and VCs, 188
 - AToM, 34–35, 128–129
 - connectivity verification model, 312
 - VCCV, 313–314
 - data plane connectivity, verifying,
 - 315–319
 - IW, 511
 - bridged, 513–529
 - case studies, 516–517
 - MTU, 515–516
 - routed, 514–515
 - routed, case study, 530–548
 - label mapping messages, decoding, 234–236
 - PSN layer, 17
 - VPLS, configuring, 575
 - WAN protocols over MPLS pseudowires,
 - configuring, 188–189
- PSN layer (packet-switched network), 337–338
- PTI field (ATM cells), 97

pure Layer 2 model, 61–62
PVCs, 5
PWE3 (Pseudowire Emulation Edge to Edge)
 group, 336

Q

QinQ, 62–65
 asymmetrical links, 65
 restrictions, 67–68
 tagging process, 66
QoS, 491
 ATM traffic management, 102
 configuring for VPLS, 593–594
 in AToM, 320
 intermediate markings, 325
 queuing, 323–324
 traffic marking, 320–322
 traffic policing, 322–323
 input service policies, 504–506
 queuing, 503–504
 traffic marking, configuring, 491–497
 traffic policing, 90–91
 configuring, 497–502
 traffic shaping, 92–93
queuing
 configuring, 503–504
 in AToM, 323–324

R

Rapid Spanning Tree Protocol, 61
redundancy, VPLS multihoming, 580
remote circuit id command, 171
required EoMPLS transport preconfiguration,
 150–153
restrictions of 802.1Q, 67–68
RFC 1547, 76
 goals of, 76
RFC 1661, PPP encapsulation, 77
routed IW, 512–515
 Frame Relay-to-ATM, case study, 547–548
 Frame Relay-to-PPP using L2TPv3, case study,
 537–544

 Frame Relay-to-VLAN using AToM, case
 study, 530–536
 MTU considerations, 515–516, 544–547
routers, EoMPLS
 configuration case studies
 port-based transport, 154–156
 VLAN-based transport, 157–161
 debugging on PE routers, 179–183
 troubleshooting, 174–179

S

security, LDP, 125
selection criteria for L2TPv3, 44
 advanced network services, 45
 existing network installation base, 45
 interoperability, 46
 network operation complexity, 46
sequence numbers, 131–132
service providers, 6
service-delimiting VLAN tags, 581
session establishment (LDP), 121
session messages (LDP), 118
session negotiation, L2TPv3, 346
shaping ATM traffic, 107–109
show arp command, 156
show connection command, 534
show ip traffic command, 459
show mpls forwarding-table command, 153, 178
show mpls l2transport vc command, 183, 592
show mpls l2transport vc commands, 174–176
show mpls ldp discovery command, 176
show mpls ldp neighbor command, 153
show processes cpu command, 458
show sss circuits command, 559
signaling, VPLS, 575–576
single cell relay mode (ATM), 243–244
SNAP (Subnetwork Access Protocol), 82
standardizing pseudowire emulation, IETF working
 groups, 22–23
 draft-kompella, 24–26
 draft-martini, 24
status enquiry messages (LMI), 85–86
status messages (LMI), 87

StopCCN (Stop-Control-Connection-Notification), 345

STP (Spanning Tree Protocol), 57

- limitations of, 60–61
- operation overview, 58–60
- Rapid Spanning Tree Protocol, 61

STP Root Guard, 62

SUP720-3BXL-based systems, configuring

- VLAN-based EoMPLS, 164

switches

- EoMPLS configuration case studies
 - port-based transport, 167
 - VLAN-based transport, 161–166
- troubleshooting EoMPLS, 183–185

T-U

tagging process, 802.1Q, 66

targeted LDP sessions, 128

TCP MD5, 34

TLS (Transparent LAN Service), 569, 571

topological models (VPLS)

- full mesh, 577
- hierarchical VPLS, 578
 - with MPLS access network, 578
 - with QinQ access network, 579
- hub and spoke, 577
- partial mesh, 578

ToS reflection, 494–495

traffic management

- ATM, 102
 - traffic policing, 102–107
 - traffic shaping, 107–109
- Frame Relay, 90
 - traffic policing, 90–91
 - traffic shaping, 92–93

traffic marking

- in AToM, 320–322
 - intermediate markings, 325
- MQC, 495–497
 - setting ToS value, 492–493
 - ToS reflection, 494–495

traffic policing, 90–91

- configuring, 497–502
- in AToM, 322–323

traffic shaping, 92–93

transparent mode (OAM), 478

transporting pseudowire traffic over PSN, 21

triggering PMTUD, 466–467

troubleshooting

- EoMPLS
 - on routers, 174–179
 - on switches, 183–185
- HDLCoMPLS configuration, 211–213
- port transparency for EoMPLS port-based transport, 155–156
- PPPoMPLS configuration, 215–218
- VLAN rewrite on Cisco 12000 series routers, 171
- VLAN-based EoMPLS on switches, 166
- VLAN-based EoMPLS transport, 159–160

trunk mode, VPLS configuration, 583–584

tunnel labels, 36

tunnel ports, 65

tunneling

- 802.1q, 62–65
 - asymmetrical links, 65
 - restrictions, 67–68
 - tagging process, 66
- L2TPv3 mechanisms, 42–43

U-bit (unknown message bit), 118

UBR (unspecified Bit Rate), 102

UBR.1 traffic policing, 107

UBR.2 traffic policing, 107

Unequal Cost Multipath, 252–253

UPC (usage parameter control), 102

update status messages (LMI), 87

UTI (Universal Transport Interface), 333–334

V

VBR (variable bit rate), 102

VBR.1 traffic policing, 104

VBR.2 traffic policing, 105

VBR.3 traffic policing, 105

VCCV (virtual circuit connectivity verification), 312

- advertising, 313–314
- data plane connectivity, verifying, 315–319

VCs (virtual circuits)

- and pseudowires, 188
- label mapping messages, decoding, 234–236
- PVCs, 5

verifying

- AAL5_SDUoL2TPv3 configuration, 440–442
- AAL5oMPLS case study configuration, 226–229
- ATM_CRoL2TPv3 configuration, 449–450
- AToM hardware support, 236–238
- cell packing configuration, 240–242
- CRoMPLS configuration, 231–233
- Ethernet port-to-port configuration, 363–365
- Ethernet port-to-port dynamic session configuration, 378–380
- Ethernet VLAN-to-VLAN dynamic session, 386–387
- FRoL2TPv3 configuration, 433–435
- FRoMPLS configuration, 220–224
- HDLCoL2TPv3 configuration, 411–415
- HDLCoMPLS configuration, 208–211
- PPPoL2TPv3 configuration, 419–422
- PPPoMPLS configuration, 215–218
- Version field (LDP packets), 117
- VFI, VPLS configuration, 585–586
- viewing encapsulation details, 559
- virtual switches, 572–573
- VLAN rewrite, configuring on Cisco 12000 series routers, case study, 160–161, 169–173
- VLAN-based EoMPLS transport
 - configuring, case study, 157–158
 - switch configuration, case study, 161, 163–166
 - troubleshooting, 159–160
- VLANs, STP, 57
 - limitations of, 60–61
 - operation overview, 58–60
- VLAN-tunneling mode (EoMPLS), 146–147
- VPDNs, legacy Layer 2 VPNs, 31–32
- VPI/VCI field (ATM cells), 97
- VPLS (Virtual Private LAN Service), 27, 569.
 - See also* hierarchical VPLS
 - access mode, configuring, 582
 - attachment circuits
 - associating to VFI, 586
 - configuring, 581–582
 - configuring, 581
 - domains, 570
 - dot1Q-tunnel mode, configuring, 584–585
 - EVCS, 572
 - example configuration, 587–592
 - flooding, 574

forwarding, 574

- Layer 2 protocol tunneling, 594–597
- multihoming, 598–602
- network reference model, 570
- per-VLAN MAC address limiting, 592
- pseudowires, displaying status, 592
- QoS, 593–594
- redundancy, multihoming, 580
- signaling, 575–576
- TLS, 571
- topological models, 577
 - full mesh, 577
 - hierarchical VPLS, 578–579
 - hub and spoke, 577
 - partial mesh, 578
- trunk mode, configuring, 583–584
- VFI, configuring, 585–586
- virtual switches, 572–573
- VPWS, 26–27
- VTP, 62

W-Z

WANs

- AAL5_SDUoL2TPv3
 - configuring, 439–440
 - control plan, 444
 - control plane, 443
 - data plan, 445, 447
 - verifying configuration, 440–442
- ATM, 93
 - AAL, 95
 - AAL5 CPCS-SDU mode, 242–243
 - cell format, 97
 - encapsulation, 94
 - ILMI, 98, 100–101
 - interaction with pseudowire protocols, 94
 - OAM, 98–101
 - packet cell relay mode, 245–246
 - single cell relay mode, 243–244
 - traffic management, 102
- traffic policing, 102–107
- traffic shaping, 107–109

- ATM_CoL2TPv3
 - configuring, 447
 - verifying configuration, 449–450
- ATMoMPLS, 198
 - AAL5 transport, 198–201
 - cell transport, 201–203
- Frame Relay, 78
 - encapsulation, 79
 - frame format, 80–82
 - interaction with pseudowire protocols, 79
 - LMI, 83–87
 - over L2TPv3, configuring, 431–435
 - traffic management, 90
 - traffic policing, 90–91
 - traffic shaping, 92–93
- FRoMPLS, 195–197
- HDLCoMPLS, 193
- over L2TPv3, 395
 - ATM transport, 404–406
 - configuring, 407–408
 - control plane, 395–396
 - data plane, 396–398
 - Frame Relay transport, 403–404
 - HDLC pseudowire transport, 402
 - L2-Specific Sublayer, 398–400
 - MTU considerations, 400–401
 - PPP transport, 402–403
- over MPLS case studies, 203–205
 - AAL5oMPLS, 224–229
 - CRoMPLS, 230–233
 - FRoMPLS, 218–224
 - HDLCoMPLS, 207–213
 - PPPoMPLS, 214–218
- PPP encapsulation, 76
 - frame format, 77–78
- PPPoMPLS, 194–195

xconnect command, syntax, 352–353